PodiumHQ — Hackathon Scoring Platform

DevSecOps Capstone Project | Final Year Technical Presentation

What is PodiumHQ?

- A full-stack web platform for organizing and judging hackathons.
- Allows judges to evaluate teams across multiple rounds and weighted criteria.
- Computes team rankings in real time and displays an automated live leaderboard.

Why I Built This (Problem & Goal)

- Solves the mess of manual spreadsheets and delayed scores during hackathon deadlines.
- Original application domain—built from scratch with zero TaskBoard code reuse.
- Goal: Take a real web app through the complete DevSecOps pipeline from commit to cloud.

Student & Project Info

- Student Name: D.N.Nanda kishore
- Roll Number: 10024 | BATCH: A
- Stack: React 18, FastAPI, PostgreSQL, Docker, GitHub Actions, Terraform, Kubernetes

Application Stack & Why I Chose These Tools

Simple, clean 3-tier architecture built with modern open-source tools

Frontend: React 18 + Vite

- What it does: Single-page application with Tailwind CSS in an Obsidian & Solar Gold theme.
- Why I chose it: Needed a fast, reactive UI where judges can submit scores without page refreshes.
- Runtime: Served through unprivileged Nginx on port 8080 (running as UID 101).

Backend: FastAPI (Python 3.12)

- What it does: Handles 15+ REST endpoints for teams, criteria, judges, and score calculations.
- Why I chose it: Automatic Swagger docs at /docs, async performance, and built-in health probes.
- Runtime: Hardened Python container running strictly as non-root appuser (UID 10001).

Database: PostgreSQL 16

- What it does: Stores events, rounds, criteria, teams, judges, and evaluations across 6 tables.
- Why I chose it: Strong relational integrity, foreign keys, and safe schema migrations with Alembic.
- Connection: Managed with SQLAlchemy 2.0 ORM and Psycopg 3 connection pooling.

System Architecture: From Code to Deployment

How code moves from local development to automated deployment and monitoring

1. Developer	2. GitHub Actions	3. Registry	4. GitOps	5. AWS EKS	6. Monitoring
Git Push / Main	Lint -> Tests -> Scan	GHCR (Git SHA Tag)	ArgoCD Auto-Sync	VPC + Pods + HPA	Prometheus & Grafana

Delivery Flow (CI/CD to Registry)

- Developer pushes code to GitHub repository.
- GitHub Actions automatically runs linters, 31 pytest tests, and builds container images.
- Trivy scans images for security vulnerabilities before anything is published.
- Images are tagged with the Git commit SHA (e.g. :f990516) and pushed to GHCR.

Runtime Flow (Cluster & Monitoring)

- ArgoCD detects new image tags in Git and synchronizes manifests with the EKS cluster.
- Ingress routes incoming traffic: / to frontend pods and /api to backend pods.
- Horizontal Pod Autoscaler (HPA) scales backend pods between 2 and 6 replicas based on CPU.
- Prometheus continuously scrapes /metrics to track response times and error rates.

CI/CD Pipeline with GitHub Actions

Automating code checks, test coverage, and security vulnerability scanning

Step 1: Code Quality & Linting

- What it does: Runs Ruff for Python code formatting and Mypy for static type validation.
- Why it matters: Catches syntax errors, bad imports, and type mismatches before tests run.
- Frontend: Runs npm run lint to catch unused variables and component bugs.

Step 2: Automated Tests & Coverage Gate

- What it does: Executes 31 unit and integration tests using Pytest.
- Coverage Gate: Pytest-cov enforces a strict 80% minimum coverage threshold.
- Current Result: 90.99% overall code coverage. If coverage falls below 80%, the build fails.

Step 3: Build & Security Scanning (Trivy)

- What it does: Builds multi-stage Docker images and scans them with Trivy.
- Security Gate: Fails the pipeline if any HIGH or CRITICAL CVEs are detected.
- Publishing: Successful builds are pushed to GHCR with immutable Git SHA tags, never :latest.

Infrastructure as Code: Terraform on AWS

Writing code to provision cloud networks and Kubernetes instead of manual setup

Network: AWS VPC (vpc.tf)

- Spans 3 Availability Zones in AWS ap-south-1 (Mumbai) for reliability.
- Creates 3 public subnets (for internet ingress) and 3 private subnets (for worker nodes).
- Includes a NAT Gateway so private worker nodes can safely pull container images.
- Tagged with kubernetes.io/role/elb so AWS can automatically manage load balancers.

Compute: EKS Cluster (eks.tf & addons.tf)

- Deploys a managed Kubernetes v1.30 control plane with managed node groups.
- Worker nodes: 2 to 4 t3.medium EC2 instances distributed across private subnets.
- Add-on 1: AWS EBS CSI driver—required so PostgreSQL can attach persistent disk volumes.
- Add-on 2: Metrics Server—required so the Horizontal Pod Autoscaler can read CPU usage.

Honest Cloud Status & Teardown Runbook

- Status: Terraform files are written, formatted, and validated with terraform validate.
- Cost Note: EKS and NAT Gateways cost ~$0.15/hour, so this was not left permanently running on AWS.
- Safety: Provided a complete terraform destroy runbook in terraform/README.md for clean teardown.

Kubernetes & Helm: Packaging Workloads

Managing application deployments, services, scaling, and database migrations

Workloads & High Availability

- Packaged as a Helm chart in helm/podiumhq with values-dev and values-prod.
- Backend & Frontend Deployments: 2 replicas each with RollingUpdate strategy.
- PodDisruptionBudget (PDB): Guarantees at least 1 backend pod stays online during node updates.
- Horizontal Pod Autoscaler (HPA): Automatically scales backend from 2 to 6 pods when CPU > 60%.

Container Security in Kubernetes

- Enforces securityContext on all pods: runAsNonRoot: true.
- Backend runs as UID 10001; Frontend runs as Nginx UID 101.
- Drops all Linux capabilities (capabilities: drop: [ALL]) to limit attack surface.
- Ingress routes / to frontend, and /api, /health, /ready, /metrics to backend.

Database Migration Job Hook

- The Problem: When 2+ backend pods boot at the same time, they race to run database migrations.
- The Solution: Created a Helm pre-upgrade/pre-install Job hook (migration-job.yaml).
- Alembic migrations run to completion first in an isolated job; application pods start only after it succeeds.

GitOps with ArgoCD: Declarative Delivery

Using Git as the single source of truth for cluster state and self-healing

What is GitOps & Why ArgoCD?

- Concept: Instead of engineers running manual kubectl apply, Git holds the desired state.
- ArgoCD controller runs inside the cluster and constantly compares live state against Git.
- Configured in argocd/application.yaml watching the helm/podiumhq chart in this repo.

Automated Sync & Pruning

- Automated Sync: When CI updates the image tag in Git, ArgoCD automatically applies the change.
- Automated Pruning (prune: true): Removes old deleted resources from the cluster automatically.
- Audit Trail: Every cluster change corresponds to a verifiable Git commit hash.

Self-Healing Drift Demonstration

- What is drift?: When someone manually alters resources in the cluster using kubectl.
- Self-Healing (selfHeal: true): ArgoCD detects the discrepancy and immediately reverts it.
- Demo check: If I run 'kubectl scale deployment backend --replicas=5', ArgoCD forces it back to 2.

Observability: Prometheus & Grafana

Monitoring system health, request traffic, and custom judging metrics

System Metrics on /metrics

- What it does: Backend exposes a Prometheus-format endpoint at /metrics.
- HTTP Telemetry: Tracks total requests, response status codes (2xx, 4xx, 5xx), and p95 latency.
- Runtime Telemetry: Tracks Python garbage collection, memory usage, CPU time, and open file descriptors.

Custom Domain Business Metrics

- podiumhq_scores_submitted_total: Counter tracking how many judge scores have been submitted.
- podiumhq_teams_by_status: Gauge showing active vs evaluated teams in the hackathon.
- podiumhq_leaderboard_requests_total: Counter tracking how often the leaderboard is viewed.

Grafana Dashboard & Alert Rules

- Grafana JSON (monitoring/grafana-dashboard.json): 5 panels showing RPS, p95 latency, 5xx errors, and scores.
- PrometheusRule (monitoring/alerts.yaml): Triggers an alert if 5xx errors exceed 1% for 2 minutes.
- Target Down Alert: Alerts immediately if the backend service stops responding.

Testing, Security & Real Debugging Challenges

Verified test coverage, non-root checks, and authentic bugs I ran into and fixed

Verified Test & Security Results

- Pytest Results: 31 tests passed in 1.32 seconds with 90.99% statement coverage.
- Test Isolation: Runs against an in-memory SQLite database so tests never pollute real data.
- Verified Non-Root: Ran 'docker compose exec backend id' -> uid=10001(appuser) and frontend -> uid=101(nginx).

Real Bug 1: In-Container Pytest Permission

- The Problem: Running pytest inside the backend container crashed with sqlite3.OperationalError.
- Root Cause: Working directory /app was created by Docker as root; appuser couldn't write the .coverage file.
- The Fix: Added explicit 'RUN chown -R appuser:appgroup /app' in the Dockerfile.

Real Bug 2: Nginx IPv6 Healthcheck Failure

- The Problem: Docker Compose reported the frontend container as 'unhealthy' even though web pages loaded.
- Root Cause: BusyBox wget resolved localhost to IPv6 ::1, but Nginx was only listening on IPv4 8080.
- The Fix: Added 'listen [::]:8080 default_server;' to the Nginx template and updated probe to 127.0.0.1.

Summary, Limitations & Key Learnings

Honest self-assessment of achievements, cloud limitations, and future improvements

What Works & Was Verified

- Fully functional hackathon scoring platform running locally on Docker Compose.
- 31 automated tests passing with 90.99% coverage and isolated test fixtures.
- Non-root container execution verified live on both backend and frontend.
- Complete, validated manifest suite: Terraform, Helm chart, ArgoCD, and Prometheus.

Honest Limitations (Cloud Scope)

- AWS EKS & ArgoCD were not deployed to live cloud infrastructure to avoid ongoing student cloud costs.
- All cloud manifests are written, syntactically validated, and ready for deployment.
- Everything runnable locally was verified 100% green with saved evidence files.

Top Engineering Lessons

- DevSecOps is in the details: file permissions, non-root users, and dual-stack networking.
- Helm pre-upgrade hooks are crucial to prevent database migration locks across replicas.
- Immutable image tags (Git commit SHAs) prevent deployment caching confusion.