

# GE23131-Programming Using C-2024

Quiz navigation



[Show one page at a time](#)

[Finish review](#)

<b>Status</b>	Finished
<b>Started</b>	Monday, 23 December 2024, 5:33 PM
<b>Completed</b>	Monday, 28 October 2024, 2:18 PM
<b>Duration</b>	56 days 3 hours

Question **1**

Correct

Marked out of  
3.00

[Flag question](#)

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false  
Sample Input 2 27 77 Sample Output 2 true

**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int num1,num2;
4     scanf("%d %d",&num1,&num2);
5     if(num1%10==num2%10){
6         printf("true\n");
7     }
8     else{
9         printf("false\n");
10    }
11    return 0;
12 }
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of  
5.00

🚩 [Flag question](#)

**Objective**

In this challenge, we're getting started with conditional statements.

**Task**

Given an integer, ***n***, perform the following conditional actions:

- If ***n*** is odd, print **Weird**
- If ***n*** is even and in the inclusive range of **2** to **5**, print **Not Weird**
- If ***n*** is even and in the inclusive range of **6** to **20**, print **Weird**
- If ***n*** is even and greater than **20**, print **Not Weird**

Complete the stub code provided in your editor to print whether or not ***n*** is weird.

A single line containing a positive integer, ***n***.

**Constraints**

·       $1 \leq n \leq 100$

**Output Format**

Print Weird if the number is weird; otherwise, print Not Weird.

**Sample Input 0**

3

**Sample Output 0**

Weird

**Sample Input 1**

24

**Sample Output 1**

## Explanation

*Sample Case 0:  $n = 3$*

$n$  is odd and odd numbers are weird, so we print **Weird**.

*Sample Case 1:  $n = 24$*

$n > 20$  and  $n$  is even, so it isn't weird. Thus, we print **Not Weird**.

**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int a;
4     scanf("%d",&a);
5     if(a%2!=0){
6         printf("Weird");
7     }
8     else{
9         if((a>=2)|| (a<=5)|| (a>20)){
10
11             printf("Not Weird");
12         }
13     }
14     else{
15         printf("Weird");
16     }
17 }
```

✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Question **3**

Correct

Marked out of  
7.00

🚩 [Flag question](#)

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since  $3^2 + 4^2 = 25 = 5^2$ . You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

**Answer:** (penalty regime: 0 %)

```

1  #include<stdio.h>
2  int main()
3  {
4  int a,b,c;
5      scanf("%d %d %d",&a,&b,&c);
6  if(a*a+b*b==c*c || a*a+c*c==b*b || b*b+c*c==a*a){
7      printf("yes");
8  }
9  else{
10     printf("no");
11 }
12 }
```

	Input	Expected	Got	
✓	3	yes	yes	✓
	5			
	4			
✓	5	no	no	✓
	8			
	2			

Passed all tests! ✓

Finish review