Experiment 15.Data Preprocessing

In [2]:
```
import numpy as np
import pandas as pd
df=pd.read_csv("/content/pre-process_datasample.csv")
print(df)
print(df.info())
print(df.Country.mode())
print(df.Country.mode()[0])
type(df.Country.mode())
df.Country.fillna(df.Country.mode()[0],inplace=True)
df.Age.fillna(df.Age.median(),inplace=True)
df.Salary.fillna(round(df.Salary.mean()),inplace=True)
print(df)
pd.get_dummies(df.Country)
updated_dataset=pd.concat([pd.get_dummies(df.Country),df.iloc[:,[1,2,3]]],axis=1)
print(updated_dataset)
print(df.info())
updated_dataset.Purchased.replace(['No','Yes'],[0,1],inplace=True)
print(updated_dataset)
```

```
   Country   Age   Salary Purchased
0   France  44.0  72000.0        No
1    Spain  27.0  48000.0       Yes
2  Germany  30.0  54000.0        No
3    Spain  38.0  61000.0        No
4  Germany  40.0      NaN       Yes
5   France  35.0  58000.0       Yes
6    Spain   NaN  52000.0        No
7   France  48.0  79000.0       Yes
8      NaN  50.0  83000.0        No
9   France  37.0  67000.0       Yes
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 10 entries, 0 to 9
Data columns (total 4 columns):
 #   Column     Non-Null Count  Dtype
---  ------     --------------  -----
 0   Country    9 non-null      object
 1   Age        9 non-null      float64
 2   Salary     9 non-null      float64
 3   Purchased  10 non-null     object
dtypes: float64(2), object(2)
memory usage: 452.0+ bytes
None
0    France
Name: Country, dtype: object
France
   Country   Age   Salary Purchased
0   France  44.0  72000.0        No
1    Spain  27.0  48000.0       Yes
2  Germany  30.0  54000.0        No
3    Spain  38.0  61000.0        No
4  Germany  40.0  63778.0       Yes
5   France  35.0  58000.0       Yes
6    Spain  38.0  52000.0        No
7   France  48.0  79000.0       Yes
8   France  50.0  83000.0        No
9   France  37.0  67000.0       Yes
   France  Germany  Spain   Age   Salary Purchased
0    True    False  False  44.0  72000.0        No
1   False    False   True  27.0  48000.0       Yes
2   False     True  False  30.0  54000.0        No
3   False    False   True  38.0  61000.0        No
4   False     True  False  40.0  63778.0       Yes
5    True    False  False  35.0  58000.0       Yes
6   False    False   True  38.0  52000.0        No
7    True    False  False  48.0  79000.0       Yes
8    True    False  False  50.0  83000.0        No
9    True    False  False  37.0  67000.0       Yes
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 10 entries, 0 to 9
Data columns (total 4 columns):
 #   Column     Non-Null Count  Dtype
---  ------     --------------  -----
 0   Country    10 non-null     object
 1   Age        10 non-null     float64
 2   Salary     10 non-null     float64
```

```
 3   Purchased  10 non-null     object
dtypes: float64(2), object(2)
memory usage: 452.0+ bytes
None
   France  Germany  Spain   Age   Salary  Purchased
0    True    False  False  44.0  72000.0          0
1   False    False   True  27.0  48000.0          1
2   False     True  False  30.0  54000.0          0
3   False    False   True  38.0  61000.0          0
4   False     True  False  40.0  63778.0          1
5    True    False  False  35.0  58000.0          1
6   False    False   True  38.0  52000.0          0
7    True    False  False  48.0  79000.0          1
8    True    False  False  50.0  83000.0          0
9    True    False  False  37.0  67000.0          1
```

```
/tmp/ipykernel_2617/3073636745.py:9: FutureWarning: A value is trying to be set on a copy of
a DataFrame or Series through chained assignment using an inplace method.
The behavior will change in pandas 3.0. This inplace method will never work because the inte
rmediate object on which we are setting values always behaves as a copy.

For example, when doing 'df[col].method(value, inplace=True)', try using 'df.method({col: va
lue}, inplace=True)' or df[col] = df[col].method(value) instead, to perform the operation in
place on the original object.


  df.Country.fillna(df.Country.mode()[0],inplace=True)
/tmp/ipykernel_2617/3073636745.py:10: FutureWarning: A value is trying to be set on a copy o
f a DataFrame or Series through chained assignment using an inplace method.
The behavior will change in pandas 3.0. This inplace method will never work because the inte
rmediate object on which we are setting values always behaves as a copy.

For example, when doing 'df[col].method(value, inplace=True)', try using 'df.method({col: va
lue}, inplace=True)' or df[col] = df[col].method(value) instead, to perform the operation in
place on the original object.


  df.Age.fillna(df.Age.median(),inplace=True)
/tmp/ipykernel_2617/3073636745.py:11: FutureWarning: A value is trying to be set on a copy o
f a DataFrame or Series through chained assignment using an inplace method.
The behavior will change in pandas 3.0. This inplace method will never work because the inte
rmediate object on which we are setting values always behaves as a copy.

For example, when doing 'df[col].method(value, inplace=True)', try using 'df.method({col: va
lue}, inplace=True)' or df[col] = df[col].method(value) instead, to perform the operation in
place on the original object.


  df.Salary.fillna(round(df.Salary.mean()),inplace=True)
/tmp/ipykernel_2617/3073636745.py:17: FutureWarning: A value is trying to be set on a copy o
f a DataFrame or Series through chained assignment using an inplace method.
The behavior will change in pandas 3.0. This inplace method will never work because the inte
rmediate object on which we are setting values always behaves as a copy.

For example, when doing 'df[col].method(value, inplace=True)', try using 'df.method({col: va
lue}, inplace=True)' or df[col] = df[col].method(value) instead, to perform the operation in
place on the original object.


  updated_dataset.Purchased.replace(['No','Yes'],[0,1],inplace=True)
/tmp/ipykernel_2617/3073636745.py:17: FutureWarning: Downcasting behavior in `replace` is de
precated and will be removed in a future version. To retain the old behavior, explicitly cal
l `result.infer_objects(copy=False)`. To opt-in to the future behavior, set `pd.set_option
('future.no_silent_downcasting', True)`
  updated_dataset.Purchased.replace(['No','Yes'],[0,1],inplace=True)
```