

# AWS EC2 Volume Setup, Mount, Verify & Auto-Mount Guide

## 1. Identify Disk

Run: `lsblk`

Identify your new disk (e.g., `/dev/xvde`) which is not mounted

## 2. Format Disk

Run: `sudo mkfs -t ext4 /dev/xvde`

This prepares the disk with ext4 filesystem

## 3. Create Mount Directory

Run: `sudo mkdir /data`

This folder will hold your mounted volume

## 4. Mount the Disk

Run: `sudo mount /dev/xvde /data`

This attaches the disk to the directory

## 5. Verify Mount

Run: `df -h`

Check if `/dev/xvde` is mounted on `/data`

## 6. Get UUID for Auto-Mount

Run: `sudo blkid`

Copy UUID of `/dev/xvde`

## 7. Configure Auto-Mount

Run: `sudo nano /etc/fstab`

Add line:

`UUID= /data ext4 defaults,nofail 0 2`

## 8. Test Configuration

Run: `sudo mount -a`

Ensure no errors before reboot

## 9. Reboot and Verify

Run: `sudo reboot`

After reboot run: `df -h`

Confirm /data is mounted automatically

## Important Notes

Always use UUID instead of device name

Use 'nofail' to prevent boot issues

Always test using `mount -a` before reboot

Device names like `xvde` may change after reboot