

MODULE 3 – READ ACL

Script-controlled record access based on Branch

ServiceNow Lab – Script-Controlled ACL

Objective

- Configure a record-level READ ACL for u_institution_details. The ACL requires bb1 and uses the Branch condition EEE. Administrators retain full access.

Create the READ ACL

- Navigate to System Security → Access Control (ACL).
- Elevate the Security_admin role if required.
- Click New.
- Type: record
- Operation: read
- Name: u_institution_details
- Active: true
- Advanced: true
- Add bb1 under Requires role.
- Add the data condition: Branch is EEE.

Script

```
(function () {  
  // Allow admin users full access  
  if (gs.hasRole('admin')) {  
    return true;  
  }  
  
  // Allow users with bb1 role  
  if (gs.hasRole('bb1')) {  
    return true;  
  }  
  
  // Deny access for all others  
  return false;  
})();
```

Verification

- The script checks for admin or bb1. The separate data condition Branch is EEE is important for the intended record filtering.
- Impersonate the EEE User and open the u_institution_details list.
- Impersonate a user without bb1 and verify protected records are not accessible.
- Impersonate Admin and verify all records are accessible.

Expected Result

- EEE user with bb1 can access records allowed by the ACL condition.
- Users without the required role cannot read the protected records.
- Admin can read all records.