

MODULE 4 – CREATE and WRITE ACL

Role-based create and edit permissions

ServiceNow Lab – Script-Controlled ACL

Objective

- Add CREATE and WRITE permissions on u_institution_details using bb2 and bb3 respectively.

CREATE ACL

- Navigate to System Security → Access Control (ACL).
- Click New.
- Type: record
- Operation: create
- Name: u_institution_details
- Active: true
- Add bb2 under Requires role.
- No data condition is required for this CREATE ACL.
- Click Submit/Save.

CREATE Verification

- Use the EEE User with bb1 and bb2.
- Open u_institution_details.
- Verify that the New button is available.
- Create a test record and verify the operation is allowed.

WRITE ACL

- Click New to create another ACL.
- Type: record
- Operation: write
- Name: u_institution_details
- Active: true
- Add bb3 under Requires role.
- No data condition is required for this WRITE ACL.
- Click Submit/Save.

WRITE Verification

- Use the EEE User with bb1, bb2 and bb3.
- Open an accessible EEE record.
- Verify that fields can be edited and the record can be saved.
- Verify that the New button remains available because CREATE permission is provided by bb2.

Expected Result

- bb2 provides CREATE permission.

- bb3 provides WRITE permission.
- The READ ACL still controls which records the user can see.