RAJALAKSHMI ENGINEERING COLLEGE

A Mohammed Adil 250701432-2025-CSE A2

Started on	Friday, 28 August 2026, 3:36 PM
State	Finished
Completed on	Friday, 28 August 2026, 3:37 PM
Time taken	54 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int N;
    scanf("%d", &N);

    int A[N], B[N];

    // Read first array
    for (int i = 0; i < N; i++) {
        scanf("%d", &A[i]);
    }

    // Read second array
    for (int i = 0; i < N; i++) {
        scanf("%d", &B[i]);
    }

    // Sort A in ascending order
    for (int i = 0; i < N - 1; i++) {
        for (int j = i + 1; j < N; j++) {
            if (A[i] > A[j]) {
                int temp = A[i];
                A[i] = A[j];
                A[j] = temp;
            }
        }
    }

    // Sort B in descending order
    for (int i = 0; i < N - 1; i++) {
        for (int j = i + 1; j < N; j++) {
            if (B[i] < B[j]) {
                int temp = B[i];
                B[i] = B[j];
                B[j] = temp;
            }
        }
    }

    // Calculate minimum sum
    long long sum = 0;

    for (int i = 0; i < N; i++) {
        sum += (long long)A[i] * B[i];
    }

    printf("%lld", sum);

    return 0;
}

```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course