

LAB PROGRAM 3A

WAP to simulate the working of a queue of integers using an array. Provide the following operations: Insert, Delete, Display The program should print appropriate messages for queue empty and queue overflow conditions

```
#include <stdio.h>

#define MAX 5

int queue[MAX];

int front = -1, rear = -1;

void insert(int value) {
    if (rear == MAX - 1) {
        printf("Queue Overflow! Cannot insert %d\n", value);
    } else {
        if (front == -1) {
            front = 0;
        }
        rear++;
        queue[rear] = value;
        printf("%d inserted into the queue.\n", value);
    }
}

void delete() {
    if (front == -1 || front > rear) {
        printf("Queue Underflow! Queue is empty.\n");
    } else {
        printf("Deleted element: %d\n", queue[front]);
        front++;
    }
}
```

```
}
```

```
void display() {  
    if (front == -1 || front > rear) {  
        printf("Queue is empty.\n");  
    } else {  
        printf("Queue elements: ");  
        for (int i = front; i <= rear; i++) {  
            printf("%d ", queue[i]);  
        }  
        printf("\n");  
    }  
}
```

```
int main() {  
    int choice, value;  
    while (1) {  
        printf("\nQueue Operations:\n");  
        printf("1. Insert\n");  
        printf("2. Delete\n");  
        printf("3. Display\n");  
        printf("4. Exit\n");  
        printf("Enter your choice: ");  
        scanf("%d", &choice);  
        switch (choice) {  
            case 1:  
                printf("Enter value to insert: ");  
                scanf("%d", &value);  
                insert(value);  
                break;  
            case 2:  
                delete();  
                break;  
            case 3:  
                display();  
                break;  
            case 4:  
                exit(0);  
                break;  
            default:  
                printf("Invalid choice\n");  
                break;  
        }  
    }  
}
```

```

        break;


    case 3:
        display();
        break;

    case 4:
        printf("Exiting program.\n");
        return 0;

    default:
        printf("Invalid choice! Please try again.\n");
    }
}
}
}

```

OUTPUT:



```

Queue Operations:
1. Insert
2. Delete
3. Display
4. Exit
Enter your choice:1

Enter value to insert:23

23 inserted into the queue.

Queue Operations:
1. Insert
2. Delete
3. Display
4. Exit
Enter your choice:1

Enter value to insert:34

34 inserted into the queue.

```

untitled4 > main.c .clang-tidy 71:1 LF UTF-8 4 spaces* C | untitled4 | Debug Non-commercial

```

queue operations:
1. Insert
2. Delete
3. Display
4. Exit
Enter your choice:1

Enter value to insert:32

32 inserted into the queue.

Queue Operations:
1. Insert
2. Delete
3. Display
4. Exit
Enter your choice:2

Deleted element: 23

```

```
Deleted element: 23

Queue Operations:
1. Insert
2. Delete
3. Display
4. Exit
Enter your choice:3

Queue elements: 34 32

Queue Operations:
1. Insert
2. Delete
3. Display
4. Exit
Enter your choice:4

Exiting program.

Process finished with exit code 0
```

titled4 > main.c .clang-tidy 71:1 LF UTF-8 4 spaces* C | untitled4 | Debug Non-commercial us