

SERVLET PROGRAMS

1. Login Web Page –

Login.html Code:

```
<!DOCTYPE html>
<html>
<head>
  <title>Login</title>
  <style>
    body{
      display:flex;
      justify-content: center;
      align-items: center;
      margin: 0;
      height: 100vh;
      background-color: #f0f2f5;
    }
    .login-box{
      width:360px;
      padding:20px;
      border-radius: 10px;
      background-color: #fff;
      box-shadow: 0 4px 8px rgba(0,0,0,0.1);
    }
    .login-box h1{text-align:center;margin-bottom:20px;}
    .login-box input[type="email"], .login-box input[type="password"], .login-box
input[type="text"]{
      width:95%;
      height: 38px;
      border: 1px solid #ccc;
      border-radius: 5px;
      padding-left: 10px;
      font-size: 16px;
      margin-bottom: 15px;
    }
    .login-box label{
      font-size: 22px;
      font-weight: bold;
    }
    .login-box input[type="checkbox"]{
      margin-bottom: 15px;
```

```

        transform: scale(1.2);
    }
    .login-box button{
        width:100%;height:38px;border-radius:5px;
        border:none;color:white;background:blue;font-size:18px;
    }
    .login-box button:hover{background:darkblue;}
    .error-msg{color:red;text-align:center;margin-bottom:10px;}
</style>
</head>
<body>

<div class="login-box">
    <h1>Login</h1>

    <div id="error" class="error-msg"></div>

    <form action="login" method="post">
        <label for="email">Email :</label>
        <input type="email" id="email" name="email" placeholder="Email" required>

        <label for="password">Password :</label>
        <input type="password" id="password" name="password" id="password"
placeholder="Password" required>

        <input type="checkbox" onclick="togglePassword()"> Show Password
        <br><br>

        <button type="submit">Login</button>
    </form>
</div>

<script>
    function togglePassword(){
        let pass = document.getElementById("password");
        pass.type = pass.type === "password" ? "text" : "password";
    }

    // Show error from URL
    const params = new URLSearchParams(window.location.search);
    if(params.get("error")){
        document.getElementById("error").innerText = params.get("error");
    }
</script>

```

```
</body>
</html>
```

2. JSP GetPost Method –

Index.jsp:

```
<!DOCTYPE html>
<html>
<head>
  <title>JSP GET & POST Demo</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      background: linear-gradient(135deg, #4e73df, #1cc88a);
      margin: 0;
      padding: 0;
    }

    .container {
      max-width: 700px;
      margin: 50px auto;
      background: white;
      padding: 25px;
      border-radius: 12px;
      box-shadow: 0 10px 25px rgba(0,0,0,0.2);
    }

    h2 {
      color: #4e73df;
      margin-bottom: 10px;
    }

    label {
      font-weight: bold;
    }

    input {
      width: 100%;
      padding: 10px;
      margin: 8px 0 15px 0;
      border-radius: 6px;
```

```

        border: 1px solid #ccc;
        font-size: 14px;
    }

    button {
        background: #4e73df;
        color: white;
        border: none;
        padding: 10px 15px;
        border-radius: 8px;
        cursor: pointer;
        font-weight: bold;
        transition: 0.3s;
    }

    button:hover {
        background: #2e59d9;
    }

    .divider {
        margin: 30px 0;
        border-top: 1px solid #ddd;
    }

    .output {
        background: #f8f9fc;
        padding: 15px;
        border-radius: 8px;
        margin-top: 15px;
    }

    .success {
        color: #1cc88a;
        font-weight: bold;
    }
</style>
</head>
<body>

<div class="container">

    <h2>GET Method Form</h2>
    <form method="get" action="index.jsp">
        <label>Name</label>

```

```

<input type="text" name="gname" required>

<label>Age</label>
<input type="number" name="gage" required>

<button type="submit">Submit using GET</button>
</form>

<div class="divider"></div>

<h2>POST Method Form</h2>
<form method="post" action="index.jsp">
  <label>Name</label>
  <input type="text" name="pname" required>

  <label>Age</label>
  <input type="number" name="pageValue" required>

  <button type="submit">Submit using POST</button>
</form>

<div class="divider"></div>

<h2>Submitted Data</h2>

<%
  String gname = request.getParameter("gname");
  String gage = request.getParameter("gage");
  String pname = request.getParameter("pname");
  String pageValue = request.getParameter("pageValue");
%>

<% if (gname != null && gage != null) { %>
  <div class="output">
    <p class="success">GET Method Output</p>
    Name: <%= gname %><br>
    Age: <%= gage %>
  </div>
<% } %>

<% if (pname != null && pageValue != null) { %>
  <div class="output">
    <p class="success">POST Method Output</p>
    Name: <%= pname %><br>

```

```

        Age: <%= pageValue %>
    </div>
<% } %>

</div>

</body>
</html>

```

3. Bank WebApp –

Bank.html code:

```

<!DOCTYPE html>
<html>
<head>
<meta charset="UTF-8">
<title>Secure Bank System</title>
<style>
body{
font-family: Arial, sans-serif;
background: linear-gradient(to right, #1e3c72, #2a5298);
margin:0;
padding:0;
color:white;
text-align:center;
}
h1{
margin-top:30px;
letter-spacing:1px;
}
.container{
width:400px;
margin:50px auto;
background:white;
color:black;
padding:30px;
border-radius:10px;
box-shadow:0 0 20px rgba(0,0,0,0.4);
}
h2{
margin-bottom:20px;
color:#1e3c72;

```

```

}
input{
width:90%;
padding:10px;
margin:8px 0;
border-radius:5px;
border:1px solid #ccc;
}
button{
width:100%;
padding:10px;
background:#1e3c72;
color:white;
border:none;
border-radius:5px;
cursor:pointer;
font-weight:bold;
}
button:hover{
background:#16325c;
}
hr{
margin:25px 0;
}
</style>
</head>
<body>
<h1>Secure Bank Management System</h1>
<div class="container">
<h2>Login</h2>
<form action="login" method="post">
<input type="email" name="email" placeholder="Email" required>
<input type="password" name="password" placeholder="Password" required>
<button type="submit">Login</button>
</form>
<hr>
<h2>Register</h2>
<form action="register" method="post">
<input type="text" name="name" placeholder="Full Name" required>
<input type="email" name="email" placeholder="Email" required>
<input type="password" name="password" placeholder="Password" required>
<button type="submit">Register</button>
</form>
</div>

```

```
</body>
</html>
```

Dashboard.jsp:

```
<%@ page session="true" %>

<%
    if(session.getAttribute("user_id") == null){
        response.sendRedirect("bank.html");
        return;
    }
%>
<!DOCTYPE html>
<html>
<head>
<meta charset="UTF-8">
<title>Bank Dashboard</title>
<style>
body{
font-family: Arial, sans-serif;
margin:0;
background:#f4f6f9;
}
.header{
background:#1e3c72;
color:white;
padding:15px;
text-align:center;
}
.container{
width:500px;
margin:40px auto;
background:white;
padding:30px;
border-radius:10px;
box-shadow:0 0 15px rgba(0,0,0,0.3);
text-align:center;
}
button{
width:100%;
padding:12px;
margin:10px 0;
background:#2a5298;
color:white;
border:none;
```



```
border-radius:5px;
font-size:16px;
cursor:pointer;
font-weight:bold;
}
button:hover{
background:#1e3c72;
}
.logout{
background:#c0392b;
}
.logout:hover{
background:#922b21;
}
.user-info{
margin-bottom:20px;
font-weight:bold;
color:#1e3c72;
}
.balance-card{
background:#eaf1ff;
padding:15px;
border-radius:8px;
margin-bottom:20px;
box-shadow:0 0 5px rgba(0,0,0,0.1);
}
.balance-amount{
font-size:22px;
color:#2a5298;
font-weight:bold;
}
.timer{
font-size:13px;
color:#888;
margin-top:5px;
}
</style>
```

```
<script>
window.history.forward();
function noBack() {
window.history.forward();
}
```

```

var timeLeft = 300;

function startTimer(){
    var timer = setInterval(function(){
        timeLeft--;
        document.getElementById("timer").innerHTML =
            "Session expires in: " + timeLeft + " sec";

        if(timeLeft <= 0){
            clearInterval(timer);
            window.location.href="logout";
        }
    },1000);
}

function loadBalance(){
    fetch("balance")
    .then(response => response.text())
    .then(data => {
        document.getElementById("balanceValue").innerHTML = data;
    });
}
</script>
</head>
<body onload="noBack(); startTimer(); loadBalance();">
<div class="header">
<h2>User Dashboard</h2>
</div>
<div class="container">
<div class="user-info">
Welcome, <%= session.getAttribute("name") != null ? session.getAttribute("name") :
"User" %>
<br>
<span class="timer" id="timer"></span>
</div>
<div class="balance-card">
Current Balance
<div class="balance-amount" id="balanceValue">
Loading...
</div>
</div>
<form action="balance" method="get">
<button type="submit">Check Balance</button>
</form>
<form action="deposit.jsp" method="get">

```

```

<button type="submit">Deposit Money</button>
</form>
<form action="withdraw.jsp" method="get">
<button type="submit">Withdraw Money</button>
</form>
<form action="transactions" method="get">
<button type="submit">View Transactions</button>
</form>
<form action="downloadStatement" method="get">
<button type="submit">Download PDF Statement</button>
</form>
<form action="logout" method="get">
<button type="submit" class="logout">Logout</button>
</form>
</div>
</body>
</html>

```

Deposit.jsp:

```

<%@ page session="true" %>
<%
if(session.getAttribute("user_id") == null){
response.sendRedirect("bank.html");
return;
}
%>
<!DOCTYPE html>
<html>
<head>
<title>Deposit Money</title>
<style>
body{
font-family: Arial, sans-serif;
background:#f4f6f9;
}
.container{
width:400px;
margin:100px auto;
background:white;
padding:30px;
border-radius:10px;
box-shadow:0 0 10px rgba(0,0,0,0.2);
text-align:center;
}

```

```
input{
width:100%;
padding:10px;
margin:10px 0;
}
button{
width:100%;
padding:12px;
background:#2a5298;
color:white;
border:none;
border-radius:5px;
cursor:pointer;
}
button:hover{
background:#1e3c72;
}
.error{
color:red;
font-size:14px;
}
.success{
color:green;
}
</style>
<script>
function validateAndSubmit() {
let amount = document.getElementById("amount").value;
if (amount === "" || isNaN(amount)) {
    showMessage("Invalid Amount", true);
    return false;
}

amount = parseFloat(amount);

if (amount <= 0) {
    showMessage("Amount must be greater than 0", true);
    return false;
}

fetch("deposit", {
    method: "POST",
    headers: {
        "Content-Type": "application/x-www-form-urlencoded"
```

```

    },
    body: "amount=" + amount
  })
  .then(response => response.text())
  .then(data => {

    if(data.startsWith("SUCCESS")){
      showMessage(data, false);
      setTimeout(() => {
        window.location.href = "dashboard.jsp";
      }, 2000);
    } else {
      showMessage(data.replace("ERROR:", ""), true);
    }
  });

return false;
}

function showMessage(msg, isError){
  let box = document.getElementById("msg");
  box.innerHTML = msg;
  box.className = isError ? "error" : "success";
}
</script>
</head>
<body>
<div class="container">
<h2>Deposit Money</h2>
<form onsubmit="return validateAndSubmit();">
<input type="number" id="amount" step="0.01" min="1" placeholder="Enter
Amount" required>
<button type="submit">Deposit</button>
</form>
<div id="msg"></div>
<br>
<a href="dashboard.jsp">Back to Dashboard</a>
</div>
</body>
</html>

```

Withdraw.jsp:

```

<%@ page session="true" %>
<%
if(session.getAttribute("user_id") == null){

```

```
response.sendRedirect("bank.html");
return;
}
%>
<!DOCTYPE html>
<html>
<head>
<title>Withdraw Money</title>
<style>
body{
font-family: Arial, sans-serif;
background:#f4f6f9;
}
.container{
width:400px;
margin:100px auto;
background:white;
padding:30px;
border-radius:10px;
box-shadow:0 0 10px rgba(0,0,0,0.2);
text-align:center;
}
input{
width:100%;
padding:10px;
margin:10px 0;
}
button{
width:100%;
padding:12px;
background:#2a5298;
color:white;
border:none;
border-radius:5px;
cursor:pointer;
}
button:hover{
background:#1e3c72;
}
.error{
color:red;
font-size:14px;
}
.success{
```

```

color:green;
}
</style>
<script>
function validateAndSubmit() {
let amount = document.getElementById("amount").value;
if (amount === "" || isNaN(amount)) {
    showMessage("Invalid Amount", true);
    return false;
}

amount = parseFloat(amount);

if (amount <= 0) {
    showMessage("Amount must be greater than 0", true);
    return false;
}

fetch("withdraw", {
    method: "POST",
    headers: {
        "Content-Type": "application/x-www-form-urlencoded"
    },
    body: "amount=" + amount
})
.then(response => response.text())
.then(data => {

    if(data.startsWith("SUCCESS")){
        showMessage(data, false);
        setTimeout(() => {
            window.location.href = "dashboard.jsp";
        }, 2000);
    } else {
        showMessage(data.replace("ERROR:", ""), true);
    }
});

return false;
}

function showMessage(msg, isError){
let box = document.getElementById("msg");
box.innerHTML = msg;
box.className = isError ? "error" : "success";

```

```
}
</script>
</head>
<body>
<div class="container">
<h2>Withdraw Money</h2>
<form onsubmit="return validateAndSubmit();">
<input type="number" id="amount" step="0.01" min="1" placeholder="Enter
Amount" required>
<button type="submit">Withdraw</button>
</form>
<div id="msg"></div>
<br>
<a href="dashboard.jsp">Back to Dashboard</a>
</div>
</body>
</html>
```