

TED (15) 4187

Reg. No.....

Revision – 2015

Signature.....

FOURTH SEMESTER DIPLOMA EXAMINATION IN ARCHITECTURE

MODEL QUESTION PAPER

WORKING DRAWING-I

(Total Marks: 100)

(Time: 3 Hours)

(Note:-- 1. Drawing shall be neat and fully dimensioned.

2. Missing data can be suitably assumed.

3. A2 size drawing sheet to be provided.)

PART –A

(Maximum Marks: 10)

Marks

I. Answer the following questions in one or two sentences:

1. Define masonry.
2. What is shallow foundation?
3. What is glazing?
4. Differentiate between baluster and balustrade.
5. State the function of purlin in a truss.

(5x2)

PART-B

(Maximum Marks: 30)

II. Answer any three questions from following. Each question carries 10 marks.

- 1 Draw two consecutive courses of one and half brick thick wall of English bond.
- 2 Draw to a suitable scale details of meeting of door frame, shutter frame and panel in a Panelled door.

- 3 Draw to a suitable scale plan and elevation of a bifurcated stair.
- 4 Draw to a suitable scale cross section of a stair and mark nosing, tread, riser and baluster
- 5 Draw to a suitable scale the detailed elevation of base plate joint of a steel truss. (3x10)

PART-C

(Maximum Marks: 60)

(Answer one full question from each module)

MODULE-I

- III. Draw the sectional elevation and plan of footing of a R.C.C. column of size 30 cm X 30 cm with footing of size 160 cm X 160 cm and 10 mm dia bars are provided as reinforcement @10 cm c/c in both directions in footing. The thickness at the edge of the footing is 20 cm and of the sloping side is 20 cm. The size of P.C.C. levelling course is 180 cm X 180 cm and thickness is 10 cm. Column is provided with 4 Nos. of 16 mm dia. bars and 8 mm dia lateral ties @ 15 cm c/c. (15)

OR

- IV. Draw plan and elevation of two consecutive courses of corner wall of rat trap bond With one end stopped at 110cm. Draw the elevation up to a height of 80 cm. (15)

MODULE-II

- V. Draw to a suitable scale plan and elevation of a double shuttered half glazed door of size 100 cm X 200 cm.
Size of door frame – 10 cm X 7 cm.
Style – 8.5 cm X 3.5 cm.
Top rail – 8.5 cm X 3.5 cm
Lock rail -15 cm X 3.5 cm
Mid rail - 9.5 cm X 3.5 cm
Bottom rail- 15 cm X 3.5 cm

Panel – 1.6 cm thick (15)

OR

VI Draw to a suitable scale plan and elevation of a fully glazed metal window of size 100 cm X 120 cm. (15)

MODULE-III

VII Draw the plan and sectional elevation of passenger lift with a capacity of 10 persons. Size of lift well is 190 cm X 210 cm. The size of lift car is 135 cm X 130 cm. Inside dimensions are given. Lift pit depth is 160 cm. The lift serves 4 floors. The floor to floor height is 360 cm. The size of machine room may be suitably assumed. (15)

OR

VIII Draw the plan and sectional elevation of R.C.C dog-legged staircase for a double storied building. Size of stair case is 180 cm X 400 cm. The width of stair is 90 cm. The floor to floor height is 300 cm. The reinforcement details are given.
Main bar-- 8mm dia @ 15 cm c/c.
Distributors – 6 mm dia. @ 15 cm c/c
Suspenders – 6 mm dia. @ 15 cm c/c. (15)

MODULE-IV

IX. Draw the fully labelled elevation of a typical steel truss having angular sections.
Effective span is 1220 cm.
The wall thickness is 20 cm. (15)

OR

X Draw the fully labelled elevation of a typical tubular truss of 800 cm clear span. The wall Thickness is 30 cm. (15)

