Christian Hopps
LabN Consulting, LLC

MGMTD
Getting Approved

PR10000 MGMTD pull-request

- Currently PR contains 194 changed files.
 - 6 commits, seem nicely separated
- Local and Remote validation options exist (thanks)
 - Local: embed component northbound functions directly in mgmtd
 - Remote: give mgmtd the set of xpaths component handles
 - Xpaths can be compiled in or signaled with RPC
- mgmtd local validation currently on by default
- mgmtd remote code needs fix
 - chopps has the patch/fix ready for review and merge.

Local Validation

• PROS:

• Tiny bit faster (1%) – e.g., 10k static route config

Local Validation: 20.76sRemote Validation: 20.95s

- Forces component authors to not use operational data during config process
 - However, this is easy to catch in review
- Pushpasis: Local validation done under mgmtds cooperative scheduler
 - [chopps: if not what batches were for, then batches are useless complexity, so let's dump them ☺]

• CONS:

- Complexity in every component
 - #ifdefs in every northbound function
 - For example, isisd will have ~124 functions with #ifdef's cutting them up
 - Far worse for BGP
- Fixable later if necessary
 - Add validation callback separate from "prepare/apply/abort" callback, no more ifdefs
 - Significant number of LOC changed, but relatively easy to review if done separately

Remote Validation

- Greatly simplifies per component requirements
 - Removes massive number of #ifdefs permeating the northbound (user written and managed) component code.
 - Changes reduced to small init/cleanup common functions
 - Required for both local and remote validation
- Simplifies review of every component b/c very little of the component is changed.
 - #ifdefs can be isolated to single machine generated file
 - Will provide script to update the existing machine generated files.
 - #ifdefs can be eliminated by using existing xpath registration API
 - Very simple to add if the existing mgmtd functionality works
 - We don't need the ifdefs even now, just need to put wildcard xpath somewhere
 - Need to move the per component xpaths from mgmtd to the component for single source of truth



Fixing Abbreviations

- Color of the bikeshed ©
- Is more than just asthetics
 - frntnd / bcknd not good
 - Removing vowels in long words leads to constant typos due to muscle memory
- Suggestion from top to bottom preference (so far)
 - _fe_ / _be_ [chosen]
 - google frontend backend, febe is top hit
 - matches our existing 2 char "nb" for northbound
 - _frend_ / _bkend_
 - less preferred too many keys, but more "readable" I guess
 - frontend / backened
 - too many characters in already long identifiers not good choice

Next Steps

- Branch Created (dev/mgmtd)
- Fix abbreviations using existing commits [picked fe/be AI: chopps]
- Remove huge topotest change commit [AI: nguggarigoud@vmware.com>]
- Fixes and improvements added using pull-request/review
 - Add simple topotest change maybe 4 files instead of ~170? [AI: nguggarigoud@vmware.com]
 - Hack: Need to load each converted component's config into mgmtd in topotest
 - Until/if we convert topotest to use consolidated config.
 - Fix remote validation [Al: chopps]
 - Fix staticd component inc. xpath wildcard [AI: pushpasis]
 - Add simple CI test [AI: chopps]
 - Fix xpath registration code 'subscribe' functionality?
 - Remove unnecessary complexity (e.g., use events not 10μs timers)?
- Enable CI test for branch
- Replace PR/10000 and get merged to master!