Logic Building Assignment : 10

1.Write a program which accept radius of circle from user and calculate its area. Consider value of PI as 3.14. (Area = PI * Radius * Radius)

Input : 5.3
Output : 88.2026

Input : 10.4
Output : 339.6224

```
#include<stdio.h>

double CircleArea(float fRadius)
{
	// Logic
}

int main()
{
	float fValue = 0.0;
	double dRet = 0.0;

	printf("Enter radius");
	scanf("%f",&fValue);

	dRet = CircleArea(fValue);

	printf("_____");

	return 0;
}
```

2. Write a program which accept width & height of rectangle from user and calculate its area. (Area = Width * Height)

Input : 5.3 9.78
Output : 51.834

```
#include<stdio.h>

double RectArea(float fWidth, float fHeight)
{
	// Logic
}
```

```
int main()
{
	float fValue1 = 0.0, fValue2 = 0.0;
	double dRet = 0.0;

	printf("Enter width");
	scanf("%f",&fValue1);

	printf("Enter height");
	scanf("%f",&fValue2);

	dRet = RectArea(fValue1, fValue2);

	printf("_____");

	return 0;
}
```

3. Write a program which accept distance in kilometre and convert it into meter. (1 kilometre = 1000 Meter)

Input : 5
Output : 5000

Input : 12
Output : 12000

```
#include<stdio.h>

int KMtoMeter(int iNo)
{
	// Logic
}

int main()
{
	int iValue = 0, iRet = 0;

	printf("Enter distance");
	scanf("%d",&iValue1);

	iRet = KMtoMeter(iValue);

	printf("_____");

	return 0;
```

```
}
```

4. Write a program which accept temperature in Fahrenheit and convert it into celsius. (1 celsius = (Fahrenheit -32) * (5/9))

Input : 10
Output : -12.2222 (10 - 32) * (5/9)

Input : 34
Output : 1.11111 (34 - 32) * (5/9)

```
#include<stdio.h>

double FhtoCs(float fTemp)
{
	// Logic
}

int main()
{
	float fValue = 0.0;
	double dRet = 0.0;

	printf("Enter temperature in Fahrenheit");
	scanf("%d",&fValue1);

	dRet = FhtoCs(fValue);

	printf("_____");

	return 0;
}
```

5. Write a program which accept area in square feet and convert it into square meter. (1 square feet = 0.0929 Square meter)

Input : 5
Output : 0.464515

Input : 7
Output : 0.650321

```
#include<stdio.h>

double SquareMeter(int iValue)
{
```

```
        // Logic
}

int main()
{
        int iValue = 0;
        double dRet = 0.0;

        printf("Enter area in square feet");
        scanf("%d",&fValue);

        dRet = SquareMeter(iValue);

        printf("_____");

        return 0;
}
```