

EXTENDS *FiniteSets, Integers, Utils, TLC*

CONSTANTS

P the set of processes
 , B the set of malicious processes
 , $tAdv$ the time it takes for a malicious process to produce a message
 , tWB the time it takes for a well-behaved process to produce a message

ASSUME $B \subseteq P$ malicious processes are a subset of all processes

$W \triangleq P \setminus B$ the set of well-behaved processes

$Tick \triangleq Nat$ a tick is a real-time clock tick

$Round \triangleq Nat$ a round is just a tag on a message

Processes build a *DAG* of messages. The message-production rate of well-behaved processes is of 1 message per tWB ticks, and that of malicious processes is of 1 message per $tAdv$ ticks. We require that, collectively, well-behaved processes produce messages at a rate strictly higher than that of malicious processes.

ASSUME $Cardinality(W) * tAdv > Cardinality(B) * tWB$

A message consists of a unique *ID*, a round number, and a coffer containing the *IDs* of a set of predecessor messages:

$MessageID \triangleq P \times Nat$

$Message \triangleq [id : MessageID, round : Round, coffer : SUBSET MessageID]$

$sender(m) \triangleq m.id[1]$

A strongly consistent chain is a subset of the messages in the *DAG* that potentially has some dangling pointers (*i.e.* messages that have predecessors not in the chain) and that satisfies the following recursive predicate:

* Any set of messages which all have a round of 0 is a strongly consistent chain.

* A set of messages C with some non-zero rounds and maximal round r is a strongly consistent chain when, with Tip being the set of messages in the chain that have round r and $Pred$ being the set of messages in the chain with round $r - 1$, $Pred$ is a strict majority of the set of predecessors of each message in Tip and $C \setminus Tip$ is a consistent chain.

The max round of a set of messages is the maximal round of its messages:

$MaxRound(M) \triangleq MaxInteger(\{m.round : m \in M\})$

$StronglyConsistentChain(M) \triangleq$

$\wedge M \neq \{\}$

$\wedge \vee MaxRound(M) = 0$

$\vee \forall r \in 1 \dots MaxRound(M) :$

LET $Tip \triangleq \{m \in M : m.round = r\}$

$Pred \triangleq \{m \in M : m.round = r - 1\}$

IN $\wedge Tip \neq \{\}$

$\wedge \forall m \in Tip :$

$\wedge \{m2.id : m2 \in Pred\} \subseteq m.coffer$

$$\wedge 2 * \text{Cardinality}(\text{Pred}) > \text{Cardinality}(m.\text{coffer})$$

A weaker version of the above:

$$\begin{aligned} \text{ConsistentChain}(M) &\triangleq \\ &\wedge M \neq \{\} \\ &\wedge \vee \text{MaxRound}(M) = 0 \\ &\vee \forall r \in 1 \dots \text{MaxRound}(M) : \\ &\quad \text{LET } \text{Tip} \triangleq \{m \in M : m.\text{round} = r\} \\ &\quad \text{Pred} \triangleq \{m \in M : m.\text{round} = r - 1\} \\ &\quad \text{IN } \wedge \text{Tip} \neq \{\} \\ &\quad \wedge \forall m \in \text{Tip} : \exists \text{Maj} \in \text{SUBSET Pred} : \\ &\quad \quad \wedge \{m2.\text{id} : m2 \in \text{Maj}\} \subseteq m.\text{coffer} \\ &\quad \wedge 2 * \text{Cardinality}(\text{Maj}) > \text{Cardinality}(m.\text{coffer}) \end{aligned}$$

$$\begin{aligned} \text{Chains}(M, r) &\triangleq \{C \in \text{SUBSET } M : \\ &\quad \wedge \forall m \in C : m.\text{round} \leq r \\ &\quad \wedge \forall r2 \in 0 \dots r : \exists m \in C : m.\text{round} = r2\} \end{aligned}$$

The set of all consistent chains that can be found in M :

$$\begin{aligned} \text{ConsistentChains}(M, r) &\triangleq \\ &\{C \in \text{Chains}(M, r) : \text{ConsistentChain}(C)\} \end{aligned}$$

The set of all strongly consistent chains that can be found in M :

$$\begin{aligned} \text{StronglyConsistentChains}(M, r) &\triangleq \\ &\{C \in \text{Chains}(M, r) : \text{StronglyConsistentChain}(C)\} \end{aligned}$$

We can rank the chains by wheight, *i.e.* just their cardinality, or we can consider the maximal or minimal one in the subset order:

$$\begin{aligned} \text{HeaviestConsistentChains}(M, r) &\triangleq \text{MaxCardinalitySets}(\text{ConsistentChains}(M, r)) \\ \text{HeaviestStronglyConsistentChains}(M, r) &\triangleq \text{MaxCardinalitySets}(\text{StronglyConsistentChains}(M, r)) \\ \text{MinimalStronglyConsistentChains}(M, r) &\triangleq \text{MinimalSets}(\text{StronglyConsistentChains}(M, r)) \\ \text{MaximalStronglyConsistentChains}(M, r) &\triangleq \text{MaximalSets}(\text{StronglyConsistentChains}(M, r)) \end{aligned}$$

Two chains are disjoint when there is a round smaller than their max round in which they share less than a strict majority of their messages.

$$\begin{aligned} \text{DisjointChains}(C1, C2) &\triangleq \\ &\text{LET } rmax \triangleq \text{MaxRound}(C1 \cup C2) \\ &\text{IN } \exists r \in 0 \dots (rmax - 1) : \\ &\quad \text{LET } I \triangleq \{m \in C1 : m.\text{round} = r\} \cap \{m \in C2 : m.\text{round} = r\} \\ &\quad \text{IN } \vee 2 * \text{Cardinality}(I) < \text{Cardinality}(C1) \\ &\quad \vee 2 * \text{Cardinality}(I) < \text{Cardinality}(C2) \end{aligned}$$

Acceptance rule

$$\begin{aligned} \text{AcceptedMessages}(M, r) &\triangleq \{m \in M : \\ &\quad \wedge m.\text{round} = r - 1 \\ &\quad \wedge \text{LET } CCs \triangleq \text{MaximalStronglyConsistentChains}(M, r - 1) \text{IN } \end{aligned} \quad \text{This looks promising!}$$

$$\begin{aligned}
& \wedge \exists C \in CCs : m \in C \\
& \wedge \forall C1, C2 \in CCs : \\
& \quad \wedge m \in C1 \\
& \quad \wedge m \notin C2 \\
& \quad \wedge DisjointChains(C1, C2) \\
& \quad \Rightarrow Cardinality(C2) \leq Cardinality(C1)
\end{aligned}$$

M does not have dangling edges:

$$Closed(M) \triangleq \forall m \in M : \forall i \in m.coffer : \exists m2 \in M : m2.id = i$$

Now we specify the algorithm

```

--algorithm Algo{
  variables
    messages = {};
    tick = 0;
    phase = "start";  each tick has two phases: "start" and "end"
    donePhase = [p ∈ P ↦ "end"];
    pendingMessage = [p ∈ P ↦ ⟨⟩];  message we're computing the VDF on
    messageCount = [p ∈ P ↦ 0];  used to generate unique message IDs
  define {
    currentRound ≜ tick ÷ tWB  round of well-behaved processes
    wellBehavedMessages ≜ {m ∈ messages : sender(m) ∈ P \ B}
    possible sets of messages received by a well-behaved process:
    receivedMsgsSets ≜
      ignore messages from future rounds:
      LET msgs ≜ {m ∈ messages : m.round < currentRound} IN
      {M ∈ SUBSET msgs :
        don't use a set of messages that has dangling edges (messages in coffers that are missing):
        ∧ Closed(M)
        ∧ wellBehavedMessages ⊆ M}
  }
  macro sendMessage( m ) {
    messages := messages ∪ {m}
  }
  process ( clock ∈ {"clock"} ) {
    tick: while ( TRUE ) {
      await ∀ p ∈ P : donePhase[p] = phase;
      if ( phase = "start" )
        phase := "end"
      else {
        phase := "start";
        tick := tick + 1
      }
    }
  }
}

```

```

    }
    process (  $proc \in P \setminus B$  )  a well-behaved process
    {
l1:   while ( TRUE ) {
        await phase = "start" ;
        if (  $tick \% tWB = 0$  ) {
            Start the VDF computation for the next message:
            with (  $msgs \in receivedMsgsSets$  )
            with (  $predMsgs = AcceptedMessages(msgs, currentRound)$  ) {
                pendingMessage[self] := [
                     $id \mapsto \langle self, messageCount[self] + 1 \rangle$ ,
                     $round \mapsto currentRound$ ,
                     $coffer \mapsto \{m.id : m \in predMsgs\}$  ;
                messageCount[self] := messageCount[self] + 1
            }
        } ;
        donePhase[self] := "start" ;
l2:   await phase = "end" ;
        if (  $tick \% tWB = tWB - 1$  )
            it's the end of the  $tWB$  period, the VDF has been computed
            sendMessage(pendingMessage[self]) ;
            donePhase[self] := "end" ;
    }
}

process (  $byz \in B$  )  a malicious process
{
lb1:  while ( TRUE ) {
        await phase = "start" ;
        when  $currentRound < 2; \setminus * TODO$  temporary hack
        if (  $tick \% tAdv = 0$  ) {
            Start the VDF computation for the next message:
            with (  $maxRound = Max(\{m.round : m \in messages\} \cup \{0\}, \leq)$  )
            with (  $rnd \in \{maxRound, maxRound + 1\}$  )
            with (  $predMsgs \in SUBSET \{m \in messages : m.round = rnd - 1\}$  ) {
                when  $rnd > 0 \Rightarrow predMsgs \neq \{\}$  ;
                pendingMessage[self] := [
                     $id \mapsto \langle self, messageCount[self] + 1 \rangle$ ,
                     $round \mapsto rnd$ ,
                     $coffer \mapsto \{m.id : m \in predMsgs\}$  ;
                messageCount[self] := messageCount[self] + 1
            }
        } ;
        donePhase[self] := "start" ;
lb2:  await phase = "end" ;
        if (  $tick \% tAdv = tAdv - 1$  )

```

```

        sendMessage(pendingMessage[self]);
        donePhase[self] := "end" ;
    } ;
}

```

Invariant describing the type of the variables:

$TypeOK \triangleq$

- $\wedge \text{ messages} \in \text{SUBSET } Message$
- $\wedge \text{ pendingMessage} \in [P \rightarrow Message \cup \{\langle \rangle\}]$
- $\wedge \text{ tick} \in Tick$
- $\wedge \text{ phase} \in \{\text{"start"}, \text{"end"}\}$
- $\wedge \text{ donePhase} \in [P \rightarrow \{\text{"start"}, \text{"end"}\}]$
- $\wedge \text{ messageCount} \in [P \rightarrow Nat]$

The main property we want to establish is that, each round, for each message m of a well-behaved process, the messages of well-behaved processes from the previous round are all in m 's coffer and consist of a strict majority of m 's coffer.

$Safety \triangleq \forall p \in P \setminus B : \text{LET } m \triangleq \text{pendingMessage}[p] \text{ IN}$

- $\wedge m \neq \langle \rangle$
- $\wedge m.\text{round} > 0$
- \Rightarrow
- $\wedge \forall m2 \in \text{wellBehavedMessages} : m2.\text{round} = m.\text{round} - 1 \Rightarrow m2.id \in m.\text{coffer}$
- $\wedge \text{LET } M \triangleq \{m2 \in \text{wellBehavedMessages} : m2.\text{round} = m.\text{round} - 1\}$
- $\text{IN } 2 * \text{Cardinality}(M) > \text{Cardinality}(m.\text{coffer})$

helper definition:

$\text{messageWithID}(id) \triangleq \text{CHOOSE } m \in \text{messages} : m.id = id$

Basic well-formedness properties:

$Inv1 \triangleq \forall m \in \text{messages} :$

- $\wedge \forall m2 \in \text{messages} : m \neq m2 \Rightarrow m.id \neq m2.id$
- $\wedge \forall id \in m.\text{coffer} :$
 - $\wedge \exists m2 \in \text{messages} : m2.id = id$
 - $\wedge \text{messageWithID}(id).\text{round} = m.\text{round} - 1$