



KAP-16

Porous Alumina Plates

KEY PROPERTIES

- Controlled porosity structure
- High temperature resistance
- Good thermal stability
- Low Density
- Good thermal shock behavior

APPLICATIONS

- Filtration systems
- Thermal insulation components
- Catalyst supports
- Furnace linings
- Lightweight structural parts

MAIN PROPERTIES

Property	Value	Unit
Density	2.75	g/cm ³
Porosity	16	%
Max Service Temperature	1750	°C
CTE (20–1100°C)	82	%

* All properties measured at 20°C unless otherwise stated.

** Measured in a wall thickness of 2 mm

OPERATING CONDITIONS

Max working temp (air)		1750 °C
Recomended temp		<1700 °C
Continuous temp		1600 °C

ELECTRICAL BEHAVIOR

Insulator

MATERIAL INFORMATION

Material type		Porous alumina
Structure		Open porosity
Porosity level		16%
Composition		Al ₂ O ₃ (82%)
Density class		Lightweight

Local overheating may occur at electrical contact points due to current concentration and geometry effects.

The information provided is for guidance only and does not constitute a guarantee.

Nanoker Research S.L.

Polígono de Olloniego, Parcela 21A, Nave 4-8, 33660, Oviedo (Asturias), Spain

(+34) 985 20 76 13 | info@nanoker.com