

```

L      130.130.0.2/32 is directly connected, FastEthernet0/1
192.168.1.0/24 is variably subnetted, 2 subnets, 2 masks
C      192.168.1.0/24 is directly connected, FastEthernet0/0
L      192.168.1.1/32 is directly connected, FastEthernet0/0
R3#
R3#
R3#
R3#
R3#
R3#
R3#
R3#
R3#
R3#
R3#
R3#
R3#
R3#
R3#
R3#
R3#
R3#
R3#
R3#
R3#
R3#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
R3(config)#ip route 60.0.0.2 255.0.0.0 130.130.0.1
%Inconsistent address and mask
R3(config)#ip route 60.0.0.0 255.0.0.0 130.130.0.1
R3(config)#ip route 50.0.0.0 255.0.0.0 130.130.0.1
R3(config)#exit
R3#sh ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       + - replicated route, % - next hop override

Gateway of last resort is not set

S      50.0.0.0/8 [1/0] via 130.130.0.1
S      60.0.0.0/8 [1/0] via 130.130.0.1
130.130.0.0/16 is variably subnetted, 2 subnets, 2 masks
C      130.130.0.0/16 is directly connected, FastEthernet0/1
L      130.130.0.2/32 is directly connected, FastEthernet0/1
192.168.1.0/24 is variably subnetted, 2 subnets, 2 masks
C      192.168.1.0/24 is directly connected, FastEthernet0/0
L      192.168.1.1/32 is directly connected, FastEthernet0/0
R3#
R3#

```

C:\Windows\system32\cmd.exe

Microsoft Windows [Version 10.0.22631.6199]
(c) Microsoft Corporation. All rights reserved.

C:\Users\Subash sanjay>ping 50.0.0.2

Pinging 50.0.0.2 with 32 bytes of data:
Reply from 50.0.0.2: bytes=32 time=1ms TTL=125
Reply from 50.0.0.2: bytes=32 time=1ms TTL=125
Reply from 50.0.0.2: bytes=32 time=2ms TTL=125
Reply from 50.0.0.2: bytes=32 time=2ms TTL=125

Ping statistics for 50.0.0.2:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\Users\Subash sanjay>

