Invoice API Guide

Cosium

Table of Contents

Overview

HTTP verbs

HTTP status codes

Access token

- How to get an access token
- How to use the access token

Hypermedia

CORS - Cross-Origin Resource Sharing

- CORS activation
- CORS cookie credentials

Resources

Invoices

- List invoices

Overview

HTTP verbs

RESTful Center tries to adhere as closely as possible to standard HTTP and REST conventions in its use of HTTP verbs.

Verb	Usage
`GET`	Used to retrieve a resource
`POST`	Used to create a new resource
`PUT`	Used to create or update a resource in an indempotent way
`PATCH`	Used to update an existing resource, including partial updates
`DELETE`	Used to delete an existing resource

HTTP status codes

RESTful Center tries to adhere as closely as possible to standard HTTP and REST conventions in its use of HTTP status codes.

Status code	Usage
`200 OK`	The request completed successfully
`201 Created`	A new resource has been created successfully. The resource's URI is available from the response's `Location` header
`204 No Content`	An update to an existing resource has been applied successfully
`400 Bad Request`	The request was malformed. The response body will include an error providing further information
`401 Unauthorized`	The request could not be authenticated. You must provide a valid access token.
`403 Forbidden`	The request has been authenticated but the operation is fobidden. This can be caused by insufficient privileges.
`404 Not Found`	The requested resource did not exist

Access token

Often, a valid access token is required to access this API resources.

How to get an access token

Request fields

Path	Type	Description
`login`	`String`	The login
`password`	`String`	The password
`site`	`String`	The site/store name to authenticate to

Response headers

Name	Description
`access_token`	The access token

Example request

HTTP

```http
POST /01ACJA05562/api/authenticate/basic HTTP/1.1
Content-Type: application/json
Content-Length: 123
Host: c1.cosium.biz

{
  "login" : "class com.cos.center.core.user.UserFixture59",
  "password" : "ReX^9ut4Kup>U)/E",
  "site" : "foo-site-42"
}
```

Example response

```http
HTTP/1.1 200 OK
Vary: Origin
Vary: Access-Control-Request-Method
Vary: Access-Control-Request-Headers
Set-Cookie: access_token=NNHiKn3rJrua3Xzs62s0cpl5z7U; Path=/01ACJA05562; Secure; HttpOnly
access_token: NNHiKn3rJrua3Xzs62s0cpl5z7U
COS-AUTH-TOKEN: NNHiKn3rJrua3Xzs62s0cpl5z7U
authentication-ok: true
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
Strict-Transport-Security: max-age=31536000 ; includeSubDomains
Content-Length: 27

NNHiKn3rJrua3Xzs62s0cpl5z7U
```

How to use the access token

You must pass the access token in each request either via:

- an Authorization AccessToken header. e.g. for token **abcd1234**, you must pass the header **Authorization: AccessToken abcd1234**
- a cookie named **access_token**
- a request parameter named **access_token**

Hypermedia

RESTful Cosium Center uses hypermedia and resources include links to other resources in their responses. Responses are in Hypertext Application from resource to resource. Language (HAL) (http://stateless.co/hal_specification.html) format. Links can be found beneath the `_links` key. Users of the API should not create URIs themselves, instead they should use the above-described links to navigate. To obtain HAL representation, you must provide the header **Accept: application/hal+json** to your Http request.

CORS - Cross-Origin Resource Sharing

CORS activation

CORS is disabled by default.

Web applications hosted on different domains need their domains to be added to CORS.

The Web Application CORS activation request must be made to a Cosium representative.

CORS cookie credentials

CORS enabled web applications relying on cookie credentials must set `XMLHttpRequest` parameter `withCredentials` to true.

Example with XMLHttpRequest

JAVASCRIPT

```javascript
var request = new XMLHttpRequest();
request.withCredentials = true;
```

MDN documentation (https://developer.mozilla.org/en-US/docs/Web/API/XMLHttpRequest/withCredentials)

Resources

Invoices

List invoices

Request parameters

Parameter	Description
`types`	List of invoice types. Valid values : INVOICE, QUOTE, CREDIT_NOTE, DELIVERY_NOTE, SHIPPING_FORM, ORDER_FORM, VALUED_NOTE, RETURN_VOUCHER, SUPPLIER_ORDER_FORM, SUPPLIER_DELIVERY_NOTE, SUPPLIER_INVOICE, SUPPLIER_CREDIT_NOTE, SUPPLIER_VALUED_NOTE, SUPPLIER_RETURN_VOUCHER, STOCK_MOVE, STOCK_MANUAL_UPDATE
`invoiceDateFrom`	Invoice date from, included. Format : yyyy-MM-dd'T'HH:mm:ss.SSSZ
`invoiceDateTo`	Invoice date to, excluded. Format : yyyy-MM-dd'T'HH:mm:ss.SSSZ
`siteId`	Invoice site id
`archived`	If true, only return archived invoices
`hasAdvancePayment`	If true, only return invoices with advance payments
`settled`	If true, only return settled invoices
`invoiceNumber`	Invoice number
`validationQuoteDateIsPresent`	Only return quotes with a validation date
`pageSize`	Page size, maximum 500, defaults to 100.

Parameter	Description
pageNumber	Page number, defaults to 0

Example request

```http
GET /01ACJA05562/api/invoices HTTP/1.1
Content-Type: application/json
Host: c1.cosium.biz
```

Response fields

Path	Type	Description
number	Number	Page number
totalElements	Number	Page total elements
totalNumberOfElements	Number	Page total elements
totalPages	Number	Total pages
numberOfElements	Number	Number of elements on current page
size	Number	Page size
content[].id	Number	Invoice id
content[].type	String	Invoice type
content[].invoiceNumber	String	Invoice number
content[].invoiceDate	String	Invoice date. Format : yyyy-MM-dd'T'HH:mm:ss.SSSZ
content[].customerName	String	Customer name
content[].siteId	Number	Owner site's id

Path	Type	Description
`content[].outstandingBalance`	`Number`	Outstanding balance
`content[].totalTI`	`Number`	Total tax included
`content[].shareSocialSecurity`	`Number`	Amount paid by social security
`content[].sharePrivateInsurance`	`Number`	Amount paid by private insurance

Example response

HTTP

```
HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: 449

{
  "content" : [ {
    "id" : 1,
    "type" : "INVOICE",
    "invoiceNumber" : "I10",
    "invoiceDate" : "2022-01-05T23:00:00.000Z",
    "customerName" : "Some guy",
    "siteId" : 1,
    "outstandingBalance" : 10.0,
    "totalTI" : 100.0,
    "shareSocialSecurity" : 20.0,
    "sharePrivateInsurance" : 0.0
  } ],
  "numberOfElements" : 1,
  "number" : 0,
  "totalNumberOfElements" : 1,
  "totalPages" : 1,
  "size" : 100,
  "totalElements" : 1
}
```