



CECL

中能芯光

万“宗” 亿“芯”，“一致”出众


四元红黄LED芯片

产品目录

— ◆ —
昆山迅雷光电子有限公司


CECL

数码、指示、显示——甚高亮红

产品型号	外观	芯片结构	测试电流	尺寸	电极	高度	亮度 (mcd)	WD
			(mA)	(mil)	(um)	(um)		(nm)
CE-G05CUR*U/L		P-UP	20	4	55	150	100-180	620-627
CE-G07SUR*U/L		P-UP	20	4.5	55	150	100-180	620-627
CE-G06CUR*U/L		P-UP	20	5	65	140	100-210	620-627
CE-G06BUR*U/L		P-UP	20	5.2	65	150	110-190	620-627
CE-G07KUR*U/L		P-UP	20	5.5	75	150	100-230	620-627
CE-G07CUR*U/L		P-UP	20	6	80	160	110-230	620-627
CE-07BUR*U/L		P-UP	20	6.5	75	160	110-230	620-627
CE-08CUR*U/L		P-UP	20	7	90	160	110-230	620-627
CE-09CUR*U/L		P-UP	20	8	90	180	50-230	620-627
CE-07CUR*U/L		P-UP	20	6.2	65	160	290-360	620-627


CECL

数码、指示、显示——超高亮红

产品型号	外观	芯片结构	测试电流	尺寸	电极	高度	亮度 (mcd)	WD
			(mA)	(mil)	(um)	(um)		(nm)
CE-07DSR*U/L		P-UP	20	5.5	75	160	10-150	630-637
CE-07CSR*U/L		P-UP	20	6	80	160	10-140	630-637
CE-07BSR*U/L		P-UP	20	6.5	75	160	10-150	630-637
CE-08CSR*U/L		P-UP	20	7	90	160	40-150	630-637
CE-09CSR*U/L		P-UP	20	8	90	180	40-125	630-637


CECL

数码、指示、显示——高亮红

产品型号	外观	芯片结构	测试电流	尺寸	电极	高度	亮度 (mcd)	WD
			(mA)	(mil)	(um)	(um)		(nm)
CE-07CHR*L		P-UP	20	6	80	180	10-80	637-645
CE-07BHR*U/L		P-UP	20	6.5	75	160	10-80	637-645
CE-08CHR*U/L		P-UP	20	7	90	160	10-80	637-645
CE-09CHR*U/L		P-UP	20	8	90	160	10-80	637-645


CECL

数码、指示、显示——橙光

产品型号	外观	芯片结构	测试电流	尺寸	电极	高度	亮度 (mcd)	WD
			(mA)	(mil)	(um)	(um)		(nm)
CE-G06CSO*U/L		P-UP	20	5	65	140	110-250	600-607
CE-06BSO*L		P-UP	20	5.5	75	180	90-210	600-607
CE-G07CSO*U/L		P-UP	20	6	80	160	110-250	600-607
CE-08CSO*U/L		P-UP	20	7	90	160	110-250	600-607
CE-09CSO*U/L		P-UP	20	8	90	160	110-250	600-607




数码、指示、显示——黄光

产品型号	外观	芯片结构	测试电流	尺寸	电极	高度	亮度 (mcd)	WD
			(mA)	(mil)	(um)	(um)		(nm)
CE-G06CSY*U/L		P-UP	20	5	65	140	100-230	583-595
CE-G07DSY*U/L		P-UP	20	5.5	75	160	110-250	583-595
CE-G07CSY*U/L		P-UP	20	6	80	160	110-250	583-595
CE-08CSY*U/L		P-UP	20	7	90	160	60-250	583-595
CE-09CSY*U/L		P-UP	20	8	90	160	60-250	583-595
CE-F12CSY*U		N-UP	20	10	96	175	300-600	583-595



CECL

数码、指示、显示——黄绿光

产品型号	外观	芯片结构	测试电流	尺寸	电极	高度	亮度 (mcd)	WD
			(mA)	(mil)	(um)	(um)		(nm)
CE-G05BYG*U/L		P-UP	20	4.5	60	140	10-100	565-576
CE-G06CYG*U/L		P-UP	20	5	65	140	10-100	565-576
CE-G07DYG*U/L		P-UP	20	5.5	75	160	10-100	565-576
CE-G07CYG*U/L		P-UP	20	6	80	160	10-100	565-576
CE-07BYG*U/L		P-UP	20	6.5	75	160	10-100	565-576
CE-08CYG*U/L		P-UP	20	7	90	180	10-80	565-576
CE-09CYG*U/L		P-UP	20	8	90	160	10-100	565-576


CECL

近二三元系列

产品型号	外观	芯片结构	测试电流	尺寸	电极	高度	亮度 (mcd)	WD
			(mA)	(mil)	(um)	(um)		(nm)
CE-F08CHR*L-F2		N-UP	20	7	100	190	10-20	640-648
CE-G07CYG*L-F2		P-UP	20	6	65	150	25-45	564-570
CE-08CYG*L-F2		P-UP	20	7	90	175	10-55	564-570
CE-09CYG*L-F2		P-UP	20	8	90	175	10-55	564-570
CE-08CSY*L-F2		P-UP	20	7	90	160	10-30	582-589
CE-F11CYG*L-F2		N-UP	20	10	100	185	20-40	568-573


CECL

户外系列

产品型号	外观	芯片结构	测试电流	尺寸	电极	高度	亮度 (mcd)	WD
			(mA)	(mil)	(um)	(um)		(nm)
CE-F07GUR*U		N-UP	20	5.0	65	145	440-600	620-625
CE-F07EUR*U		N-UP	20	5.5	65	145	440-600	620-625
CE-F07CUR*U		N-UP	20	6.0	70	140	440-600	620-625
CE-F08CUR*U		N-UP	20	7.0	72	140	480-680	620-625
CE-F08BUR*U		N-UP	20	8.0	75	140	680-830	620-625
CE-F12CUR*U		N-UP	20	10.0	80	140	760-1000	620-625
CE-F09CSY*U		N-UP	20	8	80	180	400-600	585-595
CE-F12CSY*U		N-UP	20	10	85	170	400-950	585-595
CE-F12CSO*U		N-UP	20	10	85	170	400-950	600-607

CECL

大功率系列

产品型号	外观	芯片结构	测试电流	尺寸	电极	高度	亮度 (mcd)	WD
			(mA)	(mil)	(um)	(um)		(nm)
CE-F16CUR*U		N-UP	60	14	90	160	500-100	620-625
CE-F18EUR*U		N-UP	150	16	100	160	4800-6800	620-625
CE-F26AUR*U		N-UP	250	26	100	180	10000-12000	620-625
CE-F38AUR*U		N-UP	350	38	110	180	14000-16000	620-625
CE-F16CSR*U		N-UP	60	14	90	160	700-1200	627-635
CE-F22ASR*U		N-UP	150	22	100	160	4000-6500	627-635




CECL

植物灯系列

产品型号	外观	芯片结构	测试电流	尺寸	电极	高度	亮度 (mW)	WP
			(mA)	(mil)	(um)	(um)		(nm)
CE-F11CUHR*U		N-UP	20	10	80	160	9-15	650-670
CE-F16CUHR*U		N-UP	60	14	90	160	32-48	650-670
CE-F18AUHR*U		N-UP	150	18	100	160	80-110	650-670
CE-F32AUHR*U		N-UP	350	32	105	180	200-260	650-670


CECL

红外850系列

产品型号	外观	芯片结构	测试电流	尺寸	电极	高度	亮度	WP
			(mA)	(mil)	(um)	(um)		(nm)
CE-F08AIR*U		N-UP	50	8	70	140	20-35	835-865
CE-F14CIR*U		N-UP	100	12	88	180	55-80	835-865
CE-F16CIR*U		N-UP	100	14	85	180	43-68	835-865
CE-F18CIR*ZCU		N-UP	250	16	100	180	140-180	835-865
CE-F26AIR*U		N-UP	350	26	100	180	160-190	835-865
CE-F35AIR*U		N-UP	350	35	100	180	160-190	835-865


CECL

红外940系列

产品型号	外观	芯片结构	测试电流	尺寸	电极	高度	亮度 (mW)	WP
			(mA)	(mil)	(um)	(um)		(nm)
CE-F08ANR*U		N-UP	50	8.0	85	180	9-15	925-965
CE-F10ANR*U		N-UP	50	10.0	85	180	12-18	925-965
CE-F16CNR*U		N-UP	100	14	85	180	38-63	925-965
CE-F42ANR*U		N-UP	350	42.0	100	180	190-220	925-965
CE-07ANR*U		P-UP	20	7.0	80	220	2.5-3.5	925-965
CE-08ANR*U		P-UP	20	8.0	80	220	3-4	925-965
CE-14CNR*U		P-UP	20	14.0	90	220	18-33	925-965




CECL

特殊系列

产品型号	外观	芯片结构	测试电流	尺寸	电极	高度	亮度 (mcd)	WD
			(mA)	(mil)	(um)	(um)		(nm)
CE-12C2UR*U		双电极红光	20	7*10	60	120	400-650	620-627
CE-09CUR*U			20	8*8	58	120	580-980	620-627
CE-12CUR*U			20	10*10	P70 N80	120	580-980	620-627
CE-20AUR*18VU		18V红光	20	20*20	60	160	80-120	620-627
CE-FL20B5UR*U		倒装红光	5	5*18	/	130	140-220	620-627

CECL

0201红黄系列

产品型号	外观	工艺结构	测试电流	尺寸	GAP	亮度 (mcd)	WD
			(mA)	(mm)	(um)		(nm)
CE-SS2010UR*-M		BT	5	0.57*0.28*0.38	150	30-60	620-627
CE-SS2010UR*-MF			5	0.57*0.28*0.38	150	80-120	620-627
CE-SS2010YG*-M			5	0.57*0.28*0.38	150	7-15	565-575
CE-SS2010SY*-M			5	0.57*0.28*0.38	150	30-60	586-595
CE-SS2010SO*-M			5	0.57*0.28*0.38	150	30-60	600-607
CE-SS2010SR*-M			5	0.57*0.28*0.38	150	15-25	630-637
CE-SS2010HR*-M			5	0.57*0.28*0.38	150	8-17	637-645
CE-SS2010UR*-MFL		CSP	5	0.63*0.33*0.25	150	105-230	618-627



中能芯光

以心交“芯”，筑实可“性”

昆山迅雷光电子有限公司

电话：0512-5032 9881

网址：www.cecl1688.com