



CECL

中能芯光

万“宗” 亿“芯”，“一致”出众



蓝绿LED芯片



产品目录

昆山迅雷光电子有限公司





照明正装系列

产品型号	外观	应用电流	尺寸	电极	高度	亮度	WD
		(mA)	(mil)	(um)	(um)	(mW)	(nm)
CE-06A4W*U		5-30	4*6	45	90	10-20	445-460
CE-07A5W*U		5-70	5*7	45	110	40-55	445-460
CE-08A5W*U		5-30	5*8	63	105	20-35	445-460
CE-09A5W*U		5-30	5*9	63	105	25-40	445-460
CE-10A6W*U		5-70	6*10	50	120	60-80	445-460
CE-11A7W*U		5-80	7*11	50	150	60-90	445-460
CE-14A7W*U		60	7*14	55	135	85-95	445-460

产品型号	外观	应用电流	尺寸	电极	高度	亮度	WD
		(mA)	(mil)	(um)	(um)	(mW)	(nm)
CE-15A8W*U		60	8*15	50	150	115-130	445-460
CE-18A8W*U		120	8*18	50	150	154-166	445-460
CE-25A9W*U		150	9*25	60	175	223-235	445-460




照明倒装系列


产品型号	外观	应用电流	尺寸	电极	电极间距 GAP	高度	亮度	WD
		(mA)	(mil)	(um)	(um)	(um)	(mW)	(nm)
CE-FL15A5W*U		10-60	5*15	121*94	120	120	7.5-8	445-460
CE-FL18A5W*U		10-60	5*18	142*90.5	150	120	9-9.5	445-460
CE-FL21C6W*U		10-60	6*19	142*110	150	148	8.5-11	445-460
CE-FL20C6W*9VU		10-60	6*18	140.5*122	150	135	58-63	445-460
CE-FL20C7W*18VU		10-60	7*18	130.5*141	150	150	56-58	445-460
CE-FL21C8W*U		120-150	8*19	144*170	150	150	159-175	445-460
CE-FL27A9W*U		120-150	9*27	250*194	150	180	195-205	445-460







照明高光效系列

产品型号	外观	应用电流	尺寸	电极	高度	亮度	光效	WD
		(mA)	(mil)	(um)	(um)	(mW)		(nm)
CE-30A9W*U		150	9*30	55	200	230-250	30-32lm@60mA 65-68 lm@150mA	445-460
CE-30A12W*U		150	12*30	60	200	260-280	31-33 lm @60mA 65-70 lm @150mA	445-460
CE-35A17W*U		10-200	17*35	65	200	145-150	32-34 lm @60mA	445-460
CE-35A20W*U		10-200	20*35	70	200	147.5-152.5	220 lm/w@65mA	445-460
CE-35A22W*U		10-200	22*35	70	200	150-155	230 lm/W@65mA	445-460
CE-40A22W*U		10-200	22*40	70	200	150-155	235 lm/W@65mA	445-460
CE-40A26W*U		10-200	26*40	70	200	152.5-157.5	240 lm/W@65mA	445-460




CECL TV 背光系列

产品型号	外观	应用电流	尺寸	电极	高度	亮度	光效	WD
		(mA)	(mil)	(um)	(um)	(mW)		(nm)
CE-36A25W*U		10-400	25*36	80	175	800-940	230 lm 2D 600mA	445-460
CE-51A25W*U		10-400	25*51	80	150	940-1000	280 lm 2D 380mA	445-460
CE-56A23W*U		10-400	23*56	70	200	152.5-160	50 lm 4014 pkg	445-460

CECL 手机、平板、显示器背光系列

产品型号	外观	应用电流	尺寸	电极	高度	亮度	光效	WD
		(mA)	(mil)	(um)	(um)	(mW)	Efficiency	(nm)
CE-7A22W*U		20	7*22	60	135	34-40	9.2lm@20mA	445-460
CE-27A8W*U		20	8*27	60	135	34-41.5	9.5lm@20mA	445-460
CE-41A8W*U		20	8*41	60	135	35.5-43	9.7lm@20mA	445-460
CE-45A9W*U		20	9*45	60	135	46.5-51	9.9lm@20mA	445-460
CE-48A8W*U		20	8*48	60	135	83-104	18.7lm@20mA	445-460

产品型号	外观	应用电流	尺寸	电极	高度	亮度	WD
		(mA)	(mil)	(um)	(um)		(nm)
CE-10C6B*U		1-20	6*9	65	90	38--54mcd	460-475
CE-10C6G*U		1-20	6*9	65	90	180-210mcd	515-535
CE-13C6W*U		1-20	6*11	80	120	85-110mcd	460-475
CE-13C6G*U		1-20	6*11	80	120	240-300mcd	515-535
CE-13C3W*U		1-20	8*11	75	120	5.0-7.2mW	450-475
CE-13C3G*U		1-20	8*11	75	120	220-360mcd	515-535
CE-14C9B*U		1-20	9*12	75	130	230-380mcd	460-475
CE-14C9G*U		1-20	9*12	75	130	1760-2180mcd	515-535
CE-16C1W*U		1-20	8*15	70	125	5-8mW	445-465

产品型号	外观	应用电流	尺寸	电极	高度	亮度	WD
		(mA)	(mil)	(um)	(um)		(nm)
CE-16B9B*U		1-20	9*15	65	130	200-550mcd	460-475
CE-16B9G*U		1-20	9*15	65	130	2210-2730mcd	515-535
CE-16C2B*U		5-60	12*14	80	130	60-100mW	455-475
CE-16C2G*U		5-60	12*14	80	130	15-25mW	515-535
CE-18B2B*U		60-150	12*17	70	120	35-50mW	460-475
CE-18B2G*U		60-150	12*17	70	120	36-42mW	515-535









数码倒装系列

产品型号	外观	应用电流	尺寸	电极间距 GAP	高度	亮度	WD
		(mA)	(mil)	(um)	(um)	(mW)	(nm)
CE-FL18C5W*U		10-60	5*16	120	120	8-9	445-465
CE-FL18C5G*U		10-60	5*16	120	120	6-8	515-535
CE-FL20B5W*U		10-60	6*19	150	120	9-11	445-465
CE-FL20B5G*U		10-60	6*19	150	120	7-9.5	515-535
CE-FL22C4W*U		60-120	6*20	150	120	10-12	445-465








车载后装系列

产品型号	外观	应用电流	尺寸	电极材料	电极间距 GAP	高度	亮度	光效
		(A)	(mil)	Bondingmaterials	(um)	(um)	(mW)	Lm/W
CE-FL39AW*AS-CI		1.0-1.5	39*39	AuSn	160	150	896~928	619.9@750mA
CE-FL42AW*AS-CI		1.0-1.5	42*42	AuSn	160	150	896~928	142.2@2500mA
CE-FL45A55W*AS-CI		1.0-1.7	45*55	AuSn	160	150	928~960	151.3@2000mA
CE-FL51AW*AS-CI		1.0-1.7	51*51	AuSn	160	150	928~960	
CE-FL55AW*AS-CI		1.0-1.7	55*55	AuSn	160	150	992~1024	116.9@3000mA
CE-FL72A60W*AS-CI		1.5-2.5	60*72	AuSn	160	150	1044~1080	543.7@2000mA
CE-FL75AW*AS-CI		2.0-3.0	75*75	AuSn	170	150	1044~1080	108.7@5000mA
CE-FL77AW*AS-CI		2.0-3.0	77*77	AuSn	170	150	1008~1044	538.9@2000mA



车载前装系列

产品型号	外观	应用电流	尺寸	电极材料	电极间距 GAP	高度	亮度	光效
		(A)	(mil)	Bondingmaterials	(um)	(um)	(mW)	Lm/W
CE-FL28AW*AS-CF		0.2-0.7 (烧测 0.7)	28*28	AuSn	148	150	490~505	167.8@200mA
CE-FL35AW*AS-CF		0.3-1.0	35*35	AuSn	150	150	505~520	120.6@350mA
CE-FL40AW*AS-CF		0.8-1.5 (烧测 1.2)	40*40	AuSn	168	150	928~960	142.4@1000mA

产品型号	外观	芯片 结构	应用电流	尺寸	电极	高度	亮度	WD
			(mA)	(mil)	(um)	(um)	(mW)	(nm)
CE-26AW*U		P-UP	100-500	26*26	110	175	350-600	445-460
CE-F30AW*U		N-UP	100-500	30*30	120	175	350-600	445-460
CE-F58AW*U		N-UP	300-1500	58*58	135	200	350-600	445-460



0201 白光系列

产品型号	外观	应用电流	尺寸	显指	光通量	色温	WD
		(mA)	(mm)	(CRI)	(lm)	(TC/K)	(nm)
CE-SS2010W-MFL		1-20	0.57*0.28*0.38	70	1.2-1.8	5000-15000	457-466

CECL

中能芯光

以心交“芯”，筑实可“性”

昆山迅雷光电子有限公司

电话：0512-5032 9881

网址：www.cecl1688.com