
per-phase device time - mnist (float, train)
ms per epoch
100000
75000
50000
25000
0
wall / epoch
gemm
act
delta
biasgrad
update
loss
h2d
d2h
other
cudamn/clang-22/rocblas @ RX 7900 XTX b=64 ()
cudamn/clang-22/rocblas @ RX 7900 XTX b=256 ()
cudamn/clang-22/rocblas @ RX 7900 XTX b=1024 ()
ompmn/clang-18/openblas @ TR 2950X b=64 ()
ompmn/clang-18/openblas @ TR 2950X b=256 ()
ompmn/clang-18/openblas @ TR 2950X b=1024 ()
ompmn/clang-22/openblas @ TR 2950X b=64 ()
ompmn/clang-22/openblas @ TR 2950X b=256 ()
ompmn/clang-22/openblas @ TR 2950X b=1024 ()
ompmn/clang-22/rocblas @ RX 7900 XTX b=64 ()
ompmn/clang-22/rocblas @ RX 7900 XTX b=256 ()
ompmn/clang-22/rocblas @ RX 7900 XTX b=1024 ()
ompmn/gcc-14/mkl @ TR 2950X b=64 ()
ompmn/gcc-14/mkl @ TR 2950X b=256 ()
ompmn/gcc-14/mkl @ TR 2950X b=1024 ()
ompmn/gcc-14/openblas @ TR 2950X b=64 ()
ompmn/gcc-14/openblas @ TR 2950X b=256 ()
ompmn/gcc-14/openblas @ TR 2950X b=1024 ()
ompmn/gcc-14/rocblas @ RX 7900 XTX b=64 ()
ompmn/gcc-14/rocblas @ RX 7900 XTX b=256 ()
ompmn/gcc-14/rocblas @ RX 7900 XTX b=1024 ()
sycl/mi/acpp/auto @ AdaptiveCpp OpenMP host device b=64 ()
sycl/mi/acpp/auto @ AdaptiveCpp OpenMP host device b=256 ()
sycl/mi/acpp/auto @ AdaptiveCpp OpenMP host device b=1024 ()
sycl/mi/acpp/auto @ RX 7900 XTX b=64 ()
sycl/mi/acpp/auto @ RX 7900 XTX b=256 ()
sycl/mi/acpp/auto @ RX 7900 XTX b=1024 ()
sycl/mi/clang-22/auto @ TR 2950X b=64 ()
sycl/mi/clang-22/auto @ TR 2950X b=256 ()
sycl/mi/clang-22/auto @ TR 2950X b=1024 ()
sycl/mi/clang-22/generic @ TR 2950X b=64 ("tiles": "generic")
sycl/mi/clang-22/generic @ TR 2950X b=256 ("tiles": "generic")
sycl/mi/clang-22/generic @ TR 2950X b=1024 ("tiles": "generic")
sycl/mi/clang-22/nvptx @ TR 2950X b=64 ("tiles": "nvptx")
sycl/mi/clang-22/nvptx @ TR 2950X b=256 ("tiles": "nvptx")
sycl/mi/clang-22/nvptx @ TR 2950X b=1024 ("tiles": "nvptx")
sycl/mi/clang-22/rocblb @ TR 2950X b=64 ("tiles": "rocblb")
sycl/mi/clang-22/rocblb @ TR 2950X b=256 ("tiles": "rocblb")
sycl/mi/clang-22/rocblb @ TR 2950X b=1024 ("tiles": "rocblb")