

# Hands-on Lab : MySQL User Management, Access Control, and Encryption

**Estimated time needed:** 25 minutes

In this lab, first you will learn how to manage MySQL user accounts and roles using phpMyAdmin graphical user interface (GUI) tool. Then you will learn how to control access to MySQL databases and their objects. Finally you will learn how to secure your data adding extra layer of security using data encryption.

## Objectives

After completing this lab, you will be able to use the phpMyAdmin to:

- Manage MySQL user accounts and roles
- Control access to MySQL databases and their objects
- Add last line of defense to secure data using encryption

## Software Used in this Lab

In this lab, you will use [MySQL](#). MySQL is a Relational Database Management System (RDBMS) designed to efficiently store, manipulate, and retrieve data.




To complete this lab you will utilize the MySQL relational database service available as part of the IBM Skills Network Labs (SN Labs) Cloud IDE. SN Labs is a virtual lab environment used in this course.

## Database Used in this Lab

The World database used in this lab comes from the following source: <https://dev.mysql.com/doc/world-setup/en/> under [CC BY 4.0 License](#) with [Copyright 2021 - Statistics Finland](#).

You will use a modified version of the database for the lab, so to follow the lab instructions successfully please use the database provided with the lab, rather than the database from the original source.

The following ERD diagram shows the schema of the World database:



The first row is the table name, the second is the primary key, and the remaining items are any additional attributes.


## Exercise 1: Manage MySQL user accounts and roles

In this example exercise, you will go through an example on how to manage MySQL user accounts and roles using phpMyAdmin.


User management is the process of controlling which users are allowed to connect to the MySQL server and what permissions they have on each database. phpMyAdmin does not handle user management, rather it passes the username and password on to MySQL, which then determines whether

a user is permitted to perform a particular action. Within phpMyAdmin, administrators have full control over creating users, viewing and editing privileges for existing users, and removing users.

1. Go to **Skills Network Toolbox** by clicking the following icon from the side by side launched Cloud IDE.
2. From the **Databases** drop-down menu, click **MySQL** to open the MySQL service session tab.
3. Click the *\*Create* button and wait until MySQL service session gets launched.



The MySQL server will take a few moments to start. Once it is ready, you will see the green “Active” label near the top of the window.

 MySQL X

# MySQL

ACTIVE

8.0.22 | 5.0.4 | 2.0.2

Connect to MySQL and phpMyAdmin directly in your Skills Network Labs environment.

CreateDelete

Summary **Connection Information** 4 details

MYSQL\_USERNAME:


root

MYSQL\_HOST:

172.21.34.238

MYSQL\_PORT:

3306



MySQL X

MySQL CLI Command:

MYSQL\_COMMAND:

MYSQL\_PASSWORD:

MYSQL\_TITLE:

MYSQL\_ID:

**NOTE:** Whenever you are required to enter your MySQL service session password from the MySQL service session tab at any step of the lab, copy the password by clicking on the small copy button on the right of the password block. Paste the password into the terminal using **Ctrl + V** (Mac: **⌘ + V**), and press **Enter** on the keyboard. For security reasons, you will not see the password as it is entered on the terminal.

3. Click **phpMyAdmin** button from the mysql service session tab. You will see the phpMyAdmin GUI tool.

The screenshot displays the phpMyAdmin web interface. The browser's address bar shows the URL: `sandipsahajo-8080.theiadocker-27.proxy.cognitiveclass.ai`. The interface is organized into a sidebar on the left and a main content area on the right. The sidebar contains a 'Recent' and 'Favorites' section, followed by a 'New' button and a tree view of databases: `information_schema`, `mysql`, `performance_schema`, `sakila`, and `sys`. The main content area is divided into three sections: 'General settings', 'Appearance settings', and 'Database server'. The 'General settings' section shows the 'Server connection collation' set to `utf8mb4_unicode_ci`. The 'Appearance settings' section shows the 'Language' set to 'English' and the 'Theme' set to 'pmahomme'. The 'Database server' section provides information about the server: 'Server: mysql via TCP/IP', 'Server type: MySQL', 'Server connection: SSL is not being used', 'Server version: 8.0.22 - MySQL Community Server - GPL', 'Protocol version: 10', 'User: root@172.18.0.2', and 'Server charset: UTF-8 Unicode (utf8mb4)'. Below this, the 'Web server' section shows: 'Apache/2.4.38 (Debian)', 'Database client version: libmysql - mysqlnd 7.4.15', 'PHP extension: mysqli, curl, mbstring', and 'PHP version: 7.4.15'. At the bottom, the 'phpMyAdmin' section shows version information (5.0.4, latest stable version: 5.1.0) and links to 'Documentation', 'Official Homepage', 'Contribute', 'Get support', 'List of changes', and 'License'.

4. In the tree-view, click **New** to create a new empty database. Then enter **world** as the name of the database and click **Create**.

Lab IBMCloud Launch Application

File Edit Selection View Go Run Terminal Help

MySQL phpMyAdmin x

https://sandipsahajo-8080.theiadocker-1-labs-prod-theiak8s-3-tor01.proxy.cognitiveclass.ai/

phpMyAdmin

Recent Favorites

New

information\_schema

mysql

performance\_schema

sys

Server: mysql:3306

Databases SQL Status User accounts Export Import Settings More

## Databases

Create database

world utf8mb4\_0900\_ai\_ci Create

Database	Collation	Master replication	Action
<input type="checkbox"/> information_schema	utf8_general_ci	✓ Replicated	<a href="#">Check privileges</a>
<input type="checkbox"/> mysql	utf8mb4_0900_ai_ci	✓ Replicated	<a href="#">Check privileges</a>
<input type="checkbox"/> performance_schema	utf8mb4_0900_ai_ci	✓ Replicated	<a href="#">Check privileges</a>
<input type="checkbox"/> sys	utf8mb4_0900_ai_ci	✓ Replicated	<a href="#">Check privileges</a>

Total: 4

☐ Check all With selected: [Drop](#)

Note: Enabling the database statistics here might cause heavy traffic between the web server and the MySQL server.


- [Enable statistics](#)

5. Go to the **Import** tab. Upload the following sql script file using the **Choose File** button (first download the following sql script file to your local computer storage). Then click **Go** button at the bottom. You will be notified when the import successfully gets finished. Click the **Home** icon.

- [world\\_mysql\\_script\\_full.sql](#)

The screenshot shows the phpMyAdmin web interface. The browser address bar displays the URL: `https://sandipsahajo-8080.theiadocker-1-labs-prod-theiak8s-3-tor01.proxy.cognitiveclass.ai/`. The interface includes a top navigation bar with tabs for 'Lab', 'IBMCLOUD', and 'Launch Application'. Below this is a menu bar with 'File', 'Edit', 'Selection', 'View', 'Go', 'Run', 'Terminal', and 'Help'. The left sidebar contains a tree view of databases: 'New', 'information\_schema', 'mysql', 'performance\_schema', and 'sys'. The main content area is titled 'Server: mysql:3306' and features a tabbed interface with 'Databases', 'SQL', 'Status', 'User accounts', 'Export', 'Import', 'Settings', and 'More'. The 'Import' tab is active, showing the 'File to import:' section. This section includes a 'Choose File' button (highlighted with a red box), a text input for 'Character set of the file' (set to 'utf-8'), and a 'Partial import:' section with a checked checkbox for 'Allow the interruption of an import...'. Below this is the 'Other options:' section with a checked checkbox for 'Enable foreign key checks'. The 'Format:' section shows a dropdown menu set to 'SQL'. The 'Format-specific options:' section includes a dropdown for 'SQL compatibility mode' (set to 'NONE') and a checked checkbox for 'Do not use AUTO\_INCREMENT for zero values'. At the bottom right, a 'Go' button is highlighted with a red box. The bottom status bar shows a 'Console' tab.





6. Now you will create a user account with custom role “db\_owner”. Usually a user with db\_owner role has all global privileges and access to all existing databases. Go to the **User accounts** tab and click **Add user account**.

Lab IBMCloud Launch Application

File Edit Selection View Go Run Terminal Help

MySQL phpMyAdmin x

https://sandipsahajo-8080.theiadocker-1-labs-prod-theiak8s-3-tor01.proxy.cognitiveclass.ai/

Server: mysql:3306

Databases SQL Status **User accounts** Export Import Settings More

### User accounts overview

	User name	Host name	Password	Global privileges	Grant	Action
<input type="checkbox"/>	mysql.infoschema	localhost	Yes	SELECT	No	<a href="#">Edit privileges</a> <a href="#">Export</a>
<input type="checkbox"/>	mysql.session	localhost	Yes	SHUTDOWN, SUPER	No	<a href="#">Edit privileges</a> <a href="#">Export</a>
<input type="checkbox"/>	mysql.sys	localhost	Yes	USAGE	No	<a href="#">Edit privileges</a> <a href="#">Export</a>
<input type="checkbox"/>	root	%	Yes	ALL PRIVILEGES	Yes	<a href="#">Edit privileges</a> <a href="#">Export</a>
<input type="checkbox"/>	root	localhost	Yes	ALL PRIVILEGES	Yes	<a href="#">Edit privileges</a> <a href="#">Export</a>

☐ Check all With selected: [Export](#)

**New**

[Add user account](#)

[Remove selected user accounts](#)

(Revoke all active privileges from the users and delete them afterwards.)

☐ Drop the databases that have the same names as the users.

[Go](#)

**Note:** phpMyAdmin gets the users' privileges directly from MySQL's privilege tables. The content of these tables may differ from the privileges the server uses, if they have been changed manually. In this case, you should [reload the privileges](#) before you continue.

7. Fill the **Login Information** as shown in following image (enter your own password). Under **Global privileges**, click **Check all**. Scroll down and click **Go**.

Lab IBMCloud Launch Application

File Edit Selection View Go Run Terminal Help

MySQL phpMyAdmin x

https://sandipsahajo-8080.theiadocker-1-labs-prod-theiak8s-3-tor01.proxy.cognitiveclass.ai/

# phpMyAdmin

Recent Favorites

- New
  - information\_schema
  - mysql
  - performance\_schema
  - sys
  - world
    - New
      - city
      - country
      - countrylanguage

## Add user account

### Login Information

User name: Use text field: db\_owner

Host name: Local localhost

Password: Use text field: ..... Strength: Extremely weak

Re-type: .....

Authentication Plugin: Caching sha2 authentication

Generate password: Generate

### Database for user account

☐ Create database with same name and grant all privileges.

☐ Grant all privileges on wildcard name (username\\_%).

### Global privileges ☐ Check all

Note: MySQL privilege names are expressed in English.

<input type="checkbox"/> Data	<input type="checkbox"/> Structure	<input type="checkbox"/> Administration
<input type="checkbox"/> SELECT	<input type="checkbox"/> CREATE	<input type="checkbox"/> GRANT
<input type="checkbox"/> INSERT	<input type="checkbox"/> ALTER	<input type="checkbox"/> SUPER

Console

Lab IBMCloud Launch Application

File Edit Selection View Go Run Terminal Help

MySQL phpMyAdmin x

https://sandipsahajo-8080.theiadocker-1-labs-prod-theiak8s-3-tor01.proxy.cognitiveclass.ai/

Server: mysql:3306

Databases SQL Status User accounts Export Import Settings More

### Global privileges ☒ Check all

Note: MySQL privilege names are expressed in English.

<input checked="" type="checkbox"/> Data	<input checked="" type="checkbox"/> Structure	<input checked="" type="checkbox"/> Administration
<input checked="" type="checkbox"/> SELECT	<input checked="" type="checkbox"/> CREATE	<input checked="" type="checkbox"/> GRANT
<input checked="" type="checkbox"/> INSERT	<input checked="" type="checkbox"/> ALTER	<input checked="" type="checkbox"/> SUPER
<input checked="" type="checkbox"/> UPDATE	<input checked="" type="checkbox"/> INDEX	<input checked="" type="checkbox"/> PROCESS
<input checked="" type="checkbox"/> DELETE	<input checked="" type="checkbox"/> DROP	<input checked="" type="checkbox"/> RELOAD
<input checked="" type="checkbox"/> FILE	<input checked="" type="checkbox"/> CREATE TEMPORARY TABLES	<input checked="" type="checkbox"/> SHUTDOWN
	<input checked="" type="checkbox"/> SHOW VIEW	<input checked="" type="checkbox"/> SHOW DATABASES
	<input checked="" type="checkbox"/> CREATE ROUTINE	<input checked="" type="checkbox"/> LOCK TABLES
	<input checked="" type="checkbox"/> ALTER ROUTINE	<input checked="" type="checkbox"/> REFERENCES
	<input checked="" type="checkbox"/> EXECUTE	<input checked="" type="checkbox"/> REPLICATION CLIENT
	<input checked="" type="checkbox"/> CREATE VIEW	<input checked="" type="checkbox"/> REPLICATION SLAVE
	<input checked="" type="checkbox"/> EVENT	<input checked="" type="checkbox"/> CREATE USER
	<input checked="" type="checkbox"/> TRIGGER	

### Resource limits

Note: Setting these options to 0 (zero) removes the limit.

MAX QUERIES PER HOUR	0
MAX UPDATES PER HOUR	0
MAX CONNECTIONS PER HOUR	0
MAX USER_CONNECTIONS	0

Console

8. You have successfully created a user account with appropriate privileges.

The screenshot shows the phpMyAdmin interface for a MySQL server (mysql:3306). The 'User accounts overview' page displays a table of users. The 'db\_owner' user is highlighted with a red box. The table has columns: User name, Host name, Password, Global privileges, Grant, and Action. The 'db\_owner' user has 'ALL PRIVILEGES' and 'Grant' is 'Yes'. The 'root' user also has 'ALL PRIVILEGES' and 'Grant' is 'Yes'.

User name	Host name	Password	Global privileges	Grant	Action
<input type="checkbox"/> db_owner	localhost	Yes	ALL PRIVILEGES	Yes	<a href="#">Edit privileges</a> <a href="#">Export</a>
<input type="checkbox"/> mysql.infoschema	localhost	Yes	SELECT	No	<a href="#">Edit privileges</a> <a href="#">Export</a>
<input type="checkbox"/> mysql.session	localhost	Yes	SHUTDOWN, SUPER	No	<a href="#">Edit privileges</a> <a href="#">Export</a>
<input type="checkbox"/> mysql.sys	localhost	Yes	USAGE	No	<a href="#">Edit privileges</a> <a href="#">Export</a>
<input type="checkbox"/> root	%	Yes	ALL PRIVILEGES	Yes	<a href="#">Edit privileges</a> <a href="#">Export</a>
<input type="checkbox"/> root	localhost	Yes	ALL PRIVILEGES	Yes	<a href="#">Edit privileges</a> <a href="#">Export</a>

Below the table, there is a 'Check all' checkbox and a 'With selected: Export' button. At the bottom, there is a 'New' button and a link to 'Add user account'.

## Exercise 2: Control access to MySQL databases and their objects

In this example exercise, you will learn how to control access to MySQL databases and their objects.

Making an exception to the user definition of db\_owner role you created earlier, you will modify privileges of this user so that this user won't be able to update other columns except a specific column of a specific table of a specific database. You will restrict db\_owner from updating all the other columns except the column **Population** of the table **city** of the database **world**.

1. Go to **Home > User accounts** tab. Click **Edit privileges** option of **db\_owner** user name.

The screenshot shows the phpMyAdmin interface for a MySQL server (mysql:3306). The left sidebar displays a tree view of databases, including 'world' with its sub-databases 'city', 'country', and 'countrylanguage'. The main panel shows the 'User accounts overview' page with a table of users. The 'db\_owner' user is highlighted with a red box. Below the table, there are options to 'Check all' and 'Export' for the selected users. A 'New' button and 'Add user account' link are also visible.


	User name	Host name	Password	Global privileges	Grant	Action
<input checked="" type="checkbox"/>	db_owner	localhost	Yes	ALL PRIVILEGES	Yes	<a href="#">Edit privileges</a> <a href="#">Export</a>
<input type="checkbox"/>	mysql.infoschema	localhost	Yes	SELECT	No	<a href="#">Edit privileges</a> <a href="#">Export</a>
<input type="checkbox"/>	mysql.session	localhost	Yes	SHUTDOWN, SUPER	No	<a href="#">Edit privileges</a> <a href="#">Export</a>
<input type="checkbox"/>	mysql.sys	localhost	Yes	USAGE	No	<a href="#">Edit privileges</a> <a href="#">Export</a>
<input type="checkbox"/>	root	%	Yes	ALL PRIVILEGES	Yes	<a href="#">Edit privileges</a> <a href="#">Export</a>
<input type="checkbox"/>	root	localhost	Yes	ALL PRIVILEGES	Yes	<a href="#">Edit privileges</a> <a href="#">Export</a>

☐ Check all    With selected: [Export](#)

[New](#)

[Add user account](#)

2. Under **Database** sub-tab, select **world** database and click **Go**.



3. Under **Database-specific privileges**, select **Check all** and click **Go** at the bottom.



Lab IBMCloud Launch Application

File Edit Selection View Go Run Terminal Help

MySQL phpMyAdmin x

https://sandipsahajo-8080.theiadocker-1-labs-prod-theiak8s-3-tor01.proxy.cognitiveclass.ai/

Server: mysql:3306

Databases SQL Status User accounts Export Import Settings More

Database Table Routine

## Edit privileges: User account

### 'db\_owner'@'localhost' - Database world

Database-specific privileges ☒ Check all

Note: MySQL privilege names are expressed in English.

<input checked="" type="checkbox"/> Data	<input checked="" type="checkbox"/> Structure	<input checked="" type="checkbox"/> Administration
<input checked="" type="checkbox"/> SELECT	<input checked="" type="checkbox"/> CREATE	<input checked="" type="checkbox"/> GRANT
<input checked="" type="checkbox"/> INSERT	<input checked="" type="checkbox"/> ALTER	<input checked="" type="checkbox"/> LOCK TABLES
<input checked="" type="checkbox"/> UPDATE	<input checked="" type="checkbox"/> INDEX	<input checked="" type="checkbox"/> REFERENCES
<input checked="" type="checkbox"/> DELETE	<input checked="" type="checkbox"/> DROP	
	<input checked="" type="checkbox"/> CREATE TEMPORARY TABLES	
	<input checked="" type="checkbox"/> SHOW VIEW	
	<input checked="" type="checkbox"/> CREATE ROUTINE	
	<input checked="" type="checkbox"/> ALTER ROUTINE	
	<input checked="" type="checkbox"/> EXECUTE	
	<input checked="" type="checkbox"/> CREATE VIEW	
	<input checked="" type="checkbox"/> EVENT	
	<input checked="" type="checkbox"/> TRIGGER	


Go

[ Database world: Structure ]

Recent Favorites

- New
- information\_schema
- mysql
- performance\_schema
- sys
- world
  - New
  - city
  - country
  - countrylanguage

4. Switch to **Table** sub-tab. Select the table **city** from the drop-down menu and click **Go**.



5. Under **Table-specific privileges**, configure all the SQL commands and their custom access to the columns of the table **city** as shown below. Then click **Go**. Such table-specific privilege configuration will restrict db\_owner from updating all the other columns except the column **Population** of the table **city** of the database **world**.

**Table**

## Edit privileges: User account '*db\_owner*'@'*localhost*' - Database *world* - Table *city*

**Table-specific privileges**

*Note: MySQL privilege names are expressed in English.*

SELECT	INSERT	UPDATE	REFERENCES	<input checked="" type="checkbox"/> DELETE
<input type="checkbox"/> ID <input type="checkbox"/> Name <input type="checkbox"/> CountryCode <input type="checkbox"/> District <input type="checkbox"/> Population	<input type="checkbox"/> ID <input type="checkbox"/> Name <input type="checkbox"/> CountryCode <input type="checkbox"/> District <input type="checkbox"/> Population	<input type="checkbox"/> ID <input type="checkbox"/> Name <input type="checkbox"/> CountryCode <input type="checkbox"/> District <input checked="" type="checkbox"/> Population	<input type="checkbox"/> ID <input type="checkbox"/> Name <input type="checkbox"/> CountryCode <input type="checkbox"/> District <input type="checkbox"/> Population	<input checked="" type="checkbox"/> CREATE <input checked="" type="checkbox"/> DROP <input checked="" type="checkbox"/> GRANT <input checked="" type="checkbox"/> INDEX <input checked="" type="checkbox"/> ALTER
Or <input type="checkbox"/> None	Or <input type="checkbox"/> None	Or <input type="checkbox"/> None	Or <input type="checkbox"/> None	<input checked="" type="checkbox"/> CREATE_VIEW <input checked="" type="checkbox"/> SHOW_VIEW <input checked="" type="checkbox"/> TRIGGER

**Go**


[ Database [world](#): Structure ] [ Table [city](#): Browse ]

## Exercise 3: Secure data using encryption

In this example exercise, you will learn how to secure your data adding extra layer of security using data encryption. There may be certain parts of your database containing sensitive information which *should not* be stored in plain text. This is where encryption comes in.

You will implement encryption and decryption of a column in the world database using the official AES (Advanced Encryption Standard) algorithm. AES is a symmetric encryption where the same key is used to encrypt and decrypt the data. The AES standard permits various key lengths. By default, key length of 128-bits is used. Key lengths of 196 or 256 bits can be used. The key length is a trade off between performance and security. Let's get started.

1. Click the **MySQL CLI** button from the mysql service session tab.

 MySQL X

# MySQL

ACTIVE

8.0.22 | 5.0.4 | 2.0.2


Connect to MySQL and phpMyAdmin directly in your Skills Network Labs environment.

CreateDelete

SummaryConnection InformationDetails

Your database and phpMyAdmin server are now ready to use and available with the following login credentials. For more details on how to navigate MySQL, please check out the Details section.

You can manage MySQL via:

phpMyAdmin

Or to interact with the database in the terminal, select one of these options:

MySQL CLI

New Terminal

2. First, you will need to hash your passphrase (consider your passphrase is **My secret passphrase**) with a specific hash length (consider your hash length is **512**) using a hash function (here you will use hash function from **SHA-2** family). It is good practice to hash the passphrase you use, since storing the passphrase in plaintext is a significant security vulnerability. Use the following command in the terminal to use the SHA2 algorithm to hash your passphrase and assign it to the variable `key_str`:

```
1. 1
1. SET @key_str = SHA2('My secret passphrase', 512);
```

Copied!

3. Now, let's take a look at the `world` database. First, you will want to connect to the database by entering the following command in the CLI:

```
1. 1
1. USE world;
```

Copied!

4. Next, let's take a quick look at the `countrylanguage` table in our database with the following command:

```
1. 1
1. SELECT * FROM countrylanguage LIMIT 5;
```

Copied!

```
theia@theiadocker-davidpaster2: /home/project ×

Database changed
mysql> SELECT * FROM countrylanguage LIMIT 5;
+-----+-----+-----+-----+
| CountryCode | Language | IsOfficial | Percentage |
+-----+-----+-----+-----+
| ABW        | Dutch   | T          | 5.3        |
| ABW        | English | F          | 9.5        |
| ABW        | Papiamentto | F      | 76.7       |
| ABW        | Spanish | F          | 7.4        |
| AFG        | Balochi | F          | 0.9        |
+-----+-----+-----+-----+
5 rows in set (0.00 sec)

mysql> 
```

For *demonstration purposes*, **suppose** that the last column in the table, labeled *Percentage* contains sensitive data, such as a citizen's passport number. Storing such sensitive data in plain text is an enormous security concern, so let's go ahead and encrypt that column.

5. To encrypt the *Percentage* column, we will first want to convert the data in the column into binary byte strings of length 255 by entering the following command into the CLI:

1. 1

1. ALTER TABLE countrylanguage MODIFY COLUMN Percentage varbinary(255);

Copied!

6. Now to actually encrypt the *Percentage* column, we use the AES encryption standard and our hashed passphrase to execute the following command:

1. 1

1. UPDATE countrylanguage SET Percentage = AES\_ENCRYPT(Percentage, @key\_str);

Copied!

7. Let's go ahead and see if the column was successfully encrypted by taking another look at the *countrylanguage* table. We again run the same command as in step 4:

1. 1

1. SELECT \* FROM countrylanguage LIMIT 5;

Copied!

```
theia@theiadocker-davidpaster2: /home/project x

mysql> SELECT * FROM countrylanguage LIMIT 5;
+-----+-----+-----+-----+
| CountryCode | Language | IsOfficial | Percentage |
+-----+-----+-----+-----+
| ABW        | Dutch   | T          | d0L0D00e0!0h~ |
| ABW        | English | F          | 0rG0000000(0R0KK |
| ABW        | Papiamentto | F        | 100Ä0;00 ðz0m |
| ABW        | Spanish | F          | K0000A0 o00 |
| AFG        | Balochi | F          | 00'0hB0zI0Hr |
+-----+-----+-----+-----+
5 rows in set (0.00 sec)

mysql> 
```


As you can see, the data on the *Percentage* column is encrypted and completely illegible.

8. The supposedly sensitive data is now encrypted and secured from prying eyes. However, we should still have a way to access the encrypted data when needed. To do this, we use the AES\_DECRYPT command, and since AES is symmetric, we use the same key for both encryption and decryption. In our case, recall that the key was a passphrase which was hashed and stored in the variable `key_str`. Suppose we need to access the sensitive data in that column. We can do so by entering the following command in the CLI:

1. 1

1. SELECT cast(AES\_DECRYPT(Percentage, @key\_str) as char(255)) FROM countrylanguage;

Copied!



```
theia@theiadocker-davidpaster2: /home/project x
5 rows in set (0.01 sec)

mysql> SELECT cast(AES_DECRYPT(Percentage, @key_str) as char(255)) FROM countrylanguage LIMIT 5;
+-----+
| cast(AES_DECRYPT(Percentage, @key_str) as char(255)) |
+-----+
| 5.3 |
| 9.5 |
| 76.7 |
| 7.4 |
| 0.9 |
+-----+
5 rows in set (0.00 sec)
```

## Practice Exercise: Control access to MySQL databases and their objects

In this practice exercise, you will get to put what you learned to use and modify privileges for a user.

*Scenario: You will modify privileges of the user **db\_owner** you created in example exercise A such a way that this user won't be able to insert, update and delete any column of a specific table **country** of the **world** database.*

- ▶ [Hint \(Click Here\)](#)
- ▶ [Solution \(Click Here\)](#)

## Summary

In this lab, first learned how to manage MySQL user accounts and roles using phpMyAdmin graphical user interface (GUI) tool. You also learned how to control access to MySQL databases and their objects. Finally, you learned how to secure your data adding extra layer of security using data encryption.

**Congratulations! You have completed this lab, and you are ready for the next topic.**

## **Author(s)**

- [Sandip Saha Joy](#)

## **Other Contributor(s)**

- [David Pasternak](#)

© IBM Corporation 2023. All rights reserved.