Cassandra Table Operations



Estimated time needed: 10 minutes

Objectives

After completing this lab you will be able to:

- Create a table in a keyspace by defining a column name and data type
- Extract the details of a table with the DESCRIBE command
- Alter a table by adding columns
- Drop a table by removing it from the keyspace

About This SN Labs Cloud IDE

This Skills Network Labs Cloud IDE provides a hands-on environment for course and project related labs. It utilizes Theia, an open-source IDE (Integrated Development Environment) platform, that can be run on desktop or on the cloud. To complete this lab, we will be using the Cloud IDE based on Theia and Skills Network-provided Cassandra.

Important Notice about this lab environment

Please be aware that sessions for this lab environment are not persisted. Every time you connect to this lab, a new environment is created for you. Any data you may have saved in the earlier session would get lost. Plan to complete these labs in a single session, to avoid losing your data.

Exercise 1 - Getting the environment ready

Open the Cassandra database page by clicking the button below:

Open Cassandra Page in IDE

about:blank 1/7

On that page, click the Create button to create a Cassandra database.

After creation has finished, click the Cassandra CLI button (below the Create button from the previous step) to connect to the database using the cqlsh CLI.

1. Problem:

Create a keyspace named training using SimpleStrategy and replication factor of 3.

- ► Click here for Hint
- **▼** Click here for Solution

On the cqlsh run the below command.

```
1. 1
2. 2

1. CREATE KEYSPACE training
2. WITH replication = {'class':'SimpleStrategy', 'replication_factor' : 3};
```

Copied!

Exercise 2 - Create a table

The below command creates a table named **movies**, in the **training** keyspace.

The **movies** table has three columns:

- 'movie id' is an integer and is the primary key.
- 'movie_name' is a text column.
- 'year_of_release' is an integer.

On the cassandra client run the below command.

- 1. 1 2. 2
- 3. 3
- 4. 4
- 5. 5
- 6.6
- use training;
- CREATE TABLE movies(
- movie_id int PRIMARY KEY,
- movie_name text,

about:blank 2/7

5. year_of_release int
6.);

Copied!

Verify that the table got created by listing all tables.

- 1. 1
- describe tables;

Copied!

Exercise 3 - Describe a table

In the previous exercise you created a table named **movies**. Let us print more details of it using the describe command.

Describe the table.

- 1. 1
- 1. describe movies

Copied!

Exercise 4 - Alter a table

In a previous exercise you created a table named **movies**. Let us modify it by adding a column named 'genre' which is of type 'text'.

Alter the table.

- 1. 1
- 2. 2
- 1. ALTER TABLE movies
- 2. ADD genre text;

Copied!

Verify the changes using the below command

about:blank 3/7

- 1. 1
- describe movies;

Copied!

Exercise 5 - Drop a table

To drop the **movies** table run the below command.

- 1. 1
- drop table movies;

Copied!

Verify using the below command. You should get an error.

- 1. 1
- describe movies;

Copied!

Practice exercises

1. Problem:

Create a table named **books** with 3 columns; 'book_id' which is the primary key and of integer type, 'author' which is of type text and 'title' which is of type text.

- ► Click here for Hint
- **▼** Click here for Solution

On the cqlsh run the below command.

- 1. 1
- 2. 2
- 3. 3
- 4. 4
- 5.5

about:blank 4/7

- 1. CREATE TABLE books (
- book_id int PRIMARY KEY,
- 3. author text,
- 4. title text
- 5.);

Copied!

2. Problem:

Add a column 'date of publication' which is of date type.

- ► Click here for Hint
- **▼** Click here for Solution

On the cqlsh run the below command.

- 1. 1
- 2. 2
- 1. ALTER TABLE books
- add date_of_publication date;

Copied!

3. Problem:

Add a 'column' price which is of type decimal.

- ► Click here for Hint
- **▼** Click here for Solution

On the cqlsh run the below command.

- 1. 1
- 2. 2
- 1. ALTER TABLE books
- add price decimal;

Copied!

4. Problem:

Drop the 'column' price from the books table.

- ► Click here for Hint
- **▼** Click here for Solution

On the cqlsh run the below command.

- 1. 1
- 2. 2
- 1. ALTER TABLE books
- drop price;

Copied!

5. Problem:

Drop the **books** table.

- ► Click here for Hint
- **▼** Click here for Solution

On the cqlsh run the below command.

- 1. 1
- 1. DROP TABLE books;

Copied!

6. Problem:

Drop the **training** keyspace.

- ► Click here for Hint
- **▼** Click here for Solution

On the cqlsh run the below command.

- 1. 1
- drop keyspace training;

Copied!

7. Problem:

Disconnect from the cassandra server.

- ► Click here for Hint
- **▼** Click here for Solution

Run the below command on the terminal.

- 1. 1
- 1. exit

Copied!

Authors

Ramesh Sannareddy

Other Contributors

Rav Ahuja

© IBM Corporation. All rights reserved.

about:blank 7/7