

Outline

- Getting Data Into R
- Text files
 - Comma Separated Values (CSV) files
 - Other delimited TXT files
- Excel files
- Databases
 - SQLite, MySQL, ...
- Web Data
 - HTML tables
 - JSON files



Importing Data Into R

- Other Statistical Programs
 - SAS, SPSS, Minitab, ...
- R Binary (RData) files
- R Sample Data

CSV Files - read.csv Function



- Open the already created project
 - Project: Data_Extract.Rproj
 - Folder: IDSC_4110_Files/03_Data_Extract/Lectures
 - File: Extract1_Import_CSV.r
- Reading Loans CSV file
 - Use <code>getwd()</code> function to get current working directory
 - Add the forward slash ("/") and the file name
 - Note the use of forward instead of back slashes in Windows paths
 - Use ${\tt read.csv}$ function to read content into data frame for further analysis

CSV Files - read.table Function



- The all-purpose function for reading text files
 - read.table from which others are derived
 - The most useful (and necessary) paramters
 - file path and file name to be read (required)
 - header TRUE for first row of headers, FALSE by default
 - sep "" by default, comma for CSV files, could be tab, semicolon, ...
 - stringsAsFactors when set to TRUE all character columns read as factors, could slow down big files with lots of different char levels
 - quote used to deal with single and double quotes as string delimiters
 - \bullet colClasses for specifying data types of each column

CSV Files – Other Reading Functions



- Other functions derived from read.table
- -read.delim with tab \t as default separator
- -read.csv2 and read.delim2
 - For data with comma for decimals like 123,45 euros or yen
- · Large files should be read with
 - read csv or other functions from readr package
 - \bullet Used towards the end of the class with ${\tt dplyr}\,$ package

Excel Files - readxl Package



- · Preferred to export into CSV files
- Possible to read directly using readx1 package
 - Accommodates both .xls and .xlsx extensions
 - Can specify the worksheet you want to read from
- · Read Investments Excel file
 - Install and load readx1 package
 - Create the appropriate path and file name
 - Use read_excel function to read content of the second sheet into a tibble data frame for further analysis

Databases - Install SQLite



· Download and install SQLite

https://github.com/pawelsalawa/sqlitestudio/releases

- Download the InstallSQLiteStudio EXE file (Windows) or DMG file (Mac)
- Run the installation following the instructions
- · Additional sites for SQLite and SQLiteStudio
 - _ S∩I ita
 - https://www.sqlitetutorial.net/download-install-sqlite/
 - https://www.sqlite.org/download.html
 - SQLiteStudio
 - https://sqlitestudio.pl/

Databases – Sporting Goods



- Run SQLite Studio
- Database -> Add Database -> New Database File
 - Folder: 03 Data Extract/Lectures/Data Extract
 - File: SportingGoods
- Execute the following commands
 - Connect to SportingGoods database
 - Open SQL editor
 - Load SQL from file
 - Folder: 03_Data_Extract/Lectures/Data_Extract
 - File: SportingGoods.sql
 - $-\operatorname{Run}$ the code with Execute Query button

Databases - Connectivity



- Accessed through various drivers
 - ODBC: Open Database Connectivity
- Specific open-source database connectivity packages
 - RMySQL and RPostgreSQL
- Databases without a specific package
 - Use дві or RODBC packages
- We will use SQLite specific package
 - Install and load RSQLite packageSpecify driver with dbDriver function
 - SQLite_driver <- dbDriver("SQLite")
 - Establish database connection with dbConnect function sports conn <- dbConnect (SQLite driver, db file)
 - Disconnect from the database when done dbDisconnect (sports_conn)

03_Data_Extract IDSC 4110

Databases – Product Query



- List all the tables in the database
- dbListTables(sports_conn)
- List all the fields in the Product table dbListFields(sports_conn, "Product")
- Create a query string to list the product name, product group and retail price

sql_str_prod <- "SELECT ProdName, ProdGroup, RetailPrice
FROM Product"</pre>

 Run the query to retrieve the results into a data frame for further analysis

prod_df <- dbGetQuery(sports_conn, sql_str_prod)</pre>

Databases - Sales View




- Most users have limited access to database data through so-called views or stored queries
- List all the tables in the database again to see the Sales view dbListTables(sports_conn)
- List all the fields in the Sales view just like you would for a table dbListFields (sports_conn, "Sales")
- Create a query string to select everything from the view sql_str_prod <- "SELECT * FROM Sales"
- Run the query to retrieve the results into a data frame for further analysis

sales_df <- dbGetQuery(sports_conn, sql_str_sales)</pre>

Web Data - HTML and DOM

- Web pages written in HTML
- Hypertext Markup Language
 - "Marks up" text in different ways (headers, lists, spans, divs and tables)
 - Mostly interested in HTML tables
- Browser's parser creates a document object model (DOM)
 - DOM is a hierarchical representation of the Web page
 - Tags open and close a portion of DOM tree



03_Data_Extract IDSC 4110

HTML Tables - XML Package



- We want to analyze data from a Web page
 - Data not provided in easy to access format, like .csv files
 - Need to "scrape" the data into R data frames
- Using XML package
 - htmlTreeParse creates R data structure
 htmLInternalDocument representing the HTML tree
 - getNodeSet uses the HTML tree structure to create another R data structure XMLNodeSet which includes nodes among other HTML elements
 - readHTMLTable used to retrieve the data from the node into a R data.frame

HTML Tables – rvest Package



- Using rvest package
 - Conceptually identical to ${\tt XML}$ package procedure
 - read_html creates R data structure $xml_document$ representing the HTML tree
 - html_nodes uses the HTML tree structure to create another R data structure xml_nodeset which includes nodes among other HTML elements
 - html_table used to retrieve the data from the node into R data.frame

Web Data – JSON Files



- JSON = JavaScript Object Notation
 - A text-based data format well suited for complex (nested) list-like data structures
 - $\boldsymbol{-}$ Used to transmit data between a server and Web application
 - An alternative to XML, easier to read and work with
- Using jsonlite package
 - Created JSON files in R using write_json function
 - Reading the files back in using read_json function
 - Compare and contrast reading into lists vs. vector & data frame
 - Need to stay on top of the type of data structure one is working with – it can get pretty messy

Other Statistical Program	tner s	tati	sticai	i Pro	gra	ms
---------------------------	--------	------	--------	-------	-----	----

SPSS

- Proprietary statistical software still has significant market share
 - SPSS, Stata, SAS, ...

stata

S.sas.

- Using foreign package
 - Reading files with read.spss, read.dta, read.ssd, ...
 functions into data frames
- Using haven package
 - Reading files with read_spss, read_stata, read_sas, ... functions into tibbles

R Binary RData Files



- Use save/load pair of functions to create and restore an rdata file
 - load function does not need a data frame name because it is restored from the R workspace with the same name it was created with using save function
- Alternatively use saveRDS/readRDS pair of functions to create and restore an rds file
 - readRDS function needs a data frame name because it is not maintained with saveRDS function

Sample Data in R



- Display a list of pre-loaded R data sets with data ()
- Most (if not all?) of these are data frames
- Type the name of the data frame to see content mtcars
- To learn about the data frame ?mtcars
- Use data() function to actually build the data frame data (mtcars)

03_Data_Extract IDSC 4110

Summary

- Reviewed all the major types of R data sources
- Most of the external data comes from either
 - CSV and Excel files
 - Databases (reviewed basics of SQL)
- Another major source is the data embedded in Web pages
 - HTML tables and other markup features $\,$
 - JSON files for more complex nested lists $\,$
- Other statistical software programs
 - SPSS, Stata, SAS,
- R binary data files and pre-loaded sample data