

TRUEFACE BPS // PRODUCT DOSSIER

Internal System Architecture & Deployment Blueprint

SECTION 1: SYSTEM OVERVIEW

TrueFace BPS (Bypass Protocol System) is engineered to eliminate the high-friction "infinite loops" common in standard biometric validation flows. By addressing both local hardware bottlenecks (Personal License) and server-side UI friction (DevEngine License), TrueFace BPS ensures an immediate, successful verification sequence.

Core Metrics:

Average Verification Latency: < 1.8 seconds.

Target Drop-off Mitigation: Up to 15% reduction in registration abandonment.

Privacy Architecture: Zero-knowledge local data handling (Personal Clients)

SECTION 2: TIER 01 – PERSONAL LICENSE EXTENSION

Documentation & Implementation Guide

1. System Requirements & Prerequisites

Supported Platforms: Chromium-based browsers (Chrome, Edge, Brave), standalone desktop client (Windows/macOS).

Hardware: Standard integrated webcam or external USB camera.

Minimum Resolution: 720p at 30fps.

2. Quick-Start Setup (3-Step Installation)

Step 01: Initialization

Extract the contents of the trueface-personal-v1.zip archive into a dedicated directory on your local machine.

Step 02: Extension Sideloading

Open your browser's Extension Management page

(chrome://extensions)—Toggle "Developer Mode" to ON in the upper right corner. Click "Load unpacked" and select the extracted TrueFace folder.

Step 03: Protocol Activation

Click the TrueFace BPS icon in your browser toolbar. Paste your unique seat license key from your purchase dashboard to initialize the real-time biometric stream optimization engine.

3. Environment Calibration Matrix

To guarantee a sub-two-second bypass on high-traffic validation portals, ensure your local hardware environment matches the following configuration:

Exposure Ratio: Balanced / Ambient Light (Prevents canvas shadow errors)

Frame Locking: Fixed 30 FPS (Eliminates data packet drops)

Aspect Ratio: Strict 4:3 or 16:9 (Matches standard portal crops)

SECTION 3: TIER 02 – DEVENGINE INTEGRATION SCRIPT

Technical API & Deployment Specification

1. Architecture Summary

The trueface-bps-v1.js module acts as a lightweight asynchronous wrapper that hooks into your platform's existing facial verification event handlers. It intercepts low-confidence frame triggers, dynamically normalizes ambient exposure vectors on the client side, and prevents the host UI from throwing an automatic loop error.

2. Global Script Deployment

Paste the following initialization block directly into the <head> element of your application's registration or checkout page, preceding your primary verification vendor script:<!-- Initialize TrueFace BPS Protocol Engine -->

<script src="path/to/trueface-bps-v1.js"></script>

<script>

document.addEventListener("DOMContentLoaded", function() {

**TrueFaceBPS.initialize({
environment: "production",**

```
recoveryMode: true,  
autoCalibrate: true,  
maxAttemptsBeforeBypass: 2  
});  
});  
</script>
```

Core API Reference & Event Hooks

Webmasters can customize the validation workflow by utilizing the native lifecycle hooks exposed by the engine:

TrueFaceBPS.onHook()

Fires when a biometric check is initiated by the user. Used to

trigger the stream optimization layer.

TrueFaceBPS.onFrictionDetected(callback)

Executes if the native system fails to read the face on the first frame. The callback function intercepts the error, adjusts the contrast overlay, and forces an automated re-scan before the user sees a failure message.

TrueFaceBPS.onSuccess()

Logs a successful session activation directly to your internal analytics dashboard, recording

the automated drop-off recovery event.

SECTION 4: DEPLOYMENT CHECKLIST

Before finalizing your digital storefront setup, cross-verify the following asset integrity protocols:

Archive Architecture: Ensure trueface-personal-v1.zip includes both the manifest file and the Readme_First.txt.

Documentation Delivery: Verify the trueface-devengine-docs.pdf

**links directly to your secure API
update endpoint.**