

MATH.APP.790 : Topics in Mathematics, Nonlinear time series analysis

Narayan P. Subramaniam

Tampere University (MET Faculty)

February 2021

Lecture overview

- Recurrence networks.
- Complex network measures.
- Applications.
- Primary References
 - 1 Kantz, Holger, and Thomas Schreiber. Nonlinear time series analysis. Vol. 7. Cambridge university press, 2004.
 - 2 Puthanmadam Subramaniam, Narayan. "Recurrence network analysis of EEG signals: A Geometric Approach." (2016).
 - 3 Recurrence quantification analysis. Theory and best practices.
 - 4 Zou et al. Complex network approaches to nonlinear time series. 2019 analysis.

Time series to complex networks

- Nonlinear time series analysis and complex network theory are two fundamental and important tools to analyze complex systems.

Time series to complex networks

- Nonlinear time series analysis and complex network theory are two fundamental and important tools to analyze complex systems.
- Transforming a time series into a complex network for nonlinear time series analysis has garnered much attention recently.

Time series to complex networks

- Nonlinear time series analysis and complex network theory are two fundamental and important tools to analyze complex systems.
- Transforming a time series into a complex network for nonlinear time series analysis has garnered much attention recently.
- These approaches can be broadly divided into three classes - 1) proximity networks, 2) visibility graphs and 3) transition networks.

Time series to complex networks

- Nonlinear time series analysis and complex network theory are two fundamental and important tools to analyze complex systems.
- Transforming a time series into a complex network for nonlinear time series analysis has garnered much attention recently.
- These approaches can be broadly divided into three classes - 1) proximity networks, 2) visibility graphs and 3) transition networks.
- Such complex networks can be directed or undirected.

Time series to complex networks

- Nonlinear time series analysis and complex network theory are two fundamental and important tools to analyze complex systems.
- Transforming a time series into a complex network for nonlinear time series analysis has garnered much attention recently.
- These approaches can be broadly divided into three classes - 1) proximity networks, 2) visibility graphs and 3) transition networks.
- Such complex networks can be directed or undirected.
- The vertices are represented by state vectors and the edges between the vertices are defined based on some criteria such as mutual closeness or transition probabilities.

Types of time series networks

- Proximity networks are derived based on the mutual closeness between different state vectors in the state space.

Types of time series networks

- Proximity networks are derived based on the mutual closeness between different state vectors in the state space.
- Transition networks are constructed by defining transition probabilities after coarse-graining the state space.

Types of time series networks

- Proximity networks are derived based on the mutual closeness between different state vectors in the state space.
- Transition networks are constructed by defining transition probabilities after coarse-graining the state space.
- Visibility graphs are based on the convexity relation between different observations in a time series

Types of time series networks

The proximity networks can be further divided into

Types of time series networks

The proximity networks can be further divided into

- Cycle networks (Zhang et al. 2006)

Types of time series networks

The proximity networks can be further divided into

- Cycle networks (Zhang et al. 2006)
- Correlation networks

Types of time series networks

The proximity networks can be further divided into

- Cycle networks (Zhang et al. 2006)
- Correlation networks
- Recurrence networks

Cycle networks

- A cycle network can be constructed by dividing a time series (pseudo-periodic) into cycles, with each cycle representing a vertex in the network.

Cycle networks

- A cycle network can be constructed by dividing a time series (pseudo-periodic) into cycles, with each cycle representing a vertex in the network.
- An edge is formed between the nodes if the state space distance between the corresponding cycles is lesser than a predetermined threshold

Correlation networks

In correlation networks, the Pearson correlation coefficient between two state vectors is used as a closeness measure to define the existence of an edge between two nodes (i.e., state vectors)

Recurrence networks

Recurrence networks are based on the recurrences in phase space and are obtained by reinterpreting the recurrence matrix as the adjacency matrix of a complex network.

Recurrence networks

Recurrence networks are based on the recurrences in phase space and are obtained by reinterpreting the recurrence matrix as the adjacency matrix of a complex network.

- k —nearest neighbor recurrence network.

Recurrence networks

Recurrence networks are based on the recurrences in phase space and are obtained by reinterpreting the recurrence matrix as the adjacency matrix of a complex network.

- k —nearest neighbor recurrence network.
- Adaptive nearest neighbor recurrence network.

Recurrence networks

Recurrence networks are based on the recurrences in phase space and are obtained by reinterpreting the recurrence matrix as the adjacency matrix of a complex network.

- k —nearest neighbor recurrence network.
- Adaptive nearest neighbor recurrence network.
- ε —recurrence network.

k —nearest neighbor networks

- k —nearest neighbor recurrence network is formed by simply linking every vertex i to its k nearest neighbors.

k —nearest neighbor networks

- k —nearest neighbor recurrence network is formed by simply linking every vertex i to its k nearest neighbors.
- Any distance metric (euclidean or manhattan or maximum norm) can be used.

k —nearest neighbor networks

- k —nearest neighbor recurrence network is formed by simply linking every vertex i to its k nearest neighbors.
- Any distance metric (euclidean or manhattan or maximum norm) can be used.
- Such a network is related to the original definition of an RP by Eckmann *et al.*

k —nearest neighbor networks

- k —nearest neighbor recurrence network is formed by simply linking every vertex i to its k nearest neighbors.
- Any distance metric (euclidean or manhattan or maximum norm) can be used.
- Such a network is related to the original definition of an RP by Eckmann *et al*.
- Such a network is asymmetric and directed because $i \in \mathcal{N}(j)$ does not imply $j \in \mathcal{N}(i)$.

Adaptive nearest neighbor networks

- These are symmetric, undirected complex networks obtained from time series.

Adaptive nearest neighbor networks

- These are symmetric, undirected complex networks obtained from time series.
- If vertex $j \in \mathcal{N}(i)$, then vertex i is removed from $\mathcal{N}(j)$ to avoid the possibility of double-counting.

Adaptive nearest neighbor networks

- These are symmetric, undirected complex networks obtained from time series.
- If vertex $j \in \mathcal{N}(i)$, then vertex i is removed from $\mathcal{N}(j)$ to avoid the possibility of double-counting.
- This results in a symmetric adjacency matrix with an average degree of $2K_0$, where K_0 is the fixed number of neighbors initially assigned.

ε —recurrence network

- In case of an ε -recurrence network, one defines a fixed phase space distance ε centered around a vertex i (i.e., a state vector in phase space)

ε —recurrence network

- In case of an ε -recurrence network, one defines a fixed phase space distance ε centered around a vertex i (i.e., a state vector in phase space)
- All the vertices that fall within this volume are connected to the vertex i by forming an edge.

ε —recurrence network

- In case of an ε -recurrence network, one defines a fixed phase space distance ε centered around a vertex i (i.e., a state vector in phase space)
- All the vertices that fall within this volume are connected to the vertex i by forming an edge.
- Such a network is both undirected and symmetric.

ε —recurrence network

- In case of an ε -recurrence network, one defines a fixed phase space distance ε centered around a vertex i (i.e., a state vector in phase space)
- All the vertices that fall within this volume are connected to the vertex i by forming an edge.
- Such a network is both undirected and symmetric.

The k — nearest neighbor networks, Adaptive nearest neighbor networks and ε -recurrence networks are directly related with the concept of Poincaré recurrence in phase space.

ε —recurrence network

- In case of an ε -recurrence network, one defines a fixed phase space distance ε centered around a vertex i (i.e., a state vector in phase space)
- All the vertices that fall within this volume are connected to the vertex i by forming an edge.
- Such a network is both undirected and symmetric.

The k — nearest neighbor networks, Adaptive nearest neighbor networks and ε -recurrence networks are directly related with the concept of Poincaré recurrence in phase space.

They can be used to determine the dynamical invariants of the underlying system and provide an alternative framework for studying recurrences from a geometric point of view.

ε -recurrence networks

- 1 The recurrence matrix can be reinterpreted as an adjacency matrix (Marwan et al. 2009)

$$\mathbf{A}(\varepsilon) = \mathbf{R}(\varepsilon) - \mathbb{I}$$

ε -recurrence networks

- 1 The recurrence matrix can be reinterpreted as an adjacency matrix (Marwan et al. 2009)

$$\mathbf{A}(\varepsilon) = \mathbf{R}(\varepsilon) - \mathbb{I}$$

- 2 This adjacency matrix represents the unweighted and undirected complex network known as the recurrence network (RN) (Donner et al. 2011).

ε -recurrence networks

- 1 The recurrence matrix can be reinterpreted as an adjacency matrix (Marwan et al. 2009)

$$\mathbf{A}(\varepsilon) = \mathbf{R}(\varepsilon) - \mathbb{I}$$

- 2 This adjacency matrix represents the unweighted and undirected complex network known as the recurrence network (RN) (Donner et al. 2011).
- 3 Borrowing a rich set of measures from graph theory, we can characterize the topology of the RN.

ε -recurrence networks

- 1 The recurrence matrix can be reinterpreted as an adjacency matrix (Marwan et al. 2009)

$$\mathbf{A}(\varepsilon) = \mathbf{R}(\varepsilon) - \mathbb{I}$$

- 2 This adjacency matrix represents the unweighted and undirected complex network known as the recurrence network (RN) (Donner et al. 2011).
- 3 Borrowing a rich set of measures from graph theory, we can characterize the topology of the RN.
- 4 Thus one can characterize the geometric skeleton of the attractor and gain insight into the dynamics.

Visibility graphs

- The visibility graph (VG) approach is based on the concept of mutual visibility relationships between points and obstacles in two-dimensional landscapes in the framework of computational geometry.

Visibility graphs

- The visibility graph (VG) approach is based on the concept of mutual visibility relationships between points and obstacles in two-dimensional landscapes in the framework of computational geometry.
- Lacasa *et. al.* adopted the VG approach to the analysis of structures in scalar, univariate time series.

Visibility graphs

- The visibility graph (VG) approach is based on the concept of mutual visibility relationships between points and obstacles in two-dimensional landscapes in the framework of computational geometry.
- Lacasa *et. al.* adopted the VG approach to the analysis of structures in scalar, univariate time series.
- The basic idea is to consider individual time series observations as vertices.

Visibility graphs

- The visibility graph (VG) approach is based on the concept of mutual visibility relationships between points and obstacles in two-dimensional landscapes in the framework of computational geometry.
- Lacasa *et. al.* adopted the VG approach to the analysis of structures in scalar, univariate time series.
- The basic idea is to consider individual time series observations as vertices.
- Given a time series $\{x_i\}_{i=1}^N$ with $x_i = x(t_i)$.

Visibility graphs

- The visibility graph (VG) approach is based on the concept of mutual visibility relationships between points and obstacles in two-dimensional landscapes in the framework of computational geometry.
- Lacasa *et. al.* adopted the VG approach to the analysis of structures in scalar, univariate time series.
- The basic idea is to consider individual time series observations as vertices.
- Given a time series $\{x_i\}_{i=1}^N$ with $x_i = x(t_i)$.
- The VG approach will result in a $N \times N$ binary, adjacency matrix.

Visibility graphs

- Two points t_i and t_j are considered mutually visible in a VG setting if

$$\frac{x_i - x_k}{t_k - t_i} > \frac{x_i - x_j}{t_j - t_i}$$

is fulfilled for all time points t_k with $t_i < t_k < t_j$.

Visibility graphs

- Two points t_i and t_j are considered mutually visible in a VG setting if

$$\frac{x_i - x_k}{t_k - t_i} > \frac{x_i - x_j}{t_j - t_i}$$

is fulfilled for all time points t_k with $t_i < t_k < t_j$.

- VG take the temporal information into account explicitly (compare with RNs!).

Visibility graphs

- Two points t_i and t_j are considered mutually visible in a VG setting if

$$\frac{x_i - x_k}{t_k - t_i} > \frac{x_i - x_j}{t_j - t_i}$$

is fulfilled for all time points t_k with $t_i < t_k < t_j$.

- VG take the temporal information into account explicitly (compare with RNs!).
- Pitfalls : The first time point can only be visible to points that are in the future of thi observation.

Visibility graphs

- Two points t_i and t_j are considered mutually visible in a VG setting if

$$\frac{x_i - x_k}{t_k - t_i} > \frac{x_i - x_j}{t_j - t_i}$$

is fulfilled for all time points t_k with $t_i < t_k < t_j$.

- VG take the temporal information into account explicitly (compare with RNs!).
- Pitfalls : The first time point can only be visible to points that are in the future of thi observation.
- Advantages : No parameters to tune!

Horizontal visibility graphs

- The definition of VG was modified to obtain horizontal VGs (HVG), with the criterion

$$x_k < \min\{x_i, x_j\}$$

for all t_k with $t_i < t_k < t_j$.

Horizontal visibility graphs

- The definition of VG was modified to obtain horizontal VGs (HVG), with the criterion

$$x_k < \min\{x_i, x_j\}$$

for all t_k with $t_i < t_k < t_j$.

- HVG is more restrictive (lesser connected graph) compared to VG.

Horizontal visibility graphs

- The definition of VG was modified to obtain horizontal VGs (HVG), with the criterion

$$x_k < \min\{x_i, x_j\}$$

for all t_k with $t_i < t_k < t_j$.

- HVG is more restrictive (lesser connected graph) compared to VG.
- Algorithmically simple, compared to VG.

Horizontal visibility graphs

- The definition of VG was modified to obtain horizontal VGs (HVG), with the criterion

$$x_k < \min\{x_i, x_j\}$$

for all t_k with $t_i < t_k < t_j$.

- HVG is more restrictive (lesser connected graph) compared to VG.
- Algorithmically simple, compared to VG.
- HVG is not invariant under affine transformations.

Horizontal visibility graphs

- The definition of VG was modified to obtain horizontal VGs (HVG), with the criterion

$$x_k < \min\{x_i, x_j\}$$

for all t_k with $t_i < t_k < t_j$.

- HVG is more restrictive (lesser connected graph) compared to VG.
- Algorithmically simple, compared to VG.
- HVG is not invariant under affine transformations.
- Many other definitions of VGs exist (See Zou and Donner 2019)

VG vs HVG




Figure: VG and HVG constructed from sunspot numbers.

Transition networks

- Transition networks are directed networks by definition.

Transition networks

- Transition networks are directed networks by definition.
- The nodes of a transition network correspond to certain discrete states or patterns.

Transition networks

- Transition networks are directed networks by definition.
- The nodes of a transition network correspond to certain discrete states or patterns.
- Directed links are established if one of these nodes is followed by the other with non-zero (empirical) probability along the observed trajectory of the system under study.

Transition networks

- Transition networks are directed networks by definition.
- The nodes of a transition network correspond to certain discrete states or patterns.
- Directed links are established if one of these nodes is followed by the other with non-zero (empirical) probability along the observed trajectory of the system under study.
- It is equivalent to a Markov chain with given transition probabilities between discrete states.

Ordinal Partition Transition networks

An OPTN is based on the ordinal symbolic encoding of a time series and consists of

- nodes, which represent the individual ordinal patterns and
- probability-weighted edges, which represent the transition frequencies between two successive ordinal patterns.

Ordinal Partition Transition networks

- Given a univariate time series $X = \{x_t\}_{t=1}^T$, following Takens' embedding theorem, we can qualitatively reconstruct the underlying trajectory.



$$\mathbf{z}_t = [x_t, x_{t+\tau}, \dots, x_{t+(k-1)\tau}],$$

Ordinal Partition Transition networks

- Given a univariate time series $X = \{x_t\}_{t=1}^T$, following Takens' embedding theorem, we can qualitatively reconstruct the underlying trajectory.



$$\mathbf{z}_t = [x_t, x_{t+\tau}, \dots, x_{t+(k-1)\tau}],$$

- Each embedding vector \mathbf{z}_t is mapped to a sequence of integers $(s_0, s_1, \dots, s_{k-1})$ that describes the rank order of its components.

Ordinal Partition Transition networks

The rank order is a unique permutation of the set $\{0, 1, \dots, k-1\}$, thereby satisfying

$$x_{t+s_0\tau} \leq x_{t+s_1\tau} \leq x_{t+s_2\tau} \leq \dots \leq x_{t+s_{k-1}\tau}$$

and

$$s_{l-1} < s_l \quad \text{if} \quad x_{t-s_{l-1}} = x_{t-s_l}.$$

Ordinal Partition Transition networks

The rank order is a unique permutation of the set $\{0, 1, \dots, k-1\}$, thereby satisfying

$$x_{t+s_0\tau} \leq x_{t+s_1\tau} \leq x_{t+s_2\tau} \leq \dots \leq x_{t+s_{k-1}\tau}$$

and

$$s_{l-1} < s_l \quad \text{if} \quad x_{t-s_{l-1}} = x_{t-s_l}.$$

Note that there exist $k!$ different possible ordinal patterns when a time series is embedded in k dimensions, and we denote these patterns by $\pi_1, \pi_2, \dots, \pi_{k!}$.

Ordinal Partition Transition Networks

As an example, consider a 5-dimensional embedding of a time series yielding an embedding vector

$$\{x_t, x_{t+\tau}, x_{t+2\tau}, x_{t+3\tau}, x_{t+4\tau}\} = \{3, 9, 10, 1, 6\}.$$

- Here, $x_{t+3\tau} < x_t < x_{t+4\tau} < x_{t+\tau} < x_{t+2\tau}$.

Ordinal Partition Transition Networks

As an example, consider a 5-dimensional embedding of a time series yielding an embedding vector

$$\{x_t, x_{t+\tau}, x_{t+2\tau}, x_{t+3\tau}, x_{t+4\tau}\} = \{3, 9, 10, 1, 6\}.$$

- Here, $x_{t+3\tau} < x_t < x_{t+4\tau} < x_{t+\tau} < x_{t+2\tau}$.
- This partition would be mapped to the ordinal pattern or symbol $\pi_k = \{3, 0, 4, 1, 2\}$.

Ordinal Partition Transition Networks



As an example, consider a 5-dimensional embedding of a time series yielding an embedding vector

$$\{x_t, x_{t+\tau}, x_{t+2\tau}, x_{t+3\tau}, x_{t+4\tau}\} = \{3, 9, 10, 1, 6\}.$$









- Here, $x_{t+3\tau} < x_t < x_{t+4\tau} < x_{t+\tau} < x_{t+2\tau}$.
- This partition would be mapped to the ordinal pattern or symbol $\pi_k = \{3, 0, 4, 1, 2\}$.
- The exact numerical value of the resulting integer index $k \in \{1, \dots, M!\}$ depends on the specific sorting of the permutations.
- For a univariate time series, we can then construct an (unweighted or weighted) OPTN with $k!$ nodes by repeating this encoding procedure for each embedding vector.

Ordinal Partition Transition networks


- A weighted OPTN is obtained by setting the weight of the edge between two nodes (permutations) to be equal to the empirical frequency of transitions.
- An unweighted OPTN simply contains a directed edge of unit weight between the corresponding nodes if this frequency is nonzero.



Adjacency matrices corresponding to different types of time series networks (x —component of Lorenz system)



Complex networks based on adjacency matrices corresponding to x -component of Lorenz system



ε — recurrence networks

- We will focus on ε — recurrence networks, henceforth simply referred to as RN.

ε — recurrence networks

- We will focus on ε — recurrence networks, henceforth simply referred to as RN.
- After constructing the RN, the next step is to investigate its basic statistical properties in terms local and global complex network measures such as degree distribution, average path length, local clustering coefficient etc

Vertex-based local measures : Degree centrality

Degree centrality is a simple measure used to characterize the connectivity properties of a single vertex.

Vertex-based local measures : Degree centrality

Degree centrality is a simple measure used to characterize the connectivity properties of a single vertex. For a vertex i in a complex network, it can be defined as the number of vertices directly connected to i . It is given as

$$k_i = \sum_{j=1}^N A(i, j).$$

Vertex-based local measures : Degree centrality

Degree centrality is a simple measure used to characterize the connectivity properties of a single vertex. For a vertex i in a complex network, it can be defined as the number of vertices directly connected to i . It is given as

$$k_i = \sum_{j=1}^N A(i, j).$$

k_i can be normalized to describe the local phase space density, which gives the probability that a randomly chosen state vector in the phase space is within the ε -neighborhood of the state vector \mathbf{x}_i represented by the vertex i in the complex network. It is given as

$$\rho_i = \frac{k_i}{N - 1},$$

which also corresponds to the definition of the local recurrence rate (RR).

Example of Lorenz system




Figure: Spatial distribution of local recurrence rate for the chaotic Lorenz attractor.

Closeness centrality

- Closeness centrality can be defined as the inverse of the length of the shortest path (i.e., the geodesic distance) between a vertex i and all other vertices in a network.

Closeness centrality

- Closeness centrality can be defined as the inverse of the length of the shortest path (i.e., the geodesic distance) between a vertex i and all other vertices in a network.
- Given the geodesic distance $d(i, j)$ between two vertices i and j in a network, the closeness centrality of the vertex i can be then defined as,

$$c_i = \frac{N - 1}{\sum_{j=1}^N d(i, j)}$$

Example of Lorenz system




Figure: Spatial distribution of closeness centrality for the chaotic Lorenz attractor.

Betweenness centrality

- Betweenness centrality describes the importance of a vertex in a network, like the other centrality measures.

Betweenness centrality

- Betweenness centrality describes the importance of a vertex in a network, like the other centrality measures.
- The betweenness centrality of a vertex i is defined as the fraction of shortest paths in a network traversing the vertex i .

Betweenness centrality

- Betweenness centrality describes the importance of a vertex in a network, like the other centrality measures.
- The betweenness centrality of a vertex i is defined as the fraction of shortest paths in a network traversing the vertex i .
- Let σ_{jk} be the total number of shortest paths between the vertices j to k and $\sigma_{jk}(i)$ be the cardinality of the subset of the total number of shortest paths σ_{jk} that pass through the vertex i

Betweenness centrality

- Betweenness centrality describes the importance of a vertex in a network, like the other centrality measures.
- The betweenness centrality of a vertex i is defined as the fraction of shortest paths in a network traversing the vertex i .
- Let σ_{jk} be the total number of shortest paths between the vertices j to k and $\sigma_{jk}(i)$ be the cardinality of the subset of the total number of shortest paths σ_{jk} that pass through the vertex i
- The betweenness centrality for a vertex i can then be defined as,

$$b_i = \sum_{j \neq i \neq k} \frac{\sigma_{jk}(i)}{\sigma_{jk}}.$$

Example of Lorenz system




Figure: Spatial distribution of betweenness centrality for the chaotic Lorenz attractor.

Local clustering coefficient

- The local clustering coefficient of a vertex can be used to characterize the density of connections among its neighbors.

Local clustering coefficient

- The local clustering coefficient of a vertex can be used to characterize the density of connections among its neighbors.
- It gives the probability that two randomly drawn neighbors j and q of vertex i , are themselves neighbors.

Local clustering coefficient

- The local clustering coefficient of a vertex can be used to characterize the density of connections among its neighbors.
- It gives the probability that two randomly drawn neighbors j and q of vertex i , are themselves neighbors.
- A triangle Δ can be considered as a subgraph of three vertices of undirected graph G representing a complex network and the number of triangles on vertex i can be defined as
$$\delta(i) = | \{ \{j, q\} \in E : \{i, j\} \in E : \{i, q\} \in E \} |.$$

Local clustering coefficient

- The local clustering coefficient of a vertex can be used to characterize the density of connections among its neighbors.
- It gives the probability that two randomly drawn neighbors j and q of vertex i , are themselves neighbors.
- A triangle Δ can be considered as a subgraph of three vertices of undirected graph G representing a complex network and the number of triangles on vertex i can be defined as
$$\delta(i) = |\{ \{j, q\} \in E : \{i, j\} \in E : \{i, q\} \in E \}|.$$
- A **triple** at a vertex i can be defined as a path of length two, for which i is the central vertex.

Local clustering coefficient

- The local clustering coefficient of a vertex can be used to characterize the density of connections among its neighbors.
- It gives the probability that two randomly drawn neighbors j and q of vertex i , are themselves neighbors.
- A triangle Δ can be considered as a subgraph of three vertices of undirected graph G representing a complex network and the number of triangles on vertex i can be defined as
$$\delta(i) = |\{\{j, q\} \in E : \{i, j\} \in E : \{i, q\} \in E\}|.$$
- A **triple** at a vertex i can be defined as a path of length two, for which i is the central vertex.
- The number of triples (for an undirected network) for a vertex i is given as $T_i = \binom{k_i}{2}$, where k_i is the node degree or degree centrality.

Local clustering coefficient

The local clustering coefficient can be given as the ratio

$$C_i = \frac{\delta(i)}{T_i}$$

Local clustering coefficient

The local clustering coefficient can be given as the ratio

$$C_i = \frac{\delta(i)}{T_i}$$

The above expression can be given in terms of the adjacency matrix as

$$C_i = \frac{\sum_{j,q} A(i,j)A(j,q)A(q,i)}{2T_i}$$

Example of Lorenz system




Figure: Spatial distribution of local clustering coefficient for the chaotic Lorenz attractor.

What do these local measures reveal ?

- State space regions with a high density of points are characterized by a high degree density.
- The local clustering coefficient in a RN is associated with the geometric alignment of state vectors.
- If the dynamics of the system is effectively lower-dimensional, it results in a locally enhanced fraction of closed paths of length 3 (“triangles”) and, thus, a higher local clustering coefficient.
- Regions of unstable periodic orbits (UPOs) are typically associated with high local clustering coefficient.
- Closeness centrality is typically highest at the center of the RN.
- Betweenness centrality reveals the local degree of fragmentation of the attractor.

Global network measures

- Similar to the local network measures, there are several global network measures such as Global clustering coefficient, assortativity, Transitivity etc that can be used to characterize the attractor network.

Global network measures

- Similar to the local network measures, there are several global network measures such as Global clustering coefficient, assortativity, Transitivity etc that can be used to characterize the attractor network.
- Transitivity : Let $T(G)$ and $\delta(G)$ be the total number of triples and triangles in a graph G . The transitivity of a graph G can then be given as

$$\mathcal{T} = \frac{3\delta(G)}{T(G)}$$

Global network measures

- Similar to the local network measures, there are several global network measures such as Global clustering coefficient, assortativity, Transitivity etc that can be used to characterize the attractor network.
- Transitivity : Let $T(G)$ and $\delta(G)$ be the total number of triples and triangles in a graph G . The transitivity of a graph G can then be given as

$$\mathcal{T} = \frac{3\delta(G)}{T(G)}$$

- In terms of the matrix \mathbf{A} , \mathcal{T} can be given as

$$\mathcal{T} = \frac{\sum_{i,j,q=1}^N A(i,j)A(j,q)A(q,i)}{\sum_{i,j,q=1}^N A(i,j)A(q,i)}.$$

Transitivity dimension

- The concept of dimension can be defined based on the idea of transitivity.

Transitivity dimension

- The concept of dimension can be defined based on the idea of transitivity.
- **The transitivity dimension** at a single-scale ε can be given as [Donner et al. 2012]

$$\mathcal{D}_{\mathcal{T}_\varepsilon} = \frac{\log \mathcal{T}_\varepsilon}{\log(3/4)}$$

- Where does this idea come from ?

Random geometric graphs

- Consider a set \mathcal{A} embedded in k —dimensional metric space with continuous PDF $p(x)$.

Random geometric graphs

- Consider a set \mathcal{A} embedded in k -dimensional metric space with continuous PDF $p(x)$.
- Define $f: \mathcal{A}^2 \rightarrow [0, 1]$.

Random geometric graphs

- Consider a set \mathcal{A} embedded in k –dimensional metric space with continuous PDF $p(x)$.
- Define $f: \mathcal{A}^2 \rightarrow [0, 1]$.
- $f(x, y) = f(|x - y|)$ being monotonically decreasing, describing the probability with which two elements of V (N points drawn according to $p(x)$) at positions x and y are linked.

Random geometric graphs

- Consider a set \mathcal{A} embedded in k -dimensional metric space with continuous PDF $p(x)$.
- Define $f: \mathcal{A}^2 \rightarrow [0, 1]$.
- $f(x, y) = f(|x - y|)$ being monotonically decreasing, describing the probability with which two elements of V (N points drawn according to $p(x)$) at positions x and y are linked.
- An undirected graph $(V, V \times V)$, with the elements of the edge set being determined by f is called a random geometric graph (RGG).

Random geometric graphs

- Consider a set \mathcal{A} embedded in k -dimensional metric space with continuous PDF $p(x)$.
- Define $f: \mathcal{A}^2 \rightarrow [0, 1]$.
- $f(x, y) = f(|x - y|)$ being monotonically decreasing, describing the probability with which two elements of V (N points drawn according to $p(x)$) at positions x and y are linked.
- An undirected graph $(V, V \times V)$, with the elements of the edge set being determined by f is called a random geometric graph (RGG).
- $f(x, y) = \Theta(\varepsilon - |x - y|)$.

Random geometric graphs




Figure: For a random geometric graph, network measures such as clustering coefficient are purely geometric quantity

Asymptotic solution $C_d \approx 3\sqrt{\frac{2}{\pi d}}\left(\frac{3}{4}\right)^{\frac{d+1}{2}}$


Dynamical systems and RGG

- We can think of \mathcal{A} as the manifold describing a chaotic attractor and $p(x)$ can be some invariant density.
- The structure of the attractor can be approximated by a set of elements of \mathcal{A} drawn randomly according to $p(x)$.
- The (network) properties of such RGGs reveal geometric characteristics of the attractor!


Summary of measures [Subramaniam 2016]

Network measures	Definition	Interpretation	Key references
Degree centrality (k_i)	$\sum_{j=1}^N A(i, j)$.	Local recurrence in phase space, emergence of scale-free distributions	Donner <i>et al.</i> [16] ; Zout <i>et al.</i> [169]
Closeness centrality (c_i)	$\frac{N-1}{\sum_{j=1}^N d(i, j)}$.	Identification of the attractor's center of gravity	Donner <i>et al.</i> [16]
Betweenness centrality (b_i)	$\sum_{j \neq i \neq k} \frac{\sigma_{jk}(i)}{\sigma_{jk}}$.	Local fragmentation of attractor	Donner <i>et al.</i> [16, 154]
Clustering coefficient (C_i)	$\frac{\sum_{j,q} A(i,j)A(j,q)A(q,i)}{2T_i}$, $T_i = \frac{k_i(k_i-1)}{2}$.	Presence of lower order UPOs	Donner <i>et al.</i> [16] ; Zou <i>et al.</i> [165]
Transitivity (\mathcal{T})	$\frac{\sum_{i,j,q=1}^N A(i,j)A(j,q)A(q,i)}{\sum_{i,j,q=1}^N A(i,j)A(q,i)}$.	Attractor dimension, UPOs, regularity of dynamics	Donner <i>et al.</i> [163]; Donges <i>et al.</i> [170]
Assortativity (\mathcal{R})	$\frac{\frac{1}{N} \sum_{j>i} k_i k_j A(i,j) - [\frac{1}{N} \sum_{j>i} \frac{1}{2} (k_i + k_j) A(i,j)]^2}{\frac{1}{N} \sum_{j>i} \frac{1}{2} (k_i^2 + k_j^2) A(i,j) - [\frac{1}{N} \sum_{j>i} \frac{1}{2} (k_i + k_j) A(i,j)]^2}$.	Smoothness of phase space density	Donner <i>et al.</i> [16]
Average path length (\mathcal{L})	$\frac{1}{N(N-1)} \sum_{i \neq j} d(i, j)$.	Average phase space separation, abrupt dynamical changes	Donner <i>et al.</i> [16]; Zou <i>et al.</i> [165]; Donges <i>et al.</i> [170]
Cross-clustering coefficient (\mathcal{C}_{xy})	$\frac{\sum A_{xy}(i,j)A_{xy}(i,k)A_y(j,k)}{k_{i,xy}(k_{i,xy}-1)}$.	Mutual interaction between complex networks	Donges <i>et al.</i> [149]

Real-world examples : Detecting epileptic seizure



Real-world examples : Terrigenous dust flux



Take home messages

- RN measures are advantageous as they are conceptually simple and attractor topology can be quantified using various network measures.
- Clustering coefficient is sensitive to periodicity. (longer time-scales)
- Average path length, Transitivity dimension is sensitive to transitions. (short time-scales)
- Complementary to methods such as RQA and other linear/nonlinear methods.