



Kotlin Language Documentation

Table of Contents

| | |
|--|-----|
| Overview | 5 |
| Using Kotlin for Server-side Development | 5 |
| Using Kotlin for Android Development | 7 |
| Kotlin JavaScript Overview | 8 |
| Kotlin/Native | 9 |
| What's New in Kotlin 1.1 | 10 |
| What's New in Kotlin 1.2 | 19 |
| Getting Started | 25 |
| Basic Syntax | 25 |
| Idioms | 31 |
| Coding Conventions | 36 |
| Basics | 51 |
| Basic Types | 51 |
| Packages | 57 |
| Control Flow: if, when, for, while | 59 |
| Returns and Jumps | 62 |
| Classes and Objects | 64 |
| Classes and Inheritance | 64 |
| Properties and Fields | 70 |
| Interfaces | 73 |
| Visibility Modifiers | 75 |
| Extensions | 77 |
| Data Classes | 81 |
| Sealed Classes | 83 |
| Generics | 84 |
| Nested and Inner Classes | 89 |
| Enum Classes | 90 |
| Object Expressions and Declarations | 92 |
| Delegation | 95 |
| Delegated Properties | 97 |
| Functions and Lambdas | 102 |
| Functions | 102 |
| Higher-Order Functions and Lambdas | 107 |
| Inline Functions | 112 |
| Coroutines | 115 |
| Other | 120 |
| Destructuring Declarations | 120 |
| Collections: List, Set, Map | 122 |

| | |
|--|-----|
| Ranges | 124 |
| Type Checks and Casts: 'is' and 'as' | 127 |
| This Expression | 130 |
| Equality | 131 |
| Operator overloading | 132 |
| Null Safety | 136 |
| Exceptions | 139 |
| Annotations | 141 |
| Reflection | 145 |
| Type-Safe Builders | 149 |
| Multiplatform Projects | 155 |
| Reference | 159 |
| Keywords and Operators | 159 |
| Grammar | 163 |
| Notation | 163 |
| Semicolons | 163 |
| Syntax | 163 |
| Lexical structure | 171 |
| Compatibility | 173 |
| Java Interop | 177 |
| Calling Java code from Kotlin | 177 |
| Calling Kotlin from Java | 187 |
| JavaScript | 193 |
| Dynamic Type | 193 |
| Calling JavaScript from Kotlin | 195 |
| Calling Kotlin from JavaScript | 198 |
| JavaScript Modules | 200 |
| JavaScript Reflection | 203 |
| JavaScript DCE | 204 |
| Example | 204 |
| Native | 206 |
| Concurrency in Kotlin/Native | 206 |
| Workers | 206 |
| Object transfer and freezing | 206 |
| Object subgraph detachment | 207 |
| Raw shared memory | 207 |
| Global variables and singletons | 207 |
| Immutability in Kotlin/Native | 209 |
| Kotlin/Native libraries | 210 |
| Advanced topics | 211 |
| Platform libraries | 212 |

| | |
|---|-----|
| Kotlin/Native in multiplatform projects | 213 |
| Kotlin/Native interoperability | 219 |
| Kotlin/Native interoperability with Swift/Objective-C | 226 |
| Kotlin/Native Gradle plugin | 230 |
| Tools | 250 |
| Documenting Kotlin Code | 250 |
| Annotation Processing with Kotlin | 253 |
| Using Gradle | 256 |
| Using Maven | 262 |
| Using Ant | 269 |
| Kotlin and OSGi | 272 |
| Compiler Plugins | 273 |
| FAQ | 279 |
| FAQ | 279 |
| Comparison to Java Programming Language | 282 |

Overview

Using Kotlin for Server-side Development

Kotlin is a great fit for developing server-side applications, allowing to write concise and expressive code while maintaining full compatibility with existing Java-based technology stacks and a smooth learning curve:

- **Expressiveness:** Kotlin's innovative language features, such as its support for [type-safe builders](#) and [delegated properties](#), help build powerful and easy-to-use abstractions.
- **Scalability:** Kotlin's support for [coroutines](#) helps build server-side applications that scale to massive numbers of clients with modest hardware requirements.
- **Interoperability:** Kotlin is fully compatible with all Java-based frameworks, which lets you stay on your familiar technology stack while reaping the benefits of a more modern language.
- **Migration:** Kotlin supports gradual, step by step migration of large codebases from Java to Kotlin. You can start writing new code in Kotlin while keeping older parts of your system in Java.
- **Tooling:** In addition to great IDE support in general, Kotlin offers framework-specific tooling (for example, for Spring) in the plugin for IntelliJ IDEA Ultimate.
- **Learning Curve:** For a Java developer, getting started with Kotlin is very easy. The automated Java to Kotlin converter included in the Kotlin plugin helps with the first steps. [Kotlin Koans](#) offer a guide through the key features of the language with a series of interactive exercises.

Frameworks for Server-side Development with Kotlin

- [Spring](#) makes use of Kotlin's language features to offer [more concise APIs](#), starting with version 5.0. The [online project generator](#) allows to quickly generate a new project in Kotlin.
- [Vert.x](#), a framework for building reactive Web applications on the JVM, offers [dedicated support](#) for Kotlin, including [full documentation](#).
- [Ktor](#) is a framework built by JetBrains for creating Web applications in Kotlin, making use of coroutines for high scalability and offering an easy-to-use and idiomatic API.
- [kotlinx.html](#) is a DSL that can be used to build HTML in a Web application. It serves as an alternative to traditional templating systems such as JSP and FreeMarker.
- The available options for persistence include direct JDBC access, JPA, as well as using NoSQL databases through their Java drivers. For JPA, the [kotlin-jpa compiler plugin](#) adapts Kotlin-compiled classes to the requirements of the framework.

Deploying Kotlin Server-side Applications

Kotlin applications can be deployed into any host that supports Java Web applications, including Amazon Web Services, Google Cloud Platform and more.

To deploy Kotlin applications on [Heroku](#), you can follow the [official Heroku tutorial](#).

AWS Labs provides a [sample project](#) showing the use of Kotlin for writing [AWS Lambda](#) functions.

Users of Kotlin on the Server Side

[Corda](#) is an open-source distributed ledger platform, supported by major banks, and built entirely in Kotlin.

[JetBrains Account](#), the system responsible for the entire license sales and validation process at JetBrains, is written in 100% Kotlin and has been running in production since 2015 with no major issues.

Next Steps

- The [Creating Web Applications with Http Servlets](#) and [Creating a RESTful Web Service with Spring Boot](#) tutorials show you how you can build and run very small Web applications in Kotlin.
- For a more in-depth introduction to the language, check out the [reference documentation](#) on this site and [Kotlin Koans](#).

Using Kotlin for Android Development

Kotlin is a great fit for developing Android applications, bringing all of the advantages of a modern language to the Android platform without introducing any new restrictions:

- **Compatibility:** Kotlin is fully compatible with JDK 6, ensuring that Kotlin applications can run on older Android devices with no issues. The Kotlin tooling is fully supported in Android Studio and compatible with the Android build system.
- **Performance:** A Kotlin application runs as fast as an equivalent Java one, thanks to very similar bytecode structure. With Kotlin's support for inline functions, code using lambdas often runs even faster than the same code written in Java.
- **Interoperability:** Kotlin is 100% interoperable with Java, allowing to use all existing Android libraries in a Kotlin application. This includes annotation processing, so databinding and Dagger work too.
- **Footprint:** Kotlin has a very compact runtime library, which can be further reduced through the use of ProGuard. In a [real application](#), the Kotlin runtime adds only a few hundred methods and less than 100K to the size of the .apk file.
- **Compilation Time:** Kotlin supports efficient incremental compilation, so while there's some additional overhead for clean builds, [incremental builds are usually as fast or faster than with Java](#).
- **Learning Curve:** For a Java developer, getting started with Kotlin is very easy. The automated Java to Kotlin converter included in the Kotlin plugin helps with the first steps. [Kotlin Koans](#) offer a guide through the key features of the language with a series of interactive exercises.

Kotlin for Android Case Studies

Kotlin has been successfully adopted by major companies, and a few of them have shared their experiences:

- Pinterest has successfully [introduced Kotlin into their application](#), used by 150M people every month.
- Basecamp's Android app is [100% Kotlin code](#), and they report a huge difference in programmer happiness and great improvements in work quality and speed.
- KeepSafe's App Lock app has also been [converted to 100% Kotlin](#), leading to a 30% decrease in source line count and 10% decrease in method count.

Tools for Android Development

The Kotlin team offers a set of tools for Android development that goes beyond the standard language features:

- [Kotlin Android Extensions](#) is a compiler extension that allows you to get rid of `findViewById()` calls in your code and to replace them with synthetic compiler-generated properties.
- [Anko](#) is a library providing a set of Kotlin-friendly wrappers around the Android APIs, as well as a DSL that lets you replace your layout .xml files with Kotlin code.

Next Steps

- Download and install [Android Studio 3.0](#), which includes Kotlin support out of the box.
- Follow the [Getting Started with Android and Kotlin](#) tutorial to create your first Kotlin application.
- For a more in-depth introduction, check out the [reference documentation](#) on this site and [Kotlin Koans](#).
- Another great resource is [Kotlin for Android Developers](#), a book that guides you step by step through the process of creating a real Android application in Kotlin.
- Check out Google's [sample projects written in Kotlin](#).

Kotlin JavaScript Overview

Kotlin provides the ability to target JavaScript. It does so by transpiling Kotlin to JavaScript. The current implementation targets ECMAScript 5.1 but there are plans to eventually target ECMAScript 2015 as well.

When you choose the JavaScript target, any Kotlin code that is part of the project as well as the standard library that ships with Kotlin is transpiled to JavaScript. However, this excludes the JDK and any JVM or Java framework or library used. Any file that is not Kotlin will be ignored during compilation.

The Kotlin compiler tries to comply with the following goals:

- Provide output that is optimal in size
- Provide output that is readable JavaScript
- Provide interoperability with existing module systems
- Provide the same functionality in the standard library whether targeting JavaScript or the JVM (to the largest possible degree).

How it can be used

You may want to compile Kotlin to JavaScript in the following scenarios:

- Creating Kotlin code that targets client-side JavaScript
 - **Interacting with DOM elements.** Kotlin provides a series of statically typed interfaces to interact with the Document Object Model, allowing creation and update of DOM elements.
 - **Interacting with graphics such as WebGL.** You can use Kotlin to create graphical elements on a web page using WebGL.
- Creating Kotlin code that targets server-side JavaScript
 - **Working with server-side technology.** You can use Kotlin to interact with server-side JavaScript such as Node.js

Kotlin can be used together with existing third-party libraries and frameworks, such as jQuery or React. To access third-party frameworks with a strongly-typed API, you can convert TypeScript definitions from the [Definitely Typed](#) type definitions repository to Kotlin using the [ts2kt](#) tool. Alternatively, you can use the [dynamic type](#) to access any framework without strong typing.

JetBrains develops and maintains several tools specifically for the React community: [React bindings](#) as well as [Create React Kotlin App](#). The latter helps you start building React apps with Kotlin with no build configuration.

Kotlin is compatible with CommonJS, AMD and UMD, [making interaction with different](#) module systems straightforward.

Getting Started with Kotlin to JavaScript

To find out how to start using Kotlin for JavaScript, please refer to the [tutorials](#).

Kotlin/Native

[Kotlin/Native](#) is a technology for compiling Kotlin to native binaries that run without any VM. It comprises a LLVM-based backend for the Kotlin compiler and a native implementation of the Kotlin runtime library. Kotlin/Native is primarily designed to allow compilation for platforms where virtual machines are not desirable or possible (such as iOS, embedded targets), or where a developer needs to produce a reasonably-sized self-contained program that does not require an additional runtime.

Kotlin/Native fully supports interoperability with native code. For platform libraries, the corresponding interop libraries are available out of the box. For other libraries, we provide a [tool to generate an interop library](#) from a C header file, with full support for all C language features. On macOS and iOS, interoperability with Objective-C code is also supported.

Kotlin/Native is currently in development; preview releases are available for you to try. IDE support for Kotlin/Native is available as plugins for [CLion](#) and [AppCode](#), both require the plugin to be installed via *Plugins / Install JetBrains plugin...* in the IDE preferences.

Target Platforms

Kotlin/Native currently supports the following platforms:

- Windows (x86_64 only at the moment)
- Linux (x86_64, arm32, MIPS, MIPS little endian)
- MacOS (x86_64)
- iOS (arm32 and arm64)
- Android (arm32 and arm64)
- WebAssembly (wasm32 only)

Sample Projects

We've built a number of sample projects to showcase the possibilities of Kotlin/Native:

- The [Kotlin/Native GitHub repository](#) contains a number of sample projects;
- The [KotlinConf Spinner app](#) is a simple cross-platform mobile multiplayer game fully built in Kotlin/Native, consisting of the following components:
 - a backend, using SQLite for data storage and exposing a REST/JSON API;
 - mobile clients for iOS and Android, using OpenGL;
 - a WebAssembly-based browser frontend for viewing the game scores.
- The [KotlinConf app](#) is an iOS app with a UIKit-based UI, showcasing the Objective-C interop facilities of Kotlin/Native.

What's New in Kotlin 1.1

Table of Contents

- [Coroutines](#)
- [Other language features](#)
- [Standard library](#)
- [JVM backend](#)
- [JavaScript backend](#)

JavaScript

Starting with Kotlin 1.1, the JavaScript target is no longer considered experimental. All language features are supported, and there are many new tools for integration with the front-end development environment. See [below](#) for a more detailed list of changes.

Coroutines (experimental)

The key new feature in Kotlin 1.1 is *coroutines*, bringing the support of `async / await`, `yield` and similar programming patterns. The key feature of Kotlin's design is that the implementation of coroutine execution is part of the libraries, not the language, so you aren't bound to any specific programming paradigm or concurrency library.

A coroutine is effectively a light-weight thread that can be suspended and resumed later. Coroutines are supported through [suspending functions](#): a call to such a function can potentially suspend a coroutine, and to start a new coroutine we usually use an anonymous suspending functions (i.e. suspending lambdas).

Let's look at `async / await` which is implemented in an external library, [kotlinx.coroutines](#):

```
// runs the code in the background thread pool
fun asyncOverlay() = async(CommonPool) {
    // start two async operations
    val original = asyncLoadImage("original")
    val overlay = asyncLoadImage("overlay")
    // and then apply overlay to both results
    applyOverlay(original.await(), overlay.await())
}

// launches new coroutine in UI context
launch(UI) {
    // wait for async overlay to complete
    val image = asyncOverlay().await()
    // and then show it in UI
    showImage(image)
}
```

Here, `async { ... }` starts a coroutine and, when we use `await()`, the execution of the coroutine is suspended while the operation being awaited is executed, and is resumed (possibly on a different thread) when the operation being awaited completes.

The standard library uses coroutines to support *lazily generated sequences* with `yield` and `yieldAll` functions. In such a sequence, the block of code that returns sequence elements is suspended after each element has been retrieved, and resumed when the next element is requested. Here's an example:

```

val seq = buildSequence {
    for (i in 1..5) {
        // yield a square of i
        yield(i * i)
    }
    // yield a range
    yieldAll(26..28)
}

// print the sequence
println(seq.toList())

```

Run the code above to see the result. Feel free to edit it and run again!

For more information, please refer to the [coroutine documentation](#) and [tutorial](#).

Note that coroutines are currently considered an **experimental feature**, meaning that the Kotlin team is not committing to supporting the backwards compatibility of this feature after the final 1.1 release.

Other Language Features

Type aliases

A type alias allows you to define an alternative name for an existing type. This is most useful for generic types such as collections, as well as for function types. Here is an example:

```

typealias OscarWinners = Map<String, String>

fun countLaLaLand(oscarWinners: OscarWinners) =
    oscarWinners.count { it.value.contains("La La Land") }

// Note that the type names (initial and the type alias) are interchangeable:
fun checkLaLaLandIsTheBestMovie(oscarWinners: Map<String, String>) =
    oscarWinners["Best picture"] == "La La Land"

```

See the [documentation](#) and [KEEP](#) for more details.

Bound callable references

You can now use the `::` operator to get a [member reference](#) pointing to a method or property of a specific object instance. Previously this could only be expressed with a lambda. Here's an example:

```

val numberRegex = "\\d+".toRegex()
val numbers = listOf("abc", "123", "456").filter(numberRegex::matches)

```

Read the [documentation](#) and [KEEP](#) for more details.

Sealed and data classes

Kotlin 1.1 removes some of the restrictions on sealed and data classes that were present in Kotlin 1.0. Now you can define subclasses of a top-level sealed class on the top level in the same file, and not just as nested classes of the sealed class. Data classes can now extend other classes. This can be used to define a hierarchy of expression classes nicely and cleanly:

```
sealed class Expr

data class Const(val number: Double) : Expr()
data class Sum(val e1: Expr, val e2: Expr) : Expr()
object NotANumber : Expr()

fun eval(expr: Expr): Double = when (expr) {
    is Const -> expr.number
    is Sum -> eval(expr.e1) + eval(expr.e2)
    NotANumber -> Double.NaN
}
val e = eval(Sum(Const(1.0), Const(2.0)))
```

Read the [documentation](#) or [sealed class](#) and [data class](#) KEEPs for more detail.

Destructuring in lambdas

You can now use the [destructuring declaration](#) syntax to unpack the arguments passed to a lambda. Here's an example:

```
val map = mapOf(1 to "one", 2 to "two")
// before
println(map.mapValues { entry ->
    val (key, value) = entry
    "$key -> $value!"
})
// now
println(map.mapValues { (key, value) -> "$key -> $value!" })
```

Read the [documentation](#) and [KEEP](#) for more details.

Underscores for unused parameters

For a lambda with multiple parameters, you can use the `_` character to replace the names of the parameters you don't use:

```
map.forEach { _, value -> println("$value!") }
```

This also works in [destructuring declarations](#):

```
val (_, status) = getResult()
```

Read the [KEEP](#) for more details.

Underscores in numeric literals

Just as in Java 8, Kotlin now allows to use underscores in numeric literals to separate groups of digits:

```
val oneMillion = 1_000_000
val hexBytes = 0xFF_EC_DE_5E
val bytes = 0b11010010_01101001_10010100_10010010
```

Read the [KEEP](#) for more details.

Shorter syntax for properties

For properties with the getter defined as an expression body, the property type can now be omitted:

```
data class Person(val name: String, val age: Int) {
    val isAdult get() = age >= 20 // Property type inferred to be 'Boolean'
}
```

Inline property accessors

You can now mark property accessors with the `inline` modifier if the properties don't have a backing field. Such accessors are compiled in the same way as [inline functions](#).

```
public val <T> List<T>.lastIndex: Int
    inline get() = this.size - 1
```

You can also mark the entire property as `inline` - then the modifier is applied to both accessors.

Read the [documentation](#) and [KEEP](#) for more details.

Local delegated properties

You can now use the [delegated property](#) syntax with local variables. One possible use is defining a lazily evaluated local variable:

```
val answer by lazy {
    println("Calculating the answer...")
    42
}
if (needAnswer()) {                // returns the random value
    println("The answer is $answer.") // answer is calculated at this point
}
else {
    println("Sometimes no answer is the answer...")
}
```

Read the [KEEP](#) for more details.

Interception of delegated property binding

For [delegated properties](#), it is now possible to intercept delegate to property binding using the `provideDelegate` operator. For example, if we want to check the property name before binding, we can write something like this:

```
class ResourceLoader<T>(id: ResourceID<T>) {
    operator fun provideDelegate(thisRef: MyUI, prop: KProperty<*>): ReadOnlyProperty<MyUI, T> {
        checkProperty(thisRef, prop.name)
        ... // property creation
    }

    private fun checkProperty(thisRef: MyUI, name: String) { ... }
}

fun <T> bindResource(id: ResourceID<T>): ResourceLoader<T> { ... }

class MyUI {
    val image by bindResource(ResourceID.image_id)
    val text by bindResource(ResourceID.text_id)
}
```

The `provideDelegate` method will be called for each property during the creation of a `MyUI` instance, and it can perform the necessary validation right away.

Read the [documentation](#) for more details.

Generic enum value access

It is now possible to enumerate the values of an enum class in a generic way.

```
enum class RGB { RED, GREEN, BLUE }

inline fun <reified T : Enum<T>> printAllValues() {
    print(enumValues<T>().joinToString { it.name })
}
```

Scope control for implicit receivers in DSLs

The [@DslMarker](#) annotation allows to restrict the use of receivers from outer scopes in a DSL context. Consider the canonical [HTML builder example](#):

```
table {
    tr {
        td { + "Text" }
    }
}
```

In Kotlin 1.0, code in the lambda passed to `td` has access to three implicit receivers: the one passed to `table`, to `tr` and to `td`. This allows you to call methods that make no sense in the context - for example to call `tr` inside `td` and thus to put a `<tr>` tag in a `<td>`.

In Kotlin 1.1, you can restrict that, so that only methods defined on the implicit receiver of `td` will be available inside the lambda passed to `td`. You do that by defining your annotation marked with the `@DslMarker` meta-annotation and applying it to the base class of the tag classes.

Read the [documentation](#) and [KEEP](#) for more details.

rem operator

The `mod` operator is now deprecated, and `rem` is used instead. See [this issue](#) for motivation.

Standard library

String to number conversions

There is a bunch of new extensions on the `String` class to convert it to a number without throwing an exception on invalid number: `String.toIntOrNull(): Int?`, `String.toDoubleOrNull(): Double?` etc.

```
val port = System.getenv("PORT")?.toIntOrNull() ?: 80
```

Also integer conversion functions, like `Int.toString()`, `String.toInt()`, `String.toIntOrNull()`, each got an overload with `radix` parameter, which allows to specify the base of conversion (2 to 36).

onEach()

`onEach` is a small, but useful extension function for collections and sequences, which allows to perform some action, possibly with side-effects, on each element of the collection/sequence in a chain of operations. On iterables it behaves like `forEach` but also returns the iterable instance further. And on sequences it returns a wrapping sequence, which applies the given action lazily as the elements are being iterated.

```
inputDir.walk()
    .filter { it.isFile && it.name.endsWith(".txt") }
    .onEach { println("Moving $it to $outputDir") }
    .forEach { moveFile(it, File(outputDir, it.toRelativeString(inputDir))) }
```

also(), takeIf() and takeUnless()

These are three general-purpose extension functions applicable to any receiver.

`also` is like `apply`: it takes the receiver, does some action on it, and returns that receiver. The difference is that in the block inside `apply` the receiver is available as `this`, while in the block inside `also` it's available as `it` (and you can give it another name if you want). This comes handy when you do not want to shadow `this` from the outer scope:

```
fun Block.copy() = Block().also {
    it.content = this.content
}
```

`takeIf` is like `filter` for a single value. It checks whether the receiver meets the predicate, and returns the receiver, if it does or `null` if it doesn't. Combined with an elvis-operator and early returns it allows to write constructs like:

```
val outDirFile = File(outputDir.path).takeIf { it.exists() } ?: return false
// do something with existing outDirFile
```

```
val index = input.indexOf(keyword).takeIf { it >= 0 } ?: error("keyword not found")
// do something with index of keyword in input string, given that it's found
```

`takeUnless` is the same as `takeIf`, but it takes the inverted predicate. It returns the receiver when it *doesn't* meet the predicate and `null` otherwise. So one of the examples above could be rewritten with `takeUnless` as following:

```
val index = input.indexOf(keyword).takeUnless { it < 0 } ?: error("keyword not found")
```

It is also convenient to use when you have a callable reference instead of the lambda:

```
val result = string.takeUnless(String::isEmpty)
```

groupingBy()

This API can be used to group a collection by key and fold each group simultaneously. For example, it can be used to count the number of words starting with each letter:

```
val frequencies = words.groupingBy { it.first() }.eachCount()
```

Map.toMap() and Map.toMutableMap()

These functions can be used for easy copying of maps:

```
class ImmutablePropertyBag(map: Map<String, Any>) {
    private val mapCopy = map.toMap()
}
```

Map.minus(key)

The operator `plus` provides a way to add key-value pair(s) to a read-only map producing a new map, however there was not a simple way to do the opposite: to remove a key from the map you have to resort to less straightforward ways to like `Map.filter()` or `Map.filterKeys()`. Now the operator `minus` fills this gap. There are 4 overloads available: for removing a single key, a collection of keys, a sequence of keys and an array of keys.

```
val map = mapOf("key" to 42)
val emptyMap = map - "key"
```

minOf() and maxOf()

These functions can be used to find the lowest and greatest of two or three given values, where values are primitive numbers or `Comparable` objects. There is also an overload of each function that take an additional `Comparator` instance, if you want to compare objects that are not comparable themselves.

```
val list1 = listOf("a", "b")
val list2 = listOf("x", "y", "z")
val minSize = minOf(list1.size, list2.size)
val longestList = maxOf(list1, list2, compareBy { it.size })
```

Array-like List instantiation functions

Similar to the `Array` constructor, there are now functions that create `List` and `MutableList` instances and initialize each element by calling a lambda:

```
val squares = List(10) { index -> index * index }
val mutable = MutableList(10) { 0 }
```

Map.getValue()

This extension on `Map` returns an existing value corresponding to the given key or throws an exception, mentioning which key was not found. If the map was produced with `withDefault`, this function will return the default value instead of throwing an exception.

```
val map = mapOf("key" to 42)
// returns non-nullable Int value 42
val value: Int = map.getValue("key")

val mapWithDefault = map.withDefault { k -> k.length }
// returns 4
val value2 = mapWithDefault.getValue("key2")

// map.getValue("anotherKey") // <- this will throw NoSuchElementException
```

Abstract collections

These abstract classes can be used as base classes when implementing Kotlin collection classes. For implementing read-only collections there are `AbstractCollection`, `AbstractList`, `AbstractSet` and `AbstractMap`, and for mutable collections there are `AbstractMutableCollection`, `AbstractMutableList`, `AbstractMutableSet` and `AbstractMutableMap`. On JVM these abstract mutable collections inherit most of their functionality from JDK's abstract collections.

Array manipulation functions

The standard library now provides a set of functions for element-by-element operations on arrays: comparison (`contentEquals` and `contentDeepEquals`), hash code calculation (`contentHashCode` and `contentDeepHashCode`), and conversion to a string (`contentToString` and `contentDeepToString`). They're supported both for the JVM (where they act as aliases for the corresponding functions in `java.util.Arrays`) and for JS (where the implementation is provided in the Kotlin standard library).

```
val array = arrayOf("a", "b", "c")
println(array.toString()) // JVM implementation: type-and-hash gibberish
println(array.contentToString()) // nicely formatted as list
```

JVM Backend

Java 8 bytecode support

Kotlin has now the option of generating Java 8 bytecode (`-jvm-target 1.8` command line option or the corresponding options in Ant/Maven/Gradle). For now this doesn't change the semantics of the bytecode (in particular, default methods in interfaces and lambdas are generated exactly as in Kotlin 1.0), but we plan to make further use of this later.

Java 8 standard library support

There are now separate versions of the standard library supporting the new JDK APIs added in Java 7 and 8. If you need access to the new APIs, use `kotlin-stdlib-jre7` and `kotlin-stdlib-jre8` maven artifacts instead of the standard `kotlin-stdlib`. These artifacts are tiny extensions on top of `kotlin-stdlib` and they bring it to your project as a transitive dependency.

Parameter names in the bytecode

Kotlin now supports storing parameter names in the bytecode. This can be enabled using the `-java-parameters` command line option.

Constant inlining

The compiler now inlines values of `const val` properties into the locations where they are used.

Mutable closure variables

The box classes used for capturing mutable closure variables in lambdas no longer have volatile fields. This change improves performance, but can lead to new race conditions in some rare usage scenarios. If you're affected by this, you need to provide your own synchronization for accessing the variables.

javax.script support

Kotlin now integrates with the [javax.script API](#) (JSR-223). The API allows to evaluate snippets of code at runtime:

```
val engine = ScriptEngineManager().getEngineByExtension("kts")!!
engine.eval("val x = 3")
println(engine.eval("x + 2")) // Prints out 5
```

See [here](#) for a larger example project using the API.

kotlin.reflect.full

To [prepare for Java 9 support](#), the extension functions and properties in the `kotlin-reflect.jar` library have been moved to the package `kotlin.reflect.full`. The names in the old package (`kotlin.reflect`) are deprecated and will be removed in Kotlin 1.2. Note that the core reflection interfaces (such as `KClass`) are part of the Kotlin standard library, not `kotlin-reflect`, and are not affected by the move.

JavaScript Backend

Unified standard library

A much larger part of the Kotlin standard library can now be used from code compiled to JavaScript. In particular, key classes such as collections (`ArrayList`, `HashMap` etc.), exceptions (`IllegalArgumentException` etc.) and a few others (`StringBuilder`, `Comparator`) are now defined under the `kotlin` package. On the JVM, the names are type aliases for the corresponding JDK classes, and on the JS, the classes are implemented in the Kotlin standard library.

Better code generation

JavaScript backend now generates more statically checkable code, which is friendlier to JS code processing tools, like minifiers, optimisers, linters, etc.

The external modifier

If you need to access a class implemented in JavaScript from Kotlin in a typesafe way, you can write a Kotlin declaration using the `external` modifier. (In Kotlin 1.0, the `@native` annotation was used instead.) Unlike the JVM target, the JS one permits to use external modifier with classes and properties. For example, here's how you can declare the DOM `Node` class:

```
external class Node {
    val firstChild: Node

    fun appendChild(child: Node): Node

    fun removeChild(child: Node): Node

    // etc
}
```

Improved import handling

You can now describe declarations which should be imported from JavaScript modules more precisely. If you add the `@JsModule("<module-name>")` annotation on an external declaration it will be properly imported to a module system (either CommonJS or AMD) during the compilation. For example, with CommonJS the declaration will be imported via `require(...)` function. Additionally, if you want to import a declaration either as a module or as a global JavaScript object, you can use the `@JsNonModule` annotation.

For example, here's how you can import JQuery into a Kotlin module:

```
external interface JQuery {
    fun toggle(duration: Int = definedExternally): JQuery
    fun click(handler: (Event) -> Unit): JQuery
}

@JsModule("jquery")
@JsNonModule
@JsName("$")
external fun jquery(selector: String): JQuery
```

In this case, JQuery will be imported as a module named `jquery`. Alternatively, it can be used as a `$`-object, depending on what module system Kotlin compiler is configured to use.

You can use these declarations in your application like this:

```
fun main(args: Array<String>) {
    jquery(".toggle-button").click {
        jquery(".toggle-panel").toggle(300)
    }
}
```

What's New in Kotlin 1.2

Table of Contents

- [Multiplatform projects](#)
- [Other language features](#)
- [Standard library](#)
- [JVM backend](#)
- [JavaScript backend](#)

Multiplatform Projects (experimental)

Multiplatform projects are a new **experimental** feature in Kotlin 1.2, allowing you to reuse code between target platforms supported by Kotlin – JVM, JavaScript and (in the future) Native. In a multiplatform project, you have three kinds of modules:

- A *common* module contains code that is not specific to any platform, as well as declarations without implementation of platform-dependent APIs.
- A *platform* module contains implementations of platform-dependent declarations in the common module for a specific platform, as well as other platform-dependent code.
- A regular module targets a specific platform and can either be a dependency of platform modules or depend on platform modules.

When you compile a multiplatform project for a specific platform, the code for both the common and platform-specific parts is generated.

A key feature of the multiplatform project support is the possibility to express dependencies of common code on platform-specific parts through **expected and actual declarations**. An expected declaration specifies an API (class, interface, annotation, top-level declaration etc.). An actual declaration is either a platform-dependent implementation of the API or a typealias referring to an existing implementation of the API in an external library. Here's an example:

In common code:

```
// expected platform-specific API:
expect fun hello(world: String): String

fun greet() {
    // usage of the expected API:
    val greeting = hello("multi-platform world")
    println(greeting)
}

expect class URL(spec: String) {
    open fun getHost(): String
    open fun getPath(): String
}
```

In JVM platform code:

```
actual fun hello(world: String): String =
    "Hello, $world, on the JVM platform!"

// using existing platform-specific implementation:
actual typealias URL = java.net.URL
```

See the [documentation](#) for details and steps to build a multiplatform project.

Other Language Features

Array literals in annotations

Starting with Kotlin 1.2, array arguments for annotations can be passed with the new array literal syntax instead of the `arrayOf` function:

```
@CacheConfig(cacheNames = ["books", "default"])
public class BookRepositoryImpl {
    // ...
}
```

The array literal syntax is constrained to annotation arguments.

Lateinit top-level properties and local variables

The `lateinit` modifier can now be used on top-level properties and local variables. The latter can be used, for example, when a lambda passed as a constructor argument to one object refers to another object which has to be defined later:

```
class Node<T>(val value: T, val next: () -> Node<T>)

fun main(args: Array<String>) {
    // A cycle of three nodes:
    lateinit var third: Node<Int>

    val second = Node(2, next = { third })
    val first = Node(1, next = { second })

    third = Node(3, next = { first })

    val nodes = generateSequence(first) { it.next() }
    println("Values in the cycle: ${nodes.take(7).joinToString { it.value.toString() }}, ...")
}
```

Checking whether a lateinit var is initialized

You can now check whether a `lateinit` var has been initialized using `isInitialized` on the property reference:

```
println("isInitialized before assignment: " + this::lateinitVar.isInitialized)
lateinitVar = "value"
println("isInitialized after assignment: " + this::lateinitVar.isInitialized)
```

Inline functions with default functional parameters

Inline functions are now allowed to have default values for their inlined functional parameters:

```
inline fun <E> Iterable<E>.strings(transform: (E) -> String = { it.toString() }) =
    map { transform(it) }

val defaultStrings = listOf(1, 2, 3).strings()
val customStrings = listOf(1, 2, 3).strings { "($it)" }
```

Information from explicit casts is used for type inference

The Kotlin compiler can now use information from type casts in type inference. If you're calling a generic method that returns a type parameter `T` and casting the return value to a specific type `Foo`, the compiler now understands that `T` for this call needs to be bound to the type `Foo`.

This is particularly important for Android developers, since the compiler can now correctly analyze generic `findViewById` calls in Android API level 26:

```
val button = findViewById(R.id.button) as Button
```

Smart cast improvements

When a variable is assigned from a safe call expression and checked for null, the smart cast is now applied to the safe call receiver as well:

```
val firstChar = (s as? CharSequence)?.firstOrNull()
if (firstChar != null)
    return s.count { it == firstChar } // s: Any is smart cast to CharSequence

val firstItem = (s as? Iterable<*>)?.firstOrNull()
if (firstItem != null)
    return s.count { it == firstItem } // s: Any is smart cast to Iterable<*>
```

Also, smart casts in a lambda are now allowed for local variables that are only modified before the lambda:

```
val flag = args.size == 0
var x: String? = null
if (flag) x = "Yahoo!"

run {
    if (x != null) {
        println(x.length) // x is smart cast to String
    }
}
```

Support for `::foo` as a shorthand for `this::foo`

A bound callable reference to a member of `this` can now be written without explicit receiver, `::foo` instead of `this::foo`. This also makes callable references more convenient to use in lambdas where you refer to a member of the outer receiver.

Breaking change: sound smart casts after try blocks

Earlier, Kotlin used assignments made inside a `try` block for smart casts after the block, which could break type- and null-safety and lead to runtime failures. This release fixes this issue, making the smart casts more strict, but breaking some code that relied on such smart casts.

To switch to the old smart casts behavior, pass the fallback flag `-Xlegacy-smart-cast-after-try` as the compiler argument. It will become deprecated in Kotlin 1.3.

Deprecation: data classes overriding copy

When a data class derived from a type that already had the `copy` function with the same signature, the `copy` implementation generated for the data class used the defaults from the supertype, leading to counter-intuitive behavior, or failed at runtime if there were no default parameters in the supertype.

Inheritance that leads to a `copy` conflict has become deprecated with a warning in Kotlin 1.2 and will be an error in Kotlin 1.3.

Deprecation: nested types in enum entries

Inside enum entries, defining a nested type that is not an `inner class` has been deprecated due to issues in the initialization logic. This causes a warning in Kotlin 1.2 and will become an error in Kotlin 1.3.

Deprecation: single named argument for vararg

For consistency with array literals in annotations, passing a single item for a vararg parameter in the named form (`foo(items = i)`) has been deprecated. Please use the spread operator with the corresponding array factory functions:

```
foo(items = *intArrayOf(1))
```

There is an optimization that removes redundant arrays creation in such cases, which prevents performance degradation. The single-argument form produces warnings in Kotlin 1.2 and is to be dropped in Kotlin 1.3.

Deprecation: inner classes of generic classes extending Throwable

Inner classes of generic types that inherit from `Throwable` could violate type-safety in a throw-catch scenario and thus have been deprecated, with a warning in Kotlin 1.2 and an error in Kotlin 1.3.

Deprecation: mutating backing field of a read-only property

Mutating the backing field of a read-only property by assigning `field = ...` in the custom getter has been deprecated, with a warning in Kotlin 1.2 and an error in Kotlin 1.3.

Standard Library

Kotlin standard library artifacts and split packages

The Kotlin standard library is now fully compatible with the Java 9 module system, which forbids split packages (multiple jar files declaring classes in the same package). In order to support that, new artifacts `kotlin-stdlib-jdk7` and `kotlin-stdlib-jdk8` are introduced, which replace the old `kotlin-stdlib-jre7` and `kotlin-stdlib-jre8`.

The declarations in the new artifacts are visible under the same package names from the Kotlin point of view, but have different package names for Java. Therefore, switching to the new artifacts will not require any changes to your source code.

Another change made to ensure compatibility with the new module system is removing the deprecated declarations in the `kotlin.reflect` package from the `kotlin-reflect` library. If you were using them, you need to switch to using the declarations in the `kotlin.reflect.full` package, which is supported since Kotlin 1.1.

windowed, chunked, zipWithNext

New extensions for `Iterable<T>`, `Sequence<T>`, and `CharSequence` cover such use cases as buffering or batch processing (`chunked`), sliding window and computing sliding average (`windowed`), and processing pairs of subsequent items (`zipWithNext`):

```
val items = (1..9).map { it * it }

val chunkedIntoLists = items.chunked(4)
val points3d = items.chunked(3) { (x, y, z) -> Triple(x, y, z) }
val windowed = items.windowed(4)
val slidingAverage = items.windowed(4) { it.average() }
val pairwiseDifferences = items.zipWithNext { a, b -> b - a }
```

fill, replaceAll, shuffle/shuffled

A set of extension functions was added for manipulating lists: `fill`, `replaceAll` and `shuffle` for `MutableList`, and `shuffled` for read-only `List`:

```
val items = (1..5).toMutableList()

items.shuffle()
println("Shuffled items: $items")

items.replaceAll { it * 2 }
println("Items doubled: $items")

items.fill(5)
println("Items filled with 5: $items")
```

Math operations in kotlin-stdlib

Satisfying the longstanding request, Kotlin 1.2 adds the `kotlin.math` API for math operations that is common for JVM and JS and contains the following:

- Constants: `PI` and `E`;
- Trigonometric: `cos`, `sin`, `tan` and inverse of them: `acos`, `asin`, `atan`, `atan2`;
- Hyperbolic: `cosh`, `sinh`, `tanh` and their inverse: `acosh`, `asinh`, `atanh`;
- Exponentiation: `pow` (an extension function), `sqrt`, `hypot`, `exp`, `expm1`;
- Logarithms: `log`, `log2`, `log10`, `ln`, `ln1p`;
- Rounding:
 - `ceil`, `floor`, `truncate`, `round` (half to even) functions;
 - `roundToInt`, `roundToLong` (half to integer) extension functions;
- Sign and absolute value:
 - `abs` and `sign` functions;
 - `absoluteValue` and `sign` extension properties;
 - `withSign` extension function;
- `max` and `min` of two values;
- Binary representation:
 - `ulp` extension property;
 - `nextUp`, `nextDown`, `nextTowards` extension functions;
 - `toBits`, `toRawBits`, `Double.fromBits` (these are in the `kotlin` package).

The same set of functions (but without constants) is also available for `Float` arguments.

Operators and conversions for `BigInteger` and `BigDecimal`

Kotlin 1.2 introduces a set of functions for operating with `BigInteger` and `BigDecimal` and creating them from other numeric types. These are:

- `toBigInteger` for `Int` and `Long`;
- `toBigDecimal` for `Int`, `Long`, `Float`, `Double`, and `BigInteger`;
- Arithmetic and bitwise operator functions:
 - Binary operators `+`, `-`, `*`, `/`, `%` and infix functions `and`, `or`, `xor`, `shl`, `shr`;
 - Unary operators `-`, `++`, `--`, and a function `inv`.

Floating point to bits conversions

New functions were added for converting `Double` and `Float` to and from their bit representations:

- `toBits` and `toRawBits` returning `Long` for `Double` and `Int` for `Float`;
- `Double.fromBits` and `Float.fromBits` for creating floating point numbers from the bit representation.

Regex is now serializable

The `kotlin.text.Regex` class has become `Serializable` and can now be used in serializable hierarchies.

`Closeable.use` calls `Throwable.addSuppressed` if available

The `Closeable.use` function calls `Throwable.addSuppressed` when an exception is thrown during closing the resource after some other exception.

To enable this behavior you need to have `kotlin-stdlib-jdk7` in your dependencies.

JVM Backend

Constructor calls normalization

Ever since version 1.0, Kotlin supported expressions with complex control flow, such as try-catch expressions and inline function calls. Such code is valid according to the Java Virtual Machine specification. Unfortunately, some bytecode processing tools do not handle such code quite well when such expressions are present in the arguments of constructor calls.

To mitigate this problem for the users of such bytecode processing tools, we've added a command-line option (`-Xnormalize-constructor-calls=MODE`) that tells the compiler to generate more Java-like bytecode for such constructs. Here `MODE` is one of:

- `disable` (default) – generate bytecode in the same way as in Kotlin 1.0 and 1.1;
- `enable` – generate Java-like bytecode for constructor calls. This can change the order in which the classes are loaded and initialized;
- `preserve-class-initialization` – generate Java-like bytecode for constructor calls, ensuring that the class initialization order is preserved. This can affect overall performance of your application; use it only if you have some complex state shared between multiple classes and updated on class initialization.

The “manual” workaround is to store the values of sub-expressions with control flow in variables, instead of evaluating them directly inside the call arguments. It's similar to `-Xnormalize-constructor-calls=enable`.

Java-default method calls

Before Kotlin 1.2, interface members overriding Java-default methods while targeting JVM 1.6 produced a warning on super calls: `Super calls to Java default methods are deprecated in JVM target 1.6. Recompile with '-jvm-target 1.8'`. In Kotlin 1.2, there's an **error** instead, thus requiring any such code to be compiled with JVM target 1.8.

Breaking change: consistent behavior of `x.equals(null)` for platform types

Calling `x.equals(null)` on a platform type that is mapped to a Java primitive (`Int!` , `Boolean!` , `Short!` , `Long!` , `Float!` , `Double!` , `Char!`) incorrectly returned `true` when `x` was null. Starting with Kotlin 1.2, calling `x.equals(...)` on a null value of a platform type **throws an NPE** (but `x == ...` does not).

To return to the pre-1.2 behavior, pass the flag `-Xno-exception-on-explicit-equals-for-boxed-null` to the compiler.

Breaking change: fix for platform null escaping through an inlined extension receiver

Inline extension functions that were called on a null value of a platform type did not check the receiver for null and would thus allow null to escape into the other code. Kotlin 1.2 forces this check at the call sites, throwing an exception if the receiver is null.

To switch to the old behavior, pass the fallback flag `-Xno-receiver-assertions` to the compiler.

JavaScript Backend

TypedArrays support enabled by default

The JS typed arrays support that translates Kotlin primitive arrays, such as `IntArray` , `DoubleArray` , into [JavaScript typed arrays](#), that was previously an opt-in feature, has been enabled by default.

Tools

Warnings as errors

The compiler now provides an option to treat all warnings as errors. Use `-Werror` on the command line, or the following Gradle snippet:

```
compileKotlin {
    kotlinOptions.allWarningsAsErrors = true
}
```


Getting Started

Basic Syntax

Defining packages

Package specification should be at the top of the source file:

```
package my.demo

import java.util.*

// ...
```

It is not required to match directories and packages: source files can be placed arbitrarily in the file system.

See [Packages](#).

Defining functions

Function having two `Int` parameters with `Int` return type:

```
fun sum(a: Int, b: Int): Int {
    return a + b
}
```

Function with an expression body and inferred return type:

```
fun sum(a: Int, b: Int) = a + b
```

Function returning no meaningful value:

```
fun printSum(a: Int, b: Int): Unit {
    println("sum of $a and $b is ${a + b}")
}
```

`Unit` return type can be omitted:

```
fun printSum(a: Int, b: Int) {
    println("sum of $a and $b is ${a + b}")
}
```

See [Functions](#).

Defining variables

Assign-once (read-only) local variable:

```
val a: Int = 1 // immediate assignment
val b = 2      // `Int` type is inferred
val c: Int     // Type required when no initializer is provided
c = 3          // deferred assignment
```

Mutable variable:

```
var x = 5 // `Int` type is inferred
x += 1
```

Top-level variables:

```
val PI = 3.14
var x = 0

fun incrementX() {
    x += 1
}
```

See also [Properties And Fields](#).

Comments

Just like Java and JavaScript, Kotlin supports end-of-line and block comments.

```
// This is an end-of-line comment

/* This is a block comment
   on multiple lines. */
```

Unlike Java, block comments in Kotlin can be nested.

See [Documenting Kotlin Code](#) for information on the documentation comment syntax.

Using string templates

```
var a = 1
// simple name in template:
val s1 = "a is $a"

a = 2
// arbitrary expression in template:
val s2 = "${s1.replace("is", "was")}, but now is $a"
```

See [String templates](#).

Using conditional expressions

```
fun maxOf(a: Int, b: Int): Int {
    if (a > b) {
        return a
    } else {
        return b
    }
}
```

Using `if` as an expression:

```
fun maxOf(a: Int, b: Int) = if (a > b) a else b
```

See [if-expressions](#).

Using nullable values and checking for `null`

A reference must be explicitly marked as nullable when `null` value is possible.

Return `null` if `str` does not hold an integer:

```
fun parseInt(str: String): Int? {  
    // ...  
}
```

Use a function returning nullable value:

```
fun printProduct(arg1: String, arg2: String) {  
    val x = parseInt(arg1)  
    val y = parseInt(arg2)  
  
    // Using `x * y` yields error because they may hold nulls.  
    if (x != null && y != null) {  
        // x and y are automatically cast to non-nullable after null check  
        println(x * y)  
    }  
    else {  
        println("either '$arg1' or '$arg2' is not a number")  
    }  
}
```

or

```
// ...  
if (x == null) {  
    println("Wrong number format in arg1: '$arg1'")  
    return  
}  
if (y == null) {  
    println("Wrong number format in arg2: '$arg2'")  
    return  
}  
  
// x and y are automatically cast to non-nullable after null check  
println(x * y)
```

See [Null-safety](#).

Using type checks and automatic casts

The `is` operator checks if an expression is an instance of a type. If an immutable local variable or property is checked for a specific type, there's no need to cast it explicitly:

```
fun getStringLength(obj: Any): Int? {
    if (obj is String) {
        // `obj` is automatically cast to `String` in this branch
        return obj.length
    }

    // `obj` is still of type `Any` outside of the type-checked branch
    return null
}
```

or

```
fun getStringLength(obj: Any): Int? {
    if (obj !is String) return null

    // `obj` is automatically cast to `String` in this branch
    return obj.length
}
```

or even

```
fun getStringLength(obj: Any): Int? {
    // `obj` is automatically cast to `String` on the right-hand side of `&&`
    if (obj is String && obj.length > 0) {
        return obj.length
    }

    return null
}
```

See [Classes](#) and [Type casts](#).

Using a for loop

```
val items = listOf("apple", "banana", "kiwifruit")
for (item in items) {
    println(item)
}
```

or

```
val items = listOf("apple", "banana", "kiwifruit")
for (index in items.indices) {
    println("item at $index is ${items[index]}")
}
```

See [for loop](#).

Using a while loop

```
val items = listOf("apple", "banana", "kiwifruit")
var index = 0
while (index < items.size) {
    println("item at $index is ${items[index]}")
    index++
}
```

See [while loop](#).

Using when expression

```
fun describe(obj: Any): String =
    when (obj) {
        1          -> "One"
        "Hello"    -> "Greeting"
        is Long    -> "Long"
        !is String -> "Not a string"
        else       -> "Unknown"
    }
```

See [when expression](#).

Using ranges

Check if a number is within a range using [in](#) operator:

```
val x = 10
val y = 9
if (x in 1..y+1) {
    println("fits in range")
}
```

Check if a number is out of range:

```
val list = listOf("a", "b", "c")

if (-1 !in 0..list.lastIndex) {
    println("-1 is out of range")
}
if (list.size !in list.indices) {
    println("list size is out of valid list indices range too")
}
```

Iterating over a range:

```
for (x in 1..5) {
    print(x)
}
```

or over a progression:

```
for (x in 1..10 step 2) {
    print(x)
}
println()
for (x in 9 downTo 0 step 3) {
    print(x)
}
```

See [Ranges](#).

Using collections

Iterating over a collection:

```
for (item in items) {
    println(item)
}
```

Checking if a collection contains an object using [in](#) operator:

```
when {  
    "orange" in items -> println("juicy")  
    "apple" in items -> println("apple is fine too")  
}
```

Using lambda expressions to filter and map collections:

```
val fruits = listOf("banana", "avocado", "apple", "kiwifruit")  
fruits  
    .filter { it.startsWith("a") }  
    .sortedBy { it }  
    .map { it.toUpperCase() }  
    .forEach { println(it) }
```

See [Higher-order functions and Lambdas](#).

Creating basic classes and their instances:

```
val rectangle = Rectangle(5.0, 2.0) //no 'new' keyword required  
val triangle = Triangle(3.0, 4.0, 5.0)
```

See [classes](#) and [objects and instances](#).

Idioms

A collection of random and frequently used idioms in Kotlin. If you have a favorite idiom, contribute it by sending a pull request.

Creating DTOs (POJOs/POCOs)

```
data class Customer(val name: String, val email: String)
```

provides a `Customer` class with the following functionality:

- getters (and setters in case of `vars`) for all properties
- `equals()`
- `hashCode()`
- `toString()`
- `copy()`
- `component1()`, `component2()`, ..., for all properties (see [Data classes](#))

Default values for function parameters

```
fun foo(a: Int = 0, b: String = "") { ... }
```

Filtering a list

```
val positives = list.filter { x -> x > 0 }
```

Or alternatively, even shorter:

```
val positives = list.filter { it > 0 }
```

String Interpolation

```
println("Name $name")
```

Instance Checks

```
when (x) {  
    is Foo -> ...  
    is Bar -> ...  
    else   -> ...  
}
```

Traversing a map/list of pairs

```
for ((k, v) in map) {  
    println("$k -> $v")  
}
```

`k`, `v` can be called anything.

Using ranges

```

for (i in 1..100) { ... } // closed range: includes 100
for (i in 1 until 100) { ... } // half-open range: does not include 100
for (x in 2..10 step 2) { ... }
for (x in 10 downTo 1) { ... }
if (x in 1..10) { ... }

```

Read-only list

```

val list = listOf("a", "b", "c")

```

Read-only map

```

val map = mapOf("a" to 1, "b" to 2, "c" to 3)

```

Accessing a map

```

println(map["key"])
map["key"] = value

```

Lazy property

```

val p: String by lazy {
    // compute the string
}

```

Extension Functions

```

fun String.spaceToCamelCase() { ... }

"Convert this to camelcase".spaceToCamelCase()

```

Creating a singleton

```

object Resource {
    val name = "Name"
}

```

If not null shorthand

```

val files = File("Test").listFiles()

println(files?.size)

```

If not null and else shorthand

```

val files = File("Test").listFiles()

println(files?.size ?: "empty")

```

Executing a statement if null


```
val values = ...
val email = values["email"] ?: throw IllegalStateException("Email is missing!")
```

Get first item of a possibly empty collection

```
val emails = ... // might be empty
val mainEmail = emails.firstOrNull() ?: ""
```

Execute if not null

```
val value = ...

value?.let {
    ... // execute this block if not null
}
```

Map nullable value if not null

```
val value = ...

val mapped = value?.let { transformValue(it) } ?: defaultValueIfValueIsNull
```

Return on when statement

```
fun transform(color: String): Int {
    return when (color) {
        "Red" -> 0
        "Green" -> 1
        "Blue" -> 2
        else -> throw IllegalArgumentException("Invalid color param value")
    }
}
```

'try/catch' expression

```
fun test() {
    val result = try {
        count()
    } catch (e: ArithmeticException) {
        throw IllegalStateException(e)
    }

    // Working with result
}
```

'if' expression

```
fun foo(param: Int) {
    val result = if (param == 1) {
        "one"
    } else if (param == 2) {
        "two"
    } else {
        "three"
    }
}
```

Builder-style usage of methods that return Unit

```
fun arrayOfMinusOnes(size: Int): IntArray {  
    return IntArray(size).apply { fill(-1) }  
}
```

Single-expression functions

```
fun theAnswer() = 42
```

This is equivalent to

```
fun theAnswer(): Int {  
    return 42  
}
```

This can be effectively combined with other idioms, leading to shorter code. E.g. with the [when](#)-expression:

```
fun transform(color: String): Int = when (color) {  
    "Red" -> 0  
    "Green" -> 1  
    "Blue" -> 2  
    else -> throw IllegalArgumentException("Invalid color param value")  
}
```

Calling multiple methods on an object instance ('with')

```
class Turtle {  
    fun penDown()  
    fun penUp()  
    fun turn(degrees: Double)  
    fun forward(pixels: Double)  
}  
  
val myTurtle = Turtle()  
with(myTurtle) { //draw a 100 pix square  
    penDown()  
    for(i in 1..4) {  
        forward(100.0)  
        turn(90.0)  
    }  
    penUp()  
}
```

Java 7's try with resources

```
val stream = Files.newInputStream(Paths.get("/some/file.txt"))  
stream.buffered().reader().use { reader ->  
    println(reader.readText())  
}
```

Convenient form for a generic function that requires the generic type information

```
// public final class Gson {  
//     ...  
//     public <T> T fromJson(JsonElement json, Class<T> classOfT) throws JsonSyntaxException {  
//         ...  
  
inline fun <reified T: Any> Gson.fromJson(json: JsonElement): T = this.fromJson(json, T::class.java)
```

Consuming a nullable Boolean

```
val b: Boolean? = ...  
if (b == true) {  
    ...  
} else {  
    // `b` is false or null  
}
```

Coding Conventions

This page contains the current coding style for the Kotlin language.

- [Source code organization](#)
- [Naming rules](#)
- [Formatting](#)
- [Documentation comments](#)
- [Avoiding redundant constructs](#)
- [Idiomatic use of language features](#)
- [Coding conventions for libraries](#)

Applying the style guide

To configure the IntelliJ formatter according to this style guide, please install Kotlin plugin version 1.2.20 or newer, go to Settings | Editor | Code Style | Kotlin, click on "Set from..." link in the upper right corner, and select "Predefined style / Kotlin style guide" from the menu.

To verify that your code is formatted according to the style guide, go to the inspection settings and enable the "Kotlin | Style issues | File is not formatted according to project settings" inspection. Additional inspections that verify other issues described in the style guide (such as naming conventions) are enabled by default.

Source code organization

Directory structure

In mixed-language projects, Kotlin source files should reside in the same source root as the Java source files, and follow the same directory structure (each file should be stored in the directory corresponding to each package statement).

In pure Kotlin projects, the recommended directory structure is to follow the package structure with the common root package omitted (e.g. if all the code in the project is in the "org.example.kotlin" package and its subpackages, files with the "org.example.kotlin" package should be placed directly under the source root, and files in "org.example.kotlin.foo.bar" should be in the "foo/bar" subdirectory of the source root).

Source file names

If a Kotlin file contains a single class (potentially with related top-level declarations), its name should be the same as the name of the class, with the .kt extension appended. If a file contains multiple classes, or only top-level declarations, choose a name describing what the file contains, and name the file accordingly. Use camel humps with an uppercase first letter (e.g. `ProcessDeclarations.kt`).

The name of the file should describe what the code in the file does. Therefore, you should avoid using meaningless words such as "Util" in file names.

Source file organization

Placing multiple declarations (classes, top-level functions or properties) in the same Kotlin source file is encouraged as long as these declarations are closely related to each other semantically and the file size remains reasonable (not exceeding a few hundred lines).

In particular, when defining extension functions for a class which are relevant for all clients of this class, put them in the same file where the class itself is defined. When defining extension functions that make sense only for a specific client, put them next to the code of that client. Do not create files just to hold "all extensions of Foo".

Class layout

Generally, the contents of a class is sorted in the following order:

- Property declarations and initializer blocks
- Secondary constructors
- Method declarations

— Companion object

Do not sort the method declarations alphabetically or by visibility, and do not separate regular methods from extension methods. Instead, put related stuff together, so that someone reading the class from top to bottom would be able to follow the logic of what's happening. Choose an order (either higher-level stuff first, or vice versa) and stick to it.

Put nested classes next to the code that uses those classes. If the classes are intended to be used externally and aren't referenced inside the class, put them in the end, after the companion object.

Interface implementation layout

When implementing an interface, keep the implementing members in the same order as members of the interface (if necessary, interspersed with additional private methods used for the implementation)

Overload layout

Always put overloads next to each other in a class.

Naming rules

Kotlin follows the Java naming conventions. In particular:

Names of packages are always lower case and do not use underscores (`org.example.myproject`). Using multi-word names is generally discouraged, but if you do need to use multiple words, you can either simply concatenate them together or use camel humps (`org.example.myProject`).

Names of classes and objects start with an upper case letter and use camel humps:

```
open class DeclarationProcessor { ... }

object EmptyDeclarationProcessor : DeclarationProcessor() { ... }
```

Function names

Names of functions, properties and local variables start with a lower case letter and use camel humps and no underscores:

```
fun processDeclarations() { ... }
var declarationCount = ...
```

Exception: factory functions used to create instances of classes can have the same name as the class being created:

```
abstract class Foo { ... }

class FooImpl : Foo { ... }

fun Foo(): Foo { return FooImpl(...) }
```

Names for test methods

In tests (and only in tests), it's acceptable to use method names with spaces enclosed in backticks. (Note that such method names are currently not supported by the Android runtime.) Underscores in method names are also allowed in test code.

```
class MyTestCase {
    @Test fun `ensure everything works`() { ... }

    @Test fun ensureEverythingWorks_onAndroid() { ... }
}
```

Property names

Names of constants (properties marked with `const`, or top-level or object `val` properties with no custom `get` function that hold deeply immutable data) should use uppercase underscore-separated names:

```
const val MAX_COUNT = 8
val USER_NAME_FIELD = "UserName"
```

Names of top-level or object properties which hold objects with behavior or mutable data should use regular camel-hump names:

```
val mutableCollection: MutableSet<String> = HashSet()
```

Names of properties holding references to singleton objects can use the same naming style as `object` declarations:

```
val PersonComparator: Comparator<Person> = ...
```

For enum constants, it's OK to use either uppercase underscore-separated names (`enum class Color { RED, GREEN }`) or regular camel-humps names starting with an uppercase letter, depending on the usage.

Names for backing properties

If a class has two properties which are conceptually the same but one is part of a public API and another is an implementation detail, use an underscore as the prefix for the name of the private property:

```
class C {
    private val _elementList = mutableListOf<Element>()

    val elementList: List<Element>
        get() = _elementList
}
```

Choosing good names

The name of a class is usually a noun or a noun phrase explaining what the class *is*: `List`, `PersonReader`.

The name of a method is usually a verb or a verb phrase saying what the method *does*: `close`, `readPersons`. The name should also suggest if the method is mutating the object or returning a new one. For instance `sort` is sorting a collection in place, while `sorted` is returning a sorted copy of the collection.

The names should make it clear what the purpose of the entity is, so it's best to avoid using meaningless words (`Manager`, `Wrapper` etc.) in names.

When using an acronym as part of a declaration name, capitalize it if it consists of two letters (`IOStream`); capitalize only the first letter if it is longer (`XmlFormatter`, `HttpInputStream`).

Formatting

In most cases, Kotlin follows the Java coding conventions.

Use 4 spaces for indentation. Do not use tabs.

For curly braces, put the opening brace in the end of the line where the construct begins, and the closing brace on a separate line aligned vertically with the opening construct.

```
if (elements != null) {
    for (element in elements) {
        // ...
    }
}
```

(Note: In Kotlin, semicolons are optional, and therefore line breaks are significant. The language design assumes Java-style braces, and you may encounter surprising behavior if you try to use a different formatting style.)

Horizontal whitespace

Put spaces around binary operators (`a + b`). Exception: don't put spaces around the "range to" operator (`0..i`).

Do not put spaces around unary operators (`a++`)

Put spaces between control flow keywords (`if` , `when` , `for` and `while`) and the corresponding opening parenthesis.

Do not put a space before an opening parenthesis in a primary constructor declaration, method declaration or method call.

```
class A(val x: Int)

fun foo(x: Int) { ... }

fun bar() {
    foo(1)
}
```

Never put a space after `(` , `[` , or before `]` , `)` .

Never put a space around `.` or `?.` : `foo.bar().filter { it > 2 }.joinToString()` , `foo?.bar()`

Put a space after `//` : `// This is a comment`

Do not put spaces around angle brackets used to specify type parameters: `class Map<K, V> { ... }`

Do not put spaces around `::` : `Foo::class` , `String::length`

Do not put a space before `?` used to mark a nullable type: `String?`

As a general rule, avoid horizontal alignment of any kind. Renaming an identifier to a name with a different length should not affect the formatting of either the declaration or any of the usages.

Colon

Put a space before `:` in the following cases:

- when it's used to separate a type and a supertype;
- when delegating to a superclass constructor or a different constructor of the same class;
- after the `object` keyword.

Don't put a space before `:` when it separates a declaration and its type.

Always put a space after `:` .

```
abstract class Foo<out T : Any> : IFoo {
    abstract fun foo(a: Int): T
}

class FooImpl : Foo() {
    constructor(x: String) : this(x) { ... }

    val x = object : IFoo { ... }
}
```

Class header formatting

Classes with a few primary constructor parameters can be written in a single line:

```
class Person(id: Int, name: String)
```

Classes with longer headers should be formatted so that each primary constructor parameter is in a separate line with indentation. Also, the closing parenthesis should be on a new line. If we use inheritance, then the superclass constructor call or list of implemented interfaces should be located on the same line as the parenthesis:

```
class Person(  
    id: Int,  
    name: String,  
    surname: String  
) : Human(id, name) { ... }
```

For multiple interfaces, the superclass constructor call should be located first and then each interface should be located in a different line:

```
class Person(  
    id: Int,  
    name: String,  
    surname: String  
) : Human(id, name),  
    KotlinMaker { ... }
```

For classes with a long supertype list, put a line break after the colon and align all supertype names vertically:

```
class MyFavouriteVeryLongClassHolder :  
    MyLongHolder<MyFavouriteVeryLongClass>(),  
    SomeOtherInterface,  
    AndAnotherOne {  
  
    fun foo() { ... }  
}
```

To clearly separate the class header and body when the class header is long, either put a blank line following the class header (as in the example above), or put the opening curly brace on a separate line:

```
class MyFavouriteVeryLongClassHolder :  
    MyLongHolder<MyFavouriteVeryLongClass>(),  
    SomeOtherInterface,  
    AndAnotherOne {  
  
    fun foo() { ... }  
}
```

Use regular indent (4 spaces) for constructor parameters.

Rationale: This ensures that properties declared in the primary constructor have the same indentation as properties declared in the body of a class.

Modifiers

If a declaration has multiple modifiers, always put them in the following order:


```
public / protected / private / internal
expect / actual
final / open / abstract / sealed / const
external
override
lateinit
tailrec
vararg
suspend
inner
enum / annotation
companion
inline
infix
operator
data
```

Place all annotations before modifiers:

```
@Named("Foo")
private val foo: Foo
```

Unless you're working on a library, omit redundant modifiers (e.g. `public`).

Annotation formatting

Annotations are typically placed on separate lines, before the declaration to which they are attached, and with the same indentation:

```
@Target(AnnotationTarget.PROPERTY)
annotation class JsonExclude
```

Annotations without arguments may be placed on the same line:

```
@JsonExclude @JvmField
var x: String
```

A single annotation without arguments may be placed on the same line as the corresponding declaration:

```
@Test fun foo() { ... }
```

File annotations

File annotations are placed after the file comment (if any), before the `package` statement, and are separated from `package` with a blank line (to emphasize the fact that they target the file and not the package).

```
/** License, copyright and whatever */
@file:JvmName("FooBar")

package foo.bar
```

Function formatting

If the function signature doesn't fit on a single line, use the following syntax:

```
fun longMethodName(
    argument: ArgumentType = defaultValue,
    argument2: AnotherArgumentType
): ReturnType {
    // body
}
```

Use regular indent (4 spaces) for function parameters.

Rationale: Consistency with constructor parameters

Prefer using an expression body for functions with the body consisting of a single expression.

```
fun foo(): Int {      // bad
    return 1
}

fun foo() = 1         // good
```

Expression body formatting

If the function has an expression body that doesn't fit in the same line as the declaration, put the `=` sign on the first line. Indent the expression body by 4 spaces.

```
fun f(x: String) =
    x.length
```

Property formatting

For very simple read-only properties, consider one-line formatting:

```
val isEmpty: Boolean get() = size == 0
```

For more complex properties, always put `get` and `set` keywords on separate lines:

```
val foo: String
    get() { ... }
```

For properties with an initializer, if the initializer is long, add a line break after the equals sign and indent the initializer by four spaces:

```
private val defaultCharset: Charset? =
    EncodingRegistry.getInstance().getDefaultCharsetForPropertiesFiles(file)
```

Formatting control flow statements

If the condition of an `if` or `when` statement is multiline, always use curly braces around the body of the statement. Indent each subsequent line of the condition by 4 spaces relative to statement begin. Put the closing parentheses of the condition together with the opening curly brace on a separate line:

```
if (!component.isSyncing &&
    !hasAnyKotlinRuntimeInScope(module)
) {
    return createKotlinNotConfiguredPanel(module)
}
```

Rationale: Tidy alignment and clear separation of condition and statement body

Put the `else`, `catch`, `finally` keywords, as well as the `while` keyword of a do/while loop, on the same line as the preceding curly brace:

```
if (condition) {
    // body
} else {
    // else part
}

try {
    // body
} finally {
    // cleanup
}
```

In a `when` statement, if a branch is more than a single line, consider separating it from adjacent case blocks with a blank line:

```
private fun parsePropertyValue(propName: String, token: Token) {
    when (token) {
        is Token.ValueToken ->
            callback.visitValue(propName, token.value)

        Token.LBRACE -> { // ...
        }
    }
}
```

Put short branches on the same line as the condition, without braces.

```
when (foo) {
    true -> bar() // good
    false -> { baz() } // bad
}
```

Method call formatting

In long argument lists, put a line break after the opening parenthesis. Indent arguments by 4 spaces. Group multiple closely related arguments on the same line.

```
drawSquare(
    x = 10, y = 10,
    width = 100, height = 100,
    fill = true
)
```

Put spaces around the `=` sign separating the argument name and value.

Chained call wrapping

When wrapping chained calls, put the `.` character or the `?.` operator on the next line, with a single indent:

```
val anchor = owner
    ?.firstChild!!
    .siblings(forward = true)
    .dropWhile { it is PsiComment || it is PsiWhiteSpace }
```

The first call in the chain usually should have a line break before it, but it's OK to omit it if the code makes more sense that way

Lambda formatting

In lambda expressions, spaces should be used around the curly braces, as well as around the arrow which separates the parameters from the body. If a call takes a single lambda, it should be passed outside of parentheses whenever possible.

```
list.filter { it > 10 }
```

If assigning a label for a lambda, do not put a space between the label and the opening curly brace:

```
fun foo() {  
    ints.forEach lit@{  
        // ...  
    }  
}
```

When declaring parameter names in a multiline lambda, put the names on the first line, followed by the arrow and the newline:

```
appendCommaSeparated(properties) { prop ->  
    val propertyValue = prop.get(obj) // ...  
}
```

If the parameter list is too long to fit on a line, put the arrow on a separate line:

```
foo {  
    context: Context,  
    environment: Env  
    ->  
    context.configureEnv(environment)  
}
```

Documentation comments

For longer documentation comments, place the opening `/**` on a separate line and begin each subsequent line with an asterisk:

```
/**  
 * This is a documentation comment  
 * on multiple lines.  
 */
```

Short comments can be placed on a single line:

```
/** This is a short documentation comment. */
```

Generally, avoid using `@param` and `@return` tags. Instead, incorporate the description of parameters and return values directly into the documentation comment, and add links to parameters wherever they are mentioned. Use `@param` and `@return` only when a lengthy description is required which doesn't fit into the flow of the main text.

```
// Avoid doing this:

/**
 * Returns the absolute value of the given number.
 * @param number The number to return the absolute value for.
 * @return The absolute value.
 */
fun abs(number: Int) = ...

// Do this instead:

/**
 * Returns the absolute value of the given [number].
 */
fun abs(number: Int) = ...
```

Avoiding redundant constructs

In general, if a certain syntactic construction in Kotlin is optional and highlighted by the IDE as redundant, you should omit it in your code. Do not leave unnecessary syntactic elements in code just "for clarity".

Unit

If a function returns Unit, the return type should be omitted:

```
fun foo() { // ": Unit" is omitted here

}
```

Semicolons

Omit semicolons whenever possible.

String templates

Don't use curly braces when inserting a simple variable into a string template. Use curly braces only for longer expressions.

```
println("$name has ${children.size} children")
```

Idiomatic use of language features

Immutability

Prefer using immutable data to mutable. Always declare local variables and properties as `val` rather than `var` if they are not modified after initialization.

Always use immutable collection interfaces (`Collection`, `List`, `Set`, `Map`) to declare collections which are not mutated. When using factory functions to create collection instances, always use functions that return immutable collection types when possible:

```
// Bad: use of mutable collection type for value which will not be mutated
fun validateValue(actualValue: String, allowedValues: HashSet<String>) { ... }

// Good: immutable collection type used instead
fun validateValue(actualValue: String, allowedValues: Set<String>) { ... }

// Bad: arrayOf() returns Array<T>, which is a mutable collection type
val allowedValues = arrayOf("a", "b", "c")

// Good: listOf() returns List<T>
val allowedValues = listOf("a", "b", "c")
```

Default parameter values

Prefer declaring functions with default parameter values to declaring overloaded functions.

```
// Bad
fun foo() = foo("a")
fun foo(a: String) { ... }

// Good
fun foo(a: String = "a") { ... }
```

Type aliases

If you have a functional type or a type with type parameters which is used multiple times in a codebase, prefer defining a type alias for it:

```
typealias MouseClickHandler = (Any, MouseEvent) -> Unit
typealias PersonIndex = Map<String, Person>
```

Lambda parameters

In lambdas which are short and not nested, it's recommended to use the `it` convention instead of declaring the parameter explicitly. In nested lambdas with parameters, parameters should be always declared explicitly.

Returns in a lambda

Avoid using multiple labeled returns in a lambda. Consider restructuring the lambda so that it will have a single exit point. If that's not possible or not clear enough, consider converting the lambda into an anonymous function.

Do not use a labeled return for the last statement in a lambda.

Named arguments

Use the named argument syntax when a method takes multiple parameters of the same primitive type, or for parameters of `Boolean` type, unless the meaning of all parameters is absolutely clear from context.

```
drawSquare(x = 10, y = 10, width = 100, height = 100, fill = true)
```

Using conditional statements

Prefer using the expression form of `try`, `if` and `when`. Examples:

```

return if (x) foo() else bar()

return when(x) {
    0 -> "zero"
    else -> "nonzero"
}

```

The above is preferable to:

```

if (x)
    return foo()
else
    return bar()

when(x) {
    0 -> return "zero"
    else -> return "nonzero"
}

```

if versus when

Prefer using `if` for binary conditions instead of `when`. Instead of

```

when (x) {
    null -> ...
    else -> ...
}

```

use `if (x == null) ... else ...`

Prefer using `when` if there are three or more options.

Using nullable Boolean values in conditions

If you need to use a nullable `Boolean` in a conditional statement, use `if (value == true)` or `if (value == false)` checks.

Using loops

Prefer using higher-order functions (`filter`, `map` etc.) to loops. Exception: `forEach` (prefer using a regular `for` loop instead, unless the receiver of `forEach` is nullable or `forEach` is used as part of a longer call chain).

When making a choice between a complex expression using multiple higher-order functions and a loop, understand the cost of the operations being performed in each case and keep performance considerations in mind.

Loops on ranges

Use the `until` function to loop over an open range:

```

for (i in 0..n - 1) { ... } // bad
for (i in 0 until n) { ... } // good

```

Using strings

Prefer using string templates to string concatenation.

Prefer to use multiline strings instead of embedding `\n` escape sequences into regular string literals.

To maintain indentation in multiline strings, use `trimIndent` when the resulting string does not require any internal indentation, or `trimMargin` when internal indentation is required:

```

assertEquals(
    """
    Foo
    Bar
    """.trimIndent(),
    value
)

val a = """if(a > 1) {
    |     return a
    |}""".trimMargin()

```

Functions vs Properties

In some cases functions with no arguments might be interchangeable with read-only properties. Although the semantics are similar, there are some stylistic conventions on when to prefer one to another.

Prefer a property over a function when the underlying algorithm:

- does not throw
- is cheap to calculate (or cached on the first run)
- returns the same result over invocations if the object state hasn't changed

Using extension functions

Use extension functions liberally. Every time you have a function that works primarily on an object, consider making it an extension function accepting that object as a receiver. To minimize API pollution, restrict the visibility of extension functions as much as it makes sense. As necessary, use local extension functions, member extension functions, or top-level extension functions with private visibility.

Using infix functions

Declare a function as infix only when it works on two objects which play a similar role. Good examples: `and`, `to`, `zip`. Bad example: `add`.

Don't declare a method as infix if it mutates the receiver object.

Factory functions

If you declare a factory function for a class, avoid giving it the same name as the class itself. Prefer using a distinct name making it clear why the behavior of the factory function is special. Only if there is really no special semantics, you can use the same name as the class.

Example:

```

class Point(val x: Double, val y: Double) {
    companion object {
        fun fromPolar(angle: Double, radius: Double) = Point(...)
    }
}

```

If you have an object with multiple overloaded constructors that don't call different superclass constructors and can't be reduced to a single constructor with default argument values, prefer to replace the overloaded constructors with factory functions.

Platform types

A public function/method returning an expression of a platform type must declare its Kotlin type explicitly:

```

fun apiCall(): String = MyJavaApi.getProperty("name")

```


Any property (package-level or class-level) initialised with an expression of a platform type must declare its Kotlin type explicitly:

```
class Person {
    val name: String = MyJavaApi.getProperty("name")
}
```

A local value initialised with an expression of a platform type may or may not have a type declaration:

```
fun main(args: Array<String>) {
    val name = MyJavaApi.getProperty("name")
    println(name)
}
```

Using scope functions `apply`/`with`/`run`/`also`/`let`

Kotlin provides a variety of functions to execute a block of code in the context of a given object. To choose the correct function, consider the following:

- Are you calling methods on multiple objects in the block, or passing the instance of the context object as an argument? If you are, use one of the functions that allows you to access the context object as `it`, not `this` (`also` or `let`). Use `also` if the receiver is not used at all in the block.

```
// Context object is 'it'
class Baz {
    var currentBar: Bar?
    val observable: Observable

    val foo = createBar().also {
        currentBar = it           // Accessing property of Baz
        observable.registerCallback(it) // Passing context object as argument
    }
}

// Receiver not used in the block
val foo = createBar().also {
    LOG.info("Bar created")
}

// Context object is 'this'
class Baz {
    val foo: Bar = createBar().apply {
        color = RED    // Accessing only properties of Bar
        text = "Foo"
    }
}
```

- What should the result of the call be? If the result needs to be the context object, use `apply` or `also`. If you need to return a value from the block, use `with`, `let` or `run`.

```
// Return value is context object
class Baz {
    val foo: Bar = createBar().apply {
        color = RED    // Accessing only properties of Bar
        text = "Foo"
    }
}

// Return value is block result
class Baz {
    val foo: Bar = createNetworkConnection().let {
        loadBar()
    }
}
```

— Is the context object nullable, or is it evaluated as a result of a call chain? If it is, use `apply`, `let` or `run`. Otherwise, use `with` or `also`.

```
// Context object is nullable
person.email?.let { sendEmail(it) }

// Context object is non-null and accessible directly
with(person) {
    println("First name: $firstName, last name: $lastName")
}
```

Coding conventions for libraries

When writing libraries, it's recommended to follow an additional set of rules to ensure API stability:

- Always explicitly specify member visibility (to avoid accidentally exposing declarations as public API)
- Always explicitly specify function return types and property types (to avoid accidentally changing the return type when the implementation changes)
- Provide KDoc comments for all public members, with the exception of overrides that do not require any new documentation (to support generating documentation for the library)

Basics

Basic Types

In Kotlin, everything is an object in the sense that we can call member functions and properties on any variable. Some of the types can have a special internal representation - for example, numbers, characters and booleans can be represented as primitive values at runtime - but to the user they look like ordinary classes. In this section we describe the basic types used in Kotlin: numbers, characters, booleans, arrays, and strings.

Numbers

Kotlin handles numbers in a way close to Java, but not exactly the same. For example, there are no implicit widening conversions for numbers, and literals are slightly different in some cases.

Kotlin provides the following built-in types representing numbers (this is close to Java):

| Type | Bit width |
|--------|-----------|
| Double | 64 |
| Float | 32 |
| Long | 64 |
| Int | 32 |
| Short | 16 |
| Byte | 8 |

Note that characters are not numbers in Kotlin.

Literal Constants

There are the following kinds of literal constants for integral values:

- Decimals: `123`
 - Longs are tagged by a capital `L`: `123L`
- Hexadecimals: `0x0F`
- Binaries: `0b00001011`

NOTE: Octal literals are not supported.

Kotlin also supports a conventional notation for floating-point numbers:

- Doubles by default: `123.5`, `123.5e10`
- Floats are tagged by `f` or `F`: `123.5f`

Underscores in numeric literals (since 1.1)

You can use underscores to make number constants more readable:

```
val oneMillion = 1_000_000
val creditCardNumber = 1234_5678_9012_3456L
val socialSecurityNumber = 999_99_9999L
val hexBytes = 0xFF_EC_DE_5E
val bytes = 0b11010010_01101001_10010100_10010010
```

Representation

On the Java platform, numbers are physically stored as JVM primitive types, unless we need a nullable number reference (e.g. `Int?`) or generics are involved. In the latter cases numbers are boxed.

Note that boxing of numbers does not necessarily preserve identity:

```
val a: Int = 10000
println(a === a) // Prints 'true'
val boxedA: Int? = a
val anotherBoxedA: Int? = a
println(boxedA === anotherBoxedA) // !!!Prints 'false'!!!
```

On the other hand, it preserves equality:

```
val a: Int = 10000
println(a == a) // Prints 'true'
val boxedA: Int? = a
val anotherBoxedA: Int? = a
println(boxedA == anotherBoxedA) // Prints 'true'
```

Explicit Conversions

Due to different representations, smaller types are not subtypes of bigger ones. If they were, we would have troubles of the following sort:

```
// Hypothetical code, does not actually compile:
val a: Int? = 1 // A boxed Int (java.lang.Integer)
val b: Long? = a // implicit conversion yields a boxed Long (java.lang.Long)
print(b == a) // Surprise! This prints "false" as Long's equals() checks whether the other is Long as well
```

So equality would have been lost silently all over the place, not to mention identity.

As a consequence, smaller types are NOT implicitly converted to bigger types. This means that we cannot assign a value of type `Byte` to an `Int` variable without an explicit conversion

```
val b: Byte = 1 // OK, literals are checked statically
val i: Int = b // ERROR
```

We can use explicit conversions to widen numbers

```
val i: Int = b.toInt() // OK: explicitly widened
print(i)
```

Every number type supports the following conversions:

- `toByte(): Byte`
- `toShort(): Short`
- `toInt(): Int`
- `toLong(): Long`
- `toFloat(): Float`
- `toDouble(): Double`
- `toChar(): Char`

Absence of implicit conversions is rarely noticeable because the type is inferred from the context, and arithmetical operations are overloaded for appropriate conversions, for example

```
val l = 1L + 3 // Long + Int => Long
```

Operations

Kotlin supports the standard set of arithmetical operations over numbers, which are declared as members of appropriate classes (but the compiler optimizes the calls down to the corresponding instructions). See [Operator overloading](#).

As of bitwise operations, there're no special characters for them, but just named functions that can be called in infix form, for example:

```
val x = (1 shl 2) and 0x000FF000
```

Here is the complete list of bitwise operations (available for `Int` and `Long` only):

- `shl(bits)` - signed shift left (Java's `<<`)
- `shr(bits)` - signed shift right (Java's `>>`)
- `ushr(bits)` - unsigned shift right (Java's `>>>`)
- `and(bits)` - bitwise and
- `or(bits)` - bitwise or
- `xor(bits)` - bitwise xor
- `inv()` - bitwise inversion

Floating Point Numbers Comparison

The operations on floating point numbers discussed in this section are:

- Equality checks: `a == b` and `a != b`
- Comparison operators: `a < b`, `a > b`, `a <= b`, `a >= b`
- Range instantiation and range checks: `a..b`, `x in a..b`, `x !in a..b`

When the operands `a` and `b` are statically known to be `Float` or `Double` or their nullable counterparts (the type is declared or inferred or is a result of a [smart cast](#)), the operations on the numbers and the range that they form follow the IEEE 754 Standard for Floating-Point Arithmetic.

However, to support generic use cases and provide total ordering, when the operands are **not** statically typed as floating point numbers (e.g. `Any`, `Comparable<...>`, a type parameter), the operations use the `equals` and `compareTo` implementations for `Float` and `Double`, which disagree with the standard, so that:

- `NaN` is considered equal to itself
- `NaN` is considered greater than any other element including `POSITIVE_INFINITY`
- `-0.0` is considered less than `0.0`

Characters

Characters are represented by the type `Char`. They can not be treated directly as numbers

```
fun check(c: Char) {  
    if (c == 1) { // ERROR: incompatible types  
        // ...  
    }  
}
```

Character literals go in single quotes: `'1'`. Special characters can be escaped using a backslash. The following escape sequences are supported: `\t`, `\b`, `\n`, `\r`, `\'`, `\"`, `\\` and `\$`. To encode any other character, use the Unicode escape sequence syntax: `'\uFF00'`.

We can explicitly convert a character to an `Int` number:

```
fun decimalDigitValue(c: Char): Int {
    if (c !in '0'..'9')
        throw IllegalArgumentException("Out of range")
    return c.toInt() - '0'.toInt() // Explicit conversions to numbers
}
```

Like numbers, characters are boxed when a nullable reference is needed. Identity is not preserved by the boxing operation.

Booleans

The type `Boolean` represents booleans, and has two values: `true` and `false`.

Booleans are boxed if a nullable reference is needed.

Built-in operations on booleans include

- `||` - lazy disjunction
- `&&` - lazy conjunction
- `!` - negation

Arrays

Arrays in Kotlin are represented by the `Array` class, that has `get` and `set` functions (that turn into `[]` by operator overloading conventions), and `size` property, along with a few other useful member functions:

```
class Array<T> private constructor() {
    val size: Int
    operator fun get(index: Int): T
    operator fun set(index: Int, value: T): Unit

    operator fun iterator(): Iterator<T>
    // ...
}
```

To create an array, we can use a library function `arrayOf()` and pass the item values to it, so that `arrayOf(1, 2, 3)` creates an array `[1, 2, 3]`. Alternatively, the `arrayOfNulls()` library function can be used to create an array of a given size filled with null elements.

Another option is to use the `Array` constructor that takes the array size and the function that can return the initial value of each array element given its index:

```
// Creates an Array<String> with values ["0", "1", "4", "9", "16"]
val asc = Array(5, { i -> (i * i).toString() })
asc.forEach { println(it) }
```

As we said above, the `[]` operation stands for calls to member functions `get()` and `set()`.

Note: unlike Java, arrays in Kotlin are invariant. This means that Kotlin does not let us assign an `Array<String>` to an `Array<Any>`, which prevents a possible runtime failure (but you can use `Array<out Any>`, see [Type Projections](#)).

Kotlin also has specialized classes to represent arrays of primitive types without boxing overhead: `ByteArray`, `ShortArray`, `IntArray` and so on. These classes have no inheritance relation to the `Array` class, but they have the same set of methods and properties. Each of them also has a corresponding factory function:

```
val x: IntArray = intArrayOf(1, 2, 3)
x[0] = x[1] + x[2]
```

Strings

Strings are represented by the type `String`. Strings are immutable. Elements of a string are characters that can be accessed by the indexing operation: `s[i]`. A string can be iterated over with a `for`-loop:

```
for (c in str) {  
    println(c)  
}
```

You can concatenate strings using the `+` operator. This also works for concatenating strings with values of other types, as long as the first element in the expression is a string:

```
val s = "abc" + 1  
println(s + "def")
```

Note that in most cases using [string templates](#) or raw strings is preferable to string concatenation.

String Literals

Kotlin has two types of string literals: escaped strings that may have escaped characters in them and raw strings that can contain newlines and arbitrary text. An escaped string is very much like a Java string:

```
val s = "Hello, world!\n"
```

Escaping is done in the conventional way, with a backslash. See [Characters](#) above for the list of supported escape sequences.

A raw string is delimited by a triple quote (`"""`), contains no escaping and can contain newlines and any other characters:

```
val text = """  
    for (c in "foo")  
        print(c)  
    """
```

You can remove leading whitespace with [trimMargin\(\)](#) function:

```
val text = """  
    |Tell me and I forget.  
    |Teach me and I remember.  
    |Involve me and I learn.  
    |(Benjamin Franklin)  
    """.trimMargin()
```

By default `|` is used as margin prefix, but you can choose another character and pass it as a parameter, like `trimMargin(">")`.

String Templates

Strings may contain template expressions, i.e. pieces of code that are evaluated and whose results are concatenated into the string. A template expression starts with a dollar sign (\$) and consists of either a simple name:

```
val i = 10  
println("i = $i") // prints "i = 10"
```

or an arbitrary expression in curly braces:

```
val s = "abc"  
println("$s.length is ${s.length}") // prints "abc.length is 3"
```

Templates are supported both inside raw strings and inside escaped strings. If you need to represent a literal `$` character in a raw string (which doesn't support backslash escaping), you can use the following syntax:

```
val price = ""  
${'$'}9.99  
""
```


Packages

A source file may start with a package declaration:

```
package foo.bar

fun baz() { ... }
class Goo { ... }

// ...
```

All the contents (such as classes and functions) of the source file are contained by the package declared. So, in the example above, the full name of `baz()` is `foo.bar.baz`, and the full name of `Goo` is `foo.bar.Goo`.

If the package is not specified, the contents of such a file belong to "default" package that has no name.

Default Imports

A number of packages are imported into every Kotlin file by default:

- [kotlin.*](#)
- [kotlin.annotation.*](#)
- [kotlin.collections.*](#)
- [kotlin.comparisons.*](#) (since 1.1)
- [kotlin.io.*](#)
- [kotlin.ranges.*](#)
- [kotlin.sequences.*](#)
- [kotlin.text.*](#)

Additional packages are imported depending on the target platform:

- JVM:
 - [java.lang.*](#)
 - [kotlin.jvm.*](#)
- JS:
 - [kotlin.js.*](#)

Imports

Apart from the default imports, each file may contain its own import directives. Syntax for imports is described in the [grammar](#).

We can import either a single name, e.g.

```
import foo.Bar // Bar is now accessible without qualification
```

or all the accessible contents of a scope (package, class, object etc):

```
import foo.* // everything in 'foo' becomes accessible
```

If there is a name clash, we can disambiguate by using `as` keyword to locally rename the clashing entity:

```
import foo.Bar // Bar is accessible
import bar.Bar as bBar // bBar stands for 'bar.Bar'
```

The `import` keyword is not restricted to importing classes; you can also use it to import other declarations:

- top-level functions and properties;

- functions and properties declared in [object declarations](#);
- [enum constants](#).

Unlike Java, Kotlin does not have a separate "[import static](#)" syntax; all of these declarations are imported using the regular `import` keyword.

Visibility of Top-level Declarations

If a top-level declaration is marked `private`, it is private to the file it's declared in (see [Visibility Modifiers](#)).

Control Flow: if, when, for, while

If Expression

In Kotlin, `if` is an expression, i.e. it returns a value. Therefore there is no ternary operator (condition ? then : else), because ordinary `if` works fine in this role.

```
// Traditional usage
var max = a
if (a < b) max = b

// With else
var max: Int
if (a > b) {
    max = a
} else {
    max = b
}

// As expression
val max = if (a > b) a else b
```

`if` branches can be blocks, and the last expression is the value of a block:

```
val max = if (a > b) {
    print("Choose a")
    a
} else {
    print("Choose b")
    b
}
```

If you're using `if` as an expression rather than a statement (for example, returning its value or assigning it to a variable), the expression is required to have an `else` branch.

See the [grammar for if](#).

When Expression

`when` replaces the switch operator of C-like languages. In the simplest form it looks like this

```
when (x) {
    1 -> print("x == 1")
    2 -> print("x == 2")
    else -> { // Note the block
        print("x is neither 1 nor 2")
    }
}
```

`when` matches its argument against all branches sequentially until some branch condition is satisfied. `when` can be used either as an expression or as a statement. If it is used as an expression, the value of the satisfied branch becomes the value of the overall expression. If it is used as a statement, the values of individual branches are ignored. (Just like with `if`, each branch can be a block, and its value is the value of the last expression in the block.)

The `else` branch is evaluated if none of the other branch conditions are satisfied. If `when` is used as an expression, the `else` branch is mandatory, unless the compiler can prove that all possible cases are covered with branch conditions (as, for example, with [enum class](#) entries and [sealed class](#) subtypes).

If many cases should be handled in the same way, the branch conditions may be combined with a comma:

```
when (x) {
  0, 1 -> print("x == 0 or x == 1")
  else -> print("otherwise")
}
```

We can use arbitrary expressions (not only constants) as branch conditions

```
when (x) {
  parseInt(s) -> print("s encodes x")
  else -> print("s does not encode x")
}
```

We can also check a value for being `in` or `!in` a [range](#) or a collection:

```
when (x) {
  in 1..10 -> print("x is in the range")
  in validNumbers -> print("x is valid")
  !in 10..20 -> print("x is outside the range")
  else -> print("none of the above")
}
```

Another possibility is to check that a value `is` or `!is` of a particular type. Note that, due to [smart casts](#), you can access the methods and properties of the type without any extra checks.

```
fun hasPrefix(x: Any) = when(x) {
  is String -> x.startsWith("prefix")
  else -> false
}
```

`when` can also be used as a replacement for an `if-else if` chain. If no argument is supplied, the branch conditions are simply boolean expressions, and a branch is executed when its condition is true:

```
when {
  x.isOdd() -> print("x is odd")
  x.isEven() -> print("x is even")
  else -> print("x is funny")
}
```

See the [grammar for when](#).

For Loops

`for` loop iterates through anything that provides an iterator. This is equivalent to the `foreach` loop in languages like C#. The syntax is as follows:

```
for (item in collection) print(item)
```

The body can be a block.

```
for (item: Int in ints) {
  // ...
}
```

As mentioned before, `for` iterates through anything that provides an iterator, i.e.

- has a member- or extension-function `iterator()`, whose return type
- has a member- or extension-function `next()`, and
- has a member- or extension-function `hasNext()` that returns `Boolean`.

All of these three functions need to be marked as `operator` .

To iterate over a range of numbers, use a [range expression](#):

```
for (i in 1..3) {  
    println(i)  
}  
for (i in 6 downTo 0 step 2) {  
    println(i)  
}
```

A `for` loop over a range or an array is compiled to an index-based loop that does not create an iterator object.

If you want to iterate through an array or a list with an index, you can do it this way:

```
for (i in array.indices) {  
    println(array[i])  
}
```

Alternatively, you can use the `withIndex` library function:

```
for ((index, value) in array.withIndex()) {  
    println("the element at $index is $value")  
}
```

See the [grammar for for](#).

While Loops

`while` and `do..while` work as usual

```
while (x > 0) {  
    x--  
}  
  
do {  
    val y = retrieveData()  
} while (y != null) // y is visible here!
```

See the [grammar for while](#).

Break and continue in loops

Kotlin supports traditional `break` and `continue` operators in loops. See [Returns and jumps](#).

Returns and Jumps

Kotlin has three structural jump expressions:

- **return**. By default returns from the nearest enclosing function or [anonymous function](#).
- **break**. Terminates the nearest enclosing loop.
- **continue**. Proceeds to the next step of the nearest enclosing loop.

All of these expressions can be used as part of larger expressions:

```
val s = person.name ?: return
```

The type of these expressions is the [Nothing type](#).

Break and Continue Labels

Any expression in Kotlin may be marked with a **label**. Labels have the form of an identifier followed by the **@** sign, for example: `abc@`, `fooBar@` are valid labels (see the [grammar](#)). To label an expression, we just put a label in front of it

```
loop@ for (i in 1..100) {  
    // ...  
}
```

Now, we can qualify a **break** or a **continue** with a label:

```
loop@ for (i in 1..100) {  
    for (j in 1..100) {  
        if (...) break@loop  
    }  
}
```

A **break** qualified with a label jumps to the execution point right after the loop marked with that label. A **continue** proceeds to the next iteration of that loop.

Return at Labels

With function literals, local functions and object expression, functions can be nested in Kotlin. Qualified **returns** allow us to return from an outer function. The most important use case is returning from a lambda expression. Recall that when we write this:

```
fun foo() {  
    listOf(1, 2, 3, 4, 5).forEach {  
        if (it == 3) return // non-local return directly to the caller of foo()  
        print(it)  
    }  
    println("this point is unreachable")  
}
```

The **return**-expression returns from the nearest enclosing function, i.e. `foo`. (Note that such non-local returns are supported only for lambda expressions passed to [inline functions](#).) If we need to return from a lambda expression, we have to label it and qualify the **return**:

```
fun foo() {  
    listOf(1, 2, 3, 4, 5).forEach lit@{  
        if (it == 3) return@lit // local return to the caller of the lambda, i.e. the forEach loop  
        print(it)  
    }  
    print(" done with explicit label")  
}
```

Now, it returns only from the lambda expression. Oftentimes it is more convenient to use implicit labels: such a label has the same name as the function to which the lambda is passed.

```
fun foo() {
    listOf(1, 2, 3, 4, 5).forEach {
        if (it == 3) return@forEach // local return to the caller of the lambda, i.e. the forEach loop
        print(it)
    }
    print(" done with implicit label")
}
```

Alternatively, we can replace the lambda expression with an [anonymous function](#). A `return` statement in an anonymous function will return from the anonymous function itself.

```
fun foo() {
    listOf(1, 2, 3, 4, 5).forEach(fun(value: Int) {
        if (value == 3) return // local return to the caller of the anonymous fun, i.e. the forEach
    loop
        print(value)
    })
    print(" done with anonymous function")
}
```

Note that the use of local returns in previous three examples is similar to the use of `continue` in regular loops. There is no direct equivalent for `break`, but it can be simulated by adding another nesting lambda and non-locally returning from it:

```
fun foo() {
    run loop@{
        listOf(1, 2, 3, 4, 5).forEach {
            if (it == 3) return@loop // non-local return from the lambda passed to run
            print(it)
        }
    }
    print(" done with nested loop")
}
```

When returning a value, the parser gives preference to the qualified return, i.e.

```
return@a 1
```

means "return `1` at label `@a`" and not "return a labeled expression `(@a 1)`".

Classes and Objects

Classes and Inheritance

Classes

Classes in Kotlin are declared using the keyword `class`:

```
class Invoice { ... }
```

The class declaration consists of the class name, the class header (specifying its type parameters, the primary constructor etc.) and the class body, surrounded by curly braces. Both the header and the body are optional; if the class has no body, curly braces can be omitted.

```
class Empty
```

Constructors

A class in Kotlin can have a **primary constructor** and one or more **secondary constructors**. The primary constructor is part of the class header: it goes after the class name (and optional type parameters).

```
class Person constructor(firstName: String) { ... }
```

If the primary constructor does not have any annotations or visibility modifiers, the `constructor` keyword can be omitted:

```
class Person(firstName: String) { ... }
```

The primary constructor cannot contain any code. Initialization code can be placed in **initializer blocks**, which are prefixed with the `init` keyword.

During an instance initialization, the initializer blocks are executed in the same order as they appear in the class body, interleaved with the property initializers:

```
class InitOrderDemo(name: String) {  
    val firstProperty = "First property: $name".also(::println)  
  
    init {  
        println("First initializer block that prints ${name}")  
    }  
  
    val secondProperty = "Second property: ${name.length}".also(::println)  
  
    init {  
        println("Second initializer block that prints ${name.length}")  
    }  
}
```

Note that parameters of the primary constructor can be used in the initializer blocks. They can also be used in property initializers declared in the class body:


```
class Customer(name: String) {
    val customerKey = name.toUpperCase()
}
```

In fact, for declaring properties and initializing them from the primary constructor, Kotlin has a concise syntax:

```
class Person(val firstName: String, val lastName: String, var age: Int) { ... }
```

Much the same way as regular properties, the properties declared in the primary constructor can be mutable (**var**) or read-only (**val**).

If the constructor has annotations or visibility modifiers, the **constructor** keyword is required, and the modifiers go before it:

```
class Customer public @Inject constructor(name: String) { ... }
```

For more details, see [Visibility Modifiers](#).

Secondary Constructors

The class can also declare **secondary constructors**, which are prefixed with **constructor**:

```
class Person {
    constructor(parent: Person) {
        parent.children.add(this)
    }
}
```

If the class has a primary constructor, each secondary constructor needs to delegate to the primary constructor, either directly or indirectly through another secondary constructor(s). Delegation to another constructor of the same class is done using the **this** keyword:

```
class Person(val name: String) {
    constructor(name: String, parent: Person) : this(name) {
        parent.children.add(this)
    }
}
```

Note that code in initializer blocks effectively becomes part of the primary constructor. Delegation to the primary constructor happens as the first statement of a secondary constructor, so the code in all initializer blocks is executed before the secondary constructor body. Even if the class has no primary constructor, the delegation still happens implicitly, and the initializer blocks are still executed:

```
class Constructors {
    init {
        println("Init block")
    }

    constructor(i: Int) {
        println("Constructor")
    }
}
```

If a non-abstract class does not declare any constructors (primary or secondary), it will have a generated primary constructor with no arguments. The visibility of the constructor will be public. If you do not want your class to have a public constructor, you need to declare an empty primary constructor with non-default visibility:

```
class DontCreateMe private constructor () { ... }
```

NOTE: On the JVM, if all of the parameters of the primary constructor have default values, the compiler will generate an additional parameterless constructor which will use the default values. This makes it easier to use Kotlin with libraries such as Jackson or JPA that create class instances through parameterless constructors.

```
class Customer(val customerName: String = "")
```

Creating instances of classes

To create an instance of a class, we call the constructor as if it were a regular function:

```
val invoice = Invoice()
```

```
val customer = Customer("Joe Smith")
```

Note that Kotlin does not have a `new` keyword.

Creating instances of nested, inner and anonymous inner classes is described in [Nested classes](#).

Class Members

Classes can contain:

- [Constructors and initializer blocks](#)
- [Functions](#)
- [Properties](#)
- [Nested and Inner Classes](#)
- [Object Declarations](#)

Inheritance

All classes in Kotlin have a common superclass `Any`, that is the default superclass for a class with no supertypes declared:

```
class Example // Implicitly inherits from Any
```

Note: `Any` is not `java.lang.Object`; in particular, it does not have any members other than `equals()`, `hashCode()` and `toString()`. Please consult the [Java interoperability](#) section for more details.

To declare an explicit supertype, we place the type after a colon in the class header:

```
open class Base(p: Int)
```

```
class Derived(p: Int) : Base(p)
```

The `open` annotation on a class is the opposite of Java's `final`: it allows others to inherit from this class. By default, all classes in Kotlin are `final`, which corresponds to [Effective Java, 3rd Edition](#), Item 19: *Design and document for inheritance or else prohibit it*.

If the derived class has a primary constructor, the base class can (and must) be initialized right there, using the parameters of the primary constructor.

If the class has no primary constructor, then each secondary constructor has to initialize the base type using the `super` keyword, or to delegate to another constructor which does that. Note that in this case different secondary constructors can call different constructors of the base type:

```
class MyView : View {
    constructor(ctx: Context) : super(ctx)

    constructor(ctx: Context, attrs: AttributeSet) : super(ctx, attrs)
}
```

Overriding Methods

As we mentioned before, we stick to making things explicit in Kotlin. And unlike Java, Kotlin requires explicit annotations for overridable members (we call them *open*) and for overrides:

```
open class Base {
    open fun v() { ... }
    fun nv() { ... }
}
class Derived() : Base() {
    override fun v() { ... }
}
```

The `override` annotation is required for `Derived.v()`. If it were missing, the compiler would complain. If there is no `open` annotation on a function, like `Base.nv()`, declaring a method with the same signature in a subclass is illegal, either with `override` or without it. In a final class (e.g. a class with no `open` annotation), open members are prohibited.

A member marked `override` is itself open, i.e. it may be overridden in subclasses. If you want to prohibit re-overriding, use `final`:

```
open class AnotherDerived() : Base() {
    final override fun v() { ... }
}
```

Overriding Properties

Overriding properties works in a similar way to overriding methods; properties declared on a superclass that are then redeclared on a derived class must be prefaced with `override`, and they must have a compatible type. Each declared property can be overridden by a property with an initializer or by a property with a getter method.

```
open class Foo {
    open val x: Int get() { ... }
}

class Bar1 : Foo() {
    override val x: Int = ...
}
```

You can also override a `val` property with a `var` property, but not vice versa. This is allowed because a `val` property essentially declares a getter method, and overriding it as a `var` additionally declares a setter method in the derived class.

Note that you can use the `override` keyword as part of the property declaration in a primary constructor.

```
interface Foo {
    val count: Int
}

class Bar1(override val count: Int) : Foo

class Bar2 : Foo {
    override var count: Int = 0
}
```

Derived class initialization order

During construction of a new instance of a derived class, the base class initialization is done as the first step (preceded only by evaluation of the arguments for the base class constructor) and thus happens before the initialization logic of the derived class is run.

```
//sampleStart
open class Base(val name: String) {

    init { println("Initializing Base") }

    open val size: Int =
        name.length.also { println("Initializing size in Base: $it") }
}

class Derived(
    name: String,
    val lastName: String
) : Base(name.capitalize()).also { println("Argument for Base: $it") } {

    init { println("Initializing Derived") }

    override val size: Int =
        (super.size + lastName.length).also { println("Initializing size in Derived: $it") }
}
//sampleEnd

fun main(args: Array<String>) {
    println("Constructing Derived(\"hello\", \"world\")")
    val d = Derived("hello", "world")
}
```

It means that, by the time of the base class constructor execution, the properties declared or overridden in the derived class are not yet initialized. If any of those properties are used in the base class initialization logic (either directly or indirectly, through another overridden [open](#) member implementation), it may lead to incorrect behavior or a runtime failure. When designing a base class, you should therefore avoid using [open](#) members in the constructors, property initializers, and [init](#) blocks.

Calling the superclass implementation

Code in a derived class can call its superclass functions and property accessors implementations using the [super](#) keyword:

```
open class Foo {
    open fun f() { println("Foo.f()") }
    open val x: Int get() = 1
}

class Bar : Foo() {
    override fun f() {
        super.f()
        println("Bar.f()")
    }

    override val x: Int get() = super.x + 1
}
```

Inside an inner class, accessing the superclass of the outer class is done with the [super](#) keyword qualified with the outer class name: `super@Outer`:

```
class Bar : Foo() {
    override fun f() { /* ... */ }
    override val x: Int get() = 0

    inner class Baz {
        fun g() {
            super@Bar.f() // Calls Foo's implementation of f()
            println(super@Bar.x) // Uses Foo's implementation of x's getter
        }
    }
}
```

Overriding Rules

In Kotlin, implementation inheritance is regulated by the following rule: if a class inherits many implementations of the same member from its immediate superclasses, it must override this member and provide its own implementation (perhaps, using one of the inherited ones). To denote the supertype from which the inherited implementation is taken, we use `super` qualified by the supertype name in angle brackets, e.g. `super<Base>`:

```
open class A {
    open fun f() { print("A") }
    fun a() { print("a") }
}

interface B {
    fun f() { print("B") } // interface members are 'open' by default
    fun b() { print("b") }
}

class C() : A(), B {
    // The compiler requires f() to be overridden:
    override fun f() {
        super<A>.f() // call to A.f()
        super<B>.f() // call to B.f()
    }
}
```

It's fine to inherit from both `A` and `B`, and we have no problems with `a()` and `b()` since `C` inherits only one implementation of each of these functions. But for `f()` we have two implementations inherited by `C`, and thus we have to override `f()` in `C` and provide our own implementation that eliminates the ambiguity.

Abstract Classes

A class and some of its members may be declared `abstract`. An abstract member does not have an implementation in its class. Note that we do not need to annotate an abstract class or function with `open` – it goes without saying.

We can override a non-abstract open member with an abstract one

```
open class Base {
    open fun f() {}
}

abstract class Derived : Base() {
    override abstract fun f()
}
```

Companion Objects

In Kotlin, unlike Java or C#, classes do not have static methods. In most cases, it's recommended to simply use package-level functions instead.

If you need to write a function that can be called without having a class instance but needs access to the internals of a class (for example, a factory method), you can write it as a member of an [object declaration](#) inside that class.

Even more specifically, if you declare a [companion object](#) inside your class, you'll be able to call its members with the same syntax as calling static methods in Java/C#, using only the class name as a qualifier.

Properties and Fields

Declaring Properties

Classes in Kotlin can have properties. These can be declared as mutable, using the `var` keyword or read-only using the `val` keyword.

```
class Address {
    var name: String = ...
    var street: String = ...
    var city: String = ...
    var state: String? = ...
    var zip: String = ...
}
```

To use a property, we simply refer to it by name, as if it were a field in Java:

```
fun copyAddress(address: Address): Address {
    val result = Address() // there's no 'new' keyword in Kotlin
    result.name = address.name // accessors are called
    result.street = address.street
    // ...
    return result
}
```

Getters and Setters

The full syntax for declaring a property is

```
var <propertyName>[: <PropertyType>] [= <property_initializer>]
    [<getter>]
    [<setter>]
```

The initializer, getter and setter are optional. Property type is optional if it can be inferred from the initializer (or from the getter return type, as shown below).

Examples:

```
var allByDefault: Int? // error: explicit initializer required, default getter and setter implied
var initialized = 1 // has type Int, default getter and setter
```

The full syntax of a read-only property declaration differs from a mutable one in two ways: it starts with `val` instead of `var` and does not allow a setter:

```
val simple: Int? // has type Int, default getter, must be initialized in constructor
val inferredType = 1 // has type Int and a default getter
```

We can write custom accessors, very much like ordinary functions, right inside a property declaration. Here's an example of a custom getter:

```
val isEmpty: Boolean
    get() = this.size == 0
```

A custom setter looks like this:

```
var stringRepresentation: String
    get() = this.toString()
    set(value) {
        setDataFromString(value) // parses the string and assigns values to other properties
    }
```

By convention, the name of the setter parameter is `value`, but you can choose a different name if you prefer.

Since Kotlin 1.1, you can omit the property type if it can be inferred from the getter:

```
val isEmpty get() = this.size == 0 // has type Boolean
```

If you need to change the visibility of an accessor or to annotate it, but don't need to change the default implementation, you can define the accessor without defining its body:

```
var setterVisibility: String = "abc"
    private set // the setter is private and has the default implementation

var setterWithAnnotation: Any? = null
    @Inject set // annotate the setter with Inject
```

Backing Fields

Fields cannot be declared directly in Kotlin classes. However, when a property needs a backing field, Kotlin provides it automatically. This backing field can be referenced in the accessors using the `field` identifier:

```
var counter = 0 // Note: the initializer assigns the backing field directly
    set(value) {
        if (value >= 0) field = value
    }
```

The `field` identifier can only be used in the accessors of the property.

A backing field will be generated for a property if it uses the default implementation of at least one of the accessors, or if a custom accessor references it through the `field` identifier.

For example, in the following case there will be no backing field:

```
val isEmpty: Boolean
    get() = this.size == 0
```

Backing Properties

If you want to do something that does not fit into this "implicit backing field" scheme, you can always fall back to having a *backing property*.

```
private var _table: Map<String, Int>? = null
public val table: Map<String, Int>
    get() {
        if (_table == null) {
            _table = HashMap() // Type parameters are inferred
        }
        return _table ?: throw AssertionError("Set to null by another thread")
    }
```

In all respects, this is just the same as in Java since access to private properties with default getters and setters is optimized so that no function call overhead is introduced.

Compile-Time Constants

Properties the value of which is known at compile time can be marked as *compile time constants* using the `const` modifier. Such properties need to fulfil the following requirements:

- Top-level or member of an `object`
- Initialized with a value of type `String` or a primitive type
- No custom getter

Such properties can be used in annotations:

```
const val SUBSYSTEM_DEPRECATED: String = "This subsystem is deprecated"

@Deprecated(SUBSYSTEM_DEPRECATED) fun foo() { ... }
```

Late-Initialized Properties and Variables

Normally, properties declared as having a non-null type must be initialized in the constructor. However, fairly often this is not convenient. For example, properties can be initialized through dependency injection, or in the setup method of a unit test. In this case, you cannot supply a non-null initializer in the constructor, but you still want to avoid null checks when referencing the property inside the body of a class.

To handle this case, you can mark the property with the `lateinit` modifier:

```
public class MyTest {
    lateinit var subject: TestSubject

    @SetUp fun setup() {
        subject = TestSubject()
    }

    @Test fun test() {
        subject.method() // dereference directly
    }
}
```

The modifier can be used on `var` properties declared inside the body of a class (not in the primary constructor, and only when the property does not have a custom getter or setter) and, since Kotlin 1.2, for top-level properties and local variables. The type of the property or variable must be non-null, and it must not be a primitive type.

Accessing a `lateinit` property before it has been initialized throws a special exception that clearly identifies the property being accessed and the fact that it hasn't been initialized.

Checking whether a `lateinit var` is initialized (since 1.2)

To check whether a `lateinit var` has already been initialized, use `.isInitialized` on the [reference to that property](#):

```
if (foo::bar.isInitialized) {
    println(foo.bar)
}
```

This check is only available for the properties that are lexically accessible, i.e. declared in the same type or in one of the outer types, or at top level in the same file.

Overriding Properties

See [Overriding Properties](#)

Delegated Properties

The most common kind of properties simply reads from (and maybe writes to) a backing field. On the other hand, with custom getters and setters one can implement any behaviour of a property. Somewhere in between, there are certain common patterns of how a property may work. A few examples: lazy values, reading from a map by a given key, accessing a database, notifying listener on access, etc.

Such common behaviours can be implemented as libraries using [delegated properties](#).

Interfaces

Interfaces in Kotlin are very similar to Java 8. They can contain declarations of abstract methods, as well as method implementations. What makes them different from abstract classes is that interfaces cannot store state. They can have properties but these need to be abstract or to provide accessor implementations.

An interface is defined using the keyword `interface`

```
interface MyInterface {  
    fun bar()  
    fun foo() {  
        // optional body  
    }  
}
```

Implementing Interfaces

A class or object can implement one or more interfaces

```
class Child : MyInterface {  
    override fun bar() {  
        // body  
    }  
}
```

Properties in Interfaces

You can declare properties in interfaces. A property declared in an interface can either be abstract, or it can provide implementations for accessors. Properties declared in interfaces can't have backing fields, and therefore accessors declared in interfaces can't reference them.

```
interface MyInterface {  
    val prop: Int // abstract  
  
    val propertyWithImplementation: String  
        get() = "foo"  
  
    fun foo() {  
        print(prop)  
    }  
}  
  
class Child : MyInterface {  
    override val prop: Int = 29  
}
```

Interfaces Inheritance

An interface can derive from other interfaces and thus both provide implementations for their members and declare new functions and properties. Quite naturally, classes implementing such an interface are only required to define the missing implementations:

```

interface Named {
    val name: String
}

interface Person : Named {
    val firstName: String
    val lastName: String

    override val name: String get() = "$firstName $lastName"
}

data class Employee(
    // implementing 'name' is not required
    override val firstName: String,
    override val lastName: String,
    val position: Position
) : Person

```

Resolving overriding conflicts

When we declare many types in our supertype list, it may appear that we inherit more than one implementation of the same method. For example

```

interface A {
    fun foo() { print("A") }
    fun bar()
}

interface B {
    fun foo() { print("B") }
    fun bar() { print("bar") }
}

class C : A {
    override fun bar() { print("bar") }
}

class D : A, B {
    override fun foo() {
        super<A>.foo()
        super<B>.foo()
    }

    override fun bar() {
        super<B>.bar()
    }
}

```

Interfaces *A* and *B* both declare functions *foo()* and *bar()*. Both of them implement *foo()*, but only *B* implements *bar()* (*bar()* is not marked abstract in *A*, because this is the default for interfaces, if the function has no body). Now, if we derive a concrete class *C* from *A*, we, obviously, have to override *bar()* and provide an implementation.

However, if we derive *D* from *A* and *B*, we need to implement all the methods which we have inherited from multiple interfaces, and to specify how exactly *D* should implement them. This rule applies both to methods for which we've inherited a single implementation (*bar()*) and multiple implementations (*foo()*).

Visibility Modifiers

Classes, objects, interfaces, constructors, functions, properties and their setters can have *visibility modifiers*. (Getters always have the same visibility as the property.) There are four visibility modifiers in Kotlin: `private`, `protected`, `internal` and `public`. The default visibility, used if there is no explicit modifier, is `public`.

Below please find explanations of how the modifiers apply to different types of declaring scopes.

Packages

Functions, properties and classes, objects and interfaces can be declared on the "top-level", i.e. directly inside a package:

```
// file name: example.kt
package foo

fun baz() { ... }
class Bar { ... }
```

- If you do not specify any visibility modifier, `public` is used by default, which means that your declarations will be visible everywhere;
- If you mark a declaration `private`, it will only be visible inside the file containing the declaration;
- If you mark it `internal`, it is visible everywhere in the same [module](#);
- `protected` is not available for top-level declarations.

Note: to use a visible top-level declaration from another package, you should still [import](#) it.

Examples:

```
// file name: example.kt
package foo

private fun foo() { ... } // visible inside example.kt

public var bar: Int = 5 // property is visible everywhere
    private set         // setter is visible only in example.kt

internal val baz = 6    // visible inside the same module
```

Classes and Interfaces

For members declared inside a class:

- `private` means visible inside this class only (including all its members);
- `protected` — same as `private` + visible in subclasses too;
- `internal` — any client *inside this module* who sees the declaring class sees its `internal` members;
- `public` — any client who sees the declaring class sees its `public` members.

NOTE for Java users: outer class does not see private members of its inner classes in Kotlin.

If you override a `protected` member and do not specify the visibility explicitly, the overriding member will also have `protected` visibility.

Examples:

```

open class Outer {
    private val a = 1
    protected open val b = 2
    internal val c = 3
    val d = 4 // public by default

    protected class Nested {
        public val e: Int = 5
    }
}

class Subclass : Outer() {
    // a is not visible
    // b, c and d are visible
    // Nested and e are visible

    override val b = 5 // 'b' is protected
}

class Unrelated(o: Outer) {
    // o.a, o.b are not visible
    // o.c and o.d are visible (same module)
    // Outer.Nested is not visible, and Nested::e is not visible either
}

```

Constructors

To specify a visibility of the primary constructor of a class, use the following syntax (note that you need to add an explicit `constructor` keyword):

```
class C private constructor(a: Int) { ... }
```

Here the constructor is private. By default, all constructors are `public`, which effectively amounts to them being visible everywhere where the class is visible (i.e. a constructor of an `internal` class is only visible within the same module).

Local declarations

Local variables, functions and classes can not have visibility modifiers.

Modules

The `internal` visibility modifier means that the member is visible within the same module. More specifically, a module is a set of Kotlin files compiled together:

- an IntelliJ IDEA module;
- a Maven project;
- a Gradle source set (with the exception that the `test` source set can access the internal declarations of `main`);
- a set of files compiled with one invocation of the `<kotlinc>` Ant task.

Extensions

Kotlin, similar to C# and Gosu, provides the ability to extend a class with new functionality without having to inherit from the class or use any type of design pattern such as Decorator. This is done via special declarations called *extensions*. Kotlin supports *extension functions* and *extension properties*.

Extension Functions

To declare an extension function, we need to prefix its name with a *receiver type*, i.e. the type being extended. The following adds a `swap` function to `MutableList<Int>`:

```
fun MutableList<Int>.swap(index1: Int, index2: Int) {
    val tmp = this[index1] // 'this' corresponds to the list
    this[index1] = this[index2]
    this[index2] = tmp
}
```

The `this` keyword inside an extension function corresponds to the receiver object (the one that is passed before the dot). Now, we can call such a function on any `MutableList<Int>`:

```
val l = mutableListOf(1, 2, 3)
l.swap(0, 2) // 'this' inside 'swap()' will hold the value of '1'
```

Of course, this function makes sense for any `MutableList<T>`, and we can make it generic:

```
fun <T> MutableList<T>.swap(index1: Int, index2: Int) {
    val tmp = this[index1] // 'this' corresponds to the list
    this[index1] = this[index2]
    this[index2] = tmp
}
```

We declare the generic type parameter before the function name for it to be available in the receiver type expression. See [Generic functions](#).

Extensions are resolved **statically**

Extensions do not actually modify classes they extend. By defining an extension, you do not insert new members into a class, but merely make new functions callable with the dot-notation on variables of this type.

We would like to emphasize that extension functions are dispatched **statically**, i.e. they are not virtual by receiver type. This means that the extension function being called is determined by the type of the expression on which the function is invoked, not by the type of the result of evaluating that expression at runtime. For example:

```
open class C

class D: C()

fun C.foo() = "c"

fun D.foo() = "d"

fun printFoo(c: C) {
    println(c.foo())
}

printFoo(D())
```

This example will print "c", because the extension function being called depends only on the declared type of the parameter `c`, which is the `C` class.

If a class has a member function, and an extension function is defined which has the same receiver type, the same name is applicable to given arguments, the **member always wins**. For example:

```
class C {
    fun foo() { println("member") }
}
```

```
fun C.foo() { println("extension") }
```

If we call `c.foo()` of any `c` of type `C`, it will print "member", not "extension".

However, it's perfectly OK for extension functions to overload member functions which have the same name but a different signature:

```
class C {
    fun foo() { println("member") }
}
```

```
fun C.foo(i: Int) { println("extension") }
```

The call to `C().foo(1)` will print "extension".

Nullable Receiver

Note that extensions can be defined with a nullable receiver type. Such extensions can be called on an object variable even if its value is null, and can check for `this == null` inside the body. This is what allows you to call `toString()` in Kotlin without checking for null: the check happens inside the extension function.

```
fun Any?.toString(): String {
    if (this == null) return "null"
    // after the null check, 'this' is autocast to a non-null type, so the toString() below
    // resolves to the member function of the Any class
    return toString()
}
```

Extension Properties

Similarly to functions, Kotlin supports extension properties:

```
val <T> List<T>.lastIndex: Int
    get() = size - 1
```

Note that, since extensions do not actually insert members into classes, there's no efficient way for an extension property to have a [backing field](#). This is why **initializers are not allowed for extension properties**. Their behavior can only be defined by explicitly providing getters/setters.

Example:

```
val Foo.bar = 1 // error: initializers are not allowed for extension properties
```

Companion Object Extensions

If a class has a [companion object](#) defined, you can also define extension functions and properties for the companion object:

```
class MyClass {
    companion object { } // will be called "Companion"
}
```

```
fun MyClass.Companion.foo() { ... }
```

Just like regular members of the companion object, they can be called using only the class name as the qualifier:

```
MyClass.foo()
```

Scope of Extensions

Most of the time we define extensions on the top level, i.e. directly under packages:

```
package foo.bar
```

```
fun Baz.goo() { ... }
```

To use such an extension outside its declaring package, we need to import it at the call site:

```
package com.example.usage

import foo.bar.goo // importing all extensions by name "goo"
                  // or
import foo.bar.*   // importing everything from "foo.bar"

fun usage(baz: Baz) {
    baz.goo()
}
```

See [Imports](#) for more information.

Declaring Extensions as Members

Inside a class, you can declare extensions for another class. Inside such an extension, there are multiple *implicit receivers* - objects members of which can be accessed without a qualifier. The instance of the class in which the extension is declared is called *dispatch receiver*, and the instance of the receiver type of the extension method is called *extension receiver*.

```
class D {
    fun bar() { ... }
}

class C {
    fun baz() { ... }

    fun D.foo() {
        bar() // calls D.bar
        baz() // calls C.baz
    }

    fun caller(d: D) {
        d.foo() // call the extension function
    }
}
```

In case of a name conflict between the members of the dispatch receiver and the extension receiver, the extension receiver takes precedence. To refer to the member of the dispatch receiver you can use the [qualified this syntax](#).

```
class C {
    fun D.foo() {
        toString() // calls D.toString()
        this@C.toString() // calls C.toString()
    }
}
```

Extensions declared as members can be declared as `open` and overridden in subclasses. This means that the dispatch of such functions is virtual with regard to the dispatch receiver type, but static with regard to the extension receiver type.

```

open class D { }

class D1 : D() { }

open class C {
    open fun D.foo() {
        println("D.foo in C")
    }

    open fun D1.foo() {
        println("D1.foo in C")
    }

    fun caller(d: D) {
        d.foo() // call the extension function
    }
}

class C1 : C() {
    override fun D.foo() {
        println("D.foo in C1")
    }

    override fun D1.foo() {
        println("D1.foo in C1")
    }
}

fun main(args: Array<String>) {
    C().caller(D()) // prints "D.foo in C"
    C1().caller(D()) // prints "D.foo in C1" - dispatch receiver is resolved virtually
    C().caller(D1()) // prints "D.foo in C" - extension receiver is resolved statically
}

```

Note on visibility

Extensions utilize the same [visibility of other entities](#) as regular functions declared in the same scope would. For example:

- An extension declared on top level of a file has access to the other `private` top-level declarations in the same file;
- If an extension is declared outside its receiver type, such an extension cannot access the receiver's `private` members.

Motivation

In Java, we are used to classes named `*Utils`: `FileUtils`, `StringUtils` and so on. The famous `java.util.Collections` belongs to the same breed. And the unpleasant part about these `Utils`-classes is that the code that uses them looks like this:

```

// Java
Collections.swap(list, Collections.binarySearch(list,
    Collections.max(otherList)),
    Collections.max(list));

```

Those class names are always getting in the way. We can use static imports and get this:

```

// Java
swap(list, binarySearch(list, max(otherList)), max(list));

```

This is a little better, but we have no or little help from the powerful code completion of the IDE. It would be so much better if we could say:

```

// Java
list.swap(list.binarySearch(otherList.max()), list.max());

```

But we don't want to implement all the possible methods inside the class `List`, right? This is where extensions help us.

Data Classes

We frequently create classes whose main purpose is to hold data. In such a class some standard functionality and utility functions are often mechanically derivable from the data. In Kotlin, this is called a *data class* and is marked as `data` :

```
data class User(val name: String, val age: Int)
```

The compiler automatically derives the following members from all properties declared in the primary constructor:

- `equals()` / `hashCode()` pair;
- `toString()` of the form `"User(name=John, age=42)"`;
- [componentN\(\) functions](#) corresponding to the properties in their order of declaration;
- `copy()` function (see below).

To ensure consistency and meaningful behavior of the generated code, data classes have to fulfill the following requirements:

- The primary constructor needs to have at least one parameter;
- All primary constructor parameters need to be marked as `val` or `var` ;
- Data classes cannot be abstract, open, sealed or inner;
- (before 1.1) Data classes may only implement interfaces.

Additionally, the members generation follows these rules with regard to the members inheritance:

- If there are explicit implementations of `equals()` , `hashCode()` or `toString()` in the data class body or `final` implementations in a superclass, then these functions are not generated, and the existing implementations are used;
- If a supertype has the `componentN()` functions that are `open` and return compatible types, the corresponding functions are generated for the data class and override those of the supertype. If the functions of the supertype cannot be overridden due to incompatible signatures or being final, an error is reported;
- Deriving a data class from a type that already has a `copy(...)` function with a matching signature is deprecated in Kotlin 1.2 and will be prohibited in Kotlin 1.3.
- Providing explicit implementations for the `componentN()` and `copy()` functions is not allowed.

Since 1.1, data classes may extend other classes (see [Sealed classes](#) for examples).

On the JVM, if the generated class needs to have a parameterless constructor, default values for all properties have to be specified (see [Constructors](#)).

```
data class User(val name: String = "", val age: Int = 0)
```

Properties Declared in the Class Body

Note that the compiler only uses the properties defined inside the primary constructor for the automatically generated functions. To exclude a property from the generated implementations, declare it inside the class body:

```
data class Person(val name: String) {  
    var age: Int = 0  
}
```

Only the property `name` will be used inside the `toString()` , `equals()` , `hashCode()` , and `copy()` implementations, and there will only be one component function `component1()` . While two `Person` objects can have different ages, they will be treated as equal.

```
data class Person(val name: String) {
    var age: Int = 0
}
fun main(args: Array<String>) {
    //sampleStart
    val person1 = Person("John")
    val person2 = Person("John")
    person1.age = 10
    person2.age = 20
    //sampleEnd
    println("person1 == person2: ${person1 == person2}")
    println("person1 with age ${person1.age}: ${person1}")
    println("person2 with age ${person2.age}: ${person2}")
}
```

Copying

It's often the case that we need to copy an object altering *some* of its properties, but keeping the rest unchanged. This is what `copy()` function is generated for. For the `User` class above, its implementation would be as follows:

```
fun copy(name: String = this.name, age: Int = this.age) = User(name, age)
```

This allows us to write:

```
val jack = User(name = "Jack", age = 1)
val olderJack = jack.copy(age = 2)
```

Data Classes and Destructuring Declarations

Component functions generated for data classes enable their use in [destructuring declarations](#):

```
val jane = User("Jane", 35)
val (name, age) = jane
println("$name, $age years of age") // prints "Jane, 35 years of age"
```

Standard Data Classes

The standard library provides `Pair` and `Triple`. In most cases, though, named data classes are a better design choice, because they make the code more readable by providing meaningful names for properties.

Sealed Classes

Sealed classes are used for representing restricted class hierarchies, when a value can have one of the types from a limited set, but cannot have any other type. They are, in a sense, an extension of enum classes: the set of values for an enum type is also restricted, but each enum constant exists only as a single instance, whereas a subclass of a sealed class can have multiple instances which can contain state.

To declare a sealed class, you put the `sealed` modifier before the name of the class. A sealed class can have subclasses, but all of them must be declared in the same file as the sealed class itself. (Before Kotlin 1.1, the rules were even more strict: classes had to be nested inside the declaration of the sealed class).

```
sealed class Expr
data class Const(val number: Double) : Expr()
data class Sum(val e1: Expr, val e2: Expr) : Expr()
object NotANumber : Expr()
```

(The example above uses one additional new feature of Kotlin 1.1: the possibility for data classes to extend other classes, including sealed classes.)

A sealed class is [abstract](#) by itself, it cannot be instantiated directly and can have [abstract](#) members.

Sealed classes are not allowed to have non-[private](#) constructors (their constructors are [private](#) by default).

Note that classes which extend subclasses of a sealed class (indirect inheritors) can be placed anywhere, not necessarily in the same file.

The key benefit of using sealed classes comes into play when you use them in a [when expression](#). If it's possible to verify that the statement covers all cases, you don't need to add an `else` clause to the statement. However, this works only if you use `when` as an expression (using the result) and not as a statement.

```
fun eval(expr: Expr): Double = when(expr) {
    is Const -> expr.number
    is Sum -> eval(expr.e1) + eval(expr.e2)
    NotANumber -> Double.NaN
    // the `else` clause is not required because we've covered all the cases
}
```

Generics

As in Java, classes in Kotlin may have type parameters:

```
class Box<T>(t: T) {  
    var value = t  
}
```

In general, to create an instance of such a class, we need to provide the type arguments:

```
val box: Box<Int> = Box<Int>(1)
```

But if the parameters may be inferred, e.g. from the constructor arguments or by some other means, one is allowed to omit the type arguments:

```
val box = Box(1) // 1 has type Int, so the compiler figures out that we are talking about Box<Int>
```

Variance

One of the most tricky parts of Java's type system is wildcard types (see [Java Generics FAQ](#)). And Kotlin doesn't have any. Instead, it has two other things: declaration-site variance and type projections.

First, let's think about why Java needs those mysterious wildcards. The problem is explained in [Effective Java, 3rd Edition](#), Item 31: *Use bounded wildcards to increase API flexibility*. First, generic types in Java are **invariant**, meaning that `List<String>` is **not** a subtype of `List<Object>`. Why so? If `List` was not **invariant**, it would have been no better than Java's arrays, since the following code would have compiled and caused an exception at runtime:

```
// Java  
List<String> strs = new ArrayList<String>();  
List<Object> objs = strs; // !!! The cause of the upcoming problem sits here. Java prohibits this!  
objs.add(1); // Here we put an Integer into a list of Strings  
String s = strs.get(0); // !!! ClassCastException: Cannot cast Integer to String
```

So, Java prohibits such things in order to guarantee run-time safety. But this has some implications. For example, consider the `addAll()` method from `Collection` interface. What's the signature of this method? Intuitively, we'd put it this way:

```
// Java  
interface Collection<E> ... {  
    void addAll(Collection<E> items);  
}
```

But then, we would not be able to do the following simple thing (which is perfectly safe):

```
// Java  
void copyAll(Collection<Object> to, Collection<String> from) {  
    to.addAll(from);  
    // !!! Would not compile with the naive declaration of addAll:  
    // Collection<String> is not a subtype of Collection<Object>  
}
```

(In Java, we learned this lesson the hard way, see [Effective Java, 3rd Edition](#), Item 28: *Prefer lists to arrays*)

That's why the actual signature of `addAll()` is the following:

```
// Java  
interface Collection<E> ... {  
    void addAll(Collection<? extends E> items);  
}
```

The **wildcard type argument** `? extends E` indicates that this method accepts a collection of objects of `E` or *some subtype of E*, not just `E` itself. This means that we can safely **read** `E`'s from items (elements of this collection are instances of a subclass of `E`), but **cannot write** to it since we do not know what objects comply to that unknown subtype of `E`. In return for this limitation, we have the desired behaviour: `Collection<String>` *is* a subtype of `Collection<? extends Object>`. In "clever words", the wildcard with an **extends-bound** (**upper bound**) makes the type **covariant**.

The key to understanding why this trick works is rather simple: if you can only **take** items from a collection, then using a collection of `String`s and reading `Object`s from it is fine. Conversely, if you can only *put* items into the collection, it's OK to take a collection of `Object`s and put `String`s into it: in Java we have `List<? super String>` a **supertype** of `List<Object>`.

The latter is called **contravariance**, and you can only call methods that take `String` as an argument on `List<? super String>` (e.g., you can call `add(String)` or `set(int, String)`), while if you call something that returns `T` in `List<T>`, you don't get a `String`, but an `Object`.

Joshua Bloch calls those objects you only **read** from **Producers**, and those you only **write** to **Consumers**. He recommends: "*For maximum flexibility, use wildcard types on input parameters that represent producers or consumers*", and proposes the following mnemonic:

PECS stands for Producer-Extends, Consumer-Super.

NOTE: if you use a producer-object, say, `List<? extends Foo>`, you are not allowed to call `add()` or `set()` on this object, but this does not mean that this object is **immutable**: for example, nothing prevents you from calling `clear()` to remove all items from the list, since `clear()` does not take any parameters at all. The only thing guaranteed by wildcards (or other types of variance) is **type safety**. Immutability is a completely different story.

Declaration-site variance

Suppose we have a generic interface `Source<T>` that does not have any methods that take `T` as a parameter, only methods that return `T`:

```
// Java
interface Source<T> {
    T nextT();
}
```

Then, it would be perfectly safe to store a reference to an instance of `Source<String>` in a variable of type `Source<Object>` - there are no consumer-methods to call. But Java does not know this, and still prohibits it:

```
// Java
void demo(Source<String> strs) {
    Source<Object> objects = strs; // !!! Not allowed in Java
    // ...
}
```

To fix this, we have to declare objects of type `Source<? extends Object>`, which is sort of meaningless, because we can call all the same methods on such a variable as before, so there's no value added by the more complex type. But the compiler does not know that.

In Kotlin, there is a way to explain this sort of thing to the compiler. This is called **declaration-site variance**: we can annotate the **type parameter** `T` of `Source` to make sure that it is only **returned** (produced) from members of `Source<T>`, and never consumed. To do this we provide the **out** modifier:

```
interface Source<out T> {
    fun nextT(): T
}

fun demo(strs: Source<String>) {
    val objects: Source<Any> = strs // This is OK, since T is an out-parameter
    // ...
}
```

The general rule is: when a type parameter `T` of a class `C` is declared **out**, it may occur only in **out**-position in the members of `C`, but in return `C<Base>` can safely be a supertype of `C<Derived>`.

In "clever words" they say that the class `C` is **covariant** in the parameter `T`, or that `T` is a **covariant** type parameter. You can think of `C` as being a **producer** of `T`'s, and NOT a **consumer** of `T`'s.

The **out** modifier is called a **variance annotation**, and since it is provided at the type parameter declaration site, we talk about **declaration-site variance**. This is in contrast with Java's **use-site variance** where wildcards in the type usages make the types covariant.

In addition to **out**, Kotlin provides a complementary variance annotation: **in**. It makes a type parameter **contravariant**: it can only be consumed and never produced. A good example of a contravariant type is `Comparable`:

```
interface Comparable<in T> {
    operator fun compareTo(other: T): Int
}

fun demo(x: Comparable<Number>) {
    x.compareTo(1.0) // 1.0 has type Double, which is a subtype of Number
    // Thus, we can assign x to a variable of type Comparable<Double>
    val y: Comparable<Double> = x // OK!
}
```

We believe that the words **in** and **out** are self-explaining (as they were successfully used in C# for quite some time already), thus the mnemonic mentioned above is not really needed, and one can rephrase it for a higher purpose:

The Existential Transformation: Consumer in, Producer out! :-)

Type projections

Use-site variance: Type projections

It is very convenient to declare a type parameter `T` as *out* and avoid trouble with subtyping on the use site, but some classes **can't** actually be restricted to only return `T`'s! A good example of this is `Array`:

```
class Array<T>(val size: Int) {
    fun get(index: Int): T { ... }
    fun set(index: Int, value: T) { ... }
}
```

This class cannot be either co- or contravariant in `T`. And this imposes certain inflexibilities. Consider the following function:

```
fun copy(from: Array<Any>, to: Array<Any>) {
    assert(from.size == to.size)
    for (i in from.indices)
        to[i] = from[i]
}
```

This function is supposed to copy items from one array to another. Let's try to apply it in practice:

```
val ints: Array<Int> = arrayOf(1, 2, 3)
val any = Array<Any>(3) { "" }
copy(ints, any)
// ^ type is Array<Int> but Array<Any> was expected
```

Here we run into the same familiar problem: `Array<T>` is **invariant** in `T`, thus neither of `Array<Int>` and `Array<Any>` is a subtype of the other. Why? Again, because `copy` **might** be doing bad things, i.e. it might attempt to **write**, say, a `String` to `from`, and if we actually passed an array of `Int` there, a `ClassCastException` would have been thrown sometime later.

Then, the only thing we want to ensure is that `copy()` does not do any bad things. We want to prohibit it from **writing** to `from`, and we can:

```
fun copy(from: Array<out Any>, to: Array<Any>) { ... }
```

What has happened here is called **type projection**: we said that `from` is not simply an array, but a restricted (**projected**) one: we can only call those methods that return the type parameter `T`, in this case it means that we can only call `get()`. This is our approach to **use-site variance**, and corresponds to Java's `Array<? extends Object>`, but in a slightly simpler way.

You can project a type with **in** as well:

```
fun fill(dest: Array<in String>, value: String) { ... }
```

`Array<in String>` corresponds to Java's `Array<? super String>`, i.e. you can pass an array of `CharSequence` or an array of `Object` to the `fill()` function.

Star-projections

Sometimes you want to say that you know nothing about the type argument, but still want to use it in a safe way. The safe way here is to define such a projection of the generic type, that every concrete instantiation of that generic type would be a subtype of that projection.

Kotlin provides so called **star-projection** syntax for this:

- For `Foo<out T : TUpper>`, where `T` is a covariant type parameter with the upper bound `TUpper`, `Foo<*>` is equivalent to `Foo<out TUpper>`. It means that when the `T` is unknown you can safely *read* values of `TUpper` from `Foo<*>`.
- For `Foo<in T>`, where `T` is a contravariant type parameter, `Foo<*>` is equivalent to `Foo<in Nothing>`. It means there is nothing you can *write* to `Foo<*>` in a safe way when `T` is unknown.
- For `Foo<T : TUpper>`, where `T` is an invariant type parameter with the upper bound `TUpper`, `Foo<*>` is equivalent to `Foo<out TUpper>` for reading values and to `Foo<in Nothing>` for writing values.

If a generic type has several type parameters each of them can be projected independently. For example, if the type is declared as `interface Function<in T, out U>` we can imagine the following star-projections:

- `Function<*, String>` means `Function<in Nothing, String>`;
- `Function<Int, *>` means `Function<Int, out Any?>`;
- `Function<*, *>` means `Function<in Nothing, out Any?>`.

Note: star-projections are very much like Java's raw types, but safe.

Generic functions

Not only classes can have type parameters. Functions can, too. Type parameters are placed **before** the name of the function:

```
fun <T> singletonList(item: T): List<T> {  
    // ...  
}  
  
fun <T> T.basicToString() : String { // extension function  
    // ...  
}
```

To call a generic function, specify the type arguments at the call site **after** the name of the function:

```
val l = singletonList<Int>(1)
```

Type arguments can be omitted if they can be inferred from the context, so the following example works as well:

```
val l = singletonList(1)
```

Generic constraints

The set of all possible types that can be substituted for a given type parameter may be restricted by **generic constraints**.

Upper bounds

The most common type of constraint is an **upper bound** that corresponds to Java's *extends* keyword:

```
fun <T : Comparable<T>> sort(list: List<T>) { ... }
```

The type specified after a colon is the **upper bound**: only a subtype of `Comparable<T>` may be substituted for `T`. For example:

```
sort(listOf(1, 2, 3)) // OK. Int is a subtype of Comparable<Int>  
sort(listOf(HashMap<Int, String>())) // Error: HashMap<Int, String> is not a subtype of  
Comparable<HashMap<Int, String>>
```

The default upper bound (if none specified) is `Any?`. Only one upper bound can be specified inside the angle brackets. If the same type parameter needs more than one upper bound, we need a separate **where**-clause:

```
fun <T> copyWhenGreater(list: List<T>, threshold: T): List<String>
    where T : CharSequence,
        T : Comparable<T> {
    return list.filter { it > threshold }.map { it.toString() }
}
```

Type erasure

The type safety checks that Kotlin performs for generic declaration usages are only done at compile time. At runtime, the instances of generic types do not hold any information about their actual type arguments. The type information is said to be *erased*. For example, the instances of `Foo<Bar>` and `Foo<Baz?>` are erased to just `Foo<*>`.

Therefore, there is no general way to check whether an instance of a generic type was created with certain type arguments at runtime, and the compiler [prohibits such is-checks](#).

Type casts to generic types with concrete type arguments, e.g. `foo as List<String>`, cannot be checked at runtime. These [unchecked casts](#) can be used when type safety is implied by the high-level program logic but cannot be inferred directly by the compiler. The compiler issues a warning on unchecked casts, and at runtime, only the non-generic part is checked (equivalent to `foo as List<*>`).

The type arguments of generic function calls are also only checked at compile time. Inside the function bodies, the type parameters cannot be used for type checks, and type casts to type parameters (`foo as T`) are unchecked. However, [reified type parameters](#) of inline functions are substituted by the actual type arguments in the inlined function body at the call sites and thus can be used for type checks and casts, with the same restrictions for instances of generic types as described above.

Nested and Inner Classes

Classes can be nested in other classes:

```
class Outer {  
    private val bar: Int = 1  
    class Nested {  
        fun foo() = 2  
    }  
}  
  
val demo = Outer.Nested().foo() // == 2
```

Inner classes

A class may be marked as [inner](#) to be able to access members of outer class. Inner classes carry a reference to an object of an outer class:

```
class Outer {  
    private val bar: Int = 1  
    inner class Inner {  
        fun foo() = bar  
    }  
}  
  
val demo = Outer().Inner().foo() // == 1
```

See [Qualified this expressions](#) to learn about disambiguation of [this](#) in inner classes.

Anonymous inner classes

Anonymous inner class instances are created using an [object expression](#):

```
window.addMouseListener(object: MouseAdapter() {  
  
    override fun mouseClicked(e: MouseEvent) { ... }  
  
    override fun mouseEntered(e: MouseEvent) { ... }  
})
```

If the object is an instance of a functional Java interface (i.e. a Java interface with a single abstract method), you can create it using a lambda expression prefixed with the type of the interface:

```
val listener = ActionListener { println("clicked") }
```

Enum Classes

The most basic usage of enum classes is implementing type-safe enums:

```
enum class Direction {  
    NORTH, SOUTH, WEST, EAST  
}
```

Each enum constant is an object. Enum constants are separated with commas.

Initialization

Since each enum is an instance of the enum class, they can be initialized as:

```
enum class Color(val rgb: Int) {  
    RED(0xFF0000),  
    GREEN(0x00FF00),  
    BLUE(0x0000FF)  
}
```

Anonymous Classes

Enum constants can also declare their own anonymous classes:

```
enum class ProtocolState {  
    WAITING {  
        override fun signal() = TALKING  
    },  
  
    TALKING {  
        override fun signal() = WAITING  
    };  
  
    abstract fun signal(): ProtocolState  
}
```

with their corresponding methods, as well as overriding base methods. Note that if the enum class defines any members, you need to separate the enum constant definitions from the member definitions with a semicolon, just like in Java.

Enum entries cannot contain nested types other than inner classes (deprecated in Kotlin 1.2).

Implementing Interfaces in Enum Classes

An enum class may implement an interface (but not derive from a class), providing either a single interface members implementation for all of the entries, or separate ones for each entry within its anonymous class. This is done by adding the interfaces to the enum class declaration as follows:

```

import java.util.function.BinaryOperator
import java.util.function.IntBinaryOperator

//sampleStart
enum class IntArithmetics : BinaryOperator<Int>, IntBinaryOperator {
    PLUS {
        override fun apply(t: Int, u: Int): Int = t + u
    },
    TIMES {
        override fun apply(t: Int, u: Int): Int = t * u
    };

    override fun applyAsInt(t: Int, u: Int) = apply(t, u)
}
//sampleEnd

fun main(args: Array<String>) {
    val a = 13
    val b = 31
    for (f in IntArithmetics.values()) {
        println("$f($a, $b) = ${f.apply(a, b)}")
    }
}

```

Working with Enum Constants

Just like in Java, enum classes in Kotlin have synthetic methods allowing to list the defined enum constants and to get an enum constant by its name. The signatures of these methods are as follows (assuming the name of the enum class is `EnumClass`):

```

EnumClass.valueOf(value: String): EnumClass
EnumClass.values(): Array<EnumClass>

```

The `valueOf()` method throws an `IllegalArgumentException` if the specified name does not match any of the enum constants defined in the class.

Since Kotlin 1.1, it's possible to access the constants in an enum class in a generic way, using the `enumValues<T>()` and `enumValueOf<T>()` functions:

```

enum class RGB { RED, GREEN, BLUE }

inline fun <reified T : Enum<T>> printAllValues() {
    print(enumValues<T>().joinToString { it.name })
}

printAllValues<RGB>() // prints RED, GREEN, BLUE

```

Every enum constant has properties to obtain its name and position in the enum class declaration:

```

val name: String
val ordinal: Int

```

The enum constants also implement the [Comparable](#) interface, with the natural order being the order in which they are defined in the enum class.

Object Expressions and Declarations

Sometimes we need to create an object of a slight modification of some class, without explicitly declaring a new subclass for it. Java handles this case with *anonymous inner classes*. Kotlin slightly generalizes this concept with *object expressions* and *object declarations*.

Object expressions

To create an object of an anonymous class that inherits from some type (or types), we write:

```
window.addMouseListener(object : MouseAdapter() {
    override fun mouseClicked(e: MouseEvent) { ... }

    override fun mouseEntered(e: MouseEvent) { ... }
})
```

If a supertype has a constructor, appropriate constructor parameters must be passed to it. Many supertypes may be specified as a comma-separated list after the colon:

```
open class A(x: Int) {
    public open val y: Int = x
}

interface B { ... }

val ab: A = object : A(1), B {
    override val y = 15
}
```

If, by any chance, we need "just an object", with no nontrivial supertypes, we can simply say:

```
fun foo() {
    val adHoc = object {
        var x: Int = 0
        var y: Int = 0
    }
    print(adHoc.x + adHoc.y)
}
```

Note that anonymous objects can be used as types only in local and private declarations. If you use an anonymous object as a return type of a public function or the type of a public property, the actual type of that function or property will be the declared supertype of the anonymous object, or `Any` if you didn't declare any supertype. Members added in the anonymous object will not be accessible.

```
class C {
    // Private function, so the return type is the anonymous object type
    private fun foo() = object {
        val x: String = "x"
    }

    // Public function, so the return type is Any
    fun publicFoo() = object {
        val x: String = "x"
    }

    fun bar() {
        val x1 = foo().x // Works
        val x2 = publicFoo().x // ERROR: Unresolved reference 'x'
    }
}
```

Just like Java's anonymous inner classes, code in object expressions can access variables from the enclosing scope. (Unlike Java, this is not restricted to final variables.)

```

fun countClicks(window: JComponent) {
    var clickCount = 0
    var enterCount = 0

    window.addMouseListener(object : MouseAdapter() {
        override fun mouseClicked(e: MouseEvent) {
            clickCount++
        }

        override fun mouseEntered(e: MouseEvent) {
            enterCount++
        }
    })
    // ...
}

```

Object declarations

[Singleton](#) may be useful in several cases, and Kotlin (after Scala) makes it easy to declare singletons:

```

object DataProviderManager {
    fun registerDataProvider(provider: DataProvider) {
        // ...
    }

    val allDataProviders: Collection<DataProvider>
        get() = // ...
}

```

This is called an *object declaration*, and it always has a name following the [object](#) keyword. Just like a variable declaration, an object declaration is not an expression, and cannot be used on the right hand side of an assignment statement.

Object declaration's initialization is thread-safe.

To refer to the object, we use its name directly:

```
DataProviderManager.registerDataProvider(...)
```

Such objects can have supertypes:

```

object DefaultListener : MouseAdapter() {
    override fun mouseClicked(e: MouseEvent) { ... }

    override fun mouseEntered(e: MouseEvent) { ... }
}

```

NOTE: object declarations can't be local (i.e. be nested directly inside a function), but they can be nested into other object declarations or non-inner classes.

Companion Objects

An object declaration inside a class can be marked with the [companion](#) keyword:

```

class MyClass {
    companion object Factory {
        fun create(): MyClass = MyClass()
    }
}

```

Members of the companion object can be called by using simply the class name as the qualifier:

```
val instance = MyClass.create()
```

The name of the companion object can be omitted, in which case the name `Companion` will be used:

```
class MyClass {
    companion object { }
}
```

```
val x = MyClass.Companion
```

Note that, even though the members of companion objects look like static members in other languages, at runtime those are still instance members of real objects, and can, for example, implement interfaces:

```
interface Factory<T> {
    fun create(): T
}
```

```
class MyClass {
    companion object : Factory<MyClass> {
        override fun create(): MyClass = MyClass()
    }
}
```

However, on the JVM you can have members of companion objects generated as real static methods and fields, if you use the `@JvmStatic` annotation. See the [Java interoperability](#) section for more details.

Semantic difference between object expressions and declarations

There is one important semantic difference between object expressions and object declarations:

- object expressions are executed (and initialized) **immediately**, where they are used;
- object declarations are initialized **lazily**, when accessed for the first time;
- a companion object is initialized when the corresponding class is loaded (resolved), matching the semantics of a Java static initializer.

Delegation

Property Delegation

Delegated properties are described on a separate page: [Delegated Properties](#).

Implementation by Delegation

The [Delegation pattern](#) has proven to be a good alternative to implementation inheritance, and Kotlin supports it natively requiring zero boilerplate code. A class `Derived` can implement an interface `Base` by delegating all of its public members to a specified object:

```
interface Base {
    fun print()
}

class BaseImpl(val x: Int) : Base {
    override fun print() { print(x) }
}

class Derived(b: Base) : Base by b

fun main(args: Array<String>) {
    val b = BaseImpl(10)
    Derived(b).print()
}
```

The `by`-clause in the supertype list for `Derived` indicates that `b` will be stored internally in objects of `Derived` and the compiler will generate all the methods of `Base` that forward to `b`.

Overriding a member of an interface implemented by delegation

[Overrides](#) work as you might expect: the compiler will use your `override` implementations instead of those in the delegate object. If we were to add `override fun printMessage() { print("abc") }` to `Derived`, the program would print "abc" instead of "10" when `print` is called:

```
interface Base {
    fun printMessage()
    fun printMessageLine()
}

class BaseImpl(val x: Int) : Base {
    override fun printMessage() { print(x) }
    override fun printMessageLine() { println(x) }
}

class Derived(b: Base) : Base by b {
    override fun printMessage() { print("abc") }
}

fun main(args: Array<String>) {
    val b = BaseImpl(10)
    Derived(b).printMessage()
    Derived(b).printMessageLine()
}
```

Note, however, that members overridden in this way do not get called from the members of the delegate object, which can only access its own implementations of the interface members:

```

interface Base {
    val message: String
    fun print()
}

class BaseImpl(val x: Int) : Base {
    override val message = "BaseImpl: x = $x"
    override fun print() { println(message) }
}

class Derived(b: Base) : Base by b {
    // This property is not accessed from b's implementation of `print`
    override val message = "Message of Derived"
}

fun main(args: Array<String>) {
    val b = BaseImpl(10)
    val derived = Derived(b)
    derived.print()
    println(derived.message)
}

```


Delegated Properties

There are certain common kinds of properties, that, though we can implement them manually every time we need them, would be very nice to implement once and for all, and put into a library. Examples include:

- lazy properties: the value gets computed only upon first access;
- observable properties: listeners get notified about changes to this property;
- storing properties in a map, instead of a separate field for each property.

To cover these (and other) cases, Kotlin supports *delegated properties*:

```
class Example {  
    var p: String by Delegate()  
}
```

The syntax is: `val/var <property name>: <Type> by <expression>`. The expression after `by` is the *delegate*, because `get()` (and `set()`) corresponding to the property will be delegated to its `getValue()` and `setValue()` methods. Property delegates don't have to implement any interface, but they have to provide a `getValue()` function (and `setValue()` — for `vars`). For example:

```
class Delegate {  
    operator fun getValue(thisRef: Any?, property: KProperty<*>): String {  
        return "$thisRef, thank you for delegating '${property.name}' to me!"  
    }  
  
    operator fun setValue(thisRef: Any?, property: KProperty<*>, value: String) {  
        println("$value has been assigned to '${property.name}' in $thisRef.")  
    }  
}
```

When we read from `p` that delegates to an instance of `Delegate`, the `getValue()` function from `Delegate` is called, so that its first parameter is the object we read `p` from and the second parameter holds a description of `p` itself (e.g. you can take its name). For example:

```
val e = Example()  
println(e.p)
```

This prints:

```
Example@33a17727, thank you for delegating 'p' to me!
```

Similarly, when we assign to `p`, the `setValue()` function is called. The first two parameters are the same, and the third holds the value being assigned:

```
e.p = "NEW"
```

This prints

```
NEW has been assigned to 'p' in Example@33a17727.
```

The specification of the requirements to the delegated object can be found [below](#).

Note that since Kotlin 1.1 you can declare a delegated property inside a function or code block, it shouldn't necessarily be a member of a class. Below you can find [the example](#).

Standard Delegates

The Kotlin standard library provides factory methods for several useful kinds of delegates.

Lazy

[lazy\(\)](#) is a function that takes a lambda and returns an instance of `Lazy<T>` which can serve as a delegate for implementing a lazy property: the first call to `get()` executes the lambda passed to `lazy()` and remembers the result, subsequent calls to `get()` simply return the remembered result.

```

val lazyValue: String by lazy {
    println("computed!")
    "Hello"
}

fun main(args: Array<String>) {
    println(lazyValue)
    println(lazyValue)
}

```

By default, the evaluation of lazy properties is **synchronized**: the value is computed only in one thread, and all threads will see the same value. If the synchronization of initialization delegate is not required, so that multiple threads can execute it simultaneously, pass `LazyThreadSafetyMode.PUBLICATION` as a parameter to the `lazy()` function. And if you're sure that the initialization will always happen on a single thread, you can use `LazyThreadSafetyMode.NONE` mode, which doesn't incur any thread-safety guarantees and the related overhead.

Observable

[`Delegates.observable\(\)`](#) takes two arguments: the initial value and a handler for modifications. The handler gets called every time we assign to the property (*after* the assignment has been performed). It has three parameters: a property being assigned to, the old value and the new one:

```

import kotlin.properties.Delegates

class User {
    var name: String by Delegates.observable("<no name>") {
        prop, old, new ->
        println("$old -> $new")
    }
}

fun main(args: Array<String>) {
    val user = User()
    user.name = "first"
    user.name = "second"
}

```

If you want to be able to intercept an assignment and "veto" it, use [`vetoable\(\)`](#) instead of `observable()`. The handler passed to the `vetoable` is called *before* the assignment of a new property value has been performed.

Storing Properties in a Map

One common use case is storing the values of properties in a map. This comes up often in applications like parsing JSON or doing other "dynamic" things. In this case, you can use the map instance itself as the delegate for a delegated property.

```

class User(val map: Map<String, Any?>) {
    val name: String by map
    val age: Int by map
}

```

In this example, the constructor takes a map:

```

val user = User(mapOf(
    "name" to "John Doe",
    "age" to 25
))

```

Delegated properties take values from this map (by the string keys -- names of properties):

```

class User(val map: Map<String, Any?>) {
    val name: String by map
    val age: Int by map
}

fun main(args: Array<String>) {
    val user = User(mapOf(
        "name" to "John Doe",
        "age" to 25
    ))
    //sampleStart
    println(user.name) // Prints "John Doe"
    println(user.age) // Prints 25
    //sampleEnd
}

```

This works also for `var`'s properties if you use a `MutableMap` instead of read-only `Map` :

```

class MutableUser(val map: MutableMap<String, Any?>) {
    var name: String by map
    var age: Int by map
}

```

Local Delegated Properties (since 1.1)

You can declare local variables as delegated properties. For instance, you can make a local variable lazy:

```

fun example(computeFoo: () -> Foo) {
    val memoizedFoo by lazy(computeFoo)

    if (someCondition && memoizedFoo.isValid()) {
        memoizedFoo.doSomething()
    }
}

```

The `memoizedFoo` variable will be computed on the first access only. If `someCondition` fails, the variable won't be computed at all.

Property Delegate Requirements

Here we summarize requirements to delegate objects.

For a **read-only** property (i.e. a `val`), a delegate has to provide a function named `getValue` that takes the following parameters:

- `thisRef` — must be the same or a supertype of the *property owner* (for extension properties — the type being extended);
- `property` — must be of type `KProperty<*>` or its supertype.

this function must return the same type as `property` (or its subtype).

For a **mutable** property (a `var`), a delegate has to *additionally* provide a function named `setValue` that takes the following parameters:

- `thisRef` — same as for `getValue()` ;
- `property` — same as for `getValue()` ;
- new value — must be of the same type as a property or its supertype.

`getValue()` and/or `setValue()` functions may be provided either as member functions of the delegate class or extension functions. The latter is handy when you need to delegate property to an object which doesn't originally provide these functions. Both of the functions need to be marked with the `operator` keyword.

The delegate class may implement one of the interfaces `ReadOnlyProperty` and `ReadWriteProperty` containing the required `operator` methods. These interfaces are declared in the Kotlin standard library:

```

interface ReadOnlyProperty<in R, out T> {
    operator fun getValue(thisRef: R, property: KProperty<*>): T
}

interface ReadWriteProperty<in R, T> {
    operator fun getValue(thisRef: R, property: KProperty<*>): T
    operator fun setValue(thisRef: R, property: KProperty<*>, value: T)
}

```

Translation Rules

Under the hood for every delegated property the Kotlin compiler generates an auxiliary property and delegates to it. For instance, for the property `prop` the hidden property `prop$delegate` is generated, and the code of the accessors simply delegates to this additional property.

```

class C {
    var prop: Type by MyDelegate()
}

// this code is generated by the compiler instead:
class C {
    private val prop$delegate = MyDelegate()
    var prop: Type
        get() = prop$delegate.getValue(this, this::prop)
        set(value: Type) = prop$delegate.setValue(this, this::prop, value)
}

```

The Kotlin compiler provides all the necessary information about `prop` in the arguments: the first argument `this` refers to an instance of the outer class `C` and `this::prop` is a reflection object of the `KProperty` type describing `prop` itself.

Note that the syntax `this::prop` to refer a [bound callable reference](#) in the code directly is available only since Kotlin 1.1.

Providing a delegate (since 1.1)

By defining the `provideDelegate` operator you can extend the logic of creating the object to which the property implementation is delegated. If the object used on the right hand side of `by` defines `provideDelegate` as a member or extension function, that function will be called to create the property delegate instance.

One of the possible use cases of `provideDelegate` is to check property consistency when the property is created, not only in its getter or setter.

For example, if you want to check the property name before binding, you can write something like this:

```

class ResourceDelegate<T> : ReadOnlyProperty<MyUI, T> {
    override fun getValue(thisRef: MyUI, property: KProperty<*>): T { ... }
}

class ResourceLoader<T>(id: ResourceID<T>) {
    operator fun provideDelegate(
        thisRef: MyUI,
        prop: KProperty<*>
    ): ReadOnlyProperty<MyUI, T> {
        checkProperty(thisRef, prop.name)
        // create delegate
        return ResourceDelegate()
    }

    private fun checkProperty(thisRef: MyUI, name: String) { ... }
}

class MyUI {
    fun <T> bindResource(id: ResourceID<T>): ResourceLoader<T> { ... }

    val image by bindResource(ResourceID.image_id)
    val text by bindResource(ResourceID.text_id)
}

```

The parameters of `provideDelegate` are the same as for `getValue`:

- `thisRef` — must be the same or a supertype of the *property owner* (for extension properties — the type being extended);
- `property` — must be of type `KProperty<*>` or its supertype.

The `provideDelegate` method is called for each property during the creation of the `MyUI` instance, and it performs the necessary validation right away.

Without this ability to intercept the binding between the property and its delegate, to achieve the same functionality you'd have to pass the property name explicitly, which isn't very convenient:

```
// Checking the property name without "provideDelegate" functionality
class MyUI {
    val image by bindResource(ResourceID.image_id, "image")
    val text by bindResource(ResourceID.text_id, "text")
}

fun <T> MyUI.bindResource(
    id: ResourceID<T>,
    propertyName: String
): ReadOnlyProperty<MyUI, T> {
    checkProperty(this, propertyName)
    // create delegate
}
```

In the generated code, the `provideDelegate` method is called to initialize the auxiliary `prop$delegate` property. Compare the generated code for the property declaration `val prop: Type by MyDelegate()` with the generated code [above](#) (when the `provideDelegate` method is not present):

```
class C {
    var prop: Type by MyDelegate()
}

// this code is generated by the compiler
// when the 'provideDelegate' function is available:
class C {
    // calling "provideDelegate" to create the additional "delegate" property
    private val prop$delegate = MyDelegate().provideDelegate(this, this::prop)
    var prop: Type
        get() = prop$delegate.getValue(this, this::prop)
        set(value: Type) = prop$delegate.setValue(this, this::prop, value)
}
```

Note that the `provideDelegate` method affects only the creation of the auxiliary property and doesn't affect the code generated for getter or setter.

Functions and Lambdas

Functions

Function Declarations

Functions in Kotlin are declared using the `fun` keyword:

```
fun double(x: Int): Int {  
    return 2 * x  
}
```

Function Usage

Calling functions uses the traditional approach:

```
val result = double(2)
```

Calling member functions uses the dot notation:

```
Sample().foo() // create instance of class Sample and call foo
```

Parameters

Function parameters are defined using Pascal notation, i.e. *name: type*. Parameters are separated using commas. Each parameter must be explicitly typed:

```
fun powerOf(number: Int, exponent: Int) { ... }
```

Default Arguments

Function parameters can have default values, which are used when a corresponding argument is omitted. This allows for a reduced number of overloads compared to other languages:

```
fun read(b: Array<Byte>, off: Int = 0, len: Int = b.size) { ... }
```

Default values are defined using the `=` after type along with the value.

Overriding methods always use the same default parameter values as the base method. When overriding a method with default parameters values, the default parameter values must be omitted from the signature:

```
open class A {  
    open fun foo(i: Int = 10) { ... }  
}  
  
class B : A() {  
    override fun foo(i: Int) { ... } // no default value allowed  
}
```

If a default parameter precedes a parameter with no default value, the default value can be used only by calling the function with [named arguments](#):

```
fun foo(bar: Int = 0, baz: Int) { ... }  
  
foo(baz = 1) // The default value bar = 0 is used
```

But if a last argument [lambda](#) is passed to a function call outside the parentheses, passing no values for the default parameters is allowed:

```
fun foo(bar: Int = 0, baz: Int = 1, qux: () -> Unit) { ... }

foo(1) { println("hello") } // Uses the default value baz = 1
foo { println("hello") }    // Uses both default values bar = 0 and baz = 1
```

Named Arguments

Function parameters can be named when calling functions. This is very convenient when a function has a high number of parameters or default ones.

Given the following function:

```
fun reformat(str: String,
             normalizeCase: Boolean = true,
             upperCaseFirstLetter: Boolean = true,
             divideByCamelHumps: Boolean = false,
             wordSeparator: Char = ' ') {
    ...
}
```

we could call this using default arguments:

```
reformat(str)
```

However, when calling it with non-default, the call would look something like:

```
reformat(str, true, true, false, '_')
```

With named arguments we can make the code much more readable:

```
reformat(str,
         normalizeCase = true,
         upperCaseFirstLetter = true,
         divideByCamelHumps = false,
         wordSeparator = '_')
)
```

and if we do not need all arguments:

```
reformat(str, wordSeparator = '_')
```

When a function is called with both positional and named arguments, all the positional arguments should be placed before the first named one. For example, the call `f(1, y = 2)` is allowed, but `f(x = 1, 2)` is not.

[Variable number of arguments \(vararg\)](#) can be passed in the named form by using the **spread** operator:

```
fun foo(vararg strings: String) { ... }

foo(strings = *arrayOf("a", "b", "c"))
```

Note that the named argument syntax cannot be used when calling Java functions, because Java bytecode does not always preserve names of function parameters.

Unit-returning functions

If a function does not return any useful value, its return type is `Unit`. `Unit` is a type with only one value - `Unit`. This value does not have to be returned explicitly:

```
fun printHello(name: String?): Unit {
    if (name != null)
        println("Hello ${name}")
    else
        println("Hi there!")
    // `return Unit` or `return` is optional
}
```

The `Unit` return type declaration is also optional. The above code is equivalent to:

```
fun printHello(name: String?) { ... }
```

Single-Expression functions

When a function returns a single expression, the curly braces can be omitted and the body is specified after a `=` symbol:

```
fun double(x: Int): Int = x * 2
```

Explicitly declaring the return type is [optional](#) when this can be inferred by the compiler:

```
fun double(x: Int) = x * 2
```

Explicit return types

Functions with block body must always specify return types explicitly, unless it's intended for them to return `Unit`, in which case it is [optional](#). Kotlin does not infer return types for functions with block bodies because such functions may have complex control flow in the body, and the return type will be non-obvious to the reader (and sometimes even for the compiler).

Variable number of arguments (Varargs)

A parameter of a function (normally the last one) may be marked with `vararg` modifier:

```
fun <T> asList(vararg ts: T): List<T> {  
    val result = ArrayList<T>()  
    for (t in ts) // ts is an Array  
        result.add(t)  
    return result  
}
```

allowing a variable number of arguments to be passed to the function:

```
val list = asList(1, 2, 3)
```

Inside a function a `vararg`-parameter of type `T` is visible as an array of `T`, i.e. the `ts` variable in the example above has type `Array<out T>`.

Only one parameter may be marked as `vararg`. If a `vararg` parameter is not the last one in the list, values for the following parameters can be passed using the named argument syntax, or, if the parameter has a function type, by passing a lambda outside parentheses.

When we call a `vararg`-function, we can pass arguments one-by-one, e.g. `asList(1, 2, 3)`, or, if we already have an array and want to pass its contents to the function, we use the **spread** operator (prefix the array with `*`):

```
val a = arrayOf(1, 2, 3)  
val list = asList(-1, 0, *a, 4)
```

Infix notation

Functions marked with the `infix` keyword can also be called using the infix notation (omitting the dot and the parentheses for the call). Infix functions must satisfy the following requirements:

- They must be member functions or [extension functions](#);
- They must have a single parameter;
- The parameter must not [accept variable number of arguments](#) and must have no [default value](#).

```
infix fun Int.shl(x: Int): Int { ... }
```

```
// calling the function using the infix notation  
1 shl 2
```

```
// is the same as  
1.shl(2)
```


⚠ Infix function calls have lower precedence than the arithmetic operators, type casts, and the rangeTo operator. The following expressions are equivalent:

— 1 shl 2 + 3 and 1 shl (2 + 3)
— 0 until n * 2 and 0 until (n * 2)
— xs union ys as Set<*> and xs union (ys as Set<*>)

On the other hand, infix function call's precedence is higher than that of the boolean operators && and ||, is- and in-checks, and some other operators. These expressions are equivalent as well:

— a && b xor c and a && (b xor c)
— a xor b in c and (a xor b) in c

See the [Grammar reference](#) for the complete operators precedence hierarchy.

Note that infix functions always require both the receiver and the parameter to be specified. When you're calling a method on the current receiver using the infix notation, you need to use `this` explicitly; unlike regular method calls, it cannot be omitted. This is required to ensure unambiguous parsing.

```
class MyStringCollection {
    infix fun add(s: String) { ... }

    fun build() {
        this add "abc"    // Correct
        add("abc")        // Correct
        add "abc"         // Incorrect: the receiver must be specified
    }
}
```

Function Scope

In Kotlin functions can be declared at top level in a file, meaning you do not need to create a class to hold a function, which you are required to do in languages such as Java, C# or Scala. In addition to top level functions, Kotlin functions can also be declared local, as member functions and extension functions.

Local Functions

Kotlin supports local functions, i.e. a function inside another function:

```
fun dfs(graph: Graph) {
    fun dfs(current: Vertex, visited: Set<Vertex>) {
        if (!visited.add(current)) return
        for (v in current.neighbors)
            dfs(v, visited)
    }

    dfs(graph.vertices[0], HashSet())
}
```

Local function can access local variables of outer functions (i.e. the closure), so in the case above, the *visited* can be a local variable:

```
fun dfs(graph: Graph) {
    val visited = HashSet<Vertex>()
    fun dfs(current: Vertex) {
        if (!visited.add(current)) return
        for (v in current.neighbors)
            dfs(v)
    }

    dfs(graph.vertices[0])
}
```

Member Functions

A member function is a function that is defined inside a class or object:

```
class Sample() {  
    fun foo() { print("Foo") }  
}
```

Member functions are called with dot notation:

```
Sample().foo() // creates instance of class Sample and calls foo
```

For more information on classes and overriding members see [Classes](#) and [Inheritance](#).

Generic Functions

Functions can have generic parameters which are specified using angle brackets before the function name:

```
fun <T> singletonList(item: T): List<T> { ... }
```

For more information on generic functions see [Generics](#).

Inline Functions

Inline functions are explained [here](#).

Extension Functions

Extension functions are explained in [their own section](#).

Higher-Order Functions and Lambdas

Higher-Order functions and Lambdas are explained in [their own section](#).

Tail recursive functions

Kotlin supports a style of functional programming known as [tail recursion](#). This allows some algorithms that would normally be written using loops to instead be written using a recursive function, but without the risk of stack overflow. When a function is marked with the `tailrec` modifier and meets the required form, the compiler optimises out the recursion, leaving behind a fast and efficient loop based version instead:

```
val eps = 1E-10 // "good enough", could be 10^-15
```

```
tailrec fun findFixPoint(x: Double = 1.0): Double  
    = if (Math.abs(x - Math.cos(x)) < eps) x else findFixPoint(Math.cos(x))
```

This code calculates the fixpoint of cosine, which is a mathematical constant. It simply calls `Math.cos` repeatedly starting at 1.0 until the result doesn't change any more, yielding a result of 0.7390851332151611 for the specified `eps` precision. The resulting code is equivalent to this more traditional style:

```
val eps = 1E-10 // "good enough", could be 10^-15
```

```
private fun findFixPoint(): Double {  
    var x = 1.0  
    while (true) {  
        val y = Math.cos(x)  
        if (Math.abs(x - y) < eps) return x  
        x = Math.cos(x)  
    }  
}
```

To be eligible for the `tailrec` modifier, a function must call itself as the last operation it performs. You cannot use tail recursion when there is more code after the recursive call, and you cannot use it within `try/catch/finally` blocks. Currently tail recursion is only supported in the JVM backend.

Higher-Order Functions and Lambdas

Kotlin functions are [first-class](#), which means that they can be stored in variables and data structures, passed as arguments to and returned from other [higher-order functions](#). You can operate with functions in any way that is possible for other non-function values.

To facilitate this, Kotlin, as a statically typed programming language, uses a family of [function types](#) to represent functions and provides a set of specialized language constructs, such as [lambda expressions](#).

Higher-Order Functions

A higher-order function is a function that takes functions as parameters, or returns a function.

A good example is the [functional programming idiom fold](#) for collections, which takes an initial accumulator value and a combining function and builds its return value by consecutively combining current accumulator value with each collection element, replacing the accumulator:

```
fun <T, R> Collection<T>.fold(
    initial: R,
    combine: (acc: R, nextElement: T) -> R
): R {
    var accumulator: R = initial
    for (element: T in this) {
        accumulator = combine(accumulator, element)
    }
    return accumulator
}
```

In the code above, the parameter `combine` has a [function type](#) `(R, T) -> R`, so it accepts a function that takes two arguments of types `R` and `T` and returns a value of type `R`. It is [invoked](#) inside the `for`-loop, and the return value is then assigned to `accumulator`.

To call `fold`, we need to pass it an [instance of the function type](#) as an argument, and lambda expressions ([described in more detail below](#)) are widely used for this purpose at higher-order function call sites:

```
fun main(args: Array<String>) {
    //sampleStart
    val items = listOf(1, 2, 3, 4, 5)

    // Lambdas are code blocks enclosed in curly braces.
    items.fold(0, {
        // When a lambda has parameters, they go first, followed by '->'
        acc: Int, i: Int ->
        print("acc = $acc, i = $i, ")
        val result = acc + i
        println("result = $result")
        // The last expression in a lambda is considered the return value:
        result
    })

    // Parameter types in a lambda are optional if they can be inferred:
    val joinedToString = items.fold("Elements:", { acc, i -> acc + " " + i })

    // Function references can also be used for higher-order function calls:
    val product = items.fold(1, Int::times)
    //sampleEnd
    println("joinedToString = $joinedToString")
    println("product = $product")
}
```

The following sections explain in more detail the concepts mentioned so far.

Function types

Kotlin uses a family of function types like `(Int) -> String` for declarations that deal with functions: `val onClick: () -> Unit = ...`.

These types have a special notation that corresponds to the signatures of the functions, i.e. their parameters and return values:

- All function types have a parenthesized parameter types list and a return type: `(A, B) -> C` denotes a type that represents functions taking two arguments of types `A` and `B` and returning a value of type `C`. The parameter types list may be empty, as in `() -> A`. The [Unit return type](#) cannot be omitted.
- Function types can optionally have an additional *receiver* type, which is specified before a dot in the notation: the type `A.(B) -> C` represents functions that can be called on a receiver object of `A` with a parameter of `B` and return a value of `C`. [Function literals with receiver](#) are often used along with these types.
- [Suspending functions](#) belong to function types of a special kind, which have a `suspend` modifier in the notation, such as `suspend () -> Unit` or `suspend A.(B) -> C`.

The function type notation can optionally include names for the function parameters: `(x: Int, y: Int) -> Point`. These names can be used for documenting the meaning of the parameters.

To specify that a function type is [nullable](#), use parentheses: `((Int, Int) -> Int)?`.

Function types can be combined using parentheses: `(Int) -> ((Int) -> Unit)`

The arrow notation is right-associative, `(Int) -> (Int) -> Unit` is equivalent to the previous example, but not to `((Int) -> (Int)) -> Unit`.

You can also give a function type an alternative name by using [a type alias](#):

```
typealias ClickHandler = (Button, ClickEvent) -> Unit
```

Instantiating a function type

There are several ways to obtain an instance of a function type:

- Using a code block within a function literal, in one of the forms:
 - a [lambda expression](#): `{ a, b -> a + b }`,
 - an [anonymous function](#): `fun(s: String): Int { return s.toIntOrNull() ?: 0 }`

[Function literals with receiver](#) can be used as values of function types with receiver.

- Using a callable reference to an existing declaration:
 - a top-level, local, member, or extension [function](#): `::isOdd`, `String::toInt`,
 - a top-level, member, or extension [property](#): `List<Int>::size`,
 - a [constructor](#): `::Regex`

These include [bound callable references](#) that point to a member of a particular instance: `foo::toString`.

- Using instances of a custom class that implements a function type as an interface:

```
class IntTransformer: (Int) -> Int {
    override operator fun invoke(x: Int): Int = TODO()
}
```

```
val intFunction: (Int) -> Int = IntTransformer()
```

The compiler can infer the function types for variables if there is enough information:

```
val a = { i: Int -> i + 1 } // The inferred type is (Int) -> Int
```

Non-literal values of function types with and without receiver are interchangeable, so that the receiver can stand in for the first parameter, and vice versa. For instance, a value of type `(A, B) -> C` can be passed or assigned where a `A.(B) -> C` is expected and the other way around:

```

fun main(args: Array<String>) {
    //sampleStart
    val repeatFun: String.(Int) -> String = { times -> this.repeat(times) }
    val twoParameters: (String, Int) -> String = repeatFun // OK

    fun runTransformation(f: (String, Int) -> String): String {
        return f("hello", 3)
    }
    val result = runTransformation(repeatFun) // OK
    //sampleEnd
    println("result = $result")
}

```

Note that a function type with no receiver is inferred by default, even if a variable is initialized with a reference to an extension function. To alter that, specify the variable type explicitly.

Invoking a function type instance

A value of a function type can be invoked by using its [invoke\(...\) operator](#): `f.invoke(x)` or just `f(x)`.

If the value has a receiver type, the receiver object should be passed as the first argument. Another way to invoke a value of a function type with receiver is to prepend it with the receiver object, as if the value were an [extension function](#): `1.foo(2)`,

Example:

```

fun main(args: Array<String>) {
    //sampleStart
    val stringPlus: (String, String) -> String = String::plus
    val intPlus: Int.(Int) -> Int = Int::plus

    println(stringPlus.invoke("<-", ">-"))
    println(stringPlus("Hello, ", "world!"))

    println(intPlus.invoke(1, 1))
    println(intPlus(1, 2))
    println(2.intPlus(3)) // extension-like call
    //sampleEnd
}

```

Inline functions

Sometimes it is beneficial to use [inline functions](#), which provide flexible control flow, for higher-order functions.

Lambda Expressions and Anonymous Functions

Lambda expressions and anonymous functions are 'function literals', i.e. functions that are not declared, but passed immediately as an expression. Consider the following example:

```
max(strings, { a, b -> a.length < b.length })
```

Function `max` is a higher-order function, it takes a function value as the second argument. This second argument is an expression that is itself a function, i.e. a function literal, which is equivalent to the following named function:

```
fun compare(a: String, b: String): Boolean = a.length < b.length
```

Lambda expression syntax

The full syntactic form of lambda expressions is as follows:

```
val sum = { x: Int, y: Int -> x + y }
```

A lambda expression is always surrounded by curly braces, parameter declarations in the full syntactic form go inside curly braces and have optional type annotations, the body goes after an `->` sign. If the inferred return type of the lambda is not `Unit`, the last (or possibly single) expression inside the lambda body is treated as the return value.

If we leave all the optional annotations out, what's left looks like this:

```
val sum: (Int, Int) -> Int = { x, y -> x + y }
```

Passing a lambda to the last parameter

In Kotlin, there is a convention that if the last parameter of a function accepts a function, a lambda expression that is passed as the corresponding argument can be placed outside the parentheses:

```
val product = items.fold(1) { acc, e -> acc * e }
```

If the lambda is the only argument to that call, the parentheses can be omitted entirely:

```
run { println("...") }
```

it: implicit name of a single parameter

It's very common that a lambda expression has only one parameter.

If the compiler can figure the signature out itself, it is allowed not to declare the only parameter and omit `->`. The parameter will be implicitly declared under the name `it`:

```
ints.filter { it > 0 } // this literal is of type '(it: Int) -> Boolean'
```

Returning a value from a lambda expression

We can explicitly return a value from the lambda using the [qualified return](#) syntax. Otherwise, the value of the last expression is implicitly returned.

Therefore, the two following snippets are equivalent:

```
ints.filter {  
    val shouldFilter = it > 0  
    shouldFilter  
}
```

```
ints.filter {  
    val shouldFilter = it > 0  
    return@filter shouldFilter  
}
```

This convention, along with [passing a lambda expression outside parentheses](#), allows for [LINQ-style](#) code:

```
strings.filter { it.length == 5 }.sortedBy { it }.map { it.toUpperCase() }
```

Underscore for unused variables (since 1.1)

If the lambda parameter is unused, you can place an underscore instead of its name:

```
map.forEach { _, value -> println("$value!") }
```

Destructuring in lambdas (since 1.1)

Destructuring in lambdas is described as a part of [destructuring declarations](#).

Anonymous functions

One thing missing from the lambda expression syntax presented above is the ability to specify the return type of the function. In most cases, this is unnecessary because the return type can be inferred automatically. However, if you do need to specify it explicitly, you can use an alternative syntax: an *anonymous function*.

```
fun(x: Int, y: Int): Int = x + y
```

An anonymous function looks very much like a regular function declaration, except that its name is omitted. Its body can be either an expression (as shown above) or a block:

```
fun(x: Int, y: Int): Int {  
    return x + y  
}
```

The parameters and the return type are specified in the same way as for regular functions, except that the parameter types can be omitted if they can be inferred from context:

```
ints.filter(fun(item) = item > 0)
```

The return type inference for anonymous functions works just like for normal functions: the return type is inferred automatically for anonymous functions with an expression body and has to be specified explicitly (or is assumed to be `Unit`) for anonymous functions with a block body.

Note that anonymous function parameters are always passed inside the parentheses. The shorthand syntax allowing to leave the function outside the parentheses works only for lambda expressions.

One other difference between lambda expressions and anonymous functions is the behavior of [non-local returns](#). A `return` statement without a label always returns from the function declared with the `fun` keyword. This means that a `return` inside a lambda expression will return from the enclosing function, whereas a `return` inside an anonymous function will return from the anonymous function itself.

Closures

A lambda expression or anonymous function (as well as a [local function](#) and an [object expression](#)) can access its *closure*, i.e. the variables declared in the outer scope. Unlike Java, the variables captured in the closure can be modified:

```
var sum = 0
ints.filter { it > 0 }.forEach {
    sum += it
}
print(sum)
```

Function literals with receiver

[Function types](#) with receiver, such as `A.(B) -> C`, can be instantiated with a special form of function literals – function literals with receiver.

As said above, Kotlin provides the ability [to call an instance](#) of a function type with receiver providing the *receiver object*.

Inside the body of the function literal, the receiver object passed to a call becomes an *implicit this*, so that you can access the members of that receiver object without any additional qualifiers, or access the receiver object using a [this expression](#).

This behavior is similar to [extension functions](#), which also allow you to access the members of the receiver object inside the body of the function.

Here is an example of a function literal with receiver along with its type, where `plus` is called on the receiver object:

```
val sum: Int.(Int) -> Int = { other -> plus(other) }
```

The anonymous function syntax allows you to specify the receiver type of a function literal directly. This can be useful if you need to declare a variable of a function type with receiver, and to use it later.

```
val sum = fun Int.(other: Int): Int = this + other
```

Lambda expressions can be used as function literals with receiver when the receiver type can be inferred from context. One of the most important examples of their usage is [type-safe builders](#):

```
class HTML {
    fun body() { ... }
}

fun html(init: HTML.() -> Unit): HTML {
    val html = HTML() // create the receiver object
    html.init()        // pass the receiver object to the lambda
    return html
}

html {                // lambda with receiver begins here
    body()             // calling a method on the receiver object
}
```

Inline Functions

Using [higher-order functions](#) imposes certain runtime penalties: each function is an object, and it captures a closure, i.e. those variables that are accessed in the body of the function. Memory allocations (both for function objects and classes) and virtual calls introduce runtime overhead.

But it appears that in many cases this kind of overhead can be eliminated by inlining the lambda expressions. The functions shown below are good examples of this situation. I.e., the `lock()` function could be easily inlined at call-sites. Consider the following case:

```
lock(l) { foo() }
```

Instead of creating a function object for the parameter and generating a call, the compiler could emit the following code:

```
l.lock()
try {
    foo()
}
finally {
    l.unlock()
}
```

Isn't it what we wanted from the very beginning?

To make the compiler do this, we need to mark the `lock()` function with the `inline` modifier:

```
inline fun <T> lock(lock: Lock, body: () -> T): T { ... }
```

The `inline` modifier affects both the function itself and the lambdas passed to it: all of those will be inlined into the call site.

Inlining may cause the generated code to grow; however, if we do it in a reasonable way (i.e. avoiding inlining large functions), it will pay off in performance, especially at "megamorphic" call-sites inside loops.

noinline

In case you want only some of the lambdas passed to an inline function to be inlined, you can mark some of your function parameters with the `noinline` modifier:

```
inline fun foo(inlined: () -> Unit, noinline notInlined: () -> Unit) { ... }
```

Inlinable lambdas can only be called inside the inline functions or passed as inlinable arguments, but `noinline` ones can be manipulated in any way we like: stored in fields, passed around etc.

Note that if an inline function has no inlinable function parameters and no [reified type parameters](#), the compiler will issue a warning, since inlining such functions is very unlikely to be beneficial (you can suppress the warning if you are sure the inlining is needed using the annotation `@Suppress("NOTHING_TO_INLINE")`).

Non-local returns

In Kotlin, we can only use a normal, unqualified `return` to exit a named function or an anonymous function. This means that to exit a lambda, we have to use a [label](#), and a bare `return` is forbidden inside a lambda, because a lambda cannot make the enclosing function return:

```
fun ordinaryFunction(block: () -> Unit) {
    println("hi!")
}
//sampleStart
fun foo() {
    ordinaryFunction {
        return // ERROR: cannot make `foo` return here
    }
}
//sampleEnd
fun main(args: Array<String>) {
    foo()
}
```


But if the function the lambda is passed to is inlined, the return can be inlined as well, so it is allowed:

```
inline fun inlined(block: () -> Unit) { println("hi!") }

//sampleStart
fun foo() {
    inlined {
        return // OK: the lambda is inlined
    }
}
//sampleEnd
fun main(args: Array<String>) {
    foo()
}
```

Such returns (located in a lambda, but exiting the enclosing function) are called *non-local* returns. We are used to this sort of construct in loops, which inline functions often enclose:

```
fun hasZeros(ints: List<Int>): Boolean {
    ints.forEach {
        if (it == 0) return true // returns from hasZeros
    }
    return false
}
```

Note that some inline functions may call the lambdas passed to them as parameters not directly from the function body, but from another execution context, such as a local object or a nested function. In such cases, non-local control flow is also not allowed in the lambdas. To indicate that, the lambda parameter needs to be marked with the `crossinline` modifier:

```
inline fun f(crossinline body: () -> Unit) {
    val f = object: Runnable {
        override fun run() = body()
    }
    // ...
}
```

break and continue are not yet available in inlined lambdas, but we are planning to support them too.

Reified type parameters

Sometimes we need to access a type passed to us as a parameter:

```
fun <T> TreeNode.findParentOfType(clazz: Class<T>): T? {
    var p = parent
    while (p != null && !clazz.isInstance(p)) {
        p = p.parent
    }
    @Suppress("UNCHECKED_CAST")
    return p as T?
}
```

Here, we walk up a tree and use reflection to check if a node has a certain type. It's all fine, but the call site is not very pretty:

```
treeNode.findParentOfType(MyTreeNode::class.java)
```

What we actually want is simply pass a type to this function, i.e. call it like this:

```
treeNode.findParentOfType<MyTreeNode>()
```

To enable this, inline functions support *reified type parameters*, so we can write something like this:

```
inline fun <reified T> TreeNode.findParentOfType(): T? {
    var p = parent
    while (p != null && p !is T) {
        p = p.parent
    }
    return p as T?
}
```

We qualified the type parameter with the `reified` modifier, now it's accessible inside the function, almost as if it were a normal class. Since the function is inlined, no reflection is needed, normal operators like `!is` and `as` are working now. Also, we can call it as mentioned above: `myTree.findParentOfType<MyTreeNodeType>()`.

Though reflection may not be needed in many cases, we can still use it with a reified type parameter:

```
inline fun <reified T> membersOf() = T::class.members

fun main(s: Array<String>) {
    println(membersOf<StringBuilder>().joinToString("\n"))
}
```

Normal functions (not marked as inline) cannot have reified parameters. A type that does not have a run-time representation (e.g. a non-reified type parameter or a fictitious type like `Nothing`) cannot be used as an argument for a reified type parameter.

For a low-level description, see the [spec document](#).

Inline properties (since 1.1)

The `inline` modifier can be used on accessors of properties that don't have a backing field. You can annotate individual property accessors:

```
val foo: Foo
    inline get() = Foo()

var bar: Bar
    get() = ...
    inline set(v) { ... }
```

You can also annotate an entire property, which marks both of its accessors as inline:

```
inline var bar: Bar
    get() = ...
    set(v) { ... }
```

At the call site, inline accessors are inlined as regular inline functions.

Restrictions for public API inline functions

When an inline function is `public` or `protected` and is not a part of a `private` or `internal` declaration, it is considered a [module's](#) public API. It can be called in other modules and is inlined at such call sites as well.

This imposes certain risks of binary incompatibility caused by changes in the module that declares an inline function in case the calling module is not re-compiled after the change.

To eliminate the risk of such incompatibility being introduced by a change in **non**-public API of a module, the public API inline functions are not allowed to use non-public-API declarations, i.e. `private` and `internal` declarations and their parts, in their bodies.

An `internal` declaration can be annotated with `@PublishedApi`, which allows its use in public API inline functions. When an `internal` inline function is marked as `@PublishedApi`, its body is checked too, as if it were public.

Coroutines

⚠ Coroutines are *experimental* in Kotlin 1.1+. See details [below](#)

Some APIs initiate long-running operations (such as network IO, file IO, CPU- or GPU-intensive work, etc) and require the caller to block until they complete. Coroutines provide a way to avoid blocking a thread and replace it with a cheaper and more controllable operation: *suspension* of a coroutine.

Coroutines simplify asynchronous programming by putting the complications into libraries. The logic of the program can be expressed *sequentially* in a coroutine, and the underlying library will figure out the asynchrony for us. The library can wrap relevant parts of the user code into callbacks, subscribe to relevant events, schedule execution on different threads (or even different machines!), and the code remains as simple as if it was sequentially executed.

Many asynchronous mechanisms available in other languages can be implemented as libraries using Kotlin coroutines. This includes [async/await](#) from C# and ECMAScript, [channels](#) and [select](#) from Go, and [generators/yield](#) from C# and Python. See the description [below](#) for libraries providing such constructs.

Blocking vs Suspending

Basically, coroutines are computations that can be *suspended* without *blocking a thread*. Blocking threads is often expensive, especially under high load, because only a relatively small number of threads is practical to keep around, so blocking one of them leads to some important work being delayed.

Coroutine suspension is almost free, on the other hand. No context switch or any other involvement of the OS is required. And on top of that, suspension can be controlled by a user library to a large extent: as library authors, we can decide what happens upon a suspension and optimize/log/intercept according to our needs.

Another difference is that coroutines can not be suspended at random instructions, but rather only at so called *suspension points*, which are calls to specially marked functions.

Suspending functions

A suspension happens when we call a function marked with the special modifier, `suspend`:

```
suspend fun doSomething(foo: Foo): Bar { ... }
```

Such functions are called *suspending functions*, because calls to them may suspend a coroutine (the library can decide to proceed without suspension, if the result for the call in question is already available). Suspending functions can take parameters and return values in the same manner as regular functions, but they can only be called from coroutines and other suspending functions, as well as function literals inlined into those.

In fact, to start a coroutine, there must be at least one suspending function, and it is usually a suspending lambda. Let's look at an example, a simplified `async()` function (from the [kotlinx.coroutines](#) library):

```
fun <T> async(block: suspend () -> T)
```

Here, `async()` is a regular function (not a suspending function), but the `block` parameter has a function type with the `suspend` modifier: `suspend () -> T`. So, when we pass a lambda to `async()`, it is a *suspending lambda*, and we can call a suspending function from it:

```
async {  
    doSomething(foo)  
    ...  
}
```

Note: currently, suspending function types cannot be used as supertypes, and anonymous suspending functions are currently not supported.

To continue the analogy, `await()` can be a suspending function (hence also callable from within an `async {}` block) that suspends a coroutine until some computation is done and returns its result:

```

async {
    ...
    val result = computation.await()
    ...
}

```

More information on how actual `async/await` functions work in `kotlinx.coroutines` can be found [here](#).

Note that suspending functions `await()` and `doSomething()` cannot be called from function literals that are not inlined into a suspending function body and from regular function like `main()`:

```

fun main(args: Array<String>) {
    doSomething() // ERROR: Suspending function called from a non-coroutine context

    async {
        ...
        computations.forEach { // `forEach` is an inline function, the lambda is inlined
            it.await() // OK
        }

        thread { // `thread` is not an inline function, so the lambda is not inlined
            doSomething() // ERROR
        }
    }
}

```

Also note that suspending functions can be virtual, and when overriding them, the `suspend` modifier has to be specified:

```

interface Base {
    suspend fun foo()
}

class Derived: Base {
    override suspend fun foo() { ... }
}

```

@RestrictsSuspension annotation

Extension functions (and lambdas) can also be marked `suspend`, just like regular ones. This enables creation of [DSLs](#) and other APIs that users can extend. In some cases the library author needs to prevent the user from adding *new ways* of suspending a coroutine.

To achieve this, the [@RestrictsSuspension](#) annotation may be used. When a receiver class or interface `R` is annotated with it, all suspending extensions are required to delegate to either members of `R` or other extensions to it. Since extensions can't delegate to each other indefinitely (the program would not terminate), this guarantees that all suspensions happen through calling members of `R` that the author of the library can fully control.

This is relevant in the *rare* cases when every suspension is handled in a special way in the library. For example, when implementing generators through the [buildSequence\(\)](#) function described [below](#), we need to make sure that any suspending call in the coroutine ends up calling either `yield()` or `yieldAll()` and not any other function. This is why [SequenceBuilder](#) is annotated with `@RestrictsSuspension`:

```

@RestrictsSuspension
public abstract class SequenceBuilder<in T> { ... }

```

See the sources [on Github](#).

The inner workings of coroutines

We are not trying here to give a complete explanation of how coroutines work under the hood, but a rough sense of what's going on is rather important.

Coroutines are completely implemented through a compilation technique (no support from the VM or OS side is required), and suspension works through code transformation. Basically, every suspending function (optimizations may apply, but we'll not go into this here) is transformed to a state machine where states correspond to suspending calls. Right before a suspension, the next state is stored in a field of a compiler-generated class along with relevant local variables, etc. Upon resumption of that coroutine, local variables are restored and the state machine proceeds from the state right after suspension.

A suspended coroutine can be stored and passed around as an object that keeps its suspended state and locals. The type of such objects is `Continuation`, and the overall code transformation described here corresponds to the classical [Continuation-passing style](#). Consequently, suspending functions take an extra parameter of type `Continuation` under the hood.

More details on how coroutines work may be found in [this design document](#). Similar descriptions of `async/await` in other languages (such as C# or ECMAScript 2016) are relevant here, although the language features they implement may not be as general as Kotlin coroutines.

Experimental status of coroutines

The design of coroutines is [experimental](#), which means that it will be changed in the upcoming releases. When compiling coroutines in Kotlin 1.1+, a warning is reported by default: *The feature "coroutines" is experimental*. To remove the warning, you need to specify an [opt-in flag](#).

Due to its experimental status, the coroutine-related API in the Standard Library is put under the `kotlin.coroutines.experimental` package. When the design is finalized and the experimental status lifted, the final API will be moved to `kotlin.coroutines`, and the experimental package will be kept around (probably in a separate artifact) for backward compatibility.

IMPORTANT NOTE: We advise library authors to follow the same convention: add the "experimental" (e.g. `com.example.experimental`) suffix to your packages exposing coroutine-based APIs so that your library remains binary compatible. When the final API is released, follow these steps:

- copy all the APIs to `com.example` (without the experimental suffix),
- keep the experimental package around for backward compatibility.

This will minimize migration issues for your users.

Standard APIs

Coroutines come in three main ingredients:

- language support (i.s. suspending functions, as described above);
- low-level core API in the Kotlin Standard Library;
- high-level APIs that can be used directly in the user code.

Low-level API: `kotlin.coroutines`

Low-level API is relatively small and should never be used other than for creating higher-level libraries. It consists of two main packages:

- [kotlin.coroutines.experimental](#) with main types and primitives such as:
 - [createCoroutine\(\)](#),
 - [startCoroutine\(\)](#),
 - [suspendCoroutine\(\)](#);
- [kotlin.coroutines.experimental.intrinsics](#) with even lower-level intrinsics such as [suspendCoroutineOrReturn](#).

More details about the usage of these APIs can be found [here](#).

Generators API in `kotlin.coroutines`

The only "application-level" functions in `kotlin.coroutines.experimental` are

- [buildSequence\(\)](#)
- [buildIterator\(\)](#)

These are shipped within `kotlin-stdlib` because they are related to sequences. In fact, these functions (and we can limit ourselves to `buildSequence()` alone here) implement *generators*, i.e. provide a way to cheaply build a lazy sequence:

```
import kotlin.coroutines.experimental.*

fun main(args: Array<String>) {
    //sampleStart
    val fibonacciSeq = buildSequence {
        var a = 0
        var b = 1

        yield(1)

        while (true) {
            yield(a + b)

            val tmp = a + b
            a = b
            b = tmp
        }
    }
    //sampleEnd

    // Print the first five Fibonacci numbers
    println(fibonacciSeq.take(8).toList())
}
```

This generates a lazy, potentially infinite Fibonacci sequence by creating a coroutine that yields consecutive Fibonacci numbers by calling the `yield()` function. When iterating over such a sequence every step of the iterator executes another portion of the coroutine that generates the next number. So, we can take any finite list of numbers out of this sequence, e.g. `fibonacciSeq.take(8).toList()` results in `[1, 1, 2, 3, 5, 8, 13, 21]`. And coroutines are cheap enough to make this practical.

To demonstrate the real laziness of such a sequence, let's print some debug output inside a call to `buildSequence()`:

```
import kotlin.coroutines.experimental.*

fun main(args: Array<String>) {
    //sampleStart
    val lazySeq = buildSequence {
        print("START ")
        for (i in 1..5) {
            yield(i)
            print("STEP ")
        }
        print("END")
    }

    // Print the first three elements of the sequence
    lazySeq.take(3).forEach { print("$it ") }
    //sampleEnd
}
```

Running the code above prints the first three elements. The numbers are interleaved with `STEP` s in the generating loop. This means that the computation is lazy indeed. To print `1` we only execute until the first `yield(i)`, and print `START` along the way. Then, to print `2` we need to proceed to the next `yield(i)`, and this prints `STEP`. Same for `3`. And the next `STEP` never gets printed (as well as `END`), because we never requested further elements of the sequence.

To yield a collection (or sequence) of values at once, the `yieldAll()` function is available:

```
import kotlin.coroutines.experimental.*

fun main(args: Array<String>) {
    //sampleStart
    val lazySeq = buildSequence {
        yield(0)
        yieldAll(1..10)
    }

    lazySeq.forEach { print("$it ") }
    //sampleEnd
}
```

The `buildIterator()` works similarly to `buildSequence()`, but returns a lazy iterator.

One can add custom yielding logic to `buildSequence()` by writing suspending extensions to the `SequenceBuilder` class (that bears the `@RestrictsSuspension` annotation described [above](#)):

```
import kotlin.coroutines.experimental.*

//sampleStart
suspend fun SequenceBuilder<Int>.yieldIfOdd(x: Int) {
    if (x % 2 != 0) yield(x)
}

val lazySeq = buildSequence {
    for (i in 1..10) yieldIfOdd(i)
}
//sampleEnd

fun main(args: Array<String>) {
    lazySeq.forEach { print("$it ") }
}
```

Other high-level APIs: `kotlinx.coroutines`

Only core APIs related to coroutines are available from the Kotlin Standard Library. This mostly consists of core primitives and interfaces that all coroutine-based libraries are likely to use.

Most application-level APIs based on coroutines are released as a separate library: [kotlinx.coroutines](#). This library covers

- Platform-agnostic asynchronous programming with `kotlinx.coroutines-core`:
 - this module includes Go-like channels that support `select` and other convenient primitives,
 - a comprehensive guide to this library is available [here](#);
- APIs based on `CompletableFuture` from JDK 8: `kotlinx.coroutines-jdk8`;
- Non-blocking IO (NIO) based on APIs from JDK 7 and higher: `kotlinx.coroutines-nio`;
- Support for Swing (`kotlinx.coroutines-swing`) and JavaFx (`kotlinx.coroutines-javafx`);
- Support for RxJava: `kotlinx.coroutines-rx`.

These libraries serve as both convenient APIs that make common tasks easy and end-to-end examples of how to build coroutine-based libraries.

Other

Destructuring Declarations

Sometimes it is convenient to *destructure* an object into a number of variables, for example:

```
val (name, age) = person
```

This syntax is called a *destructuring declaration*. A destructuring declaration creates multiple variables at once. We have declared two new variables: `name` and `age`, and can use them independently:

```
println(name)
println(age)
```

A destructuring declaration is compiled down to the following code:

```
val name = person.component1()
val age = person.component2()
```

The `component1()` and `component2()` functions are another example of the *principle of conventions* widely used in Kotlin (see operators like `+` and `*`, `for`-loops etc.). Anything can be on the right-hand side of a destructuring declaration, as long as the required number of component functions can be called on it. And, of course, there can be `component3()` and `component4()` and so on.

Note that the `componentN()` functions need to be marked with the `operator` keyword to allow using them in a destructuring declaration.

Destructuring declarations also work in `for`-loops: when you say:

```
for ((a, b) in collection) { ... }
```

Variables `a` and `b` get the values returned by `component1()` and `component2()` called on elements of the collection.

Example: Returning Two Values from a Function

Let's say we need to return two things from a function. For example, a result object and a status of some sort. A compact way of doing this in Kotlin is to declare a *data class* and return its instance:

```
data class Result(val result: Int, val status: Status)
fun function(...): Result {
    // computations

    return Result(result, status)
}
```

```
// Now, to use this function:
val (result, status) = function(...)
```

Since data classes automatically declare `componentN()` functions, destructuring declarations work here.

NOTE: we could also use the standard class `Pair` and have `function()` return `Pair<Int, Status>`, but it's often better to have your data named properly.

Example: Destructuring Declarations and Maps

Probably the nicest way to traverse a map is this:


```
for ((key, value) in map) {
    // do something with the key and the value
}
```

To make this work, we should

- present the map as a sequence of values by providing an `iterator()` function;
- present each of the elements as a pair by providing functions `component1()` and `component2()`.

And indeed, the standard library provides such extensions:

```
operator fun <K, V> Map<K, V>.iterator(): Iterator<Map.Entry<K, V>> = entrySet().iterator()
operator fun <K, V> Map.Entry<K, V>.component1() = getKey()
operator fun <K, V> Map.Entry<K, V>.component2() = getValue()
```

So you can freely use destructuring declarations in `for`-loops with maps (as well as collections of data class instances etc).

Underscore for unused variables (since 1.1)

If you don't need a variable in the destructuring declaration, you can place an underscore instead of its name:

```
val (_, status) = getResult()
```

The `componentN()` operator functions are not called for the components that are skipped in this way.

Destructuring in Lambdas (since 1.1)

You can use the destructuring declarations syntax for lambda parameters. If a lambda has a parameter of the `Pair` type (or `Map.Entry`, or any other type that has the appropriate `componentN` functions), you can introduce several new parameters instead of one by putting them in parentheses:

```
map.mapValues { entry -> "${entry.value}!" }
map.mapValues { (key, value) -> "$value!" }
```

Note the difference between declaring two parameters and declaring a destructuring pair instead of a parameter:

```
{ a -> ... } // one parameter
{ a, b -> ... } // two parameters
{ (a, b) -> ... } // a destructured pair
{ (a, b), c -> ... } // a destructured pair and another parameter
```

If a component of the destructured parameter is unused, you can replace it with the underscore to avoid inventing its name:

```
map.mapValues { (_, value) -> "$value!" }
```

You can specify the type for the whole destructured parameter or for a specific component separately:

```
map.mapValues { (_, value): Map.Entry<Int, String> -> "$value!" }

map.mapValues { (_, value: String) -> "$value!" }
```

Collections: List, Set, Map

Unlike many languages, Kotlin distinguishes between mutable and immutable collections (lists, sets, maps, etc). Precise control over exactly when collections can be edited is useful for eliminating bugs, and for designing good APIs.

It is important to understand up front the difference between a read-only *view* of a mutable collection, and an actually immutable collection. Both are easy to create, but the type system doesn't express the difference, so keeping track of that (if it's relevant) is up to you.

The Kotlin `List<out T>` type is an interface that provides read-only operations like `size`, `get` and so on. Like in Java, it inherits from `Collection<T>` and that in turn inherits from `Iterable<T>`. Methods that change the list are added by the `MutableList<T>` interface. This pattern holds also for `Set<out T>/MutableSet<T>` and `Map<K, out V>/MutableMap<K, V>`.

We can see basic usage of the list and set types below:

```
val numbers: MutableList<Int> = mutableListOf(1, 2, 3)
val readOnlyView: List<Int> = numbers
println(numbers)           // prints "[1, 2, 3]"
numbers.add(4)
println(readOnlyView)      // prints "[1, 2, 3, 4]"
readOnlyView.clear()       // -> does not compile
```

```
val strings = hashSetOf("a", "b", "c", "c")
assert(strings.size == 3)
```

Kotlin does not have dedicated syntax constructs for creating lists or sets. Use methods from the standard library, such as `listOf()`, `mutableListOf()`, `setOf()`, `mutableSetOf()`. Map creation in NOT performance-critical code can be accomplished with a simple [idiom](#): `mapOf(a to b, c to d)`.

Note that the `readOnlyView` variable points to the same list and changes as the underlying list changes. If the only references that exist to a list are of the read-only variety, we can consider the collection fully immutable. A simple way to create such a collection is like this:

```
val items = listOf(1, 2, 3)
```

Currently, the `listOf` method is implemented using an array list, but in future more memory-efficient fully immutable collection types could be returned that exploit the fact that they know they can't change.

Note that the read-only types are [covariant](#). That means, you can take a `List<Rectangle>` and assign it to `List<Shape>` assuming `Rectangle` inherits from `Shape` (the collection types have the same inheritance relationship as the element types). This wouldn't be allowed with the mutable collection types because it would allow for failures at runtime: you might add a `Circle` into the `List<Shape>`, creating a `List<Rectangle>` with a `Circle` in it somewhere else in the program.

Sometimes you want to return to the caller a snapshot of a collection at a particular point in time, one that's guaranteed to not change:

```
class Controller {
    private val _items = mutableListOf<String>()
    val items: List<String> get() = _items.toList()
}
```

The `toList` extension method just duplicates the lists items, thus, the returned list is guaranteed to never change.

There are various useful extension methods on lists and sets that are worth being familiar with:

```
val items = listOf(1, 2, 3, 4)
items.first() == 1
items.last() == 4
items.filter { it % 2 == 0 } // returns [2, 4]

val rwList = mutableListOf(1, 2, 3)
rwList.requireNonNulls() // returns [1, 2, 3]
if (rwList.none { it > 6 }) println("No items above 6") // prints "No items above 6"
val item = rwList.firstOrNull()
```

... as well as all the utilities you would expect such as `sort`, `zip`, `fold`, `reduce` and so on.

Maps follow the same pattern. They can be easily instantiated and accessed like this:

```
val readWriteMap = hashMapOf("foo" to 1, "bar" to 2)
println(readWriteMap["foo"]) // prints "1"
val snapshot: Map<String, Int> = HashMap(readWriteMap)
```

Ranges

Range expressions are formed with `rangeTo` functions that have the operator form `..` which is complemented by `in` and `!in`. Range is defined for any comparable type, but for integral primitive types it has an optimized implementation. Here are some examples of using ranges:

```
if (i in 1..10) { // equivalent of 1 <= i && i <= 10
    println(i)
}
```

Integral type ranges (`IntRange`, `LongRange`, `CharRange`) have an extra feature: they can be iterated over. The compiler takes care of converting this analogously to Java's indexed `for`-loop, without extra overhead:

```
fun main(args: Array<String>) {
    //sampleStart
    for (i in 1..4) print(i)

    for (i in 4..1) print(i)
    //sampleEnd
}
```

What if you want to iterate over numbers in reverse order? It's simple. You can use the `downTo()` function defined in the standard library:

```
fun main(args: Array<String>) {
    //sampleStart
    for (i in 4 downTo 1) print(i)
    //sampleEnd
}
```

Is it possible to iterate over numbers with arbitrary step, not equal to 1? Sure, the `step()` function will help you:

```
fun main(args: Array<String>) {
    //sampleStart
    for (i in 1..4 step 2) print(i)

    for (i in 4 downTo 1 step 2) print(i)
    //sampleEnd
}
```

To create a range which does not include its end element, you can use the `until` function:

```
fun main(args: Array<String>) {
    //sampleStart
    for (i in 1 until 10) {
        // i in [1, 10), 10 is excluded
        println(i)
    }
    //sampleEnd
}
```

How it works

Ranges implement a common interface in the library: `ClosedRange<T>`.

`ClosedRange<T>` denotes a closed interval in the mathematical sense, defined for comparable types. It has two endpoints: `start` and `endInclusive`, which are included in the range. The main operation is `contains`, usually used in the form of `in`/`!in` operators.

Integral type progressions (`IntProgression`, `LongProgression`, `CharProgression`) denote an arithmetic progression. Progressions are defined by the `first` element, the `last` element and a non-zero `step`. The first element is `first`, subsequent elements are the previous element plus `step`. The `last` element is always hit by iteration unless the progression is empty.

A progression is a subtype of `Iterable<N>`, where `N` is `Int`, `Long` or `Char` respectively, so it can be used in `for`-loops and functions like `map`, `filter`, etc. Iteration over `Progression` is equivalent to an indexed `for`-loop in Java/JavaScript:

```
for (int i = first; i != last; i += step) {
    // ...
}
```

For integral types, the `..` operator creates an object which implements both `ClosedRange<T>` and `*Progression`. For example, `IntRange` implements `ClosedRange<Int>` and extends `IntProgression`, thus all operations defined for `IntProgression` are available for `IntRange` as well. The result of the `downTo()` and `step()` functions is always a `*Progression`.

Progressions are constructed with the `fromClosedRange` function defined in their companion objects:

```
IntProgression.fromClosedRange(start, end, step)
```

The `last` element of the progression is calculated to find maximum value not greater than the `end` value for positive `step` or minimum value not less than the `end` value for negative `step` such that `(last - first) % step == 0`.

Utility functions

`rangeTo()`

The `rangeTo()` operators on integral types simply call the constructors of `*Range` classes, e.g.:

```
class Int {
    //...
    operator fun rangeTo(other: Long): LongRange = LongRange(this, other)
    //...
    operator fun rangeTo(other: Int): IntRange = IntRange(this, other)
    //...
}
```

Floating point numbers (`Double`, `Float`) do not define their `rangeTo` operator, and the one provided by the standard library for generic `Comparable` types is used instead:

```
public operator fun <T: Comparable<T>> T.rangeTo(that: T): ClosedRange<T>
```

The range returned by this function cannot be used for iteration.

`downTo()`

The `downTo()` extension function is defined for any pair of integral types, here are two examples:

```
fun Long.downTo(other: Int): LongProgression {
    return LongProgression.fromClosedRange(this, other.toLong(), -1L)
}

fun Byte.downTo(other: Int): IntProgression {
    return IntProgression.fromClosedRange(this.toInt(), other, -1)
}
```

`reversed()`

The `reversed()` extension functions are defined for each `*Progression` classes, and all of them return reversed progressions:

```
fun IntProgression.reversed(): IntProgression {
    return IntProgression.fromClosedRange(last, first, -step)
}
```

`step()`

`step()` extension functions are defined for `*Progression` classes, all of them return progressions with modified `step` values (function parameter). The step value is required to be always positive, therefore this function never changes the direction of iteration:

```

fun IntProgression.step(step: Int): IntProgression {
    if (step <= 0) throw IllegalArgumentException("Step must be positive, was: $step")
    return IntProgression.fromClosedRange(first, last, if (this.step > 0) step else -step)
}

fun CharProgression.step(step: Int): CharProgression {
    if (step <= 0) throw IllegalArgumentException("Step must be positive, was: $step")
    return CharProgression.fromClosedRange(first, last, if (this.step > 0) step else -step)
}

```

Note that the `last` value of the returned progression may become different from the `last` value of the original progression in order to preserve the invariant `(last - first) % step == 0`. Here is an example:

```

(1..12 step 2).last == 11 // progression with values [1, 3, 5, 7, 9, 11]
(1..12 step 3).last == 10 // progression with values [1, 4, 7, 10]
(1..12 step 4).last == 9  // progression with values [1, 5, 9]

```

Type Checks and Casts: 'is' and 'as'

is and !is Operators

We can check whether an object conforms to a given type at runtime by using the `is` operator or its negated form `!is`:

```
if (obj is String) {
    print(obj.length)
}

if (obj !is String) { // same as !(obj is String)
    print("Not a String")
}
else {
    print(obj.length)
}
```

Smart Casts

In many cases, one does not need to use explicit cast operators in Kotlin, because the compiler tracks the `is`-checks and [explicit casts](#) for immutable values and inserts (safe) casts automatically when needed:

```
fun demo(x: Any) {
    if (x is String) {
        print(x.length) // x is automatically cast to String
    }
}
```

The compiler is smart enough to know a cast to be safe if a negative check leads to a return:

```
if (x !is String) return
print(x.length) // x is automatically cast to String
```

or in the right-hand side of `&&` and `||`:

```
// x is automatically cast to string on the right-hand side of `||`
if (x !is String || x.length == 0) return

// x is automatically cast to string on the right-hand side of `&&`
if (x is String && x.length > 0) {
    print(x.length) // x is automatically cast to String
}
```

Such *smart casts* work for [when-expressions](#) and [while-loops](#) as well:

```
when (x) {
    is Int -> print(x + 1)
    is String -> print(x.length + 1)
    is IntArray -> print(x.sum())
}
```

Note that smart casts do not work when the compiler cannot guarantee that the variable cannot change between the check and the usage. More specifically, smart casts are applicable according to the following rules:

- `val` local variables - always except for [local delegated properties](#);
- `val` properties - if the property is private or internal or the check is performed in the same module where the property is declared. Smart casts aren't applicable to open properties or properties that have custom getters;
- `var` local variables - if the variable is not modified between the check and the usage, is not captured in a lambda that modifies it, and is not a local delegated property;
- `var` properties - never (because the variable can be modified at any time by other code).

"Unsafe" cast operator

Usually, the cast operator throws an exception if the cast is not possible. Thus, we call it *unsafe*. The unsafe cast in Kotlin is done by the infix operator `as` (see [operator precedence](#)):

```
val x: String = y as String
```

Note that `null` cannot be cast to `String` as this type is not [nullable](#), i.e. if `y` is null, the code above throws an exception. In order to match Java cast semantics we have to have nullable type at cast right hand side, like:

```
val x: String? = y as String?
```

"Safe" (nullable) cast operator

To avoid an exception being thrown, one can use a *safe* cast operator `as?` that returns `null` on failure:

```
val x: String? = y as? String
```

Note that despite the fact that the right-hand side of `as?` is a non-null type `String` the result of the cast is nullable.

Type erasure and generic type checks

Kotlin ensures type safety of operations involving [generics](#) at compile time, while, at runtime, instances of generic types hold no information about their actual type arguments. For example, `List<Foo>` is erased to just `List<*>`. In general, there is no way to check whether an instance belongs to a generic type with certain type arguments at runtime.

Given that, the compiler prohibits *is*-checks that cannot be performed at runtime due to type erasure, such as `ints is List<Int>` or `list is T` (type parameter). You can, however, check an instance against a [star-projected type](#):

```
if (something is List<*>) {
    something.forEach { println(it) } // The items are typed as `Any?`
}
```

Similarly, when you already have the type arguments of an instance checked statically (at compile time), you can make an *is*-check or a cast that involves the non-generic part of the type. Note that angle brackets are omitted in this case:

```
fun handleStrings(list: List<String>) {
    if (list is ArrayList) {
        // `list` is smart-cast to `ArrayList<String>`
    }
}
```

The same syntax with omitted type arguments can be used for casts that do not take type arguments into account: `list as ArrayList`.

Inline functions with [reified type parameters](#) have their actual type arguments inlined at each call site, which enables `arg is T` checks for the type parameters, but if `arg` is an instance of a generic type itself, *its* type arguments are still erased.

Example:

```
//sampleStart
inline fun <reified A, reified B> Pair<*, *>.asPairOf(): Pair<A, B>? {
    if (first !is A || second !is B) return null
    return first as A to second as B
}

val somePair: Pair<Any?, Any?> = "items" to listOf(1, 2, 3)

val stringToSomething = somePair.asPairOf<String, Any>()
val stringToInt = somePair.asPairOf<String, Int>()
val stringToList = somePair.asPairOf<String, List<*>>()
val stringToStringList = somePair.asPairOf<String, List<String>>() // Breaks type safety!
//sampleEnd

fun main(args: Array<String>) {
    println("stringToSomething = " + stringToSomething)
    println("stringToInt = " + stringToInt)
    println("stringToList = " + stringToList)
    println("stringToStringList = " + stringToStringList)
}
```

Unchecked casts

As said above, type erasure makes checking actual type arguments of a generic type instance impossible at runtime, and generic types in the code might be connected to each other not closely enough for the compiler to ensure type safety.

Even so, sometimes we have high-level program logic that implies type safety instead. For example:

```
fun readDictionary(file: File): Map<String, *> = file.inputStream().use {
    TODO("Read a mapping of strings to arbitrary elements.")
}

// We saved a map with `Int`s into that file
val intsFile = File("ints.dictionary")

// Warning: Unchecked cast: `Map<String, *>` to `Map<String, Int>`
val intsDictionary: Map<String, Int> = readDictionary(intsFile) as Map<String, Int>
```

The compiler produces a warning for the cast in the last line. The cast cannot be fully checked at runtime and provides no guarantee that the values in the map are `Int`.

To avoid unchecked casts, you can redesign the program structure: in the example above, there could be interfaces `DictionaryReader<T>` and `DictionaryWriter<T>` with type-safe implementations for different types. You can introduce reasonable abstractions to move unchecked casts from calling code to the implementation details. Proper use of [generic variance](#) can also help.

For generic functions, using [reified type parameters](#) makes the casts such as `arg as T` checked, unless `arg`'s type has *its own* type arguments that are erased.

An unchecked cast warning can be suppressed by [annotating](#) the statement or the declaration where it occurs with `@Suppress("UNCHECKED_CAST")`:

```
inline fun <reified T> List<*>.asListOfType(): List<T>? =
    if (all { it is T })
        @Suppress("UNCHECKED_CAST")
        this as List<T> else
        null
```

On the JVM, the [array types](#) (`Array<Foo>`) retain the information about the erased type of their elements, and the type casts to an array type are partially checked: the nullability and actual type arguments of the elements type are still erased. For example, the cast `foo as Array<List<String>?>` will succeed if `foo` is an array holding any `List<*>`, nullable or not.

This Expression

To denote the current *receiver*, we use `this` expressions:

- In a member of a [class](#), `this` refers to the current object of that class.
- In an [extension function](#) or a [function literal with receiver](#) `this` denotes the *receiver* parameter that is passed on the left-hand side of a dot.

If `this` has no qualifiers, it refers to the *innermost enclosing scope*. To refer to `this` in other scopes, *label qualifiers* are used:

Qualified `this`

To access `this` from an outer scope (a [class](#), or [extension function](#), or labeled [function literal with receiver](#)) we write `this@label` where `@label` is a [label](#) on the scope `this` is meant to be from:

```
class A { // implicit label @A
    inner class B { // implicit label @B
        fun Int.foo() { // implicit label @foo
            val a = this@A // A's this
            val b = this@B // B's this

            val c = this // foo()'s receiver, an Int
            val c1 = this@foo // foo()'s receiver, an Int

            val funLit = lambda@ fun String.() {
                val d = this // funLit's receiver
            }

            val funLit2 = { s: String ->
                // foo()'s receiver, since enclosing lambda expression
                // doesn't have any receiver
                val d1 = this
            }
        }
    }
}
```

Equality

In Kotlin there are two types of equality:

- Structural equality (a check for `equals()`).
- Referential equality (two references point to the same object);

Structural equality

Structural equality is checked by the `==` operation (and its negated counterpart `!=`). By convention, an expression like `a == b` is translated to:

```
a?.equals(b) ?: (b === null)
```

i.e. if `a` is not `null` , it calls the `equals(Any?)` function, otherwise (i.e. `a` is `null`) it checks that `b` is referentially equal to `null` .

Note that there's no point in optimizing your code when comparing to `null` explicitly: `a == null` will be automatically translated to `a === null` .

Floating point numbers equality

When an equality check operands are statically known to be `Float` or `Double` (nullable or not), the check follows the IEEE 754 Standard for Floating-Point Arithmetic.

Otherwise, the structural equality is used, which disagrees with the standard so that `NaN` is equal to itself, and `-0.0` is not equal to `0.0` .

See: [Floating Point Numbers Comparison](#).

Referential equality

Referential equality is checked by the `===` operation (and its negated counterpart `!==`). `a === b` evaluates to true if and only if `a` and `b` point to the same object. For values which are represented as primitive types at runtime (for example, `Int`), the `===` equality check is equivalent to the `==` check.

Operator overloading

Kotlin allows us to provide implementations for a predefined set of operators on our types. These operators have fixed symbolic representation (like `+` or `*`) and fixed [precedence](#). To implement an operator, we provide a [member function](#) or an [extension function](#) with a fixed name, for the corresponding type, i.e. left-hand side type for binary operations and argument type for unary ones. Functions that overload operators need to be marked with the `operator` modifier.

Further we describe the conventions that regulate operator overloading for different operators.

Unary operations

Unary prefix operators

| Expression | Translated to |
|-----------------|-----------------------------|
| <code>+a</code> | <code>a.unaryPlus()</code> |
| <code>-a</code> | <code>a.unaryMinus()</code> |
| <code>!a</code> | <code>a.not()</code> |

This table says that when the compiler processes, for example, an expression `+a`, it performs the following steps:

- Determines the type of `a`, let it be `T`;
- Looks up a function `unaryPlus()` with the `operator` modifier and no parameters for the receiver `T`, i.e. a member function or an extension function;
- If the function is absent or ambiguous, it is a compilation error;
- If the function is present and its return type is `R`, the expression `+a` has type `R`;

Note that these operations, as well as all the others, are optimized for [Basic types](#) and do not introduce overhead of function calls for them.

As an example, here's how you can overload the unary minus operator:

```
data class Point(val x: Int, val y: Int)

operator fun Point.unaryMinus() = Point(-x, -y)

val point = Point(10, 20)

fun main(args: Array<String>) {
    println(-point) // prints "Point(x=-10, y=-20)"
}
```

Increments and decrements

| Expression | Translated to |
|------------------|----------------------------------|
| <code>a++</code> | <code>a.inc()</code> + see below |
| <code>a--</code> | <code>a.dec()</code> + see below |

The `inc()` and `dec()` functions must return a value, which will be assigned to the variable on which the `++` or `--` operation was used. They shouldn't mutate the object on which the `inc` or `dec` was invoked.

The compiler performs the following steps for resolution of an operator in the *postfix* form, e.g. `a++`:

- Determines the type of `a`, let it be `T`;
- Looks up a function `inc()` with the `operator` modifier and no parameters, applicable to the receiver of type `T`;
- Checks that the return type of the function is a subtype of `T`.

The effect of computing the expression is:

- Store the initial value of `a` to a temporary storage `a0`;

- Assign the result of `a.inc()` to `a`;
- Return `a0` as a result of the expression.

For `a--` the steps are completely analogous.

For the *prefix* forms `++a` and `--a` resolution works the same way, and the effect is:

- Assign the result of `a.inc()` to `a`;
- Return the new value of `a` as a result of the expression.

Binary operations

Arithmetic operators

| Expression | Translated to |
|--------------------|--|
| <code>a + b</code> | <code>a.plus(b)</code> |
| <code>a - b</code> | <code>a.minus(b)</code> |
| <code>a * b</code> | <code>a.times(b)</code> |
| <code>a / b</code> | <code>a.div(b)</code> |
| <code>a % b</code> | <code>a.rem(b)</code> , <code>a.mod(b)</code> (deprecated) |
| <code>a..b</code> | <code>a.rangeTo(b)</code> |

For the operations in this table, the compiler just resolves the expression in the *Translated to* column.

Note that the `rem` operator is supported since Kotlin 1.1. Kotlin 1.0 uses the `mod` operator, which is deprecated in Kotlin 1.1.

Example

Below is an example `Counter` class that starts at a given value and can be incremented using the overloaded `+` operator:

```
data class Counter(val dayIndex: Int) {
    operator fun plus(increment: Int): Counter {
        return Counter(dayIndex + increment)
    }
}
```

'In' operator

| Expression | Translated to |
|----------------------|-----------------------------|
| <code>a in b</code> | <code>b.contains(a)</code> |
| <code>a !in b</code> | <code>!b.contains(a)</code> |

For `in` and `!in` the procedure is the same, but the order of arguments is reversed.

Indexed access operator

| Expression | Translated to |
|-----------------------------------|--------------------------------------|
| <code>a[i]</code> | <code>a.get(i)</code> |
| <code>a[i, j]</code> | <code>a.get(i, j)</code> |
| <code>a[i_1, ..., i_n]</code> | <code>a.get(i_1, ..., i_n)</code> |
| <code>a[i] = b</code> | <code>a.set(i, b)</code> |
| <code>a[i, j] = b</code> | <code>a.set(i, j, b)</code> |
| <code>a[i_1, ..., i_n] = b</code> | <code>a.set(i_1, ..., i_n, b)</code> |

Square brackets are translated to calls to `get` and `set` with appropriate numbers of arguments.

Invoke operator

| Expression | Translated to |
|-------------------------------|--------------------------------------|
| <code>a()</code> | <code>a.invoke()</code> |
| <code>a(i)</code> | <code>a.invoke(i)</code> |
| <code>a(i, j)</code> | <code>a.invoke(i, j)</code> |
| <code>a(i_1, ..., i_n)</code> | <code>a.invoke(i_1, ..., i_n)</code> |

Parentheses are translated to calls to `invoke` with appropriate number of arguments.

Augmented assignments

| Expression | Translated to |
|---------------------|--|
| <code>a += b</code> | <code>a.plusAssign(b)</code> |
| <code>a -= b</code> | <code>a.minusAssign(b)</code> |
| <code>a *= b</code> | <code>a.timesAssign(b)</code> |
| <code>a /= b</code> | <code>a.divAssign(b)</code> |
| <code>a %= b</code> | <code>a.remAssign(b), a.modAssign(b)</code> (deprecated) |

For the assignment operations, e.g. `a += b`, the compiler performs the following steps:

- If the function from the right column is available
 - If the corresponding binary function (i.e. `plus()` for `plusAssign()`) is available too, report error (ambiguity),
 - Make sure its return type is `Unit`, and report an error otherwise,
 - Generate code for `a.plusAssign(b)`;
- Otherwise, try to generate code for `a = a + b` (this includes a type check: the type of `a + b` must be a subtype of `a`).

Note: assignments are *NOT* expressions in Kotlin.

Equality and inequality operators

| Expression | Translated to |
|---------------------|--|
| <code>a == b</code> | <code>a?.equals(b) ?: (b === null)</code> |
| <code>a != b</code> | <code>!(a?.equals(b) ?: (b === null))</code> |

Note: `===` and `!==` (identity checks) are not overloadable, so no conventions exist for them.

The `==` operation is special: it is translated to a complex expression that screens for `null`'s. `null == null` is always true, and `x == null` for a non-null `x` is always false and won't invoke `x.equals()`.

Comparison operators

| Expression | Translated to |
|------------------------|-------------------------------------|
| <code>a > b</code> | <code>a.compareTo(b) > 0</code> |
| <code>a < b</code> | <code>a.compareTo(b) < 0</code> |
| <code>a >= b</code> | <code>a.compareTo(b) >= 0</code> |
| <code>a <= b</code> | <code>a.compareTo(b) <= 0</code> |

All comparisons are translated into calls to `compareTo`, that is required to return `Int`.

Property delegation operators

`provideDelegate`, `getValue` and `setValue` operator functions are described in [Delegated properties](#).

Infix calls for named functions

We can simulate custom infix operations by using [infix function calls](#).

Null Safety

Nullable types and Non-Null Types

Kotlin's type system is aimed at eliminating the danger of null references from code, also known as the [The Billion Dollar Mistake](#).

One of the most common pitfalls in many programming languages, including Java, is that accessing a member of a null reference will result in a null reference exception. In Java this would be the equivalent of a `NullPointerException` or NPE for short.

Kotlin's type system is aimed to eliminate `NullPointerException`'s from our code. The only possible causes of NPE's may be:

- An explicit call to `throw NullPointerException()`;
- Usage of the `!!` operator that is described below;
- Some data inconsistency with regard to initialization, such as when:
 - An uninitialized `this` available in a constructor is passed and used somewhere ("leaking `this`");
 - [A superclass constructor calls an open member](#) whose implementation in the derived class uses uninitialized state;
- Java interoperation:
 - Attempts to access a member on a `null` reference of a [platform type](#);
 - Generic types used for Java interoperation with incorrect nullability, e.g. a piece of Java code might add `null` into a Kotlin `MutableList<String>`, meaning that `MutableList<String?>` should be used for working with it;
 - Other issues caused by external Java code.

In Kotlin, the type system distinguishes between references that can hold `null` (nullable references) and those that can not (non-null references). For example, a regular variable of type `String` can not hold `null`:

```
fun main(args: Array<String>) {  
    //sampleStart  
    var a: String = "abc"  
    a = null // compilation error  
    //sampleEnd  
}
```

To allow nulls, we can declare a variable as nullable string, written `String?`:

```
fun main(args: Array<String>) {  
    //sampleStart  
    var b: String? = "abc"  
    b = null // ok  
    print(b)  
    //sampleEnd  
}
```

Now, if you call a method or access a property on `a`, it's guaranteed not to cause an NPE, so you can safely say:

```
val l = a.length
```

But if you want to access the same property on `b`, that would not be safe, and the compiler reports an error:

```
val l = b.length // error: variable 'b' can be null
```

But we still need to access that property, right? There are a few ways of doing that.

Checking for `null` in conditions

First, you can explicitly check if `b` is `null`, and handle the two options separately:

```
val l = if (b != null) b.length else -1
```

The compiler tracks the information about the check you performed, and allows the call to `length` inside the `if`. More complex conditions are supported as well:


```

fun main(args: Array<String>) {
//sampleStart
    val b = "Kotlin"
    if (b != null && b.length > 0) {
        print("String of length ${b.length}")
    } else {
        print("Empty string")
    }
//sampleEnd
}

```

Note that this only works where `b` is immutable (i.e. a local variable which is not modified between the check and the usage or a member `val` which has a backing field and is not overridable), because otherwise it might happen that `b` changes to `null` after the check.

Safe Calls

Your second option is the safe call operator, written `?.`:

```

fun main(args: Array<String>) {
//sampleStart
    val a = "Kotlin"
    val b: String? = null
    println(b?.length)
    println(a?.length)
//sampleEnd
}

```

This returns `b.length` if `b` is not null, and `null` otherwise. The type of this expression is `Int?`.

Safe calls are useful in chains. For example, if Bob, an Employee, may be assigned to a Department (or not), that in turn may have another Employee as a department head, then to obtain the name of Bob's department head (if any), we write the following:

```
bob?.department?.head?.name
```

Such a chain returns `null` if any of the properties in it is null.

To perform a certain operation only for non-null values, you can use the safe call operator together with `let`:

```

fun main(args: Array<String>) {
//sampleStart
    val listWithNulls: List<String?> = listOf("Kotlin", null)
    for (item in listWithNulls) {
        item?.let { println(it) } // prints A and ignores null
    }
//sampleEnd
}

```

A safe call can also be placed on the left side of an assignment. Then, if one of the receivers in the safe calls chain is null, the assignment is skipped, and the expression on the right is not evaluated at all:

```
// If either `person` or `person.department` is null, the function is not called:
person?.department?.head = managersPool.getManager()
```

Elvis Operator

When we have a nullable reference `r`, we can say "if `r` is not null, use it, otherwise use some non-null value `x`":

```
val l: Int = if (b != null) b.length else -1
```

Along with the complete `if`-expression, this can be expressed with the Elvis operator, written `?:`:

```
val l = b?.length ?: -1
```

If the expression to the left of `?:` is not null, the elvis operator returns it, otherwise it returns the expression to the right. Note that the right-hand side expression is evaluated only if the left-hand side is null.

Note that, since `throw` and `return` are expressions in Kotlin, they can also be used on the right hand side of the elvis operator. This can be very handy, for example, for checking function arguments:

```
fun foo(node: Node): String? {
    val parent = node.getParent() ?: return null
    val name = node.getName() ?: throw IllegalArgumentException("name expected")
    // ...
}
```

The !! Operator

The third option is for NPE-lovers: the not-null assertion operator (`!!`) converts any value to a non-null type and throws an exception if the value is null. We can write `b!!`, and this will return a non-null value of `b` (e.g., a `String` in our example) or throw an NPE if `b` is null:

```
val l = b!!.length
```

Thus, if you want an NPE, you can have it, but you have to ask for it explicitly, and it does not appear out of the blue.

Safe Casts

Regular casts may result into a `ClassCastException` if the object is not of the target type. Another option is to use safe casts that return `null` if the attempt was not successful:

```
val aInt: Int? = a as? Int
```

Collections of Nullable Type

If you have a collection of elements of a nullable type and want to filter non-null elements, you can do so by using `filterNotNull`:

```
val nullableList: List<Int?> = listOf(1, 2, null, 4)
val intList: List<Int> = nullableList.filterNotNull()
```

Exceptions

Exception Classes

All exception classes in Kotlin are descendants of the class `Throwable`. Every exception has a message, stack trace and an optional cause.

To throw an exception object, use the `throw`-expression:

```
fun main(args: Array<String>) {  
    //sampleStart  
    throw Exception("Hi There!")  
    //sampleEnd  
}
```

To catch an exception, use the `try`-expression:

```
try {  
    // some code  
}  
catch (e: SomeException) {  
    // handler  
}  
finally {  
    // optional finally block  
}
```

There may be zero or more `catch` blocks. `finally` blocks may be omitted. However at least one `catch` or `finally` block should be present.

Try is an expression

`try` is an expression, i.e. it may have a return value:

```
val a: Int? = try { parseInt(input) } catch (e: NumberFormatException) { null }
```

The returned value of a `try`-expression is either the last expression in the `try` block or the last expression in the `catch` block (or blocks). Contents of the `finally` block do not affect the result of the expression.

Checked Exceptions

Kotlin does not have checked exceptions. There are many reasons for this, but we will provide a simple example.

The following is an example interface of the JDK implemented by `StringBuilder` class:

```
Appendable append(CharSequence csq) throws IOException;
```

What does this signature say? It says that every time I append a string to something (a `StringBuilder`, some kind of a log, a console, etc.) I have to catch those `IOExceptions`. Why? Because it might be performing IO (`Writer` also implements `Appendable`)... So it results into this kind of code all over the place:

```
try {  
    log.append(message)  
}  
catch (IOException e) {  
    // Must be safe  
}
```

And this is no good, see [Effective Java, 3rd Edition](#), Item 77: *Don't ignore exceptions*.

Bruce Eckel says in [Does Java need Checked Exceptions?](#):

Examination of small programs leads to the conclusion that requiring exception specifications could both enhance developer productivity and enhance code quality, but experience with large software projects suggests a different result – decreased productivity and little or no increase in code quality.

Other citations of this sort:

- [Java's checked exceptions were a mistake](#) (Rod Waldhoff)
- [The Trouble with Checked Exceptions](#) (Anders Hejlsberg)

The Nothing type

`throw` is an expression in Kotlin, so you can use it, for example, as part of an Elvis expression:

```
val s = person.name ?: throw IllegalArgumentException("Name required")
```

The type of the `throw` expression is the special type `Nothing`. The type has no values and is used to mark code locations that can never be reached. In your own code, you can use `Nothing` to mark a function that never returns:

```
fun fail(message: String): Nothing {  
    throw IllegalArgumentException(message)  
}
```

When you call this function, the compiler will know that the execution doesn't continue beyond the call:

```
val s = person.name ?: fail("Name required")  
println(s)    // 's' is known to be initialized at this point
```

Another case where you may encounter this type is type inference. The nullable variant of this type, `Nothing?`, has exactly one possible value, which is `null`. If you use `null` to initialize a value of an inferred type and there's no other information that can be used to determine a more specific type, the compiler will infer the `Nothing?` type:

```
val x = null           // 'x' has type `Nothing?`  
val l = listOf(null)   // 'l' has type `List<Nothing?>
```

Java Interoperability

Please see the section on exceptions in the [Java Interoperability section](#) for information about Java interoperability.

Annotations

Annotation Declaration

Annotations are means of attaching metadata to code. To declare an annotation, put the `annotation` modifier in front of a class:

```
annotation class Fancy
```

Additional attributes of the annotation can be specified by annotating the annotation class with meta-annotations:

- `@Target` specifies the possible kinds of elements which can be annotated with the annotation (classes, functions, properties, expressions etc.);
- `@Retention` specifies whether the annotation is stored in the compiled class files and whether it's visible through reflection at runtime (by default, both are true);
- `@Repeatable` allows using the same annotation on a single element multiple times;
- `@MustBeDocumented` specifies that the annotation is part of the public API and should be included in the class or method signature shown in the generated API documentation.

```
@Target(AnnotationTarget.CLASS, AnnotationTarget.FUNCTION,
        AnnotationTarget.VALUE_PARAMETER, AnnotationTarget.EXPRESSION)
@Retention(AnnotationRetention.SOURCE)
@MustBeDocumented
annotation class Fancy
```

Usage

```
@Fancy class Foo {
    @Fancy fun baz(@Fancy foo: Int): Int {
        return (@Fancy 1)
    }
}
```

If you need to annotate the primary constructor of a class, you need to add the `constructor` keyword to the constructor declaration, and add the annotations before it:

```
class Foo @Inject constructor(dependency: MyDependency) { ... }
```

You can also annotate property accessors:

```
class Foo {
    var x: MyDependency? = null
    @Inject set
}
```

Constructors

Annotations may have constructors that take parameters.

```
annotation class Special(val why: String)
```

```
@Special("example") class Foo {}
```

Allowed parameter types are:

- types that correspond to Java primitive types (Int, Long etc.);
- strings;
- classes (`Foo::class`);
- enums;
- other annotations;
- arrays of the types listed above.

Annotation parameters cannot have nullable types, because the JVM does not support storing `null` as a value of an annotation attribute.

If an annotation is used as a parameter of another annotation, its name is not prefixed with the `@` character:

```
annotation class ReplaceWith(val expression: String)

annotation class Deprecated(
    val message: String,
    val replaceWith: ReplaceWith = ReplaceWith(""))

@Deprecated("This function is deprecated, use === instead", ReplaceWith("this === other"))
```

If you need to specify a class as an argument of an annotation, use a Kotlin class ([KClass](#)). The Kotlin compiler will automatically convert it to a Java class, so that the Java code will be able to see the annotations and arguments normally.

```
import kotlin.reflect.KClass

annotation class Ann(val arg1: KClass<*>, val arg2: KClass<out Any>)

@Ann(String::class, Int::class) class MyClass
```

Lambdas

Annotations can also be used on lambdas. They will be applied to the `invoke()` method into which the body of the lambda is generated. This is useful for frameworks like [Quasar](#), which uses annotations for concurrency control.

```
annotation class Suspendable

val f = @Suspendable { Fiber.sleep(10) }
```

Annotation Use-site Targets

When you're annotating a property or a primary constructor parameter, there are multiple Java elements which are generated from the corresponding Kotlin element, and therefore multiple possible locations for the annotation in the generated Java bytecode. To specify how exactly the annotation should be generated, use the following syntax:

```
class Example(@field:Ann val foo,    // annotate Java field
              @get:Ann val bar,     // annotate Java getter
              @param:Ann val quux)  // annotate Java constructor parameter
```

The same syntax can be used to annotate the entire file. To do this, put an annotation with the target `file` at the top level of a file, before the package directive or before all imports if the file is in the default package:

```
@file:JvmName("Foo")

package org.jetbrains.demo
```

If you have multiple annotations with the same target, you can avoid repeating the target by adding brackets after the target and putting all the annotations inside the brackets:

```
class Example {
    @set:[Inject VisibleForTesting]
    var collaborator: Collaborator
}
```

The full list of supported use-site targets is:

- `file`;
- `property` (annotations with this target are not visible to Java);
- `field`;
- `get` (property getter);
- `set` (property setter);
- `receiver` (receiver parameter of an extension function or property);

- `param` (constructor parameter);
- `setparam` (property setter parameter);
- `delegate` (the field storing the delegate instance for a delegated property).

To annotate the receiver parameter of an extension function, use the following syntax:

```
fun @receiver:Fancy String.myExtension() { ... }
```

If you don't specify a use-site target, the target is chosen according to the `@Target` annotation of the annotation being used. If there are multiple applicable targets, the first applicable target from the following list is used:

- `param`;
- `property`;
- `field`.

Java Annotations

Java annotations are 100% compatible with Kotlin:

```
import org.junit.Test
import org.junit.Assert.*
import org.junit.Rule
import org.junit.rules.*

class Tests {
    // apply @Rule annotation to property getter
    @get:Rule val tempFolder = TemporaryFolder()

    @Test fun simple() {
        val f = tempFolder.newFile()
        assertEquals(42, getTheAnswer())
    }
}
```

Since the order of parameters for an annotation written in Java is not defined, you can't use a regular function call syntax for passing the arguments. Instead, you need to use the named argument syntax:

```
// Java
public @interface Ann {
    int intValue();
    String stringValue();
}

// Kotlin
@Ann(intValue = 1, stringValue = "abc") class C
```

Just like in Java, a special case is the `value` parameter; its value can be specified without an explicit name:

```
// Java
public @interface AnnWithValue {
    String value();
}

// Kotlin
@AnnWithValue("abc") class C
```

Arrays as annotation parameters

If the `value` argument in Java has an array type, it becomes a `vararg` parameter in Kotlin:

```
// Java
public @interface AnnWithArrayValue {
    String[] value();
}
```

```
// Kotlin
@AnnWithArrayValue("abc", "foo", "bar") class C
```

For other arguments that have an array type, you need to use the array literal syntax (since Kotlin 1.2) or `arrayOf(...)`:

```
// Java
public @interface AnnWithArrayMethod {
    String[] names();
}
```

```
// Kotlin 1.2+:
@AnnWithArrayMethod(names = ["abc", "foo", "bar"])
class C
```

```
// Older Kotlin versions:
@AnnWithArrayMethod(names = arrayOf("abc", "foo", "bar"))
class D
```

Accessing properties of an annotation instance

Values of an annotation instance are exposed as properties to Kotlin code:

```
// Java
public @interface Ann {
    int value();
}
```

```
// Kotlin
fun foo(ann: Ann) {
    val i = ann.value
}
```


Reflection

Reflection is a set of language and library features that allows for introspecting the structure of your own program at runtime. Kotlin makes functions and properties first-class citizens in the language, and introspecting them (i.e. learning a name or a type of a property or function at runtime) is closely intertwined with simply using a functional or reactive style.

⚠ On the Java platform, the runtime component required for using the reflection features is distributed as a separate JAR file (`kotlin-reflect.jar`). This is done to reduce the required size of the runtime library for applications that do not use reflection features. If you do use reflection, please make sure that the `.jar` file is added to the classpath of your project.

Class References

The most basic reflection feature is getting the runtime reference to a Kotlin class. To obtain the reference to a statically known Kotlin class, you can use the *class literal* syntax:

```
val c = MyClass::class
```

The reference is a value of type `KClass`.

Note that a Kotlin class reference is not the same as a Java class reference. To obtain a Java class reference, use the `.java` property on a `KClass` instance.

Bound Class References (since 1.1)

You can get the reference to a class of a specific object with the same `::class` syntax by using the object as a receiver:

```
val widget: Widget = ...
assert(widget is GoodWidget) { "Bad widget: ${widget::class.qualifiedName}" }
```

You obtain the reference to an exact class of an object, for instance `GoodWidget` or `BadWidget`, despite the type of the receiver expression (`Widget`).

Callable references

References to functions, properties, and constructors, apart from introspecting the program structure, can also be called or used as instances of [function types](#).

The common supertype for all callable references is [KCallable<out R>](#), where `R` is the return value type, which is the property type for properties, and the constructed type for constructors.

Function References

When we have a named function declared like this:

```
fun isOdd(x: Int) = x % 2 != 0
```

We can easily call it directly (`isOdd(5)`), but we can also use it as a function type value, e.g. pass it to another function. To do this, we use the `::` operator:

```
fun isOdd(x: Int) = x % 2 != 0

fun main(args: Array<String>) {
    //sampleStart
    val numbers = listOf(1, 2, 3)
    println(numbers.filter(::isOdd))
    //sampleEnd
}
```

Here `::isOdd` is a value of function type `(Int) -> Boolean`.

Function references belong to one of the [KFunction<out R>](#) subtypes, depending on the parameter count, e.g. `KFunction3<T1, T2, T3, R>`.

`::` can be used with overloaded functions when the expected type is known from the context. For example:

```
fun main(args: Array<String>) {
    //sampleStart
    fun isOdd(x: Int) = x % 2 != 0
    fun isOdd(s: String) = s == "brillig" || s == "slithy" || s == "tove"

    val numbers = listOf(1, 2, 3)
    println(numbers.filter(::isOdd)) // refers to isOdd(x: Int)
    //sampleEnd
}
```

Alternatively, you can provide the necessary context by storing the method reference in a variable with an explicitly specified type:

```
val predicate: (String) -> Boolean = ::isOdd // refers to isOdd(x: String)
```

If we need to use a member of a class, or an extension function, it needs to be qualified, e.g. `String::toCharArray`.

Note that even if you initialize a variable with a reference to an extension function, the inferred function type will have no receiver (it will have an additional parameter accepting a receiver object). To have a function type with receiver instead, specify the type explicitly:

```
val isEmptyStringList: List<String>().() -> Boolean = List::isEmpty
```

Example: Function Composition

Consider the following function:

```
fun <A, B, C> compose(f: (B) -> C, g: (A) -> B): (A) -> C {
    return { x -> f(g(x)) }
}
```

It returns a composition of two functions passed to it: `compose(f, g) = f(g(*))`. Now, you can apply it to callable references:

```
fun <A, B, C> compose(f: (B) -> C, g: (A) -> B): (A) -> C {
    return { x -> f(g(x)) }
}
```

```
fun isOdd(x: Int) = x % 2 != 0
```

```
fun main(args: Array<String>) {
    //sampleStart
    fun length(s: String) = s.length

    val oddLength = compose(::isOdd, ::length)
    val strings = listOf("a", "ab", "abc")

    println(strings.filter(oddLength))
    //sampleEnd
}
```

Property References

To access properties as first-class objects in Kotlin, we can also use the `::` operator:

```
val x = 1
```

```
fun main(args: Array<String>) {
    println(::x.get())
    println(::x.name)
}
```

The expression `::x` evaluates to a property object of type `KProperty<Int>`, which allows us to read its value using `get()` or retrieve the property name using the `name` property. For more information, please refer to the [docs on the KProperty class](#).

For a mutable property, e.g. `var y = 1`, `::y` returns a value of type `KMutableProperty<Int>`, which has a `set()` method:

```
var y = 1
```

```
fun main(args: Array<String>) {
    ::y.set(2)
    println(y)
}
```

A property reference can be used where a function with one parameter is expected:

```
fun main(args: Array<String>) {
    //sampleStart
    val strs = listOf("a", "bc", "def")
    println(strs.map(String::length))
    //sampleEnd
}
```

To access a property that is a member of a class, we qualify it:

```
fun main(args: Array<String>) {
    //sampleStart
    class A(val p: Int)
    val prop = A::p
    println(prop.get(A(1)))
    //sampleEnd
}
```

For an extension property:

```
val String.lastChar: Char
    get() = this[length - 1]

fun main(args: Array<String>) {
    println(String::lastChar.get("abc"))
}
```

Interoperability With Java Reflection

On the Java platform, standard library contains extensions for reflection classes that provide a mapping to and from Java reflection objects (see package `kotlin.reflect.jvm`). For example, to find a backing field or a Java method that serves as a getter for a Kotlin property, you can say something like this:

```
import kotlin.reflect.jvm.*

class A(val p: Int)

fun main(args: Array<String>) {
    println(A::p.javaGetter) // prints "public final int A.getP()"
    println(A::p.javaField)  // prints "private final int A.p"
}
```

To get the Kotlin class corresponding to a Java class, use the `.kotlin` extension property:

```
fun getKClass(o: Any): KClass<Any> = o.javaClass.kotlin
```

Constructor References

Constructors can be referenced just like methods and properties. They can be used wherever an object of function type is expected that takes the same parameters as the constructor and returns an object of the appropriate type. Constructors are referenced by using the `::` operator and adding the class name. Consider the following function that expects a function parameter with no parameters and return type `Foo`:

```
class Foo

fun function(factory: () -> Foo) {
    val x: Foo = factory()
}
```

Using `::Foo`, the zero-argument constructor of the class `Foo`, we can simply call it like this:

```
function(::Foo)
```

Callable references to constructors are typed as one of the [KFunction<out R>](#) subtypes , depending on the parameter count.

Bound Function and Property References (since 1.1)

You can refer to an instance method of a particular object:

```
fun main(args: Array<String>) {
//sampleStart
    val numberRegex = "\\d+".toRegex()
    println(numberRegex.matches("29"))

    val isNumber = numberRegex::matches
    println(isNumber("29"))
//sampleEnd
}
```

Instead of calling the method `matches` directly we are storing a reference to it. Such reference is bound to its receiver. It can be called directly (like in the example above) or used whenever an expression of function type is expected:

```
fun main(args: Array<String>) {
//sampleStart
    val numberRegex = "\\d+".toRegex()
    val strings = listOf("abc", "124", "a70")
    println(strings.filter(numberRegex::matches))
//sampleEnd
}
```

Compare the types of bound and the corresponding unbound references. Bound callable reference has its receiver "attached" to it, so the type of the receiver is no longer a parameter:

```
val isNumber: (CharSequence) -> Boolean = numberRegex::matches
```

```
val matches: (Regex, CharSequence) -> Boolean = Regex::matches
```

Property reference can be bound as well:

```
fun main(args: Array<String>) {
//sampleStart
    val prop = "abc"::length
    println(prop.get())
//sampleEnd
}
```

Since Kotlin 1.2, explicitly specifying `this` as the receiver is not necessary: `this::foo` and `::foo` are equivalent.

Bound constructor references

A bound callable reference to a constructor of an [inner class](#) can be obtained by providing an instance of the outer class:

```
class Outer {
    inner class Inner
}

val o = Outer()
val boundInnerCtor = o::Inner
```

Type-Safe Builders

By using well-named functions as builders in combination with [function literals with receiver](#) it is possible to create type-safe, statically-typed builders in Kotlin.

Type-safe builders allow creating Kotlin-based domain-specific languages (DSLs) suitable for building complex hierarchical data structures in a semi-declarative way. Some of the example use cases for the builders are:

- Generating markup with Kotlin code, such as [HTML](#) or XML;
- Programmatically laying out UI components: [Anko](#)
- Configuring routes for a web server: [Ktor](#).

A type-safe builder example

Consider the following code:

```
import com.example.html.* // see declarations below

fun result(args: Array<String>) =
    html {
        head {
            title {+"XML encoding with Kotlin"}
        }
        body {
            h1 {+"XML encoding with Kotlin"}
            p {+"this format can be used as an alternative markup to XML"}

            // an element with attributes and text content
            a(href = "http://kotlinlang.org") {+"Kotlin"}

            // mixed content
            p {
                +"This is some"
                b {+"mixed"}
                +"text. For more see the"
                a(href = "http://kotlinlang.org") {+"Kotlin"}
                +"project"
            }
            p {+"some text"}

            // content generated by
            p {
                for (arg in args)
                    +arg
            }
        }
    }
```

This is completely legitimate Kotlin code. You can play with this code online (modify it and run in the browser) [here](#).

How it works

Let's walk through the mechanisms of implementing type-safe builders in Kotlin. First of all, we need to define the model we want to build, in this case we need to model HTML tags. It is easily done with a bunch of classes. For example, `HTML` is a class that describes the `<html>` tag, i.e. it defines children like `<head>` and `<body>`. (See its declaration [below](#).)

Now, let's recall why we can say something like this in the code:

```
html {
    // ...
}
```

`html` is actually a function call that takes a [lambda expression](#) as an argument. This function is defined as follows:

```
fun html(init: HTML.() -> Unit): HTML {
    val html = HTML()
    html.init()
    return html
}
```

This function takes one parameter named `init`, which is itself a function. The type of the function is `HTML.() -> Unit`, which is a *function type with receiver*. This means that we need to pass an instance of type `HTML` (a *receiver*) to the function, and we can call members of that instance inside the function. The receiver can be accessed through the `this` keyword:

```
html {
    this.head { ... }
    this.body { ... }
}
```

(`head` and `body` are member functions of `HTML`.)

Now, `this` can be omitted, as usual, and we get something that looks very much like a builder already:

```
html {
    head { ... }
    body { ... }
}
```

So, what does this call do? Let's look at the body of `html` function as defined above. It creates a new instance of `HTML`, then it initializes it by calling the function that is passed as an argument (in our example this boils down to calling `head` and `body` on the `HTML` instance), and then it returns this instance. This is exactly what a builder should do.

The `head` and `body` functions in the `HTML` class are defined similarly to `html`. The only difference is that they add the built instances to the `children` collection of the enclosing `HTML` instance:

```
fun head(init: Head.() -> Unit) : Head {
    val head = Head()
    head.init()
    children.add(head)
    return head
}

fun body(init: Body.() -> Unit) : Body {
    val body = Body()
    body.init()
    children.add(body)
    return body
}
```

Actually these two functions do just the same thing, so we can have a generic version, `initTag`:

```
protected fun <T : Element> initTag(tag: T, init: T.() -> Unit): T {
    tag.init()
    children.add(tag)
    return tag
}
```

So, now our functions are very simple:

```
fun head(init: Head.() -> Unit) = initTag(Head(), init)
```

```
fun body(init: Body.() -> Unit) = initTag(Body(), init)
```

And we can use them to build `<head>` and `<body>` tags.

One other thing to be discussed here is how we add text to tag bodies. In the example above we say something like:

```
html {
    head {
        title {+"XML encoding with Kotlin"}
    }
    // ...
}
```

So basically, we just put a string inside a tag body, but there is this little `+` in front of it, so it is a function call that invokes a prefix `unaryPlus()` operation. That operation is actually defined by an extension function `unaryPlus()` that is a member of the `TagWithText` abstract class (a parent of `Title`):

```
operator fun String.unaryPlus() {
    children.add(TextElement(this))
}
```

So, what the prefix `+` does here is wrapping a string into an instance of `TextElement` and adding it to the `children` collection, so that it becomes a proper part of the tag tree.

All this is defined in a package `com.example.html` that is imported at the top of the builder example above. In the last section you can read through the full definition of this package.

Scope control: @DslMarker (since 1.1)

When using DSLs, one might have come across the problem that too many functions can be called in the context. We can call methods of every available implicit receiver inside a lambda and therefore get an inconsistent result, like the tag `head` inside another `head`:

```
html {
    head {
        head {} // should be forbidden
    }
    // ...
}
```

In this example only members of the nearest implicit receiver `this@head` must be available; `head()` is a member of the outer receiver `this@html`, so it must be illegal to call it.

To address this problem, in Kotlin 1.1 a special mechanism to control receiver scope was introduced.

To make the compiler start controlling scopes we only have to annotate the types of all receivers used in the DSL with the same marker annotation. For instance, for HTML Builders we declare an annotation `@HTMLTagMarker`:

```
@DslMarker
annotation class HtmlTagMarker
```

An annotation class is called a DSL marker if it is annotated with the `@DslMarker` annotation.

In our DSL all the tag classes extend the same superclass `Tag`. It's enough to annotate only the superclass with `@HtmlTagMarker` and after that the Kotlin compiler will treat all the inherited classes as annotated:

```
@HtmlTagMarker
abstract class Tag(val name: String) { ... }
```

We don't have to annotate the `HTML` or `Head` classes with `@HtmlTagMarker` because their superclass is already annotated:

```
class HTML() : Tag("html") { ... }
class Head() : Tag("head") { ... }
```

After we've added this annotation, the Kotlin compiler knows which implicit receivers are part of the same DSL and allows to call members of the nearest receivers only:

```
html {
    head {
        head { } // error: a member of outer receiver
    }
    // ...
}
```

Note that it's still possible to call the members of the outer receiver, but to do that you have to specify this receiver explicitly:

```
html {
    head {
        this@html.head { } // possible
    }
    // ...
}
```

Full definition of the `com.example.html` package

This is how the package `com.example.html` is defined (only the elements used in the example above). It builds an HTML tree. It makes heavy use of [extension functions](#) and [lambdas with receiver](#).

Note that the `@DslMarker` annotation is available only since Kotlin 1.1.

```
package com.example.html

interface Element {
    fun render(builder: StringBuilder, indent: String)
}

class TextElement(val text: String) : Element {
    override fun render(builder: StringBuilder, indent: String) {
        builder.append("$indent$text\n")
    }
}

@DslMarker
annotation class HtmlTagMarker

@HtmlTagMarker
abstract class Tag(val name: String) : Element {
    val children = arrayListOf<Element>()
    val attributes = hashMapOf<String, String>()

    protected fun <T : Element> initTag(tag: T, init: T.() -> Unit): T {
        tag.init()
        children.add(tag)
        return tag
    }

    override fun render(builder: StringBuilder, indent: String) {
        builder.append("$indent<$name${renderAttributes()}>\n")
        for (c in children) {
            c.render(builder, indent + " ")
        }
        builder.append("$indent</$name>\n")
    }

    private fun renderAttributes(): String {
        val builder = StringBuilder()
        for ((attr, value) in attributes) {
            builder.append(" $attr=\"$value\"")
        }
        return builder.toString()
    }

    override fun toString(): String {
        val builder = StringBuilder()
        render(builder, "")
        return builder.toString()
    }
}

abstract class TagWithText(name: String) : Tag(name) {
```



```

        operator fun String.unaryPlus() {
            children.add(TextElement(this))
        }
    }

class HTML : TagWithText("html") {
    fun head(init: Head.() -> Unit) = initTag(Head(), init)

    fun body(init: Body.() -> Unit) = initTag(Body(), init)
}

class Head : TagWithText("head") {
    fun title(init: Title.() -> Unit) = initTag(Title(), init)
}

class Title : TagWithText("title")

abstract class BodyTag(name: String) : TagWithText(name) {
    fun b(init: B.() -> Unit) = initTag(B(), init)
    fun p(init: P.() -> Unit) = initTag(P(), init)
    fun h1(init: H1.() -> Unit) = initTag(H1(), init)
    fun a(href: String, init: A.() -> Unit) {
        val a = initTag(A(), init)
        a.href = href
    }
}

class Body : BodyTag("body")
class B : BodyTag("b")
class P : BodyTag("p")
class H1 : BodyTag("h1")

class A : BodyTag("a") {
    var href: String
    get() = attributes["href"]!!
    set(value) {
        attributes["href"] = value
    }
}

fun html(init: HTML.() -> Unit): HTML {
    val html = HTML()
    html.init()
    return html
}

```

Type aliases

Type aliases provide alternative names for existing types. If the type name is too long you can introduce a different shorter name and use the new one instead.

It's useful to shorten long generic types. For instance, it's often tempting to shrink collection types:

```
typealias NodeSet = Set<Network.Node>

typealias FileTable<K> = MutableMap<K, MutableList<File>>
```

You can provide different aliases for function types:

```
typealias MyHandler = (Int, String, Any) -> Unit

typealias Predicate<T> = (T) -> Boolean
```

You can have new names for inner and nested classes:

```
class A {
    inner class Inner
}
class B {
    inner class Inner
}

typealias AInner = A.Inner
typealias BInner = B.Inner
```

Type aliases do not introduce new types. They are equivalent to the corresponding underlying types. When you add `typealias Predicate<T>` and use `Predicate<Int>` in your code, the Kotlin compiler always expand it to `(Int) -> Boolean`. Thus you can pass a variable of your type whenever a general function type is required and vice versa:

```
typealias Predicate<T> = (T) -> Boolean

fun foo(p: Predicate<Int>) = p(42)

fun main(args: Array<String>) {
    val f: (Int) -> Boolean = { it > 0 }
    println(foo(f)) // prints "true"

    val p: Predicate<Int> = { it > 0 }
    println(listOf(1, -2).filter(p)) // prints "[1]"
}
```

Multiplatform Projects

⚠ Multiplatform projects are a new experimental feature in Kotlin 1.2. All of the language and tooling features described in this document are subject to change in future Kotlin versions.

A Kotlin multiplatform project allows you to compile the same code to multiple target platforms. At this time supported target platforms are the JVM and JS, with Native to be added later.

Multiplatform Project Structure

A multiplatform project consists of three types of modules:

- A *common* module contains code that is not specific to any platform, as well as declarations without implementation of platform-dependent APIs. Those declarations allow common code to depend on platform-specific implementations.
- A *platform* module contains implementations of platform-dependent declarations in the common module for a specific platform, as well as other platform-dependent code. A platform module is always an implementation of a single common module.
- A regular module. Such modules target a specific platform and can either be dependencies of platform modules or depend on platform modules.

A common module can depend only on other common modules and libraries, including the common version of the Kotlin standard library (`kotlin-stdlib-common`). Common modules contain only Kotlin code, and not code in any other languages.

A platform module can depend on any modules and libraries available on the given platform (including Java libraries in case of Kotlin/JVM and JS libraries for Kotlin/JS). Platform modules targeting Kotlin/JVM can also contain code in Java and other JVM languages.

Compiling a common module produces a special *metadata* file containing all the declarations in the module. Compiling a platform module produces target-specific code (JVM bytecode or JS source code) for the code in the platform module as well as the common module that it implements.

Therefore, each multiplatform library needs to be distributed as a set of artifacts - a common .jar containing the metadata for common code, as well as platform specific .jars containing the compiled implementation code for each platform.

Setting Up a Multiplatform Project

As of Kotlin 1.2, multiplatform projects have to be built with Gradle; other build systems are not supported. If you work with a multiplatform project in IDE, make sure that `Delegate IDE build/run actions to gradle` option is enabled and `Gradle Test Runner` is set for `Run tests using` option. Both options may be found here: *Settings > Build, execution, Deployment > Build Tools > Gradle > Runner*

To create a new multiplatform project in the IDE, select the "Kotlin (Multiplatform)" option under "Kotlin" in the New Project dialog. This will create a project with three modules, a common one and two platform ones for JVM and JS. To add additional modules, select one of the "Kotlin (Multiplatform)" options under "Gradle" in the New Module dialog.

If you need to configure the project manually, use the following steps:

- Add the Kotlin Gradle plugin to the buildscript classpath: `classpath "org.jetbrains.kotlin:kotlin-gradle-plugin:$kotlin_version"`
- Apply the `kotlin-platform-common` plugin to the common module
- Add the `kotlin-stdlib-common` dependency to the common module
- Apply the `kotlin-platform-jvm`, `kotlin-platform-android`, and `kotlin-platform-js` plugins to the platform modules for JVM, Android, and JS, respectively
- Add dependencies with `expectedBy` scope from the platform modules to the common module

The following example demonstrates a complete `build.gradle` file for a common module with Kotlin 1.2:

```

buildscript {
    ext.kotlin_version = '1.2.70'

    repositories {
        mavenCentral()
    }
    dependencies {
        classpath "org.jetbrains.kotlin:kotlin-gradle-plugin:$kotlin_version"
    }
}

apply plugin: 'kotlin-platform-common'

repositories {
    mavenCentral()
}

dependencies {
    compile "org.jetbrains.kotlin:kotlin-stdlib-common:$kotlin_version"
    testCompile "org.jetbrains.kotlin:kotlin-test-common:$kotlin_version"
}

```

And the example below shows a complete `build.gradle` for a JVM module. Pay special attention to the `expectedBy` line in the `dependencies` block:

```

buildscript {
    ext.kotlin_version = '1.2.70'

    repositories {
        mavenCentral()
    }
    dependencies {
        classpath "org.jetbrains.kotlin:kotlin-gradle-plugin:$kotlin_version"
    }
}

apply plugin: 'kotlin-platform-jvm'

repositories {
    mavenCentral()
}

dependencies {
    compile "org.jetbrains.kotlin:kotlin-stdlib:$kotlin_version"
    expectedBy project(":")
    testCompile "junit:junit:4.12"
    testCompile "org.jetbrains.kotlin:kotlin-test-junit:$kotlin_version"
    testCompile "org.jetbrains.kotlin:kotlin-test:$kotlin_version"
}

```

Platform-Specific Declarations

One of the key capabilities of Kotlin's multiplatform code is a way for common code to depend on platform-specific declarations. In other languages, this can often be accomplished by building a set of interfaces in the common code and implementing these interfaces in platform-specific modules. However, this approach is not ideal in cases when you have a library on one of the platforms that implements the functionality you need, and you'd like to use the API of this library directly without extra wrappers. Also, it requires common declarations to be expressed as interfaces, which doesn't cover all possible cases.

As an alternative, Kotlin provides a mechanism of *expected and actual declarations*. With this mechanism, a common module can define *expected declarations*, and a platform module can provide *actual declarations* corresponding to the expected ones. To see how this works, let's look at an example first. This code is part of a common module:

```
package org.jetbrains.foo

expect class Foo(bar: String) {
    fun frob()
}

fun main(args: Array<String>) {
    Foo("Hello").frob()
}
```

And this is the corresponding JVM module:

```
package org.jetbrains.foo

actual class Foo actual constructor(val bar: String) {
    actual fun frob() {
        println("Frobbing the $bar")
    }
}
```

This illustrates several important points:

- An expected declaration in the common module and its actual counterparts always have exactly the same fully qualified name.
- An expected declaration is marked with the `expect` keyword; the actual declaration is marked with the `actual` keyword.
- All actual declarations that match any part of an expected declaration need to be marked as `actual`.
- Expected declarations never contain any implementation code.

Note that expected declarations are not restricted to interfaces and interface members. In this example, the expected class has a constructor and can be created directly from common code. You can apply the `expect` modifier to other declarations as well, including top-level declarations and annotations:

```
// Common
expect fun formatString(source: String, vararg args: Any): String

expect annotation class Test

// JVM
actual fun formatString(source: String, vararg args: Any) =
    String.format(source, args)

actual typealias Test = org.junit.Test
```

The compiler ensures that every expected declaration has actual declarations in all platform modules that implement the corresponding common module, and reports an error if any actual declarations are missing. The IDE provides tools that help you create the missing actual declarations.

If you have a platform-specific library that you want to use in common code while providing your own implementation for another platform, you can provide a `typealias` to an existing class as the actual declaration:

```
expect class AtomicRef<V>(value: V) {
    fun get(): V
    fun set(value: V)
    fun getAndSet(value: V): V
    fun compareAndSet(expect: V, update: V): Boolean
}

actual typealias AtomicRef<V> = java.util.concurrent.atomic.AtomicReference<V>
```

Multiplatform tests

It is possible to write tests in a common project so that they will be compiled and run in each platform project. There are 4 annotations provided in `kotlin.test` package to markup tests in common code: `@Test`, `@Ignore`, `@BeforeTest` and `@AfterTest`. In JVM platform these annotations are mapped to the corresponding JUnit 4 annotations, and in JS they are already available since 1.1.4 to support JS unit testing.

In order to use them you need to add a dependency on `kotlin-test-annotations-common` to your common module, on `kotlin-test-junit` to your JVM module, and on `kotlin-test-js` to the JS module.

Reference

Keywords and Operators

Hard Keywords

The following tokens are always interpreted as keywords and cannot be used as identifiers:

- `as`
 - is used for [type casts](#)
 - specifies an [alias for an import](#)
- `as?` is used for [safe type casts](#)
- `break` [terminates the execution of a loop](#)
- `class` declares a [class](#)
- `continue` [proceeds to the next step of the nearest enclosing loop](#)
- `do` begins a [do/while loop](#) (loop with postcondition)
- `else` defines the branch of an [if expression](#) which is executed when the condition is false
- `false` specifies the 'false' value of the [Boolean type](#)
- `for` begins a [for loop](#)
- `fun` declares a [function](#)
- `if` begins an [if expression](#)
- `in`
 - specifies the object being iterated in a [for loop](#)
 - is used as an infix operator to check that a value belongs to [a range](#), a collection or another entity that [defines the 'contains' method](#)
 - is used in [when expressions](#) for the same purpose
 - marks a type parameter as [contravariant](#)
- `!in`
 - is used as an operator to check that a value does NOT belong to [a range](#), a collection or another entity that [defines the 'contains' method](#)
 - is used in [when expressions](#) for the same purpose
- `interface` declares an [interface](#)
- `is`
 - checks that [a value has a certain type](#)
 - is used in [when expressions](#) for the same purpose
- `!is`
 - checks that [a value does NOT have a certain type](#)
 - is used in [when expressions](#) for the same purpose
- `null` is a constant representing an object reference that doesn't point to any object
- `object` declares [a class and its instance at the same time](#)
- `package` specifies the [package for the current file](#)
-

- `return` [returns from the nearest enclosing function or anonymous function](#)
- `super`
 - [refers to the superclass implementation of a method or property](#)
 - [calls the superclass constructor from a secondary constructor](#)
- `this`
 - refers to [the current receiver](#)
 - [calls another constructor of the same class from a secondary constructor](#)
- `throw` [throws an exception](#)
- `true` specifies the 'true' value of the [Boolean type](#)
- `try` [begins an exception handling block](#)
- `typealias` declares a [type alias](#)
- `val` declares a read-only [property](#) or [local variable](#)
- `var` declares a mutable [property](#) or [local variable](#)
- `when` begins a [when expression](#) (executes one of the given branches)
- `while` begins a [while loop](#) (loop with precondition)

Soft Keywords

The following tokens act as keywords in the context when they are applicable and can be used as identifiers in other contexts:

- `by`
 - [delegates the implementation of an interface to another object](#)
 - [delegates the implementation of accessors for a property to another object](#)
- `catch` begins a block that [handles a specific exception type](#)
- `constructor` declares a [primary or secondary constructor](#)
- `delegate` is used as an [annotation use-site target](#)
- `dynamic` references a [dynamic type](#) in Kotlin/JS code
- `field` is used as an [annotation use-site target](#)
- `file` is used as an [annotation use-site target](#)
- `finally` begins a block that [is always executed when a try block exits](#)
- `get`
 - declares the [getter of a property](#)
 - is used as an [annotation use-site target](#)
- `import` [imports a declaration from another package into the current file](#)
- `init` begins an [initializer block](#)
- `param` is used as an [annotation use-site target](#)
- `property` is used as an [annotation use-site target](#)
- `receiver` is used as an [annotation use-site target](#)
- `set`
 - declares the [setter of a property](#)
 - is used as an [annotation use-site target](#)
- `setparam` is used as an [annotation use-site target](#)
- `where` specifies [constraints for a generic type parameter](#)

Modifier Keywords

The following tokens act as keywords in modifier lists of declarations and can be used as identifiers in other contexts:

- `actual` denotes a platform-specific implementation in [multiplatform projects](#)
- `abstract` marks a class or member as [abstract](#)
- `annotation` declares an [annotation class](#)
- `companion` declares a [companion object](#)
- `const` marks a property as a [compile-time constant](#)
- `crossinline` forbids [non-local returns in a lambda passed to an inline function](#)
- `data` instructs the compiler to [generate canonical members for a class](#)
- `enum` declares an [enumeration](#)
- `expect` marks a declaration as [platform-specific](#), expecting an implementation in platform modules.
- `external` marks a declaration as implemented not in Kotlin (accessible through [JNI](#) or in [JavaScript](#))
- `final` forbids [overriding a member](#)
- `infix` allows calling a function in [infix notation](#)
- `inline` tells the compiler to [inline the function and the lambdas passed to it at the call site](#)
- `inner` allows referring to the outer class instance from a [nested class](#)
- `internal` marks a declaration as [visible in the current module](#)
- `lateinit` allows initializing a [non-null property outside of a constructor](#)
- `noinline` turns off [inlining of a lambda passed to an inline function](#)
- `open` allows [subclassing a class or overriding a member](#)
- `operator` marks a function as [overloading an operator or implementing a convention](#)
- `out` marks a type parameter as [covariant](#)
- `override` marks a member as an [override of a superclass member](#)
- `private` marks a declaration as [visible in the current class or file](#)
- `protected` marks a declaration as [visible in the current class and its subclasses](#)
- `public` marks a declaration as [visible anywhere](#)
- `reified` marks a type parameter of an inline function as [accessible at runtime](#)
- `sealed` declares a [sealed class](#) (a class with restricted subclassing)
- `suspend` marks a function or lambda as suspending (usable as a [coroutine](#))
- `tailrec` marks a function as [tail-recursive](#) (allowing the compiler to replace recursion with iteration)
- `vararg` allows [passing a variable number of arguments for a parameter](#)

Special Identifiers

The following identifiers are defined by the compiler in specific contexts and can be used as regular identifiers in other contexts:

- `field` is used inside a property accessor to refer to the [backing field of the property](#)
- `it` is used inside a lambda to [refer to its parameter implicitly](#)

Operators and Special Symbols

Kotlin supports the following operators and special symbols:

- `+`, `-`, `*`, `/`, `%` - mathematical operators
 - `*` is also used to [pass an array to a vararg parameter](#)
- `=`
 - assignment operator
 - is used to specify [default values for parameters](#)
- `+=`, `-=`, `*=`, `/=`, `%=` - [augmented assignment operators](#)

- `++`, `--` - [increment and decrement operators](#)
- `&&`, `||`, `!` - logical 'and', 'or', 'not' operators (for bitwise operations, use corresponding [infix functions](#))
- `==`, `!=` - [equality operators](#) (translated to calls of `equals()` for non-primitive types)
- `===`, `!==` - [referential equality operators](#)
- `<`, `>`, `<=`, `>=` - [comparison operators](#) (translated to calls of `compareTo()` for non-primitive types)
- `[,]` - [indexed access operator](#) (translated to calls of `get` and `set`)
- `!!` [asserts that an expression is non-null](#)
- `?.` performs a [safe call](#) (calls a method or accesses a property if the receiver is non-null)
- `?:` takes the right-hand value if the left-hand value is null (the [elvis operator](#))
- `::` creates a [member reference](#) or a [class reference](#)
- `..` creates a [range](#)
- `:` separates a name from a type in declarations
- `?` marks a type as [nullable](#)
- `->`
 - separates the parameters and body of a [lambda expression](#)
 - separates the parameters and return type declaration in a [function type](#)
 - separates the condition and body of a [when expression](#) branch
- `@`
 - introduces an [annotation](#)
 - introduces or references a [loop label](#)
 - introduces or references a [lambda label](#)
 - references a ['this' expression from an outer scope](#)
 - references an [outer superclass](#)
- `;` separates multiple statements on the same line
- `$` references a variable or expression in a [string template](#)
- `_`
 - substitutes an unused parameter in a [lambda expression](#)
 - substitutes an unused parameter in a [destructuring declaration](#)

Grammar

Notation

This section informally explains the grammar notation used below.

Symbols and naming

Terminal symbol names start with an uppercase letter, e.g. **SimpleName**.

Nonterminal symbol names start with a lowercase letter, e.g. **kotlinFile**.

Each *production* starts with a colon (:).

Symbol definitions may have many productions and are terminated by a semicolon (;).

Symbol definitions may be prepended with *attributes*, e.g. `start` attribute denotes a start symbol.

EBNF expressions

Operator `|` denotes *alternative*.

Operator `*` denotes *iteration* (zero or more).

Operator `+` denotes *iteration* (one or more).

Operator `?` denotes *option* (zero or one).

alpha { beta } denotes a nonempty *beta*-separated list of *alpha*'s.

Operator `++` means that no space or comment is allowed between operands.

Semicolons

Kotlin provides "semicolon inference": syntactically, subsentences (e.g., statements, declarations etc) are separated by the pseudo-token [SEMI](#), which stands for "semicolon or newline". In most cases, there's no need for semicolons in Kotlin code.

Syntax

Relevant pages: [Packages](#)

```
start
kotlinFile
: preamble topLevelObject*
;
script
: preamble expression*
;
preamble
(used by script, kotlinFile)
: fileAnnotations? packageHeader? import*
;
fileAnnotations
(used by preamble)
: fileAnnotation*
;
fileAnnotation
(used by fileAnnotations)
: "@" "file" ":" ("[" unescapedAnnotation + "]" | unescapedAnnotation)
;
packageHeader
(used by preamble)
: modifiers "package" SimpleName { "." } SEMI?
;
See Packages

import
(used by preamble)
: "import" SimpleName { "." } ( "." "*" | "as" SimpleName )? SEMI?
;
See Imports

topLevelObject
(used by kotlinFile)
: class
: object
: function
: property
: typeAlias
;
typeAlias
(used by memberDeclaration, declaration, topLevelObject)
```

: [modifiers](#) "typealias" [SimpleName](#) [typeParameters](#)? "=" [type](#)
;

Classes

See [Classes and Inheritance](#)

class
(used by [memberDeclaration](#), [declaration](#), [topLevelObject](#))
: [modifiers](#) ("class" | "interface") [SimpleName](#)
 [typeParameters](#)?
 [primaryConstructor](#)?
 (":" [annotations](#) [delegationSpecifier](#){"", "}")?
 [typeConstraints](#)
 ([classBody](#)? | [enumClassBody](#))
;
primaryConstructor
(used by [class](#), [object](#))
: ([modifiers](#) "constructor")? ("(" [functionParameter](#){"", "}" " ")")
;
classBody
(used by [objectLiteral](#), [enumEntry](#), [class](#), [companionObject](#), [object](#))
: ("{" [members](#) "}")?
;
members
(used by [enumClassBody](#), [classBody](#))
: [memberDeclaration](#)*
;
delegationSpecifier
(used by [objectLiteral](#), [class](#), [companionObject](#), [object](#))
: [constructorInvocation](#)
 [userType](#)
 [explicitDelegation](#)
;
explicitDelegation
(used by [delegationSpecifier](#))
: [userType](#) "by" [expression](#)
;
typeParameters
(used by [typeAlias](#), [class](#), [property](#), [function](#))
: "<" [typeParameter](#){"", "}" ">"
;
typeParameter
(used by [typeParameters](#))
: [modifiers](#) [SimpleName](#) (":" [userType](#))?
;
See [Generic classes](#)

typeConstraints
(used by [class](#), [property](#), [function](#))
: ("where" [typeConstraint](#){"", "}")?
;
typeConstraint
(used by [typeConstraints](#))
: [annotations](#) [SimpleName](#) ":" [type](#)
;
See [Generic constraints](#)

Class members

memberDeclaration
(used by [members](#))
: [companionObject](#)
 [object](#)
 [function](#)
 [property](#)
 [class](#)
 [typeAlias](#)
 [anonymousInitializer](#)
 [secondaryConstructor](#)
;
anonymousInitializer
(used by [memberDeclaration](#))
: "init" [block](#)
;
companionObject
(used by [memberDeclaration](#))
: [modifiers](#) "companion" "object" [SimpleName](#)? (":" [delegationSpecifier](#){"", "}")? [classBody](#)?
;
valueParameters
(used by [secondaryConstructor](#), [function](#))
: ("(" [functionParameter](#){"", "}" "?" " ")")
;
functionParameter
(used by [valueParameters](#), [primaryConstructor](#))

```

: modifiers ("val" | "var")? parameter ("=" expression)?
;
block
(used by catchBlock, anonymousInitializer, secondaryConstructor, functionBody, controlStructureBody, try, finallyBlock)
: "{" statements "}"
;
function
(used by memberDeclaration, declaration, topLevelObject)
: modifiers "fun"
  typeParameters?
  (type "."?)?
  SimpleName
  typeParameters? valueParameters (":" type)?
  typeConstraints
  functionBody?
;
functionBody
(used by getter, setter, function)
: block
: "=" expression
;
variableDeclarationEntry
(used by for, lambdaParameter, property, multipleVariableDeclarations)
: SimpleName (":" type)?
;
multipleVariableDeclarations
(used by for, lambdaParameter, property)
: "(" variableDeclarationEntry "{" "," "}" ")"
;
property
(used by memberDeclaration, declaration, topLevelObject)
: modifiers ("val" | "var")
  typeParameters?
  (type "."?)?
  (multipleVariableDeclarations | variableDeclarationEntry)
  typeConstraints
  ("by" | "=" expression SEMI)?
  (getter? setter? | setter? getter?) SEMI?
;
See Properties and Fields

getter
(used by property)
: modifiers "get"
: modifiers "get" "(" "(" ")" "(" ":" type )? functionBody
;
setter
(used by property)
: modifiers "set"
: modifiers "set" "(" "(" modifiers (SimpleName | parameter) ")" functionBody
;
parameter
(used by functionType, setter, functionParameter)
: SimpleName ":" type
;
object
(used by memberDeclaration, declaration, topLevelObject)
: modifiers "object" SimpleName primaryConstructor? (":" delegationSpecifier "{" "," "}")? classBody?
;
secondaryConstructor
(used by memberDeclaration)
: modifiers "constructor" valueParameters (":" constructorDelegationCall)? block
;
constructorDelegationCall
(used by secondaryConstructor)
: "this" valueArguments
: "super" valueArguments
;
See Object expressions and Declarations

```

Enum classes

See [Enum classes](#)

```

enumClassBody
(used by class)
: "{" enumEntries ";" members "}"
;
enumEntries
(used by enumClassBody)
: (enumEntry "{" "," "}" "?" ";" "?" )?
;
enumEntry
(used by enumEntries)
: modifiers SimpleName valueArguments? classBody?
;

```

Types

See [Types](#)

```
type
  (used by namedInfix, simpleUserType, getter, atomicExpression, whenCondition, property, typeArguments, function, typeAlias,
  parameter, functionType, variableDeclarationEntry, lambdaParameter, typeConstraint)
  : typeModifiers typeReference
;

typeReference
  (used by typeReference, nullableType, type)
  : "(" typeReference ")"
  : functionType
  : userType
  : nullableType
  : "dynamic"
;

nullableType
  (used by typeReference)
  : typeReference "?"
;

userType
  (used by typeParameter, catchBlock, callableReference, typeReference, delegationSpecifier, constructorInvocation,
  explicitDelegation)
  : simpleUserType {"."}
;

simpleUserType
  (used by userType)
  : SimpleName ("<" (projection? type | "*" ) {"."} ">")?
;

projection
  (used by simpleUserType)
  : varianceAnnotation
;

functionType
  (used by typeReference)
  : (type "." )? "(" parameter {"."} ? ")" "->" type
;
;
```

Control structures

See [Control structures](#)

```
controlStructureBody
  (used by whenEntry, for, if, doWhile, while)
  : block
  : blockLevelExpression
;

if
  (used by atomicExpression)
  : "if" "(" expression ")" controlStructureBody SEMI? ("else" controlStructureBody)?
;

try
  (used by atomicExpression)
  : "try" block catchBlock* finallyBlock?
;

catchBlock
  (used by try)
  : "catch" "(" annotations SimpleName ":" userType ")" block
;

finallyBlock
  (used by try)
  : "finally" block
;

loop
  (used by atomicExpression)
  : for
  : while
  : doWhile
;

for
  (used by loop)
  : "for" "(" annotations (multipleVariableDeclarations | variableDeclarationEntry) "in" expression ")" controlStructureBody
;

while
  (used by loop)
  : "while" "(" expression ")" controlStructureBody
;

doWhile
  (used by loop)
  : "do" controlStructureBody "while" "(" expression ")"
;
;
```

Expressions

Precedence

| Precedence | Title | Symbols |
|------------|----------------|--|
| Highest | Postfix | ++, --, ., ?., ? |
| | Prefix | -, +, ++, --, !, labelDefinition |
| | Type RHS | :, as, as? |
| | Multiplicative | *, /, % |
| | Additive | +, - |
| | Range | .. |
| | Infix function | SimpleName |
| | Elvis | ?: |
| | Named checks | in, !in, is, !is |
| | Comparison | <, >, <=, >= |
| | Equality | ==, \!== |
| | Conjunction | && |
| | Disjunction | |
| | Assignment | =, +=, -=, *=, /=, %= |
| Lowest | Assignment | =, +=, -=, *=, /=, %= |

Rules

```

expression
(used by for, atomicExpression, longTemplate, whenCondition, functionBody, doWhile, property, script, explicitDelegation,
jump, while, arrayAccess, blockLevelExpression, if, when, valueArguments, functionParameter)
: disjunction (assignmentOperator disjunction)*
;
disjunction
(used by expression)
: conjunction ("||" conjunction)*
;
conjunction
(used by disjunction)
: equalityComparison ("&&" equalityComparison)*
;
equalityComparison
(used by conjunction)
: comparison (equalityOperation comparison)*
;
comparison
(used by equalityComparison)
: namedInfix (comparisonOperation namedInfix)*
;
namedInfix
(used by comparison)
: elvisExpression (inOperation elvisExpression)*
: elvisExpression (isOperation type)?
;
elvisExpression
(used by namedInfix)
: infixFunctionCall ("?:" infixFunctionCall)*
;
infixFunctionCall
(used by elvisExpression)
: rangeExpression (SimpleName rangeExpression)*
;
rangeExpression
(used by infixFunctionCall)
: additiveExpression (".." additiveExpression)*
;
additiveExpression
(used by rangeExpression)
: multiplicativeExpression (additiveOperation multiplicativeExpression)*
;
multiplicativeExpression
(used by additiveExpression)
: typeRHS (multiplicativeOperation typeRHS)*
;
typeRHS
(used by multiplicativeExpression)
: prefixUnaryExpression (typeOperation prefixUnaryExpression)*
;
prefixUnaryExpression
(used by typeRHS)
: prefixUnaryOperation* postfixUnaryExpression
;
postfixUnaryExpression

```

```

(used by prefixUnaryExpression, postfixUnaryOperation)
: atomicExpression postfixUnaryOperation*
: callableReference postfixUnaryOperation*
;
callableReference
(used by postfixUnaryExpression)
: (userType "?"*)? "::" SimpleName typeArguments?
;
atomicExpression
(used by postfixUnaryExpression)
: "(" expression ")"
: literalConstant
: functionLiteral
: "this" labelReference?
: "super" ("<" type ">")? labelReference?
: if
: when
: try
: objectLiteral
: jump
: loop
: collectionLiteral
: SimpleName
;
labelReference
(used by atomicExpression, jump)
: "@" ++ LabelName
;
labelDefinition
(used by prefixUnaryOperation, annotatedLambda)
: LabelName ++ "@"
;
literalConstant
(used by atomicExpression)
: "true" | "false"
: stringTemplate
: NoEscapeString
: IntegerLiteral
: CharacterLiteral
: FloatLiteral
: "null"
;
stringTemplate
(used by literalConstant)
: "\"" stringTemplateElement* "\""
;
stringTemplateElement
(used by stringTemplate)
: RegularStringPart
: ShortTemplateEntryStart (SimpleName | "this")
: EscapeSequence
: longTemplate
;
longTemplate
(used by stringTemplateElement)
: "${" expression "}"
;
declaration
(used by statement)
: function
: property
: class
: typeAlias
: object
;
statement
(used by statements)
: declaration
: blockLevelExpression
;
blockLevelExpression
(used by statement, controlStructureBody)
: annotations ("\\n")+ expression
;
multiplicativeOperation
(used by multiplicativeExpression)
: "*" : "/" : "%"
;
additiveOperation
(used by additiveExpression)
: "+" : "-"
;
inOperation
(used by namedInfix)
: "in" : "!in"
;
typeOperation
(used by typeRHS)
: "as" : "as?" : ":"

```



```

;
isOperation
(used by namedInfix)
: "is" : "!is"
;
comparisonOperation
(used by comparison)
: "<" : ">" : ">=" : "<="
;
equalityOperation
(used by equalityComparison)
: "=" : "=="
;
assignmentOperator
(used by expression)
: "="
: "+=" : "-=" : "*=" : "/=" : "%="
;
prefixUnaryOperation
(used by prefixUnaryExpression)
: "-" : "+"
: "++" : "--"
: "!"
: annotations
: labelDefinition
;
postfixUnaryOperation
(used by postfixUnaryExpression)
: "++" : "--" : "!!"
: callSuffix
: arrayAccess
: memberAccessOperation postfixUnaryExpression
;
callSuffix
(used by constructorInvocation, postfixUnaryOperation)
: typeArguments? valueArguments annotatedLambda
: typeArguments annotatedLambda
;
annotatedLambda
(used by callSuffix)
: ("@" unescapedAnnotation)* labelDefinition? functionLiteral
;
memberAccessOperation
(used by postfixUnaryOperation)
: "." : "?" : "?"
;
typeArguments
(used by callSuffix, callableReference, unescapedAnnotation)
: "<" type { "," } ">"
;
valueArguments
(used by callSuffix, enumEntry, constructorDelegationCall, unescapedAnnotation)
: "(" ((SimpleName "=")? "*" expression) { "," } ")"
;
jump
(used by atomicExpression)
: "throw" expression
: "return" ++ labelReference? expression?
: "continue" ++ labelReference?
: "break" ++ labelReference?
;
functionLiteral
(used by atomicExpression, annotatedLambda)
: "{" statements "}"
: "{" lambdaParameter { "," } "->" statements "}"
;
lambdaParameter
(used by functionLiteral)
: variableDeclarationEntry
: multipleVariableDeclarations (":" type)?
;
statements
(used by block, functionLiteral)
: SEMI* statement { SEMI+ } SEMI*
;
constructorInvocation
(used by delegationSpecifier)
: userType callSuffix
;
arrayAccess
(used by postfixUnaryOperation)
: "[" expression { "," } "]"
;
objectLiteral
(used by atomicExpression)
: "object" (":" delegationSpecifier { "," })? classBody
;
collectionLiteral
(used by atomicExpression)

```

```
: "[" element { "," } ? "]"
;
```

When-expression

See [When-expression](#)

when

(used by [atomicExpression](#))

```
: "when" "(" (" expression ") )? "{"
  whenEntry *
  "}"
;
```

whenEntry

(used by [when](#))

```
: whenCondition { "," } "->" controlStructureBody SEMI
: "else" "->" controlStructureBody SEMI
;
```

whenCondition

(used by [whenEntry](#))

```
: expression
: ("in" | "in" ) expression
: ("is" | "is" ) type
;
```

Modifiers

modifiers

(used by [typeParameter](#), [getter](#), [packageHeader](#), [class](#), [property](#), [object](#), [function](#), [typeAlias](#), [secondaryConstructor](#), [enumEntry](#), [setter](#), [companionObject](#), [primaryConstructor](#), [functionParameter](#))

```
: ( modifier | annotations ) *
;
```

typeModifiers

(used by [type](#))

```
: ( suspendModifier | annotations ) *
;
```

modifier

(used by [modifiers](#))

```
: classModifier
: accessModifier
: varianceAnnotation
: memberModifier
: parameterModifier
: typeParameterModifier
: functionModifier
: propertyModifier
;
```

classModifier

(used by [modifier](#))

```
: "abstract"
: "final"
: "enum"
: "open"
: "annotation"
: "sealed"
: "data"
;
```

memberModifier

(used by [modifier](#))

```
: "override"
: "open"
: "final"
: "abstract"
: "lateinit"
;
```

accessModifier

(used by [modifier](#))

```
: "private"
: "protected"
: "public"
: "internal"
;
```

varianceAnnotation

(used by [modifier](#), [projection](#))

```
: "in"
: "out"
;
```

parameterModifier

(used by [modifier](#))

```
: "noinline"
: "crossinline"
: "vararg"
;
```

typeParameterModifier

(used by [modifier](#))

```
: "reified"
;
```

```

;
functionModifier
(used by modifier)
: "tailrec"
: "operator"
: "infix"
: "inline"
: "external"
: suspendModifier
;
propertyModifier
(used by modifier)
: "const"
;
suspendModifier
(used by typeModifiers, functionModifier)
: "suspend"
;

```

Annotations

```

annotations
(used by catchBlock, prefixUnaryOperation, blockLevelExpression, for, typeModifiers, class, modifiers, typeConstraint)
: (annotation | annotationList)*
;
annotation
(used by annotations)
: "@" (annotationUseSiteTarget ":")? unescapedAnnotation
;
annotationList
(used by annotations)
: "@" (annotationUseSiteTarget ":")? "[" unescapedAnnotation + "]"
;
annotationUseSiteTarget
(used by annotation, annotationList)
: "field"
: "file"
: "property"
: "get"
: "set"
: "receiver"
: "param"
: "setparam"
: "delegate"
;
unescapedAnnotation
(used by annotation, fileAnnotation, annotatedLambda, annotationList)
: SimpleName { "." } typeArguments? valueArguments?
;

```

Lexical structure

```

helper
LongSuffix
(used by IntegerLiteral)
: "L"
;
IntegerLiteral
(used by literalConstant)
: DecimalLiteral LongSuffix?
: HexadecimalLiteral LongSuffix?
: BinaryLiteral LongSuffix?
;
helper
Digit
(used by DecimalLiteral, HexDigit)
: ["0".."9"]
;
DecimalLiteral
(used by IntegerLiteral)
: Digit
: Digit (Digit | "_" )* Digit
;
FloatLiteral
(used by literalConstant)
: <Java double literal>
;
helper
HexDigit
(used by HexadecimalLiteral, UnicodeEscapeSequence)
: Digit | ["A".."F", "a".."f"]
;
HexadecimalLiteral
(used by IntegerLiteral)
: "0" ("x" | "X") HexDigit
: "0" ("x" | "X") HexDigit (HexDigit | "_" )* HexDigit
;
helper

```

BinaryDigit
(used by [BinaryLiteral](#))
: ("0" | "1")
;

BinaryLiteral
(used by [IntegerLiteral](#))
: "0" ("b" | "B") [BinaryDigit](#)
: "0" ("b" | "B") [BinaryDigit](#) ([BinaryDigit](#) | "_") * [BinaryDigit](#)

CharacterLiteral
(used by [literalConstant](#))
: <character as in Java>
;

See [Basic types](#)

NoEscapeString
(used by [literalConstant](#))
: <""""-quoted string>
;

RegularStringPart
(used by [stringTemplateElement](#))
: <any character other than backslash, quote, \$ or newline>
;

ShortTemplateEntryStart
(used by [stringTemplateElement](#))
: "\$"
;

EscapeSequence
(used by [stringTemplateElement](#))
: [UnicodeEscapeSequence](#) | [RegularEscapeSequence](#)
;

UnicodeEscapeSequence
(used by [EscapeSequence](#))
: "\u" [HexDigit](#) { 4 }
;

RegularEscapeSequence
(used by [EscapeSequence](#))
: "\" <any character other than newline>
;

See [String templates](#)

SEMI
(used by [whenEntry](#), [if](#), [statements](#), [packageHeader](#), [property](#), [import](#))
: <semicolon or newline>
;

SimpleName
(used by [typeParameter](#), [catchBlock](#), [simpleUserType](#), [atomicExpression](#), [LabelName](#), [packageHeader](#), [class](#), [object](#), [infixFunctionCall](#), [function](#), [typeAlias](#), [parameter](#), [callableReference](#), [variableDeclarationEntry](#), [stringTemplateElement](#), [enumEntry](#), [setter](#), [import](#), [companionObject](#), [valueArguments](#), [unescapedAnnotation](#), [typeConstraint](#))
: <java identifier>
: "\" <java identifier> \""
;

See [Java interoperability](#)

LabelName
(used by [labelReference](#), [labelDefinition](#))
: [SimpleName](#)
;

See [Returns and jumps](#)

Compatibility

This page describes compatibility guarantees for different versions and subsystems of Kotlin.

Compatibility glossary

Compatibility means answering the question: for given two versions of Kotlin (for example, 1.2 and 1.1.5), can the code written for one version be used with another version? The list below explains the compatibility modes of different pairs of versions. Note that a version is older if it has a smaller version number (even if it was released later than the version with a larger version number). We use OV for "Older Version", and NV for "Newer Version".

— **C** - Full **C**ompatibility

- Language
 - no syntax changes (*modulo bugs**)
 - new warnings/hints may be added or removed
- API (`kotlin-stdlib-*` , `kotlin-reflect-*`)
 - no API changes
 - deprecations with level `WARNING` may be added/removed
- Binaries (ABI)
 - runtime: binaries can be used interchangeably
 - compilation: binaries can be used interchangeably

— **BCLA** - **B**ackward **C**ompatibility for the **L**anguage and **A**PI

- Language
 - syntax deprecated in OV may be removed in NV
 - other than that, all code compilable in OV is compilable by in NV (*modulo bugs**)
 - new syntax may be added in NV
 - some restrictions of OV may be lifted in NV
 - new warnings/hints may be added or removed
- API (`kotlin-stdlib-*` , `kotlin-reflect-*`)
 - new APIs may be added
 - deprecations with level `WARNING` may be added/removed
 - deprecations with level `WARNING` may be elevated to level `ERROR` or `HIDDEN` in NV

— **BCB** - **B**ackward **C**ompatibility for **B**inaries

- Binaries (ABI)
 - runtime: NV-binaries can be used everywhere where OV binaries worked
 - NV compiler: code compilable against OV binaries is compilable against NV binaries
 - OV compiler may not accept NV binaries (e.g. those that exhibit newer language features or APIs)

— **BC** - Full **B**ackward **C**ompatibility

- BC = BCLA & BCB

— **EXP** - Experimental feature

- see [below](#)

— **NO** - No compatibility guarantees

- we'll do our best to offer smooth migration, but can give no guarantees
- migration is planned individually for every incompatible subsystem

* No changes *modulo bugs* means that if an important bug is found (e.g. in the compiler diagnostics or elsewhere), a fix for it may introduce a breaking change, but we are always very careful with such changes.

Compatibility guarantees for Kotlin releases

Kotlin for JVM:

- patch version updates (e.g. 1.1.X) are fully compatible;
- minor version updates (e.g. 1.X) are backwards compatible.

| Kotlin | 1.0 | 1.0.X | 1.1 | 1.1.X | ... | 2.0 |
|--------|-----|-------|-----|-------|-----|-----|
| 1.0 | - | C | BC | BC | ... | ? |
| 1.0.X | C | - | BC | BC | ... | ? |
| 1.1 | BC | BC | - | C | ... | ? |
| 1.1.X | BC | BC | C | - | ... | ? |
| ... | ... | ... | ... | ... | ... | ... |
| 2.0 | ? | ? | ? | ? | ... | - |

Kotlin for JS: starting with Kotlin 1.1, both patch and minor version updates provide backward compatibility for the language and API (BCLA), but no BCB.

| Kotlin | 1.0.X | 1.1 | 1.1.X | ... | 2.0 |
|--------|-------|------|-------|-----|-----|
| 1.0.X | - | EXP | EXP | ... | EXP |
| 1.1 | EXP | - | BCLA | ... | ? |
| 1.1.X | EXP | BCLA | - | ... | ? |
| ... | ... | ... | ... | ... | ... |
| 2.0 | EXP | ? | ? | ... | - |

Kotlin Scripts: both patch and minor version updates provide backward compatibility for the language and API (BCLA), but no BCB.

Compatibility across platforms

Kotlin is available for several platforms (JVM/Android, JavaScript and the upcoming native platforms). Every platform has its own peculiarities (e.g. JavaScript has no proper integers), so we have to adapt the language accordingly. Our goal is to provide reasonable code portability without sacrificing too much.

Every platform may feature specific language extensions (such as platform types for JVM and dynamic types for JavaScript) or restrictions (e.g. some overloading-related restrictions on the JVM), but the core language remains the same.

The Standard Library provides a core API available on all platforms, and we strive to make these APIs work in the same way on every platform. Along with these, the Standard Library provides platform-specific extensions (e.g. `java.io` for JVM, or `js()` for JavaScript), plus some APIs that can be called uniformly, but work differently (such as regular expressions for JVM and JavaScript).

Experimental features

Experimental features, such as coroutines in Kotlin 1.1, have exemption from the compatibility modes listed above. Such features require an opt-in to use without compiler warning. Experimental features are at least backwards compatible for patch version updates, but we do not guarantee any compatibility for minor version updates (migration aids will be provided where possible).

| Kotlin | 1.1 | 1.1.X | 1.2 | 1.2.X |
|--------|-----|-------|-----|-------|
| 1.1 | - | BC | NO | NO |
| 1.1.X | BC | - | NO | NO |
| 1.2 | NO | NO | - | BC |
| 1.2.X | NO | NO | BC | - |

EAP builds

We publish Early Access Preview (EAP) builds to special channels where early adopters from the community can try them out and give us feedback. Such builds provide no compatibility guarantees whatsoever (although we do our best to keep them reasonably compatible with releases and with each other). Quality expectations for such builds are also much lower than for releases. Beta builds also fall under this category.

IMPORTANT NOTE: all binaries compiled by EAP builds for 1.X (e.g. 1.1.0-eap-X) are **rejected by release builds of the compiler**. We don't want any code compiled by pre-release versions to be kept around after a stable version is released. This does not concern EAPs of patch versions (e.g. 1.1.3-eap-X), these EAPs produce builds with stable ABI.

Compatibility modes

When a big team is migrating onto a new version, it may appear in a "inconsistent state" at some point, when some developers have already updated, and others haven't. To prevent the former from writing and committing code that others may not be able to compile, we provide the following command line switches (also available in the IDE and [Gradle/Maven](#)):

- `-language-version X.Y` - compatibility mode for Kotlin language version X.Y, reports errors for all language features that came out later.
- `-api-version X.Y` - compatibility mode for Kotlin API version X.Y, reports errors for all code using newer APIs from the Kotlin Standard Library (including the code generated by the compiler).

Binary compatibility warnings

If you use the NV Kotlin compiler and have the OV standard library or the OV reflection library in the classpath, it can be a sign that the project is misconfigured. To prevent unexpected problems during compilation or at runtime, we suggest either updating the dependencies to NV, or specifying the API version / language version arguments explicitly. Otherwise the compiler detects that something can go wrong and reports a warning.

For example, if OV = 1.0 and NV = 1.1, you can observe one of the following warnings:

Runtime JAR files in the classpath have the version 1.0, which is older than the API version 1.1. Consider using the runtime of version 1.1, or pass `'-api-version 1.0'` explicitly to restrict the available APIs to the runtime of version 1.0.

This means that you're using the Kotlin compiler 1.1 against the standard or reflection library of version 1.0. This can be handled in different ways:

- If you intend to use the APIs from the 1.1 Standard Library, or language features that depend on those APIs, you should upgrade the dependency to the version 1.1.
- If you want to keep your code compatible with the 1.0 standard library, you can pass `-api-version 1.0`.
- If you've just upgraded to Kotlin 1.1 but can not use new language features yet (e.g. because some of your teammates may not have upgraded), you can pass `-language-version 1.0`, which will restrict all APIs and language features to 1.0.

Runtime JAR files in the classpath should have the same version. These files were found in the classpath:

```
kotlin-reflect.jar (version 1.0)
kotlin-stdlib.jar (version 1.1)
```

Consider providing an explicit dependency on `kotlin-reflect 1.1` to prevent strange errors

Some runtime JAR files in the classpath have an incompatible version. Consider removing them from the classpath

This means that you have a dependency on libraries of different versions, for example the 1.1 standard library and the 1.0 reflection library. To prevent subtle errors at runtime, we recommend you to use the same version of all Kotlin libraries. In this case, consider adding an explicit dependency on the 1.1 reflection library.

Some JAR files in the classpath have the Kotlin Runtime library bundled into them.

This may cause difficult to debug problems if there's a different version of the Kotlin Runtime library in the classpath.

Consider removing these libraries from the classpath

This means that there's a library in the classpath which does not depend on the Kotlin standard library as a Gradle/Maven dependency, but is distributed in the same artifact with it (i.e. has it *bundled*). Such a library may cause issues because standard build tools do not consider it an instance of the Kotlin standard library, thus it's not subject to the dependency version resolution mechanisms, and you can end up with several versions of the same library in the classpath. Consider contacting the authors of such a library and suggesting to use the Gradle/Maven dependency instead.

Java Interop

Calling Java code from Kotlin

Kotlin is designed with Java Interoperability in mind. Existing Java code can be called from Kotlin in a natural way, and Kotlin code can be used from Java rather smoothly as well. In this section we describe some details about calling Java code from Kotlin.

Pretty much all Java code can be used without any issues:

```
import java.util.*

fun demo(source: List<Int>) {
    val list = ArrayList<Int>()
    // 'for'-loops work for Java collections:
    for (item in source) {
        list.add(item)
    }
    // Operator conventions work as well:
    for (i in 0..source.size - 1) {
        list[i] = source[i] // get and set are called
    }
}
```

Getters and Setters

Methods that follow the Java conventions for getters and setters (no-argument methods with names starting with `get` and single-argument methods with names starting with `set`) are represented as properties in Kotlin. `Boolean` accessor methods (where the name of the getter starts with `is` and the name of the setter starts with `set`) are represented as properties which have the same name as the getter method.

For example:

```
import java.util.Calendar

fun calendarDemo() {
    val calendar = Calendar.getInstance()
    if (calendar.firstDayOfWeek == Calendar.SUNDAY) { // call getFirstDayOfWeek()
        calendar.firstDayOfWeek = Calendar.MONDAY // call setFirstDayOfWeek()
    }
    if (!calendar.isLenient) { // call isLenient()
        calendar.isLenient = true // call setLenient()
    }
}
```

Note that, if the Java class only has a setter, it will not be visible as a property in Kotlin, because Kotlin does not support set-only properties at this time.

Methods returning void

If a Java method returns void, it will return `Unit` when called from Kotlin. If, by any chance, someone uses that return value, it will be assigned at the call site by the Kotlin compiler, since the value itself is known in advance (being `Unit`).

Escaping for Java identifiers that are keywords in Kotlin

Some of the Kotlin keywords are valid identifiers in Java: `in`, `object`, `is`, etc. If a Java library uses a Kotlin keyword for a method, you can still call the method escaping it with the backtick (```) character:

```
foo.`is`(bar)
```

Null-Safety and Platform Types

Any reference in Java may be `null`, which makes Kotlin's requirements of strict null-safety impractical for objects coming from Java. Types of Java declarations are treated specially in Kotlin and called *platform types*. Null-checks are relaxed for such types, so that safety guarantees for them are the same as in Java (see more [below](#)).

Consider the following examples:

```
val list = ArrayList<String>() // non-null (constructor result)
list.add("Item")
val size = list.size // non-null (primitive int)
val item = list[0] // platform type inferred (ordinary Java object)
```

When we call methods on variables of platform types, Kotlin does not issue nullability errors at compile time, but the call may fail at runtime, because of a null-pointer exception or an assertion that Kotlin generates to prevent nulls from propagating:

```
item.substring(1) // allowed, may throw an exception if item == null
```

Platform types are *non-denotable*, meaning that one can not write them down explicitly in the language. When a platform value is assigned to a Kotlin variable, we can rely on type inference (the variable will have an inferred platform type then, as `item` has in the example above), or we can choose the type that we expect (both nullable and non-null types are allowed):

```
val nullable: String? = item // allowed, always works
val notNull: String = item // allowed, may fail at runtime
```

If we choose a non-null type, the compiler will emit an assertion upon assignment. This prevents Kotlin's non-null variables from holding nulls. Assertions are also emitted when we pass platform values to Kotlin functions expecting non-null values etc. Overall, the compiler does its best to prevent nulls from propagating far through the program (although sometimes this is impossible to eliminate entirely, because of generics).

Notation for Platform Types

As mentioned above, platform types cannot be mentioned explicitly in the program, so there's no syntax for them in the language. Nevertheless, the compiler and IDE need to display them sometimes (in error messages, parameter info etc), so we have a mnemonic notation for them:

- `T!` means "`T` or `T?`",
- `(Mutable)Collection<T>!` means "Java collection of `T` may be mutable or not, may be nullable or not",
- `Array<(out) T>!` means "Java array of `T` (or a subtype of `T`), nullable or not"

Nullability annotations

Java types which have nullability annotations are represented not as platform types, but as actual nullable or non-null Kotlin types. The compiler supports several flavors of nullability annotations, including:

- [JetBrains](#) (`@Nullable` and `@NotNull` from the `org.jetbrains.annotations` package)
- [Android](#) (`com.android.annotations` and `android.support.annotations`)
- [JSR-305](#) (`javax.annotation`, more details below)
- [FindBugs](#) (`edu.umd.cs.findbugs.annotations`)
- [Eclipse](#) (`org.eclipse.jdt.annotation`)
- [Lombok](#) (`lombok.NonNull`).

You can find the full list in the [Kotlin compiler source code](#).

Annotating type parameters

It is possible to annotate type arguments of generic types to provide nullability information for them as well. For example, consider these annotations on a Java declaration:

```
@NotNull
Set<@NotNull String> toSet(@NotNull Collection<@NotNull String> elements) { ... }
```

It leads to the following signature seen in Kotlin:

```
fun toSet(elements: (Mutable)Collection<String>) : (Mutable)Set<String> { ... }
```

Note the `@NotNull` annotations on `String` type arguments. Without them, we get platform types in the type arguments:

```
fun toSet(elements: (Mutable)Collection<String!>) : (Mutable)Set<String!> { ... }
```

Annotating type arguments works with Java 8 target or higher and requires the nullability annotations to support the `TYPE_USE` target (`org.jetbrains.annotations` supports this in version 15 and above).

JSR-305 Support

The `@Nonnull` annotation defined in [JSR-305](#) is supported for denoting nullability of Java types.

If the `@Nonnull(when = ...)` value is `When.ALWAYS`, the annotated type is treated as non-null; `When.MAYBE` and `When.NEVER` denote a nullable type; and `When.UNKNOWN` forces the type to be [platform one](#).

A library can be compiled against the JSR-305 annotations, but there's no need to make the annotations artifact (e.g. `jsr305.jar`) a compile dependency for the library consumers. The Kotlin compiler can read the JSR-305 annotations from a library without the annotations present on the classpath.

Since Kotlin 1.1.50, [custom nullability qualifiers \(KEEP-79\)](#) are also supported (see below).

Type qualifier nicknames (since 1.1.50)

If an annotation type is annotated with both [@TypeQualifierNickname](#) and JSR-305 `@Nonnull` (or its another nickname, such as `@CheckForNull`), then the annotation type is itself used for retrieving precise nullability and has the same meaning as that nullability annotation:

```
@TypeQualifierNickname
@Nonnull(when = When.ALWAYS)
@Retention(RetentionPolicy.RUNTIME)
public @interface MyNonnull {
}

@TypeQualifierNickname
@CheckForNull // a nickname to another type qualifier nickname
@Retention(RetentionPolicy.RUNTIME)
public @interface MyNullable {
}

interface A {
    @MyNullable String foo(@MyNonnull String x);
    // in Kotlin (strict mode): `fun foo(x: String): String?`

    String bar(List<@MyNonnull String> x);
    // in Kotlin (strict mode): `fun bar(x: List<String!>): String!`
}
```

Type qualifier defaults (since 1.1.50)

[@TypeQualifierDefault](#) allows introducing annotations that, when being applied, define the default nullability within the scope of the annotated element.

Such annotation type should itself be annotated with both `@Nonnull` (or its nickname) and `@TypeQualifierDefault(...)` with one or more `ElementType` values:

- `ElementType.METHOD` for return types of methods;
- `ElementType.PARAMETER` for value parameters;
- `ElementType.FIELD` for fields; and
- `ElementType.TYPE_USE` (since 1.1.60) for any type including type arguments, upper bounds of type parameters and wildcard types.

The default nullability is used when a type itself is not annotated by a nullability annotation, and the default is determined by the innermost enclosing element annotated with a type qualifier default annotation with the `ElementType` matching the type usage.

```
@NonNull
@TypeQualifierDefault({ElementType.METHOD, ElementType.PARAMETER})
public @interface NonNullApi {
}

@NonNull(when = When.MAYBE)
@TypeQualifierDefault({ElementType.METHOD, ElementType.PARAMETER, ElementType.TYPE_USE})
public @interface NullableApi {
}

@NullableApi
interface A {
    String foo(String x); // fun foo(x: String?): String?

    @NotNullApi // overriding default from the interface
    String bar(String x, @Nullable String y); // fun bar(x: String, y: String?): String

    // The List<String> type argument is seen as nullable because of `@NullableApi`
    // having the `TYPE_USE` element type:
    String baz(List<String> x); // fun baz(List<String?>?): String?

    // The type of `x` parameter remains platform because there's an explicit
    // UNKNOWN-marked nullability annotation:
    String qux(@NonNull(when = When.UNKNOWN) String x); // fun baz(x: String!): String?
}
```

Note: the types in this example only take place with the strict mode enabled, otherwise, the platform types remain. See the [@UnderMigration annotation](#) and [Compiler configuration](#) sections.

Package-level default nullability is also supported:

```
// FILE: test/package-info.java
@NonNullApi // declaring all types in package 'test' as non-nullable by default
package test;
```

`@UnderMigration` annotation (since 1.1.60)

The `@UnderMigration` annotation (provided in a separate artifact `kotlin-annotations-jvm`) can be used by library maintainers to define the migration status for the nullability type qualifiers.

The status value in `@UnderMigration(status = ...)` specifies how the compiler treats inappropriate usages of the annotated types in Kotlin (e.g. using a `@MyNullable`-annotated type value as non-null):

- `MigrationStatus.STRICT` makes annotation work as any plain nullability annotation, i.e. report errors for the inappropriate usages and affect the types in the annotated declarations as they are seen in Kotlin;
- with `MigrationStatus.WARN`, the inappropriate usages are reported as compilation warnings instead of errors, but the types in the annotated declarations remain platform; and
- `MigrationStatus.IGNORE` makes the compiler ignore the nullability annotation completely.

A library maintainer can add `@UnderMigration` status to both type qualifier nicknames and type qualifier defaults:

```

@NonNull(when = When.ALWAYS)
@TypeQualifierDefault({ElementType.METHOD, ElementType.PARAMETER})
@UnderMigration(status = MigrationStatus.WARN)
public @interface NonNullApi {
}

// The types in the class are non-null, but only warnings are reported
// because `@NonNullApi` is annotated `@UnderMigration(status = MigrationStatus.WARN)`
@NonNullApi
public class Test {}

```

Note: the migration status of a nullability annotation is not inherited by its type qualifier nicknames but is applied to its usages in default type qualifiers.

If a default type qualifier uses a type qualifier nickname and they are both `@UnderMigration`, the status from the default type qualifier is used.

Compiler configuration

The JSR-305 checks can be configured by adding the `-Xjsr305` compiler flag with the following options (and their combination):

- `-Xjsr305={strict|warn|ignore}` to set up the behavior for non- `@UnderMigration` annotations. Custom nullability qualifiers, especially `@TypeQualifierDefault`, are already spread among many well-known libraries, and users may need to migrate smoothly when updating to the Kotlin version containing JSR-305 support. Since Kotlin 1.1.60, this flag only affects non- `@UnderMigration` annotations.
- `-Xjsr305=under-migration:{strict|warn|ignore}` (since 1.1.60) to override the behavior for the `@UnderMigration` annotations. Users may have different view on the migration status for the libraries: they may want to have errors while the official migration status is `WARN`, or vice versa, they may wish to postpone errors reporting for some until they complete their migration.
- `-Xjsr305=@<fq.name>:{strict|warn|ignore}` (since 1.1.60) to override the behavior for a single annotation, where `<fq.name>` is the fully qualified class name of the annotation. May appear several times for different annotations. This is useful for managing the migration state for a particular library.

The `strict`, `warn` and `ignore` values have the same meaning as those of `MigrationStatus`, and only the `strict` mode affects the types in the annotated declarations as they are seen in Kotlin.

Note: the built-in JSR-305 annotations `@NonNull`, `@Nullable` and `@CheckForNull` are always enabled and affect the types of the annotated declarations in Kotlin, regardless of compiler configuration with the `-Xjsr305` flag.

For example, adding `-Xjsr305=ignore -Xjsr305=under-migration:ignore -Xjsr305=@org.library.MyNullable:warn` to the compiler arguments makes the compiler generate warnings for inappropriate usages of types annotated by `@org.library.MyNullable` and ignore all other JSR-305 annotations.

For kotlin versions 1.1.50+/1.2, the default behavior is the same to `-Xjsr305=warn`. The `strict` value should be considered experimental (more checks may be added to it in the future).

Mapped types

Kotlin treats some Java types specially. Such types are not loaded from Java "as is", but are *mapped* to corresponding Kotlin types. The mapping only matters at compile time, the runtime representation remains unchanged. Java's primitive types are mapped to corresponding Kotlin types (keeping [platform types](#) in mind):

| Java type | Kotlin type |
|-----------|--------------|
| byte | kotlin.Byte |
| short | kotlin.Short |
| int | kotlin.Int |
| long | kotlin.Long |
| char | kotlin.Char |
| float | kotlin.Float |

| Java type | Kotlin type |
|-----------|----------------|
| boolean | kotlin.Boolean |

Some non-primitive built-in classes are also mapped:

| Java type | Kotlin type |
|------------------------|----------------------|
| java.lang.Object | kotlin.Any! |
| java.lang.Cloneable | kotlin.Cloneable! |
| java.lang.Comparable | kotlin.Comparable! |
| java.lang.Enum | kotlin.Enum! |
| java.lang.Annotation | kotlin.Annotation! |
| java.lang.Deprecated | kotlin.Deprecated! |
| java.lang.CharSequence | kotlin.CharSequence! |
| java.lang.String | kotlin.String! |
| java.lang.Number | kotlin.Number! |
| java.lang.Throwable | kotlin.Throwable! |

Java's boxed primitive types are mapped to nullable Kotlin types:

| Java type | Kotlin type |
|---------------------|-----------------|
| java.lang.Byte | kotlin.Byte? |
| java.lang.Short | kotlin.Short? |
| java.lang.Integer | kotlin.Int? |
| java.lang.Long | kotlin.Long? |
| java.lang.Character | kotlin.Char? |
| java.lang.Float | kotlin.Float? |
| java.lang.Double | kotlin.Double? |
| java.lang.Boolean | kotlin.Boolean? |

Note that a boxed primitive type used as a type parameter is mapped to a platform type: for example, `List<java.lang.Integer>` becomes a `List<Int!>` in Kotlin.

Collection types may be read-only or mutable in Kotlin, so Java's collections are mapped as follows (all Kotlin types in this table reside in the package `kotlin.collections`):

| Java type | Kotlin read-only type | Kotlin mutable type | Loaded platform type |
|-----------------|-----------------------|-------------------------------|------------------------------------|
| Iterator<T> | Iterator<T> | MutableIterator<T> | (Mutable)Iterator<T>! |
| Iterable<T> | Iterable<T> | MutableIterable<T> | (Mutable)Iterable<T>! |
| Collection<T> | Collection<T> | MutableCollection<T> | (Mutable)Collection<T>! |
| Set<T> | Set<T> | MutableSet<T> | (Mutable)Set<T>! |
| List<T> | List<T> | MutableList<T> | (Mutable)List<T>! |
| ListIterator<T> | ListIterator<T> | MutableListIterator<T> | (Mutable)ListIterator<T>! |
| Map<K, V> | Map<K, V> | MutableMap<K, V> | (Mutable)Map<K, V>! |
| Map.Entry<K, V> | Map.Entry<K, V> | MutableMap.MutableEntry<K, V> | (Mutable)Map.(Mutable)Entry<K, V>! |

Java's arrays are mapped as mentioned [below](#):

| Java type | Kotlin type |
|-----------|-----------------------------|
| int[] | kotlin.IntArray! |
| String[] | kotlin.Array<(out) String>! |

Note: the static members of these Java types are not directly accessible on the [companion objects](#) of the Kotlin types. To call them, use the full qualified names of the Java types, e.g. `java.lang.Integer.toHexString(foo)`.

Java generics in Kotlin

Kotlin's generics are a little different from Java's (see [Generics](#)). When importing Java types to Kotlin we perform some conversions:

- Java's wildcards are converted into type projections,
 - `Foo<? extends Bar>` becomes `Foo<out Bar!>!`,
 - `Foo<? super Bar>` becomes `Foo<in Bar!>!`;
- Java's raw types are converted into star projections,
 - `List` becomes `List<*>!`, i.e. `List<out Any?>!`.

Like Java's, Kotlin's generics are not retained at runtime, i.e. objects do not carry information about actual type arguments passed to their constructors, i.e. `ArrayList<Integer>()` is indistinguishable from `ArrayList<Character>()`. This makes it impossible to perform `is`-checks that take generics into account. Kotlin only allows `is`-checks for star-projected generic types:

```
if (a is List<Int>) // Error: cannot check if it is really a List of Ints
// but
if (a is List<*>) // OK: no guarantees about the contents of the list
```

Java Arrays

Arrays in Kotlin are invariant, unlike Java. This means that Kotlin does not let us assign an `Array<String>` to an `Array<Any>`, which prevents a possible runtime failure. Passing an array of a subclass as an array of superclass to a Kotlin method is also prohibited, but for Java methods this is allowed (through [platform types](#) of the form `Array<(out) String>!`).

Arrays are used with primitive datatypes on the Java platform to avoid the cost of boxing/unboxing operations. As Kotlin hides those implementation details, a workaround is required to interface with Java code. There are specialized classes for every type of primitive array (`IntArray`, `DoubleArray`, `CharArray`, and so on) to handle this case. They are not related to the `Array` class and are compiled down to Java's primitive arrays for maximum performance.

Suppose there is a Java method that accepts an int array of indices:

```
public class JavaArrayExample {
    public void removeIndices(int[] indices) {
        // code here...
    }
}
```

To pass an array of primitive values you can do the following in Kotlin:

```
val javaObj = JavaArrayExample()
val array = intArrayOf(0, 1, 2, 3)
javaObj.removeIndices(array) // passes int[] to method
```

When compiling to JVM byte codes, the compiler optimizes access to arrays so that there's no overhead introduced:

```
val array = arrayOf(1, 2, 3, 4)
array[1] = array[1] * 2 // no actual calls to get() and set() generated
for (x in array) { // no iterator created
    print(x)
}
```

Even when we navigate with an index, it does not introduce any overhead:

```
for (i in array.indices) { // no iterator created
    array[i] += 2
}
```

Finally, `in`-checks have no overhead either:

```
if (i in array.indices) { // same as (i >= 0 && i < array.size)
    print(array[i])
}
```

Java Varargs

Java classes sometimes use a method declaration for the indices with a variable number of arguments (varargs):

```
public class JavaArrayExample {

    public void removeIndicesVarArg(int... indices) {
        // code here...
    }
}
```

In that case you need to use the spread operator `*` to pass the `IntArray`:

```
val javaObj = JavaArrayExample()
val array = intArrayOf(0, 1, 2, 3)
javaObj.removeIndicesVarArg(*array)
```

It's currently not possible to pass `null` to a method that is declared as varargs.

Operators

Since Java has no way of marking methods for which it makes sense to use the operator syntax, Kotlin allows using any Java methods with the right name and signature as operator overloads and other conventions (`invoke()` etc.) Calling Java methods using the infix call syntax is not allowed.

Checked Exceptions

In Kotlin, all exceptions are unchecked, meaning that the compiler does not force you to catch any of them. So, when you call a Java method that declares a checked exception, Kotlin does not force you to do anything:

```
fun render(list: List<*>, to: Appendable) {
    for (item in list) {
        to.append(item.toString()) // Java would require us to catch IOException here
    }
}
```

Object Methods

When Java types are imported into Kotlin, all the references of the type `java.lang.Object` are turned into `Any`. Since `Any` is not platform-specific, it only declares `toString()`, `hashCode()` and `equals()` as its members, so to make other members of `java.lang.Object` available, Kotlin uses [extension functions](#).

wait()/notify()

[Effective Java, 3rd Edition](#) Item 81 kindly suggests to prefer concurrency utilities to `wait()` and `notify()`. Thus, these methods are not available on references of type `Any`. If you really need to call them, you can cast to `java.lang.Object`:

```
(foo as java.lang.Object).wait()
```

getClass()

To retrieve the Java class of an object, use the `java` extension property on a [class reference](#):

```
val fooClass = foo::class.java
```

The code above uses a [bound class reference](#), which is supported since Kotlin 1.1. You can also use the `javaClass` extension property:

```
val fooClass = foo.javaClass
```

clone()

To override `clone()`, your class needs to extend `kotlin.Cloneable`:

```
class Example : Cloneable {
    override fun clone(): Any { ... }
}
```

Do not forget about [Effective Java, 3rd Edition](#), Item 13: *Override clone judiciously*.

finalize()

To override `finalize()`, all you need to do is simply declare it, without using the `override` keyword:

```
class C {
    protected fun finalize() {
        // finalization logic
    }
}
```

According to Java's rules, `finalize()` must not be `private`.

Inheritance from Java classes

At most one Java class (and as many Java interfaces as you like) can be a supertype for a class in Kotlin.

Accessing static members

Static members of Java classes form "companion objects" for these classes. We cannot pass such a "companion object" around as a value, but can access the members explicitly, for example:

```
if (Character.isLetter(a)) { ... }
```

To access static members of a Java type that is [mapped](#) to a Kotlin type, use the full qualified name of the Java type:

```
java.lang.Integer.bitCount(foo) .
```

Java Reflection

Java reflection works on Kotlin classes and vice versa. As mentioned above, you can use `instance::class.java`, `ClassName::class.java` or `instance.javaClass` to enter Java reflection through `java.lang.Class`.

Other supported cases include acquiring a Java getter/setter method or a backing field for a Kotlin property, a `KProperty` for a Java field, a Java method or constructor for a `KFunction` and vice versa.

SAM Conversions

Just like Java 8, Kotlin supports SAM conversions. This means that Kotlin function literals can be automatically converted into implementations of Java interfaces with a single non-default method, as long as the parameter types of the interface method match the parameter types of the Kotlin function.

You can use this for creating instances of SAM interfaces:

```
val runnable = Runnable { println("This runs in a runnable") }
```

...and in method calls:

```
val executor = ThreadPoolExecutor()
// Java signature: void execute(Runnable command)
executor.execute { println("This runs in a thread pool") }
```

If the Java class has multiple methods taking functional interfaces, you can choose the one you need to call by using an adapter function that converts a lambda to a specific SAM type. Those adapter functions are also generated by the compiler when needed:

```
executor.execute(Runnable { println("This runs in a thread pool") })
```

Note that SAM conversions only work for interfaces, not for abstract classes, even if those also have just a single abstract method.

Also note that this feature works only for Java interop; since Kotlin has proper function types, automatic conversion of functions into implementations of Kotlin interfaces is unnecessary and therefore unsupported.

Using JNI with Kotlin

To declare a function that is implemented in native (C or C++) code, you need to mark it with the `external` modifier:

```
external fun foo(x: Int): Double
```

The rest of the procedure works in exactly the same way as in Java.

Calling Kotlin from Java

Kotlin code can be called from Java easily.

Properties

A Kotlin property is compiled to the following Java elements:

- A getter method, with the name calculated by prepending the `get` prefix;
- A setter method, with the name calculated by prepending the `set` prefix (only for `var` properties);
- A private field, with the same name as the property name (only for properties with backing fields).

For example, `var firstName: String` gets compiled to the following Java declarations:

```
private String firstName;

public String getFirstName() {
    return firstName;
}

public void setFirstName(String firstName) {
    this.firstName = firstName;
}
```

If the name of the property starts with `is`, a different name mapping rule is used: the name of the getter will be the same as the property name, and the name of the setter will be obtained by replacing `is` with `set`. For example, for a property `isOpen`, the getter will be called `isOpen()` and the setter will be called `setOpen()`. This rule applies for properties of any type, not just `Boolean`.

Package-Level Functions

All the functions and properties declared in a file `example.kt` inside a package `org.foo.bar`, including extension functions, are compiled into static methods of a Java class named `org.foo.bar.ExampleKt`.

```
// example.kt
package demo

class Foo

fun bar() { ... }

// Java
new demo.Foo();
demo.ExampleKt.bar();
```

The name of the generated Java class can be changed using the `@JvmName` annotation:

```
@file:JvmName("DemoUtils")

package demo

class Foo

fun bar() { ... }

// Java
new demo.Foo();
demo.DemoUtils.bar();
```

Having multiple files which have the same generated Java class name (the same package and the same name or the same `@JvmName` annotation) is normally an error. However, the compiler has the ability to generate a single Java facade class which has the specified name and contains all the declarations from all the files which have that name. To enable the generation of such a facade, use the `@JvmMultifileClass` annotation in all of the files.

```

// oldutils.kt
@file:JvmName("Utils")
@file:JvmMultifileClass

package demo

fun foo() { ... }

// newutils.kt
@file:JvmName("Utils")
@file:JvmMultifileClass

package demo

fun bar() { ... }

// Java
demo.Utils.foo();
demo.Utils.bar();

```

Instance Fields

If you need to expose a Kotlin property as a field in Java, you need to annotate it with the `@JvmField` annotation. The field will have the same visibility as the underlying property. You can annotate a property with `@JvmField` if it has a backing field, is not private, does not have `open`, `override` or `const` modifiers, and is not a delegated property.

```

class C(id: String) {
    @JvmField val ID = id
}

// Java
class JavaClient {
    public String getID(C c) {
        return c.ID;
    }
}

```

[Late-Initialized](#) properties are also exposed as fields. The visibility of the field will be the same as the visibility of `lateinit` property setter.

Static Fields

Kotlin properties declared in a named object or a companion object will have static backing fields either in that named object or in the class containing the companion object.

Usually these fields are private but they can be exposed in one of the following ways:

- `@JvmField` annotation;
- `lateinit` modifier;
- `const` modifier.

Annotating such a property with `@JvmField` makes it a static field with the same visibility as the property itself.

```

class Key(val value: Int) {
    companion object {
        @JvmField
        val COMPARATOR: Comparator<Key> = compareBy<Key> { it.value }
    }
}

// Java
Key.COMPARATOR.compare(key1, key2);
// public static final field in Key class

```

A [late-initialized](#) property in an object or a companion object has a static backing field with the same visibility as the property setter.

```
object Singleton {
    lateinit var provider: Provider
}

// Java
Singleton.provider = new Provider();
// public static non-final field in Singleton class
```

Properties annotated with `const` (in classes as well as at the top level) are turned into static fields in Java:

```
// file example.kt

object Obj {
    const val CONST = 1
}

class C {
    companion object {
        const val VERSION = 9
    }
}

const val MAX = 239
```

In Java:

```
int c = Obj.CONST;
int d = ExampleKt.MAX;
int v = C.VERSION;
```

Static Methods

As mentioned above, Kotlin represents package-level functions as static methods. Kotlin can also generate static methods for functions defined in named objects or companion objects if you annotate those functions as `@JvmStatic`. If you use this annotation, the compiler will generate both a static method in the enclosing class of the object and an instance method in the object itself. For example:

```
class C {
    companion object {
        @JvmStatic fun foo() {}
        fun bar() {}
    }
}
```

Now, `foo()` is static in Java, while `bar()` is not:

```
C.foo(); // works fine
C.bar(); // error: not a static method
C.Companion.foo(); // instance method remains
C.Companion.bar(); // the only way it works
```

Same for named objects:

```
object Obj {
    @JvmStatic fun foo() {}
    fun bar() {}
}
```

In Java:

```
Obj.foo(); // works fine
Obj.bar(); // error
Obj.INSTANCE.bar(); // works, a call through the singleton instance
Obj.INSTANCE.foo(); // works too
```

`@JvmStatic` annotation can also be applied on a property of an object or a companion object making its getter and setter methods be static members in that object or the class containing the companion object.

Visibility

The Kotlin visibilities are mapped to Java in the following way:

- `private` members are compiled to `private` members;
- `private` top-level declarations are compiled to package-local declarations;
- `protected` remains `protected` (note that Java allows accessing protected members from other classes in the same package and Kotlin doesn't, so Java classes will have broader access to the code);
- `internal` declarations become `public` in Java. Members of `internal` classes go through name mangling, to make it harder to accidentally use them from Java and to allow overloading for members with the same signature that don't see each other according to Kotlin rules;
- `public` remains `public`.

KClass

Sometimes you need to call a Kotlin method with a parameter of type `KClass`. There is no automatic conversion from `Class` to `KClass`, so you have to do it manually by invoking the equivalent of the `Class<T>.kotlin` extension property:

```
kotlin.jvm.JvmClassMappingKt.getKotlinClass(MainView.class)
```

Handling signature clashes with @JvmName

Sometimes we have a named function in Kotlin, for which we need a different JVM name the byte code. The most prominent example happens due to *type erasure*:

```
fun List<String>.filterValid(): List<String>
fun List<Int>.filterValid(): List<Int>
```

These two functions can not be defined side-by-side, because their JVM signatures are the same:

`filterValid(Ljava/util/List;)Ljava/util/List;`. If we really want them to have the same name in Kotlin, we can annotate one (or both) of them with `@JvmName` and specify a different name as an argument:

```
fun List<String>.filterValid(): List<String>

@JvmName("filterValidInt")
fun List<Int>.filterValid(): List<Int>
```

From Kotlin they will be accessible by the same name `filterValid`, but from Java it will be `filterValid` and `filterValidInt`.

The same trick applies when we need to have a property `x` alongside with a function `getX()`:

```
val x: Int
    @JvmName("getX_prop")
    get() = 15

fun getX() = 10
```

To change the names of generated accessor methods for properties without explicitly implemented getters and setters, you can use `@get:JvmName` and `@set:JvmName`:

```
@get:JvmName("x")
@set:JvmName("changeX")
var x: Int = 23
```

Overloads Generation

Normally, if you write a Kotlin function with default parameter values, it will be visible in Java only as a full signature, with all parameters present. If you wish to expose multiple overloads to Java callers, you can use the `@JvmOverloads` annotation.

The annotation also works for constructors, static methods etc. It can't be used on abstract methods, including methods defined in interfaces.

```
class Foo @JvmOverloads constructor(x: Int, y: Double = 0.0) {
    @JvmOverloads fun f(a: String, b: Int = 0, c: String = "abc") { ... }
}
```

For every parameter with a default value, this will generate one additional overload, which has this parameter and all parameters to the right of it in the parameter list removed. In this example, the following will be generated:

```
// Constructors:
Foo(int x, double y)
Foo(int x)

// Methods
void f(String a, int b, String c) { }
void f(String a, int b) { }
void f(String a) { }
```

Note that, as described in [Secondary Constructors](#), if a class has default values for all constructor parameters, a public no-argument constructor will be generated for it. This works even if the `@JvmOverloads` annotation is not specified.

Checked Exceptions

As we mentioned above, Kotlin does not have checked exceptions. So, normally, the Java signatures of Kotlin functions do not declare exceptions thrown. Thus if we have a function in Kotlin like this:

```
// example.kt
package demo

fun foo() {
    throw IOException()
}
```

And we want to call it from Java and catch the exception:

```
// Java
try {
    demo.Example.foo();
}
catch (IOException e) { // error: foo() does not declare IOException in the throws list
    // ...
}
```

we get an error message from the Java compiler, because `foo()` does not declare `IOException`. To work around this problem, use the `@Throws` annotation in Kotlin:

```
@Throws(IOException::class)
fun foo() {
    throw IOException()
}
```

Null-safety

When calling Kotlin functions from Java, nobody prevents us from passing `null` as a non-null parameter. That's why Kotlin generates runtime checks for all public functions that expect non-nulls. This way we get a `NullPointerException` in the Java code immediately

Variant generics

When Kotlin classes make use of [declaration-site variance](#), there are two options of how their usages are seen from the Java code. Let's say we have the following class and two functions that use it:

```

class Box<out T>(val value: T)

interface Base
class Derived : Base

fun boxDerived(value: Derived): Box<Derived> = Box(value)
fun unboxBase(box: Box<Base>): Base = box.value

```

A naive way of translating these functions into Java would be this:

```

Box<Derived> boxDerived(Derived value) { ... }
Base unboxBase(Box<Base> box) { ... }

```

The problem is that in Kotlin we can say `unboxBase(boxDerived("s"))`, but in Java that would be impossible, because in Java the class `Box` is *invariant* in its parameter `T`, and thus `Box<Derived>` is not a subtype of `Box<Base>`. To make it work in Java we'd have to define `unboxBase` as follows:

```

Base unboxBase(Box<? extends Base> box) { ... }

```

Here we make use of Java's *wildcards types* (`? extends Base`) to emulate declaration-site variance through use-site variance, because it is all Java has.

To make Kotlin APIs work in Java we generate `Box<Super>` as `Box<? extends Super>` for covariantly defined `Box` (or `Foo<? super Bar>` for contravariantly defined `Foo`) when it appears *as a parameter*. When it's a return value, we don't generate wildcards, because otherwise Java clients will have to deal with them (and it's against the common Java coding style). Therefore, the functions from our example are actually translated as follows:

```

// return type - no wildcards
Box<Derived> boxDerived(Derived value) { ... }

// parameter - wildcards
Base unboxBase(Box<? extends Base> box) { ... }

```

NOTE: when the argument type is final, there's usually no point in generating the wildcard, so `Box<String>` is always `Box<String>`, no matter what position it takes.

If we need wildcards where they are not generated by default, we can use the `@JvmWildcard` annotation:

```

fun boxDerived(value: Derived): Box<@JvmWildcard Derived> = Box(value)
// is translated to
// Box<? extends Derived> boxDerived(Derived value) { ... }

```

On the other hand, if we don't need wildcards where they are generated, we can use `@JvmSuppressWildcards`:

```

fun unboxBase(box: Box<@JvmSuppressWildcards Base>): Base = box.value
// is translated to
// Base unboxBase(Box<Base> box) { ... }

```

NOTE: `@JvmSuppressWildcards` can be used not only on individual type arguments, but on entire declarations, such as functions or classes, causing all wildcards inside them to be suppressed.

Translation of type `Nothing`

The type `Nothing` is special, because it has no natural counterpart in Java. Indeed, every Java reference type, including `java.lang.Void`, accepts `null` as a value, and `Nothing` doesn't accept even that. So, this type cannot be accurately represented in the Java world. This is why Kotlin generates a raw type where an argument of type `Nothing` is used:

```

fun emptyList(): List<Nothing> = listOf()
// is translated to
// List emptyList() { ... }

```


JavaScript

Dynamic Type

⚠ The dynamic type is not supported in code targeting the JVM

Being a statically typed language, Kotlin still has to interoperate with untyped or loosely typed environments, such as the JavaScript ecosystem. To facilitate these use cases, the `dynamic` type is available in the language:

```
val dyn: dynamic = ...
```

The `dynamic` type basically turns off Kotlin's type checker:

- a value of this type can be assigned to any variable or passed anywhere as a parameter;
- any value can be assigned to a variable of type `dynamic` or passed to a function that takes `dynamic` as a parameter;
- `null`-checks are disabled for such values.

The most peculiar feature of `dynamic` is that we are allowed to call **any** property or function with any parameters on a `dynamic` variable:

```
dyn.whatever(1, "foo", dyn) // 'whatever' is not defined anywhere
dyn.whatever(*arrayOf(1, 2, 3))
```

On the JavaScript platform this code will be compiled "as is": `dyn.whatever(1)` in Kotlin becomes `dyn.whatever(1)` in the generated JavaScript code.

When calling functions written in Kotlin on values of `dynamic` type, keep in mind the name mangling performed by the Kotlin to JavaScript compiler. You may need to use the [@JsName annotation](#) to assign well-defined names to the functions that you need to call.

A dynamic call always returns `dynamic` as a result, so we can chain such calls freely:

```
dyn.foo().bar.baz()
```

When we pass a lambda to a dynamic call, all of its parameters by default have the type `dynamic`:

```
dyn.foo {
    x -> x.bar() // x is dynamic
}
```

Expressions using values of `dynamic` type are translated to JavaScript "as is", and do not use the Kotlin operator conventions. The following operators are supported:

- binary: `+`, `-`, `*`, `/`, `%`, `>`, `<`, `>=`, `<=`, `==`, `!=`, `===`, `!==`, `&&`, `||`
- unary
 - prefix: `-`, `+`, `!`
 - prefix and postfix: `++`, `--`
- assignments: `+=`, `-=`, `*=`, `/=`, `%=`
- indexed access:
 - read: `d[a]`, more than one argument is an error
 - write: `d[a1] = a2`, more than one argument in `[]` is an error

`in`, `!in` and `..` operations with values of type `dynamic` are forbidden.

For a more technical description, see the [spec document](#).

Calling JavaScript from Kotlin

Kotlin was designed for easy interoperation with Java platform. It sees Java classes as Kotlin classes, and Java sees Kotlin classes as Java classes. However, JavaScript is a dynamically-typed language, which means it does not check types in compile-time. You can freely talk to JavaScript from Kotlin via [dynamic](#) types, but if you want the full power of Kotlin type system, you can create Kotlin headers for JavaScript libraries.

Inline JavaScript

You can inline some JavaScript code into your Kotlin code using the `js("...")` function. For example:

```
fun jsTypeOf(o: Any): String {
    return js("typeof o")
}
```

The parameter of `js` is required to be a string constant. So, the following code is incorrect:

```
fun jsTypeOf(o: Any): String {
    return js(getTypeof() + " o") // error reported here
}
fun getTypeof() = "typeof"
```

external modifier

To tell Kotlin that a certain declaration is written in pure JavaScript, you should mark it with `external` modifier. When the compiler sees such a declaration, it assumes that the implementation for the corresponding class, function or property is provided by the developer, and therefore does not try to generate any JavaScript code from the declaration. This means that you should omit bodies of `external` declarations. For example:

```
external fun alert(message: Any?): Unit
```

```
external class Node {
    val firstChild: Node

    fun append(child: Node): Node

    fun removeChild(child: Node): Node

    // etc
}
```

```
external val window: Window
```

Note that `external` modifier is inherited by nested declarations, i.e. in `Node` class we do not put `external` before member functions and properties.

The `external` modifier is only allowed on package-level declarations. You can't declare an `external` member of a non-`external` class.

Declaring (static) members of a class

In JavaScript you can define members either on a prototype or a class itself. I.e.:

```
function MyClass() { ... }
MyClass.sharedMember = function() { /* implementation */ };
MyClass.prototype.ownMember = function() { /* implementation */ };
```

There's no such syntax in Kotlin. However, in Kotlin we have `companion` objects. Kotlin treats companion objects of `external` class in a special way: instead of expecting an object, it assumes members of companion objects to be members of the class itself. To describe `MyClass` from the example above, you can write:

```
external class MyClass {
    companion object {
        fun sharedMember()
    }

    fun ownMember()
}
```

Declaring optional parameters

An external function can have optional parameters. How the JavaScript implementation actually computes default values for these parameters, is unknown to Kotlin, thus it's impossible to use the usual syntax to declare such parameters in Kotlin. You should use the following syntax:

```
external fun myFunWithOptionalArgs(x: Int,
    y: String = definedExternally,
    z: Long = definedExternally)
```

This means you can call `myFunWithOptionalArgs` with one required argument and two optional arguments (their default values are calculated by some JavaScript code).

Extending JavaScript classes

You can easily extend JavaScript classes as they were Kotlin classes. Just define an `external` class and extend it by non-`external` class. For example:

```
external open class HTMLElement : Element() {
    /* members */
}

class CustomElement : HTMLElement() {
    fun foo() {
        alert("bar")
    }
}
```

There are some limitations:

1. When a function of external base class is overloaded by signature, you can't override it in a derived class.
2. You can't override a function with default arguments.

Note that you can't extend a non-external class by external classes.

external interfaces

JavaScript does not have the concept of interfaces. When a function expects its parameter to support `foo` and `bar` methods, you just pass objects that actually have these methods. You can use interfaces to express this for statically-typed Kotlin, for example:

```
external interface HasFooAndBar {
    fun foo()

    fun bar()
}

external fun myFunction(p: HasFooAndBar)
```

Another use case for external interfaces is to describe settings objects. For example:

```

external interface JQueryAjaxSettings {
    var async: Boolean

    var cache: Boolean

    var complete: (JQueryXHR, String) -> Unit

    // etc
}

fun JQueryAjaxSettings(): JQueryAjaxSettings = js("{}")

external class JQuery {
    companion object {
        fun get(settings: JQueryAjaxSettings): JQueryXHR
    }
}

fun sendQuery() {
    JQuery.get(JQueryAjaxSettings()).apply {
        complete = { (xhr, data) ->
            window.alert("Request complete")
        }
    })
}

```

External interfaces have some restrictions:

1. They can't be used on the right hand side of `is` checks.
2. `as` cast to external interface always succeeds (and produces a warning in compile-time).
3. They can't be passed as reified type arguments.
4. They can't be used in class literal expressions (i.e. `I::class`).

Calling Kotlin from JavaScript

Kotlin compiler generates normal JavaScript classes, functions and properties you can freely use from JavaScript code. Nevertheless, there are some subtle things you should remember.

Isolating declarations in a separate JavaScript object

To prevent spoiling the global object, Kotlin creates an object that contains all Kotlin declarations from the current module. So if you name your module as `myModule`, all declarations are available to JavaScript via `myModule` object. For example:

```
fun foo() = "Hello"
```

Can be called from JavaScript like this:

```
alert(myModule.foo());
```

This is not applicable when you compile your Kotlin module to JavaScript module (see [JavaScript Modules](#) for more information on this). In this case there won't be a wrapper object, instead, declarations will be exposed as a JavaScript module of a corresponding kind. For example, in case of CommonJS you should write:

```
alert(require('myModule').foo());
```

Package structure

Kotlin exposes its package structure to JavaScript, so unless you define your declarations in the root package, you have to use fully-qualified names in JavaScript. For example:

```
package my.qualified.packagename
```

```
fun foo() = "Hello"
```

Can be called from JavaScript like this:

```
alert(myModule.my.qualified.packagename.foo());
```

@JsName annotation

In some cases (for example, to support overloads), Kotlin compiler mangles names of generated functions and attributes in JavaScript code. To control the generated names, you can use the `@JsName` annotation:

```
// Module 'kjs'
class Person(val name: String) {
    fun hello() {
        println("Hello $name!")
    }

    @JsName("helloWithGreeting")
    fun hello(greeting: String) {
        println("$greeting $name!")
    }
}
```

Now you can use this class from JavaScript in the following way:

```
var person = new kjs.Person("Dmitry"); // refers to module 'kjs'
person.hello();                        // prints "Hello Dmitry!"
person.helloWithGreeting("Servus");   // prints "Servus Dmitry!"
```

If we didn't specify the `@JsName` annotation, the name of the corresponding function would contain a suffix calculated from the function signature, for example `hello_61zpoes$`.

Note that Kotlin compiler does not apply such mangling to `external` declarations, so you don't have to use `@JsName` on them. Another case worth noticing is inheriting non-external classes from external classes. In this case any overridden functions won't be mangled as well.

The parameter of `@JsName` is required to be a constant string literal which is a valid identifier. The compiler will report an error on any attempt to pass non-identifier string to `@JsName`. The following example produces a compile-time error:

```
@JsName("new C()") // error here
external fun newC()
```

Representing Kotlin types in JavaScript

- Kotlin numeric types, except for `kotlin.Long` are mapped to JavaScript Number.
- `kotlin.Char` is mapped to JavaScript Number representing character code.
- Kotlin can't distinguish between numeric types at run time (except for `kotlin.Long`), i.e. the following code works:

```
fun f() {
    val x: Int = 23
    val y: Any = x
    println(y as Float)
}
```
- Kotlin preserves overflow semantics for `kotlin.Int`, `kotlin.Byte`, `kotlin.Short`, `kotlin.Char` and `kotlin.Long`.
- There's no 64 bit integer number in JavaScript, so `kotlin.Long` is not mapped to any JavaScript object, it's emulated by a Kotlin class.
- `kotlin.String` is mapped to JavaScript String.
- `kotlin.Any` is mapped to JavaScript Object (i.e. `new Object()`, `{}`, etc).
- `kotlin.Array` is mapped to JavaScript Array
- Kotlin collections (i.e. `List`, `Set`, `Map`, etc) are not mapped to any specific JavaScript type.
- `kotlin.Throwable` is mapped to JavaScript Error.
- Kotlin preserves lazy object initialization in JavaScript.
- Kotlin does not implement lazy initialization of top-level properties in JavaScript.

Starting with version 1.1.50 primitive array translation utilizes JavaScript TypedArray.

- `kotlin.ByteArray`, `- .ShortArray`, `- .IntArray`, `- .FloatArray`, and `- .DoubleArray` are mapped to JavaScript `Int8Array`, `Int16Array`, `Int32Array`, `Float32Array`, and `Float64Array` correspondingly.
- `kotlin.BooleanArray` is mapped to JavaScript `Int8Array` with a property `$type$ == "BooleanArray"`
- `kotlin.CharArray` is mapped to JavaScript `UInt16Array` with a property `$type$ == "CharArray"`
- `kotlin.LongArray` is mapped to JavaScript Array of `kotlin.Long` with a property `$type$ == "LongArray"`.

JavaScript Modules

Kotlin allows you to compile your Kotlin projects to JavaScript modules for popular module systems. Here is the list of available options:

1. Plain. Don't compile for any module system. As usual, you can access a module by its name in the global scope. This option is used by default.
2. [Asynchronous Module Definition \(AMD\)](#), which is in particular used by require.js library
3. [CommonJS](#) convention, widely used by node.js/npm (`require` function and `module.exports` object)
4. Unified Module Definitions (UMD), which is compatible with both *AMD* and *CommonJS*, and works as "plain" when neither *AMD* nor *CommonJS* is available at runtime.

Choosing the Target Module System

Choosing the target module system depends on your build environment:

From IntelliJ IDEA

Setup per module: Open File -> Project Structure..., find your module in Modules and select "Kotlin" facet under it. Choose appropriate module system in "Module kind" field.

Setup for the whole project: Open File -> Settings, select "Build, Execution, Deployment" -> "Compiler" -> "Kotlin compiler". Choose appropriate module system in "Module kind" field.

From Maven

To select module system when compiling via Maven, you should set `moduleKind` configuration property, i.e. your `pom.xml` should look like this:

```
<plugin>
  <artifactId>kotlin-maven-plugin</artifactId>
  <groupId>org.jetbrains.kotlin</groupId>
  <version>${kotlin.version}</version>
  <executions>
    <execution>
      <id>compile</id>
      <goals>
        <goal>js</goal>
      </goals>
    </execution>
  </executions>
  <!-- Insert these lines -->
  <configuration>
    <moduleKind>commonjs</moduleKind>
  </configuration>
  <!-- end of inserted text -->
</plugin>
```

Available values are: `plain`, `amd`, `commonjs`, `umd`.

From Gradle

To select module system when compiling via Gradle, you should set `moduleKind` property, i.e.

```
compileKotlin2Js.kotlinOptions.moduleKind = "commonjs"
```

Available values are similar to Maven.

@JsModule annotation

To tell Kotlin that an `external` class, package, function or property is a JavaScript module, you can use `@JsModule` annotation. Consider you have the following CommonJS module called "hello":


```
module.exports.sayHello = function(name) { alert("Hello, " + name); }
```

You should declare it like this in Kotlin:

```
@JsModule("hello")
external fun sayHello(name: String)
```

Applying @JsModule to packages

Some JavaScript libraries export packages (namespaces) instead of functions and classes. In terms of JavaScript, it's an object that has members that *are* classes, functions and properties. Importing these packages as Kotlin objects often looks unnatural. The compiler allows to map imported JavaScript packages to Kotlin packages, using the following notation:

```
@file:JsModule("extModule")
package ext.jspackage.name
```

```
external fun foo()
```

```
external class C
```

where the corresponding JavaScript module is declared like this:

```
module.exports = {
    foo: { /* some code here */ },
    C: { /* some code here */ }
}
```

Important: files marked with `@file:JsModule` annotation can't declare non-external members. The example below produces compile-time error:

```
@file:JsModule("extModule")
package ext.jspackage.name
```

```
external fun foo()
```

```
fun bar() = "!" + foo() + "!" // error here
```

Importing deeper package hierarchies

In the previous example the JavaScript module exports a single package. However, some JavaScript libraries export multiple packages from within a module. This case is also supported by Kotlin, though you have to declare a new `.kt` file for each package you import.

For example, let's make our example a bit more complicated:

```
module.exports = {
    mylib: {
        pkg1: {
            foo: function() { /* some code here */ },
            bar: function() { /* some code here */ }
        },
        pkg2: {
            baz: function() { /* some code here */ }
        }
    }
}
```

To import this module in Kotlin, you have to write two Kotlin source files:

```
@file:JsModule("extModule")
@file:JsQualifier("mylib.pkg1")
package extlib.pkg1
```

```
external fun foo()
```

```
external fun bar()
```

and

```
@file:JsModule("extModule")
@file:JsQualifier("mylib.pkg2")
package extlib.pkg2
```

```
external fun baz()
```

@JsNonModule annotation

When a declaration has `@JsModule`, you can't use it from Kotlin code when you don't compile it to a JavaScript module. Usually, developers distribute their libraries both as JavaScript modules and downloadable `.js` files that you can copy to project's static resources and include via `<script>` element. To tell Kotlin that it's ok to use a `@JsModule` declaration from non-module environment, you should put `@JsNonModule` declaration. For example, given JavaScript code:

```
function topLevelSayHello(name) { alert("Hello, " + name); }
if (module && module.exports) {
    module.exports = topLevelSayHello;
}
```

can be described like this:

```
@JsModule("hello")
@JsNonModule
@JsName("topLevelSayHello")
external fun sayHello(name: String)
```

Notes

Kotlin is distributed with `kotlin.js` standard library as a single file, which is itself compiled as an UMD module, so you can use it with any module system described above. Also it is available on NPM as [kotlin package](#)

JavaScript Reflection

At this time, JavaScript does not support the full Kotlin reflection API. The only supported part of the API is the `::class` syntax which allows you to refer to the class of an instance, or the class corresponding to the given type. The value of a `::class` expression is a stripped-down [KClass](#) implementation that only supports the [simpleName](#) and [isInstance](#) members.

In addition to that, you can use [KClass.js](#) to access the [JsClass](#) instance corresponding to the class. The `JsClass` instance itself is a reference to the constructor function. This can be used to interoperate with JS functions that expect a reference to a constructor.

Examples:

```
class A
class B
class C
```

```
inline fun <reified T> foo() {
    println(T::class.simpleName)
}
```

```
val a = A()
println(a::class.simpleName) // Obtains class for an instance; prints "A"
println(B::class.simpleName) // Obtains class for a type; prints "B"
println(B::class.js.name)    // prints "B"
foo<C>()                     // prints "C"
```

JavaScript DCE

Since version 1.1.4, Kotlin/JS includes a dead code elimination (DCE) tool. This tool allows to strip out unused properties, functions and classes from the generated JS. There are several ways you get unused declarations:

- Functions can be inlined and never get called directly (which happens always except for few situations).
- You are using a shared library which provides much more functions than you actually need. For example, standard library (`kotlin.js`) contains functions for manipulating lists, arrays, char sequences, adapters for DOM, etc, which together gives about 1.3 mb file. A simple "Hello, world" application only requires console routines, which is only few kilobytes for the entire file.

Dead code elimination is often also called 'tree shaking'.

How to use

DCE tool is currently available from Gradle.

To activate DCE tool, add the following line to `build.gradle` :

```
apply plugin: 'kotlin-dce-js'
```

Note that if you are using multi-project build, you should apply plugin to the main project that is an entry point to your application.

By default, the resulting set of JavaScript files (your application together with all dependencies) can be found at path `$BUILD_DIR/min/`, where `$BUILD_DIR` is the path to generated JavaScript (usually, `build/classes/main`).

Configuring

To configure DCE on the main source set, you can use the `runDceKotlinJs` task (and corresponding `runDce<sourceSetName>KotlinJs` for other source sets).

Sometimes you are going to use a Kotlin declaration directly from JavaScript, and it's being stripped out by DCE. You may want to keep this declaration. To do so, you can use the following syntax in `build.gradle` :

```
runDceKotlinJs.keep "declarationToKeep"[, "declarationToKeep", ...]
```

Where `declarationToKeep` has the following syntax:

```
moduleName.dot.separated.package.name.declarationName
```

For example, consider a module is named `kotlin-js-example` and it contains a function named `toKeep` in package `org.jetbrains.kotlin.examples`. Use the following line:

```
runDceKotlinJs.keep "kotlin-js-example_main.org.jetbrains.kotlin.examples.toKeep"
```

Note that if your function has parameters, its name will be mangled, so the mangled name should be used in the keep directive.

Development mode

Running DCE takes a bit of extra time each build, and the output size does not matter during development. You can improve development builds time by making the DCE tool skip actual dead code elimination with the `dceOptions.devMode` flag of the DCE tasks.

For example, to disable DCE based on a custom condition for the `main` source set and always for the `test` code, add the following lines to the build script:

```
runDceKotlinJs.dceOptions.devMode = isDevMode
runDceTestKotlinJs.dceOptions.devMode = true
```

Example

A full example that shows how to integrate Kotlin with DCE and webpack to get a small bundle, can be found [here](#).

Notes

- As for 1.1.x versions, DCE tool is an *experimental* feature. This does not mean we are going to remove it, or that it's unusable for production. This means that we can change names of configuration parameters, default settings, etc.
- Currently you should not use DCE tool if your project is a shared library. It's only applicable when you are developing an application (which may use shared libraries). The reason is: DCE does not know which parts of the library are going to be used by the user's application.
- DCE does not perform minification (uglifyfication) of your code by removing unnecessary whitespaces and shortening identifiers. You should use existing tools, like UglifyJS (<https://github.com/mishoo/UglifyJS2>) or Google Closure Compiler (<https://developers.google.com/closure/compiler/>) for this purpose.

Native

Concurrency in Kotlin/Native

Kotlin/Native runtime doesn't encourage a classical thread-oriented concurrency model with mutually exclusive code blocks and conditional variables, as this model is known to be error-prone and unreliable. Instead, we suggest a collection of alternative approaches, allowing you to use hardware concurrency and implement blocking IO. Those approaches are as follows, and they will be elaborated on in further sections:

- Workers with message passing
- Object subgraph ownership transfer
- Object subgraph freezing
- Object subgraph detachment
- Raw shared memory using C globals
- Coroutines for blocking operations (not covered in this document)

Workers

Instead of threads Kotlin/Native runtime offers the concept of workers: concurrently executed control flow streams with an associated request queue. Workers are very similar to the actors in the Actor Model. A worker can exchange Kotlin objects with another worker, so that at any moment each mutable object is owned by a single worker, but ownership can be transferred. See section [Object transfer and freezing](#).

Once a worker is started with the `Worker.start` function call, it can be addressed with its own unique integer worker id. Other workers, or non-worker concurrency primitives, such as OS threads, can send a message to the worker with the `execute` call.

```
val future = execute(TransferMode.SAFE, { SomeDataForWorker() }) {
    // data returned by the second function argument comes to the
    // worker routine as 'input' parameter.
    input ->
    // Here we create an instance to be returned when someone consumes result future.
    WorkerResult(input.stringParam + " result")
}

future.consume {
    // Here we see result returned from routine above. Note that future object or
    // id could be transferred to another worker, so we don't have to consume future
    // in same execution context it was obtained.
    result -> println("result is $result")
}
```

The call to `execute` uses a function passed as its second parameter to produce an object subgraph (i.e. set of mutually referring objects) which is then passed as a whole to that worker, it is then no longer available to the thread that initiated the request. This property is checked if the first parameter is `TransferMode.SAFE` by graph traversal and is just assumed to be true, if it is `TransferMode.UNSAFE`. The last parameter to `execute` is a special Kotlin lambda, which is not allowed to capture any state, and is actually invoked in the target worker's context. Once processed, the result is transferred to whatever consumes it in the future, and it is attached to the object graph of that worker/thread.

If an object is transferred in `UNSAFE` mode and is still accessible from multiple concurrent executors, program will likely crash unexpectedly, so consider that last resort in optimizing, not a general purpose mechanism.

For a more complete example please refer to the [workers example](#) in the Kotlin/Native repository.

Object transfer and freezing

An important invariant that Kotlin/Native runtime maintains is that the object is either owned by a single thread/worker, or it is immutable (*shared XOR mutable*). This ensures that the same data has a single mutator, and so there is no need for locking to exist. To achieve such an invariant, we use the concept of not externally referred object subgraphs. This is a subgraph which has no external references from outside of the subgraph, which could be checked algorithmically with $O(N)$ complexity (in ARC systems), where N is the number of elements in such a subgraph. Such subgraphs are usually produced as a result of a lambda expression, for example some builder, and may not contain objects, referred to externally.

Freezing is a runtime operation making a given object subgraph immutable, by modifying the object header so that future mutation attempts throw an `InvalidMutabilityException`. It is deep, so if an object has a pointer to other objects - transitive closure of such objects will be frozen. Freezing is a one way transformation, frozen objects cannot be unfrozen. Frozen objects have a nice property that due to their immutability, they can be freely shared between multiple workers/threads without breaking the "mutable XOR shared" invariant.

If an object is frozen it can be checked with an extension property `isFrozen`, and if it is, object sharing is allowed. Currently, Kotlin/Native runtime only freezes the enum objects after creation, although additional autofreezing of certain provably immutable objects could be implemented in the future.

Object subgraph detachment

An object subgraph without external references can be disconnected using `DetachedObjectGraph<T>` to a `COpaquePointer` value, which could be stored in `void*` data, so the disconnected object subgraphs can be stored in a C data structure, and later attached back with `DetachedObjectGraph<T>.attach()` in an arbitrary thread or a worker. Combining it with [raw memory sharing](#) it allows side channel object transfer between concurrent threads, if the worker mechanisms are insufficient for a particular task.

Raw shared memory

Considering the strong ties between Kotlin/Native and C via interoperability, in conjunction with the other mechanisms mentioned above it is possible to build popular data structures, like concurrent hashmap or shared cache with Kotlin/Native. It is possible to rely upon shared C data, and store in it references to detached object subgraphs. Consider the following .def file:

```
package = global

---
typedef struct {
    int version;
    void* kotlinObject;
} SharedData;

SharedData sharedData;
```

After running the cinterop tool it can share Kotlin data in a versionized global structure, and interact with it from Kotlin transparently via autogenerated Kotlin like this:

```
class SharedData(rawPtr: NativePtr) : CStructVar(rawPtr) {
    var version: Int
    var kotlinObject: COpaquePointer?
}
```

So in combination with the top level variable declared above, it can allow looking at the same memory from different threads and building traditional concurrent structures with platform-specific synchronization primitives.

Global variables and singletons

Frequently, global variables are a source of unintended concurrency issues, so *Kotlin/Native* implements the following mechanisms to prevent the unintended sharing of state via global objects:

- global variables, unless specially marked, can be only accessed from the main thread (that is, the thread *Kotlin/Native* runtime was first initialized), if other thread access such a global, `IncorrectDereferenceException` is thrown
- for global variables marked with the `@kotlin.native.ThreadLocal` annotation each threads keeps thread-local copy, so changes are not visible between threads
- for global variables marked with the `@kotlin.native.SharedImmutable` annotation value is shared, but frozen before

publishing, so each threads sees the same value

- singleton objects unless marked with `@kotlin.native.ThreadLocal` are frozen and shared, lazy values allowed, unless cyclic frozen structures were attempted to be created
- enums are always frozen

Combined, these mechanisms allow natural race-free programming with code reuse across platforms in MPP projects.

Immutability in Kotlin/Native

Kotlin/Native implements strict mutability checks, ensuring the important invariant that the object is either immutable or accessible from the single thread at that moment in time (`mutable XOR global`).

Immutability is a runtime property in Kotlin/Native, and can be applied to an arbitrary object subgraph using the `kotlin.native.concurrent.freeze` function. It makes all the objects reachable from the given one immutable, such a transition is a one-way operation (i.e., objects cannot be unfrozen later). Some naturally immutable objects such as `kotlin.String`, `kotlin.Int`, and other primitive types, along with `AtomicInt` and `AtomicReference` are frozen by default. If a mutating operation is applied to a frozen object, an `InvalidMutabilityException` is thrown.

To achieve `mutable XOR global` invariant, all globally visible state (currently, `object` singletons and enums) are automatically frozen. If object freezing is not desired, a `kotlin.native.ThreadLocal` annotation can be used, which will make the object state thread local, and so, mutable (but the changed state is not visible to other threads).

Top level/global variables of non-primitive types are by default accessible in the main thread (i.e., the thread which initialized *Kotlin/Native* runtime first) only. Access from another thread will lead to an `IncorrectDereferenceException` being thrown. To make such variables accessible in other threads, you can use either the `@ThreadLocal` annotation, and mark the value thread local or `@SharedImmutable`, which will make the value frozen and accessible from other threads.

Class `AtomicReference` can be used to publish the changed frozen state to other threads, and so build patterns like shared caches.

Kotlin/Native libraries

Kotlin compiler specifics

To produce a library with the Kotlin/Native compiler use the `-produce library` or `-p library` flag. For example:

```
$ kotlinc foo.kt -p library -o bar
```

the above command will produce a `bar.klib` with the compiled contents of `foo.kt`.

To link to a library use the `-library <name>` or `-l <name>` flag. For example:

```
$ kotlinc qux.kt -l bar
```

the above command will produce a `program.kexe` out of `qux.kt` and `bar.klib`

cinterop tool specifics

The **cinterop** tool produces `.klib` wrappers for native libraries as its main output. For example, using the simple `stdio.def` native library definition file provided in your Kotlin/Native distribution

```
$ cinterop -def ./samples/csvparser/src/main/c_interop/stdio.def -o stdio
```

we will obtain `stdio.klib`.

klib utility

The **klib** library management utility allows you to inspect and install the libraries.

The following commands are available.

To list library contents:

```
$ klib contents <name>
```

To inspect the bookkeeping details of the library

```
$ klib info <name>
```

To install the library to the default location use

```
$ klib install <name>
```

To remove the library from the default repository use

```
$ klib remove <name>
```

All of the above commands accept an additional `-repository <directory>` argument for specifying a repository different to the default one.

```
$ klib <command> <name> -repository <directory>
```

Several examples

First let's create a library:

```
$ cinterop -h /usr/include/math.h -pkg libc.math -o math
```

The library has been created in the current directory:

```
$ ls math.klib
math.klib
```

Now let's check out the contents of the library:

```
$ klib contents math
```

We can install `math` to the default repository:

```
$ klib install math
```

Remove any traces of it and its build process from the current directory:

```
$ rm -rf ./math*
```

Create a very short program and place it into a `sin.kt` :

```
import libc.math.*
fun main(args: Array<String>) {
    println(sin(2.0))
}
```

Now compile the program linking with the library we have just created:

```
$ kotlinc sin.kt -l math -o mysin
```

And run the program:

```
$ ./mysin.kexe
0.9092974268256817
```

Have fun!

Advanced topics

Library search sequence

When given a `-library foo` flag, the compiler searches the `foo` library in the following order:

- * Current compilation directory or an absolute path.
- * All repositories specified with ``-repo`` flag.
- * Libraries installed in the default repository (For now the default is ``~/.konan``, however it could be changed by setting `**KONAN_DATA_DIR**` environment variable).
- * Libraries installed in ``$installation/klib`` directory.

The library format

WARNING: the library format is *very* preliminary. It is subject to change right under your fingertips. And it can include changes which will make it incompatible between releases at least until Kotlin/Native is stabilized.

Kotlin/Native libraries are zip files containing a predefined directory structure, with the following layout:

foo.klib when unpacked as **foo/** gives us:

```
- foo/
  - targets/
    - $platform/
      - kotlin/
        - Kotlin compiled to LLVM bitcode.
      - native/
        - Bitcode files of additional native objects.
    - $another_platform/
      - There can be several platform specific kotlin and native pairs.
  - linkdata/
    - A set of ProtoBuf files with serialized linkage metadata.
  - resources/
    - General resources such as images. (Not used yet).
  - manifest - A file in *java property* format describing the library.
```

An example layout can be found in `klib/stdlib` directory of your installation.

Platform libraries

Overview

To provide access to user's native operating system services, `Kotlin/Native` distribution includes a set of prebuilt libraries specific to each target. We call them **Platform Libraries**.

POSIX bindings

For all `Unix` or `Windows` based targets (including `Android` and `iPhone`) we provide the `posix` platform lib. It contains bindings to platform's implementation of `POSIX` standard.

To use the library just

```
import platform.posix.*
```

The only target for which it is not available is [WebAssembly](#).

Note that the content of `platform.posix` is NOT identical on different platforms, in the same way as different `POSIX` implementations are a little different.

Popular native libraries

There are many more platform libraries available for host and cross-compilation targets. `Kotlin/Native` distribution provides access to `OpenGL`, `SDL`, `zlib` and other popular native libraries on applicable platforms.

On Apple platforms `objc` library is provided for interoperability with [Objective-C](#).

Inspect the contents of `dist/klib/platform/$target` of the distribution for the details.

Availability by default

The packages from platform libraries are available by default. No special link flags need to be specified to use them.

`Kotlin/Native` compiler automatically detects which of the platform libraries have been accessed and automatically links the needed libraries.

On the other hand, the platform libs in the distribution are merely just wrappers and bindings to the native libraries. That means the native libraries themselves (`.so`, `.a`, `.dylib`, `.dll` etc) should be installed on the machine.

Examples

`Kotlin/Native` installation provides a wide spectrum of examples demonstrating the use of platform libraries. See [samples](#) for details.

Kotlin/Native in multiplatform projects

While Kotlin/Native can be used as the only Kotlin compiler in a project, it is pretty common to combine Kotlin/Native with other Kotlin backends, such as Kotlin/JVM (for JVM or Android targets) or Kotlin/JS (for web and Node.js applications). This document describes the recommended approaches and best practices for such scenarios.

Kotlin as a language provides a notion of expect/actual declarations, and Gradle in turn augments it with the notion of multiplatform projects (aka MPP). These two, combined together, provide a flexible standardized [mechanism of multiplatform development](#) across various Kotlin flavors.

Code, common amongst multiple platforms can be placed in common modules, while platform-specific code can be placed into platform-specific modules, and expect/actual declarations can bind them together in a developer-friendly way.

Below you will find a step-by-step tutorial for creating a Kotlin multiplatform application for Android and iOS.

Creating multiplatform Android/iOS application with Kotlin

To create an MPP application you have to start with clear understanding of which parts of an application are common for different targets, and which are specific, and then organize the module structure accordingly. For shared Kotlin code the common ground consists of Kotlin's standard library, which does include basic data structures and computational primitives, along with some expected classes with platform-specific implementation. Most frequently, such code consists of a GUI, input-output, cryptography, and other APIs, available on the particular platform.

In this tutorial, the multiplatform application will include three parts:

- An **Android application** represented by a separate Android Studio project written in Kotlin.
- An **iOS application** represented by a separate Xcode project, written in Swift.
- A **multiplatform library** containing the business logic of the application and used by both Android and iOS applications. This library can contain both platform-dependent and platform-independent code and is compiled into a `jar`-library for Android and in a `Framework` for iOS by Gradle.

So, the multiplatform library will include three subprojects:

- `common` - contains common logic for both applications
- `ios` - contains iOS-specific code
- `android` - contains Android-specific code

1. Preparing a workspace

Let's represent the structure described above as a directory tree. Assume that our multiplatform library is intended to generate different greetings on different platforms. Create the following directory structure:

```
application/  
├── androidApp/  
├── iosApp/  
└── greeting/  
    ├── common/  
    ├── android/  
    └── ios/
```

As said above, [Gradle](#) is the main build system for Kotlin so our project will use it.

To install Gradle refer to [these instructions](#). Despite being able to use the local Gradle installation for building a project, it's recommended to use the [Gradle wrapper](#) instead. To create the wrapper, install Gradle as described above, and execute `gradle wrapper` in the root directory of the project. After that you can use `./gradlew` to run the build instead of using your local Gradle installation.

Once the wrapper is created we need to describe the project structure in Gradle terms. To do this, create a `settings.gradle` file in the root directory of the project and put the following snippet into it:

```
include ':greeting'  
include ':greeting:common'  
include ':greeting:android'  
include ':greeting:ios'
```

Here we declare all subprojects for our `greeting` multiplatform library. All other multiplatform libraries included in the project also must be declared here.

Note that both iOS and Android applications are not included in the root Gradle build. They are represented by independent builds which are managed by specific IDEs (Android Studio and Xcode). Such an approach makes working with these builds easier from the IDEs.

As for an IDE for other parts of the project, [IntelliJ IDEA](#) is recommended.

Note: Kotlin/Native is not supported by IntelliJ IDEA so the only IDE to develop Kotlin/Native sub-projects is [CLion](#). But at the moment CLion has no Gradle integration. As a workaround you can create a CLion Cmake project from a Kotlin/Native Gradle one. Just run `./gradlew generateCMake` for this project. It will generate all the necessary files which are required. See [this](#) blog post to learn more about Kotlin/Native support in CLion.

For the final step create the empty `build.gradle` files in the root directory of the project and in all subprojects which are included in `settings.gradle`. After performing all these actions the project structure will be the following (files generated by the Gradle wrapper are not shown):

```
application/
├─ androidApp/
├─ iosApp/
├─ greeting/
│  └─ android/
│     └─ build.gradle
│  └─ common/
│     └─ build.gradle
│  └─ ios/
│     └─ build.gradle
│  └─ build.gradle
├─ build.gradle
└─ settings.gradle
```

Now we have the basic structure of the project and can proceed to implement the multiplatform library.

2. Multiplatform library

We need to add buildscript dependencies to be able to use the Kotlin plugins for Gradle in our build. Open the `build.gradle` in the `greeting` directory and put the following snippet into it:

```
// Set up a buildscript dependency on the Kotlin plugin.
buildscript {
    // Specify a Kotlin version you need.
    ext.kotlin_version = '1.2.41'

    repositories {
        jcenter()
        maven { url "https://dl.bintray.com/jetbrains/kotlin-native-dependencies" }
    }

    // Specify all the plugins used as dependencies
    dependencies {
        classpath "org.jetbrains.kotlin:kotlin-gradle-plugin:$kotlin_version"
        classpath "org.jetbrains.kotlin:kotlin-native-gradle-plugin:0.7"
    }
}

// Set up compilation dependency repositories for all projects.
subprojects {
    repositories {
        jcenter()
    }
}
```

Now all subprojects of the library can use Kotlin plugins.

2.1 Common subproject

The `common` subproject contains platform-independent code. To build it, add the following snippet in `common/build.gradle`:

apply plugin: 'kotlin-platform-common'

```
// Specify a group and a version of the library to access it in Android Studio.
// By default the project directory name is used as an artifact name thus the full dependency
// description will be 'org.greeting:common:1.0'
group = 'org.greeting'
version = 1.0
```

```
dependencies {
    // Set up a compilation dependency on common Kotlin stdlib
    implementation "org.jetbrains.kotlin:kotlin-stdlib-common:$kotlin_version"
}
```

Now we can write some logic available for all platforms. Create `common/src/main/kotlin/common.kt` and add some functionality into it:

```
// greeting/common/src/main/kotlin/common.kt
package org.greeting

expect class Platform() {
    val platform: String
}

class Greeting {
    fun greeting(): String = "Hello, ${Platform().platform}"
}
```

Here we create a simple class using the `expect / actual` paradigm. Find details about platform-specific declarations [here](#).

2.2 Android subproject

The `android` subproject contains platform-dependent implementations of the `expect`-declarations we've created in the `common` project. We compile it into a Java library which an Android Studio project can depend on. The content of the `android/build.gradle` will be the following:

apply plugin: 'kotlin-platform-jvm'

```
// Specify a group and a version of the library to access it in Android Studio.
// By default the project directory name is used as an artifact name thus the full dependency
// description will be 'org.greeting:android:1.0'
group = 'org.greeting'
version = 1.0
```

```
dependencies {
    // Specify Kotlin/JVM stdlib dependency.
    implementation "org.jetbrains.kotlin:kotlin-stdlib-jre7:$kotlin_version"

    // Specify dependency on a common project for Kotlin multiplatform build.
    expectedBy project(':greeting:common')
}
```

As mentioned above this subproject should include actual implementations of the common project's `expect`-declarations. Let's write an Android-specific method:

```
// greeting/android/src/main/kotlin/android.kt
package org.greeting

actual class Platform actual constructor() {
    actual val platform: String = "Android"
}
```

2.3 iOS subproject

This project is compiled into an Objective-C framework using the Kotlin/Native compiler. To do this, declare a framework in `ios/build.gradle` and add an `expectedBy` dependency in the same manner as was done in the Android project:

```
apply plugin: 'konan'

// Specify targets to build the framework: iOS and iOS simulator
konan.targets = ['ios_arm64', 'ios_x64']

konanArtifacts {
    // Declare building into a framework.
    framework('Greeting') {
        // The multiplatform support is disabled by default.
        enableMultiplatform true
    }
}

dependencies {
    // Specify dependency on a common project for Kotlin multiplatform build
    expectedBy project(':greeting:common')
}
```

As well as `android`, this project contains platform-dependent implementations of `expect` -declarations:

```
// greeting/ios/src/main/kotlin/ios.kt
package org.greeting

actual class Platform actual constructor() {
    actual val platform: String = "iOS"
}
```

3. Android application

Now we can create an Android application which will use the library we implemented in the previous step. Open Android Studio and create a new project in the `androidApp` directory. Android Studio will generate all the necessary files and directories.

Kotlin/Native requires Gradle 4.7 or higher so you need to make sure that the AS project uses the correct Gradle version. To do this, open `androidApp/gradle/gradle-wrapper.properties` and check the `distributionUrl` property. Upgrade the wrapper if necessary (see [Gradle documentation](#)).

Now we only need to add a dependency on our library. There are 2 actions we need to take:

1. Add dependency on the library. To do this just open `androidApp/app/build.gradle` and add the following snippet in the `dependencies` script block:

```
implementation 'org.greeting:android:1.0'
```

2. Include `greeting` build in the Android Studio project as a part of [composite build](#). To do this, add the following line in `androidApp/settings.gradle`:

```
includeBuild '../'
```

Now dependencies of the application can be resolved in artifacts built by `greeting`. You also may publish the Android part of `greeting` into some Maven repo and get it from there. In this case you don't need to set up the composite build.

Note: Android Studio may fail to resolve declarations from the library added unless it's built. If you face such a problem, build the library by executing `./gradlew greeting:android:jar` in the root directory of the project.

Alternatively you can add the multiplatform library subprojects right into the Android Studio one instead of creating a composite build. To do this you need to declare them along with their directories in `androidApp/settings.gradle`:

```
include ':greeting'
include ':greeting:common'
include ':greeting:android'

project(':greeting').projectDir = file('../greeting')
project(':greeting:common').projectDir = file('../greeting/common')
project(':greeting:android').projectDir = file('../greeting/android')
```

Now you can declare dependencies directly on projects instead of using maven-like coordinates:

```
implementation project(':greeting:android')
```

After these steps we can access our library as we would with any other Kotlin code:

```
import org.greeting.*

/* ... */

fun foo() {
    println(Greeting().greeting())
}
```

4. iOS application

As already mentioned above the multiplatform library can also be used in iOS applications. The general approach here is the same as in the case of the Android application: we create a separate Xcode project and add the library as a framework. But we need to make some additional steps here.

Unlike Android Studio Xcode doesn't use Gradle, so we cannot just add the library as a dependency. Instead we need to create a new framework in the Xcode project and then replace its default build phases with a custom one which delegates building the framework to Gradle.

To do this, perform the following steps:

1. Create a new Xcode project in the root directory of your project (the `application` directory in the [section 1](#)). Name it `iosApp` so Xcode will create the project in the directory we created in the section 1.
2. Add a new framework in the project. Go to `File -> New -> Target -> Cocoa Touch Framework`. Specify the same framework name as is in `greeting/ios/build.gradle`: `Greeting`.
3. Choose the new framework in the `Project Navigator` and open the `Build Settings` tab. Here we need to add a new build setting specifying what Gradle task will be executed to build the framework for one or another platform. Fortunately, Xcode allows us to set different values for the same build setting depending on the platform. Create a new build setting in the `User-defined` section and name it `KONAN_TASK`. Then specify the following values for it for different platforms (for both `Debug` and `Release` modes):

| Platform | Value |
|-----------------------|--|
| Any iOS simulator SDK | <code>compileKonan<framework name>Ios_x64</code> |
| Any iOS SDK | <code>compileKonan<framework name>Ios_arm64</code> |

Replace `<framework name>` with the name you specified in the library's `ios/build.gradle`. Use camel case, e.g. for our `greeting` library these tasks will be named `compileKonanGreetingIos_x64` and `compileKonanGreetingIos_arm64`.

4. Add one more build setting for the framework to manage optimizations performed by the Kotlin/Native compiler. Name it `KONAN_ENABLE_OPTIMIZATIONS` and set its value to `YES` for the `Release` mode and to `NO` for the `Debug` mode.
5. Ensure that the framework is still selected in the `Project Navigator` and open the `Build phases` tab. Remove all the default phases except `Target Dependencies`.
6. Add a new `Run Script` build phase and put the following code into the script field:

```
"$SRCROOT/../gradlew" -p "$SRCROOT/../greeting/ios" "$KONAN_TASK" \
-Pkonan.configuration.build.dir="$CONFIGURATION_BUILD_DIR" \
-Pkonan.debugging.symbols="$DEBUGGING_SYMBOLS" \
-Pkonan.optimizations.enable="$KONAN_ENABLE_OPTIMIZATIONS"
```

This script executes the Gradle build to compile the multiplatform library into a framework. Let's examine this command in more detail.

- `"$SRCROOT/../gradlew"` - here we invoke the Gradle wrapper located in the root directory of the project. If you use a local Gradle installation you need to invoke it instead of the wrapper.
- `-p "$SRCROOT/../greeting/ios"` - specify a path to the Gradle subproject containing the framework.
- `"$KONAN_TASK"` - specify a Gradle task to execute. The build setting created above is used here.
- `-Pkonan.configuration.build.dir="$CONFIGURATION_BUILD_DIR"` - specify a directory provided by Xcode as an output one.
- `-Pkonan.debugging.symbols="$DEBUGGING_SYMBOLS"` - allow Xcode to enable debugging symbols generation.
- `-Pkonan.optimizations.enable="$KONAN_ENABLE_OPTIMIZATIONS"` - disable/enable optimizations. The build setting created above is used here.

7. Add Kotlin sources into the framework: run `File -> Add files to "iosApp"...` and choose a directory with Kotlin sources (`greeting/ios/src` in this sample). Choose the framework created as a target to add these sources to. Do this for the common code of the library too.

Now the framework is added and all the Kotlin API are available from Swift code (note that you need to build the framework in order to get code completion). Let's print our greeting:

```
import Greeting

/* ... */

func foo() {
    print(GreetingGreeting().greeting())
}
```

Sample

A sample implementation which follows this documentation can be found [here](#). You may also look at the [calculator sample](#). It has a simpler structure (particularly both Android app and Kotlin/Native library are combined in a single Gradle build) but also uses the multiplatform support provided by Kotlin.

Kotlin/Native interoperability

Introduction

Kotlin/Native follows the general tradition of Kotlin to provide excellent existing platform software interoperability. In the case of a native platform, the most important interoperability target is a C library. So *Kotlin/Native* comes with a `cinterop` tool, which can be used to quickly generate everything needed to interact with an external library.

The following workflow is expected when interacting with the native library.

- create a `.def` file describing what to include into bindings
- use the `cinterop` tool to produce Kotlin bindings
- run *Kotlin/Native* compiler on an application to produce the final executable

The interoperability tool analyses C headers and produces a "natural" mapping of the types, functions, and constants into the Kotlin world. The generated stubs can be imported into an IDE for the purpose of code completion and navigation.

Interoperability with Swift/Objective-C is provided too and covered in a separate document [OBJC_INTEROP.md](#).

Simple example

Build the dependencies and compiler (see `README.md`).

Prepare stubs for the system sockets library:

```
cd samples/socket
../../dist/bin/cinterop -def src/main/c_interop/sockets.def \
-o sockets
```

Compile the echo server:

```
../../dist/bin/kotlinc src/main/kotlin/EchoServer.kt \
-library sockets -o EchoServer
```

This whole process is automated in the `build.sh` script, which also supports cross-compilation to supported cross-targets with `TARGET=raspberrypi` `./build.sh` (the `cross_dist` target must be executed first).

Run the server:

```
./EchoServer.kexe 3000 &
```

Test the server by connecting to it, for example with telnet:

```
telnet localhost 3000
```

Write something to the console and watch the server echo it back.

Creating bindings for a new library

To create bindings for a new library, start by creating a `.def` file. Structurally it's a simple property file, which looks like this:

```
headers = zlib.h
compilerOpts = -std=c99
```

Then run the `cinterop` tool with something like this (note that for host libraries that are not included in the sysroot search paths, headers may be needed):

```
cinterop -def zlib.def -copt -I/opt/local/include -o zlib
```

This command will produce a `zlib.klib` compiled library and `zlib-build/kotlin` directory containing Kotlin source code for the library.

If the behavior for a certain platform needs to be modified, you can use a format like `compilerOpts.osx` or `compilerOpts.linux` to provide platform-specific values to the options.

Note, that the generated bindings are generally platform-specific, so if you are developing for multiple targets, the bindings need to be regenerated.

After the generation of bindings, they can be used by the IDE as a proxy view of the native library.

For a typical Unix library with a config script, the `compilerOpts` will likely contain the output of a config script with the `--cflags` flag (maybe without exact paths).

The output of a config script with `--libs` will be passed as a `-linkedArgs` `kotlinc` flag value (quoted) when compiling.

Selecting library headers

When library headers are imported to a C program with the `#include` directive, all of the headers included by these headers are also included in the program. So all header dependencies are included in generated stubs as well.

This behavior is correct but it can be very inconvenient for some libraries. So it is possible to specify in the `.def` file which of the included headers are to be imported. The separate declarations from other headers can also be imported in case of direct dependencies.

Filtering headers by globs

It is possible to filter headers by globs. The `headerFilter` property value from the `.def` file is treated as a space-separated list of globs. If the included header matches any of the globs, then the declarations from this header are included into the bindings.

The globs are applied to the header paths relative to the appropriate include path elements, e.g. `time.h` or `curl/curl.h`. So if the library is usually included with `#include <SomeLibrary/Header.h>`, then it would probably be correct to filter headers with

```
headerFilter = SomeLibrary/**
```

If a `headerFilter` is not specified, then all headers are included.

Filtering by module maps

Some libraries have proper `module.modulemap` or `module.map` files in its headers. For example, macOS and iOS system libraries and frameworks do. The [module map file](#) describes the correspondence between header files and modules. When the module maps are available, the headers from the modules that are not included directly can be filtered out using the experimental `excludeDependentModules` option of the `.def` file:

```
headers = OpenGL/gl.h OpenGL/glu.h GLUT/glut.h
compilerOpts = -framework OpenGL -framework GLUT
excludeDependentModules = true
```

When both `excludeDependentModules` and `headerFilter` are used, they are applied as an intersection.

Adding custom declarations

Sometimes it is required to add custom C declarations to the library before generating bindings (e.g., for [macros](#)). Instead of creating an additional header file with these declarations, you can include them directly to the end of the `.def` file, after a separating line, containing only the separator sequence `---`:

```
headers = errno.h

---

static inline int getErrno() {
    return errno;
}
```

Note that this part of the `.def` file is treated as part of the header file, so functions with the body should be declared as `static`. The declarations are parsed after including the files from the `headers` list.

Including static library in your klib

Sometimes it is more convenient to ship a static library with your product, rather than assume it is available within the user's environment. To include a static library into `.klib` use `staticLibrary` and `libraryPaths` clauses. For example:

```
staticLibraries = libfoo.a
libraryPaths = /opt/local/lib /usr/local/opt/curl/lib
```

When given the above snippet the `cinterop` tool will search `libfoo.a` in `/opt/local/lib` and `/usr/local/opt/curl/lib`, and if it is found include the library binary into `klib`.

When using such `klib` in your program, the library is linked automatically.

Using bindings

Basic interop types

All the supported C types have corresponding representations in Kotlin:

- Signed, unsigned integral, and floating point types are mapped to their Kotlin counterpart with the same width.
- Pointers and arrays are mapped to `CPointer<T>?`.
- Enums can be mapped to either Kotlin enum or integral values, depending on heuristics and the definition file hints (see "Definition file hints" below).
- Structs are mapped to types having fields available via the dot notation, i.e. `someStructInstance.field1`.
- `typedef` are represented as `typealias`.

Also, any C type has the Kotlin type representing the lvalue of this type, i.e., the value located in memory rather than a simple immutable self-contained value. Think C++ references, as a similar concept. For structs (and `typedef`s to structs) this representation is the main one and has the same name as the struct itself, for Kotlin enums it is named `_${type}Var`, for `CPointer<T>` it is `CPointerVar<T>`, and for most other types it is `_${type}Var`.

For types that have both representations, the one with a "lvalue" has a mutable `.value` property for accessing the value.

Pointer types

The type argument `T` of `CPointer<T>` must be one of the "lvalue" types described above, e.g., the C type `struct S*` is mapped to `CPointer<S>`, `int8_t*` is mapped to `CPointer<int_8tVar>`, and `char**` is mapped to `CPointer<CPointerVar<ByteVar>>`.

C null pointer is represented as Kotlin's `null`, and the pointer type `CPointer<T>` is not nullable, but the `CPointer<T>?` is. The values of this type support all the Kotlin operations related to handling `null`, e.g. `?:`, `?.`, `!!` etc.:

```
val path = getenv("PATH")?.toKString() ?: ""
```

Since the arrays are also mapped to `CPointer<T>`, it supports the `[]` operator for accessing values by index:

```
fun shift(ptr: CPointer<BytePtr>, length: Int) {
    for (index in 0 .. length - 2) {
        ptr[index] = ptr[index + 1]
    }
}
```

The `.pointed` property for `CPointer<T>` returns the lvalue of type `T`, pointed by this pointer. The reverse operation is `.ptr`: it takes the lvalue and returns the pointer to it.

`void*` is mapped to `COpaquePointer` – the special pointer type which is the supertype for any other pointer type. So if the C function takes `void*`, then the Kotlin binding accepts any `CPointer`.

Casting a pointer (including `COpaquePointer`) can be done with `.reinterpret<T>`, e.g.:

```
val intPtr = bytePtr.reinterpret<IntVar>()
```

or

```
val intPtr: CPointer<IntVar> = bytePtr.reinterpret()
```

As is with C, these reinterpret casts are unsafe and can potentially lead to subtle memory problems in the application.

Also there are unsafe casts between `CPointer<T>?` and `Long` available, provided by the `.toLong()` and `.toCPointer<T>()` extension methods:

```
val longValue = ptr.toLong()
val originalPtr = longValue.toCPointer<T>()
```

Note that if the type of the result is known from the context, the type argument can be omitted as usual due to the type inference.

Memory allocation

The native memory can be allocated using the `NativePlacement` interface, e.g.

```
val byteVar = placement.alloc<ByteVar>()
```

or

```
val bytePtr = placement.allocArray<ByteVar>(5):
```

The most "natural" placement is in the object `nativeHeap`. It corresponds to allocating native memory with `malloc` and provides an additional `.free()` operation to free allocated memory:

```
val buffer = nativeHeap.allocArray<ByteVar>(size)
<use buffer>
nativeHeap.free(buffer)
```

However, the lifetime of allocated memory is often bound to the lexical scope. It is possible to define such scope with `memScoped { ... }`. Inside the braces, the temporary placement is available as an implicit receiver, so it is possible to allocate native memory with `alloc` and `allocArray`, and the allocated memory will be automatically freed after leaving the scope.

For example, the C function returning values through pointer parameters can be used like

```
val fileSize = memScoped {
    val statBuf = alloc<statStruct>()
    val error = stat("/", statBuf.ptr)
    statBuf.st_size
}
```

Passing pointers to bindings

Although C pointers are mapped to the `CPointer<T>` type, the C function pointer-typed parameters are mapped to `CValuesRef<T>`. When passing `CPointer<T>` as the value of such a parameter, it is passed to the C function as is. However, the sequence of values can be passed instead of a pointer. In this case the sequence is passed "by value", i.e., the C function receives the pointer to the temporary copy of that sequence, which is valid only until the function returns.

The `CValuesRef<T>` representation of pointer parameters is designed to support C array literals without explicit native memory allocation. To construct the immutable self-contained sequence of C values, the following methods are provided:

- `${type}Array.toCValues()`, where `type` is the Kotlin primitive type
- `Array<CPointer<T>?>.toCValues()`, `List<CPointer<T>?>.toCValues()`
- `cValuesOf(vararg elements: ${type})`, where `type` is a primitive or pointer

For example:

C:

```
void foo(int* elements, int count);
...
int elements[] = {1, 2, 3};
foo(elements, 3);
```

Kotlin:

```
foo(cValuesOf(1, 2, 3), 3)
```

Working with the strings

Unlike other pointers, the parameters of type `const char*` are represented as a Kotlin `String`. So it is possible to pass any Kotlin string to a binding expecting a C string.

There are also some tools available to convert between Kotlin and C strings manually:

```
— fun CPointer<ByteRef>.toKString(): String
— val String.cstr: CValuesRef<ByteRef>.
```

To get the pointer, `.cstr` should be allocated in native memory, e.g.

```
val cString = kotlinString.cstr.getPointer(nativeHeap)
```

In all cases, the C string is supposed to be encoded as UTF-8.

To skip automatic conversion and ensure raw pointers are used in the bindings, a `noStringConversion` statement in the `.def` file could be used, i.e.

```
noStringConversion = LoadCursorA LoadCursorW
```

This way any value of type `CPointer<ByteVar>` can be passed as an argument of `const char*` type. If a Kotlin string should be passed, code like this could be used:

```
memScoped {
    LoadCursorA(null, "cursor.bmp".cstr.ptr) // for ASCII version
    LoadCursorW(null, "cursor.bmp".wcstr.ptr) // for Unicode version
}
```

Scope-local pointers

It is possible to create a scope-stable pointer of C representation of `CValues<T>` instance using the `CValues<T>.ptr` extension property, available under `memScoped { ... }`. It allows using the APIs which require C pointers with a lifetime bound to a certain `MemScope`. For example:

```
memScoped {
    items = arrayOfNulls<CPointer<ITEM>?>(6)
    arrayOf("one", "two").forEachIndexed { index, value -> items[index] = value.cstr.ptr }
    menu = new_menu("Menu".cstr.ptr, items.toCValues().ptr)
    ...
}
```

In this example, all values passed to the C API `new_menu()` have a lifetime of the innermost `memScope` it belongs to. Once the control flow leaves the `memScoped` scope the C pointers become invalid.

Passing and receiving structs by value

When a C function takes or returns a struct `T` by value, the corresponding argument type or return type is represented as `CValue<T>`.

`CValue<T>` is an opaque type, so the structure fields cannot be accessed with the appropriate Kotlin properties. It should be possible, if an API uses structures as handles, but if field access is required, there are the following conversion methods available:

```
— fun T.readValue(): CValue<T>. Converts (the lvalue) T to a CValue<T>. So to construct the CValue<T>, T can be allocated, filled, and then converted to CValue<T>.
— CValue<T>.useContents(block: T.() -> R): R. Temporarily places the CValue<T> to memory, and then runs the passed lambda with this placed value T as receiver. So to read a single field, the following code can be used:

val fieldValue = structValue.useContents { field }
```

Callbacks

To convert a Kotlin function to a pointer to a C function, `staticCFunction(::kotlinFunction)` can be used. It is also able to provide the lambda instead of a function reference. The function or lambda must not capture any values.

Note that some function types are not supported currently. For example, it is not possible to get a pointer to a function that receives or returns structs by value.

If the callback doesn't run in the main thread, it is mandatory to init the *Kotlin/Native* runtime by calling `kotlin.native.initRuntimeIfNeeded()`.

Passing user data to callbacks

Often C APIs allow passing some user data to callbacks. Such data is usually provided by the user when configuring the callback. It is passed to some C function (or written to the struct) as e.g. `void*`. However, references to Kotlin objects can't be directly passed to C. So they require wrapping before configuring the callback and then unwrapping in the callback itself, to safely swim from Kotlin to Kotlin through the C world. Such wrapping is possible with `StableRef` class.

To wrap the reference:

```
val stablePtr = StableRef.create(kotlinReference)
val voidPtr = stablePtr.value
```

where the `voidPtr` is a `COpaquePointer` and can be passed to the C function.

To unwrap the reference:

```
val stablePtr = StableRef.fromValue(voidPtr)
val kotlinReference = stablePtr.get()
```

where `kotlinReference` is the original wrapped reference (however, its type is `Any` so it may require casting).

The created `StableRef` should eventually be manually disposed using the `.dispose()` method to prevent memory leaks:

```
stablePtr.dispose()
```

After that it becomes invalid, so `voidPtr` can't be unwrapped anymore.

See the `samples/libcurl` for more details.

Macros

Every C macro that expands to a constant is represented as a Kotlin property. Other macros are not supported. However, they can be exposed manually by wrapping them with supported declarations. E.g. function-like macro `F00` can be exposed as function `foo` by [adding the custom declaration](#) to the library.

```
headers = library/base.h
```

```
---
```

```
static inline int foo(int arg) {
    return F00(arg);
}
```

Definition file hints

The `.def` file supports several options for adjusting the generated bindings.

- `excludedFunctions` property value specifies a space-separated list of the names of functions that should be ignored. This may be required because a function declared in the C header is not generally guaranteed to be really callable, and it is often hard or impossible to figure this out automatically. This option can also be used to workaround a bug in the interop itself.
- `strictEnums` and `nonStrictEnums` properties values are space-separated lists of the enums that should be generated as a Kotlin enum or as integral values correspondingly. If the enum is not included into any of these lists, then it is generated according to the heuristics.

Portability

Sometimes the C libraries have function parameters or struct fields of a platform-dependent type, e.g. `long` or `size_t`. Kotlin itself doesn't provide neither implicit integer casts nor C-style integer casts (e.g. `(size_t) intValue`), so to make writing portable code in such cases easier, the `convert` method is provided:

```
fun ${type1}.convert<${type2}>(): ${type2}
```

where each of `type1` and `type2` must be an integral type, either signed or unsigned.

`.convert<${type}>` has the same semantics as one of the `.toByte`, `.toShort`, `.toInt`, `.toLong`, `.toUByte`, `.toUShort`, `.toUInt` or `.toULong` methods, depending on `type`.

The example of using `convert`:

```
fun zeroMemory(buffer: COpaquePointer, size: Int) {  
    memset(buffer, 0, size.convert<size_t>())  
}
```

Also, the type parameter can be inferred automatically and so may be omitted in some cases.

Kotlin/Native interoperability with Swift/Objective-C

This document covers some details of Kotlin/Native interoperability with Swift/Objective-C.

Usage

Kotlin/Native provides bidirectional interoperability with Objective-C. Objective-C frameworks and libraries can be used in Kotlin code if properly imported to the build (system frameworks are imported by default). See e.g. "Interop libraries" in [Gradle plugin documentation](#). A Swift library can be used in Kotlin code if its API is exported to Objective-C with `@objc`. Pure Swift modules are not yet supported.

Kotlin modules can be used in Swift/Objective-C code if compiled into a [framework](#). See [calculator sample](#) for an example.

Mappings

The table below shows how Kotlin concepts are mapped to Swift/Objective-C and vice versa.

| Kotlin | Swift | Objective-C | Notes |
|---------------------|---------------------------|--------------------------|---|
| class | class | @interface | note |
| interface | protocol | @protocol | |
| constructor/create | Initializer | Initializer | note |
| Property | Property | Property | note |
| Method | Method | Method | note note |
| @Throws | throws | error:(NSError**)error | note |
| Extension | Extension | Category member | note |
| companion member <- | Class method or property | Class method or property | |
| null | nil | nil | |
| Singleton | Singleton() | [Singleton singleton] | note |
| Primitive type | Primitive type / NSNumber | | note |
| Unit return type | Void | void | |
| String | String | NSString | |
| String | NSMutableString | NSMutableString | note |
| List | Array | NSArray | |
| MutableList | NSMutableArray | NSMutableArray | |
| Set | Set | NSSet | |
| MutableSet | NSMutableSet | NSMutableSet | note |
| Map | Dictionary | NSDictionary | |
| MutableMap | NSMutableDictionary | NSMutableDictionary | note |
| Function type | Function type | Block pointer type | note |

Name translation

Objective-C classes are imported into Kotlin with their original names. Protocols are imported as interfaces with `Protocol` name suffix, i.e. `@protocol Foo -> interface FooProtocol`. These classes and interfaces are placed into a package [specified in build configuration](#) (`platform.*` packages for preconfigured system frameworks).

The names of Kotlin classes and interfaces are prefixed when imported to Objective-C. The prefix is derived from the framework name.

Initializers

Swift/Objective-C initializers are imported to Kotlin as constructors and factory methods named `create`. The latter happens with initializers declared in the Objective-C category or as a Swift extension, because Kotlin has no concept of extension constructors.

Kotlin constructors are imported as initializers to Swift/Objective-C.

Top-level functions and properties

Top-level Kotlin functions and properties are accessible as members of special classes. Each Kotlin file is translated into such a class. E.g.

```
// MyLibraryUtils.kt
package my.library
```

```
fun foo() {}
```

can be called from Swift like

```
MyLibraryUtilskt.foo()
```

Method names translation

Generally Swift argument labels and Objective-C selector pieces are mapped to Kotlin parameter names. Anyway these two concepts have different semantics, so sometimes Swift/Objective-C methods can be imported with a clashing Kotlin signature. In this case the clashing methods can be called from Kotlin using named arguments, e.g.:

```
[player moveTo:LEFT byMeters:17]
[player moveTo:UP byInches:42]
```

in Kotlin it would be:

```
player.moveTo(LEFT, byMeters = 17)
player.moveTo(UP, byInches = 42)
```

Errors and exceptions

Kotlin has no concept of checked exceptions, all Kotlin exceptions are unchecked. Swift has only checked errors. So if Swift or Objective-C code calls a Kotlin method which throws an exception to be handled, then the Kotlin method should be marked with a `@Throws` annotation. In this case all Kotlin exceptions (except for instances of `Error`, `RuntimeException` and subclasses) are translated into a Swift error/ `NSError`.

Note that the opposite reversed translation is not implemented yet: Swift/Objective-C error-throwing methods aren't imported to Kotlin as exception-throwing.

Category members

Members of Objective-C categories and Swift extensions are imported to Kotlin as extensions. That's why these declarations can't be overridden in Kotlin. And the extension initializers aren't available as Kotlin constructors.

Kotlin singletons

Kotlin singleton (made with an `object` declaration, including `companion object`) is imported to Swift/Objective-C as a class with a single instance. The instance is available through the factory method, i.e. as `[MySingleton mySingleton]` in Objective-C and `MySingleton()` in Swift.

NSNumber

Kotlin primitive type boxes are mapped to special Swift/Objective-C classes. For example, `kotlin.Int` box is represented as `KotlinInt` class instance in Swift (or `${prefix}Int` instance in Objective-C, where `prefix` is the framework names prefix). These classes are derived from `NSNumber`, so the instances are proper `NSNumber`s supporting all corresponding operations.

`NSNumber` type is not automatically translated to Kotlin primitive types when used as a Swift/Objective-C parameter type or return value. The reason is that `NSNumber` type doesn't provide enough information about a wrapped primitive value type, i.e. `NSNumber` is statically not known to be a e.g. `Byte`, `Boolean`, or `Double`. So Kotlin primitive values should be cast to/from `NSNumber` manually (see [below](#)).

NSMutableString

`NSMutableString` Objective-C class is not available from Kotlin. All instances of `NSMutableString` are copied when passed to Kotlin.

Collections

Kotlin collections are converted to Swift/Objective-C collections as described in the table above. Swift/Objective-C collections are mapped to Kotlin in the same way, except for `NSMutableSet` and `NSMutableDictionary`. `NSMutableSet` isn't converted to a Kotlin `MutableSet`. To pass an object for Kotlin `MutableSet`, you can create this kind of Kotlin collection explicitly by either creating it in Kotlin with e.g. `mutableSetOf()`, or using the `KotlinMutableSet` class in Swift (or `$_{prefix}MutableSet` in Objective-C, where `prefix` is the framework names prefix). The same holds for `MutableMap`.

Function types

Kotlin function-typed objects (e.g. lambdas) are converted to Swift functions / Objective-C blocks. However there is a difference in how types of parameters and return values are mapped when translating a function and a function type. In the latter case primitive types are mapped to their boxed representation. Kotlin `Unit` return value is represented as a corresponding `Unit` singleton in Swift/Objective-C. The value of this singleton can be retrieved in the same way as it is for any other Kotlin `object` (see singletons in the table above). To sum the things up:

```
fun foo(block: (Int) -> Unit) { ... }
```

would be represented in Swift as

```
func foo(block: (KotlinInt) -> KotlinUnit)
```

and can be called like

```
foo {  
    bar($0 as! Int32)  
    return KotlinUnit()  
}
```

Casting between mapped types

When writing Kotlin code, an object may need to be converted from a Kotlin type to the equivalent Swift/Objective-C type (or vice versa). In this case a plain old Kotlin cast can be used, e.g.

```
val nsArray = listOf(1, 2, 3) as NSArray  
val string = nsString as String  
val nsNumber = 42 as NSNumber
```

Subclassing

Subclassing Kotlin classes and interfaces from Swift/Objective-C

Kotlin classes and interfaces can be subclassed by Swift/Objective-C classes and protocols. Currently a class that adopts the Kotlin protocol should inherit `NSObject` (either directly or indirectly). Note that all Kotlin classes do inherit `NSObject`, so a Swift/Objective-C subclass of Kotlin class can adopt the Kotlin protocol.

Subclassing Swift/Objective-C classes and protocols from Kotlin

Swift/Objective-C classes and protocols can be subclassed with a Kotlin `final` class. Non-`final` Kotlin classes inheriting Swift/Objective-C types aren't supported yet, so it is not possible to declare a complex class hierarchy inheriting Swift/Objective-C types.

Normal methods can be overridden using the `override` Kotlin keyword. In this case the overriding method must have the same parameter names as the overridden one.

Sometimes it is required to override initializers, e.g. when subclassing `UIViewController`. Initializers imported as Kotlin constructors can be overridden by Kotlin constructors marked with the `@OverrideInit` annotation:

```
class ViewController : UIViewController {  
    @OverrideInit constructor(coder: NSCoder) : super(coder)  
  
    ...  
}
```

The overriding constructor must have the same parameter names and types as the overridden one.

To override different methods with clashing Kotlin signatures, you can add a `@Suppress("CONFLICTING_OVERLOADS")` annotation to the class.

By default the Kotlin/Native compiler doesn't allow calling a non-designated Objective-C initializer as a `super(...)` constructor. This behaviour can be inconvenient if the designated initializers aren't marked properly in the Objective-C library. Adding a `disableDesignatedInitializerChecks = true` to the `.def` file for this library would disable these compiler checks.

C features

See [INTEROP.md](#) for an example case where the library uses some plain C features (e.g. unsafe pointers, structs etc.).

Kotlin/Native Gradle plugin

Note: For the experimental DSL see the [corresponding section](#).

Overview

You may use the Gradle plugin to build *Kotlin/Native* projects. Since version 0.8 release builds of the plugin are [available](#) at the Gradle plugin portal, so you can apply it using Gradle plugin DSL:

```
plugins {
    id "org.jetbrains.kotlin.konan" version "0.9"
}
```

Note: The 0.9 version of Kotlin/Native is based on Kotlin 1.3-M1 which is an EAP version and isn't available on the plugin portal. In this case you need to add a Kotlin EAP repository in your `settings.gradle`:

```
pluginManagement {
    repositories {
        gradlePluginPortal()
        maven {
            url = 'http://dl.bintray.com/kotlin/kotlin-eap'
        }
    }
}
```

You also can get the plugin from a Bintray repository. In addition to releases, this repo contains old and development versions of the plugin which are not available at the plugin portal. To get the plugin from the Bintray repo, include the following snippet in your build script:

```
buildscript {
    repositories {
        mavenCentral()
        maven {
            url "https://dl.bintray.com/jetbrains/kotlin-native-dependencies"
        }
        maven {
            url "http://dl.bintray.com/kotlin/kotlin-eap"
        }
    }

    dependencies {
        classpath "org.jetbrains.kotlin:kotlin-native-gradle-plugin:0.8-dev-*"
    }
}

apply plugin: 'konan'
```

The Kotlin/Native plugin depends on `org.jetbrains.kotlin:kotlin-native-gradle-plugin`. So if a build contains both these plugins as buildscript dependencies, it's recommended to **declare them in the same build.gradle** to avoid issues with plugin classpath.

By default the plugin downloads the Kotlin/Native compiler during the first run. If you have already downloaded the compiler manually you can specify the path to its root directory using `konan.home` project property (e.g. in `gradle.properties`).

```
konan.home=/home/user/kotlin-native-0.8
```

In this case the compiler will not be downloaded by the plugin.

Building artifacts

The Kotlin/Native Gradle plugin allows building artifacts of the following types:

- Executable
- KLibrary - a library used by Kotlin/Native compiler (`*.klib`)
- Interoperability library - a special type of library providing an interoperability with some native API. See [INTEROP.md](#) for details

- Dynamic library (*.so / *.dylib / *.dll)
- Objective-C framework
- LLVM bitcode

All Kotlin/Native artifacts should be declared in the `konanArtifacts` block. Note that the `konanInterop` script block was removed in v0.3.4. Use the `interop` method of the `konanArtifact` block instead:

```
konanArtifacts {
    program('foo') // executable 'foo'
    library('bar') // library 'bar'
    bitcode('baz') // bitcode file 'baz'
    interop('qux') // interoperability library 'qux'. Use it instead of konanInterop block.
    dynamic('quux') // dynamic library
    framework('quuux') // Objective-C framework
}
```

All artifacts except interop libraries are built by the Kotlin/Native compiler. Such an artifact may be configured using its script block. It is here that you can specify source directories, used libraries, and compilation flags (see [Plugin DSL](#) section for details). The plugin uses `src/main/kotlin/` as a default source directory for all compiler artifacts:

```
konanArtifacts {
    // Build foo.klib
    library('foo') {
        srcDir 'src/foo/kotlin' // Use custom source path
    }

    // Build executable 'bar'
    program('bar') {
        // The default source path is used (src/main/kotlin)

        // Optimize the output code
        enableOptimizations true

        libraries {
            // Use foo.klib as a library
            artifact 'foo'
        }
    }
}
```

Interop libraries are built using the `cinterop` tool. They also may have configuration blocks but the options available in these blocks differ from ones available for compiler artifacts. The input for such an artifact is a def-file describing a native API. By default the def-file path is `src/main/c_interop/<library-name>.def` but it may be changed using the `defFile` method of the configuration block of an interoperability library:

```
konanArtifacts {
    // Interoperability library stdio.klib
    // Use the default def-file path: src/main/c_interop/stdio.def
    interop('stdio')

    // Interoperability library openal.klib
    interop('openal') {
        defFile 'src/openal/openal.def'
    }

    program('main') {
        libraries {
            // Link with stdio.klib
            artifact 'stdio'
        }
    }
}
```

Building for different targets

All the artifacts declared in a project may be built for different targets. By default they are built only for the `host` target i.e. a computer used for building. One may change the default target list using the `konan.targets` project extension:

```
konan.targets = [ 'linux', 'android_arm64', 'android_arm32' ]
```

One may specify a custom target set for each particular artifact using the `targets` parameter of an artifact declaration:

```
konan.targets = [ 'linux', 'android_arm64' ]

konanArtifacts {
    // This artifact has no custom targets and will be built
    // for all the default ones: 'linux', 'android_arm64'
    program('foo') { /* ... */ }

    // This artifact will be built only for Linux and Wasm32
    program('bar', targets: ['linux', 'wasm32']) { /* ... */ }

    // An Objective-C framework cannot be built for Linux and Wasm32 thus
    // these targets will be skipped and the artifact will be built only for iOS
    framework('baz', targets: [ 'linux', 'wasm32', 'iphone' ]) { /* ... */ }
}
```

The plugin creates tasks to compile each artifact for all the targets supported by the current host and declared in the `konan.targets` list. You can perform additional configuration for a target using the `target` method of an artifact configuration block:

```
konan.targets = [ 'linux', 'macbook', 'wasm32' ]

konanArtifacts {
    program('foo') {
        // This source file is used for all targets
        srcFiles 'common.kt'

        target('linux') {
            // For Linux common.kt and linux.kt will be compiled
            srcFiles 'linux.kt'
        }

        target('macbook') {
            // For MacOS common.kt and macbook.kt will be compiled
            srcFiles 'macbook.kt'
        }

        // Only common.kt will be compiled for wasm32
    }
}
```

One may access to a task for some target via artifact methods or properties:

```
// Both of them return a task building artifact 'foo' for MacOS
konanArtifacts.foo.getByTarget("macbook")
konanArtifacts.foo.macbook
```

Using libraries

You can specify used libraries for artifacts of all types using the `libraries` script block:

```
program('foo') {
    libraries {
        // configure the libraries used
    }
}
```

There are several ways to describe a library used by an artifact:

- Specify a library file directly. You can specify it using the `file` method of the `libraries` script block. All the objects accepted by the [Project.file](#) method may be passed there:


```
libraries {
    file 'libs/foo.klib'
    files 'lib1.klib', 'lib2.klib'
}
```

- Specify a Kotlin/Native artifact object or its name. In this case the plugin automatically chooses a library with the correct target and sets dependencies between building tasks.

```
libraries {
    // Artifact object or just its name may be used
    artifact 'foo'
    artifact kotlinArtifacts.bar

    // Artifacts from other projects are also allowed
    artifact project(':bazProject'), 'bazLibrary'

    // Interopability libraries are also allowed
    // Use it instead of the `useInterop` method available in versions before 0.3.4
    artifact 'stdio'
}
```

- Specify a project containing libraries. In this case all libraries built by the project specified will be used:

```
libraries {
    allLibrariesFrom project(':subproject')

    // If we need only interoperability libraries
    allInteropLibrariesFrom project(':interop')
}
```

- Specify only the name of a library. In this case the compiler will look for the library in its repositories.

```
libraries {
    klib 'foo'
    klibs 'lib1', 'lib2'

    // One may specify additional repositories
    // All objects accepted by the Project.file method may be used here
    useRepo 'build/libraries'
}
```

Multiplatform build

Kotlin/Native, Kotlin/JVM, and Kotlin/JS, support multiplatform projects. Such support is included in the Kotlin/Native Gradle plugin by default and there is no need to apply any additional plugins to use it. By default multiplatform support is turned off, and can be enabled with the `enableMultiplatform` DSL method:

```
apply 'konan'
```

```
konanArtifacts {
    program('foo') {
        enableMultiplatform true
    }
}
```

The Gradle plugin adds an `expectedBy` dependency configuration that is used to specify a dependency from a Kotlin/Native project to a common project:

```
apply 'konan'
```

```
dependencies {
    expectedBy project('commonProject')
}
```

When a common project is added as an `expectedBy` dependency, all the artifacts with the multiplatform support enabled will use its `main` source set as a common module. One may specify custom source sets for each artifact using the `commonSourceSets` DSL method. In this case the multiplatform support will be also enabled for this artifact.

```
konanArtifacts {
    program('foo') {
        commonSourceSets 'customSourceSet', 'anotherCustomSourceSet'
    }
}
```

See more about multiplatform projects [here](#).

Tasks

The Kotlin/Native plugin creates the following tasks:

- **compileKonan<ArtifactName><Target>**. The plugin creates a task for each target declared in the `konan.targets` list and for each an artifact is defined in a `konanArtifacts` block. Such a task may have different properties depending on the artifact type:

Properties available for a compiler task (executable, library or bitcode building task):

| Property | Type | Description |
|---------------------|----------------------------|--|
| target | String | Target the artifact is built for. Read only |
| artifactName | String | Base name for the output file (without an extension) |
| destinationDir | File | Directory to place the output artifact |
| artifact | File | The output artifact. Read only |
| headerFile | File | The output C header. Only for dynamic libraries, read only |
| srcFiles | Collection<FileCollection> | Compiled files |
| nativeLibraries | Collection<FileCollection> | *.bc libraries used by the artifact |
| linkerOpts | List<String> | Additional options passed to the linker |
| enableDebug | boolean | Is the debugging support enabled |
| noStdLib | boolean | Is the artifact not linked with stdlib |
| noMain | boolean | Is the main function provided by a library used |
| enableOptimizations | boolean | Are the optimizations enabled |
| enableAssertions | boolean | Is the assertion support enabled |
| measureTime | boolean | Does the compiler print phase time |
| enableMultiplatform | boolean | Is multiplatform support enabled for this artifact |
| commonSourceSets | Collection<String> | Names of source sets used as a common module |

Properties available for a cinterop task (task building an interoperability library):

| Property | Type | Description |
|----------------|----------------------------|--|
| target | String | Target the artifact is built for. Read only |
| artifactName | String | Base name for the output file (without an extension) |
| destinationDir | File | Directory to place the output artifact |
| artifact | File | The output artifact. Read only. |
| defFile | File | Def-file used by the interop |
| compilerOpts | List<String> | Additional options passed to clang |
| linkerOpts | List<String> | Additional options passed to a linker |
| headers | Collection<FileCollection> | Additional headers used for stub generation |

| Property | Type | Description |
|----------|------|-------------|
|----------|------|-------------|

- **compileKonan<ArtifactName>**. Aggregate task allowing you to build an artifact for several targets. By default it builds the artifact for all the supported targets declared for the project. You can change this behavior by specifying the space-separated target list in the `konan.build.targets` project property:

```
./gradlew compileKonanFoo -Pkonan.build.targets='android_arm32 android_arm64'
```

The task has no properties to use by a build script.

- **compileKonan**. Aggregate task to build all the Kotlin/Native artifacts for all available targets. `konan.build.targets` project property also may be used to override the target list. The task has no properties that can be used by a build script.
- **run<ArtifactName>**. Such a task is created for each executable supported by the current host and allows you to run this executable. The task is an instance of Gradle's [Exec](#) so it supports all the settings provided by `Exec`. Additionally, run parameters may be passed to the task using the `runArgs` project property:

```
./gradlew runFoo -PrunArgs='foo bar'
```

The plugin also edits the default `build` and `clean` tasks so that the first one allows you to build all the artifacts supported (it's dependent on the `compileKonan` task) and the second one removes the files created by the Kotlin/Native build.

Building dynamic libraries and frameworks

Kotlin/Native supports building artifacts to be used by other native languages. There are two types of such artifacts: Objective-C framework and dynamic library.

Dynamic library

A dynamic library may be built using the `dynamic` artifact block. This block contains the same options as the other ones (except `interop`) allowing you to specify source files, compiler options, and the libraries used. Each task building a dynamic library produces two files: the library itself (a `*.so` / `*.dylib` / `*.dll` file depending on the target platform) and a C language header. Both of them may be accessed via properties of a building task (both properties have type `File`):

```
konanArtifacts {
    // Build a dynamic library
    dynamic('foo') { /* ... */ }
}

konanArtifacts.foo.getByTarget('host').artifact // Points to the library file
konanArtifacts.foo.getByTarget('host').headerFile // Points to the header file
```

Using a dynamic library is shown in the [python extension sample](#).

Framework

An Objective-C framework can be built using the `framework` artifact block. This block contains the same options as other ones. One may access the framework built using `artifact` property of the building task (see the [Tasks](#) section). Unlike other artifacts this property points to a directory instead of a regular file.

```
konanArtifacts {
    // Build an Objective-C framework
    framework('foo') { /* ... */ }
}

konanArtifacts.foo.getByTarget('host').artifact // Points to the framework directory
```

Using a framework is shown in the [calculator sample](#).

Additional options

You can also pass additional command line keys to the compiler or cinterop tool using the `extraOpts` expression available in the artifact configuration script block. For example this sample enables a verbose output for a link and bitcode generation stages and prints the execution time for all the compiler phases:

```
konanArtifacts {
    program('foo') {
        extraOpts '--verbose', 'linker', '--verbose', 'bitcode', '--time'
    }
}
```

Any command line key supported by the according tool (compiler or cinterop) can be used. Some of them are listed in the tables below.

Compiler additional options

| Key | Description |
|--------------------------------------|---|
| <code>--disable <Phase></code> | Disable backend phase |
| <code>--enable <Phase></code> | Enable backend phase |
| <code>--list_phases</code> | List all backend phases |
| <code>--time</code> | Report execution time for compiler phases |
| <code>--verbose <Phase></code> | Trace phase execution |
| <code>-verbose</code> | Enable verbose logging output |

Cinterop additional options

| Key | Description |
|---------------------------------------|--|
| <code>-verbose <boolean></code> | Increase verbosity |
| <code>-shims <boolean></code> | Add generation of shims tracing native library calls |

Plugin DSL

// Default targets to build for.

```
konan.targets = ['macbook', 'linux', 'wasm32']
```

// Language and API version.

```
konan.languageVersion = 'version'
```

```
konan.apiVersion = 'version'
```

```
konanArtifacts {
    // Targets to build this artifact for (optional, override the konan.targets list)
    program('foo', targets: ['android_arm32', 'android_arm64']) {

        // Directory with source files. The default path is src/main/kotlin.
        srcDir 'src/other'

        // Source files.
        srcFiles project.fileTree('src')
        srcFiles 'foo.kt', 'bar.kt'

        // Custom output artifact name (without extension).
        // The default is a name of the artifact
        artifactName 'customName'

        // Base Directory for the output artifacts.
        // Separate subdirectories for each target will be created
        // The default is build/konan/bin
        baseDir 'path/to/output/dir'

        libraries {
            // Library files
            file 'foo.klib'
            files 'file1.klib', 'file2.klib'
            files project.files('file3.klib', 'file4.klib')

            // An artifact from the current project
            artifact konanArtifacts.bar
            artifact 'baz'

            // An artifact from another project
            artifact project(':path:to:a:project'), 'artifactName'

            // All libraries from another project
            allLibrariesFrom project(':some:project')

            // Only interoperability libraries from another project
            allInteropLibrariesFrom project(':some:interop:project')

            // Named libraries for search in repositories
        }
    }
}
```

```

    klib 'foo'
    klib 'bar', 'baz'

    // Custom repository paths
    useRepo 'path/to/a/repo'
    useRepos 'another/repo/1', 'another/repo/2'
}

// A native library (*.bc) for linking.
nativeLibrary project.file('path/to/native/library.bc')
nativeLibraries 'library1.bc', 'library2.bc'

noStdLib true           // Don't link with stdlib (true/false).
enableOptimizations true // Enable compiler optimizations (true/false).
enableAssertions true   // Enable assertions in binaries generated (true/false).
enableDebug true        // Enable debugging for binaries generated (true/false).
noDefaultLibs true      // Don't link with default libraries

// Custom entry point
entryPoint 'org.demo.foo'

// Arguments to be passed to a linker.
linkerOpts 'Some linker option', 'More linker options'

// Print all parameters during the build.
dumpParameters true

// Print time of compilation phases (equivalent of the `--time` command line option).
measureTime true

// Add the `anotherTask` to the compilation task dependencies.
dependsOn anotherTask

// Pass additional command line options to the compiler.
extraOpts '--time', '--verbose', 'linker'

// Additional configuration for Linux.
target('linux') {
    // Exact output directory for a file compile for the given target
    // The default is <baseDir>/<target>
    destinationDir 'exact/output/path'

    // Also all options described for this artifact above are available here.
}
}

library('bar') {
    // Library has the same parameters as an executable
    // The default baseDir is build/konan/libs
}

bitcode('baz') {
    // Bitcode has the same parameters as an executable
    // The default baseDir is build/konan/bitcode
}

dynamic('quux') {
    // Dynamic library has the same parameters as an executable
    // The default baseDir is build/konan/bin
}

framework('quuux') {
    // Framework has the same parameters as an executable
    // The default baseDir is build/konan/bin
}

```

```

interop('qux') {
    // Def-file describing the native API.
    // The default path is src/main/c_interop/<interop-name>.def
    defFile project.file("deffile.def")

    // Custom output artifact name (without extension).
    // The default is a name of the artifact
    artifactName 'customName'

    // Base Directory for the output artifacts.
    // Separate subdirectories for each target will be created
    // The default is build/konan/libs
    baseDir 'path/to/output/dir'

    // Package to place the Kotlin API generated.
    packageName 'org.sample'

    libraries {
        // All library options from the executable example above are available here.
    }

    // Options to be passed to compiler and linker by cinterop tool.
    compilerOpts 'Options for native stubs compilation'
    linkerOpts 'Options for native stubs'

    // Additional headers to parse.
    headers project.files('header1.h', 'header2.h')

    // Directories to look for headers.
    includeDirs {
        // All objects accepted by the Project.file method may be used with both options.

        // Directories for header search (an analogue of the -I<path> compiler option).
        allHeaders 'path1', 'path2'

        // Additional directories to search headers listed in the 'headerFilter' def-file option.
        // -headerFilterAdditionalSearchPrefix command line option analogue.
        headerFilterOnly 'path1', 'path2'
    }
    // A shortcut for includeDirs.allHeaders.
    includeDirs "include/directory" "another/directory"

    // Additional files to link with native stubs.
    link <files which will be linked with native stubs>

    // Print all parameters during the build.
    dumpParameters true

    // Add the `anotherTask` to the stub generation task dependencies.
    dependsOn anotherTask

    // Pass additional command line options to the cinterop tool.
    extraOpts '-shims', 'true'

    // Additional configuration for Linux.
    target('linux') {
        // Exact output directory for a file compile for the given target
        // The default is <baseDir>/<target>
        destinationDir 'exact/output/path'

        // Also all options described for this artifact above are available here.
    }
}
}

```

Multiplatform DSL

apply plugin: 'konan'

// In this example common code is located in 'foo' and 'bar' source sets of ':common' project.

```
konanArtifacts {
    // All the artifact types except interop libraries may use common modules.
    program('foo') {
        // All artifact settings described above are available here.

        // Enable multiplatform support for this artifact.
        enableMultiplatform true

        // Set a custom names for source sets used as a common module.
        // The default source set is 'main'
        commonSourceSets 'foo', 'bar'
    }
}

dependencies {
    // Use the ':foo' project as a common project for multiplatform build.
    expectedBy project(':common')
}
```

Publishing to Maven

Publishing the Kotlin/Native artifacts depends on mechanisms which were introduced in Gradle Native support, e.g. Gradle's metadata feature. So some additional steps are required. First of all, the gradle version shouldn't be less than the gradle version of kotlin native plugin that it depends on (currently Gradle 4.7). Before Gradle 5.0, the feature [GRADLE_METADATA](#) should be enabled for the build. e.g. in settings.gradle

```
enableFeaturePreview('GRADLE_METADATA')
```

Some Maven repositories require some declarations in the `pom` files, that should be present in all auxiliary `pom` files (platform x build types). To meet this requirement the Kotlin/Native plugin has the following syntax to do it:

```
konanArtifacts {
    interop('libcurl') {
        target('linux') {
            includeDirs.headerFilterOnly '/usr/include'
        }
        target('macbook') {
            includeDirs.headerFilterOnly '/opt/local/include', '/usr/local/include'
        }
        pom {
            withXml {
                def root = asNode()
                root.appendNode('name', 'libcurl interop library')
                root.appendNode('description', 'A library providing interoperability with host libcurl')
            }
        }
    }
}
```

In this example `name` and `description` tags will be added to each generated `pom` file for *libcurl* published artifact.

Experimental plugin

In the version 0.8 a new experimental plugin has been introduced. It is integrated with new Gradle support for native languages and provides a new DSL which is much closer to the DSL of Kotlin/JVM and Kotlin/JS plugins than the old one. The plugin is available at the Gradle plugin portal:

```
plugins {
    id "org.jetbrains.kotlin.platform.native" version "0.9"
}
```

Source management

Source management in the `kotlin.platform.native` plugin is uniform with other Kotlin plugins and is based on source sets. A source set is a group of Kotlin/Native source which may contain both common and platform-specific code. The plugin provides a top-level script block `sourceSets` allowing you to configure source sets. Also it creates the default source sets `main` and `test` (for production and test code respectively). By default the production sources are located in `src/main/kotlin` and the test sources - in `src/test/kotlin`.

```
sourceSets {  
    // Adding target-independent sources.  
    main.kotlin.srcDirs += 'src/main/mySources'  
  
    // Adding Linux-specific code. It will be compiled in Linux binaries only.  
    main.target('linux_x64').srcDirs += 'src/main/linux'  
}
```

Targets and output kinds

By default the plugin creates software components for the main and test source sets. You can access them via the `components` container provided by Gradle or via the `component` property of a corresponding source set:

```
// Main component.  
components.main  
sourceSets.main.component  
  
// Test component.  
components.test  
sourceSets.test.component
```

Components allow you to specify:

- Targets (e.g. Linux/x64 or iOS/arm64 etc)
- Output kinds (e.g. executable, library, framework etc)
- Dependencies (including interop ones)

Targets can be specified by setting a corresponding component property:

```
components.main {  
    // Compile this component for 64-bit MacOS, Linux and Windows.  
    targets = ['macos_x64', 'linux_x64', 'mingw_x64']  
}
```

The plugin uses the same notation as the compiler. By default, test component uses the same targets as specified for the main one.

Output kinds can also be specified using a special property:

```
components.main {  
    // Compile the component into an executable and a Kotlin/Native library.  
    outputKinds = [EXECUTABLE, KLIBRARY]  
}
```

All constants used here are available inside a component configuration script block. The plugin supports producing binaries of the following kinds:

- `EXECUTABLE` - an executable file;
- `KLIBRARY` - a Kotlin/Native library (*.klib);
- `FRAMEWORK` - an Objective-C framework;
- `DYNAMIC` - shared native library;
- `STATIC` - static native library.

Also each binary is built in two variants (build types): `debug` (debuggable, not optimized) and `release` (not debuggable, optimized).

Compile tasks

The plugin creates a compilation task for each combination of the target, output kind, and build type. The tasks have the following naming convention:

`compile<ComponentName><BuildType><OutputKind><Target>KotlinNative`

For example `compileDebugKlibraryMacos_x64KotlinNative`, `compileTestDebugKotlinNative`.

The name contains the following parts (some of them may be empty):

- `<ComponentName>` - name of a component. Empty for the main component.
- `<BuildType>` - `Debug` or `Release`.
- `<OutputKind>` - output kind name, e.g. `Executable` or `Dynamic`. Empty if the component has only one output kind.
- `<Target>` - target the component is built for, e.g. `Macos_x64` or `Wasm32`. Empty if the component is built only for one target.

Also the plugin creates a number of aggregate tasks allowing you to build all the binaries for a build type (e.g. `assembleAllDebug`) or all the binaries for a particular target (e.g. `assembleAllWasm32`).

Basic lifecycle tasks like `assemble`, `build`, and `clean` are also available.

Running tests

The plugin builds a test executable for all the targets specified for the `test` component. If the current host platform is included in this list the test running tasks are also created. To run tests, execute the standard lifecycle `check` task:

```
./gradlew check
```

Dependencies

The plugin allows you to declare dependencies on files and other projects using traditional Gradle's mechanism of configurations. The plugin supports Kotlin multiplatform projects allowing you to declare the `expectedBy` dependencies

```
dependencies {
    implementation files('path/to/file/dependencies')
    implementation project('library')
    testImplementation project('testLibrary')
    expectedBy project('common')
}
```

It's possible to depend on a Kotlin/Native library published earlier in a maven repo. The plugin relies on Gradle's [metadata](#) support so the corresponding feature must be enabled. Add the following line in your `settings.gradle`:

```
enableFeaturePreview('GRADLE_METADATA')
```

Now you can declare a dependency on a Kotlin/Native library in the traditional `group:artifact:version` notation:

```
dependencies {
    implementation 'org.sample.test:mylibrary:1.0'
    testImplementation 'org.sample.test:testlibrary:1.0'
}
```

`implementation`-dependencies are also available in the component block:

```
components.main {
    dependencies {
        implementation 'org.sample.test:mylibrary:1.0'
    }
}

components.test {
    dependencies {
        implementation 'org.sample.test:testlibrary:1.0'
    }
}
```

Using cinterop

It's possible to declare a cinterop dependency for a component. The DSL here is similar to the one used in the `konan` plugin:

```
components.main {
    dependencies {
        cinterop('mystdio') {
            // src/main/c_interop/mystdio.def is used as a def file.

            // Set up compiler options
            compilerOpts '-I/my/include/path'

            // It's possible to set up different options for different targets
            target('linux') {
                compilerOpts '-I/linux/include/path'
            }
        }
    }
}
```

Here an interop library will be built and added in the component dependencies.

Often it's necessary to specify target-specific linker options for a Kotlin/Native binary using an interop. It can be done using the `target` script block:

```
components.main {
    target('linux') {
        linkerOpts '-L/path/to/linux/libs'
    }
}
```

Also the `allTargets` block is available

```
components.main {
    // Configure all targets.
    allTargets {
        linkerOpts '-L/path/to/libs'
    }
}
```

Publishing

In the presence of `maven-publish` plugin the publications for all the binaries built are created. The plugin uses Gradle metadata to publish the artifacts so this feature must be enabled (see the [dependencies](#) section).

Now you can publish the artifacts with the standard Gradle `publish` task:

```
./gradlew publish
```

Only `EXECUTABLE` and `KLIBRARY` binaries are published currently.

The plugin allows you to customize the pom generated for the publication with the `pom` code block available for every component:

```
components.main {
    pom {
        withXml {
            def root = asNode()
            root.appendNode('name', 'My library')
            root.appendNode('description', 'A Kotlin/Native library')
        }
    }
}
```

DSL example

In this section a commented DSL is shown. See also the example projects that use this plugin, e.g. [Kotlinx.coroutines](#), [MPP http client](#)

```

plugins {
    id "org.jetbrains.kotlin.platform.native" version "0.9"
}

sourceSets.main {
    // Plugin uses Gradle's source directory sets here,
    // so all the DSL methods available in SourceDirectorySet can be called here.
    // Platform independent sources.
    kotlin.srcDirs += 'src/main/customDir'

    // Linux-specific sources
    target('linux').srcDirs += 'src/main/linux'
}

components.main {

    // Set up targets
    targets = ['linux_x64', 'macos_x64', 'mingw_x64']

    // Set up output kinds
    outputKinds = [EXECUTABLE, KLIBRARY, FRAMEWORK, DYNAMIC, STATIC]

    // Specify custom entry point for executables
    entryPoint = "org.test.myMain"

    // Target-specific options
    target('linux_x64') {
        linkerOpts '-L/linux/lib/path'
    }

    // Targets independent options
    allTargets {
        linkerOpts '-L/common/lib/path'
    }

    dependencies {

        // Dependency on a published Kotlin/Native library.
        implementation 'org.test:mylib:1.0'

        // Dependency on a project
        implementation project('library')

        // Cinterop dependency
        cinterop('interop-name') {
            // Def-file describing the native API.
            // The default path is src/main/c_interop/<interop-name>.def
            defFile project.file("deffile.def")

            // Package to place the Kotlin API generated.
            packageName 'org.sample'

            // Options to be passed to compiler and linker by cinterop tool.
            compilerOpts 'Options for native stubs compilation'
            linkerOpts 'Options for native stubs'

            // Additional headers to parse.
            headers project.files('header1.h', 'header2.h')

            // Directories to look for headers.
            includeDirs {
                // All objects accepted by the Project.file method may be used with both options.

                // Directories for header search (an analogue of the -I<path> compiler option).
                allHeaders 'path1', 'path2'
            }
        }
    }
}

```

```

        // Additional directories to search headers listed in the 'headerFilter' def-file option.
        // -headerFilterAdditionalSearchPrefix command line option analogue.
        headerFilterOnly 'path1', 'path2'
    }
    // A shortcut for includeDirs.allHeaders.
    includeDirs "include/directory" "another/directory"

    // Pass additional command line options to the cinterop tool.
    extraOpts '-shims', 'true'

    // Additional configuration for Linux.
    target('linux') {
        compilerOpts 'Linux-specific options'
    }
}

// Additional pom settings for publication.
pom {
    withXml {
        def root = asNode()
        root.appendNode('name', 'My library')
        root.appendNode('description', 'A Kotlin/Native library')
    }
}

// Additional options passed to the compiler.
extraOpts '--time'
}

```

type: doc layout: reference title: "Debugging" —

Debugging

Currently the Kotlin/Native compiler produces debug info compatible with the DWARF 2 specification, so modern debugger tools can perform the following operations:

- breakpoints
- stepping
- inspection of type information
- variable inspection

Producing binaries with debug info with Kotlin/Native compiler

To produce binaries with the Kotlin/Native compiler it's sufficient to use the `-g` option on the command line.

Example:

```
0:b-debugger-fixes:minamoto@unit-703(0)# cat - > hello.kt
fun main(args: Array<String>) {
    println("Hello world")
    println("I need your clothes, your boots and your motorcycle")
}
0:b-debugger-fixes:minamoto@unit-703(0)# dist/bin/konanc -g hello.kt -o terminator
KtFile: hello.kt
0:b-debugger-fixes:minamoto@unit-703(0)# lldb terminator.kexe
(lldb) target create "terminator.kexe"
Current executable set to 'terminator.kexe' (x86_64).
(lldb) b kfun:main(kotlin.Array<kotlin.String>)
Breakpoint 1: where = terminator.kexe`kfun:main(kotlin.Array<kotlin.String>) + 4 at hello.kt:2, address =
0x000000001000012e4
(lldb) r
Process 28473 launched: '/Users/minamoto/ws/.git-trees/debugger-fixes/terminator.kexe' (x86_64)
Process 28473 stopped
* thread #1, queue = 'com.apple.main-thread', stop reason = breakpoint 1.1
    frame #0: 0x000000001000012e4 terminator.kexe`kfun:main(kotlin.Array<kotlin.String>) at hello.kt:2
  1   fun main(args: Array<String>) {
-> 2       println("Hello world")
    3       println("I need your clothes, your boots and your motorcycle")
    4   }
(lldb) n
Hello world
Process 28473 stopped
* thread #1, queue = 'com.apple.main-thread', stop reason = step over
    frame #0: 0x000000001000012f0 terminator.kexe`kfun:main(kotlin.Array<kotlin.String>) at hello.kt:3
  1   fun main(args: Array<String>) {
    2       println("Hello world")
-> 3       println("I need your clothes, your boots and your motorcycle")
    4   }
(lldb)
```

Breakpoints

Modern debuggers provide several ways to set a breakpoint, see below for a tool-by-tool breakdown:

lldb

- by name

```
(lldb) b -n kfun:main(kotlin.Array<kotlin.String>)
Breakpoint 4: where = terminator.kexe`kfun:main(kotlin.Array<kotlin.String>) + 4 at hello.kt:2, address =
0x000000001000012e4
```

-n is optional, this flag is applied by default

— by location (filename, line number)

```
(lldb) b -f hello.kt -l 1
```

```
Breakpoint 1: where = terminator.kexe`kfun:main(kotlin.Array<kotlin.String>) + 4 at hello.kt:2, address = 0x00000001000012e4
```

— by address

```
(lldb) b -a 0x00000001000012e4
```

```
Breakpoint 2: address = 0x00000001000012e4
```

— by regex, you might find it useful for debugging generated artifacts, like lambda etc. (where used # symbol in name).

```
3: regex = 'main\(', locations = 1
```

```
3.1: where = terminator.kexe`kfun:main(kotlin.Array<kotlin.String>) + 4 at hello.kt:2, address = terminator.kexe[0x00000001000012e4], unresolved, hit count = 0
```

gdb

— by regex

```
(gdb) rbreak main(
```

```
Breakpoint 1 at 0x1000109b4
```

```
struct ktype:kotlin.Unit &kfun:main(kotlin.Array<kotlin.String>);
```

— by name **unusable**, because ; is a separator for the breakpoint by location

```
(gdb) b kfun:main(kotlin.Array<kotlin.String>)
```

```
No source file named kfun.
```

```
Make breakpoint pending on future shared library load? (y or [n]) y
```

```
Breakpoint 1 (kfun:main(kotlin.Array<kotlin.String>)) pending
```

— by location

```
(gdb) b hello.kt:1
```

```
Breakpoint 2 at 0x100001704: file /Users/minamoto/ws/.git-trees/hello.kt, line 1.
```

— by address

```
(gdb) b *0x100001704
```

```
Note: breakpoint 2 also set at pc 0x100001704.
```

```
Breakpoint 3 at 0x100001704: file /Users/minamoto/ws/.git-trees/hello.kt, line 2.
```

Stepping

Stepping functions works mostly the same way as for C/C++ programs

Variable inspection

Variable inspections for var variables works out of the box for primitive types. For non-primitive types there are custom pretty printers for lldb in `konan_lldb.py`:

```

λ cat main.kt | nl
  1 fun main(args: Array<String>) {
  2     var x = 1
  3     var y = 2
  4     var p = Point(x, y)
  5     println("p = $p")
  6 }

  7 data class Point(val x: Int, val y: Int)

λ lldb ./program.kexe -o 'b main.kt:5' -o
(lldb) target create "./program.kexe"
Current executable set to './program.kexe' (x86_64).
(lldb) b main.kt:5
Breakpoint 1: where = program.kexe`kfun:main(kotlin.Array<kotlin.String>) + 289 at main.kt:5, address =
0x000000000040af11
(lldb) r
Process 4985 stopped
* thread #1, name = 'program.kexe', stop reason = breakpoint 1.1
   frame #0: program.kexe`kfun:main(kotlin.Array<kotlin.String>) at main.kt:5
   2     var x = 1
   3     var y = 2
   4     var p = Point(x, y)
->  5     println("p = $p")
   6 }
   7
   8     data class Point(val x: Int, val y: Int)

Process 4985 launched: './program.kexe' (x86_64)
(lldb) fr var
(int) x = 1
(int) y = 2
(ObjHeader *) p = 0x00000000007643d8
(lldb) command script import dist/tools/konan_lldb.py
(lldb) fr var
(int) x = 1
(int) y = 2
(ObjHeader *) p = Point(x=1, y=2)
(lldb) p p
(ObjHeader *) $2 = Point(x=1, y=2)
(lldb)

```

Getting representation of the object variable (var) could also be done using the built-in runtime function `Konan_DebugPrint` (this approach also works for gdb, using a module of command syntax):

```

0:b-debugger-fixes:minamoto@unit-703(0)# cat ../debugger-plugin/1.kt | nl -p
 1 fun foo(a:String, b:Int) = a + b
 2 fun one() = 1
 3 fun main(arg:Array<String>) {
 4     var a_variable = foo("(a_variable) one is ", 1)
 5     var b_variable = foo("(b_variable) two is ", 2)
 6     var c_variable = foo("(c_variable) two is ", 3)
 7     var d_variable = foo("(d_variable) two is ", 4)
 8     println(a_variable)
 9     println(b_variable)
10     println(c_variable)
11     println(d_variable)
12 }
0:b-debugger-fixes:minamoto@unit-703(0)# lldb ./program.kexe -o 'b -f 1.kt -l 9' -o r
(lldb) target create "./program.kexe"
Current executable set to './program.kexe' (x86_64).
(lldb) b -f 1.kt -l 9
Breakpoint 1: where = program.kexe`kfun:main(kotlin.Array<kotlin.String>) + 463 at 1.kt:9, address =
0x0000000100000dbf
(lldb) r
(a_variable) one is 1
Process 80496 stopped
* thread #1, queue = 'com.apple.main-thread', stop reason = breakpoint 1.1
   frame #0: 0x0000000100000dbf program.kexe`kfun:main(kotlin.Array<kotlin.String>) at 1.kt:9
       6     var c_variable = foo("(c_variable) two is ", 3)
       7     var d_variable = foo("(d_variable) two is ", 4)
       8     println(a_variable)
->  9     println(b_variable)
      10     println(c_variable)
      11     println(d_variable)
      12 }

Process 80496 launched: './program.kexe' (x86_64)
(lldb) expression -- Konan_DebugPrint(a_variable)
(a_variable) one is 1(KInt) $0 = 0
(lldb)

```

Known issues

— performance of Python bindings.

Note: Supporting the DWARF 2 specification means that the debugger tool recognizes Kotlin as C89, because before the DWARF 5 specification, there is no identifier for the Kotlin language type in specification.

Q: How do I run my program?

A: Define a top level function `fun main(args: Array<String>)`, please ensure it's not in a package. Also compiler switch `-entry` could be used to make any function taking `Array<String>` and return `Unit` as an entry point.

Q: What is Kotlin/Native memory management model?

A: Kotlin/Native provides an automated memory management scheme, similar to what Java or Swift provides. The current implementation includes an automated reference counter with a cycle collector to collect cyclical garbage.

Q: How do I create a shared library?

A: Use the `-produce dynamic` compiler switch, or `konanArtifacts { dynamic('foo') {} }` in Gradle. It will produce a platform-specific shared object (.so on Linux, .dylib on macOS, and .dll on Windows targets) and a C language header, allowing the use of all public APIs available in your Kotlin/Native program from C/C++ code. See `samples/python_extension` for an example of using such a shared object to provide a bridge between Python and Kotlin/Native.

Q: How do I create a static library or an object file?

A: Use the `-produce static` compiler switch, or `konanArtifacts { static('foo') {} }` in Gradle. It will produce a platform-specific static object (.a library format) and a C language header, allowing you to use all the public APIs available in your Kotlin/Native program from C/C++ code.

Q: How do I run Kotlin/Native behind a corporate proxy?

A: As Kotlin/Native needs to download a platform specific toolchain, you need to specify `-Dhttp.proxyHost=xxx -Dhttp.proxyPort=xxx` as the compiler's or `gradlew` arguments, or set it via the `JAVA_OPTS` environment variable.

Q: How do I specify a custom Objective-C prefix/name for my Kotlin framework?

A: Use the `-module_name` compiler option or matching Gradle DSL statement, i.e.

```
framework("MyCustomFramework") {  
    extraOpts '-module_name', 'TheName'  
}
```

Q: Why do I see InvalidMutabilityException?

A: It likely happens, because you are trying to mutate a frozen object. An object can transfer to the frozen state either explicitly, as objects reachable from objects on which the `kotlin.native.concurrent.freeze` is called, or implicitly (i.e. reachable from `enum` or global singleton object - see the next question).

Q: How do I make a singleton object mutable?

A: Currently, singleton objects are immutable (i.e. frozen after creation), and it's generally considered good practise to have the global state immutable. If for some reason you need a mutable state inside such an object, use the `@konan.ThreadLocal` annotation on the object. Also the `kotlin.native.concurrent.AtomicReference` class could be used to store different pointers to frozen objects in a frozen object and automatically update them.

Q: How can I compile my project against the Kotlin/Native master?

A: We release dev builds frequently, usually at least once a week. You can check the [list of available versions](#). But if we recently fixed an issue and you want to check it before a release is done, you can do:

- For the CLI, you can compile using gradle as stated in the README (and if you get errors, you can try to do a `./gradlew clean`):
- For Gradle, you can use [Gradle composite builds](#) like this:

Tools

Documenting Kotlin Code

The language used to document Kotlin code (the equivalent of Java's JavaDoc) is called **KDoc**. In its essence, KDoc combines JavaDoc's syntax for block tags (extended to support Kotlin's specific constructs) and Markdown for inline markup.

Generating the Documentation

Kotlin's documentation generation tool is called [Dokka](#). See the [Dokka README](#) for usage instructions.

Dokka has plugins for Gradle, Maven and Ant, so you can integrate documentation generation into your build process.

KDoc Syntax

Just like with JavaDoc, KDoc comments start with `/**` and end with `*/`. Every line of the comment may begin with an asterisk, which is not considered part of the contents of the comment.

By convention, the first paragraph of the documentation text (the block of text until the first blank line) is the summary description of the element, and the following text is the detailed description.

Every block tag begins on a new line and starts with the `@` character.

Here's an example of a class documented using KDoc:

```
/**
 * A group of *members*.
 *
 * This class has no useful logic; it's just a documentation example.
 *
 * @param T the type of a member in this group.
 * @property name the name of this group.
 * @constructor Creates an empty group.
 */
class Group<T>(val name: String) {
    /**
     * Adds a [member] to this group.
     * @return the new size of the group.
     */
    fun add(member: T): Int { ... }
}
```

Block Tags

KDoc currently supports the following block tags:

`@param <name>`

Documents a value parameter of a function or a type parameter of a class, property or function. To better separate the parameter name from the description, if you prefer, you can enclose the name of the parameter in brackets. The following two syntaxes are therefore equivalent:

```
@param name description.
@param[name] description.
```

`@return`

Documents the return value of a function.

`@constructor`

Documents the primary constructor of a class.

`@receiver`

Documents the receiver of an extension function.

`@property <name>`

Documents the property of a class which has the specified name. This tag can be used for documenting properties declared in the primary constructor, where putting a doc comment directly before the property definition would be awkward.

`@throws <class>, @exception <class>`

Documents an exception which can be thrown by a method. Since Kotlin does not have checked exceptions, there is also no expectation that all possible exceptions are documented, but you can still use this tag when it provides useful information for users of the class.

`@sample <identifier>`

Embeds the body of the function with the specified qualified name into the documentation for the current element, in order to show an example of how the element could be used.

`@see <identifier>`

Adds a link to the specified class or method to the **See Also** block of the documentation.

`@author`


Specifies the author of the element being documented.

`@since`

Specifies the version of the software in which the element being documented was introduced.

`@suppress`

Excludes the element from the generated documentation. Can be used for elements which are not part of the official API of a module but still have to be visible externally.

 KDoc does not support the `@deprecated` tag. Instead, please use the `@Deprecated` annotation.

Inline Markup

For inline markup, KDoc uses the regular [Markdown](#) syntax, extended to support a shorthand syntax for linking to other elements in the code.

Linking to Elements

To link to another element (class, method, property or parameter), simply put its name in square brackets:

Use the method `[foo]` for this purpose.

If you want to specify a custom label for the link, use the Markdown reference-style syntax:

Use `[this method][foo]` for this purpose.

You can also use qualified names in the links. Note that, unlike JavaDoc, qualified names always use the dot character to separate the components, even before a method name:

Use `[kotlin.reflect.KClass.properties]` to enumerate the properties of the class.

Names in links are resolved using the same rules as if the name was used inside the element being documented. In particular, this means that if you have imported a name into the current file, you don't need to fully qualify it when you use it in a KDoc comment.

Note that KDoc does not have any syntax for resolving overloaded members in links. Since the Kotlin documentation generation tool puts the documentation for all overloads of a function on the same page, identifying a specific overloaded function is not required for the link to work.

Module and Package Documentation

Documentation for a module as a whole, as well as packages in that module, is provided as a separate Markdown file, and the paths to that file is passed to Dokka using the `-include` command line parameter or the corresponding parameters in Ant, Maven and Gradle plugins.

Inside the file, the documentation for the module as a whole and for individual packages is introduced by the corresponding first-level headings. The text of the heading must be "Module `<module name>`" for the module, and "Package `<package qualified name>`" for a package.

Here's an example content of the file:

```
# Module kotlin-demo
```

The module shows the Dokka syntax usage.

```
# Package org.jetbrains.kotlin.demo
```

Contains assorted useful stuff.

```
## Level 2 heading
```

Text after this heading is also part of documentation for ``org.jetbrains.kotlin.demo``

```
# Package org.jetbrains.kotlin.demo2
```

Useful stuff in another package.

Annotation Processing with Kotlin

Annotation processors (see [JSR 269](#)) are supported in Kotlin with the *kapt* compiler plugin.

Being short, you can use libraries such as [Dagger](#) or [Data Binding](#) in your Kotlin projects.

Please read below about how to apply the *kapt* plugin to your Gradle/Maven build.

Using in Gradle

Apply the `kotlin-kapt` Gradle plugin:

```
apply plugin: 'kotlin-kapt'
```

Or you can apply it using the plugins DSL:

```
plugins {  
    id "org.jetbrains.kotlin.kapt" version "1.2.70"  
}
```

Then add the respective dependencies using the `kapt` configuration in your `dependencies` block:

```
dependencies {  
    kapt 'groupId:artifactId:version'  
}
```

If you previously used the [Android support](#) for annotation processors, replace usages of the `annotationProcessor` configuration with `kapt`. If your project contains Java classes, `kapt` will also take care of them.

If you use annotation processors for your `androidTest` or `test` sources, the respective `kapt` configurations are named `kaptAndroidTest` and `kaptTest`. Note that `kaptAndroidTest` and `kaptTest` extends `kapt`, so you can just provide the `kapt` dependency and it will be available both for production sources and tests.

Annotation Processor Arguments

Use `arguments {}` block to pass arguments to annotation processors:

```
kapt {  
    arguments {  
        arg("key", "value")  
    }  
}
```

Java Compiler Options

Kapt uses Java compiler to run annotation processors.

Here is how you can pass arbitrary options to javac:

```
kapt {  
    javacOptions {  
        // Increase the max count of errors from annotation processors.  
        // Default is 100.  
        option("-Xmaxerrs", 500)  
    }  
}
```

Non Existent Type Correction

Some annotation processors (such as `AutoFactory`) rely on precise types in declaration signatures. By default, Kapt replaces every unknown type (including types for the generated classes) to `NonExistentClass`, but you can change this behavior. Add the additional flag to the `build.gradle` file to enable error type inferring in stubs:

```
kapt {  
    correctErrorTypes = true  
}
```

Using in Maven

Add an execution of the `kapt` goal from `kotlin-maven-plugin` before `compile` :

```
<execution>
  <id>kapt</id>
  <goals>
    <goal>kapt</goal>
  </goals>
  <configuration>
    <sourceDirs>
      <sourceDir>src/main/kotlin</sourceDir>
      <sourceDir>src/main/java</sourceDir>
    </sourceDirs>
    <annotationProcessorPaths>
      <!-- Specify your annotation processors here. -->
      <annotationProcessorPath>
        <groupId>com.google.dagger</groupId>
        <artifactId>dagger-compiler</artifactId>
        <version>2.9</version>
      </annotationProcessorPath>
    </annotationProcessorPaths>
  </configuration>
</execution>
```

You can find a complete sample project showing the use of Kotlin, Maven and Dagger in the [Kotlin examples repository](#).

Please note that `kapt` is still not supported for IntelliJ IDEA's own build system. Launch the build from the "Maven Projects" toolbar whenever you want to re-run the annotation processing.

Using in CLI

Kapt compiler plugin is available in the binary distribution of the Kotlin compiler.

You can attach the plugin by providing the path to its JAR file using the `Xplugin` `kotlinc` option:

```
-Xplugin=$KOTLIN_HOME/lib/kotlin-annotation-processing.jar
```

Here is a list of the available options:

- `sources` (*required*): An output path for the generated files.
- `classes` (*required*): An output path for the generated class files and resources.
- `stubs` (*required*): An output path for the stub files. In other words, some temporary directory.
- `incrementalData` : An output path for the binary stubs.
- `apclasspath` (*repeatable*): A path to the annotation processor JAR. Pass as many `apclasspath` options as many JARs you have.
- `apoptions` : A base64-encoded list of the annotation processor options. See [AP/javac options encoding](#) for more information.
- `javacArguments` : A base64-encoded list of the options passed to `javac`. See [AP/javac options encoding](#) for more information.
- `processors` : A comma-specified list of annotation processor qualified class names. If specified, `kapt` does not try to find annotation processors in `apclasspath` .
- `verbose` : Enable verbose output.
- `aptMode` (*required*)
 - `stubs` - only generate stubs needed for annotation processing;
 - `apt` - only run annotation processing;
 - `stubsAndApt` - generate stubs and run annotation processing.

— `correctErrorTypes` : See [below](#). Disabled by default.

The plugin option format is: `-P plugin:<plugin id>:<key>=<value>`. Options can be repeated.

An example:

```
-P plugin:org.jetbrains.kotlin.kapt3:sources=build/kapt/sources
-P plugin:org.jetbrains.kotlin.kapt3:classes=build/kapt/classes
-P plugin:org.jetbrains.kotlin.kapt3:stubs=build/kapt/stubs

-P plugin:org.jetbrains.kotlin.kapt3:apclasspath=lib/ap.jar
-P plugin:org.jetbrains.kotlin.kapt3:apclasspath=lib/anotherAp.jar

-P plugin:org.jetbrains.kotlin.kapt3:correctErrorTypes=true
```

Generating Kotlin Sources

Kapt can generate Kotlin sources. Just write the generated Kotlin source files to the directory specified by `processingEnv.options["kapt.kotlin.generated"]`, and these files will be compiled together with the main sources.

You can find the complete sample in the [kotlin-examples](#) Github repository.

Note that Kapt does not support multiple rounds for the generated Kotlin files.

AP/Javac Options Encoding

`apoptions` and `javacArguments` CLI options accept an encoded map of options.

Here is how you can encode options by yourself:

```
fun encodeList(options: Map<String, String>): String {
    val os = ByteArrayOutputStream()
    val oos = ObjectOutputStream(os)

    oos.writeInt(options.size)
    for ((key, value) in options.entries) {
        oos.writeUTF(key)
        oos.writeUTF(value)
    }

    oos.flush()
    return Base64.getEncoder().encodeToString(os.toByteArray())
}
```

Using Gradle

In order to build Kotlin with Gradle you should [set up the *kotlin-gradle* plugin](#), [apply it](#) to your project and [add *kotlin-stdlib* dependencies](#). Those actions may also be performed automatically in IntelliJ IDEA by invoking the Tools | Kotlin | Configure Kotlin in Project action.

Plugin and Versions

The `kotlin-gradle-plugin` compiles Kotlin sources and modules.

The version of Kotlin to use is usually defined as the `kotlin_version` property:

```
buildscript {
    ext.kotlin_version = '1.2.70'

    repositories {
        mavenCentral()
    }

    dependencies {
        classpath "org.jetbrains.kotlin:kotlin-gradle-plugin:$kotlin_version"
    }
}
```

This is not required when using Kotlin Gradle plugin 1.1.1 and above with the [Gradle plugins DSL](#), and with [Gradle Kotlin DSL](#).

Targeting the JVM

To target the JVM, the Kotlin plugin needs to be applied:

```
apply plugin: "kotlin"
```

Or, starting with Kotlin 1.1.1, the plugin can be applied using the [Gradle plugins DSL](#):

```
plugins {
    id "org.jetbrains.kotlin.jvm" version "1.2.70"
}
```

The `version` should be literal in this block, and it cannot be applied from another build script.

With Gradle Kotlin DSL, apply the plugin as follows:

```
plugins {
    kotlin("jvm") version "1.2.70"
}
```

Kotlin sources can be mixed with Java sources in the same folder, or in different folders. The default convention is using different folders:

```
project
- src
  - main (root)
    - kotlin
    - java
```

The corresponding `sourceSets` property should be updated if not using the default convention:

```
sourceSets {
    main.kotlin.srcDirs += 'src/main/myKotlin'
    main.java.srcDirs += 'src/main/myJava'
}
```

With Gradle Kotlin DSL, configure source sets with `java.sourceSets { ... }` instead.

Targeting JavaScript

When targeting JavaScript, a different plugin should be applied:


```
apply plugin: "kotlin2js"
```

This plugin only works for Kotlin files so it is recommended to keep Kotlin and Java files separate (if it's the case that the same project contains Java files). As with targeting the JVM, if not using the default convention, we need to specify the source folder using *sourceSets*:

```
sourceSets {  
    main.kotlin.srcDirs += 'src/main/myKotlin'  
}
```

In addition to the output JavaScript file, the plugin by default creates an additional JS file with binary descriptors. This file is required if you're building a re-usable library that other Kotlin modules can depend on, and should be distributed together with the result of translation. The generation is controlled by the `kotlinOptions.metaInfo` option:

```
compileKotlin2Js {  
    kotlinOptions.metaInfo = true  
}
```

Targeting Android

Android's Gradle model is a little different from ordinary Gradle, so if we want to build an Android project written in Kotlin, we need *kotlin-android* plugin instead of *kotlin*:

```
buildscript {  
    ext.kotlin_version = '1.2.70'  
  
    ...  
  
    dependencies {  
        classpath "org.jetbrains.kotlin:kotlin-gradle-plugin:$kotlin_version"  
    }  
}  
apply plugin: 'com.android.application'  
apply plugin: 'kotlin-android'
```

Don't forget to configure the [standard library dependency](#).

Android Studio

If using Android Studio, the following needs to be added under android:

```
android {  
    ...  
  
    sourceSets {  
        main.java.srcDirs += 'src/main/kotlin'  
    }  
}
```

This lets Android Studio know that the kotlin directory is a source root, so when the project model is loaded into the IDE it will be properly recognized. Alternatively, you can put Kotlin classes in the Java source directory, typically located in `src/main/java`.

Configuring Dependencies

In addition to the `kotlin-gradle-plugin` dependency shown above, you need to add a dependency on the Kotlin standard library:

```
repositories {  
    mavenCentral()  
}  
  
dependencies {  
    compile "org.jetbrains.kotlin:kotlin-stdlib"  
}
```

If you target JavaScript, use `compile "org.jetbrains.kotlin:kotlin-stdlib-js"` instead.

If you're targeting JDK 7 or JDK 8, you can use extended versions of the Kotlin standard library which contain additional extension functions for APIs added in new JDK versions. Instead of `kotlin-stdlib`, use one of the following dependencies:

```
compile "org.jetbrains.kotlin:kotlin-stdlib-jdk7"
compile "org.jetbrains.kotlin:kotlin-stdlib-jdk8"
```

With Gradle Kotlin DSL, the following notation for the dependencies is equivalent:

```
dependencies {
    compile(kotlin("stdlib"))
    // or one of:
    compile(kotlin("stdlib-jdk7"))
    compile(kotlin("stdlib-jdk8"))
}
```

In Kotlin 1.1.x, use `kotlin-stdlib-jre7` and `kotlin-stdlib-jre8` instead.

If your project uses [Kotlin reflection](#) or testing facilities, you need to add the corresponding dependencies as well:

```
compile "org.jetbrains.kotlin:kotlin-reflect"
testCompile "org.jetbrains.kotlin:kotlin-test"
testCompile "org.jetbrains.kotlin:kotlin-test-junit"
```

Or, with Gradle Kotlin DSL:

```
compile(kotlin("reflect"))
testCompile(kotlin("test"))
testCompile(kotlin("test-junit"))
```

Starting with Kotlin 1.1.2, the dependencies with group `org.jetbrains.kotlin` are by default resolved with the version taken from the applied plugin. You can provide the version manually using the full dependency notation like `compile "org.jetbrains.kotlin:kotlin-stdlib:$kotlin_version"`, or `kotlin("stdlib", kotlinVersion)` in Gradle Kotlin DSL.

Annotation processing

See the description of [Kotlin annotation processing tool](#) (`kapt`).

Incremental compilation

Kotlin supports optional incremental compilation in Gradle. Incremental compilation tracks changes of source files between builds so only files affected by these changes would be compiled.

Starting with Kotlin 1.1.1, incremental compilation is enabled by default.

There are several ways to override the default setting:

1. add `kotlin.incremental=true` or `kotlin.incremental=false` line either to a `gradle.properties` or to a `local.properties` file;
2. add `-Pkotlin.incremental=true` or `-Pkotlin.incremental=false` to Gradle command line parameters. Note that in this case the parameter should be added to each subsequent build, and any build with disabled incremental compilation invalidates incremental caches.

Note, that the first build won't be incremental.

Coroutines support

[Coroutines](#) support is an experimental feature in Kotlin 1.2, so the Kotlin compiler reports a warning when you use coroutines in your project. To turn off the warning, add the following block to your `build.gradle` file:

```
kotlin {
    experimental {
        coroutines 'enable'
    }
}
```

Or, with Gradle Kotlin DSL:

```
import org.jetbrains.kotlin.gradle.dsl.Coroutines
// ...
```

```
kotlin.experimental.coroutines = Coroutines.ENABLE
```

Module names

The Kotlin modules that the build produces are named accordingly to the `archivesBaseName` property of the project. If a project has a broad name like `lib` or `jvm`, which is common for subprojects, the Kotlin output files related to the module (`*.kotlin_module`) might clash with those from third-party modules with the same name. This causes problems when a project is packaged into a single archive (e.g. APK).

To avoid this, consider setting a unique `archivesBaseName` manually:

```
archivesBaseName = 'myExampleProject_lib'
```

With Gradle Kotlin DSL, it is:

```
setProperty("archivesBaseName", "myExampleProject_lib")
```

Gradle Build Cache support (since 1.2.20)

The Kotlin plugin supports [Gradle Build Cache](#) (Gradle version 4.3 and above is required; caching is disabled with lower versions).

The kapt annotation processing tasks are not cached by default since annotation processors run arbitrary code that may not necessarily transform the task inputs into the outputs, might access and modify the files that are not tracked by Gradle etc. To enable caching for kapt anyway, add the following lines to the build script:

```
kapt {
    useBuildCache = true
}
```

To disable the caching for all Kotlin tasks, set the system property flag `kotlin.caching.enabled` to `false` (run the build with the argument `-Dkotlin.caching.enabled=false`).

Compiler Options

To specify additional compilation options, use the `kotlinOptions` property of a Kotlin compilation task.

When targeting the JVM, the tasks are called `compileKotlin` for production code and `compileTestKotlin` for test code. The tasks for custom source sets are called accordingly to the `compile<Name>Kotlin` pattern.

The names of the tasks in Android Projects contain the [build variant](#) names and follow the pattern `compile<BuildVariant>Kotlin`, for example, `compileDebugKotlin`, `compileReleaseUnitTestKotlin`.

When targeting JavaScript, the tasks are called `compileKotlin2Js` and `compileTestKotlin2Js` respectively, and `compile<Name>Kotlin2Js` for custom source sets.

To configure a single task, use its name. Examples:

```
compileKotlin {
    kotlinOptions.suppressWarnings = true
}
```

```
compileKotlin {
    kotlinOptions {
        suppressWarnings = true
    }
}
```

With Gradle Kotlin DSL, get the task from the project's `tasks` first:

```
import org.jetbrains.kotlin.gradle.tasks.KotlinCompile
// ...
```

```
val kotlinCompile: KotlinCompile by tasks
```

```
kotlinCompile.kotlinOptions.suppressWarnings = true
```

Use the types `Kotlin2JsCompile` and `KotlinCompileCommon` for the JS and Common targets, accordingly.

It is also possible to configure all Kotlin compilation tasks in the project:

```
tasks.withType(org.jetbrains.kotlin.gradle.tasks.KotlinCompile::class.java).all {
    kotlinOptions { ... }
}
```

A complete list of options for the Gradle tasks follows:

Attributes common for JVM, JS, and JS DCE

| Name | Description | Possible values | Default value |
|----------------------------------|---|-----------------|---------------|
| <code>allWarningsAsErrors</code> | Report an error if there are any warnings | | false |
| <code>suppressWarnings</code> | Generate no warnings | | false |
| <code>verbose</code> | Enable verbose logging output | | false |
| <code>freeCompilerArgs</code> | A list of additional compiler arguments | | [] |

Attributes common for JVM and JS

| Name | Description | Possible values | Default value |
|------------------------------|--|---|---------------|
| <code>apiVersion</code> | Allow to use declarations only from the specified version of bundled libraries | "1.0", "1.1", "1.2", "1.3 (EXPERIMENTAL)" | |
| <code>languageVersion</code> | Provide source compatibility with specified language version | "1.0", "1.1", "1.2", "1.3 (EXPERIMENTAL)" | |

Attributes specific for JVM

| Name | Description | Possible values | Default value |
|-----------------------------|--|-----------------|---------------|
| <code>javaParameters</code> | Generate metadata for Java 1.8 reflection on method parameters | | false |
| <code>jdkHome</code> | Path to JDK home directory to include into classpath, if differs from default <code>JAVA_HOME</code> | | |
| <code>jvmTarget</code> | Target version of the generated JVM bytecode (1.6 or 1.8), default is 1.6 | "1.6", "1.8" | "1.6" |
| <code>noJdk</code> | Don't include Java runtime into classpath | | false |
| <code>noReflect</code> | Don't include Kotlin reflection implementation into classpath | | true |
| <code>noStdlib</code> | Don't include Kotlin runtime into classpath | | true |

Attributes specific for JS

| Name | Description | Possible values | Default value |
|------------------------------------|--|-----------------------------------|---------------|
| <code>friendModulesDisabled</code> | Disable internal declaration export | | false |
| <code>main</code> | Whether a main function should be called | "call", "noCall" | "call" |
| <code>metaInfo</code> | Generate <code>.meta.js</code> and <code>.kjsm</code> files with metadata. Use to create a library | | true |
| <code>moduleKind</code> | Kind of a module generated by compiler | "plain", "amd", "commonjs", "umd" | "plain" |
| <code>noStdlib</code> | Don't use bundled Kotlin stdlib | | true |
| <code>outputFile</code> | Output file path | | |
| <code>sourceMap</code> | Generate source map | | false |
| <code>sourceMapEmbedSources</code> | Embed source files into source map | "never", "always", "inlining" | |

| Name | Description | Possible values | Default value |
|-----------------|---|-----------------|---------------|
| sourceMapPrefix | Prefix for source maps in a source map | | |
| target | Generate JS files for specific ECMA version | "v5" | "v5" |
| typedArrays | Translate primitive arrays to JS typed arrays | | true |

Generating documentation

To generate documentation for Kotlin projects, use [Dokka](#); please refer to the [Dokka README](#) for configuration instructions. Dokka supports mixed-language projects and can generate output in multiple formats, including standard JavaDoc.

OSGi

For OSGi support see the [Kotlin OSGi page](#).

Using Gradle Kotlin DSL

When using [Gradle Kotlin DSL](#), apply the Kotlin plugins using the `plugins { ... }` block. If you apply them with `apply { plugin(...) }` instead, you may encounter unresolved references to the extensions generated by Gradle Kotlin DSL. To resolve that, you can comment out the erroneous usages, run the Gradle task `kotlinDslAccessorsSnapshot`, then uncomment the usages back and rerun the build or reimport the project into the IDE.

Examples

The following examples show different possibilities of configuring the Gradle plugin:

- [Kotlin](#)
- [Mixed Java and Kotlin](#)
- [Android](#)
- [JavaScript](#)

Using Maven

Plugin and Versions

The *kotlin-maven-plugin* compiles Kotlin sources and modules. Currently only Maven v3 is supported.

Define the version of Kotlin you want to use via a *kotlin.version* property:

```
<properties>
  <kotlin.version>1.2.70</kotlin.version>
</properties>
```

Dependencies

Kotlin has an extensive standard library that can be used in your applications. Configure the following dependency in the pom file:

```
<dependencies>
  <dependency>
    <groupId>org.jetbrains.kotlin</groupId>
    <artifactId>kotlin-stdlib</artifactId>
    <version>${kotlin.version}</version>
  </dependency>
</dependencies>
```

If you're targeting JDK 7 or JDK 8, you can use extended versions of the Kotlin standard library which contain additional extension functions for APIs added in new JDK versions. Instead of `kotlin-stdlib`, use `kotlin-stdlib-jdk7` or `kotlin-stdlib-jdk8`, depending on your JDK version (for Kotlin 1.1.x, `kotlin-stdlib-jre7` and `kotlin-stdlib-jre8`).

If your project uses [Kotlin reflection](#) or testing facilities, you need to add the corresponding dependencies as well. The artifact IDs are `kotlin-reflect` for the reflection library, and `kotlin-test` and `kotlin-test-junit` for the testing libraries.

Compiling Kotlin only source code

To compile source code, specify the source directories in the tag:

```
<build>
  <sourceDirectory>${project.basedir}/src/main/kotlin</sourceDirectory>
  <testSourceDirectory>${project.basedir}/src/test/kotlin</testSourceDirectory>
</build>
```

The Kotlin Maven Plugin needs to be referenced to compile the sources:

```

<build>
  <plugins>
    <plugin>
      <artifactId>kotlin-maven-plugin</artifactId>
      <groupId>org.jetbrains.kotlin</groupId>
      <version>${kotlin.version}</version>

      <executions>
        <execution>
          <id>compile</id>
          <goals> <goal>compile</goal> </goals>
        </execution>

        <execution>
          <id>test-compile</id>
          <goals> <goal>test-compile</goal> </goals>
        </execution>
      </executions>
    </plugin>
  </plugins>
</build>

```

Compiling Kotlin and Java sources

To compile mixed code applications Kotlin compiler should be invoked before Java compiler. In maven terms that means kotlin-maven-plugin should be run before maven-compiler-plugin using the following method, making sure that the kotlin plugin is above the maven-compiler-plugin in your pom.xml file:

```

<build>
  <plugins>
    <plugin>
      <artifactId>kotlin-maven-plugin</artifactId>
      <groupId>org.jetbrains.kotlin</groupId>
      <version>${kotlin.version}</version>
      <executions>
        <execution>
          <id>compile</id>
          <goals> <goal>compile</goal> </goals>
          <configuration>
            <sourceDirs>
              <sourceDir>${project.basedir}/src/main/kotlin</sourceDir>
              <sourceDir>${project.basedir}/src/main/java</sourceDir>
            </sourceDirs>
          </configuration>
        </execution>
        <execution>
          <id>test-compile</id>
          <goals> <goal>test-compile</goal> </goals>
          <configuration>
            <sourceDirs>
              <sourceDir>${project.basedir}/src/test/kotlin</sourceDir>
              <sourceDir>${project.basedir}/src/test/java</sourceDir>
            </sourceDirs>
          </configuration>
        </execution>
      </executions>
    </plugin>
    <plugin>
      <groupId>org.apache.maven.plugins</groupId>
      <artifactId>maven-compiler-plugin</artifactId>
      <version>3.5.1</version>
      <executions>
        <!-- Replacing default-compile as it is treated specially by maven -->
        <execution>
          <id>default-compile</id>
          <phase>none</phase>
        </execution>
        <!-- Replacing default-testCompile as it is treated specially by maven -->
        <execution>
          <id>default-testCompile</id>
          <phase>none</phase>
        </execution>
        <execution>
          <id>java-compile</id>
          <phase>compile</phase>
          <goals> <goal>compile</goal> </goals>
        </execution>
        <execution>
          <id>java-test-compile</id>
          <phase>test-compile</phase>
          <goals> <goal>testCompile</goal> </goals>
        </execution>
      </executions>
    </plugin>
  </plugins>
</build>

```

Incremental compilation

To make your builds faster, you can enable incremental compilation for Maven (supported since Kotlin 1.1.2). In order to do that, define the `kotlin.compiler.incremental` property:


```
<properties>
  <kotlin.compiler.incremental>true</kotlin.compiler.incremental>
</properties>
```

Alternatively, run your build with the `-Dkotlin.compiler.incremental=true` option.

Annotation processing

See the description of [Kotlin annotation processing tool](#) (`kapt`).

Coroutines support

[Coroutines](#) support is an experimental feature in Kotlin 1.2, so the Kotlin compiler reports a warning when you use coroutines in your project. To turn off the warning, add the following block to your `pom.xml` file:

```
<configuration>
  <experimentalCoroutines>enable</experimentalCoroutines>
</configuration>
```

Jar file

To create a small Jar file containing just the code from your module, include the following under `build->plugins` in your Maven `pom.xml` file, where `main.class` is defined as a property and points to the main Kotlin or Java class:

```
<plugin>
  <groupId>org.apache.maven.plugins</groupId>
  <artifactId>maven-jar-plugin</artifactId>
  <version>2.6</version>
  <configuration>
    <archive>
      <manifest>
        <addClasspath>true</addClasspath>
        <mainClass>${main.class}</mainClass>
      </manifest>
    </archive>
  </configuration>
</plugin>
```

Self-contained Jar file

To create a self-contained Jar file containing the code from your module along with dependencies, include the following under `build->plugins` in your Maven `pom.xml` file, where `main.class` is defined as a property and points to the main Kotlin or Java class:

```

<plugin>
  <groupId>org.apache.maven.plugins</groupId>
  <artifactId>maven-assembly-plugin</artifactId>
  <version>2.6</version>
  <executions>
    <execution>
      <id>make-assembly</id>
      <phase>package</phase>
      <goals> <goal>single</goal> </goals>
      <configuration>
        <archive>
          <manifest>
            <mainClass>${main.class}</mainClass>
          </manifest>
        </archive>
        <descriptorRefs>
          <descriptorRef>jar-with-dependencies</descriptorRef>
        </descriptorRefs>
      </configuration>
    </execution>
  </executions>
</plugin>

```

This self-contained jar file can be passed directly to a JRE to run your application:

```
java -jar target/mymodule-0.0.1-SNAPSHOT-jar-with-dependencies.jar
```

Targeting JavaScript

In order to compile JavaScript code, you need to use the `js` and `test-js` goals for the `compile` execution:

```

<plugin>
  <groupId>org.jetbrains.kotlin</groupId>
  <artifactId>kotlin-maven-plugin</artifactId>
  <version>${kotlin.version}</version>
  <executions>
    <execution>
      <id>compile</id>
      <phase>compile</phase>
      <goals>
        <goal>js</goal>
      </goals>
    </execution>
    <execution>
      <id>test-compile</id>
      <phase>test-compile</phase>
      <goals>
        <goal>test-js</goal>
      </goals>
    </execution>
  </executions>
</plugin>

```

You also need to change the standard library dependency:

```

<groupId>org.jetbrains.kotlin</groupId>
<artifactId>kotlin-stdlib-js</artifactId>
<version>${kotlin.version}</version>

```

For unit testing support, you also need to add a dependency on the `kotlin-test-js` artifact.

See the [Getting Started with Kotlin and JavaScript with Maven](#) tutorial for more information.

Specifying compiler options

Additional options and arguments for the compiler can be specified as tags under the `<configuration>` element of the Maven plugin node:

```
<plugin>
  <artifactId>kotlin-maven-plugin</artifactId>
  <groupId>org.jetbrains.kotlin</groupId>
  <version>${kotlin.version}</version>
  <executions>...</executions>
  <configuration>
    <nowarn>true</nowarn> <!-- Disable warnings -->
    <args>
      <arg>-Xjsr305=strict</arg> <!-- Enable strict mode for JSR-305 annotations -->
      ...
    </args>
  </configuration>
</plugin>
```

Many of the options can also be configured through properties:

```
<project ...>
  <properties>
    <kotlin.compiler.languageVersion>1.0</kotlin.compiler.languageVersion>
  </properties>
</project>
```

The following attributes are supported:

Attributes common for JVM and JS

| Name | Property name | Description | Possible values | Default value |
|-----------------|---------------------------------|--|---|--------------------------|
| nowarn | | Generate no warnings | true, false | false |
| languageVersion | kotlin.compiler.languageVersion | Provide source compatibility with specified language version | "1.0", "1.1", "1.2", "1.3 (EXPERIMENTAL)" | |
| apiVersion | kotlin.compiler.apiVersion | Allow to use declarations only from the specified version of bundled libraries | "1.0", "1.1", "1.2", "1.3 (EXPERIMENTAL)" | |
| sourceDirs | | The directories containing the source files to compile | | The project source roots |
| compilerPlugins | | Enabled compiler plugins | | [] |
| pluginOptions | | Options for compiler plugins | | [] |
| args | | Additional compiler arguments | | [] |

Attributes specific for JVM

| Name | Property name | Description | Possible values | Default value |
|-----------|---------------------------|---|-----------------|---------------|
| jvmTarget | kotlin.compiler.jvmTarget | Target version of the generated JVM bytecode | "1.6", "1.8" | "1.6" |
| jdkHome | kotlin.compiler.jdkHome | Path to JDK home directory to include into classpath, if differs from default JAVA_HOME | | |

Attributes specific for JS

| Name | Property name | Description | Possible values | Default value |
|------------|---------------|--|-----------------|---------------|
| outputFile | | Output file path | | |
| metaInfo | | Generate .meta.js and .kjsm files with metadata. Use to create a library | true, false | true |

| Name | Property name | Description | Possible values | Default value |
|-----------------------|---------------|--|-----------------------------------|---------------|
| sourceMap | | source map | | |
| sourceMapEmbedSources | | Embed source files into source map | "never", "always", "inlining" | "inlining" |
| sourceMapPrefix | | Prefix for paths in a source map | | |
| moduleKind | | Kind of a module generated by compiler | "plain", "amd", "commonjs", "umd" | "plain" |

Generating documentation

The standard JavaDoc generation plugin (`maven-javadoc-plugin`) does not support Kotlin code. To generate documentation for Kotlin projects, use [Dokka](#); please refer to the [Dokka README](#) for configuration instructions. Dokka supports mixed-language projects and can generate output in multiple formats, including standard JavaDoc.

OSGi

For OSGi support see the [Kotlin OSGi page](#).

Examples

An example Maven project can be [downloaded directly from the GitHub repository](#)

Using Ant

Getting the Ant Tasks

Kotlin provides three tasks for Ant:

- `kotlinc`: Kotlin compiler targeting the JVM;
- `kotlin2js`: Kotlin compiler targeting JavaScript;
- `withKotlin`: Task to compile Kotlin files when using the standard `javac` Ant task.

These tasks are defined in the `kotlin-ant.jar` library which is located in the `lib` folder for the [Kotlin Compiler](#) Ant version 1.8.2+ is required.

Targeting JVM with Kotlin-only source

When the project consists of exclusively Kotlin source code, the easiest way to compile the project is to use the `kotlinc` task:

```
<project name="Ant Task Test" default="build">
  <typedef resource="org/jetbrains/kotlin/ant/antlib.xml" classpath="${kotlin.lib}/kotlin-ant.jar"/>

  <target name="build">
    <kotlinc src="hello.kt" output="hello.jar"/>
  </target>
</project>
```

where `${kotlin.lib}` points to the folder where the Kotlin standalone compiler was unzipped.

Targeting JVM with Kotlin-only source and multiple roots

If a project consists of multiple source roots, use `src` as elements to define paths:

```
<project name="Ant Task Test" default="build">
  <typedef resource="org/jetbrains/kotlin/ant/antlib.xml" classpath="${kotlin.lib}/kotlin-ant.jar"/>

  <target name="build">
    <kotlinc output="hello.jar">
      <src path="root1"/>
      <src path="root2"/>
    </kotlinc>
  </target>
</project>
```

Targeting JVM with Kotlin and Java source

If a project consists of both Kotlin and Java source code, while it is possible to use `kotlinc`, to avoid repetition of task parameters, it is recommended to use `withKotlin` task:

```
<project name="Ant Task Test" default="build">
  <typedef resource="org/jetbrains/kotlin/ant/antlib.xml" classpath="${kotlin.lib}/kotlin-ant.jar"/>

  <target name="build">
    <delete dir="classes" failonerror="false"/>
    <mkdir dir="classes"/>
    <javac destdir="classes" includeAntRuntime="false" srcdir="src">
      <withKotlin/>
    </javac>
    <jar destfile="hello.jar">
      <fileset dir="classes"/>
    </jar>
  </target>
</project>
```

You can also specify the name of the module being compiled as the `moduleName` attribute:

```
<withKotlin moduleName="myModule"/>
```

Targeting JavaScript with single source folder

```
<project name="Ant Task Test" default="build">
  <typedef resource="org/jetbrains/kotlin/ant/antlib.xml" classpath="${kotlin.lib}/kotlin-ant.jar"/>

  <target name="build">
    <kotlin2js src="root1" output="out.js"/>
  </target>
</project>
```

Targeting JavaScript with Prefix, PostFix and sourcemap options

```
<project name="Ant Task Test" default="build">
  <taskdef resource="org/jetbrains/kotlin/ant/antlib.xml" classpath="${kotlin.lib}/kotlin-ant.jar"/>

  <target name="build">
    <kotlin2js src="root1" output="out.js" outputPrefix="prefix" outputPostfix="postfix"
    sourcemap="true"/>
  </target>
</project>
```

Targeting JavaScript with single source folder and metaInfo option

The `metaInfo` option is useful, if you want to distribute the result of translation as a Kotlin/JavaScript library. If `metaInfo` was set to `true`, then during compilation additional JS file with binary metadata will be created. This file should be distributed together with the result of translation:

```
<project name="Ant Task Test" default="build">
  <typedef resource="org/jetbrains/kotlin/ant/antlib.xml" classpath="${kotlin.lib}/kotlin-ant.jar"/>

  <target name="build">
    <!-- out.meta.js will be created, which contains binary metadata -->
    <kotlin2js src="root1" output="out.js" metaInfo="true"/>
  </target>
</project>
```

References

Complete list of elements and attributes are listed below:

Attributes common for `kotlinc` and `kotlin2js`

| Name | Description | Required | Default Value |
|-------------|---|----------|---------------|
| src | Kotlin source file or directory to compile | Yes | |
| nowarn | Suppresses all compilation warnings | No | false |
| noStdlib | Does not include the Kotlin standard library into the classpath | No | false |
| failOnError | Fails the build if errors are detected during the compilation | No | true |

`kotlinc` Attributes

| Name | Description | Required | Default Value |
|-----------|---|----------|---------------|
| output | Destination directory or .jar file name | Yes | |
| classpath | Compilation class path | No | |

| Name | Description | Required | Default Value |
|----------------|---|----------|--|
| classpathref | Compilation class path reference | No | |
| includeRuntime | If output is a .jar file, whether Kotlin runtime library is included in the jar | No | true |
| moduleName | Name of the module being compiled | No | The name of the target (if specified) or the project |

kotlin2js Attributes

| Name | Description | Required |
|--------------|---|----------|
| output | Destination file | Yes |
| libraries | Paths to Kotlin libraries | No |
| outputPrefix | Prefix to use for generated JavaScript files | No |
| outputSuffix | Suffix to use for generated JavaScript files | No |
| sourcemap | Whether sourcemap file should be generated | No |
| metaInfo | Whether metadata file with binary descriptors should be generated | No |
| main | Should compiler generated code call the main function | No |

Passing raw compiler arguments

To pass custom raw compiler arguments, you can use `<compilerarg>` elements with either `value` or `line` attributes. This can be done within the `<kotlinc>`, `<kotlin2js>`, and `<withKotlin>` task elements, as follows:

```
<kotlinc src="${test.data}/hello.kt" output="${temp}/hello.jar">
  <compilerarg value="-Xno-inline"/>
  <compilerarg line="-Xno-call-assertions -Xno-param-assertions"/>
  <compilerarg value="-Xno-optimize"/>
</kotlinc>
```

The full list of arguments that can be used is shown when you run `kotlinc -help`.

Kotlin and OSGi

To enable Kotlin OSGi support you need to include `kotlin-osgi-bundle` instead of regular Kotlin libraries. It is recommended to remove `kotlin-runtime`, `kotlin-stdlib` and `kotlin-reflect` dependencies as `kotlin-osgi-bundle` already contains all of them. You also should pay attention in case when external Kotlin libraries are included. Most regular Kotlin dependencies are not OSGi-ready, so you shouldn't use them and should remove them from your project.

Maven

To include the Kotlin OSGi bundle to a Maven project:

```
<dependencies>
  <dependency>
    <groupId>org.jetbrains.kotlin</groupId>
    <artifactId>kotlin-osgi-bundle</artifactId>
    <version>${kotlin.version}</version>
  </dependency>
</dependencies>
```

To exclude the standard library from external libraries (notice that "star exclusion" works in Maven 3 only):

```
<dependency>
  <groupId>some.group.id</groupId>
  <artifactId>some.library</artifactId>
  <version>some.library.version</version>

  <exclusions>
    <exclusion>
      <groupId>org.jetbrains.kotlin</groupId>
      <artifactId>*</artifactId>
    </exclusion>
  </exclusions>
</dependency>
```

Gradle

To include `kotlin-osgi-bundle` to a gradle project:

```
compile "org.jetbrains.kotlin:kotlin-osgi-bundle:$kotlinVersion"
```

To exclude default Kotlin libraries that comes as transitive dependencies you can use the following approach:

```
dependencies {
  compile (
    [group: 'some.group.id', name: 'some.library', version: 'someversion'],
    .....) {
    exclude group: 'org.jetbrains.kotlin'
  }
}
```

FAQ

Why not just add required manifest options to all Kotlin libraries

Even though it is the most preferred way to provide OSGi support, unfortunately it couldn't be done for now due to so called ["package split" issue](#) that couldn't be easily eliminated and such a big change is not planned for now. There is `Require-Bundle` feature but it is not the best option too and not recommended to use. So it was decided to make a separate artifact for OSGi.

Compiler Plugins

All-open compiler plugin

Kotlin has classes and their members `final` by default, which makes it inconvenient to use frameworks and libraries such as Spring AOP that require classes to be `open`. The *all-open* compiler plugin adapts Kotlin to the requirements of those frameworks and makes classes annotated with a specific annotation and their members open without the explicit `open` keyword.

For instance, when you use Spring, you don't need all the classes to be open, but only classes annotated with specific annotations like `@Configuration` or `@Service`. *All-open* allows to specify such annotations.

We provide *all-open* plugin support both for Gradle and Maven with the complete IDE integration.

Note: For Spring you can use the `kotlin-spring` compiler plugin ([see below](#)).

Using in Gradle

Add the plugin artifact to the buildscript dependencies and apply the plugin:

```
buildscript {
    dependencies {
        classpath "org.jetbrains.kotlin:kotlin-allopen:$kotlin_version"
    }
}

apply plugin: "kotlin-allopen"
```

As an alternative, you can enable it using the `plugins` block:

```
plugins {
    id "org.jetbrains.kotlin.plugin.allopen" version "1.2.70"
}
```

Then specify the list of annotations that will make classes open:

```
allOpen {
    annotation("com.my.Annotation")
    // annotations("com.another.Annotation", "com.third.Annotation")
}
```

If the class (or any of its superclasses) is annotated with `com.my.Annotation`, the class itself and all its members will become open.

It also works with meta-annotations:

```
@com.my.Annotation
annotation class MyFrameworkAnnotation
```

```
@MyFrameworkAnnotation
class MyClass // will be all-open
```

`MyFrameworkAnnotation` is annotated with the all-open meta-annotation `com.my.Annotation`, so it becomes an all-open annotation as well.

Using in Maven

Here's how to use all-open with Maven:

```

<plugin>
  <artifactId>kotlin-maven-plugin</artifactId>
  <groupId>org.jetbrains.kotlin</groupId>
  <version>${kotlin.version}</version>

  <configuration>
    <compilerPlugins>
      <!-- Or "spring" for the Spring support -->
      <plugin>all-open</plugin>
    </compilerPlugins>

    <pluginOptions>
      <!-- Each annotation is placed on its own line -->
      <option>all-open:annotation=com.my.Annotation</option>
      <option>all-open:annotation=com.their.AnotherAnnotation</option>
    </pluginOptions>
  </configuration>

  <dependencies>
    <dependency>
      <groupId>org.jetbrains.kotlin</groupId>
      <artifactId>kotlin-maven-allopen</artifactId>
      <version>${kotlin.version}</version>
    </dependency>
  </dependencies>
</plugin>

```

Please refer to the "Using in Gradle" section above for the detailed information about how all-open annotations work.

Spring support

If you use Spring, you can enable the *kotlin-spring* compiler plugin instead of specifying Spring annotations manually. The *kotlin-spring* is a wrapper on top of *all-open*, and it behaves exactly the same way.

As with *all-open*, add the plugin to the buildscript dependencies:

```

buildscript {
  dependencies {
    classpath "org.jetbrains.kotlin:kotlin-allopen:$kotlin_version"
  }
}

```

apply plugin: "kotlin-spring" // instead of "kotlin-allopen"

Or using the Gradle plugins DSL:

```

plugins {
  id "org.jetbrains.kotlin.plugin.spring" version "1.2.70"
}

```

In Maven, enable the `spring` plugin:

```

<compilerPlugins>
  <plugin>spring</plugin>
</compilerPlugins>

```

The plugin specifies the following annotations: [@Component](#), [@Async](#), [@Transactional](#), [@Cacheable](#) and [@SpringBootTest](#). Thanks to meta-annotations support classes annotated with [@Configuration](#), [@Controller](#), [@RestController](#), [@Service](#) or [@Repository](#) are automatically opened since these annotations are meta-annotated with [@Component](#).

Of course, you can use both `kotlin-allopen` and `kotlin-spring` in the same project.

Note that if you use the project template generated by the [start.spring.io](#) service, the `kotlin-spring` plugin will be enabled by default.

Using in CLI

All-open compiler plugin JAR is available in the binary distribution of the Kotlin compiler. You can attach the plugin by providing the path to its JAR file using the `-Xplugin kotlinc` option:

```
-Xplugin=$KOTLIN_HOME/lib/allopen-compiler-plugin.jar
```

You can specify all-open annotations directly, using the `annotation` plugin option, or enable the "preset". The only preset available now for all-open is `spring`.

```
# The plugin option format is: "-P plugin:<plugin id>:<key>=<value>".
# Options can be repeated.

-P plugin:org.jetbrains.kotlin.allopen:annotation=com.my.Annotation
-P plugin:org.jetbrains.kotlin.allopen:preset=spring
```

No-arg compiler plugin

The *no-arg* compiler plugin generates an additional zero-argument constructor for classes with a specific annotation.

The generated constructor is synthetic so it can't be directly called from Java or Kotlin, but it can be called using reflection.

This allows the Java Persistence API (JPA) to instantiate a class although it doesn't have the zero-parameter constructor from Kotlin or Java point of view (see the description of `kotlin-jpa` plugin [below](#)).

Using in Gradle

The usage is pretty similar to all-open.

Add the plugin and specify the list of annotations that must lead to generating a no-arg constructor for the annotated classes.

```
buildscript {
    dependencies {
        classpath "org.jetbrains.kotlin:kotlin-noarg:$kotlin_version"
    }
}
```

```
apply plugin: "kotlin-noarg"
```

Or using the Gradle plugins DSL:

```
plugins {
    id "org.jetbrains.kotlin.plugin.noarg" version "1.2.70"
}
```

Then specify the list of no-arg annotations:

```
noArg {
    annotation("com.my.Annotation")
}
```

Enable `invokeInitializers` option if you want the plugin to run the initialization logic from the synthetic constructor. Starting from Kotlin 1.1.3-2, it is disabled by default because of [KT-18667](#) and [KT-18668](#) which will be addressed in the future.

```
noArg {
    invokeInitializers = true
}
```

Using in Maven

```

<plugin>
  <artifactId>kotlin-maven-plugin</artifactId>
  <groupId>org.jetbrains.kotlin</groupId>
  <version>${kotlin.version}</version>

  <configuration>
    <compilerPlugins>
      <!-- Or "jpa" for JPA support -->
      <plugin>no-arg</plugin>
    </compilerPlugins>

    <pluginOptions>
      <option>no-arg:annotation=com.my.Annotation</option>
      <!-- Call instance initializers in the synthetic constructor -->
      <!-- <option>no-arg:invokeInitializers=true</option> -->
    </pluginOptions>
  </configuration>

  <dependencies>
    <dependency>
      <groupId>org.jetbrains.kotlin</groupId>
      <artifactId>kotlin-maven-noarg</artifactId>
      <version>${kotlin.version}</version>
    </dependency>
  </dependencies>
</plugin>

```

JPA support

As with the *kotlin-spring* plugin, *kotlin-jpa* is a wrapped on top of *no-arg*. The plugin specifies [@Entity](#), [@Embeddable](#) and [@MappedSuperclass](#) *no-arg* annotations automatically.

That's how you add the plugin in Gradle:

```

buildscript {
  dependencies {
    classpath "org.jetbrains.kotlin:kotlin-noarg:$kotlin_version"
  }
}

```

apply plugin: "kotlin-jpa"

Or using the Gradle plugins DSL:

```

plugins {
  id "org.jetbrains.kotlin.plugin.jpa" version "1.2.70"
}

```

In Maven, enable the `jpa` plugin:

```

<compilerPlugins>
  <plugin>jpa</plugin>
</compilerPlugins>

```

Using in CLI

As with all-open, add the plugin JAR file to the compiler plugin classpath and specify annotations or presets:

```

-Xplugin=$KOTLIN_HOME/lib/noarg-compiler-plugin.jar
-P plugin:org.jetbrains.kotlin.noarg:annotation=com.my.Annotation
-P plugin:org.jetbrains.kotlin.noarg:preset=jpa

```

SAM-with-receiver compiler plugin

The *sam-with-receiver* compiler plugin makes the first parameter of the annotated Java "single abstract method" (SAM) interface method a receiver in Kotlin. This conversion only works when the SAM interface is passed as a Kotlin lambda, both for SAM adapters and SAM constructors (see the [documentation](#) for more details).

Here is an example:

```
public @interface SamWithReceiver {}

@SamWithReceiver
public interface TaskRunner {
    void run(Task task);
}

fun test(context: TaskContext) {
    val handler = TaskHandler {
        // Here 'this' is an instance of 'Task'

        println("$name is started")
        context.executeTask(this)
        println("$name is finished")
    }
}
```

Using in Gradle

The usage is the same to all-open and no-arg, except the fact that sam-with-receiver does not have any built-in presets, and you need to specify your own list of special-treated annotations.

```
buildscript {
    dependencies {
        classpath "org.jetbrains.kotlin:kotlin-sam-with-receiver:$kotlin_version"
    }
}
```

```
apply plugin: "kotlin-sam-with-receiver"
```

Then specify the list of SAM-with-receiver annotations:

```
samWithReceiver {
    annotation("com.my.Annotation")
}
```

Using in Maven

```

<plugin>
  <artifactId>kotlin-maven-plugin</artifactId>
  <groupId>org.jetbrains.kotlin</groupId>
  <version>${kotlin.version}</version>

  <configuration>
    <compilerPlugins>
      <plugin>sam-with-receiver</plugin>
    </compilerPlugins>

    <pluginOptions>
      <option>
        sam-with-receiver:annotation=com.my.SamWithReceiver
      </option>
    </pluginOptions>
  </configuration>

  <dependencies>
    <dependency>
      <groupId>org.jetbrains.kotlin</groupId>
      <artifactId>kotlin-maven-sam-with-receiver</artifactId>
      <version>${kotlin.version}</version>
    </dependency>
  </dependencies>
</plugin>

```

Using in CLI

Just add the plugin JAR file to the compiler plugin classpath and specify the list of sam-with-receiver annotations:

```

-Xplugin=$KOTLIN_HOME/lib/sam-with-receiver-compiler-plugin.jar
-P plugin:org.jetbrains.kotlin.samWithReceiver:annotation=com.my.SamWithReceiver

```

FAQ

FAQ

What is Kotlin?

Kotlin is an OSS statically typed programming language that targets the JVM, Android, JavaScript and Native. It's developed by [JetBrains](#). The project started in 2010 and was open source from very early on. The first official 1.0 release was in February 2016.

What is the current version of Kotlin?

The currently released version is 1.2.70, published on September 12, 2018.

Is Kotlin free?

Yes. Kotlin is free, has been free and will remain free. It is developed under the Apache 2.0 license and the source code is available [on GitHub](#).

Is Kotlin an object-oriented language or a functional one?

Kotlin has both object-oriented and functional constructs. You can use it in both OO and FP styles, or mix elements of the two. With first-class support for features such as higher-order functions, function types and lambdas, Kotlin is a great choice if you're doing or exploring functional programming.

What advantages does Kotlin give me over the Java programming language?

Kotlin is more concise. Rough estimates indicate approximately a 40% cut in the number of lines of code. It's also more type-safe, e.g. support for non-nullable types makes applications less prone to NPE's. Other features including smart casting, higher-order functions, extension functions and lambdas with receivers provide the ability to write expressive code as well as facilitating creation of DSL.

Is Kotlin compatible with the Java programming language?

Yes. Kotlin is 100% interoperable with the Java programming language and major emphasis has been placed on making sure that your existing codebase can interact properly with Kotlin. You can easily call Kotlin code from Java and Java code from Kotlin. This makes adoption much easier and lower-risk. There's also an automated Java-to-Kotlin converter built into the IDE that simplifies migration of existing code.

What can I use Kotlin for?

Kotlin can be used for any kind of development, be it server-side, client-side web and Android. With Kotlin/Native currently in the works, support for other platforms such as embedded systems, macOS and iOS is coming. People are using Kotlin for mobile and server-side applications, client-side with JavaScript or JavaFX, and data science, just to name a few possibilities.

Can I use Kotlin for Android development?

Yes. Kotlin is supported as a first-class language on Android. There are hundreds of applications already using Kotlin for Android, such as Basecamp, Pinterest and more. For more information check out [the resource on Android development](#).

Can I use Kotlin for server-side development?

Yes. Kotlin is 100% compatible with the JVM and as such you can use any existing frameworks such as Spring Boot, vert.x or JSF. In addition there are specific frameworks written in Kotlin such as [Ktor](#). For more information check out [the resource on server-side development](#).

Can I use Kotlin for web development?

Yes. In addition to using for backend web, you can also use Kotlin/JS for client-side web. Kotlin can use definitions from [DefinitelyTyped](#) to get static typing for common JavaScript libraries, and it is compatible with existing module systems such as AMD and CommonJS. For more information check out [the resource on client-side development](#).

Can I use Kotlin for desktop development?

Yes. You can use any Java UI framework such as JavaFX, Swing or other. In addition there are Kotlin specific frameworks such as [TornadoFX](#).

Can I use Kotlin for native development?

Kotlin/Native is currently [in the works](#). It compiles Kotlin to native code that can run without a VM. There is a Technology Preview released but it is not production-ready yet, and doesn't yet target all the platforms that we plan to support for 1.0. For more information check out the [blog post announcing Kotlin/Native](#).

What IDEs support Kotlin?

Kotlin is supported by all major Java IDEs including [IntelliJ IDEA](#), [Android Studio](#), [Eclipse](#) and [NetBeans](#). In addition, a [command line compiler](#) is available and provides straightforward support for compiling and running applications.

What build tools support Kotlin?

On the JVM side, the main build tools include [Gradle](#), [Maven](#), [Ant](#), and [Kobalt](#). There are also some build tools available that target client-side JavaScript.

What does Kotlin compile down to?

When targeting the JVM, Kotlin produces Java compatible bytecode. When targeting JavaScript, Kotlin transpiles to ES5.1 and generates code which is compatible with module systems including AMD and CommonJS. When targeting native, Kotlin will produce platform-specific code (via LLVM).

Does Kotlin only target Java 6?

No. Kotlin lets you choose between generating Java 6 and Java 8 compatible bytecode. More optimal byte code may be generated for higher versions of the platform.

Is Kotlin hard?

Kotlin is inspired by existing languages such as Java, C#, JavaScript, Scala and Groovy. We've tried to ensure that Kotlin is easy to learn, so that people can easily jump on board, reading and writing Kotlin in a matter of days. Learning idiomatic Kotlin and using some more of its advanced features can take a little longer, but overall it is not a complicated language.

What companies are using Kotlin?

There are too many companies using Kotlin to list, but some more visible companies that have publicly declared usage of Kotlin, be this via blog posts, GitHub repositories or talks include [Square](#), [Pinterest](#) or [Basecamp](#).

Who develops Kotlin?

Kotlin is primarily developed by a team of engineers at JetBrains (current team size is 40+). The lead language designer is [Andrey Breslav](#). In addition to the core team, there are also over 100 external contributors on GitHub.

Where can I learn more about Kotlin?

The best place to start is [this website](#). From there you can download the compiler, [try it online](#) as well as get access to resources, [reference documentation](#) and [tutorials](#).

Are there any books on Kotlin?

There are already [a number of books](#) available for Kotlin, including [Kotlin in Action](#) which is by Kotlin team members Dmitry Jemerov and Svetlana Isakova, [Kotlin for Android Developers](#) targeted at Android developers.

Are there any online courses available for Kotlin?

There are a few courses available for Kotlin, including a [Pluralsight Kotlin Course](#) by Kevin Jones, an [O'Reilly Course](#) by Hadi Hariri and an [Udemy Kotlin Course](#) by Peter Sommerhoff.

There are also many recordings of [Kotlin talks](#) available on YouTube and Vimeo.

Does Kotlin have a community?

Yes. Kotlin has a very vibrant community. Kotlin developers hang out on the [Kotlin forums](#), [StackOverflow](#) and more actively on the [Kotlin Slack](#) (with close to 7000 members as of May 2017).

Are there Kotlin events?

Yes. There are many User Groups and Meetups now focused exclusively around Kotlin. You can find [a list on the web site](#). In addition there are community organised [Kotlin Nights](#) events around the world.

Is there a Kotlin conference?

Yes. The first official [KotlinConf](#), taking place in San Francisco 2-3 November 2017. Kotlin is also being covered in different conferences worldwide. You can find a list of [upcoming talks on the web site](#).

Is Kotlin on Social Media?

Yes. The most active Kotlin account is [on Twitter](#). There is also a [Google+ group](#).

Any other online Kotlin resources?

The web site has a bunch of [online resources](#), including [Kotlin Digests](#) by community members, a [newsletter](#), a [podcast](#) and more.

Where can I get an HD Kotlin logo?

Logos can be downloaded [here](#). Please follow simple rules in the `guidelines.pdf` inside the archive.

Comparison to Java Programming Language

Some Java issues addressed in Kotlin

Kotlin fixes a series of issues that Java suffers from:

- Null references are [controlled by the type system](#).
- [No raw types](#)
- Arrays in Kotlin are [invariant](#)
- Kotlin has proper [function types](#), as opposed to Java's SAM-conversions
- [Use-site variance](#) without wildcards
- Kotlin does not have checked [exceptions](#)

What Java has that Kotlin does not

- [Checked exceptions](#)
- [Primitive types](#) that are not classes
- [Static members](#)
- [Non-private fields](#)
- [Wildcard-types](#)
- [Ternary-operator](#) `a ? b : c`

What Kotlin has that Java does not

- [Lambda expressions](#) + [Inline functions](#) = performant custom control structures
- [Extension functions](#)
- [Null-safety](#)
- [Smart casts](#)
- [String templates](#)
- [Properties](#)
- [Primary constructors](#)
- [First-class delegation](#)
- [Type inference for variable and property types](#)
- [Singletons](#)
- [Declaration-site variance & Type projections](#)
- [Range expressions](#)
- [Operator overloading](#)
- [Companion objects](#)
- [Data classes](#)
- [Separate interfaces for read-only and mutable collections](#)
- [Coroutines](#)

