

```
sh ip eigrp neighbors
```

```
R2#show ip eigrp neighbors
EIGRP-IPv4 VR(ENTERPRISE) Address-Family Neighbors for AS(100)
H   Address          Interface          Hold Uptime      SRTT      RTO   Q   Seq
                               (sec)           (ms)          Cnt  Num
2   10.0.25.2         Gi0/2             14 00:02:03      4    100   0    5
1   10.0.23.2         Gi0/1             13 00:02:38      1    100   0   11
0   10.0.12.1         Gi0/0             13 00:02:59     638   3828   0    9
```

```
sh ip route eigrp
```

```
R2#show ip route eigrp
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
        E1 - OSPF external type 1, E2 - OSPF external type 2
        i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
        ia - IS-IS inter area, * - candidate default, U - per-user static route
        o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
        a - application route
        + - replicated route, % - next hop override, p - overrides from PFR

Gateway of last resort is not set

  1.0.0.0/32 is subnetted, 1 subnets
D       1.1.1.1 [90/10880] via 10.0.12.1, 00:05:19, GigabitEthernet0/0
  3.0.0.0/32 is subnetted, 1 subnets
D       3.3.3.3 [90/10880] via 10.0.23.2, 00:04:19, GigabitEthernet0/1
  4.0.0.0/32 is subnetted, 1 subnets
D       4.4.4.4 [90/16000] via 10.0.23.2, 00:04:19, GigabitEthernet0/1
        [90/16000] via 10.0.12.1, 00:04:19, GigabitEthernet0/0
  5.0.0.0/32 is subnetted, 1 subnets
D       5.5.5.5 [90/10880] via 10.0.25.2, 00:04:19, GigabitEthernet0/2
 10.0.0.0/8 is variably subnetted, 9 subnets, 2 masks
D       10.0.14.0/30 [90/15360] via 10.0.12.1, 00:04:36, GigabitEthernet0/0
D       10.0.34.0/30 [90/15360] via 10.0.23.2, 00:04:19, GigabitEthernet0/1
D       10.0.35.0/30 [90/15360] via 10.0.25.2, 00:04:19, GigabitEthernet0/2
        [90/15360] via 10.0.23.2, 00:04:19, GigabitEthernet0/1
```

```
sh ip protocols
```

```

R2#
R2#show ip protocols
*** IP Routing is NSF aware ***

Routing Protocol is "application"
  Sending updates every 0 seconds
  Invalid after 0 seconds, hold down 0, flushed after 0
  Outgoing update filter list for all interfaces is not set
  Incoming update filter list for all interfaces is not set
  Maximum path: 32
  Routing for Networks:
  Routing Information Sources:
    Gateway          Distance      Last Update
  Distance: (default is 4)

Routing Protocol is "eigrp 100"
  Outgoing update filter list for all interfaces is not set
  Incoming update filter list for all interfaces is not set
  Default networks flagged in outgoing updates
  Default networks accepted from incoming updates
  EIGRP-IPv4 VR(ENTERPRISE) Address-Family Protocol for AS(100)
    Metric weight K1=1, K2=0, K3=1, K4=0, K5=0 K6=0
    Metric rib-scale 128
    Metric version 64bit
    Soft SIA disabled
    NSF-aware route hold timer is 240
    Router-ID: 2.2.2.2
    Topology : 0 (base)
      Active Timer: 3 min
      Distance: internal 90 external 170
      Maximum path: 4
      Maximum hopcount 100
      Maximum metric variance 1
      Total Prefix Count: 11
      Total Redist Count: 0

Automatic Summarization: disabled
Maximum path: 4
Routing for Networks:
  2.2.2.2/32
  10.0.12.0/30
  10.0.23.0/30
  10.0.25.0/30
  10.2.0.0/24
Passive Interface(s):
  Loopback0
Routing Information Sources:
  Gateway          Distance      Last Update
  10.0.12.1         90            00:04:43
  10.0.25.2         90            00:04:43
  10.0.23.2         90            00:04:43
  Distance: internal 90 external 170

```

```
sh ip eigrp topology
```

```
R2#sh ip eigrp topology
EIGRP-IPv4 VR(ENTERPRISE) Topology Table for AS(100)/ID(2.2.2.2)
Codes: P - Passive, A - Active, U - Update, Q - Query, R - Reply,
       r - reply Status, s - sia Status

P 10.0.34.0/30, 1 successors, FD is 1966080
   via 10.0.23.2 (1966080/1310720), GigabitEthernet0/1
P 10.0.25.0/30, 1 successors, FD is 1310720
   via Connected, GigabitEthernet0/2
P 4.4.4.4/32, 2 successors, FD is 2048000
   via 10.0.12.1 (2048000/1392640), GigabitEthernet0/0
   via 10.0.23.2 (2048000/1392640), GigabitEthernet0/1
P 5.5.5.5/32, 1 successors, FD is 1392640
   via 10.0.25.2 (1392640/163840), GigabitEthernet0/2
P 10.0.14.0/30, 1 successors, FD is 1966080
   via 10.0.12.1 (1966080/1310720), GigabitEthernet0/0
P 10.0.35.0/30, 2 successors, FD is 1966080
   via 10.0.23.2 (1966080/1310720), GigabitEthernet0/1
   via 10.0.25.2 (1966080/1310720), GigabitEthernet0/2
P 2.2.2.2/32, 1 successors, FD is 163840
   via Connected, Loopback0
P 10.0.23.0/30, 1 successors, FD is 1310720
   via Connected, GigabitEthernet0/1
P 3.3.3.3/32, 1 successors, FD is 1392640
   via 10.0.23.2 (1392640/163840), GigabitEthernet0/1
P 1.1.1.1/32, 1 successors, FD is 1392640
   via 10.0.12.1 (1392640/163840), GigabitEthernet0/0
P 10.0.12.0/30, 1 successors, FD is 1310720
   via Connected, GigabitEthernet0/0
```