

On R3, sh ip bgp

```
R3(config)#exit
R3#sh ip bgp
*Sep  2 10:55:18.348: %SYS-5-CONFIG_I: Configured from console by console
BGP table version is 5, local router ID is 192.168.100.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
               r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
               x best-external, a additional-path, c RIB-compressed,
               t secondary path,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

   Network          Next Hop           Metric LocPrf Weight Path
*>  192.168.100.0    0.0.0.0              0         32768 i
*   203.0.113.0     10.0.23.1            200          0 65001 i
*>  10.0.13.1        10.0.13.1             0          0 65001 i
*>  203.0.114.0     10.0.23.1            200          0 65001 i
R3#
```

sh ip bgp summary

```
R3#sh ip bgp summary
BGP router identifier 192.168.100.1, local AS number 65010
BGP table version is 5, main routing table version 5
3 network entries using 432 bytes of memory
4 path entries using 336 bytes of memory
3/3 BGP path/bestpath attribute entries using 480 bytes of memory
1 BGP AS-PATH entries using 24 bytes of memory
0 BGP route-map cache entries using 0 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 1272 total bytes of memory
BGP activity 3/0 prefixes, 4/0 paths, scan interval 60 secs

Neighbor      V        AS MsgRcvd MsgSent  TblVer  InQ  OutQ  Up/Down   State/PfxRcd
10.0.13.1      4         65001     29     35        5     0     0 00:23:03         1
10.0.23.1      4         65001     31     38        5     0     0 00:23:03         2
10.0.34.1      4         65002      0      0         1     0     0 never        Idle
10.0.35.2      4         65010      0      0         1     0     0 never        Active
R3#
```

show ip bgp 203.0.113.0

```
R3#show ip bgp 203.0.113.0
BGP routing table entry for 203.0.113.0/24, version 3
Paths: (2 available, best #2, table default)
  Advertised to update-groups:
    2
  Refresh Epoch 1
  65001
    10.0.23.1 from 10.0.23.1 (203.0.114.1)
      Origin IGP, metric 200, localpref 100, valid, external
      rx pathid: 0, tx pathid: 0
  Refresh Epoch 1
  65001
    10.0.13.1 from 10.0.13.1 (203.0.113.1)
      Origin IGP, metric 0, localpref 100, valid, external, best
      rx pathid: 0, tx pathid: 0x0
R3#
```

Ping from routers

```
sh route-map
```