ATmega328P Timer/Counter 1

Narendiran S

July 25, 2020

1 Features

- General purpose 16-bit PWM/Counter module.
- Two independent output compare units and One input capture unit
- Variable PWM.
- Four independent interrupt sources (TOV0, OCF0A, OCF1B and ICF1).
- Clear timer on compare match (auto reload)

2 Block Diagram



3 Terminologies and Registers

Parameter	Description
BOTTOM	counter reaches 0x0000
MAX	ounter reaches 0xFFFF
TOP	counter reaches highest value (depends on mode of operation can be 0xFF, 0x1FF, 0x3FF, OCR1A, ICR1)

Register - 16 bit	Name
TCN10	Timer/Counter1count value
TCCR1A	Timer/Coutner1 Control Register A
TCCR1B	Timer/Coutner1 Control Register B
OCBR1A	Output compare register A
OCBR1B	Output compare register B
TIFR1	Timer Interrupt Flag Register
TIMSK1	Timer interrupt Mask Register
ICR1	Input Capture Register

Note:

- The CNT1, OCR1A/B, and ICR1 are 16-bit registers that can be accessed by the CPU via the 8-bit data bus.
- **For 16-bit write, the high byte must be written before the low byte.**
- **For 16-bit read, the low byte must be read before the high byte.**

4 Timer/Counter1 Units

4.1 Clock Source/Select Unit



- The source for the Timer/Counter0 can be external or internal.
- External clock source is from *T1* pin.
- While Internal Clock source can be clocked via a prescalar.
- The output of this unit is the timer clock (clk_{T1}).
- It uses ***CS1[2:0]*** bits in **TCCR1B** register to select the source.

4.2 Counter Unit



Signal	Description
count	Increment or decrement TCNT1 by 1
direction	Select between increment or decrement
clear	Clears TCNT1 to 0x0000
clk_{T1}	Timer/Coutner1 clock
top	Signalize that TCNT1 has maximum value
bottom	Signalize that TCNT1 has minimum value(0x0000)

- The main part of the 16-bit Timer/Counter is the programmable bi-directional counter.
- Counter high (TCNT1H) containing the upper eight bits of the counter, and counter low (TCNT1L) containing the lower eight bits.
- Depending the mode of operation the counter is cleared, incremented, or decremented at each timer clock (clk_{T1}).
- Counting sequence is determined by ***WGM1[3:0]*** bits of **TCCR1A** -Timer/Counter1 Control register A and **TCCR1B** - Timer/Counter1 Control register B.
- The Timer/Counter1 Overflow flag ***(TOV1)*** is set and can generate interrupt according to the mode.

4.3 Input Capture Unit



- Can capture external events and give them time-stamp indicating time of occurance.
- External signal can be from ICP1 pin or analog-comparator unit.
- Usage : calculate frequency, duty-cycle, log of the signal
- When a change of the logic level (an event) occurs on the input capture pin (*ICP1*), or on the analog comparator output (*ACO*), and this change confirms to the setting of the edge detector, a capture will be triggered.
- When a capture is triggered, the 16-bit value of the counter (**TCNT1**) is written to the input capture register (**ICR1**).
- The input capture flag (***ICF1***) is set at the same system clock as the **TCNT1** value is copied into **ICR1** register.
- If enabled (***ICIE1*** = 1), the input capture flag generates an input capture interrupt.
- ***ICF1*** flag is automatically cleared when the interrupt is executed and by writing on to i.
- An input capture can be triggered by software by controlling the port of the *ICP1* pin.

4.4 Output Compare Unit



- 16-bit comparator continuously compares **TCNT1** with both **OCR1A** and **OCR1B**.
- When **TCNT1** equals **OCR1A** or **OCR1B**, the comparator signals a match which will set the output compare flag at the next timer clock cycle.
- If interrupts are enabled, then output compare interrupt is generated.
- The waveform generator uses the match signal to generate an output according to operating mode set by the ***WGM1[3:0]*** bits and compare output mode ***COM0x[1:0]*** bits.

4.5 Compare Match Output Unit



- This unit is used for changing the state of *OC1A* and *OC1B* pins by configuring the ***COM1x[1:0]*** bits.
- But, general I/O port function is overriiden by DDR reigster.