



AIM: To install the Damn Vulnerable Web Application (DVWA) on a local XAMPP server and use OWASP ZAP to perform an automated vulnerability scan against the running web application.

PROCEDURE:

1. Download and install XAMPP for Windows from <https://www.apachefriends.org>. From the XAMPP control panel, start the Apache and MySQL services.



2. Download DVWA from <https://github.com/digininja/DVWA>, extract it into C:\xampp\htdocs\dvwa and open <http://localhost/dvwa/setup.php> in the browser. Click 'Create / Reset Database'.



3. Login to DVWA using the default credentials admin / password and set DVWA Security to 'Low' from the DVWA Security tab.

DVWA Security

Security Level


Security level is currently: **low**.

You can set the security level to low, medium, high or impossible. The security level changes the vulnerability level of DVWA:


1. Low - This security level is completely vulnerable and **has no security measures at all**. It's use is to be as an example of how web application vulnerabilities manifest through bad coding practices and to serve as a platform to teach or learn basic exploitation techniques.
2. Medium - This setting is mainly to give an example to the user of **bad security practices**, where the developer has tried but failed to secure an application. It also acts as a challenge to users to refine their exploitation techniques.
3. High - This option is an extension to the medium difficulty, with a mixture of **harder or alternative bad practices** to attempt to secure the code. The vulnerability may not allow the same extent of the exploitation, similar in various Capture The Flags (CTFs) competitions.
4. Impossible - This level should be **secure against all vulnerabilities**. It is used to compare the vulnerable source code to the secure source code.
Prior to DVWA v1.9, this level was known as 'high'.

Low Submit


4. Download and install OWASP ZAP from <https://www.zaproxy.org>. Open ZAP and select 'Automated Scan'.



5. Enter the target URL <http://localhost/dvwa/> and click 'Attack'. ZAP will spider the site and run an active scan.



6. After the scan completes, open the 'Alerts' tab to view the vulnerabilities found in DVWA, such as Cross Site Scripting (XSS), SQL Injection, and CSRF.



RESULT: Thus, a vulnerable web application (DVWA) was installed locally and scanned successfully using OWASP ZAP, and the common web server / web application vulnerabilities were identified.