

G53FUZ

Fuzzy Sets and Systems

Fuzzy Modelling and Tuning
Real World Examples

Jon Garibaldi
*Intelligent Modelling and Analysis
Research Group*

Fuzzy Model Identification

- Finding a good fuzzy model can be formulated in terms of searching for a candidate solution from a (very) wide range of possibilities
 - model identification
 - model optimisation
 - model tuning
- There are very many design parameters in any fuzzy model
 - perhaps this is the ‘secret’ of success?

Structure or Parameters?

- Some people divide problem into two parts
 - structure identification
 - finding the number of linguistic variables, fuzzy terms (membership functions) in each, form of rules, etc.
 - parameter tuning
 - finding the exact values of the m.f. parameters, rule weights, defuzzification parameters, etc.
- All parts of the process can be parameterised and tuned
 - with the possibility of automatic methods

Selecting the ‘Best’

- Usually, each candidate fuzzy model has associated with it some measure of how good it is
 - objective function
 - cost function
 - error measure, RMS error (RMSE), error
- The structure and parameters can be altered and the performance measure either maximised or minimised
 - maximise objective functions / performance
 - minimise cost functions / error

FIS Example


- We want to create a system to advise on buying or selling shares
 - inputs
 - FTSE index (UK stock market price)
 - pound / dollar exchange rate
 - actually the daily change in each of these
 - output
 - advice on whether to sell/hold/buy Microsoft shares
 - daily advice to sell/hold/buy

FIS Structure

- Two inputs
 - FTSE index
 - three terms (m.f.s): falling, stable, rising
 - exchange_rate
 - three terms (m.f.s): down, unchanged, up
- One output
 - advice
 - three terms: sell, hold, buy
- Three rules
 1. If *exchange* is *falling* and *ftse* is *up* then *advice* is *buy*
 2. If *exchange* is *rising* and *ftse* is *down* then *advice* is *sell*
 3. If *exchange* is *stable* or *ftse* is *unchanged* then *advice* is *hold*

FIS Parameters

- Each of the two inputs has three triangular m.f.s with one shared control parameter



FIS Evaluation

- Produces advice on buying/selling shares
 - there is no obvious error to minimise
 - we have no pre-specified target output
 - the output itself is not an objective function
 - we have no objective measure of goodness of advice
- A suitable indirect objective function can be created by using the advice to buy/sell shares
 - trade shares (unseen data) over a certain period
 - how much money does one end up with?

Fuzzy Model Example

```
evalmodel <- function(ms, out) {
  cash= 1000
  shares= 0

  n= length(out)

  for ( i in 1:n ) {
    if ( out[i] >= 55 && cash >= ms[i] ) {
      # buy
      shares= shares + 1
      cash= cash - ms[i]
    } else if ( out[i] <= 45 && shares > 0 ) {
      # sell
      shares= shares - 1
      cash= cash + ms[i]
    }
  }

  value= cash + shares * ms[i]
}
```

Exhaustive Search

- Evaluate each combination in turn using some systematic method, e.g.
 - start (1,1) → (1,99)
 - (2,1) → (2,99)
 - ...
 - (99,1) → (99,99)
 - sometimes called the 'brute-force' approach
- This cannot be done for most real problems
 - there are too many combinations
 - too computationally expensive

Fuzzy Model Example

```
tune_ex <- function(inp, msr) {
  vmax= 0

  for ( i in 1:99 ) {
    for ( j in 1:99 ) {
      fis= makefis('shares', c(i, j) )
      out= evalfis(inp, fis)
      v= evalmodel(msr, out)
      if ( v > vmax ) {
        opt= fis
        vmax= v
      }
    }
  }

  return(list('fis'= opt, 'vmax'= vmax))
}
```

Monte Carlo

- Suppose we just guess random set of parameters
- The Monte Carlo algorithm
 - generate a random starting position
 - evaluate the starting position and store it as best
 - repeat
 - generate a new random position
 - evaluate the new position
 - if the new position is better than the best found so far
 - store the new position as the best
 - until we decide to stop (e.g. not improved for 20 goes)
- This may or may not find the global maximum

Fuzzy Model Example

```
tune_mc <- function(inp, msr) {
  vmax= 0
  for ( L in 1:50 ) {
    cp= sample(99, 2, replace=T)
    fis= makefis('shares', cp)
    out= evalfis(inp, fis)
    v= evalmodel(msr, out)
    if ( v > vmax ) {
      vmax= v
      opt= fis
    }
    rm(fis)
  }
  return(list('fis'= opt, 'vmax'= vmax))
}
```

Hill Climbing

- The hill climbing algorithm
 - start at either a fixed or random position
 - evaluate the current position
 - at each step
 - evaluate in each of the surrounding directions
 - up, down, left, right
 - move in direction of greatest improvement
 - stop if all moves are lower than current position
- This is guaranteed to find the peak (maximum)
 - but *only* if there is just one (global) maximum

Local Maxima

- Suppose the quality grid changes to this
- If the hill-climbing starts at e.g. (1,5) and heads *right* first
 - the global maximum at (5,5) is found
- However, if the hill-climbing starts at e.g. (1,5) and heads *up* first
 - a local maxima at (1,3) is found

		flour								
		1	2	3	4	5	6	7	8	9
sugar	1	1	2	3	2	1	2	3	2	1
	2	2	3	2	1	2	1	2	3	2
	3	3	2	1	2	3	2	1	2	3
	4	2	1	2	3	4	3	2	1	2
	5	1	2	3	4	5	4	3	2	1
	6	2	1	2	3	4	3	2	1	2
	7	3	2	1	2	3	2	1	2	3
	8	2	3	2	1	2	1	2	3	2
	9	1	2	3	2	1	2	3	2	1

Stochastic Local Search

- The performance of local hill climbing is very dependent on the shape of the landscape
 - if the landscape has very many local maxima, the chance of finding the global maximum is small
- Why not combine Monte Carlo + Hill Climbing?
 - repeat
 - generate a random starting position
 - hill climb to the local maximum
 - store best local maximum
 - until *stopping_criteria*
- *Stochastic*: 'random'
- *Local search*: moves in the local neighbourhood

Fuzzy Model Example

```
tune_hc <- function(inp, msr) {
  vmax= 0
  vt= rep(0,4)
  dp= rbind(c(-1,0),c(1,0),c(0,-1),c(0,1))
  for ( L in 1:20 ) {
    cp= sample(99, 2, replace=T)
    # hill climb to (local) maximum
    repeat {
      # get four surrounding positions (in random order)
      np= pmin(pmax(rep(cp,each=4) + dp[sample(4),, 1], 99)
      # evaluate each of the surrounding positions
      for ( k in 1:4 ) {
        fis= makefis('shares', np[k,])
        out= evalfis(inp, fis)
        vt[k]= evalmodel(msr, out)
        if ( vt[k] > vmax ) {
          vmax= vt[k]
          opt= fis
        }
      }
      # stop if new best is not an improvement
      if ( (vnew= max(vt)) <= v ) break
      # make current position the best new one
      v= vnew
      cp= np[which.max(vt),]
    }
  }
  return(list('fis'= opt, 'vmax'= vmax))
}
```

Simulated Annealing

- Search algorithm inspired by physical annealing
 - adaptation of hill climbing which allows some downhill steps
 - accept all uphill steps
 - start by allowing all downhill steps and then gradually reduce the likelihood (depending on the size of the downhill step)
- In the *simulated annealing* algorithm
 - a temperature parameter controls the algorithm
 - initially, at high temperatures
 - all downhill steps are allowed
 - the temperature is gradually reduced
 - (step size / temperature) governs the chances of acceptance

SA Outline

- SA algorithm is usually implemented as a refinement of the basic hill climbing algorithm
 - initialise temperature, T
 - generate random solution, i
 - repeat
 - generate a new (nearby) solution, j
 - if $fitness(j)$ is higher than $fitness(i)$ then accept the move
 - if $fitness(j)$ is lower than $fitness(i)$ then
 - accept the move according to a probability which decreases with the size of the difference in fitness and increases with temperature, T
 - reduce the temperature, T
 - until stopping criteria

Downhill Steps

- The equation for accepting downhill steps comes from the physical annealing process
$$e^{-\{\Delta E/T\}}$$
 - where ΔE is the *energy change*
- If the energy change is small (i.e. a small downhill move) or the temperature is high
$$e^{-\{\Delta E/T\}} \rightarrow e^{-0} \approx 1$$
, move probably accepted
- If the energy change is large (i.e. a large downhill move) or the temperature is low
$$e^{-\{\Delta E/T\}} \rightarrow e^{-\infty} \approx 0$$
, move probably rejected

SA Parameters

- Need to choose an initial temperature T such that
 - almost all moves are accepted (uphill & probably downhill)
 - the search is a 'random walk'
- The decrease the temperature T gradually, until
 - only uphill moves are accepted
 - the search is now a hill climb to the (local) optimum
- Can let the algorithm repeat a number of times at each T , rather than decreasing T after every step
 - the length parameter, L , specifies the number of steps to be repeated at each temperature, T

Fuzzy Model Example

```
tune_sa <- function(inp, msr) {  
  vmax= 0  
  cp= sample(99, 2, replace=T)  
  dp= rbind(c(-1,0),c(1,0),c(0,-1),c(0,1))  
  fis= makefis('shares', cp)  
  out= evalfis(inp, fis)  
  vmax= v= evalmodel(msr, out)  
  
  Temp= 50  
  for ( X in 1:50 ) {  
    for ( L in 1:10 ) {  
      np= pmin(gmax(cp + dp[sample(4,1),], 1), 99)  
      fis= makefis('shares', np)  
      out= evalfis(inp, fis)  
      vnew= evalmodel(msr, out)  
      if ( vnew >= v | runif(1) < exp(-(vnew-v) / Temp) ) {  
        cp= np  
        v= vnew  
      }  
      if ( v > vmax ) {  
        vmax= v  
        opt= fis  
      }  
      rm(fis)  
    }  
    Temp = Temp / 1.1  
  }  
  return(list('fis'= opt, 'vmax'= vmax))  
}
```

Real-Valued Parameters

- So far we have only considered integer values
 - only a fixed number of combinations of parameters
 - combinatorial optimisation*
- Suppose one or more parameters are *reals*
 - what step length should be used in e.g. hill climbing?
- Too big?
 - might step right over a sharp peak
- Too small?
 - might spend too long searching uninteresting areas

The Solution


- Dynamic step length dependent on terrain
- Ideally using the shape of the terrain
- But gradients are not (usually) available
- Need a gradient-free dynamic algorithm
- Solution: Nelder-Mead simplex
 - "A simplex method for function minimization"
 - J.A. Nelder and R. Mead
 - The Computer Journal*
 - Vol. 7: pp. 308–313, 1965

The Simplex Method

- A shape of with $N+1$ vertices is used where N is the dimensionality of the problem
 - e.g. a triangle in 2D
 - the shape starts at a random position
- Certain transformations of the shape are allowed
 - reflection of the lowest vertex through the opposite face
 - a reflection of the lowest with expansion
 - a contraction of the lowest towards the opposite face
 - a contraction along all faces towards the highest vertex
- If new point is higher, the new shape is accepted


A Simplex Illustrated

- A reflection results in an uphill step (improvement), so the step is accepted



Simplex Method with SA

- Uphill steps are always accepted



- Sometimes (randomly) accept downhill steps according to the simulated annealing algorithm

The Outcome of Labour

- A huge mix of outcome measures in childbirth
 - maternal
 - mortality (death)
 - morbidity (illness, injury)
 - blood loss, pain, postnatal depression
 - other
 - delivery mode, length of labour, type of anaesthetic
 - neonatal
 - mortality (death)
 - morbidity (illness, injury)
 - resuscitation, SCBU / NICU
 - other
 - birth weight, head circumference, adult IQ


Umbilical Cord Acid-Base Analysis



Umbilical Acid-Base Analysis

- Need evidence of oxygen lack during labour
- Clamp the umbilical cord immediately
 - sample arterial and venous blood
- Use blood gas analysis machine to measure
 - pH, $p\text{CO}_2$, $p\text{O}_2$
 - derive *base deficit* (extracellular fluid)
- Analysis of all these parameters in combination provides information on the severity and duration of lack of oxygen during labour
 - umbilical acid-base (UAB) analysis



Problems with UAB Analysis




- Need to distinguish *metabolic* from *respiratory* acidemia
- Need pH and $p\text{CO}_2$ from **both** artery and vein
 - input and output blood
- 25% error rate typical
 - errors go unnoticed
- Difficult to interpret
 - too many figures
 - considerable experience required
- Must be done on every delivery
 - staff availability

Fuzzy Expert System

1. Validates results



2. Stores information to database




3. Provides an interpretation

The Fuzzy Expert System

- Fuzzy rule base elicited from experts (25 rules)
 - four fuzzy input variables
 - $p\text{Ha}$, $p\text{Hv}$: 4 fuzzy terms (*low*, *intermediate*, *normal*, *high*)
 - BDa , BDv : 3 fuzzy terms (*low*, *intermediate*, *high*)
 - three fuzzy output variables
 - *acidemia*: 5 terms (*severe*, *significant*, *moderate*, *mild*, *none*)
 - *component*: 3 terms (*metabolic*, *mixed*, *respiratory*)
 - *duration*: 3 terms (*chronic*, *intermediate*, *acute*)
- The FES implicitly interprets imprecise or missing input parameters
 - crisp system required separate rules (54 rules total)

Example Membership Functions




Fuzzy Inference

- Use rules of fuzzy logic to perform approximate reasoning with linguistic variables in a fuzzy ES
- The rules can be directly in the form elicited from the human expert, for example


IF $p\text{Ha}$ IS *low* AND BDa IS *high* AND $p\text{Hv}$ IS *low* AND BDv IS *high*

THEN *acidemia* IS *severe* AND *component* IS *metabolic*
- Multiple rules fire to form complex fuzzy output


Imprecise Input Parameters



Missing Input Parameters



Example of Fuzzy Inference



The Validation Task

- 50 difficult umbilical acid-base cases selected
- Ranked in order from 'worst' to 'best'
 - consider four dimensional data in parallel
 - as pH decreases, condition is worse
 - as BD increases, condition is worse
 - so, which is worse?

<i>pHa</i>	<i>BDa</i>	<i>pHv</i>	<i>BDv</i>
6.94	11.6	6.97	11.8
6.87	8.5	7.11	9.4

Comparisons of Performance

- Used Spearman Rank Correlation to compare
 - relationship to performance of clinicians
 - clinicians to each other
 - crisp system to clinicians
 - fuzzy system to clinicians
 - relationship to other immediate outcome by Apgar score at 1 and 5 minutes
 - clinicians to outcome
 - crisp system to outcome
 - fuzzy system to outcome

Initial Results


- Agreement with clinicians
 - clinicians \Leftrightarrow clinicians ≈ 0.91
 - crisp \Leftrightarrow clinicians ≈ 0.80
 - **fuzzy \Leftrightarrow clinicians ≈ 0.67**
- Agreement with *outcome*
 - clinicians \Leftrightarrow *outcome* ≈ 0.64
 - crisp \Leftrightarrow *outcome* ≈ 0.52
 - **fuzzy \Leftrightarrow *outcome* ≈ 0.25**

Fuzzy System Detail

- Mamdani model
 - max-min inference
 - sigmoid membership functions
 - terms matched to crossovers in crisp rules
- Rules from expert elicitation
 - all rules feature all four input variables
- Centroid defuzzification
 - acidemia
 - component
 - duration
 - $PIAD = \text{acidemia} / X + \text{component} / Y + \text{duration} / Z$

Fuzzy Choices

- And/Or operators
 - $A \text{ and } B = \min(A, B)$ $A \text{ or } B = \max(A, B)$
 - $A \text{ and } B = A * B$ $A \text{ or } B = A + B - A * B$
- Membership functions
 - shape
 - sigmoid, triangular, arbitrary
 - characteristics
 - number of terms, locations, crossovers
- Number / form of rules




Fuzzy Model Tuning

- The *simplex method* with modifications to include simultaneous simulated annealing based optimisation of
 - integers (combinatorial optimisation)
 - reals (continuous optimisation)
 was applied to the initial fuzzy expert system
- *Application of Simulated Annealing Fuzzy Model Tuning to Umbilical Acid-Base Interpretation*
 - J.M. Garibaldi and E.C. Ifeachor
 - IEEE Trans Fuzzy Systems, 7(1), 72-84, 1999

Fuzzy System Refined


- As a result of tuning, the fuzzy expert system was modified to improve performance
 - the best number of pHa and pHv terms was found to be four (rather than three)
 - all membership functions were shifted
 - 'optimal' linear combination of outputs was found
 - $PIAD = \text{acidemia} + \text{component} / 20 + \text{duration} / 10$



Tuned Fuzzy System Results

- Agreement with clinicians
 - clinicians \Leftrightarrow clinicians ≈ 0.91
 - crisp \Leftrightarrow clinicians ≈ 0.80
 - fuzzy¹ \Leftrightarrow clinicians ≈ 0.67
 - **fuzzy² \Leftrightarrow clinicians ≈ 0.93**
- Agreement with *outcome*
 - clinicians \Leftrightarrow *outcome* ≈ 0.64
 - crisp \Leftrightarrow *outcome* ≈ 0.52
 - fuzzy¹ \Leftrightarrow *outcome* ≈ 0.25
 - **fuzzy² \Leftrightarrow *outcome* ≈ 0.65**

Agreement with FES



Summary

- Lecture summary
 - fuzzy model identification comprises finding the structure and parameters of a fuzzy system
 - there are various (semi-) automatic algorithmic approaches that can be used to tune systems
 - a real world example in umbilical acid-base analysis demonstrates the real benefits in fuzzy tuning
- Next lecture
 - ANFIS: adaptive neuro-fuzzy inference system