

Narmadha

S

ECE D

24080121

6

Problem Statement:1

A binary number is a combination of 1s and 0s. Its n th least significant digit is the n th digit

starting from the right starting with 1. Given a decimal number, convert it to binary and

determine the value of the 4th least significant digit.

Example

number=23

- Convert the decimal number 23 to binary number: $23_{10} = 2^4 + 2^2 + 2^1 + 2^0 = (10111)_2$.

- The value of the 4th index from the right in the binary representation is 0.

Function Description

Complete the function fourthBit in the editor below. fourthBit

has the following parameter(s):

int number: a decimal integer

Returns:

int: an integer 0 or 1 matching the 4th least significant digit in the binary representation of number.

Constraints

$0 \leq \text{number} < 2^{31}$

Input Format for Custom Testing

Input from stdin will be processed as follows and passed to the function. The only line contains an integer, number.

Sample Input

STDIN Function

32 → number=32

Sample Output

0



Explanation

- Convert the decimal number 32 to binary number: $32_{10} = (100000)_2$.
- The value of the 4th index from the right in the binary representation is 0.

```
1  /*
2   * Complete the 'fourthBit' function below.
3   *
4   * The function is expected to return an INTEGER.
5   * The function accepts INTEGER number as parameter.
6   */
7
8  int fourthBit(int number)
9  {
10     int binary[32];
11     int i = 0;
12     while(number > 0)
13     {
14         binary[i] = number % 2;
15         number /= 2;
16         i++;
17     }
18     if(i >= 4)
19     {
20         return binary[3];
21     }
22     else
23         return 0;
24 }
```

	Test	Expected	Got	
✓	printf("%d", fourthBit(32))	0	0	✓
✓	printf("%d", fourthBit(77))	1	1	✓

Passed all tests! ✓



ProblemStatement:2

Determinethefactorsofanumber(i.e.,allpositiveintegervaluesthat evenly divide into a number)andthenreturnthepthelementofthelist,sortedascending.If there is no pth element,return0.

Example

n = 20

p=3

Thefactorsof20inascendingorderare{1,2,4,5,10,20}.Using1-based indexing, if p =

3,then4isreturned.If p>6,0wouldbereturned. Function

Description

ComplethefunctionpthFactorintheeditorbelow.

pthFactor has the following parameter(s):

intn:theintegerwhosefactorsaretobefound



int:theindexofthefactortobereturned

Returns:

int:thelongintegervalueofthe p thintegerfactorof n ,ifthereisno factor at that index,then0isreturned

Constraints

$1 \leq n \leq 10^{15}$

$1 \leq p \leq 10^9$

InputFormatforCustomTesting

Inputfromstdinwillbeprocessedasfollowsandpassedtothefunction. The first line contains an integer n , the number to factor.

Thesecondlinecontainsaninteger p ,the1-basedindexofthefactorto return.

Sample Input

STDINFunction

$10 \rightarrow n=10$

$3 \rightarrow p = 3$

SampleOutput

5

Explanation

Factoring $n=10$ resultsin $\{1,2,5,10\}$.Returnthe $p=3$ rdfactor,5,asthe answer.



```

2  *Complethe'pthFactor' functionbelow.
4  *ThefunctionisexpectedtoreturnaLONGINTEGER.
5  *Thefunctionaccepts*ollowingparameters:
6  "1.LONGINTEGERn
7  "2.LOfJG_IfJTEGERp
8  "/"
10 long pthFactor(long n, long p)
11 {
12     int count=0;
13     for(long i=1; i<=n; ++i)
14     {
15         if(n%i==0)
16         {
17             count++;
18             if(count==p)
19                 return i;
20         }
21     }
22     return 0;
23 }
24
25

```

Test		ExpectedGot	
W	printf("&1d",pthFactor(10,3))	5	✓
	printf("%ld",pthFactor(10,5))	0	✓
	printf("%ld",pthFactor(1,1))	1	✓
Passed all tests! ✓			



ProblemStatement:3

Youareabankaccountthacker.Initiallyyouhave1rupeeinyouraccount, and you want exactlyNrupeesinyouraccount.Youwrotetwohacks,firsthackcan multiply the amount ofmoneyyouownby10,whilethesecondcanmultiplyitby20.These hacks can be used anynumeroftime.CanyouachievethedesiredamountNusingthese hacks.

Constraints:

$$1 \leq T \leq 100$$

$$1 \leq N \leq 10^{12}$$

Input

- ThetestcasecontainsasingleintegerN.

Output

Foreachtestcase,printasinglelinecontainingthestring"1"ifyoucan make exactly N rupeesor"0"otherwise. SAMPLE

INPUT



1

SAMPLEOUTPUT 1

SAMPLEINPUT 2

SAMPLEOUTPUT 0

```
2  * Complete the 'myFunc' function below.
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts INTEGER n as parameter.
6  */
7
8  int myFunc(int n)
9  {
10     if(n == 1) return 1;
11     if(n % 10 == 0 && myFunc(n / 10)) return 1;
12     if(n % 20 == 0 && myFunc(n / 20)) return 1;
13     return 0;
14 }
15
```

	Test	Expected	Got	
✓	printf("%d", myFunc(1))	1	1	✓
✓	printf("%d", myFunc(2))	0	0	✓
✓	printf("%d", myFunc(10))	1	1	✓
✓	printf("%d", myFunc(25))	0	0	✓
✓	printf("%d", myFunc(200))	1	1	✓

Passed all tests! ✓



Edit with WPS Office

Problem Statement:4

Find the number of ways that a given integer, X , can be expressed as the sum of the N th

powers of unique, natural numbers.

For example, if $X=13$ and $N=2$, we have to find all combinations of unique squares adding

upto 13. The only solution is $2^2 + 3^2$. Function

Description

Complete the powerSum function in the editor below. It should return an integer that represents the number of possible combinations.

powerSum has the following parameter(s):

X : the integer to sum to

N : the integer power to raise numbers to Input

Format

The first line contains an integer X .

The second line contains an integer N .

Constraints

$$1 \leq X \leq 1000$$

$$2 \leq N \leq 10$$

Output Format

Output a single integer, the number of possible combinations calculated. Sample

Input

10

2

Sample Output

1

Explanation

If $X=10$ and $N=2$, we need to find the number of ways that 10 can be represented as the

sum of squares of unique numbers. 10

$$= 1^2 + 3^2$$



This is the only way in which 10 can be expressed as the sum of unique squares.

```
1  /*
2  * Complete the 'powerSum' function below.
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts following parameters:
6  * 1. INTEGER x
7  * 2. INTEGER n
8  */
9
10 int powerSum(int x, int m, int n)
11 {
12     int power = 1;
13     for(int i = 0; i < n; i++)
14         power *= m;
15     if(power > x) return 0;
16     if(power == x) return 1;
17     return powerSum(x - power, m + 1, n) + powerSum(x, m + 1, n);
18 }
```

	Test	Expected	Got	
✓	printf("%d", powerSum(10, 1, 2))	1	1	✓

Passed all tests! ✓

Finish review



Edit with WPS Office