



Spring - SimpleJdbcTemplate with Example

Last Updated : 23 Jul, 2025

The **SimpleJdbcTemplate** includes all the features and functionalities of the **JdbcTemplate** class, and it also supports the **Java 5 features** such as var-args(variable arguments) and autoboxing. Along with the **JdbcTemplate** class, it also provides the **update()** method, which takes two arguments the SQL query and arbitrary arguments that depend upon the SQL query. In order to access the methods of the old **JdbcTemplate** class, we use the **getJdbcOperations()** method and we call all those methods over **SimpleJdbcTemplate**.

Key features of Spring SimpleJdbcTemplate:

- Simplified database operations with parameterized queries.
- Support for Java 5 features like var-args and autoboxing.
- Backward compatibility with **JdbcTemplate** methods using **getJdbcOperations()**.
- Seamless integration for Spring database operations.

Note: We need to pass the parameters inside the **update()** method in the same order we defined them in the parameterized query.

Syntax for update() method

```
int update(String sqlQuery, Object parameters)
```

Step-by-Step Implementation

In this example, we will update a student's details using the **update()** method of the **SimpleJdbcTemplate** class. For this tutorial, we will be

using the following schema for the Student table.

```
Student(id INT, name VARCHAR(45), department VARCHAR(45))
```

Step 1: Create the Student Table

In this step, we will create a Student table to store students' information. For this tutorial, we will assume you have created the following table in your database.

```
CREATE TABLE STUDENT(  
  id INT PRIMARY KEY,  
  name VARCHAR(45),  
  department VARCHAR(45)  
);
```

After creating the table we will insert the following data in our table.

```
INSERT INTO STUDENT VALUES(1, "geek", "computer science");
```

Step 2: Adding dependencies

To use Spring JDBC, we need to add the following dependencies to the pom.xml file

```
<dependencies>  
  <!-- Spring JDBC Dependency -->  
  <dependency>  
    <groupId>org.springframework</groupId>  
    <artifactId>spring-jdbc</artifactId>  
    <version>5.3.23</version> <!-- Use the Latest stable version -->  
  </dependency>  
  
  <!-- Database Driver (Example: MySQL) -->  
  <dependency>  
    <groupId>mysql</groupId>  
    <artifactId>mysql-connector-java</artifactId>
```



```
<version>8.0.33</version> <!-- Use the version compatible with your
database -->
</dependency>
</dependencies>
```

Note: Replace the database driver with the appropriate one for your database (e.g., H2, PostgreSQL).

Step 3: Create a model class

Create a Student class to represent the student entity. This class will have three fields: id, name, and department. Include constructors, getters, setters, and a toString() method.

```
public class Student {
    // member variables
    private int id;
    private String name;
    private String department;

    // no args constructor
    public Student(){}

    // parameterized constructor
    public Student(int id, String name, String department) {
        super();
        this.id = id;
        this.name = name;
        this.department = department;
    }

    // getters and setters method
    public int getId() {
        return id;
    }
    public void setId(int id) {
        this.id = id;
    }
    public String getName() {
        return name;
    }
    public void setName(String name) {
        this.name = name;
    }
    public String getDepartment() {
        return department;
    }
    public void setDepartment(String department) {
```

```

        this.department = department;
    }

    // toString() method
    @Override
    public String toString() {
        return "Student [id=" + id + ", name=" + name + ", department=" +
department + " ]";
    }
}

```

Step 4: Create a DAO class

In this step, we will create a StudentDao.java class. In this class, we will define **SimpleJdbcTemplate** and **update()** method and provide its definition to update our data.

```

import org.springframework.jdbc.core.JdbcTemplate;
import org.springframework.dao.DataAccessException;
import javax.sql.DataSource;

public class StudentDao {

    // Defining JdbcTemplate as a member variable
    private JdbcTemplate jdbcTemplate;

    // Constructor - used to inject DataSource using constructor injection
    public StudentDao(DataSource dataSource) {
        this.jdbcTemplate = new JdbcTemplate(dataSource);
    }

    // Method to update student details
    public int update(Student student) {
        String sqlQuery = "UPDATE student SET name = ? WHERE id = ?";

        try {
            // Execute the update query
            return jdbcTemplate.update(sqlQuery, student.getName(),
student.getId());
        } catch (DataAccessException e) {

            // Handle database-related exceptions
            System.err.println("Error updating student: " + e.getMessage());
            return 0; // Return 0 to indicate failure
        }
    }
}

```

Note: The update() method of JdbcTemplate takes the SQL query and parameters as arguments. The parameters must be passed in the same order as they appear in the query.

Step 5: Configure Spring Beans

In this step, we will create the Spring configuration file named application-context.xml. This file will define the beans required for database connectivity and dependency injection.

```
<beans xmlns="http://www.springframework.org/schema/beans/"
        xmlns:xsi="https://www.w3.org/2001/XMLSchema-instance"
        xsi:schemaLocation="http://www.springframework.org/schema/beans/
        http://www.springframework.org/schema/beans//spring-beans.xsd">

    <!-- Database DataSource Configuration -->
    <bean id="dataSource"
class="org.springframework.jdbc.datasource.DriverManagerDataSource">
        <property name="driverClassName" value="com.mysql.cj.jdbc.Driver" />
        <property name="url"
value="jdbc:mysql://localhost:3306/your_database" />
        <property name="username" value="root" />
        <property name="password" value="password" />
    </bean>

    <!-- StudentDao Bean Configuration -->
    <bean id="studentDao" class="com.geeksforgeeks.dao.StudentDao">
        <constructor-arg ref="dataSource" />
    </bean>
</beans>
```

Note: Replace the url, username, and password with your actual database credentials.

Step 6: Create a Utility Class for Testing

Now, we will create a Utility class for testing our application. For this create a new class and name it **TestSimpleJdbcTemplate.java** and add the following code to it.

```

import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;

public class TestJdbcTemplate {
    public static void main(String[] args) {

        // Load the Spring configuration file
        ApplicationContext context = new
        ClassPathXmlApplicationContext("application-context.xml");

        // Get the StudentDao bean
        StudentDao studentDao = context.getBean("studentDao",
        StudentDao.class);

        // Update student details
        int rowsUpdated = studentDao.updateStudent(1, "updatedName",
        "updatedDepartment");

        // Verify the result
        if (rowsUpdated > 0) {
            System.out.println("Student details updated successfully!");
        } else {
            System.out.println("Failed to update student details.");
        }
    }
}

```

Output:

Now, we will run our application. If the update() method will return 1 it means the query is executed successfully otherwise not.



```

<terminated> TestSimpleJdbcTemplate [Java Application] C:\Users\palan\p2\pool\plugins\c
Feb 28, 2022 6:21:26 PM org.springframework.beans.factory.xml:
INFO: Loading XML bean definitions from class path resource [a
Feb 28, 2022 6:21:26 PM org.springframework.jdbc.datasource.D
INFO: Loaded JDBC driver: com.mysql.jdbc.Driver
1

```

We will also cross-check it by executing the query at the database. We have created a student table and inserted the following data 1, "geek", "computer science" respectively.

```
SELECT * FROM STUDENT WHERE id = 1;
```

Result Grid			
Filter Rows: <input type="text"/>			
	id	name	department
▶	1	Rohan	computer science

[Comment](#)[More info](#)[Advertise with us](#)**Corporate & Communications Address:**

A-143, 7th Floor, Sovereign Corporate
Tower, Sector- 136, Noida, Uttar Pradesh
(201305)

Registered Address:

K 061, Tower K, Gulshan Vivante
Apartment, Sector 137, Noida, Gautam
Buddh Nagar, Uttar Pradesh, 201305

[Advertise with us](#)**Company**

[About Us](#)
[Legal](#)
[Privacy Policy](#)
[Careers](#)
[Contact Us](#)
[Corporate Solution](#)
[Campus Training Program](#)

Tutorials

[Programming Languages](#)

Explore

[POTD](#)
[Job-A-Thon](#)
[Connect](#)
[Community](#)
[Videos](#)
[Blogs](#)
[Nation Skill Up](#)

Courses

[IBM Certification](#)