

# CEE 616: Probabilistic Machine Learning

## M5 Unsupervised Learning:

### 5B: Factor Analysis and Autoencoders

**Jimi Oke**

UMass**Amherst**  

---

College of Engineering

Dec 4, 2025



# Outline

- ① Factor analysis
- ② FA Estimation
- ③ Autoencoders
- ④ AE variants
- ⑤ Outlook



# Factor analysis model



# Factor analysis model

- Basic idea: there are latent (hidden) **common factors**  $\mathbf{z}$  underlying some multivariate observations  $\mathbf{x}_n \in \mathbb{R}^D$



# Factor analysis model

- Basic idea: there are latent (hidden) **common factors**  $\mathbf{z}$  underlying some multivariate observations  $\mathbf{x}_n \in \mathbb{R}^D$

Factor analysis (FA) is a latent variable generative model specified as:



# Factor analysis model

- Basic idea: there are latent (hidden) **common factors**  $\mathbf{z}$  underlying some multivariate observations  $\mathbf{x}_n \in \mathbb{R}^D$

Factor analysis (FA) is a latent variable generative model specified as:

$$p(\mathbf{z}) = \mathcal{N}(\mathbf{z} | \boldsymbol{\mu}_0, \boldsymbol{\Sigma}_0) \quad (1)$$



# Factor analysis model

- Basic idea: there are latent (hidden) **common factors**  $\mathbf{z}$  underlying some multivariate observations  $\mathbf{x}_n \in \mathbb{R}^D$

Factor analysis (FA) is a latent variable generative model specified as:

$$p(\mathbf{z}) = \mathcal{N}(\mathbf{z} | \boldsymbol{\mu}_0, \boldsymbol{\Sigma}_0) \quad (1)$$

$$p(\mathbf{x} | \mathbf{z}, \boldsymbol{\theta}) = \mathcal{N}(\mathbf{x} | \mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (2)$$



# Factor analysis model

- Basic idea: there are latent (hidden) **common factors**  $\mathbf{z}$  underlying some multivariate observations  $\mathbf{x}_n \in \mathbb{R}^D$

Factor analysis (FA) is a latent variable generative model specified as:

$$p(\mathbf{z}) = \mathcal{N}(\mathbf{z} | \boldsymbol{\mu}_0, \boldsymbol{\Sigma}_0) \quad (1)$$

$$p(\mathbf{x} | \mathbf{z}, \boldsymbol{\theta}) = \mathcal{N}(\mathbf{x} | \mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (2)$$

where:

- $\mathbf{z}$ : latent vector



# Factor analysis model

- Basic idea: there are latent (hidden) **common factors**  $\mathbf{z}$  underlying some multivariate observations  $\mathbf{x}_n \in \mathbb{R}^D$

Factor analysis (FA) is a latent variable generative model specified as:

$$p(\mathbf{z}) = \mathcal{N}(\mathbf{z} | \boldsymbol{\mu}_0, \boldsymbol{\Sigma}_0) \quad (1)$$

$$p(\mathbf{x} | \mathbf{z}, \boldsymbol{\theta}) = \mathcal{N}(\mathbf{x} | \mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (2)$$

where:

- $\mathbf{z}$ : latent vector
- $\mathbf{W}$ : factor loading matrix,  $D \times L$



# Factor analysis model

- Basic idea: there are latent (hidden) **common factors**  $\mathbf{z}$  underlying some multivariate observations  $\mathbf{x}_n \in \mathbb{R}^D$

Factor analysis (FA) is a latent variable generative model specified as:

$$p(\mathbf{z}) = \mathcal{N}(\mathbf{z} | \boldsymbol{\mu}_0, \boldsymbol{\Sigma}_0) \quad (1)$$

$$p(\mathbf{x} | \mathbf{z}, \boldsymbol{\theta}) = \mathcal{N}(\mathbf{x} | \mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (2)$$

where:

- $\mathbf{z}$ : latent vector
- $\mathbf{W}$ : factor loading matrix,  $D \times L$
- $\boldsymbol{\Psi}$ : diagonal covariance matrix,  $D \times D$



# Factor analysis model

- Basic idea: there are latent (hidden) **common factors**  $\mathbf{z}$  underlying some multivariate observations  $\mathbf{x}_n \in \mathbb{R}^D$

Factor analysis (FA) is a latent variable generative model specified as:

$$p(\mathbf{z}) = \mathcal{N}(\mathbf{z} | \boldsymbol{\mu}_0, \boldsymbol{\Sigma}_0) \quad (1)$$

$$p(\mathbf{x} | \mathbf{z}, \boldsymbol{\theta}) = \mathcal{N}(\mathbf{x} | \mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (2)$$

where:

- $\mathbf{z}$ : latent vector
- $\mathbf{W}$ : factor loading matrix,  $D \times L$
- $\boldsymbol{\Psi}$ : diagonal covariance matrix,  $D \times D$



# Induced marginal distribution



# Induced marginal distribution

$$p(\mathbf{x}|\boldsymbol{\theta}) =$$



# Induced marginal distribution

$$p(\mathbf{x}|\boldsymbol{\theta}) = \int \mathcal{N}(\mathbf{x}|\mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi})\mathcal{N}(\mathbf{z}|\boldsymbol{\mu}_0, \boldsymbol{\Sigma}_0)d\mathbf{z} \quad (3)$$



# Induced marginal distribution

$$p(\mathbf{x}|\boldsymbol{\theta}) = \int \mathcal{N}(\mathbf{x}|\mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \mathcal{N}(\mathbf{z}|\boldsymbol{\mu}_0, \boldsymbol{\Sigma}_0) d\mathbf{z} \quad (3)$$

$$= \mathcal{N}(\mathbf{x} | \underbrace{\mathbf{W}\boldsymbol{\mu}_0 + \boldsymbol{\mu}}_{\text{mean}}, \underbrace{\boldsymbol{\Psi} + \mathbf{W}\boldsymbol{\Sigma}_0\mathbf{W}^\top}_{\text{variance}}) \quad (4)$$



# Induced marginal distribution

$$p(\mathbf{x}|\boldsymbol{\theta}) = \int \mathcal{N}(\mathbf{x}|\mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \mathcal{N}(\mathbf{z}|\boldsymbol{\mu}_0, \boldsymbol{\Sigma}_0) d\mathbf{z} \quad (3)$$

$$= \mathcal{N}(\mathbf{x} | \underbrace{\mathbf{W}\boldsymbol{\mu}_0 + \boldsymbol{\mu}}_{\text{mean}}, \underbrace{\boldsymbol{\Psi} + \mathbf{W}\boldsymbol{\Sigma}_0\mathbf{W}^\top}_{\text{variance}}) \quad (4)$$

Simplifications:

- $\boldsymbol{\mu}_0 \rightarrow \mathbf{0}$



# Induced marginal distribution

$$p(\mathbf{x}|\boldsymbol{\theta}) = \int \mathcal{N}(\mathbf{x}|\mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi})\mathcal{N}(\mathbf{z}|\boldsymbol{\mu}_0, \boldsymbol{\Sigma}_0)d\mathbf{z} \quad (3)$$

$$= \mathcal{N}(\mathbf{x}|\underbrace{\mathbf{W}\boldsymbol{\mu}_0 + \boldsymbol{\mu}}_{\text{mean}}, \underbrace{\boldsymbol{\Psi} + \mathbf{W}\boldsymbol{\Sigma}_0\mathbf{W}^\top}_{\text{variance}}) \quad (4)$$

Simplifications:

- $\boldsymbol{\mu}_0 \rightarrow \mathbf{0}$
- $\boldsymbol{\Sigma}_0 \rightarrow \mathbf{I}$



# Induced marginal distribution

$$p(\mathbf{x}|\boldsymbol{\theta}) = \int \mathcal{N}(\mathbf{x}|\mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \mathcal{N}(\mathbf{z}|\boldsymbol{\mu}_0, \boldsymbol{\Sigma}_0) d\mathbf{z} \quad (3)$$

$$= \mathcal{N}(\mathbf{x} | \underbrace{\mathbf{W}\boldsymbol{\mu}_0 + \boldsymbol{\mu}}_{\text{mean}}, \underbrace{\boldsymbol{\Psi} + \mathbf{W}\boldsymbol{\Sigma}_0\mathbf{W}^\top}_{\text{variance}}) \quad (4)$$

Simplifications:

- $\boldsymbol{\mu}_0 \rightarrow \mathbf{0}$
- $\boldsymbol{\Sigma}_0 \rightarrow \mathbf{I}$

The simplified marginal distribution then becomes:



# Induced marginal distribution

$$p(\mathbf{x}|\boldsymbol{\theta}) = \int \mathcal{N}(\mathbf{x}|\mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi})\mathcal{N}(\mathbf{z}|\boldsymbol{\mu}_0, \boldsymbol{\Sigma}_0)d\mathbf{z} \quad (3)$$

$$= \mathcal{N}(\mathbf{x}|\underbrace{\mathbf{W}\boldsymbol{\mu}_0 + \boldsymbol{\mu}}_{\text{mean}}, \underbrace{\boldsymbol{\Psi} + \mathbf{W}\boldsymbol{\Sigma}_0\mathbf{W}^\top}_{\text{variance}}) \quad (4)$$

Simplifications:

- $\boldsymbol{\mu}_0 \rightarrow \mathbf{0}$
- $\boldsymbol{\Sigma}_0 \rightarrow \mathbf{I}$

The simplified marginal distribution then becomes:

$$p(\mathbf{x}|\boldsymbol{\theta}) = \mathcal{N}(\mathbf{x}|\boldsymbol{\mu}, \mathbf{W}\mathbf{W}^\top + \boldsymbol{\Psi}) \quad (5)$$



# Generative model simplified

$$\text{[Prior]} \quad p(\mathbf{z}) = \mathcal{N}(\mathbf{z}|\mathbf{0}, \mathbf{I}) \quad (6)$$



# Generative model simplified

$$\begin{array}{ll} \text{[Prior]} & p(\mathbf{z}) = \mathcal{N}(\mathbf{z}|\mathbf{0}, \mathbf{I}) \\ \text{[Likelihood]} & p(\mathbf{x}|\mathbf{z}) \end{array} \quad (6)$$



# Generative model simplified

$$\text{[Prior]} \quad p(\mathbf{z}) = \mathcal{N}(\mathbf{z}|\mathbf{0}, \mathbf{I}) \quad (6)$$

$$\text{[Likelihood]} \quad p(\mathbf{x}|\mathbf{z}) = \mathcal{N}(\mathbf{x}|\mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (7)$$



# Generative model simplified

$$\text{[Prior]} \quad p(\mathbf{z}) = \mathcal{N}(\mathbf{z}|\mathbf{0}, \mathbf{I}) \quad (6)$$

$$\text{[Likelihood]} \quad p(\mathbf{x}|\mathbf{z}) = \mathcal{N}(\mathbf{x}|\mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (7)$$

$$\text{[Evidence/marginal]} \quad p(\mathbf{x})$$



# Generative model simplified

$$\text{[Prior]} \quad p(\mathbf{z}) = \mathcal{N}(\mathbf{z}|\mathbf{0}, \mathbf{I}) \quad (6)$$

$$\text{[Likelihood]} \quad p(\mathbf{x}|\mathbf{z}) = \mathcal{N}(\mathbf{x}|\mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (7)$$

$$\text{[Evidence/marginal]} \quad p(\mathbf{x}) = \mathcal{N}(\mathbf{x}|\boldsymbol{\mu}, \mathbf{W}\mathbf{W}^\top + \boldsymbol{\Psi}) \quad (8)$$



# What FA does



# What FA does

It approximates the covariance matrix of the visible/observed vector  $\mathbf{x}$  using a low-rank decomposition:



# What FA does

It approximates the covariance matrix of the visible/observed vector  $\mathbf{x}$  using a low-rank decomposition:

$$\mathbf{C} = \text{Cov}[\mathbf{x}] = \underbrace{\mathbf{W}\mathbf{W}^T}_{\text{low-rank decomp}} + \mathbf{\Psi} \quad (9)$$



# What FA does

It approximates the covariance matrix of the visible/observed vector  $\mathbf{x}$  using a low-rank decomposition:

$$\mathbf{C} = \text{Cov}[\mathbf{x}] = \underbrace{\mathbf{W}\mathbf{W}^\top}_{\text{low-rank decomp}} + \mathbf{\Psi} \quad (9)$$

- $\mathbf{W}\mathbf{W}^\top$  is  $D \times D$  (recall:  $\mathbf{W} \in \mathbb{R}^{D \times L}$ )



# What FA does

It approximates the covariance matrix of the visible/observed vector  $\mathbf{x}$  using a low-rank decomposition:

$$\mathbf{C} = \text{Cov}[\mathbf{x}] = \underbrace{\mathbf{W}\mathbf{W}^\top}_{\text{low-rank decomp}} + \mathbf{\Psi} \quad (9)$$

- $\mathbf{W}\mathbf{W}^\top$  is  $D \times D$  (recall:  $\mathbf{W} \in \mathbb{R}^{D \times L}$ )
- $\mathbf{\Psi}$  is  $D \times D$  (restricted to be diagonal)



# What FA does

It approximates the covariance matrix of the visible/observed vector  $\mathbf{x}$  using a low-rank decomposition:

$$\mathbf{C} = \text{Cov}[\mathbf{x}] = \underbrace{\mathbf{W}\mathbf{W}^\top}_{\text{low-rank decomp}} + \mathbf{\Psi} \quad (9)$$

- $\mathbf{W}\mathbf{W}^\top$  is  $D \times D$  (recall:  $\mathbf{W} \in \mathbb{R}^{D \times L}$ )
- $\mathbf{\Psi}$  is  $D \times D$  (restricted to be diagonal)
- For each variable  $x_d$ , the **marginal variance** (each diagonal term in  $\mathbf{C}$ ) is given by:



# What FA does

It approximates the covariance matrix of the visible/observed vector  $\mathbf{x}$  using a low-rank decomposition:

$$\mathbf{C} = \text{Cov}[\mathbf{x}] = \underbrace{\mathbf{W}\mathbf{W}^\top}_{\text{low-rank decomp}} + \mathbf{\Psi} \quad (9)$$

- $\mathbf{W}\mathbf{W}^\top$  is  $D \times D$  (recall:  $\mathbf{W} \in \mathbb{R}^{D \times L}$ )
- $\mathbf{\Psi}$  is  $D \times D$  (restricted to be diagonal)
- For each variable  $x_d$ , the **marginal variance** (each diagonal term in  $\mathbf{C}$ ) is given by:

$$\mathbb{V}[x_d] = \sum_{k=1}^L \underbrace{w_{dk}^2}_{\text{common}} + \underbrace{\psi_d}_{\text{unique}} \quad (10)$$



# Parameters to be estimated



# Parameters to be estimated

The unknown parameters in FA are:



# Parameters to be estimated

The unknown parameters in FA are:

- $\mathbf{W}$ : factor loading matrix



# Parameters to be estimated

The unknown parameters in FA are:

- $\mathbf{W}$ : factor loading matrix
- $\Psi$ : covariance matrix



# Parameters to be estimated

The unknown parameters in FA are:

- $\mathbf{W}$ : factor loading matrix
- $\Psi$ : covariance matrix

These can be estimated via:

- Maximum likelihood estimation (MLE)



# Parameters to be estimated

The unknown parameters in FA are:

- $\mathbf{W}$ : factor loading matrix
- $\Psi$ : covariance matrix

These can be estimated via:

- Maximum likelihood estimation (MLE)
- Expectation-maximization (EM) algorithm



# Parameters to be estimated

The unknown parameters in FA are:

- $\mathbf{W}$ : factor loading matrix
- $\Psi$ : covariance matrix

These can be estimated via:

- Maximum likelihood estimation (MLE)
- Expectation-maximization (EM) algorithm
- Bayesian methods (e.g., variational inference, MCMC)



# Parameters to be estimated

The unknown parameters in FA are:

- $\mathbf{W}$ : factor loading matrix
- $\Psi$ : covariance matrix

These can be estimated via:

- Maximum likelihood estimation (MLE)
- Expectation-maximization (EM) algorithm
- Bayesian methods (e.g., variational inference, MCMC)

Once estimated, the **posterior** of latent embeddings is given by:



# Parameters to be estimated

The unknown parameters in FA are:

- $\mathbf{W}$ : factor loading matrix
- $\Psi$ : covariance matrix

These can be estimated via:

- Maximum likelihood estimation (MLE)
- Expectation-maximization (EM) algorithm
- Bayesian methods (e.g., variational inference, MCMC)

Once estimated, the **posterior** of latent embeddings is given by:

$$p(\mathbf{z}|\mathbf{x}) = \mathcal{N}(\mathbf{z}|\mathbf{W}^\top \mathbf{C}^{-1}(\mathbf{x} - \boldsymbol{\mu}), \mathbf{I} - \mathbf{W}^\top \mathbf{C}^{-1} \mathbf{W}) \quad (11)$$



# Parameters to be estimated

The unknown parameters in FA are:

- $\mathbf{W}$ : factor loading matrix
- $\Psi$ : covariance matrix

These can be estimated via:

- Maximum likelihood estimation (MLE)
- Expectation-maximization (EM) algorithm
- Bayesian methods (e.g., variational inference, MCMC)

Once estimated, the **posterior** of latent embeddings is given by:

$$p(\mathbf{z}|\mathbf{x}) = \mathcal{N}(\mathbf{z}|\mathbf{W}^\top \mathbf{C}^{-1}(\mathbf{x} - \boldsymbol{\mu}), \mathbf{I} - \mathbf{W}^\top \mathbf{C}^{-1} \mathbf{W}) \quad (11)$$

- Posterior has closed-form solution under Gaussian distribution



# FA model summary



# FA model summary

$$\text{[Prior]} \quad p(\mathbf{z}) = \mathcal{N}(\mathbf{z}|\mathbf{0}, \mathbf{I}) \quad (12)$$



# FA model summary

$$\begin{array}{ll} \text{[Prior]} & p(\mathbf{z}) = \mathcal{N}(\mathbf{z}|\mathbf{0}, \mathbf{I}) \\ \text{[Likelihood]} & p(\mathbf{x}|\mathbf{z}) \end{array} \quad (12)$$



# FA model summary

$$\text{[Prior]} \quad p(\mathbf{z}) = \mathcal{N}(\mathbf{z} | \mathbf{0}, \mathbf{I}) \quad (12)$$

$$\text{[Likelihood]} \quad p(\mathbf{x} | \mathbf{z}) = \mathcal{N}(\mathbf{x} | \mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (13)$$



# FA model summary

$$\text{[Prior]} \quad p(\mathbf{z}) = \mathcal{N}(\mathbf{z} | \mathbf{0}, \mathbf{I}) \quad (12)$$

$$\text{[Likelihood]} \quad p(\mathbf{x} | \mathbf{z}) = \mathcal{N}(\mathbf{x} | \mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (13)$$

$$\text{[Evidence/marginal]} \quad p(\mathbf{x})$$



# FA model summary

$$\text{[Prior]} \quad p(\mathbf{z}) = \mathcal{N}(\mathbf{z} | \mathbf{0}, \mathbf{I}) \quad (12)$$

$$\text{[Likelihood]} \quad p(\mathbf{x} | \mathbf{z}) = \mathcal{N}(\mathbf{x} | \mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (13)$$

$$\text{[Evidence/marginal]} \quad p(\mathbf{x}) = \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}, \mathbf{C}) \quad (14)$$



# FA model summary

$$\text{[Prior]} \quad p(\mathbf{z}) = \mathcal{N}(\mathbf{z} | \mathbf{0}, \mathbf{I}) \quad (12)$$

$$\text{[Likelihood]} \quad p(\mathbf{x} | \mathbf{z}) = \mathcal{N}(\mathbf{x} | \mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (13)$$

$$\text{[Evidence/marginal]} \quad p(\mathbf{x}) = \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}, \mathbf{C}) \quad (14)$$

$$\text{[Posterior]} \quad p(\mathbf{z} | \mathbf{x}) = \mathcal{N}(\mathbf{z} | \mathbf{W}^\top \mathbf{C}^{-1}(\mathbf{x} - \boldsymbol{\mu}), \mathbf{I} - \mathbf{W}^\top \mathbf{C}^{-1} \mathbf{W}) \quad (15)$$



# FA model summary

$$\text{[Prior]} \quad p(\mathbf{z}) = \mathcal{N}(\mathbf{z} | \mathbf{0}, \mathbf{I}) \quad (12)$$

$$\text{[Likelihood]} \quad p(\mathbf{x} | \mathbf{z}) = \mathcal{N}(\mathbf{x} | \mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (13)$$

$$\text{[Evidence/marginal]} \quad p(\mathbf{x}) = \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}, \mathbf{C}) \quad (14)$$

$$\text{[Posterior]} \quad p(\mathbf{z} | \mathbf{x}) = \mathcal{N}(\mathbf{z} | \mathbf{W}^\top \mathbf{C}^{-1}(\mathbf{x} - \boldsymbol{\mu}), \mathbf{I} - \mathbf{W}^\top \mathbf{C}^{-1} \mathbf{W}) \quad (15)$$

- $\mathbf{z}$ : latent vector, length  $L$  (assumed to be zero-mean, unit variance)



# FA model summary

$$\text{[Prior]} \quad p(\mathbf{z}) = \mathcal{N}(\mathbf{z} | \mathbf{0}, \mathbf{I}) \quad (12)$$

$$\text{[Likelihood]} \quad p(\mathbf{x} | \mathbf{z}) = \mathcal{N}(\mathbf{x} | \mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (13)$$

$$\text{[Evidence/marginal]} \quad p(\mathbf{x}) = \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}, \mathbf{C}) \quad (14)$$

$$\text{[Posterior]} \quad p(\mathbf{z} | \mathbf{x}) = \mathcal{N}(\mathbf{z} | \mathbf{W}^\top \mathbf{C}^{-1}(\mathbf{x} - \boldsymbol{\mu}), \mathbf{I} - \mathbf{W}^\top \mathbf{C}^{-1} \mathbf{W}) \quad (15)$$

- $\mathbf{z}$ : latent vector, length  $L$  (assumed to be zero-mean, unit variance)
- $\mathbf{x}$ : observed vector



# FA model summary

$$\text{[Prior]} \quad p(\mathbf{z}) = \mathcal{N}(\mathbf{z}|\mathbf{0}, \mathbf{I}) \quad (12)$$

$$\text{[Likelihood]} \quad p(\mathbf{x}|\mathbf{z}) = \mathcal{N}(\mathbf{x}|\mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (13)$$

$$\text{[Evidence/marginal]} \quad p(\mathbf{x}) = \mathcal{N}(\mathbf{x}|\boldsymbol{\mu}, \mathbf{C}) \quad (14)$$

$$\text{[Posterior]} \quad p(\mathbf{z}|\mathbf{x}) = \mathcal{N}(\mathbf{z}|\mathbf{W}^\top \mathbf{C}^{-1}(\mathbf{x} - \boldsymbol{\mu}), \mathbf{I} - \mathbf{W}^\top \mathbf{C}^{-1} \mathbf{W}) \quad (15)$$

- $\mathbf{z}$ : latent vector, length  $L$  (assumed to be zero-mean, unit variance)
- $\mathbf{x}$ : observed vector
- $\mathbf{W}$ :  $D \times L$  factor loading matrix



# FA model summary

$$\text{[Prior]} \quad p(\mathbf{z}) = \mathcal{N}(\mathbf{z}|\mathbf{0}, \mathbf{I}) \quad (12)$$

$$\text{[Likelihood]} \quad p(\mathbf{x}|\mathbf{z}) = \mathcal{N}(\mathbf{x}|\mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (13)$$

$$\text{[Evidence/marginal]} \quad p(\mathbf{x}) = \mathcal{N}(\mathbf{x}|\boldsymbol{\mu}, \mathbf{C}) \quad (14)$$

$$\text{[Posterior]} \quad p(\mathbf{z}|\mathbf{x}) = \mathcal{N}(\mathbf{z}|\mathbf{W}^\top \mathbf{C}^{-1}(\mathbf{x} - \boldsymbol{\mu}), \mathbf{I} - \mathbf{W}^\top \mathbf{C}^{-1} \mathbf{W}) \quad (15)$$

- $\mathbf{z}$ : latent vector, length  $L$  (assumed to be zero-mean, unit variance)
- $\mathbf{x}$ : observed vector
- $\mathbf{W}$ :  $D \times L$  factor loading matrix
- $\boldsymbol{\Psi}$ :  $D \times D$  diagonal covariance matrix or **matrix of unique variances**



# FA model summary

$$\text{[Prior]} \quad p(\mathbf{z}) = \mathcal{N}(\mathbf{z} | \mathbf{0}, \mathbf{I}) \quad (12)$$

$$\text{[Likelihood]} \quad p(\mathbf{x} | \mathbf{z}) = \mathcal{N}(\mathbf{x} | \mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}) \quad (13)$$

$$\text{[Evidence/marginal]} \quad p(\mathbf{x}) = \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}, \mathbf{C}) \quad (14)$$

$$\text{[Posterior]} \quad p(\mathbf{z} | \mathbf{x}) = \mathcal{N}(\mathbf{z} | \mathbf{W}^\top \mathbf{C}^{-1}(\mathbf{x} - \boldsymbol{\mu}), \mathbf{I} - \mathbf{W}^\top \mathbf{C}^{-1} \mathbf{W}) \quad (15)$$

- $\mathbf{z}$ : latent vector, length  $L$  (assumed to be zero-mean, unit variance)
- $\mathbf{x}$ : observed vector
- $\mathbf{W}$ :  $D \times L$  factor loading matrix
- $\boldsymbol{\Psi}$ :  $D \times D$  diagonal covariance matrix or **matrix of unique variances**
- $\mathbf{C} = \mathbf{W}\mathbf{W}^\top + \boldsymbol{\Psi}$



# Unidentifiability of FA parameters



# Unidentifiability of FA parameters

The parameters  $\mathbf{W}$  and  $\Psi$  are unidentifiable.



# Unidentifiability of FA parameters

The parameters  $\mathbf{W}$  and  $\Psi$  are unidentifiable. This can be addressed via:



# Unidentifiability of FA parameters

The parameters  $\mathbf{W}$  and  $\Psi$  are unidentifiable. This can be addressed via:

- Constraining  $\mathbf{W}$  to have orthonormal columns [PCA]



# Unidentifiability of FA parameters

The parameters  $\mathbf{W}$  and  $\Psi$  are unidentifiable. This can be addressed via:

- Constraining  $\mathbf{W}$  to have orthonormal columns [PCA]
- Constraining  $\mathbf{W}$  to be lower triangular



# Unidentifiability of FA parameters

The parameters  $\mathbf{W}$  and  $\Psi$  are unidentifiable. This can be addressed via:

- Constraining  $\mathbf{W}$  to have orthonormal columns [PCA]
- Constraining  $\mathbf{W}$  to be lower triangular
- Informative rotation:  $\tilde{\mathbf{W}} = \mathbf{W}\mathbf{R}$ , where  $\mathbf{R}$  is the rotation matrix



# Unidentifiability of FA parameters

The parameters  $\mathbf{W}$  and  $\Psi$  are unidentifiable. This can be addressed via:

- Constraining  $\mathbf{W}$  to have orthonormal columns [PCA]
- Constraining  $\mathbf{W}$  to be lower triangular
- Informative rotation:  $\tilde{\mathbf{W}} = \mathbf{W}\mathbf{R}$ , where  $\mathbf{R}$  is the rotation matrix
  - Commonly used rotations: Varimax, Promax, Oblimin, Geomin, Thurstone, Equamax



# Unidentifiability of FA parameters

The parameters  $\mathbf{W}$  and  $\Psi$  are unidentifiable. This can be addressed via:

- Constraining  $\mathbf{W}$  to have orthonormal columns [PCA]
- Constraining  $\mathbf{W}$  to be lower triangular
- Informative rotation:  $\tilde{\mathbf{W}} = \mathbf{W}\mathbf{R}$ , where  $\mathbf{R}$  is the rotation matrix
  - Commonly used rotations: Varimax, Promax, Oblimin, Geomin, Thurstone, Equamax
- Sparsity-promoting priors on  $\mathbf{W}$



# Unidentifiability of FA parameters

The parameters  $\mathbf{W}$  and  $\Psi$  are unidentifiable. This can be addressed via:

- Constraining  $\mathbf{W}$  to have orthonormal columns [PCA]
- Constraining  $\mathbf{W}$  to be lower triangular
- Informative rotation:  $\tilde{\mathbf{W}} = \mathbf{W}\mathbf{R}$ , where  $\mathbf{R}$  is the rotation matrix
  - Commonly used rotations: Varimax, Promax, Oblimin, Geomin, Thurstone, Equamax
- Sparsity-promoting priors on  $\mathbf{W}$
- Non-Gaussian priors for latent factors



# PCA as a special case of FA



# PCA as a special case of FA

Principal components analysis (PCA) is a special case of FA with:



# PCA as a special case of FA

Principal components analysis (PCA) is a special case of FA with:

$$\Psi = \sigma^2 I \quad (16)$$



# PCA as a special case of FA

Principal components analysis (PCA) is a special case of FA with:

$$\Psi = \sigma^2 I \quad (16)$$

where  $\sigma^2$  is the isotropic noise variance.



# PCA as a special case of FA

Principal components analysis (PCA) is a special case of FA with:

$$\Psi = \sigma^2 I \quad (16)$$

where  $\sigma^2$  is the isotropic noise variance. In PCA, the covariance of the observed vector is given by:



# PCA as a special case of FA

Principal components analysis (PCA) is a special case of FA with:

$$\Psi = \sigma^2 I \quad (16)$$

where  $\sigma^2$  is the isotropic noise variance. In PCA, the covariance of the observed vector is given by:

$$\mathbf{C} = \mathbf{W}\mathbf{W}^\top + \sigma^2 I \quad (17)$$



# Autoencoders as nonlinear PCA/FA



# Autoencoders as nonlinear PCA/FA

In PCA/FA, we learn a **linear mapping** from a high-dimensional observed space  $\mathbf{x} \in \mathbb{R}^D$  to a low-dimensional latent space  $\mathbf{z} \in \mathbb{R}^L$  and vice-versa.



# Autoencoders as nonlinear PCA/FA

In PCA/FA, we learn a **linear mapping** from a high-dimensional observed space  $\mathbf{x} \in \mathbb{R}^D$  to a low-dimensional latent space  $\mathbf{z} \in \mathbb{R}^L$  and vice-versa.

- **Encoder**  $f_e$ : mapping from  $\mathbf{x} \rightarrow \mathbf{z}$



# Autoencoders as nonlinear PCA/FA

In PCA/FA, we learn a **linear mapping** from a high-dimensional observed space  $\mathbf{x} \in \mathbb{R}^D$  to a low-dimensional latent space  $\mathbf{z} \in \mathbb{R}^L$  and vice-versa.

- **Encoder**  $f_e$ : mapping from  $\mathbf{x} \rightarrow \mathbf{z}$
- **Decoder**  $f_d$ : mapping from  $\mathbf{z} \rightarrow \mathbf{x}$



# Autoencoders as nonlinear PCA/FA

In PCA/FA, we learn a **linear mapping** from a high-dimensional observed space  $\mathbf{x} \in \mathbb{R}^D$  to a low-dimensional latent space  $\mathbf{z} \in \mathbb{R}^L$  and vice-versa.

- **Encoder**  $f_e$ : mapping from  $\mathbf{x} \rightarrow \mathbf{z}$
- **Decoder**  $f_d$ : mapping from  $\mathbf{z} \rightarrow \mathbf{x}$

In PCA, for example,  $f_e$  is given by:



# Autoencoders as nonlinear PCA/FA

In PCA/FA, we learn a **linear mapping** from a high-dimensional observed space  $\mathbf{x} \in \mathbb{R}^D$  to a low-dimensional latent space  $\mathbf{z} \in \mathbb{R}^L$  and vice-versa.

- **Encoder**  $f_e$ : mapping from  $\mathbf{x} \rightarrow \mathbf{z}$
- **Decoder**  $f_d$ : mapping from  $\mathbf{z} \rightarrow \mathbf{x}$

In PCA, for example,  $f_e$  is given by:

$$\mathbf{z} = \mathbf{W}^\top \mathbf{x} \equiv f_e(\mathbf{x}) \quad (18)$$



# Autoencoders as nonlinear PCA/FA

In PCA/FA, we learn a **linear mapping** from a high-dimensional observed space  $\mathbf{x} \in \mathbb{R}^D$  to a low-dimensional latent space  $\mathbf{z} \in \mathbb{R}^L$  and vice-versa.

- **Encoder**  $f_e$ : mapping from  $\mathbf{x} \rightarrow \mathbf{z}$
- **Decoder**  $f_d$ : mapping from  $\mathbf{z} \rightarrow \mathbf{x}$

In PCA, for example,  $f_e$  is given by:

$$\mathbf{z} = \mathbf{W}^\top \mathbf{x} \equiv f_e(\mathbf{x}) \quad (18)$$

And  $f_d$  is given by:



# Autoencoders as nonlinear PCA/FA

In PCA/FA, we learn a **linear mapping** from a high-dimensional observed space  $\mathbf{x} \in \mathbb{R}^D$  to a low-dimensional latent space  $\mathbf{z} \in \mathbb{R}^L$  and vice-versa.

- **Encoder**  $f_e$ : mapping from  $\mathbf{x} \rightarrow \mathbf{z}$
- **Decoder**  $f_d$ : mapping from  $\mathbf{z} \rightarrow \mathbf{x}$

In PCA, for example,  $f_e$  is given by:

$$\mathbf{z} = \mathbf{W}^\top \mathbf{x} \equiv f_e(\mathbf{x}) \quad (18)$$

And  $f_d$  is given by:

$$\hat{\mathbf{x}} = \mathbf{W}\mathbf{z} \equiv f_d(\mathbf{z}) \quad (19)$$

To introduce flexibility, we can specify  $f_e$  and  $f_d$  are nonlinear/more complex functions. This is best accomplished via neural network, resulting in an **autoencoder** (AE).



# Reconstruction loss



# Reconstruction loss

The reconstruction function is the approximation of the observation from the decoder:



# Reconstruction loss

The reconstruction function is the approximation of the observation from the decoder:

$$\hat{\mathbf{x}} \equiv r(\mathbf{x}) = f_d(f_e(\mathbf{x})) \quad (20)$$



# Reconstruction loss

The reconstruction function is the approximation of the observation from the decoder:

$$\hat{\mathbf{x}} \equiv r(\mathbf{x}) = f_d(f_e(\mathbf{x})) \quad (20)$$

An autoencoder is thus trained to minimize the reconstruction loss



# Reconstruction loss

The reconstruction function is the approximation of the observation from the decoder:

$$\hat{\mathbf{x}} \equiv r(\mathbf{x}) = f_d(f_e(\mathbf{x})) \quad (20)$$

An autoencoder is thus trained to minimize the reconstruction loss

$$\mathcal{L}(\boldsymbol{\theta}) = ||r(\mathbf{x}) - \mathbf{x}||_2^2 \quad (21)$$

or equivalently, the negative log-likelihood:



# Reconstruction loss

The reconstruction function is the approximation of the observation from the decoder:

$$\hat{\mathbf{x}} \equiv r(\mathbf{x}) = f_d(f_e(\mathbf{x})) \quad (20)$$

An autoencoder is thus trained to minimize the reconstruction loss

$$\mathcal{L}(\boldsymbol{\theta}) = ||r(\mathbf{x}) - \mathbf{x}||_2^2 \quad (21)$$

or equivalently, the negative log-likelihood:

$$\mathcal{L}(\boldsymbol{\theta}) = -\log p(\mathbf{x}|r(\mathbf{x})) \quad (22)$$




# Basic autoencoder (AE) architecture



# Basic autoencoder (AE) architecture


Autoencoder with 2 single-layer MLPS: input layer, hidden layer (latent representation) and output layer (reconstruction)





# Basic autoencoder (AE) architecture

Autoencoder with 2 single-layer MLPS: input layer, hidden layer (latent representation) and output layer (reconstruction)




- Hidden layer (size  $L$ ) is a low-dimensional **bottleneck** between input and reconstruction



# Basic autoencoder (AE) architecture

Autoencoder with 2 single-layer MLPS: input layer, hidden layer (latent representation) and output layer (reconstruction)




- Hidden layer (size  $L$ ) is a low-dimensional **bottleneck** between input and reconstruction
- $L \ll D$ : undercomplete representation



# Basic autoencoder (AE) architecture

Autoencoder with 2 single-layer MLPS: input layer, hidden layer (latent representation) and output layer (reconstruction)



- Hidden layer (size  $L$ ) is a low-dimensional **bottleneck** between input and reconstruction
- $L \ll D$ : undercomplete representation
- $L \gg D$ : overcomplete representation (regularize to prevent identity learning)



# Denoising autoencoders



# Denoising autoencoders

In denoising autoencoders (DAEs), the input is corrupted ( $\tilde{\mathbf{x}}$ ) by:


- Gaussian noise:  $p_c(\tilde{\mathbf{x}}|\mathbf{x}) = \mathcal{N}(\tilde{\mathbf{x}}|\mathbf{x}, \sigma^2 \mathbf{I})$



# Denoising autoencoders

In denoising autoencoders (DAEs), the input is corrupted ( $\tilde{\mathbf{x}}$ ) by:

- Gaussian noise:  $p_c(\tilde{\mathbf{x}}|\mathbf{x}) = \mathcal{N}(\tilde{\mathbf{x}}|\mathbf{x}, \sigma^2 \mathbf{I})$
- Bernoulli dropout: randomly setting a proportion of input nodes to zero



Schematic of a DAE.

Source: <https://lilianweng.github.io/posts/2018-08-12-vae/>

The model is then trained to minimize the loss between the reconstructed input  $r(\tilde{\mathbf{x}})$  and its uncorrupted version  $\mathbf{x}$



# Uses of DAE




# Uses of DAE

- DAEs are used for denoising images



# Uses of DAE

- DAEs are used for denoising images



Original, corrupted and reconstructed images from MNIST dataset.


Source: <http://www.opendeep.org/v0.0.5/docs/tutorial-your-first-model>

- They can also learn vector fields of input data



# Uses of DAE

- DAEs are used for denoising images



Original, corrupted and reconstructed images from MNIST dataset.

Source: <http://www.opendeep.org/v0.0.5/docs/tutorial-your-first-model>

- They can also learn vector fields of input data
- Popular for their simplicity



# Sparse autoencoder (SAE)



# Sparse autoencoder (SAE)

**Sparse autoencoder** (SAE): sparsity penalty on latent activations




# Sparse autoencoder (SAE)


**Sparse autoencoder (SAE):** sparsity penalty on latent activations

$$\Omega(\mathbf{z}) = \lambda \|\mathbf{z}\|_1 \quad (23)$$

- k*-Sparse autoencoder:** use only *k* largest activations in training



(a)  $k = 70$



(b)  $k = 40$



(c)  $k = 25$



(d)  $k = 10$

Filters of the *k*-sparse autoencoder for different sparsity levels *k*, learnt from MNIST with 1000 hidden units.

Source: <https://arxiv.org/pdf/1312.5663.pdf>

Useful for interpretability



# Other AEs



# Other AEs

- **Contractive autoencoder** (CAE): regularizes via penalty on reconstruction loss



# Other AEs

- **Contractive autoencoder** (CAE): regularizes via penalty on reconstruction loss

$$\Omega(\mathbf{z}, \mathbf{x}) = \lambda \left\| \left\| \frac{\partial f_e(\mathbf{x})}{\partial \mathbf{x}} \right\|_F \right\|^2 \quad (24)$$



# Other AEs

- **Contractive autoencoder** (CAE): regularizes via penalty on reconstruction loss

$$\Omega(\mathbf{z}, \mathbf{x}) = \lambda \left\| \left\| \frac{\partial f_e(\mathbf{x})}{\partial \mathbf{x}} \right\|_F \right\|^2 \quad (24)$$

- Variational autoencoder (VAE): probabilistic version of AE/generative model



# Reading

- **PMLI 20.3**
- **DL 20**