

DORA-002

Cassini Radar Instrument Team

Volume Software Interface Specification (SIS) for Cassini Radar Instrument Team Data Products

Version 1.0

Bryan Stiles

February 2004

**Jet Propulsion Laboratory
California Institute of Technology
NASA**

D-27890

Prepared By:

Bryan Stiles
Cassini Radar Ground Processor Engineer

Date: _____

Approved By:

Randolph Kirk
USGS Astrogeology Team

Date: _____

Phil Callahan
Cassini Radar Instrument Team Project Element Manager

Date: _____

Concurred By:

Charles Elachi
Cassini RADAR Principal Investigator

Date: _____

Diane Conner
Cassini Archive Data Engineer

Date: _____

Lisa Gaddis
USGS Imaging Node

Date: _____

Steve Adams
PDS Central Node Manager

Date: _____

Document Log

[illegible]

1	INTRODUCTION	8
1.1	Purpose and Scope	8
1.2	Applicable Documents	8
2	ARCHIVE VOLUME GENERATION	9
2.1	Data Transfer and Validation Method	9
2.2	Data Volume Estimates	9
2.3	Interface Media Characteristics	10
2.4	Backup and Duplicates	10
3	ARCHIVE VOLUME CONTENTS	11
3.1	Root Directory Contents	11
3.2	INDEX Directory Contents	11
3.2.1	Fields in the Index Table File	12
3.3	DOCUMENTS Directory Contents	13
3.4	CATALOG Directory Contents	14
3.5	DATA Directory Contents	15
3.5.1	Data File Naming Conventions	15
3.6	CALIB Directory Contents	17
4	ARCHIVE VOLUME FORMAT	18
4.1	Document File Format	18
4.2	Tabular File Format	18
4.3	PDS Label Format	18
4.4	Catalog File Format	19
4.5	Science Data File Format	19

1 INTRODUCTION

1.1 Purpose and Scope

This Software Interface Specification (SIS) describes the formats, contents, and generation of the media volumes for data produced by the Cassini Radar Instrument Team including the Burst Ordered Data Products (BODP) and the Basic Image Data Records (BIDR). Observations in the Saturn system will target Titan, Saturn, the Saturnian ring systems, and various icy satellites.

Observations of targets outside the Saturn system will also be included in the data volume. For example, radiometer observations of Jupiter, the sun, and various microwave sources will be included as well as radiometer and scatterometer observations of the Earth.

The specifications in this document apply to all data products produced by the Cassini Radar Instrument Team at the Jet Propulsion Laboratory.

This SIS is intended to provide enough information to enable users to understand the way in which the data products are organized within the volume data set. It is intended to be used in conjunction with the Cassini Radar Burst Ordered Data Products SIS D-27891 which describes the internal format of the BODP data files and the Cassini Basic Image Data Record SIS D-27889 which similarly documents the BIDR files. The users for whom this SIS is intended are software developers, engineers, and scientists interested in accessing and using either of the two data product types.

1.2 Applicable Documents

This SIS is responsive to the following Cassini Mission Documents:

1 Project Data Management Plan, JPL PD 699-061

2 Cassini/Huygens Program Archive Plan for Science Data, JPL PD 699-068

This SIS is also consistent with the following Planetary Data System documents:

3. Planetary Data System Data Preparation Workbook, February 1, 1995, Version 3.1, JPL D-7669, Part 1

4. Planetary Data System Data Standards Reference, June 15, 2001, Version 3.4, JPL D-7669, Part 2

Finally this SIS is consistent with the contract negotiated between the Cassini Project and the Cassini Radar Experiment Principal Investigator (PI) in which data products and documentation are explicitly defined as deliverable products.

2 ARCHIVE VOLUME GENERATION

2.1 Data Transfer and Validation Method

The Cassini Radar Team will produce the BODP and BIDR Data Archive Collection. During active mission operations intermediate science data products are made available to Cassini Radar Team members for their analysis and evaluation. The data sets will be continually updated during the mission as new observations are acquired. At the end of the data preparation phase, the copies of the data product archive will be distributed to the peer review panel for their evaluation. The peer panel, with representation from the Cassini Radar Team, PDS, Cassini Science Archive Working Group (SAWG) and the general science community will review and validate the products and volume for scientific integrity and compliance with PDS standards. The data products will be evaluated against the design as defined in the product and volume SIS's. These SIS's are peer reviewed prior to Saturn system data acquisition.

2.2 Data Volume Estimates

The following table summarizes product sizes for the Cassini Radar Instrument Team Data Products. These include the BIDR files and the three different formats of BODP files. The various types are described in detail in section 3.5 and in the BODP Data SIS. BIDR files and BODP files of the same format have the same constant fixed record length which can be read from the PDS label attached at the beginning of the file or the index table file. The approximate record sizes for each file type are also listed in table 1 along with the nominal data volume per pass (for 10 hour Titan passes) and some notes briefly describing each product type. For the exact record sizes see the BODP or BIDR data SIS. The total data volume for the mission is estimated to be 80 GBytes for 20 sequences. This estimate is probably high because the radar will not be obtaining measurements for the full ten hours for every Titan pass. On the other hand, in the event of an extended mission we may acquire more passes.

Table 1: Data Volume Estimates

Product Type	Data Set ID	Record Size (KBytes)	Data Volume per pass (MBytes)	Name: Description
SBDR	CO-V/E/J/S-RADAR-3-SBDR-V1.0	1.2	54	Short Burst Data Record: Time ordered engineering, S/C geometry, and science data
LBDR	CO-V/E/J/S-RADAR-3-LBDR-V1.0	133	2200	Long Burst Data Record: SBDR + active mode sampled echo data

Table 1: Data Volume Estimates

Product Type	Data Set ID	Record Size (KBytes)	Data Volume per pass (MBytes)	Name: Description
ABDR	CO-SSA-RADAR-3-ABDR-V1.0	133	240	Altimeter Burst Data Record: SBDR + range compressed altimeter echo data
BIDR	CO-SSA-RADAR-5-BIDR-V1.0	varies for different image resolutions	1400	Basic Image Data Record: SAR image from a single Titan pass

A single copy of the data product volumes will be delivered to the PDS Imaging Node. The Imaging Node will be responsible for developing the methods for distributing the data products to the user community. Copies of the preliminary DVD-R volumes will be provided to the peer review panel for their evaluation.

2.3 Interface Media Characteristics

Data products will be delivered to the PDS electronically. Deliveries will be tracked using the Cassini Archive Tracking System (CATS).

2.4 Backup and Duplicates

The Cassini Radar Instrument Team will keep backup copies of the data throughout the duration of the Cassini Mission.

3 ARCHIVE VOLUME CONTENTS

This section describes the directories and contents of the Cassini Radar Instrument Team Data Product volumes, including the file names, file contents, and file types. The ancillary files described herein appear on each volume in the Cassini Radar Instrument Team Data Product volume series.

3.1 Root Directory Contents

The following table lists files located in the root directory.

Table 2: Contents of Root Directory

File Name	File Contents
AAREADME.TXT	File providing introductory information about the contents and format of the volumes.
VOLDESC.CAT	A description of the contents of this volume in a PDS labeled format.
ERRATA.TXT	A cumulative listing of comments and special considerations.
INDEX	Directory containing index table.
DOCUMENTS	Documentation Directory
CATALOG	Directory containing catalog files.
DATA	Directory containing data products.
CALIB	Directory containing files used to calibrate data.
EXTRAS	Directory containing files which do not fit anywhere else.

3.2 INDEX Directory Contents

The following table summarizes files located in the index directory. A single index table is provided for all Cassini Radar Instrument Team Products. Data set ID is one of the fields in the index file.

Table 3: Contents of INDEX Directory

File Name	File Contents
INDEXINFO.TXT	A description of the contents of this directory.
INDEX.TAB	Index table file for Cassini Radar Instrument Team Data Products.
INDEX.LBL	Detached label file describing contents of index.tab.

3.2.1 Fields in the Index Table File

This section describes the fields in the index.tab file. This file is included to provide the user with a way of quickly producing a list of data files from desired ranges of search criteria such as time, target, latitude, or longitude. See below for descriptions of each column in the index file.

3.2.1.1 file_name

The name of each BODP or BIDR data file in the data volume.

3.2.1.2 dir

The directory in which the file can be found. This entry should always be 'data/XXXX' where XXXX is the four letter acronym for the data set (SBDR, LBDR, ABDR or BIDR).

3.2.1.3 data_set_id

A text string which identifies the type of data in the file. The valid strings are listed in Table 1.

3.2.1.4 start_time

UTC (YYYY-DOYTHH:MM:SS.sss) formatted time at start of data acquisition for data in the file.

3.2.1.5 end_time

UTC formatted time at end of data acquisition for data in the file.

3.2.1.6 target

Identifier for target of observation. (TITAN, SATURN, etc.)

3.2.1.7 latitude_min

Minimum latitude in target body frame for data in file. For target for which this is not applicable the default value of -1000 is used.

3.2.1.8 latitude_max

Maximum latitude in target body frame for data in file. For target for which this is not applicable the default value of -1000 is used.

3.2.1.9 longitude_westernmost

Westernmost longitude in target body frame for data in file. For target for which this is not applicable the default value of -1000 is used. Valid values are between 0 and 360.

3.2.1.10 longitude_easternmost

Easternmost longitude in target body frame for data in file. For target for which this is not applicable the default value of -1000 is used. Valid values are between 0 and 360.

3.2.1.11 look_direction

5 letter ASCII string ("RIGHT", "LEFT", or "BOTH") indicating the side of the space-

craft groundtrack to which the antenna is pointed for data acquired within each data product (file). The "BOTH " option will only be used for BODP files. The SAR images stored in the BIDR files are always acquired on only one side of the ground track for each Titan pass. This value also indicates from which side the SAR image is illuminated. If the spacecraft images to the left of its ground track, the image will be illuminated from the (viewer's) left side, and, conversely, if the spacecraft looks to the right, the illumination will come from the right in the image file. The direction of illumination is critical to interpretation of features in the image.

3.3 DOCUMENTS Directory Contents

The following table lists files located in the Document Directory.

Table 4: Contents of DOCUMENTS Directory

File Name	File Contents
DOCINFO.TXT	A description of the contents of this directory.
BODPSIS.PDF BODPSIS.LBL BODPSIS.HTML	PDF and HTML versions of Burst Ordered Data Products SIS and detached label file documenting them.
BIDRSIS.PDF BIDRSIS.LBL BIDRSIS.HTML	PDF and HTML versions of Basic Image Data Record SIS and detached label file documenting them.
VOLSIS.PDF VOLSIS.LBL VOLSIS.HTML	PDF and HTML versions of Volume SIS (this file) and detached label file documenting them.
SBDR.FMT LBDR.FMT ABDR.FMT	Format files for BODP table objects which are referenced in the attached PDS labels.
CRT	Directory containing Cassini Radar Transition files for each observation.

The CRT directory contains a Cassini Radar Transition file for each observation. These files document the times of radar mode transitions and the beginning and end of radar or radiometer scans. File names are of the form CRT_yyy_Vnn.TAB where yyy is the three digit radar observation counter, and nn is a two digit version number.

The Cassini Radar Transition files in the CRT directory consist of four tab delimited columns of ASCII text. The first column is a UTC time tag in yyyy-doyThh:mm:ss.sss format. The second column is a two digit decimal integer denoting the type of transition. The third column is a 15 character (spaces are padded at the end) ASCII transition type tag. The fourth column is a unique record identification number. Rows are in temporal order. The following table maps transition type integers to tags. The tags denote the ending and beginning times of individual raster scans as well as the

ending and beginning times for each radar mode. For completeness, the end time of

Table 5: Transition Number Map for CRT Files

Transition Tag	Transition Number
ScanStart	00
ScanEnd	01
RadOnlyStart	02
RadOnlyEnd	03
ScatStart	04
ScatEnd	05
AltStart	06
AltEnd	07
LoResSARStart	09
LoResSAREnd	10
HiResSARStart	11
HiResSAREnd	12

one mode and the beginning time of the next mode are both listed. Unless there is a gap between the two modes both times will be identical and will correspond to the starting time of the first burst in the second mode. Record identification number on the other hand will be different for the two rows. The mode ending row will have the last record identification number for the old mode. The mode starting row will contain the first record identification number for the new mode. It is important to note that scatterometer data will be available during altimetry and SAR modes and that radiometer data will be available during all modes.

3.4 CATALOG Directory Contents

The files in the Catalog directory provide a top-level understanding of the Cassini Mission, spacecraft, instruments, and data sets in the form of completed PDS templates. The files are produced or collected by the Cassini Radar Team. The files in this directory are coordinated with the PDS engineer. The following table lists files in the Catalog Directory.

Table 6: Contents of CATALOG Directory

File Name	File Contents
CATINFO.TXT	A description of the contents of this directory.
MISSION.CAT	PDS mission catalog information about the Cassini Mission.
PERSON.CAT	PDS personnel catalog information about Cassini Team members responsible for generating the data products
INST.CAT	PDS instrument catalog information about the Cassini Radar instrument.
INSTHOST.CAT	PDS instrument catalog information about the Cassini spacecraft.
DSMAP.CAT	PDS mission catalog information about map projection definition. It includes the definition of oblique cylindrical.
REF.CAT	PDS references mentioned in other *.CAT files
BODP.CAT	PDS data set catalog information about the Burst Ordered Data Product data sets.
BIDR.CAT	PDS data set catalog information about the Basic Image Data Record data set.

3.5 DATA Directory Contents

The DATA directory has four sub-directories SBDR, LBDR, ABDR, and BIDR which each contain all the data files for the corresponding data set.

3.5.1 Data File Naming Conventions

Files are named using the product ID and an extension specifying the PDS file type. The product ID is the string following the PRODUCT_ID keyword in the attached PDS label. BIDR files are of the format aabcddefff_gg_Vnn.IMG where "aabcddefff_gg_Vnn" is the product ID and ".IMG" is the extension for PDS image files. Similarly the BODP files are named xxxx_yy_zzz_Vnn.TAB, where "xxxx_yy_zzz_Vnn" is the product ID and ".TAB" is the extension for a PDS Table file.

The BIDR product ID aabcddefff_gg_Vnn is defined as follows:

aa = Dataset

BI = BIDR

b = Kind and bit-type of data

F = Primary dataset (e.g., incidence angle corrected sigma0) in 32-bit floating-point format (Linear scale values, not in dB.)

B = Primary dataset in unsigned byte format. (Values converted to dB then normalized to fit in [0,255] range.)

U = Sigma0 without incidence angle correction in 32-bit floating point format. (Linear scale values, not in dB.)

E = Incidence angle map, floating point values in degrees.

T = Latitude map, floating point values in degrees.

N = Longitude map, floating point values in degrees.

M = Beam mask map, 8 bit values.

c = Map resolution

B = 2 pixels/degree

D = 8 pixels/degree

F = 32 pixels/degree

H = 128 pixels/degree

I = 256 pixels/degree

dd = Absolute value of latitude at center of file, rounded to nearest degree

e = Hemisphere of center of file

N = North

S = South

fff = West longitude at center of file, rounded to nearest degree

gg = Two-digit index of Titan flyby from which data are included

nn = Two-digit version number

The BODP product ID xxxx_yy_zzzz_Vnn is defined as follows:

xxxx = The acronym for the data set LBDR, SBDR, or ABDR

yy = The radar mode of the data in the file represented as a two digit decimal integer between 00 and 15. This value represents a 4-bit binary flagging scheme

Bit 0 (LSB) = 1 means radiometer only mode data is present in the file.

Bit 1 = 1 means scatterometer mode data is present in the file

Bit 2 = 1 means altimeter mode data is present in the file.

Bit 3 = 1 means SAR mode data is present in the file.

The only yy values expected to occur are 01=radiometer mode only, 02=scatterometer mode only, 07= all but SAR modes, 08= SAR mode only, and 15=all four modes, but all possibilities are covered. It is important to note that scatterometer measurements are obtained in all modes except radiometer only not just in scatterometer mode. Similarly, radiometer measurements are obtained in all modes without exception.

zzz = 3 digit radar observation counter. One observation corresponds to a single up-linked radar command sequence. For example, a Titan fly-by is one observation.
nn = 2 digit version number

3.6 CALIB Directory Contents

The following table lists files located in the CALIB Directory.

Table 7: Contents of CALIB Directory

File Name	File Contents
BEAMPAT	Directory containing antenna gain pattern files for each beam and documentation for those files.
CONFIG	Directory containing processor configuration files and documentation for those files.

The CALIB directory contains two subdirectories BEAMPAT and CONFIG. These directories contain ancillary information which specifies how the Cassini Radar data was calibrated and processed.

The BEAMPAT directory contains estimates of the antenna gain pattern for each of the five Cassini Radar beams. The beam pattern file name convention is:

BEAMX_VNN.PAT where X is a beam number between 1 and 5 and NN is a two digit version number.

The CONFIG directory contains a processor configuration file for each Cassini Radar observation. This file contains keyword and value pairs (Processor keywords are not PDS keywords.) which were used in running the ground processing software used to generate the BODP and BIDR files for that observation. Each processor configuration file is named "PCF_yyyy_Vnn.CFG" where yyyy is the four digit radar observation counter and nn is a two digit version number.

Files in the BEAMPAT and CONFIG directories will be not be needed by most users of Cassini Radar Instrument Team data. For those who desire to use them, documentation files BEAMPAT.DOC and CONFIG.DOC are available in the appropriate directories.

4 ARCHIVE VOLUME FORMAT

This section describes the format of files contained in the Cassini Radar Instrument Team Archive Volumes. Data that comprise the Archive will be formatted in accordance with the Planetary Data System specifications [Planetary Science Data Dictionary, 1996; PDS Data Preparation Workbook, 1995; PDS Standards Reference 1995].

4.1 Document File Format

Document files with the.TXT suffix exist in the Root, Index, Catalog, Document, and Extras directories. They are ASCII files with embedded PDS labels with line lengths that do not exceed 80 characters. Document files have variable length lines with an end-of-line designator consisting of a carriage-return character followed by a line-feed character. This allows the files to be read by the MacOS, Microsoft Windows, and Unix operating Systems.

4.2 Tabular File Format

A Tabular file (INDEX.TAB) exists in the Index directory. This file is an ASCII file formatted for direct reading into many database management systems on various computers. Commas separate all fields, and character fields are enclosed in double quotation marks ("). Character fields are left justified and padded on the right with spaces to keep quotation marks in the same columns of successive records. Number fields are right justified and padded with spaces on the left to keep fixed-width fields. The records are of fixed length, and the last two bytes of each record contain the ASCII carriage-return and line-feed character. This allows a table to be treated as a fixed length record file on computers that support this file type and as a text file with embedded line delimiters on those that don't.

A detached PDS label describes INDEX.TAB. The PDS label file name is the same as the tabular file but with the extension ".LBL".

4.3 PDS Label Format

All data files in the Cassini Radar Instrument Team Archive Collection have PDS labels [Planetary Science Data Dictionary, 1996; PDS Standards Reference, 1995]. A PDS label, whether embedded or detached from its associated file, provides descriptive information about the associated file. The PDS label is an object-oriented structure consisting of sets of "keyword = value" declarations. The object to which the label refers (e.g. IMAGE, TABLE, etc.) denotes the form:

^object = location

in which the caret character (^, also called a pointer in this context) indicates where to find the object. In an embedded label, the location is an integer representing the starting record number of the object (the first record in the file is record 1). In a detached label, the location denotes the name of the file containing the object, along with the starting record or byte number, if there is more than one object in the file.

For example:

```
^HEADER = ("F01.IMG",1)
^IMAGE = ("F01.IMG",1025 <BYTES>)
```

indicates that the IMAGE object begins at byte 1025 of the file F01.IMG, in the same directory as the detached label file. Below is a list of the possible formats for the ^object definition.

```
^object = n
^object = n<BYTES>
^object = "filename.ext"
^object = ("filename.ext",n)
^object = ("[dirlist]filename.ext",n)
^object = ("filename.ext",n<BYTES>)
^object = ("[dirlist]filename.ext",n<BYTES>)
```

where:

n is the starting record or byte number of the object, counting from the beginning of the file (record 1, byte 1),

<BYTES> indicates that the number given is in units of bytes,

filename is the up to 24 character, alphanumeric upper-case file name, ext is the 3 character upper-case file extension,

dirlist is a period-delimited path-list of parent directories, in upper case, that specifies the object file directory (used only when the object is not in the same directory as the label file). The list begins at the directory level below the root directory of the CD-ROM. '[dirlist]' may be omitted when the object being described is located in the same directory as the detached label.

Detached label files have variable length lines with an end-of-line designator consisting of a carriage-return character followed by a line-feed character. This allows the files to be read by the MacOS, Microsoft Windows, and Unix operating Systems.

4.4 Catalog File Format

Catalog files (suffix.CAT) exist in the Root and Catalog directories. They are formatted in an object-oriented structure consisting of sets of "keyword = value" declarations.

4.5 Science Data File Format

The Cassini BODP science data files are formatted using the "table object" structure

of the PDS standards. Each row of the table consists of a data record comprising radar and ancillary data for a single burst. Rows occur in time order. A column represents a particular data field with a specific meaning and data type (i.e. integer, real, etc.) Real values are either 32-bit or 64-bit IEEE floating-point values with little endian byte order (PC REAL). For more information about the format and content of the BODP files, see the Cassini Radar Burst Ordered Data Product SIS, JPL D-27891.

The Cassini BIDR science data files are formatted using the "image object" structure of the PDS standards. The size and coordinate system of the image is defined in the attached PDS label. Images pixels may have several different meanings and data types. For more information about the format and content of the BIDR files, see the Cassini Radar Basic Image Data Record SIS, JPL D-27889.