# dcapp Installation and User Guide

version 1.0

NASA Johnson Space Center



# **Table of Contents**

1.0 Introduction	1
2.0 Installation	1
2.1 Mandatory Prerequisites	
2.2 Optional Prerequisites	
2.3 dcapp	
3.0 Activation	2
4.0 Specfile	3
4.1 Root Element	3
4.2 Universal Elements	4
4.3 Initialization Elements	5
4.3.1 Settings Elements	5
4.3.2 Input/Output Elements	
4.3.3 Logic Element	9
4.4 Display Setup	9
4.5 Display Primitives	9
4.5.1 Visual Primitives	10
4.5.2 Event Primitives	13
5.0 Technical Details	15
5.1 Color Format Specification	
5.2 Alignment Specification	
5.3 Graphic File Formats	
5.4 Display Logic File	16
5.5 Element Values	
5.5.1 Constants	17
5.5.2 Variables	
5.5.3 Environment Variables	17

### 1.0 Introduction

"dcapp" (pronounced "dee see app") is a displays and controls software package designed for UNIX platforms, specifically MacOS and Linux. It is built upon standard UNIX technologies like OpenGL for graphics, libxml2 for input file parsing, and FreeType2 for font handling. For window management and event handling, it uses Cocoa on MacOS machines and X11 for Linux-based machines. It has built-in communication libraries to communicate with external Trick-based simulations (via trick\_comm) and EDGE graphics (via EDGE's remote commanding server (RCS)).

For more information, please contact:

Michael McFarlane michael.r.mcfarlane@nasa.gov **ER7/Simulation and Graphics Branch NASA Johnson Space Center** 

### 2.0 Installation

### 2.1 Mandatory Prerequisites

dcapp is designed to run on MacOS and Linux-based machines. Building dcapp requires a compiler that can accommodate the C++11 programming language. For all of the packages described hereafter, be sure to get "development" versions that include header files. These packages must be installed before building or running dcapp:

- OpenGL
- libxml2
- FreeType2

OpenGL is a standard environment for developing portable, interactive 2D and 3D graphics applications. It is a standard package on most MacOS and Linux installations, but it can be accessed at <a href="http://www.opengl.org">http://www.opengl.org</a> if needed.

libxml2 is an XML file parser that is a standard package on most MacOS and Linux installations, but it can be accessed at <a href="http://xmlsoft.org">http://xmlsoft.org</a> if needed.

FreeType2 is a freely available software library for rendering fonts. It is capable of producing high-quality output (glyph images) of most vector- and bitmap- font formats. It is a standard package on most MacOS and Linux installations, but it can be accessed at http://www.freetype.org if needed.

### 2.2 Optional Prerequisites

If the user wants to use IPEG images in a dcapp display, then they should install either libipeg or libipeg-turbo prior to building dcapp, dcapp will build just fine without one of these packages, but it won't be able to process IPEG images unless one of the packages is properly installed.

Much of the PixelStream functionality associated with the MJPEG and VSM protocols is built upon curl. If the user needs this functionality, then they should install curl prior to building dcapp. dcapp will build without curl, but most of the MJPEG and VSM PixelStream capabilities will be unavailable to the user unless curl is properly installed.

If dcapp is to be run in conjunction with a Trick simulation, then the trick-gte command (or the gte command for Trick version 15 and earlier) must be accessible via the command line for dcapp to build correctly. Also, a stand-alone version of trick\_comm must be successfully built prior to building dcapp. trick\_comm is a Trick library that provides an interface to a Trick simulation via the Trick variable server. Note that some older versions of Trick do not automatically build the stand-alone version of trick comm. If this is the case, install Trick, cd to \${TRICK HOME}, and type "make stand alone". Note that dcapp should work well with any Trick release numbered 10.2 or higher.

dcapp can be configured to monitor hardware inputs (dials, switches, etc.) via a controller area network (CAN) bus. CAN is a serial bus protocol used to connect individual systems and sensors over a single- or dual-wire networked data bus. Be sure that the CAN bus software is appropriately built and that the CANBUS HOME environment variable is set to the directory containing the necessary header and library files.

### 2.3 dcapp

Extract the dcapp package if necessary, cd to the top level of the package, and type "make". This should build the dcapp executable within the dcapp.app/Contents/\${OSSPEC} subdirectory, where OSSPEC is defined by the returned value of "dcapp.app/Contents/dcapp-config --osspec". On MacOS systems, OSSPEC is "MacOS". On other systems, it is typically set to a combination of 'uname -s' (converted to lower case) followed by an underscore ("\_") followed by 'uname -m' (for instance, "linux x86 64"). You should then add the returned value of "dcapp.app/Contents/dcapp-config --exepath" to your \$PATH environment variable if you intend to launch dcapp from the command line.

## 3.0 Activation

After following the instructions in section 2, simply type the following on the command line to activate dcapp:

```
dcapp file.xml [const=value...]
```

where file.xml is a full or partial path to a valid dcapp specfile (see section 4 for more information on dcapp specfiles). Note that the optional "const=value" constructs may be used as many times as needed to override the value of any constants defined within the specfile.

For instance, if a user wants to run dcapp with a specfile called myspec.xml but overriding the constants "WinWidth" and "WinHeight" with "480" and "640" respectively, the user would type the following command:

```
dcapp myspec.xml WinWidth=480 WinHeight=640
```

If a user chooses to run in debugging mode, which provides a wealth of debugging information to the console screen, the user may include a "-debug" argument anywhere on the command line after the specfile (file.xml).

Note that on MacOS, an alternative to launching dcapp via the command line is to use dcapp.app, which is automatically built during the "make" step described in section 2.3. dcapp.app can be launched like any MacOS application (double clicking it, launching it from the Dock, etc.). It brings up a simple user interface that requests the information described above from the user, then proceeds to launch dcapp accordingly.

# 4.0 Specfile

The dcapp specfile is a standard XML file used to customize the features and capabilities of dcapp. See http://www.w3.org/XML/ for more information about XML files, including valid file specifications, definition and usage of character entities, use of comments, etc. The elements contained within the dcapp specfile are detailed in this section.

#### 4.1 Root Element

Element	DCAPP
Parent	(none)
Children	(any)
Attributes	(none)
Description	All dcapp specfiles must contain this root element. All of the other
	elements, described in the following sections, must be enclosed within
	this root element.

### **4.2 Universal Elements**

These elements may appear anywhere within the dcapp specfile, and they may be embedded within any element that allows children.

Element	Dummy
Parent	(any)
Children	(any)
Attributes	(none)
Description	This element does nothing besides allowing the user to group sub- elements. This is potentially useful when using XML's <xi:include> element, which requires included files to be "well-formed", which means, among other things, that the file must contain only one element at its root level.</xi:include>

Element	Include
Parent	(any)
Children	(any)
Attributes	(none)
Description	This element inserts the contents of a separate file into this portion of the specfile. The content of this element must point to a valid XML file containing valid dcapp data via an absolute path or a path relative to the current file.

Element	lt
Parent	(any)
Children	True, False, (any)
Attributes	Operator, Value, Value1, Value2
Description	This element applies the <i>Operator</i> (one of "eq", "ne", "gt", "lt", "ge", or
	"le") to <i>Value1</i> and <i>Value2</i> to evaluate a true or false condition. If no
	Operator is defined, then it simply tests Value to determine true or
	false. If the logic evaluates to true, then the sub-elements within the
	"True" element are processed, otherwise, the sub-elements within the
	"False" element are processed. If there is no "True" or "False" sub-
	element defined, the contents of this element are assumed to be
	contained within a virtual "True" element.

Element	True
Parent	If
Children	(any)
Attributes	(none)
Description	This element simply encloses sub-elements that are to be processed if
	the logic of the encompassing "If" element resolves to "true".

Parent	If
Children	(any)
Attributes	(none)
Description	This element simply encloses sub-elements that are to be processed if
Î	the logic of the encompassing "If" element resolves to "false".

Element	Set
Parent	(any)
Children	(none)
Attributes	Variable, Operator, MinimumValue, MaximumValue
Description	This sets the value of <i>Variable</i> to a new value defined by the content of
	the element. The <i>Operator</i> is "=" by default, but may also be "+=" or "-
	=" if this element is to be used to increment or decrement <i>Variable</i>
	(usable only if <i>Variable</i> is a numeric type). <i>MinimumValue</i> and
	MaximumValue may optionally be set to bound the new numeric value.

Element	Animation
Parent	(any)
Children	Set, If
Attributes	Duration
Description	For each embedded "Set" element, this takes a snapshot of the current
	value and gradually sets it to the specified value over the course of the
	specified <i>Duration</i> . This is done linearly over each execution of dcapp
	until <i>Duration</i> is reached, at which point this element goes dormant
	until it is invoked again.

# **4.3 Initialization Elements**

These elements typically appear near the top of the dcapp specfile. They define the behavior of subsequent elements within the specfile.

# **4.3.1 Settings Elements**

Element	Constant
Parent	DCAPP
Children	(none)
Attributes	Name
Description	This allows a user to create a constant that can be accessed subsequently within the specfile. This is handy for setting values that are used frequently throughout the display. For instance, the user may set: <constant name="FontSize">24</constant> The pre-processor will then replace all instances of "#FontSize" in the rest of the specfile with "24".
Element	Variable

Parent	DCAPP
Children	Type, InitialValue
Attributes	(none)
Description	This allows a user to create a variable that can be accessed
	subsequently within the specfile. The <i>Type</i> must be either "Float",
	"Integer", or "String". For instance, the user may set:
	<variable type="Integer">MyVar</variable>
	Any subsequent elements may then use the associated value by
	specifying a value of "@MyVar". Note that if <i>InitialValue</i> is not
	specified, the default value is 0 for float and integer parameters and an
	empty string ("") for string parameters.

Element	Style
Parent	DCAPP
Children	(any)
Attributes	Name
Description	This allows a user to define a style, which defines attributes for any element that is used subsequently within the specfile. For instance, the user may set: <pre></pre>

Element	Defaults
Parent	DCAPP
Children	(any)
Attributes	(none)
Description	This allows a user to define default attributes for any element that is used subsequently within the specfile. For instance, the user may set: <defaults></defaults>
	be defined within a single "Defaults" element.

# 4.3.2 Input/Output Elements

Element	TrickIo
Parent	DCAPP
Children	FromTrick, ToTrick
Attributes	Host, Port, DataRate, DisconnectAction
Description	This construct specifies communication between dcapp and the Trick

variable server. *Host* specifies the hostname upon which the Trick simulation is executing. If not specified, the default value is the hostname of the machine upon which dcapp is executing. *Port* specifies the port over which communication with the Trick variable server takes place. If not specified, the default value is 7000. DataRate specifies the data rate (in seconds) at which Trick will attempt to communicate with dcapp. If not specified, the default value is 1 second. *DisconnectAction* defines the action that dcapp takes if it loses connection with Trick. Options are "Terminate" or "Reconnect", with "Terminate" being the default action if none is specified. Note that the values for *Host* and *Port* may be overridden by the commandline arguments outlined in section 3.

Eleme	nt	FromTrick
Parent	t	Tricklo
Childr	en	TrickVariable
Attrib	utes	(none)
Descri	ption	This contains a list of the "TrickVariable" elements that are used to
		over-write dcapp data with data from the attached Trick simulation.

Element	ToTrick
Parent	TrickIo
Children	TrickVariable
Attributes	(none)
Description	This contains a list of the "TrickVariable" elements that are used to
	over-write Trick simulation data with data from dcapp.

Element	TrickVariable
Parent	FromTrick, ToTrick
Children	(none)
Attributes	Name, Units
Description	This element attaches a dcapp "Variable" to the variable in the
	attached Trick simulation defined by <i>Name</i> . The user may optionally
	define the <i>Units</i> of the data within dcapp, which the Trick variable
	server will use to convert the data, if necessary. The <i>Units</i> must be a
	unit string recognizable by Trick. For instance:
	<pre><trickvariable name="trickobj.var">MyVar</trickvariable></pre>

Element	EdgeIo
Parent	DCAPP
Children	FromEdge, ToEdge
Attributes	Host, Port, DataRate
Description	This construct specifies communication between dcapp and EDGE via
	EDGE's remote commanding server server. <i>Host</i> specifies the
	hostname upon which EDGE is executing. If not specified, the default

value is the hostname of the machine upon which dcapp is executing.
Port specifies the port over which communication with EDGE takes
place. If not specified, the default value is 5451. <i>DataRate</i> specifies
the data rate (in seconds) at which EDGE will be polled by dcapp. If
not specified, the default value is 1 second.

Element	FromEdge
Parent	EdgeIo
Children	EdgeVariable
Attributes	(none)
Description	This contains a list of the "EdgeVariable" elements that are used to
	over-write dcapp data with data from the attached EDGE instance. For
	instance:
	<pre><edgevariable rcscommand="doug.node Light set - lit int">LightCmd</edgevariable></pre>
Description	over-write dcapp data with data from the attached EDGE instance. For instance:

Element	ToEdge
Parent	EdgeIo
Children	EdgeVariable
Attributes	(none)
Description	This contains a list of the "EdgeVariable" elements that are used to
	over-write EDGE data with data from dcapp.

Element	EdgeVariable
Parent	FromEdge, ToEdge
Children	(none)
Attributes	RcsCommand
Description	This element attaches a dcapp "Variable" to the variable in the
	attached EDGE instance defined by RcsCommand.

Element	CAN
Parent	DCAPP
Children	(none)
Attributes	Network, ButtonID, ControlID
Description	This element assigns bezel keys to data associated with a CAN bus
	based upon <i>Network</i> , <i>ButtonID</i> , and <i>ControlID</i> of the unit associated
	with this instance of dcapp. The bezel keys are processed via the
	"Button" and/or "BezelEvent" elements.

Element	UEI
Parent	DCAPP
Children	(none)
Attributes	Host, Port, BezelID
Description	This element assigns bezel keys to data associated with a UEI
•	controller based upon the <i>Host</i> and <i>Port</i> of the UEI and the <i>BezelID</i> of

the unit associated with this instance of dcapp. The bezel keys are processed via the "Button" and/or "BezelEvent" elements.

# **4.3.3 Logic Element**

Element	DisplayLogic
Parent	DCAPP
Children	(none)
Attributes	(none)
Description	The content of this element specifies a shared object file to be linked
	into dcapp at execution time. See section 5.3 for more information
	about the format and content of this file.

# 4.4 Display Setup

Element	Window
Parent	DCAPP
Children	Panel
Attributes	X, Y, Width, Height, FullScreen, ActiveDisplay, ForceUpdate
Description	This defines the position ( <i>X</i> and <i>Y</i> ) and size ( <i>Width</i> and <i>Height</i> ) of the window containing the dcapp displays. If <i>FullScreen</i> is set to "true", "yes", or "on", the window will be rendered full screen regardless of <i>X</i> , <i>Y</i> , <i>Width</i> , and <i>Height</i> settings. The <i>ActiveDisplay</i> attribute allows the user to assign a variable to determine which display is active at any given time. If the value of this variable corresponds to the <i>DisplayIndex</i> of a given panel (see below), then that panel becomes the active display. By default, dcapp only updates when it senses an event (a mouse event, input data change, etc.), but the user may set <i>ForceUpdate</i> to specify an interval, in seconds, after which dcapp will automatically update.

Element	Panel
Parent	Window
Children	(display primitives)
Attributes	DisplayIndex, BackgroundColor, VirtualWidth, VirtualHeight
Description	This contains all of the display primitives for a given display panel. The <i>DisplayIndex</i> attribute is used to define when this display is the active display. <i>BackgroundColor</i> specifies the background color for the panel. See section 5.1 for information on specifying color. If not specified, the default color is black ("0 0 0"). <i>VirtualWidth</i> and <i>VirtualHeight</i> define the user-specified geometry of the display panel, which is used to render the position and size of the display primitives. If not specified, the default geometry is 100x100 units.

# **4.5 Display Primitives**

The display primitives are the building blocks that define how the individual display panels look, feel, and react to user input. They are grouped into two primary classifications: visual primitives, which are primitives that render data to the screen, and event primitives, which are primitives that handle user input.

### **4.5.1 Visual Primitives**

P1 .	
Element	Container
Parent	Panel, Container, Button, Active, Inactive, On, Transition, Off
Children	(display primitives)
Attributes	X, Y, Width, Height, HorizontalAlign, VerticalAlign, VirtualWidth, VirtualHeight, Rotate
Description	This redefines the coordinate frame for subsequent primitives by allowing the user to define a box of size <i>Width</i> by <i>Height</i> at position <i>X</i> , <i>Y</i> , and aligned by <i>HorizontalAlign</i> and <i>VerticalAlign</i> , within the current coordinate frame. The new coordinate frame can also be rotated by <i>Rotate</i> degrees from the current coordinate frame, and the new coordinate frame uses <i>VirtualWidth</i> and <i>VirtualHeight</i> to define the width and height of subsequent elements within the new frame.
Element	T to a
Element Parent	Line Panel Container Button Active Inactive On Transition Off
Children	Panel, Container, Button, Active, Inactive, On, Transition, Off Vertex
Attributes	LineWidth, Color
	This attaches the enclosed "Vertex" primitives to form a single,
Description	continuous line with the specified <i>LineWidth</i> and <i>Color</i> .
	continuous fine with the specified linewidth and color.
Element	Polygon
Parent	Panel, Container, Button, Active, Inactive, On, Transition, Off
Children	Vertex
Attributes	FillColor, LineColor, LineWidth
Description	This attaches the enclosed "Vertex" primitives to form a polygon. The polygon is filled with <i>FillColor</i> and outlined with a line of color <i>LineColor</i> and a width of <i>LineWidth</i> . If <i>FillColor</i> is not set, then the polygon is not filled. Likewise, if <i>LineColor</i> and <i>LineWidth</i> are not set, then the polygon is not outlined. Note that this primitive works well for convex polygons, but the behavior for polygons with concave vertices is undefined.
73	
Element	Vertex
Parent	Panel, Container, Button, Active, Inactive, On, Transition, Off
Children	(none)
Attributes	X, Y
Description	This defines the <i>X</i> and <i>Y</i> coordinates of a vertex within a "Line" or "Polygon" primitive.

Element	Rectangle
Parent	Panel, Container, Button, Active, Inactive, On, Transition, Off
Children	(none)
Attributes	X, Y, Width, Height, HorizontalAlign, VerticalAlign, Rotate, FillColor,
	LineColor, LineWidth
Description	This renders a rectangle based upon the location, size, alignment, and orientation specified by the user. The rectangle is filled with <i>FillColor</i> and outlined with a line of color <i>LineColor</i> and a width of <i>LineWidth</i> . If <i>FillColor</i> is not set, then the rectangle is not filled. Likewise, if
	LineColor and LineWidth are not set, then the rectangle is not outlined.

Element	Circle
Parent	Panel, Container, Button, Active, Inactive, On, Transition, Off
Children	(none)
Attributes	X, Y, HorizontalAlign, VerticalAlign, Radius, Segments, FillColor,
	LineColor, LineWidth
Description	This renders a circle based upon the location, radius, and alignment
	specified by the user. The user may also specify the number of
	straight-line segments used to render the circle via Segments (default
	is 80). The circle is filled with <i>FillColor</i> and outlined with a line of
	color <i>LineColor</i> and a width of <i>LineWidth</i> . If <i>FillColor</i> is not set, then
	the circle is not filled. Likewise, if <i>LineColor</i> and <i>LineWidth</i> are not set,
	then the circle is not outlined.

Element	String
Parent	Panel, Container, Button, Active, Inactive, On, Transition, Off
Children	(none)
Attributes	X, Y, Rotate, Size, HorizontalAlign, VerticalAlign, Color,
	BackgroundColor, ShadowOffset, Font, Face, ForceMono
Description	This renders a character string based on the location, size, alignment, and rotation specified by the user. The user may also specify the <i>Font</i> and <i>Face</i> . Note that <i>Font</i> must point to a valid FreeType-accessible font file (most modern font files are FreeType-accessible) via an absolute path or a path relative to the current file. Different font files offer different options for <i>Face</i> , but typical options include "Bold", "Italic", etc., and if <i>Face</i> is not specified, the default face for the font is used. The <i>ForceMono</i> optional flag accommodates three possible values: "Numeric", "Alphanumeric", or "All". This allows the user to render some or all of the characters in a variable-width font as fixed width. The user may specify font <i>Color</i> with an optional <i>BackgroundColor</i> , and <i>ShadowOffset</i> allows the user to specify the offset of a shadow to be rendered behind the font (no shadow is rendered if <i>ShadowOffset</i> is not set). The content of this element is the string to be rendered, and it may contain static text, variable text, or

both. dcapp variables may be accessed using the ampersand: "@MyVar", as well as an optional C-format specifier contained within parentheses: "@MyVar(%.2f)".

Element	Image
Parent	Panel, Container, Button, Active, Inactive, On, Transition, Off
Children	(none)
Attributes	X, Y, Width, Height, HorizontalAlign, VerticalAlign, Rotate
Description	This renders an image based on the location, size, alignment, and rotation specified by the user. The content of this element must point to a graphical file in a format usable by dcapp (see section 5.3) via an absolute path or a path relative to the current file.

Element	PixelStream
Parent	Panel, Container, Button, Active, Inactive, On, Transition, Off
Children	(none)
Attributes	X, Y, Width, Height, HorizontalAlign, VerticalAlign, Rotate, Protocol,
	Host, Port, Path, SharedMemoryKey, File, TestPattern
Description	This renders a dynamic image based on the location, size, alignment,
	and rotation specified by the user. The dynamic image must be
	generated by a separate package running a compatible PixelStream
	writer. <i>Protocol</i> is either "File", "MJPEG", "TCP", or "VSM" ("File" is
	typically best if the writer is on the same computer as dcapp, and
	"MJPEG" is typically best if the writer is on a remote computer. "VSM"
	is designed specifically for use with the video stream manager (VSM)
	application). Note that "MJPEG" and "VSM" only work <i>IF</i> the user has installed libjpeg (or libjpeg-turbo) and curl on their computer. For
	"File", the user must specify a <i>SharedMemoryKey</i> , which provides
	shared memory space for hand-shaking, and a <i>File</i> , which provides
	disk space containing image RGB information, that matches those
	settings for the writer. For "MJPEG" or "TCP", the user must provide
	the name of the remote <i>Host</i> (default is "localhost") and the <i>Port</i>
	number (default for "MJPEG" is "80") used by the PixelStream writer.
	Also for "MJPEG" the user may specify a <i>Path</i> in addition to <i>Host</i> and
	Port. "VSM" requires the user to specify a Host and Port for the VSM
	application as well as <i>Camera</i> , which specifies the name of the camera
	to be requested from VSM (this is typically a variable name). A user
	may also specify a <i>Path</i> for VSM that overrides the default path passed
	back by VSM. If the user specifies a <i>TestPattern</i> file in a graphical
	format usable by dcapp (see section 5.3) via an absolute path or a path
	relative to the current file, then the image associated with this file will
	be displayed if the PixelStream is not currently connected to a
	PixelStream source.

Element

ADI

Parent	Panel, Container, Button, Active, Inactive, On, Transition, Off
Children	(none)
Attributes	X, Y, Width, Height, HorizontalAlign, VerticalAlign, OuterRadius, BallRadius, ChevronWidth, ChevronHeight, BallFile, CoverFile, Roll,
	Pitch, Yaw, RollError, PitchError, YawError
Description	This renders an attitude direction indicator (ADI), or 8-ball, used in
	flying vehicles to show attitude (pitch/yaw/roll) information. It is
	rendered with the location, size, and alignment information provided
	by the user. The user may also customize OuterRadius, BallRadius,
	ChevronWidth, and ChevronHeight. BallFile and CoverFile allow the
	user to specify an image to overlay on the 8-ball and an image for the
	instrument face. Roll, Pitch, Yaw, RollError, PitchError, and YawError
	point to variables used to drive the information on the ADI.

# **4.5.2 Event Primitives**

Element	Button
Parent	Panel, Container
Children	Active, Inactive, On, Transition, Off, OnPress, OnRelease, (display primitives)
Attributes	X, Y, Width, Height, HorizontalAlign, VerticalAlign, Rotate, Type, Key, KeyASCII, BezelKey, Variable, On, Off, SwitchVariable, SwitchOn, SwitchOff, IndicatorVariable, IndicatorOn, ActiveVariable, ActiveOn
Description	

Element	Active
Parent	Button
Children	(display primitives)
Attributes	(none)
Description	This contains a list of primitives to be rendered when a Button is in
	the "active" state (when ActiveVariable is set to the ActiveOn value).

Element	Inactive
Parent	Button
Children	(display primitives)
Attributes	(none)
Description	This contains a list of primitives to be rendered when a Button is in
_	the "inactive" state (when ActiveVariable is not set to the ActiveOn
	value).

Element	On
Parent	Button
Children	(display primitives)
Attributes	(none)
Description	This contains a list of primitives to be rendered when a Button is in

	the "on" state (when Indicator Variable is set to the Indicator On value).
Element	Transition
Parent	Button
Children	(display primitives)
Attributes	(none)
Description	This contains a list of primitives to be rendered when a Button is in
Bescription	the "transition" state (when Indicator Variable and Switch Variable are
	in different states).
Element	Off
Parent	Button
Children	(display primitives)
Attributes	(none)
Description	This contains a list of primitives to be rendered when a Button is in
	the "off" state (when IndicatorVariable is not set to the IndicatorOn
	value).
Element	MouseMotion
Parent	Panel, Container
Children	(none)
Attributes	XVariable, YVariable
Description	This element provides the user with the current X and Y position of
•	the mouse within the context of the Panel or Container within which it
	exists. Note that if this element is active, it will sense any mouse
	motion as an event, which will trigger a display update, which can be
	computationally expensive.
Pl .	LW B
Element	MouseEvent
Parent	Panel, Container
Children Attributes	OnPress, OnRelease, Set, If, Animation X, Y, Width, Height, HorizontalAlign, VerticalAlign
Description	This element sets up a listener to react when the mouse is pressed or
Description	released in a bounding volume specified by this element's attributes.
	The listener then executes the elements contained within its
	"OnPress" and "OnRelease" elements. If there is no "OnPress" or
	"OnRelease" sub-element defined, the contents of this element are
	assumed to be contained within a virtual "OnPress" element.
_,	
Element	KeyboardEvent
Parent	Panel, Container
Children	OnPress, OnRelease, Set, If, Animation
Attributes	Key, KeyASCII
Description	This element sets up a listener to react when a specified key on a
	keyboard is pressed or released. The key can be specified either with

Key (for instance "a", "b", "Q", "3", "\$", etc.) or with KeyASCII if the user wishes to specify a key that is not easily specifiable in an XML file (for instance, "8" to represent the "backspace" key). The listener then executes the elements contained within its "OnPress" and "OnRelease" elements. If there is no "OnPress" or "OnRelease" sub-element defined, the contents of this element are assumed to be contained within a virtual "OnPress" element.

Element	BezelEvent
Parent	Panel, Container
Children	OnPress, OnRelease, Set, If, Animation
Attributes	Key
Description	This element sets up a listener to react when a specified bezel <i>Key</i> is
	pressed or released. The listener then executes the elements
	contained within its "OnPress" and "OnRelease" elements. If there is
	no "OnPress" or "OnRelease" sub-element defined, the contents of this
	element are assumed to be contained within a virtual "OnPress"
	element.

Element	OnPress
Parent	Button, MouseEvent, KeyboardEvent, BezelEvent
Children	Set, If, Animation
Attributes	(none)
Description	This element defines a list of actions to take if the parent element
	senses a "press" condition.

Element	OnRelease
Parent	Button, MouseEvent, KeyboardEvent, BezelEvent
Children	Set, If, Animation
Attributes	(none)
Description	This element defines a list of actions to take if the parent element
	senses a "release" condition.

### 5.0 Technical Details

### **5.1 Color Format Specification**

When specifying color formats for any dcapp display elements, the following format must be used:

```
red_level green_level blue_level alpha_level
```

where each level is expressed as a number between 0 (full off) and 1 (full on). Note that if alpha level isn't specified, dcapp assumes a value of 1 (fully opaque).

Examples may include: black specified as "0 0 0", white specified as "1 1 1", blue specified as "0 0 1", grey specified as "0.5 0.5 0.5", etc.

### **5.2 Alignment Specification**

Options for HorizontalAlign attributes are "AlignLeft", "AlignCenter", and "AlignRight". Options for VerticalAlign attributes are "AlignBottom", "AlignMiddle", and "AlignTop". If a user doesn't specify alignment, "AlignLeft" and "AlignBottom" are used as default values.

### **5.3 Graphic File Formats**

dcapp can currently handle graphic files in TARGA (.tga) and bitmap (.bmp) formats. TARGA files should be saved uncompressed with a "bottom left" origin. Bitmap files should be saved in 24-bit format, although files saved in other valid bitmap formats may work. dcapp also handles IPEG (.jpg or .jpeg) formats IF the user has installed libjpeg (or libjpeg-turbo) on their computer.

#### 5.4 Display Logic File

While dcapp sets the value of its variables automatically based upon user specifications provided within the XML specfile, it also provides the capability for a user to modify those variables using custom C++ software. This is useful if the user wants the display to operate in non-standard or complex ways. To facilitate this, dcapp provides a command-line tool called dcapp genheader, which is activated with the following syntax:

```
dcapp genheader file.xml [output file]
```

where file.xml is a full or partial path to a valid dcapp specfile and output file is the name of the C++ header file to be created (the default value is "dcapp.h"). This tool mines the specifie, finds all of the dcapp variables, and provides them to the user as pointers (double \*, int \*, or std::string \*, depending upon how they're defined in the specfile) in output file.

From there, the user may create one or more C++ files to manipulate these variables. The user must #include output file in the C++ files and include C++ logic within one of these three "void" routines:

- DisplayInit
- DisplayLogic
- DisplayClose

Note that these routines do not accept arguments, and the user need only include the ones that are needed for their logic. DisplayInit is executed once at dcapp startup and DisplayClose is executed once at dcapp shutdown. DisplayLogic is

executed whenever dcapp senses that a display should be updated, which includes a keyboard or mouse event, a variable update, etc.

Once the user creates the logic files, they should be compiled into a shared object. Doing so can differ per operating system but typically looks something like:

```
c++ -fPIC -shared mylogic.cc -o mylogic.so
```

From there, the user instructs dcapp to use this customized logic by using the DisplayLogic element (see section 4.3.3) within the specfile.

**5.5 Element Values** 

5.5.1 Constants

5.5.2 Variables

#### **5.5.3 Environment Variables**

The user may access the value of any available environment variable from within the specfile by prepending the name of the environment variable with a dollar sign ("\$"). For instance, the following String element shows the value of the USER environment variable:

```
<String>my user name is $USER</String>
```

Note that dcapp makes the following environment variables available to the user:

- dcappOSTYPE
- dcappOSSPEC
- dcappOBIDIR
- dcappBINDIR

These values are set to the return values of the dcapp.app/Contents/dcapp-config script with the following arguments respectively: --ostype, --osspec, --objdir, and -bindir. Note that using the above environment variables in the specfile in conjunction with the corresponding return values from the dcapp.app/Contents/dcapp-config script in build files are a great way of ensuring that the specfile and build files are pointing to the same files and directories.

Other environment variables provided by dcapp include:

- dcappDisplayHome
- dcappVersion

The dcappDisplayHome variable is set to the directory containing the specfile. It is useful for specifying a path to a Font, Image, etc., with respect to the specfile instead

of to the current file, which may change if Include elements are used. The dcappVersion provides a way to test the current version of dcapp from within the specfile in the event that a display needs to run with two or more versions of dcapp that may or may not be fully compatible from a programming interface perspective.

Besides the above variables, dcapp makes the following environment variables available to the user from within the specfile by setting them if they haven't already been set:

- USER
- LOGNAME
- HOME
- OSTYPE
- MACHTYPE
- HOST