

Named Item Routines

5.4

Generated by Doxygen 1.9.1

1 Module Index	1
1.1 Modules	1
2 Namespace Index	3
2.1 Namespace List	3
3 Data Structure Index	5
3.1 Data Structures	5
4 File Index	7
4.1 File List	7
5 Module Documentation	9
5.1 Models	9
5.1.1 Detailed Description	9
5.2 Utils	9
5.2.1 Detailed Description	9
5.3 NamedItem	9
5.3.1 Detailed Description	10
5.3.2 Macro Definition Documentation	10
5.3.2.1 __has_include	10
5.3.3 Function Documentation	10
5.3.3.1 operator==([1/2])	10
5.3.3.2 operator==([2/2])	10
6 Namespace Documentation	11
6.1 jeod Namespace Reference	11
6.1.1 Detailed Description	11
7 Data Structure Documentation	13
7.1 jeod::NamedItem Class Reference	13
7.1.1 Detailed Description	15
7.1.2 Member Typedef Documentation	15
7.1.2.1 size_type	15
7.1.3 Constructor & Destructor Documentation	15
7.1.3.1 NamedItem() [1/3]	15
7.1.3.2 NamedItem() [2/3]	16
7.1.3.3 NamedItem() [3/3]	16
7.1.3.4 ~NamedItem()	16
7.1.4 Member Function Documentation	16
7.1.4.1 c_str()	16
7.1.4.2 construct_name() [1/2]	16
7.1.4.3 construct_name() [2/2]	16
7.1.4.4 demangle()	17

7.1.4.5 ends_with()	17
7.1.4.6 freeze_name()	18
7.1.4.7 get_is_frozen()	18
7.1.4.8 get_name()	18
7.1.4.9 operator=() [1/3]	19
7.1.4.10 operator=() [2/3]	19
7.1.4.11 operator=() [3/3]	19
7.1.4.12 operator==()	19
7.1.4.13 p()	20
7.1.4.14 set_name() [1/2]	20
7.1.4.15 set_name() [2/2]	20
7.1.4.16 size()	20
7.1.4.17 suffix() [1/2]	21
7.1.4.18 suffix() [2/2]	21
7.1.4.19 unfreeze_name()	21
7.1.4.20 validate_name() [1/2]	22
7.1.4.21 validate_name() [2/2]	22
7.1.4.22 verify_unfrozen_name()	23
7.1.5 Field Documentation	23
7.1.5.1 is_frozen	23
7.1.5.2 name	23
7.2 jeod::NamedItemMessages Class Reference	24
7.2.1 Detailed Description	24
7.2.2 Constructor & Destructor Documentation	24
7.2.2.1 NamedItemMessages() [1/2]	24
7.2.2.2 NamedItemMessages() [2/2]	24
7.2.3 Member Function Documentation	25
7.2.3.1 JEOD_CLASS_ESTABLISH_FRIENDS2()	25
7.2.3.2 operator=()	25
7.2.4 Field Documentation	25
7.2.4.1 bad_args	25
7.2.4.2 frozen_name	25
7.2.4.3 invalid_name	25
8 File Documentation	27
8.1 named_item.cc File Reference	27
8.1.1 Detailed Description	27
8.2 named_item.hh File Reference	28
8.2.1 Detailed Description	28
8.3 named_item_demangle.cc File Reference	28
8.3.1 Detailed Description	29
8.4 named_item_messages.cc File Reference	29

8.4.1 Detailed Description	29
8.4.2 Macro Definition Documentation	29
8.4.2.1 MAKE_NAMEDITEM_MESSAGE_CODE	29
8.5 named_item_messages.hh File Reference	30
8.5.1 Detailed Description	30
Index	31

Chapter 1

Module Index

1.1 Modules

Here is a list of all modules:

Models	9
Utils	9
NamedItem	9

Chapter 2

Namespace Index

2.1 Namespace List

Here is a list of all namespaces with brief descriptions:

jeod	Namespace jeod	11
----------------------	--------------------------	--------------------

Chapter 3

Data Structure Index

3.1 Data Structures

Here are the data structures with brief descriptions:

jeod::NamedItem	
Provides a set of static methods for constructing dot-conjoined names	13
jeod::NamedItemMessages	
Specifies the message IDs used in the named_item model	24

Chapter 4

File Index

4.1 File List

Here is a list of all files with brief descriptions:

named_item.cc	Construct the name of a NamedItem object by conjoining the passed parameters with a dot . . .	27
named_item.hh	Define the NamedItem utility class	28
named_item_demangle.cc	Demangle a C++ name, isolated from other NamedItem methods because this has the potential to get big and ugly if JEOD is ported to a number of different systems	28
named_item_messages.cc	Implement the class NamedItemMessages	29
named_item_messages.hh	Define the class NamedItemMessages, the class that specifies the message IDs used in the named item model	30

Chapter 5

Module Documentation

5.1 Models

Modules

- [Utils](#)

5.1.1 Detailed Description

5.2 Utils

Modules

- [NamedItem](#)

5.2.1 Detailed Description

5.3 NamedItem

Files

- file [named_item.hh](#)
Define the NamedItem utility class.
- file [named_item_messages.hh](#)
Define the class NamedItemMessages, the class that specifies the message IDs used in the named item model.
- file [named_item.cc](#)
Construct the name of a NamedItem object by conjoining the passed parameters with a dot.
- file [named_item_demangle.cc](#)
Demangle a C++ name, isolated from other NamedItem methods because this has the potential to get big and ugly if JEOD is ported to a number of different systems.
- file [named_item_messages.cc](#)
Implement the class NamedItemMessages.

Macros

- `#define __has_include(x) 0`

Functions

- `bool operator==(const jeod::NamedItem &lhs, const std::string &rhs)`
Comparison to string.
- `bool operator==(const std::string &lhs, const jeod::NamedItem &rhs)`

5.3.1 Detailed Description

5.3.2 Macro Definition Documentation

5.3.2.1 __has_include

```
#define __has_include(  
    x ) 0
```

Definition at line 32 of file named_item_demangle.cc.

5.3.3 Function Documentation

5.3.3.1 operator==() [1/2]

```
bool operator== (  
    const jeod::NamedItem & lhs,  
    const std::string & rhs )
```

Comparison to string.

Definition at line 103 of file named_item.cc.

References jeod::NamedItem::get_name().

5.3.3.2 operator==() [2/2]

```
bool operator== (  
    const std::string & lhs,  
    const jeod::NamedItem & rhs )
```

Definition at line 108 of file named_item.cc.

References jeod::NamedItem::get_name().

Chapter 6

Namespace Documentation

6.1 jeod Namespace Reference

Namespace jeod.

Data Structures

- class [NamedItem](#)
Provides a set of static methods for constructing dot-conjoined names.
- class [NamedItemMessages](#)
Specifies the message IDs used in the named_item model.

6.1.1 Detailed Description

Namespace jeod.

Chapter 7

Data Structure Documentation

7.1 jeod::NamedItem Class Reference

Provides a set of static methods for constructing dot-conjoined names.

```
#include <named_item.hh>
```

Public Types

- using `size_type` = `std::string::size_type`
The size type used in `std::string`.

Public Member Functions

- `NamedItem` (`std::string name_in=std::string()`, `bool frozen_in=false`)
Default constructor.
- `NamedItem` (`const NamedItem &`)=default
Copy constructor.
- `NamedItem` (`NamedItem &&`)=default
Move constructor.
- virtual `~NamedItem` ()=default
Destructor.
- `NamedItem & operator=` (`const NamedItem &src`)
Copy assignment.
- `NamedItem & operator=` (`NamedItem &&src`)
Move assignment.
- `NamedItem & operator=` (`const std::string &name_in`)
Assignment from a string.
- `bool operator==` (`const NamedItem &rhs`)
Comparison of names.
- `std::string get_name` () const
Getter for name.
- `const char * c_str` () const
Getter for name, as a C-style string.

- `size_type size ()` const
Getter for the length of the name.
- `bool get_is_frozen ()` const
Getter for is_frozen.
- `bool ends_with (size_type pos1, const std::string &other)` const
Compare the end of this string to a C-style string.
- `std::string suffix (const std::string &test_name)` const
Given a dot-conjoined test name, find the part of the test name that follows this name, as a prefix.
- `void set_name (const std::string &nameIn)`
- `template<typename... Type>`
`void set_name (const std::string &nameIn, Type... namesIn)`
Set the name as a dot-conjoined string of the given inputs.
- `void verify_unfrozen_name ()` const
Verify that the name is not frozen.
- `void validate_name (const char *file, unsigned int line, const std::string &variable_type, const std::string &variable_name)`
Checks whether a name is trivially invalid, failing if it is.
- `void freeze_name ()`
Freeze the name – i.e., denote that the name as no longer settable.

Static Public Member Functions

- `static std::string construct_name (const std::string &nameIn)`
Construct a name from the given input, as a string.
- `template<typename... Type>`
`static std::string construct_name (const std::string &nameIn, Type... namesIn)`
Construct a name as a dot-conjoined string of the given inputs.
- `static std::string suffix (const std::string &prefix, const std::string &name)`
Given a prefix and a dot-conjoined name, find the part of the name that follows the prefix.
- `static const std::string demangle (const std::type_info &info)`
Demangle a C++ name.
- `static void validate_name (const char *file, unsigned int line, const std::string &variable_value, const std::string &variable_type, const std::string &variable_name)`
Checks whether a name is trivially invalid, failing if it is.

Protected Member Functions

- `void unfreeze_name ()`
Unfreeze the name – i.e., denote that the name is now settable.

Private Member Functions

- `JEOD_CLASS_ESTABLISH_FRIENDS2 p (jeod, NamedItem)`

Private Attributes

- `std::string name`
The item's name.
- `bool is_frozen`
Indicates whether the name is frozen.

7.1.1 Detailed Description

Provides a set of static methods for constructing dot-conjoined names.

The methods defined in this class allocate memory and do not release it. Releasing that memory is the responsibility of the calling function. Use the macro JEOD_DELETE_ARRAY to release this memory.

Prior to JEOD 4.0, the [NamedItem](#) class was not instantiable. It is in JEOD 4.0. The [NamedItem](#) class forms the basis of a thing with a name, with the name being a `std::string`. The `construct_name` functions and & related functions that allocate a C-style string are deprecated.

Definition at line 94 of file `named_item.hh`.

7.1.2 Member Typedef Documentation

7.1.2.1 size_type

```
using jeod::NamedItem::size_type = std::string::size_type
```

The size type used in `std::string`.

Definition at line 100 of file `named_item.hh`.

7.1.3 Constructor & Destructor Documentation

7.1.3.1 NamedItem() [1/3]

```
jeod::NamedItem::NamedItem (
    std::string name_in = std::string(),
    bool frozen_in = false ) [inline]
```

Default constructor.

This is the default constructor by virtue of the defaults.

Parameters

<i>name_in</i>	Initial value of the name, defaults to the empty string.
<i>frozen_in</i>	Initial value of <code>is_frozen</code> , defaults to false.

Definition at line 164 of file `named_item.hh`.

7.1.3.2 NamedItem() [2/3]

```
jeod::NamedItem::NamedItem (
    const NamedItem & ) [default]
```

Copy constructor.

The default implementation works fine.

7.1.3.3 NamedItem() [3/3]

```
jeod::NamedItem::NamedItem (
    NamedItem && ) [default]
```

Move constructor.

The default implementation works fine.

7.1.3.4 ~NamedItem()

```
virtual jeod::NamedItem::~~NamedItem ( ) [virtual], [default]
```

Destructor.

The default implementation virtually works fine.

7.1.4 Member Function Documentation**7.1.4.1 c_str()**

```
const char* jeod::NamedItem::c_str ( ) const [inline]
```

Getter for name, as a C-style string.

Definition at line 242 of file named_item.hh.

7.1.4.2 construct_name() [1/2]

```
static std::string jeod::NamedItem::construct_name (
    const std::string & nameIn ) [inline], [static]
```

Construct a name from the given input, as a string.

The input must not be the empty string or the null pointer.

Definition at line 106 of file named_item.hh.

7.1.4.3 construct_name() [2/2]

```
template<typename... Type>
static std::string jeod::NamedItem::construct_name (
    const std::string & nameIn,
    Type... namesIn ) [inline], [static]
```

Construct a name as a dot-conjoined string of the given inputs.

Each input must not be the empty string or the null pointer.

Template Parameters

<i>Type</i>	Types of the remaining arguments to construct_name.
-------------	---

Parameters

<i>nameIn</i>	First argument to construct_name.
<i>names↔In</i>	Remaining arguments to construct_name.

Returns

The given inputs as a dot-conjoined string.

Definition at line 120 of file named_item.hh.

7.1.4.4 demangle()

```
const std::string jeod::NamedItem::demangle (
    const std::type_info & info ) [static]
```

Demangle a C++ name.

Returns

Demangled name

Parameters

<i>in</i>	<i>info</i>	Typeinfo to be demangled
-----------	-------------	--------------------------

Definition at line 58 of file named_item_demangle.cc.

7.1.4.5 ends_with()

```
bool jeod::NamedItem::ends_with (
    size_type pos1,
    const std::string & other ) const [inline]
```

Compare the end of this string to a C-style string.

See std::string::compare.

Parameters

<i>pos1</i>	The start index in the name.
<i>other</i>	The C-style null-terminated string.

Returns

True if the end part of the name equals the given C-style string.

Definition at line 270 of file `named_item.hh`.

7.1.4.6 freeze_name()

```
void jeod::NamedItem::freeze_name ( ) [inline]
```

Freeze the name – i.e., denote that the name as no longer settable.

Definition at line 329 of file `named_item.hh`.

7.1.4.7 get_is_frozen()

```
bool jeod::NamedItem::get_is_frozen ( ) const [inline]
```

Getter for `is_frozen`.

Definition at line 258 of file `named_item.hh`.

7.1.4.8 get_name()

```
std::string jeod::NamedItem::get_name ( ) const [inline]
```

Getter for `name`.

Definition at line 234 of file `named_item.hh`.

Referenced by operator `==()`.

7.1.4.9 operator=() [1/3]

```
NamedItem& jeod::NamedItem::operator= (
    const NamedItem & src ) [inline]
```

Copy assignment.

Only the name is copied, and only if the name isn't frozen.

Definition at line 195 of file named_item.hh.

7.1.4.10 operator=() [2/3]

```
NamedItem& jeod::NamedItem::operator= (
    const std::string & name_in ) [inline]
```

Assignment from a string.

Definition at line 216 of file named_item.hh.

7.1.4.11 operator=() [3/3]

```
NamedItem& jeod::NamedItem::operator= (
    NamedItem && src ) [inline]
```

Move assignment.

The default implementation works fine.

Definition at line 205 of file named_item.hh.

7.1.4.12 operator==()

```
bool jeod::NamedItem::operator== (
    const NamedItem & rhs ) [inline]
```

Comparison of names.

Definition at line 226 of file named_item.hh.

7.1.4.13 p()

```
JEOD_CLASS_ESTABLISH_FRIENDS2 jeod::NamedItem::p (
    jeod ,
    NamedItem ) [private]
```

References `validate_name()`.

7.1.4.14 set_name() [1/2]

```
void jeod::NamedItem::set_name (
    const std::string & nameIn ) [inline]
```

Definition at line 288 of file `named_item.hh`.

7.1.4.15 set_name() [2/2]

```
template<typename... Type>
void jeod::NamedItem::set_name (
    const std::string & nameIn,
    Type... namesIn ) [inline]
```

Set the name as a dot-conjoined string of the given inputs.

Each input must not be the empty string or the null pointer.

Template Parameters

<i>Type</i>	Types of the remaining arguments to construct <code>_name</code> .
-------------	--

Parameters

<i>nameIn</i>	First argument to construct <code>_name</code> .
<i>namesIn</i>	Remaining arguments to construct <code>_name</code> .

Definition at line 300 of file `named_item.hh`.

7.1.4.16 size()

```
size_type jeod::NamedItem::size ( ) const [inline]
```

Getter for the length of the name.

Definition at line 250 of file `named_item.hh`.

7.1.4.17 suffix() [1/2]

```
std::string jeod::NamedItem::suffix (
    const std::string & prefix,
    const std::string & name ) [static]
```

Given a prefix and a dot-conjoined name, find the part of the name that follows the prefix.

For names of the form "prefix.suffix", this function returns a pointer to "suffix". The function returns the input name if the name does not start with "prefix.".

Returns

Suffix

Parameters

in	<i>prefix</i>	Prefix
in	<i>name</i>	Name, possibly prefixed

Definition at line 51 of file named_item.cc.

References name.

7.1.4.18 suffix() [2/2]

```
std::string jeod::NamedItem::suffix (
    const std::string & test_name ) const [inline]
```

Given a dot-conjoined test name, find the part of the test name that follows this name, as a prefix.

For names of the form "prefix.suffix", this function returns a pointer to "suffix". The function returns the input name if the name does not start with "prefix.".

Returns

Suffix

Parameters

in	<i>test_name</i>	Test name, possibly prefixed
----	------------------	------------------------------

Definition at line 283 of file named_item.hh.

7.1.4.19 unfreeze_name()

```
void jeod::NamedItem::unfreeze_name ( ) [inline], [protected]
```

Unfreeze the name – i.e., denote that the name is now settable.

This exists solely to parallel [freeze_name\(\)](#).

Definition at line 339 of file `named_item.hh`.

7.1.4.20 `validate_name()` [1/2]

```
void jeod::NamedItem::validate_name (
    const char * file,
    unsigned int line,
    const std::string & variable_type,
    const std::string & variable_name ) [inline]
```

Checks whether a name is trivially invalid, failing if it is.

Parameters

in	<i>file</i>	Usually FILE
in	<i>line</i>	Usually LINE
in	<i>variable_type</i>	Variable description
in	<i>variable_name</i>	Variable name

Definition at line 318 of file `named_item.hh`.

7.1.4.21 `validate_name()` [2/2]

```
void jeod::NamedItem::validate_name (
    const char * file,
    unsigned int line,
    const std::string & variable_value,
    const std::string & variable_type,
    const std::string & variable_name ) [static]
```

Checks whether a name is trivially invalid, failing if it is.

Parameters

in	<i>file</i>	Usually FILE
in	<i>line</i>	Usually LINE
in	<i>variable_value</i>	Value to check
in	<i>variable_type</i>	Variable description
in	<i>variable_name</i>	Variable name

Definition at line 71 of file `named_item.cc`.

References `jeod::NamedItemMessages::invalid_name`.

Referenced by `p()`.

7.1.4.22 `verify_unfrozen_name()`

```
void jeod::NamedItem::verify_unfrozen_name ( ) const
```

Verify that the name is not frozen.

Definition at line 89 of file `named_item.cc`.

References `jeod::NamedItemMessages::frozen_name`, `is_frozen`, and `name`.

7.1.5 Field Documentation

7.1.5.1 `is_frozen`

```
bool jeod::NamedItem::is_frozen [private]
```

Indicates whether the name is frozen.

`trick_units(-)`

Definition at line 353 of file `named_item.hh`.

Referenced by `verify_unfrozen_name()`.

7.1.5.2 `name`

```
std::string jeod::NamedItem::name [private]
```

The item's name.

`trick_units(-)`

Definition at line 348 of file `named_item.hh`.

Referenced by `suffix()`, and `verify_unfrozen_name()`.

The documentation for this class was generated from the following files:

- [named_item.hh](#)
- [named_item.cc](#)
- [named_item_demangle.cc](#)

7.2 jeod::NamedItemMessages Class Reference

Specifies the message IDs used in the named_item model.

```
#include <named_item_messages.hh>
```

Public Member Functions

- [NamedItemMessages](#) ()=delete
- [NamedItemMessages](#) (const [NamedItemMessages](#) &)=delete
- [NamedItemMessages](#) & [operator=](#) (const [NamedItemMessages](#) &)=delete

Static Public Attributes

- static const char * [bad_args](#) = "utils/named_item/" "bad_args"
Error issued when the arguments to named item are invalid.
- static const char * [invalid_name](#) = "utils/named_item/" "invalid_name"
Error issued when a name is the null pointer or an empty string.
- static const char * [frozen_name](#) = "utils/named_item/" "frozen_name"
Error issued when set_name is called with the name marked as frozen.

Private Member Functions

- [JEOD_CLASS_ESTABLISH_FRIENDS2](#) (jeod, [NamedItemMessages](#))

7.2.1 Detailed Description

Specifies the message IDs used in the named_item model.

Definition at line 77 of file named_item_messages.hh.

7.2.2 Constructor & Destructor Documentation

7.2.2.1 NamedItemMessages() [1/2]

```
jeod::NamedItemMessages::NamedItemMessages ( ) [delete]
```

7.2.2.2 NamedItemMessages() [2/2]

```
jeod::NamedItemMessages::NamedItemMessages (
    const NamedItemMessages & ) [delete]
```

7.2.3 Member Function Documentation

7.2.3.1 JEOD_CLASS_ESTABLISH_FRIENDS2()

```
jeod::NamedItemMessages::JEOD_CLASS_ESTABLISH_FRIENDS2 (
    jeod ,
    NamedItemMessages ) [private]
```

7.2.3.2 operator=()

```
NamedItemMessages& jeod::NamedItemMessages::operator= (
    const NamedItemMessages & ) [delete]
```

7.2.4 Field Documentation

7.2.4.1 bad_args

```
char const * jeod::NamedItemMessages::bad_args = "utils/named_item/" "bad_args" [static]
```

Error issued when the arguments to named item are invalid.

trick_units(-)

Definition at line 86 of file named_item_messages.hh.

7.2.4.2 frozen_name

```
char const * jeod::NamedItemMessages::frozen_name = "utils/named_item/" "frozen_name" [static]
```

Error issued when set_name is called with the name marked as frozen.

trick_units(-)

Definition at line 96 of file named_item_messages.hh.

Referenced by jeod::NamedItem::verify_unfrozen_name().

7.2.4.3 invalid_name

```
char const * jeod::NamedItemMessages::invalid_name = "utils/named_item/" "invalid_name" [static]
```

Error issued when a name is the null pointer or an empty string.

trick_units(-)

Definition at line 91 of file named_item_messages.hh.

Referenced by jeod::NamedItem::validate_name().

The documentation for this class was generated from the following files:

- [named_item_messages.hh](#)
- [named_item_messages.cc](#)

Chapter 8

File Documentation

8.1 `named_item.cc` File Reference

Construct the name of a `NamedItem` object by conjoining the passed parameters with a dot.

```
#include <cstdint>
#include <stddef>
#include <cstring>
#include "utils/memory/include/jeod_alloc.hh"
#include "utils/message/include/message_handler.hh"
#include "../include/named_item.hh"
#include "../include/named_item_messages.hh"
```

Namespaces

- [jeod](#)

Namespace `jeod`.

Functions

- `bool operator==(const jeod::NamedItem &lhs, const std::string &rhs)`
Comparison to string.
- `bool operator==(const std::string &lhs, const jeod::NamedItem &rhs)`

8.1.1 Detailed Description

Construct the name of a `NamedItem` object by conjoining the passed parameters with a dot.

8.2 `named_item.hh` File Reference

Define the NamedItem utility class.

```
#include "utils/sim_interface/include/jeod_class.hh"
#include <array>
#include <cstdint>
#include <string>
#include <typeinfo>
#include <utility>
#include <vector>
```

Data Structures

- class `jeod::NamedItem`

Provides a set of static methods for constructing dot-conjoined names.

Namespaces

- `jeod`

Namespace jeod.

Functions

- bool `operator==` (const `jeod::NamedItem` &lhs, const std::string &rhs)
Comparison to string.
- bool `operator==` (const std::string &lhs, const `jeod::NamedItem` &rhs)

8.2.1 Detailed Description

Define the NamedItem utility class.

8.3 `named_item_demangle.cc` File Reference

Demangle a C++ name, isolated from other NamedItem methods because this has the potential to get big and ugly if JEOD is ported to a number of different systems.

```
#include <cstdlib>
#include <string>
#include <typeinfo>
#include "../include/named_item.hh"
#include "../include/named_item_messages.hh"
```

Namespaces

- [jeod](#)

Namespace jeod.

Macros

- `#define __has_include(x) 0`

8.3.1 Detailed Description

Demangle a C++ name, isolated from other NamedItem methods because this has the potential to get big and ugly if JEOD is ported to a number of different systems.

8.4 named_item_messages.cc File Reference

Implement the class NamedItemMessages.

```
#include "utils/message/include/make_message_code.hh"
#include "../include/named_item_messages.hh"
```

Namespaces

- [jeod](#)

Namespace jeod.

Macros

- `#define MAKE_NAMEDITEM_MESSAGE_CODE(id) JEOD_MAKE_MESSAGE_CODE(NamedItemMessages, "utils/named_item/", id)`

8.4.1 Detailed Description

Implement the class NamedItemMessages.

8.4.2 Macro Definition Documentation

8.4.2.1 MAKE_NAMEDITEM_MESSAGE_CODE

```
#define MAKE_NAMEDITEM_MESSAGE_CODE(  
    id ) JEOD_MAKE_MESSAGE_CODE(NamedItemMessages, "utils/named_item/", id)
```

Definition at line 43 of file named_item_messages.cc.

8.5 `named_item_messages.hh` File Reference

Define the class `NamedItemMessages`, the class that specifies the message IDs used in the named item model.

```
#include "utils/sim_interface/include/jeod_class.hh"
```

Data Structures

- class [jeod::NamedItemMessages](#)
Specifies the message IDs used in the `named_item` model.

Namespaces

- [jeod](#)
Namespace `jeod`.

8.5.1 Detailed Description

Define the class `NamedItemMessages`, the class that specifies the message IDs used in the named item model.

Index

- `__has_include`
 - `NamedItem`, [10](#)
 - `~NamedItem`
 - `jeod::NamedItem`, [16](#)
- `bad_args`
 - `jeod::NamedItemMessages`, [25](#)
- `c_str`
 - `jeod::NamedItem`, [16](#)
- `construct_name`
 - `jeod::NamedItem`, [16](#)
- `demangle`
 - `jeod::NamedItem`, [17](#)
- `ends_with`
 - `jeod::NamedItem`, [17](#)
- `freeze_name`
 - `jeod::NamedItem`, [18](#)
- `frozen_name`
 - `jeod::NamedItemMessages`, [25](#)
- `get_is_frozen`
 - `jeod::NamedItem`, [18](#)
- `get_name`
 - `jeod::NamedItem`, [18](#)
- `invalid_name`
 - `jeod::NamedItemMessages`, [25](#)
- `is_frozen`
 - `jeod::NamedItem`, [23](#)
- `jeod`, [11](#)
- `jeod::NamedItem`, [13](#)
 - `~NamedItem`, [16](#)
 - `c_str`, [16](#)
 - `construct_name`, [16](#)
 - `demangle`, [17](#)
 - `ends_with`, [17](#)
 - `freeze_name`, [18](#)
 - `get_is_frozen`, [18](#)
 - `get_name`, [18](#)
 - `is_frozen`, [23](#)
 - `name`, [23](#)
 - `NamedItem`, [15](#), [16](#)
 - `operator=`, [18](#), [19](#)
 - `operator==`, [19](#)
 - `p`, [19](#)
 - `set_name`, [20](#)
 - `size`, [20](#)
 - `size_type`, [15](#)
 - `suffix`, [20](#), [21](#)
 - `unfreeze_name`, [21](#)
 - `validate_name`, [22](#)
 - `verify_unfrozen_name`, [23](#)
- `jeod::NamedItemMessages`, [24](#)
 - `bad_args`, [25](#)
 - `frozen_name`, [25](#)
 - `invalid_name`, [25](#)
 - `JEOD_CLASS_ESTABLISH_FRIENDS2`, [25](#)
 - `NamedItemMessages`, [24](#)
 - `operator=`, [25](#)
- `JEOD_CLASS_ESTABLISH_FRIENDS2`
 - `jeod::NamedItemMessages`, [25](#)
- `MAKE_NAMEDITEM_MESSAGE_CODE`
 - `named_item_messages.cc`, [29](#)
- `Models`, [9](#)
- `name`
 - `jeod::NamedItem`, [23](#)
- `named_item.cc`, [27](#)
- `named_item.hh`, [28](#)
- `named_item_demangle.cc`, [28](#)
- `named_item_messages.cc`, [29](#)
 - `MAKE_NAMEDITEM_MESSAGE_CODE`, [29](#)
- `named_item_messages.hh`, [30](#)
- `NamedItem`, [9](#)
 - `__has_include`, [10](#)
 - `jeod::NamedItem`, [15](#), [16](#)
 - `operator==`, [10](#)
- `NamedItemMessages`
 - `jeod::NamedItemMessages`, [24](#)
- `operator=`
 - `jeod::NamedItem`, [18](#), [19](#)
 - `jeod::NamedItemMessages`, [25](#)
- `operator==`
 - `jeod::NamedItem`, [19](#)
 - `NamedItem`, [10](#)
- `p`
 - `jeod::NamedItem`, [19](#)
- `set_name`
 - `jeod::NamedItem`, [20](#)
- `size`
 - `jeod::NamedItem`, [20](#)
- `size_type`
 - `jeod::NamedItem`, [15](#)

suffix

jeod::NamedItem, [20](#), [21](#)

unfreeze_name

jeod::NamedItem, [21](#)

Utils, [9](#)

validate_name

jeod::NamedItem, [22](#)

verify_unfrozen_name

jeod::NamedItem, [23](#)