Multi-Spacecraft Concept and Autonomy Tool (MuSCAT) Version 2

Dr. Saptarshi Bandyopadhyay,
Jet Propulsion Laboratory, California Institute of Technology
Email: saptarshi.bandyopadhyay@jpl.nasa.gov

April 14, 2025

Contents

Chapter 1

Introduction

Multi-Spacecraft Concept and Autonomy Tool (MuSCAT) open-source simulation software offers an integrated platform for conducting low-fidelity simulations of single/multiple cruising/orbiting spacecraft mission concepts and test of autonomy algorithms. MuSCAT encompasses various spacecraft subsystems such as (i) Navigation, (ii) Attitude Determination and Control, (iii) Power Management, (iv) Data Handling, (v) Communication (including direct-to-Earth and inter-spacecraft), and (vi) Scientific Instruments. It provides mission designers with a means to quantitatively verify if the mission concept meets level-1 science functional requirements.

[1] provides a detailed description of the software architecture and use cases of MuSCAT.



Figure 1.1: Diagram showing all the classes that are inside MuSCAT. Classes in gray are currently under development.



Figure 1.2: Block diagram that shows the different components inside the MuSCAT simulator. The blocks in gray are currently under development.

1.1 Coding Conventions

- Items marked with # are not initialized, and computed internally
- In naming functions,
  `update` is used when the function is called often (every time step),
  `compute` is used when it is called rarely (or only once).
- All functions are prefixed with `func_`, and colored green.
- All classes within the physics-based simulation represent real objects like Solar System or small body, and are prefixed with `True_`, and those that belong to the spacecraft are prefixed with `True_SC_`.
- All classes within the autonomous flight software that only exist within the spacecraft's onboard computer are prefixed with `Software_SC_`.

1.2 Coding Tips for Multi-Mission Usage

- Within each class, use `data` to track all mission-specific variables.
- If a component uses different power in different spacecraft modes, use `data.instantaneous_power_consumed_per_SC_mode` to track that.

1.3 Acknowledgment

This research was carried out at the Jet Propulsion Laboratory, California Institute of Technology, under a contract with the National Aeronautics and Space Administration. Government sponsorship acknowledged.

The authors also thank the following people for their invaluable time and technical expertise in constructing this code base:

- Thibault Wartel from Institut supérieur de l'aéronautique et de l'espace (ISAE-SUPAERO), France
- Cesc Casanovas Gasso from International Space University, France
- Ian Aenishanslin from Institut polytechnique des sciences avancées (IPSA), France
- Carmine Buonagura from Politecnico di Milano, Italy
- Chris Agia from Stanford, USA
- Kazu Echigo from University of Washington, USA
- Minduli C Wijayatunga from University of Auckland, New Zealand

Chapter 2

Implementing Custom Missions in MuSCAT

2.1 Overview of Mission Implementation

The Multi-Spacecraft Concept and Autonomy Tool (MuSCAT) provides a flexible framework for simulating spacecraft missions. This chapter explains in detail how to implement your own custom mission using MuSCAT's modular architecture.

At its core, MuSCAT follows an object-oriented approach where various spacecraft subsystems, environmental elements, and software components are instantiated as objects and connected together to form a complete mission simulation. The central data structure that ties everything together is the `mission` structure, which serves as the global state for the entire simulation.

2.2 Understanding the Mission Structure

The `mission` structure contains all the objects and parameters that define your mission:

- **mission.name**: Name identifier for the mission
- **mission.num_SC**: Number of spacecraft in the mission
- **mission.num_target**: Number of target bodies (e.g., asteroids, planets)
- **mission.frame**: Reference frame type ('Absolute', 'Relative', or 'Combined')
- **mission.true_time**: Time-related parameters and functions
- **mission.storage**: Data storage configuration
- **mission.true_stars**: Star catalog for attitude determination
- **mission.true_solar_system**: Solar system bodies
- **mission.true_target**: Target bodies (e.g., asteroids)
- **mission.true_ground_station**: Ground station parameters
- **mission.true_SC**: Array of spacecraft objects

Each spacecraft contains numerous subsystems, all properly organized within the structure:

- **mission.true_SC{i}.true_SC_body**: Physical properties and geometry
- **mission.true_SC{i}.true_SC_navigation**: Position, velocity, and orbital parameters
- **mission.true_SC{i}.true_SC_adc**: Attitude determination and control
- **mission.true_SC{i}.true_SC_power**: Power subsystem
- **mission.true_SC{i}.true_SC_data_handling**: Data management
- **mission.true_SC{i}.true_SC_[hardware]**: Various hardware components
- **mission.true_SC{i}.software_SC_[software]**: Flight software components

2.3 MuSCAT Code Organization

Understanding the organization of MuSCAT's codebase is essential for effectively implementing and customizing missions. The codebase follows a modular structure that separates different aspects of spacecraft simulation into distinct directories, each with a specific purpose.

2.3.1 Top-Level Directory Structure

The MuSCAT codebase is organized into several key directories:

- **/Mission/**: Contains mission definition files that serve as the entry points for simulations
- **/Main/**: Contains the main simulation engine that executes the time steps
- **/True_SC/**: Houses the core spacecraft system classes (body, navigation, power, etc.)
- **/True_Sensors_Actuators/**: Contains sensor and actuator hardware implementations
- **/True_Environment/**: Defines environmental models (solar system, stars, etc.)
- **/Software_SC/**: Implements flight software components
- **/Supporting_Functions/**: Contains utility functions used throughout the codebase
- **/Documentation/**: Contains detailed documentation files
- **/Output/**: Default location for simulation results and visualizations

2.3.2 Mission Files

The `/Mission/` directory is where users should focus most of their attention when creating new simulations. Each mission file (e.g., `Mission_DART.m`) follows the same general structure:

1. Configure mission parameters (name, number of spacecraft, etc.)
2. Set up time and storage parameters
3. Configure environmental elements (stars, solar system, targets)

4. Set up ground stations
5. For each spacecraft:
   - Define physical properties
   - Set initial position and attitude
   - Configure hardware components
   - Set up flight software
6. Perform final initialization
7. Execute the simulation
8. Generate and save results

These mission files serve as the "glue" that brings together all the individual components into a cohesive simulation.

2.3.3 True_SC: Core Spacecraft Systems

The `/True_SC/` directory contains the fundamental spacecraft subsystem classes:

- **True_SC_Body.m**: Defines the physical properties of the spacecraft, including mass, inertia, and shape
- **True_SC_Navigation.m**: Handles position and velocity dynamics
- **True_SC_ADC.m**: Manages attitude dynamics and control
- **True_SC_Power.m**: Tracks power generation, consumption, and distribution
- **True_SC_Data_Handling.m**: Manages onboard data flows

These core classes form the backbone of each spacecraft model. They work together to provide a complete representation of the physical spacecraft and its core functionalities.

2.3.4 Class Interfaces and Update Functions

All MuSCAT classes follow a consistent interface pattern that enables the simulation loop to update each component appropriately. Understanding this pattern is key to extending MuSCAT with custom components.

2.3.4.1 Main Update Functions

Each class in MuSCAT has a corresponding `func_main_[className]` function that the simulation loop calls to update that component's state. For example:

- `func_main_true_SC_navigation`: Updates spacecraft position and velocity
- `func_main_true_SC_adc`: Updates spacecraft attitude
- `func_main_true_SC_star_tracker`: Updates star tracker measurements

- `func_main_software_SC_executive`: Executes decision-making logic

These functions follow a consistent pattern:

```
function func_main_[className](obj, mission, i_SC, [optional parameters])
    % Update the object's state based on current mission state
    % obj: The object instance being updated
    % mission: The global mission structure
    % i_SC: The spacecraft index (for spacecraft components)
    % [optional parameters]: Component-specific parameters

    % Update code specific to this component
    % ...

    % Update stored data if needed
    func_store_data(obj, mission);
end
```

2.3.4.2 Extension Without Modification

It's important to note that users should **never modify** these core update functions directly. Instead, MuSCAT provides several approaches for customization:

1. **Mode Selectors**: Most classes have a `mode_[className]_selector` parameter that can be set to choose different behavioral modes. For example, setting `mode_true_SC_navigation_dynamics_sele` `= 'Absolute Dynamics'` selects the absolute dynamics mode.
2. **Mission-Specific Extensions**: Flight software classes are designed to be extended with mission-specific implementations. For instance, the `Software_SC_Executive` class allows you to add a new function named `func_software_SC_executive_YourMission` that implements your custom decision logic.
3. **Custom Component Creation**: You can create entirely new component classes in your mission directory, inheriting from existing parent classes where appropriate.

2.3.4.3 Custom Function Implementation

When implementing custom functions for flight software, follow this pattern:

```
function obj = func_software_SC_[component]_YourMission(obj, mission, i_SC)
    % Your custom implementation
    % ...

    % Return the updated object
end
```

By strictly adhering to these patterns, you ensure that your custom components will integrate seamlessly with the main simulation loop.

2.3.5 True_Sensors_Actuators: Hardware Components

The `/True_Sensors_Actuators/` directory contains all the individual hardware components that can be added to a spacecraft:

- **Sensors**: Star trackers, sun sensors, IMUs, cameras, etc.
- **Actuators**: Reaction wheels, thrusters, etc.
- **Communication**: Radio antennas, communication links, etc.
- **Power**: Solar panels, batteries, etc.
- **Data**: Onboard computers, memory, etc.

Each hardware component is represented by a MATLAB class that inherits from a common parent class. This object-oriented approach allows for easy extension with new components and consistent interfaces across all hardware.

The number of each hardware component is specified in the mission file and directly influences how the simulation behaves. For example, specifying 6 sun sensors will result in 6 separate hardware objects being created and included in the simulation loop. Each component will be updated during the appropriate part of the simulation cycle.

2.3.6 Software_SC: Flight Software

The `/Software_SC/` directory contains the flight software classes that control the spacecraft's autonomous behavior:

- **Software_SC_Executive.m**: The main decision-making component that determines spacecraft operating modes
- **Software_SC_Estimate_Attitude.m**: Algorithms for estimating spacecraft attitude
- **Software_SC_Estimate_Orbit.m**: Algorithms for estimating spacecraft orbit
- **Software_SC_Control_Attitude.m**: Algorithms for controlling spacecraft attitude
- **Software_SC_Control_Orbit.m**: Algorithms for controlling spacecraft orbit
- **Software_SC_Communication.m**: Logic for managing communications
- **Software_SC_Power.m**: Logic for managing power
- **Software_SC_Data_Handling.m**: Logic for managing data

These software components interact with the hardware models and implement the autonomous behavior of the spacecraft. They are executed at each appropriate time step in the simulation loop.

2.3.7 True_Environment: Environmental Models

The `/True_Environment/` directory contains models of the space environment:

- **True_Solar_System.m**: Models of solar system bodies
- **True_Stars.m**: Star catalog for attitude determination
- **True_Target.m**: Models of mission targets (e.g., asteroids)
- **True_Ground_Station.m**: Earth-based ground stations
- **True_SRP.m**: Solar radiation pressure model
- **True_Gravity_Gradient.m**: Gravity gradient torque model

These environmental models provide the context in which the spacecraft operates and influence various aspects of the simulation, from orbital dynamics to sensor measurements.

2.3.8 Main Simulation Engine

The `/Main/` directory contains the main simulation engine in `main_v3.m`. This script implements the time-stepping algorithm that advances the simulation state:

1. Update simulation time and date
2. Update solar system and target bodies
3. For each spacecraft:
    - Update environmental effects (solar radiation pressure, gravity gradient)
    - Update spacecraft body, position, and velocity
    - Update onboard clock and computer systems
    - Execute the Executive software to determine operating mode
    - Update all sensors, actuators, and subsystems
    - Run the attitude dynamics loop at a higher frequency
    - Update communication systems
    - Update power and data handling systems
4. Update ground station systems
5. Save data and update visualizations

The main simulation engine is responsible for calling all the appropriate update functions for each component in the correct order, ensuring that dependencies between components are properly handled.

2.4 Step-by-Step Guide to Implementing a Mission

2.4.1 Customization Best Practices

When implementing your own mission in MuSCAT, it's critical to follow these best practices to ensure maintainability and compatibility with future updates:

1. **Never Modify Core Files**: The core MuSCAT files (`/True_SC/`, `/True_Sensors_Actuators/`, `/Main/`, etc.) should never be directly edited. These files contain the fundamental simulation engine and component models that are designed to be used as-is.

2. **Create Mission-Specific Directories**: For each new mission, create a dedicated directory in `/Mission/` (e.g., `/Mission/YourMission/`) to contain all mission-specific files.

3. **Use Extension Mechanisms**: MuSCAT provides specific extension points (via mode selectors and mission-specific functions) that allow you to customize behavior without modifying core files.

4. **Document Custom Components**: When creating mission-specific extensions, thoroughly document their purpose, interfaces, and requirements to facilitate future maintenance.

5. **Follow Naming Conventions**: Use consistent naming patterns (e.g., `func_software_SC_executive_YourMission`) to ensure that your custom functions are correctly discovered and invoked by the simulation engine.

By adhering to these practices, you ensure that:

- Your mission can be easily upgraded when new MuSCAT versions are released
- You can transfer your custom components between different MuSCAT installations
- Collaboration with other users is simplified through clear separation of core and custom code
- Debugging is easier since modifications are isolated to specific mission files

2.4.2 Creating a New Mission File

1. Navigate to the `/Mission` directory in the MuSCAT codebase

2. Copy `Mission_DART.m` to a new file with your mission name (e.g., `Mission_YourMission.m`)

3. Open the new file and begin customizing according to your mission requirements

Each mission file follows a structured format, with initialization of different subsystems organized into sections. Let's examine each section.

2.4.3 Basic Mission Configuration

The first step is to define basic mission parameters:

```
%% Mission Definition
mission = [];
mission.name = 'YourMission';       % Name of the Mission
mission.num_SC = 1;                 % Number of Spacecraft
mission.num_target = 1;             % Number of Target bodies
mission.frame = 'Absolute';         % Frame type: 'Absolute', 'Relative', or 'Combined'
mission.flag_stop_sim = 0;          % Boolean flag to stop simulation if needed
```

2.4.4 Time and Storage Configuration

The time configuration is a critical aspect of MuSCAT as it defines the temporal resolution and duration of your simulation. MuSCAT employs a dual-loop architecture to efficiently handle different timescales for spacecraft dynamics:

```
%% Time Configuration
init_data = [];
init_data.t_initial = 0;                                        % [sec] Initial time
init_data.t_final = 10000;                                      % [sec] Final time
init_data.time_step = 5;                                        % [sec] Simulation time step
init_data.t_initial_date_string = '01-JAN-2025 00:00:00';  % Starting date
init_data.time_step_attitude = 0.1;                      % [sec] Attitude dynamics time step
mission.true_time = True_Time(init_data);
```

2.4.4.1 Understanding the Dual-Loop Architecture

MuSCAT's main simulation engine in `main_v3.m` implements two nested time loops:

1. **Outer Loop (Orbital Dynamics)**: Runs at the slower rate specified by `time_step` (typically 5 seconds). This loop handles orbital dynamics, subsystem operations, communications, power systems, and other slower-changing phenomena.

2. **Inner Loop (Attitude Dynamics)**: Runs at the faster rate specified by `time_step_attitude` (typically 0.1 seconds). This nested loop simulates attitude dynamics and control, which require higher temporal resolution due to the faster rotational motion of spacecraft.

This dual-loop architecture is essential because attitude dynamics typically evolve much more rapidly than orbital dynamics. For example, a spacecraft might complete a full rotation in minutes while its orbit might take hours or days to complete. Using a single timestep would either:

- Be too slow for accurate attitude simulation (if using the orbital timestep)
- Be computationally prohibitive for long-duration missions (if using the attitude timestep for everything)

In the `main_v3.m` file, you'll see this implemented as:

```
%% Time Loop (Outer Loop)
for k = 1:1:mission.true_time.num_time_steps
    % Update Time, Date, Storage, Solar System, etc.

    %% Attitude Dynamics Loop (Inner Loop)
    for k_attitude = 1:1:mission.true_time.num_time_steps_attitude
        % Update attitude, sensors, actuators, etc.
    end

    % Continue with other subsystems...
end
```

2.4.4.2 Storage Configuration

Similarly, storage configuration determines how frequently simulation data is saved:

```
%% Storage Configuration
init_data = [];
init_data.time_step_storage = 1;                                % Data storage interval
init_data.time_step_storage_attitude = 0.5;                     % Attitude data storage interva
init_data.flag_visualize_SC_attitude_orbit_during_sim = 0; % Don't show attitude during s
init_data.flag_realtime_plotting = 0;                           % Show mission data during sim
init_data.flag_save_plots = 1;                                  % Save plots to disk
init_data.flag_save_video = 0;                                  % Save animation to video
mission.storage = Storage(init_data, mission);
```

The storage configuration follows the same dual-timescale approach as the main simulation:

- `time_step_storage`: How often to save orbital and subsystem data (in seconds)
- `time_step_storage_attitude`: How often to save attitude data (in seconds)

Setting appropriate storage intervals is crucial for managing memory usage. Setting them too small can lead to memory issues with large simulations, while setting them too large might miss important transient behaviors.

The visualization flags control real-time display and post-simulation outputs:

- `flag_visualize_SC_attitude_orbit_during_sim`: Toggles 3D visualization during simulation
- `flag_realtime_plotting`: Enables data plots during simulation (can slow performance)
- `flag_save_plots`: Saves figures to disk after simulation completes
- `flag_save_video`: Records video of 3D visualization (memory-intensive)

2.4.5 Environment Configuration

Configure the stars catalog, solar system bodies, and target bodies:

```
%% Star Catalog Configuration
mission.true_stars = True_Stars(mission);
mission.true_stars.maximum_magnitude = 10;  % Maximum star magnitude to include

%% Solar System Configuration
init_data = [];
init_data.SS_body_names = ["Sun", "Earth", "Mars"];  % Relevant solar system bodies
mission.true_solar_system = True_Solar_System(init_data, mission);

%% Target Body Configuration
for i_target = 1:1:mission.num_target
    init_data = [];
    init_data.target_name = 'Bennu';        % Target asteroid name
    mission.true_target{i_target} = True_Target_SPICE(init_data, mission);
end
```

2.4.6 Ground Station Configuration

Ground stations are essential elements of spacecraft missions, providing the Earth-based communications infrastructure for telemetry, tracking, and command. In MuSCAT, ground stations are modeled with realistic visibility constraints, antenna properties, and communication capabilities.

2.4.6.1 Ground Station Fundamentals

The ground station model in MuSCAT accounts for:

- **Earth Rotation**: Ground stations rotate with Earth, affecting visibility periods
- **Antenna Characteristics**: Gain patterns, pointing capabilities, and frequency-dependent properties
- **Link Budget Calculations**: Realistic modeling of signal strength, noise, and data rate capabilities
- **Visibility Constraints**: Line-of-sight calculations based on Earth's position and rotation

To configure a ground station, first specify the number of antennas:

```
%% Ground Station Configuration
init_data = [];
init_data.num_GS_radio_antenna = 1;  % Number of ground station antennas
mission.true_ground_station = True_Ground_Station(init_data, mission);
```

Then, configure each antenna with appropriate communication parameters:

```
%% Ground Station Radio Antenna Configuration
for i_HW = 1:1:mission.true_ground_station.num_GS_radio_antenna
    init_data = [];

    % Basic configuration
```

```
    init_data.antenna_type = 'High Gain';
    init_data.mode_true_GS_radio_antenna_selector = 'RX';  % Receive mode

    % Link budget parameters
    init_data.antenna_gain = 90;            % [dB] Very high gain (DSN-like)
    init_data.noise_temperature = 100;      % [K] System noise temperature
    init_data.beamwidth = 0.1;              % [MHz] Receiver bandwidth
    init_data.energy_bit_required = 4.2;    % [dB] Required Eb/N0
    init_data.line_loss = 0;                % [dB] Transmission line losses
    init_data.coding_gain = 7.3;            % [dB] Error correction coding gain

    % Create the antenna object
    mission.true_GS_radio_antenna{i_HW} = True_GS_Radio_Antenna(init_data, mission, i_HW)
end
```

2.4.6.2 Ground Station Parameters

The key parameters affecting ground station performance include:

- **Antenna Gain**: Higher gain provides better signal strength but narrower beamwidth requiring more precise pointing. The value of 90 dB represents a large Deep Space Network (DSN) class antenna.
- **Noise Temperature**: Lower values (in Kelvin) improve signal-to-noise ratio. Typical values range from 20K (very cold, space-pointing receivers) to 290K (room temperature).
- **Beamwidth**: The receiver's frequency bandwidth in MHz. Narrower bandwidths reduce noise but limit data rate.
- **Eb/N0 Requirement**: Energy per bit to noise density ratio required for reliable communication. Higher values increase reliability but reduce achievable data rate.
- **Coding Gain**: The improvement in effective signal-to-noise ratio achieved through error correction coding.

2.4.6.3 Simulation Impact

During simulation, the ground station model:

1. Calculates its position based on Earth's rotation
2. Determines visibility to each spacecraft based on line-of-sight
3. Computes achievable data rates based on distance, antenna parameters, and pointing
4. Transfers data between spacecraft and ground when links are established

The ground station configuration directly affects communication windows and data throughput, which in turn influence mission planning, data collection strategies, and onboard storage requirements.

2.4.7 Spacecraft Configuration

2.4.7.1 Spacecraft Physical Properties

Configure the physical properties of each spacecraft, including shape, mass, and moment of inertia:

```
%% Spacecraft Body Configuration
i_SC = 1;  % First spacecraft

init_data = [];
init_data.i_SC = i_SC;

% Body shape model
init_data.shape_model{1} = [];
init_data.shape_model{1}.Vertices = [0 0 0;
    0.3 0 0;
    0.3 0 0.1;
    0 0 0.1;
    0 0.2 0;
    0.3 0.2 0;
    0.3 0.2 0.1;
    0 0.2 0.1]; % [m]
init_data.shape_model{1}.Faces = [1 2 3;
    1 4 3;
    2 3 7;
    2 6 7;
    3 4 8;
    3 7 8;
    1 4 8;
    1 5 8;
    1 2 6;
    1 5 6;
    5 6 7;
    5 8 7];

init_data.shape_model{1}.Face_reflectance_factor = 0.6*ones(size(init_data.shape_model{1}
init_data.shape_model{1}.type = 'cuboid';
init_data.shape_model{1}.mass = 11; % [kg] Dry mass

% Additional mass components
init_data.mass.supplement{1}.mass = 0.5; % [kg]
init_data.mass.supplement{1}.location = [0.1 0 0]; % [m]
init_data.mass.supplement{1}.MI_over_m = zeros(3,3); % [m^2]

init_data.mode_COM_selector = 'update';  % Compute Center of Mass dynamically
init_data.mode_MI_selector = 'update';   % Compute Moment of Inertia dynamically
```

2.4.7.2 Spacecraft Hardware Complement

When designing a spacecraft in MuSCAT, the hardware complement defines what components are present on the spacecraft and in what quantities. This configuration directly impacts how the simulation behaves by determining:

- What hardware-specific loops will be executed during simulation
- How many instances of each component will be created and updated
- What capabilities the spacecraft will have during the mission
- The physical and performance characteristics of the spacecraft

The hardware complement is specified through the `num_hardware_exists` structure:

```
% Define hardware complement
init_data.num_hardware_exists.num_onboard_clock = 1;      % Timing system
init_data.num_hardware_exists.num_camera = 1;             % Imaging system
init_data.num_hardware_exists.num_solar_panel = 3;        % Power generation
init_data.num_hardware_exists.num_battery = 2;            % Energy storage
init_data.num_hardware_exists.num_onboard_memory = 2;     % Data storage
init_data.num_hardware_exists.num_sun_sensor = 6;         % Sun direction sensing
init_data.num_hardware_exists.num_star_tracker = 3;       % Star-based attitude determina
init_data.num_hardware_exists.num_imu = 1;                % Inertial measurement
init_data.num_hardware_exists.num_micro_thruster = 12;    % Small attitude control thrust
init_data.num_hardware_exists.num_chemical_thruster = 1;  % Main propulsion
init_data.num_hardware_exists.num_reaction_wheel = 3;     % Momentum exchange devices
init_data.num_hardware_exists.num_communication_link = 2; % Data links (up/downlink)
init_data.num_hardware_exists.num_radio_antenna = 1;      % Communication hardware
init_data.num_hardware_exists.num_fuel_tank = 1;          % Propellant storage
init_data.num_hardware_exists.num_onboard_computer = 2;   % Computing resources
```

2.4.7.2.1 Simulation Impact Each number specified here has direct consequences for the simulation:

1. **Loop Execution**: In `main_v3.m`, the simulation iterates through each hardware type according to the specified count. For example, with 6 sun sensors:

   ```
   for i_HW = 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_sun_se
       func_main_true_SC_sun_sensor(mission.true_SC{i_SC}.true_SC_sun_sensor{i_HW},
   end
   ```

2. **Resource Consumption**: Each hardware component consumes power and generates data, affecting the overall spacecraft power balance and data handling requirements.
3. **Redundancy and Failure Tolerance**: Multiple instances of critical components (e.g., computers, batteries) provide redundancy for fault tolerance.

4. **Capability Coverage**: The placement and orientation of sensors (like sun sensors or star trackers) determine the spacecraft's ability to determine attitude in different orientations.

5. **Control Authority**: The number and arrangement of reaction wheels and thrusters determine the spacecraft's control capabilities.

2.4.7.2.2 Selecting Appropriate Hardware When designing your mission, consider these questions when selecting hardware:

- What sensing capabilities are required for the mission objectives?
- What control authority is needed for attitude and orbital maneuvers?
- How much power generation and storage is needed?
- What data rates and storage capacities are required?
- What level of redundancy is appropriate for mission criticality?

After defining the hardware complement, you must create a `True_SC_Body` object that will encapsulate this information:

```
mission.true_SC{i_SC}.true_SC_body = True_SC_Body(init_data, mission);
```

This object becomes the foundation for all subsequent hardware initialization and will be used to calculate mass properties and other physical characteristics of the spacecraft.

2.4.7.3 Initial Position and Attitude

The initial state of the spacecraft—its position, velocity, and attitude—defines the starting point of the simulation and has profound impacts on mission trajectory, operations, and results. In MuSCAT, there are multiple methods to specify these initial conditions, each serving different purposes.

2.4.7.3.1 Position and Velocity Initialization There are three primary methods to specify the initial position and velocity of a spacecraft:

1. **SPICE-Based Initialization**: Using NASA's SPICE toolkit for high-fidelity ephemeris data
2. **Direct Specification**: Explicitly defining position and velocity vectors
3. **Orbital Elements**: Specifying Keplerian orbital elements

The SPICE-based method is shown below and is preferred for missions with predefined trajectories:

```
%% Initialize Spacecraft's Position and Velocity
init_data = [];
init_data.spice_filename = '../../MuSCAT_Supporting_Files/SC_data/YourMission/trajectory.
cspice_furnsh(init_data.spice_filename)

init_data.spice_name = '-110'; % SPICE ID for the spacecraft
init_data.SC_pos_vel = cspice_spkezr(init_data.spice_name, mission.true_time.date,
                                    'J2000', 'NONE', 'SUN');
init_data.position = init_data.SC_pos_vel(1:3)'; % [km]
init_data.velocity = init_data.SC_pos_vel(4:6)'; % [km/sec]
```

Alternatively, you can directly specify position and velocity:

```
init_data.position = [149598023, 0, 0]; % [km] Position in Sun-centered frame
init_data.velocity = [0, 29.78, 0];     % [km/sec] Velocity in Sun-centered frame
```

The dynamics mode selection determines how the position and velocity will evolve during simulation:

```
init_data.mode_true_SC_navigation_dynamics_selector = 'Absolute Dynamics';
```

MuSCAT currently supports two navigation dynamics modes:

- **Absolute Dynamics**: Full orbital dynamics with gravitational forces
- **SPICE**: Position/velocity updated directly from SPICE kernels

After configuration, create the navigation object:

```
mission.true_SC{i_SC}.true_SC_navigation = True_SC_Navigation(init_data, mission);
```

2.4.7.3.2 Attitude Initialization Spacecraft attitude defines the orientation in three-dimensional space. In MuSCAT, attitudes can be specified using various representations:

1. **Quaternions**: A four-parameter representation avoiding singularities
2. **Modified Rodrigues Parameters (MRP)**: A three-parameter representation
3. **Euler Angles**: Classical roll, pitch, yaw angles (not singularity-free)
4. **Direction Cosine Matrix (DCM)**: 3×3 rotation matrix

The example below uses Modified Rodrigues Parameters, then converts to quaternions:

```
%% Initialize Spacecraft's Attitude
init_data = [];
% Method 1: Starting with MRP
init_data.SC_MRP_init = [0.1 0.2 0.3]; % Modified Rodrigues Parameters
init_data.SC_omega_init = [0 0 0.001]; % [rad/sec] Angular velocity

% Convert MRP to quaternion
init_data.SC_e_init = init_data.SC_MRP_init/norm(init_data.SC_MRP_init);
init_data.SC_Phi_init = 4*atand(init_data.SC_MRP_init(1)/init_data.SC_e_init(1)); % [deg]
init_data.SC_beta_v_init = init_data.SC_e_init * sind(init_data.SC_Phi_init/2);
init_data.SC_beta_4_init = cosd(init_data.SC_Phi_init/2);

init_data.attitude = [init_data.SC_beta_v_init, init_data.SC_beta_4_init]; % [quaternion]
init_data.attitude = func_quaternion_properize(init_data.attitude); % [quaternion] proper
init_data.angular_velocity = init_data.SC_omega_init;
```

Alternatively, you can specify quaternions directly:

```
% Method 2: Direct quaternion specification
init_data.attitude = [0, 0, 0, 1]; % Identity quaternion (no rotation)
init_data.angular_velocity = [0, 0, 0]; % [rad/sec] No initial rotation
```

The attitude dynamics mode determines how the orientation will evolve:

```
init_data.mode_true_SC_attitude_dynamics_selector = 'Rigid';
```

Currently, MuSCAT only supports the 'Rigid' mode, which implements standard rigid body dynamics. After configuration, create the attitude dynamics and control object:

```
mission.true_SC{i_SC}.true_SC_adc = True_SC_ADC(init_data, mission);
```

2.4.7.3.3 Simulation Impact The initial state significantly influences the simulation:

- **Orbital Period and Evolution**: Initial position and velocity determine the spacecraft's orbit, affecting visibility of ground stations, targets, and available sunlight
- **Pointing Capabilities**: Initial attitude affects which sensors can view their targets and which solar panels receive sunlight
- **Thermal Conditions**: Orientation relative to the Sun impacts thermal conditions
- **Communication Opportunities**: Position influences when communication with Earth is possible
- **Scientific Observations**: Initial state determines when observation targets are visible

When implementing your mission, carefully consider the initial state based on mission objectives, launch conditions, and operational requirements.

2.4.8 Configuring Spacecraft Subsystems

Configure various spacecraft subsystems such as power, data handling, communications, and sensors:

2.4.8.1 Power Subsystem

```
%% Initialize Spacecraft's Power
init_data = [];
init_data.power_loss_rate = 0.05; % [float] 5% power loss in distribution and conversion
mission.true_SC{i_SC}.true_SC_power = True_SC_Power(init_data, mission);

%% Initialize Spacecraft's Solar Panels
for i_HW = 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_solar_panel
    init_data = [];
    init_data.instantaneous_power_consumed = 0.01; % [W]
    init_data.instantaneous_data_rate_generated = (1e-3)*8; % [kbps]

    % Define solar panel geometry
    init_data.shape_model = [];
    init_data.shape_model.Vertices = [0 0 0; 0.2 0 0; 0.2 0 -0.6; 0 0 -0.6];
```

```
    init_data.shape_model.Faces = [1 2 3; 1 4 3];
    init_data.shape_model.Face_reflectance_factor_solar_cell_side = [0.01; 0.01];
    init_data.shape_model.Face_reflectance_factor_opposite_side = [0.5; 0.5];
    init_data.shape_model.Face_orientation_solar_cell_side = [0 -1 0];
    init_data.shape_model.type = 'cuboid';

    init_data.mass = 0.24; % [kg]
    init_data.type = 'passive_deployed';
    init_data.packing_fraction = 0.74; % Packing fraction of solar cells
    init_data.solar_cell_efficiency = 0.28; % Efficiency of each solar cell

    mission.true_SC{i_SC}.true_SC_solar_panel{i_HW} = True_SC_Solar_Panel(init_data, miss
end

%% Initialize Spacecraft's Battery
for i_HW = 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_battery
    init_data = [];
    init_data.maximum_capacity = 40; % [W hr]
    init_data.charging_efficiency = 0.96; % [float <= 1]
    init_data.discharging_efficiency = 0.96; % [float <= 1]
    init_data.instantaneous_power_consumed = 1e-4; % [W]
    init_data.instantaneous_data_rate_generated = (1e-3)*8; % [kbps]

    mission.true_SC{i_SC}.true_SC_battery{i_HW} = True_SC_Battery(init_data, mission, i_S
end
```

2.4.8.2 Data Handling Subsystem

```
%% Initialize Spacecraft's Data Handling
init_data = [];
init_data.mode_true_SC_data_handling_selector = 'Generic';
mission.true_SC{i_SC}.true_SC_data_handling = True_SC_Data_Handling(init_data, mission);

%% Initialize Spacecraft's Onboard Memory
for i_HW = 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_onboard_memory
    init_data = [];
    init_data.maximum_capacity = 1e6; % [kb]
    init_data.instantaneous_power_consumed = 1; % [W]
    init_data.instantaneous_data_rate_generated = (1e-3)*8; % [kbps]

    mission.true_SC{i_SC}.true_SC_onboard_memory{i_HW} = True_SC_Onboard_Memory(init_data
end
```

2.4.8.3 Communication Subsystem

```
%% Initialize Spacecraft's Radio Antenna
for i_HW = 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_radio_antenna
    init_data = [];
    init_data.location = [0 1 0];   % [unit vector] antenna physical axis in Body frame
```

```
    init_data.orientation = [0 0 1]; % [unit vector] antenna pointing direction

    % Antenna parameters
    init_data.antenna_type = "dipole";
    init_data.antenna_gain = 28.1;          % [dB]
    init_data.antenna_frequency = 8450;     % [MHz]
    init_data.tx_line_loss = 1;             % [dB]
    init_data.noise_temperature = 100;      % [K]
    init_data.maximum_data_rate = 1000;     % [kbps]
    init_data.TX_power_consumed = 50;       % [W]
    init_data.RX_power_consumed = 25;       % [W]

    mission.true_SC{i_SC}.true_SC_radio_antenna{i_HW} = True_SC_Radio_Antenna(init_data,
end

%% Spacecraft Communication Links Configuration
for i_HW = 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_communication_l
    init_data = [];

    if i_HW == 1
        % Downlink: Spacecraft to Earth
        init_data.TX_spacecraft = i_SC;
        init_data.TX_spacecraft_Radio_HW = 1;
        init_data.RX_spacecraft = 0;        % Ground Station
        init_data.RX_spacecraft_Radio_HW = 1;
        init_data.given_data_rate = 360;    % [kbps]
    else
        % Uplink: Earth to Spacecraft
        init_data.TX_spacecraft = 0;        % Ground Station
        init_data.TX_spacecraft_Radio_HW = 1;
        init_data.RX_spacecraft = i_SC;
        init_data.RX_spacecraft_Radio_HW = 1;
        init_data.given_data_rate = 0;      % [kbps]
    end

    mission.true_SC{i_SC}.true_SC_communication_link{i_HW} = True_SC_Communication_Link(i
end
```

2.4.8.4 Sensors and Actuators

Configure sensors (cameras, star trackers, IMUs) and actuators (thrusters, reaction wheels):

```
%% Initialize Spacecraft's Cameras
for i_HW = 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_camera
    init_data = [];
    init_data.instantaneous_power_consumed = 10; % [W]
    init_data.mode_true_SC_camera_selector = 'Simple';
    init_data.measurement_wait_time = 60; % [sec]
```

```
    init_data.location = [0.3 0.1 0.05]; % [m]
    init_data.orientation = [1 0 0]; % [unit vector]
    init_data.orientation_up = [0 0 1]; % [unit vector]

    init_data.resolution = [512 512];  % [x y] pixel
    init_data.field_of_view = 10; % [deg]
    init_data.flag_show_camera_plot = 0;
    init_data.flag_show_stars = 1;

    mission.true_SC{i_SC}.true_SC_camera{i_HW} = True_SC_Camera(init_data, mission, i_SC,
end

%% Initialize Spacecraft's Star Trackers
for i_HW = 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_star_tracker
    init_data = [];
    init_data.instantaneous_power_consumed = 1.5; % [W]
    init_data.mode_true_SC_star_tracker_selector = 'Simple with Sun outside FOV';
    init_data.measurement_wait_time = 0.1; % [sec]
    init_data.measurement_noise = 2e-4; % [rad]
    init_data.field_of_view = 90; % [deg]

    init_data.location = [0.3 0.15 0.05]; % [m]
    init_data.orientation = [1 0 0]; % [unit vector]

    mission.true_SC{i_SC}.true_SC_star_tracker{i_HW} = True_SC_Star_Tracker(init_data, mi
end

%% Initialize Spacecraft's Reaction Wheels
for i_HW = 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_reaction_wheel
    init_data = [];
    init_data.location = [0,0,0];
    init_data.radius = (43e-3)/2; % [m]
    init_data.mass = 0.137; % [kg]
    init_data.max_angular_velocity = 6500*2*pi/60; % [rad/s]
    init_data.max_torque = 3.2*1e-3; % [Nm]

    % Set orientation based on configuration (3 or 4 wheels)
    if mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_reaction_wheel == 3
        % 3-wheel configuration along principal axes
        switch i_HW
            case 1
                init_data.orientation = [1, 0, 0];  % X-axis
            case 2
                init_data.orientation = [0, 1, 0];  % Y-axis
            case 3
                init_data.orientation = [0, 0, 1];  % Z-axis
        end
    end
```

```
    mission.true_SC{i_SC}.true_SC_reaction_wheel{i_HW} = True_SC_Reaction_Wheel(init_data
end
```

2.4.9 Flight Software Configuration

The final step is to configure the flight software components that control the spacecraft. Each software component serves a specific purpose in the autonomous operation of the spacecraft.

2.4.9.1 Executive Software

The Executive software was described in detail in Section 4.6.1. To briefly recap, it is responsible for determining the spacecraft's operating mode and coordinating subsystem activities. When creating a custom mission, you should:

1. Define the operating modes relevant to your mission in your mission configuration file
2. Create a custom implementation function in `Software_SC_Executive.m`
3. Set the `mode_software_SC_executive_selector` parameter to your custom function name

See Section 4.6.1 for implementation examples and code samples.

2.4.9.2 Attitude & Orbit Estimation

These components determine the spacecraft's current attitude and position:

```
%% Spacecraft Software: Attitude Estimation Configuration
init_data = [];
init_data.mode_software_SC_estimate_attitude_selector = 'Truth';
mission.true_SC{i_SC}.software_SC_estimate_attitude =
    Software_SC_Estimate_Attitude(init_data, mission, i_SC);

%% Spacecraft Software: Orbit Estimation Configuration
init_data = [];
init_data.mode_software_SC_estimate_orbit_selector = 'TruthWithErrorGrowth';
mission.true_SC{i_SC}.software_SC_estimate_orbit =
    Software_SC_Estimate_Orbit(init_data, mission, i_SC);
```

For initial mission development, you can use the 'Truth' estimators that simply read the actual spacecraft state. For more realistic simulations, you can implement custom estimators that process sensor data.

2.4.9.3 Orbit & Attitude Control

The control components determine how to move the spacecraft to desired states:

```
%% Spacecraft Software: Orbit Control Configuration
init_data = [];
init_data.max_time_before_control = 0.5*60*60 + 900;  % 45 minutes
init_data.mode_software_SC_control_orbit_selector = 'YourMission';
```

```
mission.true_SC{i_SC}.software_SC_control_orbit =
    Software_SC_Control_Orbit(init_data, mission, i_SC);

%% Spacecraft Software: Attitude Control Configuration
init_data = [];
init_data.mode_software_SC_control_attitude_selector = 'YourMission Control';
init_data.control_gain = [1 0.2];    % Controller gain parameters
mission.true_SC{i_SC}.software_SC_control_attitude =
    Software_SC_Control_Attitude(init_data, mission, i_SC);
```

You'll need to implement custom control algorithms that match the mode selector names provided here.

2.4.9.4 Communication & Resource Management

These components manage communication opportunities and onboard resources:

```
%% Spacecraft Software: Communication Configuration
init_data = [];
init_data.mode_software_SC_communication_selector = 'YourMission';
init_data.attitude_error_threshold_deg = 1;  % Max attitude error for comms
mission.true_SC{i_SC}.software_SC_communication =
    Software_SC_Communication(init_data, mission, i_SC);
```

The communication software determines when to establish links with ground stations and manages the flow of data to and from the spacecraft.

2.4.10 Final Initialization and Simulation Execution

After configuring all subsystems, several final initialization steps must be performed before running the simulation. These steps ensure that all spacecraft properties are properly calculated and that the simulation environment is ready:

```
%% Final Things to Do Before Running the Simulation

% Initialize mass properties
func_update_SC_body_total_mass_COM_MI(mission.true_SC{i_SC}.true_SC_body);

% Initialize power and data handling storage
func_initialize_store_HW_power_consumed_generated(mission.true_SC{i_SC}.true_SC_power, mi
func_initialize_store_HW_data_generated_removed(mission.true_SC{i_SC}.true_SC_data_handli

% Clean up temporary variables
clear init_data i_SC i_HW i_target

% Visualize the spacecraft in 3D
func_visualize_SC(mission.storage, mission, true);

% Save initial state
```

```
save([mission.storage.output_folder, 'all_data.mat'], '-v7.3')

%% Execute Main File
run main_v3.m

%% Save All Data and Generate Plots
save([mission.storage.output_folder, 'all_data.mat'], '-v7.3')
func_visualize_simulation_data(mission.storage, mission);
```

The initialization process includes calculating the total mass, center of mass, and moment of inertia for the spacecraft body, setting up storage for power and data handling metrics, and cleaning up temporary variables used during configuration. The spacecraft is then visualized in 3D to provide a visual confirmation of the configuration.

After initialization, the main simulation file (`main_v3.m`) is executed, which runs the simulation according to the configured parameters. Once the simulation is complete, all data is saved to the specified output folder, and visualization functions are called to generate plots of the simulation results.

2.5 Understanding SPICE Integration

MuSCAT uses NASA's SPICE toolkit for accurate ephemeris calculations, providing precise positions and velocities of solar system bodies and spacecraft. This section explains how SPICE is integrated into MuSCAT and how to use it effectively for your mission.

2.5.1 What is SPICE?

SPICE (Spacecraft, Planet, Instrument, C-matrix, Events) is a NASA toolkit developed by the Navigation and Ancillary Information Facility (NAIF) at JPL. It provides essential information for mission design, planning, and science data analysis for space science missions. SPICE consists of data files called "kernels" and a suite of software tools that read and interpret these kernels to provide spacecraft and planetary ephemerides, instrument pointing information, time conversions, and other critical mission data.

2.5.2 Why MuSCAT Uses SPICE

MuSCAT integrates SPICE for several critical reasons:

- **Accurate Ephemerides**: SPICE provides high-precision positions and velocities of solar system bodies based on the latest planetary ephemerides (like DE430 or DE440), ensuring that simulations accurately represent the gravitational influences of planets and other bodies.
- **Realistic Trajectory Modeling**: Enables detailed simulation of spacecraft trajectories, including complex orbital maneuvers and gravity assists, which is essential for mission planning and validation.
- **Time System Conversions**: Provides robust time system conversions between various time standards (UTC, TDB, TDT, etc.), which is crucial for correlating events across different reference frames and mission phases.

- **Reference Frame Transformations**: Handles complex coordinate transformations between different reference frames (J2000, ICRF, body-fixed, etc.), allowing for accurate representation of spacecraft orientation and position relative to various celestial bodies.
- **Industry Standard**: SPICE is the de facto standard for deep space mission design at NASA and other space agencies, making MuSCAT compatible with industry practices and facilitating data exchange with other mission analysis tools.
- **Validation and Verification**: Using SPICE allows MuSCAT simulations to be validated against real mission data and other industry-standard tools, increasing confidence in simulation results.

2.5.3 SPICE Navigation Dynamics Mode

When using the 'SPICE' navigation dynamics mode in MuSCAT, the spacecraft's position and velocity are directly obtained from SPICE kernels rather than being propagated using orbital dynamics equations. This approach:

- Ensures consistency with mission design trajectories
- Allows for simulation of complex trajectories that may be difficult to model with standard orbital dynamics
- Provides a ground truth reference for validating other dynamics models
- Simplifies the simulation of multi-body trajectories (e.g., lunar or interplanetary missions)

2.5.4 SPICE Kernel Types Used in MuSCAT

MuSCAT uses several types of SPICE kernels:

- **SPK (Spacecraft and Planet Kernels)**: Contain ephemeris data for spacecraft and celestial bodies. These files define the positions and velocities of objects as functions of time.
- **LSK (Leapseconds Kernels)**: Provide information about leap seconds, allowing accurate conversion between different time systems.
- **PCK (Planetary Constants Kernels)**: Contain physical and cartographic constants for planets and satellites, such as size, shape, and orientation.
- **FK (Frame Kernels)**: Define reference frames needed for coordinate transformations.
- **IK (Instrument Kernels)**: Contain geometric and operational parameters of instruments (used for more advanced simulations).

2.5.5 SPICE Setup in MuSCAT

To use SPICE in your MuSCAT mission:

1. Ensure the SPICE toolkit (MICE for MATLAB) is correctly installed in `MuSCAT_Supporting_Files/SP`
2. Collect necessary SPICE kernels for your mission:

- Leapseconds kernel (LSK) for time conversions (e.g., `naif0012.tls`)
- Planetary ephemeris kernel (SPK) for solar system bodies (e.g., `de430.bsp`)
- Spacecraft trajectory kernel (SPK) for your spacecraft (e.g., `YourMission.bsp`)
- Frame kernel (FK) if using custom reference frames

3. Load the required kernels in your mission file:

```
% Load necessary SPICE kernels
cspice_furnsh('../../MuSCAT_Supporting_Files/SPICE/naif0012.tls');  % Leapsecond
cspice_furnsh('../../MuSCAT_Supporting_Files/SPICE/de430.bsp');     % Planetary
init_data.spice_filename = '../../MuSCAT_Supporting_Files/SC_data/YourMission/tr
cspice_furnsh(init_data.spice_filename);  % Your spacecraft trajectory
```

4. Retrieve position and velocity data:

```
init_data.spice_name = '-123';  % SPICE ID for your spacecraft (negative integer
init_data.SC_pos_vel = cspice_spkezr(init_data.spice_name, mission.true_time.dat
                                   'J2000', 'NONE', 'SUN');
init_data.position = init_data.SC_pos_vel(1:3)'; % [km]
init_data.velocity = init_data.SC_pos_vel(4:6)'; % [km/sec]
```

5. Specify SPICE mode in navigation dynamics (if using SPICE for position/velocity updates):

```
init_data.mode_true_SC_navigation_dynamics_selector = 'SPICE';
```

2.5.6 Creating SPICE Kernels for Your Mission

You can create your own SPICE SPK kernel for a custom spacecraft trajectory:

1. Generate a trajectory using your preferred method (analytical, numerical integration, etc.)
2. Convert the trajectory to SPICE format using SPICE utilities:
   - For MATLAB, use MICE functions like `cspice_spkw08` or `cspice_spkw09`
   - For standalone processing, use the SPICE utility `mkspk`
3. Format the trajectory data as a time series of position and velocity vectors
4. Assign a NAIF ID for your spacecraft (usually a negative integer)
5. Create the SPK file with appropriate metadata (reference frame, time coverage, etc.)
6. Place your SPK file in the appropriate directory: `MuSCAT_Supporting_Files/SC_data/YourMission/`

2.5.7 SPICE Integration with Main Simulation Loop

During simulation, SPICE integration occurs at several key points:

1. **Initialization**: SPICE kernels are loaded and initial states are obtained
2. **Time Updates**: Each simulation step updates the current epoch used for SPICE queries
3. **Navigation Updates**: When using SPICE mode, the `func_main_true_SC_navigation` function retrieves updated position/velocity directly from SPICE
4. **Environmental Calculations**: SPICE may be used to determine positions of other bodies for gravity calculations
5. **Ground Station Visibility**: SPICE data helps determine line-of-sight between spacecraft and ground stations

This integration provides a seamless interface between MuSCAT's simulation environment and the high-fidelity ephemeris data provided by SPICE, ensuring accurate representation of spacecraft trajectories and celestial body positions throughout the simulation.

2.6 Creating Custom Flight Software

Flight software defines the autonomous behavior of your spacecraft. In MuSCAT, flight software is implemented as MATLAB classes in the `Software_SC` directory. This section explains how to create custom flight software for your mission.

2.6.1 Executive Software

The Executive software was described in detail in Section 4.6.1. To briefly recap, it is responsible for determining the spacecraft's operating mode and coordinating subsystem activities. When creating a custom mission, you should:

1. Define the operating modes relevant to your mission in your mission configuration file
2. Create a custom implementation function in `Software_SC_Executive.m`
3. Set the `mode_software_SC_executive_selector` parameter to your custom function name

See Section 4.6.1 for implementation examples and code samples.

2.6.2 Attitude & Orbit Controllers

Similarly, you can create custom orbit and attitude controllers for your mission:

1. Add your custom controller implementation to the appropriate file (`Software_SC_Control_Orbit.m` or `Software_SC_Control_Attitude.m`)
2. Implement the control logic specific to your mission requirements
3. Reference your controller in the mission file:

```
init_data.mode_software_SC_control_orbit_selector = 'YourMission';
mission.true_SC{i_SC}.software_SC_control_orbit = Software_SC_Control_Orbit(init
```

2.7 Simulation Execution and Analysis

Once your mission configuration is complete, the simulation is executed by running the `main_v3.m` script. This script contains the main time loop that updates all components of the mission at each time step.

2.7.1 Main Simulation Loop

The main simulation loop in `main_v3.m` proceeds as follows:

1. Update simulation time and date
2. Update solar system and target bodies
3. For each spacecraft:
    - Update environmental effects (solar radiation pressure, gravity gradient)
    - Update spacecraft body, position, and velocity
    - Update onboard clock and computer systems
    - Execute the Executive software to determine operating mode
    - Update all sensors, actuators, and subsystems
    - Run the attitude dynamics loop at a higher frequency
    - Update communication systems
    - Update power and data handling systems
4. Update ground station systems
5. Save data and update visualizations

2.7.2 Visualizing Results

MuSCAT provides comprehensive visualization tools to analyze mission performance:

- `func_visualize_SC`: Creates a 3D visualization of the spacecraft
- `func_visualize_simulation_data`: Generates plots for various subsystems
- Real-time visualization can be enabled with `flag_realtime_plotting = 1`

Key visualizations include:

- Spacecraft configuration and ConOps
- Orbit and attitude dynamics
- Power generation and consumption
- Data handling and communication performance
- Sensor and actuator performance

2.8 Advanced Topics

2.8.1 Creating Custom Hardware Components

If the built-in hardware models don't meet your needs, you can create custom components. This should be done without modifying the core MuSCAT files, following the extension patterns described earlier.

2.8.1.1 Custom Hardware Component Development Steps

1. Create a new MATLAB class file in your mission-specific directory that inherits from the appropriate parent class:

```
classdef Your_Custom_Sensor < True_SC_Sensor
    % Your custom sensor implementation
    properties
        % Custom properties specific to your sensor
        custom_parameter_1
        custom_parameter_2
    end

    methods
        % Constructor
        function obj = Your_Custom_Sensor(init_data, mission, i_SC, i_HW)
            % Call parent constructor
            obj@True_SC_Sensor(init_data, mission, i_SC, i_HW);

            % Initialize custom properties
            obj.custom_parameter_1 = init_data.custom_parameter_1;
            obj.custom_parameter_2 = init_data.custom_parameter_2;
        end
    end
end
```

2. Create a corresponding `func_main_your_custom_sensor` function that follows the standard MuSCAT update pattern:

```
function func_main_your_custom_sensor(obj, mission, i_SC, i_HW)
    % Update the custom sensor state based on current mission state

    % Your custom update logic here
    % ...

    % Store data if needed
    func_store_data(obj, mission);
end
```

3. Add your component to the simulation loop by extending the appropriate hardware update section in a copy of `main_v3.m` that you create for your mission:

```
%% Custom Hardware Update
for i_SC = 1:1:mission.num_SC
    for i_HW = 1:1:mission.true_SC{i_SC}.num_your_custom_sensor
        func_main_your_custom_sensor(mission.true_SC{i_SC}.your_custom_sensor{i_
                                     mission, i_SC, i_HW);
    end
end
```

4. In your mission file, instantiate your custom hardware:

```
% Add custom hardware to the hardware complement
init_data.num_hardware_exists.num_your_custom_sensor = 2;

% Create the custom sensor objects
for i_HW = 1:1:init_data.num_hardware_exists.num_your_custom_sensor
    init_data = [];
    init_data.custom_parameter_1 = value1;
    init_data.custom_parameter_2 = value2;

    mission.true_SC{i_SC}.your_custom_sensor{i_HW} =
        Your_Custom_Sensor(init_data, mission, i_SC, i_HW);
end
```

2.8.1.2 Integration with MuSCAT's Core Features

To ensure your custom component works seamlessly with MuSCAT:

- **Power Subsystem Integration**: Implement proper power consumption tracking by setting `instantaneous_power_consumed` and updating it during operation.
- **Data Handling Integration**: Set `instantaneous_data_rate_generated` to track data generation and ensure it's properly routed through the data handling subsystem.
- **Visualization Support**: Implement `func_visualize` methods if your component has visual representation.
- **Error Handling**: Include appropriate error checks and failure modes to enhance simulation realism.
- **Documentation**: Thoroughly document your custom component's interfaces, parameters, and behaviors.

By creating custom components in this way, you maintain compatibility with future MuSCAT updates while extending its capabilities to meet your specific mission requirements.

2.8.2 Multi-Spacecraft Missions

To simulate missions with multiple spacecraft:

1. Set `mission.num_SC` to the desired number of spacecraft
2. Configure each spacecraft using a loop over `i_SC`
3. Implement inter-spacecraft communication using communication links

2.8.3 Monte Carlo Simulations

For uncertainty analysis, you can run Monte Carlo simulations:

1. Create a wrapper script that calls your mission file multiple times
2. Vary key parameters according to your uncertainty model
3. Collect and analyze the results across all simulations

2.9 Conclusion

MuSCAT provides a flexible, modular framework for simulating complex spacecraft missions. By following the steps outlined in this chapter, you can implement your own custom missions, from initial concept to detailed simulation and analysis.

The implementation process involves several key steps:

1. **Mission Definition**: Set up the basic parameters like mission name, number of spacecraft, and target bodies.
2. **Time and Storage Configuration**: Configure the dual-loop time steps to properly handle both orbital and attitude dynamics at appropriate temporal resolutions.
3. **Environment Setup**: Configure the star catalog, solar system bodies, target bodies, and ground stations that form the operational context for your mission.
4. **Spacecraft Configuration**: Define the physical properties, hardware complement, initial position, and attitude for each spacecraft in your mission.
5. **Subsystem Configuration**: Set up power, data handling, communications, sensors, and actuators with the specific properties required for your mission.
6. **Flight Software Implementation**: Configure the executive, estimation, and control algorithms that will govern the autonomous behavior of your spacecraft.
7. **Simulation Execution**: Run the main simulation loop to simulate your mission over the specified time period.
8. **Results Analysis**: Analyze the simulation results using MuSCAT's visualization tools to evaluate mission performance.

MuSCAT's modular architecture allows for extensive customization at every level. You can:

- Create new hardware components by implementing additional classes in the appropriate directories
- Develop custom flight software algorithms to implement novel autonomous behaviors
- Simulate complex multi-spacecraft missions with varied objectives and capabilities
- Perform trade studies by varying parameters and analyzing the impacts on mission performance
- Validate mission concepts and requirements before detailed design

The object-oriented nature of MuSCAT means that each component is self-contained with well-defined interfaces, making it straightforward to extend the functionality without disrupting existing capabilities. This modularity also facilitates incremental development, allowing you to start with a simple mission model and progressively add complexity as your understanding evolves.

By leveraging NASA's SPICE toolkit for ephemeris calculations, MuSCAT ensures high-fidelity position and velocity data for spacecraft and celestial bodies, enabling realistic simulation of mission scenarios in the complex dynamical environment of space.

Whether you're designing a simple Earth-orbiting satellite or a complex interplanetary mission with multiple spacecraft, MuSCAT provides the tools and framework to model, simulate, and evaluate your mission concept efficiently and effectively.

2.10 Troubleshooting and Best Practices

2.10.1 Common Issues and Solutions

When implementing missions in MuSCAT, you may encounter several common issues. This section provides guidance on identifying and resolving these problems:

- **Memory Errors**: For large simulations with many time steps or spacecraft:
  - Increase the storage intervals (`time_step_storage` and `time_step_storage_attitude`)
  - Use the `clear` command strategically to free memory during long simulations
  - Consider breaking the simulation into multiple segments and combining results afterward
- **SPICE-Related Errors**: When working with SPICE:
  - Ensure MICE is properly installed and on the MATLAB path
  - Verify kernel coverage spans your entire simulation time period
  - Check for NAIF ID conflicts between different objects
  - Use `cspice_furnsh` with absolute paths to avoid path-related issues
- **Simulation Instability**: If your simulation becomes unstable:
  - Reduce the time step, especially for attitude dynamics
  - Check for physical inconsistencies (e.g., mismatched units, unrealistic parameters)
  - Verify that actuator limitations (e.g., maximum torque) are realistic
  - Implement controllers with appropriate stability margins

- **Missing Data in Results**: If expected data is missing:
  - Verify that storage flags are enabled for relevant components
  - Check that sensor/actuator update times align with storage times
  - Ensure `func_store_data` is called in all custom components

2.10.2 Performance Optimization

For complex missions or Monte Carlo simulations, performance optimization becomes critical:

1. **Time Step Optimization**:
   - Use the largest time step that maintains accuracy for your specific mission
   - Consider variable time stepping for different mission phases
   - Balance the attitude time step with the dynamics of your spacecraft
2. **Hardware Selection**:
   - Only include hardware components necessary for your mission
   - Use a reasonable number of sensors/actuators (e.g., 4-6 sun sensors rather than dozens)
   - Group hardware with similar functions when possible
3. **Vectorization**:
   - Rewrite custom component code to use MATLAB's vectorized operations
   - Avoid loops when matrix/vector operations can accomplish the same task
   - Pre-allocate arrays for storing time-series data
4. **Visualization**:
   - Disable real-time visualization during long simulations
   - Generate plots after the simulation completes rather than during execution
   - Consider lower-resolution shape models for faster 3D rendering

2.10.3 Units and Conventions

MuSCAT uses a consistent set of units and conventions throughout the codebase:

- **Time**: Seconds (s) for simulation time; UTC for absolute dates
- **Length**: Meters (m) for spacecraft dimensions; Kilometers (km) for orbital distances
- **Mass**: Kilograms (kg)
- **Angles**: Radians (rad) internally
- **Angular Velocity**: Radians per second (rad/s)
- **Force**: Newtons (N)

- **Torque**: Newton-meters (N·m)
- **Power**: Watts (W)
- **Energy**: Watt-hours (W·hr) for batteries
- **Data**: Kilobits (kb) for storage; Kilobits per second (kbps) for rates
- **Reference Frames**:
  - J2000 for inertial references
  - Body-fixed frames for spacecraft-relative quantities

Consistent use of these units is essential for correct simulation behavior.

2.10.4 Glossary of Terms

- **ADC**: Attitude Determination and Control
- **ConOps**: Concept of Operations
- **DCM**: Direction Cosine Matrix
- **DSN**: Deep Space Network
- **Eb/N0**: Energy per bit to noise density ratio
- **FK**: Frame Kernel (SPICE)
- **IMU**: Inertial Measurement Unit
- **LSK**: Leapseconds Kernel (SPICE)
- **MICE**: MATLAB Interface to SPICE
- **MRP**: Modified Rodrigues Parameters
- **NAIF**: Navigation and Ancillary Information Facility
- **PCK**: Planetary Constants Kernel (SPICE)
- **SPK**: Spacecraft and Planet Kernel (SPICE)
- **SRP**: Solar Radiation Pressure

2.10.5 Known Limitations

As with any simulation framework, MuSCAT has some known limitations:

- **Physical Fidelity**: Some physical effects are simplified or not modeled:
  - Thermal effects on spacecraft materials and instruments
  - Detailed propellant slosh dynamics
  - Advanced radiation effects on electronics
  - Detailed structural flexibility
- **Scalability**: Performance may degrade with very complex missions:
  - Formations with many (¿10) spacecraft
  - Very long duration missions (¿1 year) at high temporal resolution
- **Navigation Models**: Some specialized navigation techniques lack detailed models:
  - Optical navigation using small bodies
  - Inter-spacecraft relative navigation
  - GPS-like navigation in cislunar space
- **Environment Models**: Some environmental effects have simplified models:
  - Higher-order gravitational terms
  - Atmospheric drag variation with solar activity
  - Detailed magnetic field modeling

Users should be aware of these limitations when interpreting simulation results and consider supplementing MuSCAT with specialized tools for detailed analysis of these effects when necessary.

2.11 Practical Examples and Design Patterns

This section provides concrete examples of common tasks and design patterns to help you implement your missions effectively.

2.11.1 Common Mode Implementation Patterns

The following examples illustrate typical implementations for common spacecraft operating modes:

2.11.1.1 Sun-Safe Mode

This mode orients the spacecraft to maximize solar panel exposure while keeping sensitive instruments safe:

```
% In your Executive implementation function
if strcmp(obj.this_sc_mode, 'Sun-Safe')
    % Get Sun direction in spacecraft body frame
    sun_body = mission.true_SC{i_SC}.true_SC_navigation.sun_direction_body;

    % Set attitude target to align solar panels with Sun
    % Assuming Z-axis is normal to solar panels
    target_quaternion = func_quaternion_from_two_vectors([0 0 1], sun_body);

    % Point solar panels at Sun with moderate rotation rate
    mission.true_SC{i_SC}.software_SC_control_attitude.target_attitude = target_quaternio
    mission.true_SC{i_SC}.software_SC_control_attitude.target_rate = [0 0 0];

    % Disable components to save power
    mission.true_SC{i_SC}.true_SC_camera{1}.flag_executive = 0;
    mission.true_SC{i_SC}.true_SC_micro_thruster{1}.flag_executive = 0;

    % Enable power-critical components
    mission.true_SC{i_SC}.software_SC_estimate_attitude.flag_executive = 1;
    mission.true_SC{i_SC}.software_SC_control_attitude.flag_executive = 1;
end
```

2.11.1.2 Science Observation Mode

This mode points instruments at a target of interest:

```
% In your Executive implementation function
if strcmp(obj.this_sc_mode, 'Science Observation')
    % Get target direction in inertial frame
    target_inertial = mission.true_SC{i_SC}.true_SC_navigation.target_direction_inertial;

    % Convert to required quaternion (assuming camera points along X-axis)
    target_quaternion = func_quaternion_from_two_vectors([1 0 0], target_inertial);

    % Point instrument and stabilize
    mission.true_SC{i_SC}.software_SC_control_attitude.target_attitude = target_quaternio
    mission.true_SC{i_SC}.software_SC_control_attitude.target_rate = [0 0 0];

    % Enable science instruments
    mission.true_SC{i_SC}.true_SC_camera{1}.flag_executive = 1;

    % Log start of observation if mode just activated
    if ~strcmp(obj.data.previous_mode, 'Science Observation')
        disp(['Science observation started at t = ', ...
              num2str(mission.true_time.time), ' seconds']);
        obj.data.observation_start_time = mission.true_time.time;
    end
end
```

2.11.2 Implementing Common Mission Types

The following patterns demonstrate implementations for common mission types:

2.11.2.1 Earth-Orbiting Remote Sensing Satellite

For an Earth-observing satellite, consider this implementation pattern:

```
%% Mission Definition
mission = [];
mission.name = 'EarthObsSat';
mission.num_SC = 1;
mission.num_target = 1;  % Earth as target
mission.frame = 'Absolute';

%% Initialize Spacecraft's Position and Velocity
init_data = [];
% Sun-synchronous orbit at 700 km altitude
orbit_altitude = 700;  % [km]
earth_radius = 6378.1;  % [km]
orbit_radius = earth_radius + orbit_altitude;
orbit_velocity = sqrt(398600.4415 / orbit_radius);  % [km/s]

% Position at ascending node
init_data.position = [0, -orbit_radius, 0];  % [km]
init_data.velocity = [orbit_velocity, 0, 0];  % [km/s]
init_data.mode_true_SC_navigation_dynamics_selector = 'Absolute Dynamics';

% Key operational modes
init_data.sc_modes = {'Nadir Pointing', 'Target Imaging',
                     'Data Downlink', 'Safe Mode'};

% Payload-specific hardware
init_data.num_hardware_exists.num_camera = 2;  % Multispectral + Panchromatic
init_data.num_hardware_exists.num_solar_panel = 2;  % Two deployable panels
init_data.num_hardware_exists.num_star_tracker = 2;  % Redundant attitude determination
init_data.num_hardware_exists.num_reaction_wheel = 4;  % 4-wheel configuration
init_data.num_hardware_exists.num_magnetorquer = 3;  % For wheel desaturation
```

2.11.2.2 Interplanetary Science Mission

For an interplanetary probe, use this implementation pattern:

```
%% Mission Definition
mission = [];
mission.name = 'MarsMission';
mission.num_SC = 1;
mission.num_target = 1;  % Mars as target
mission.frame = 'Absolute';
```

```
%% SPICE-Based Trajectory
init_data = [];
init_data.spice_filename = '../../MuSCAT_Supporting_Files/SC_data/MarsMission/trajectory.
cspice_furnsh(init_data.spice_filename);
cspice_furnsh('../../MuSCAT_Supporting_Files/SPICE/de430.bsp');  % Planetary ephemeris

init_data.spice_name = '-123';  % SPICE ID for the spacecraft
init_data.SC_pos_vel = cspice_spkezr(init_data.spice_name, mission.true_time.date,
                                     'J2000', 'NONE', 'SUN');
init_data.position = init_data.SC_pos_vel(1:3)';  % [km]
init_data.velocity = init_data.SC_pos_vel(4:6)';  % [km/sec]
init_data.mode_true_SC_navigation_dynamics_selector = 'SPICE';

% Mission-specific modes
init_data.sc_modes = {'Cruise', 'TCM', 'Science',
                     'Mars Orbit Insertion', 'Communication', 'Safe Mode'};

% Deep space hardware
init_data.num_hardware_exists.num_high_gain_antenna = 1;  % For long-distance comms
init_data.num_hardware_exists.num_camera = 3;  % Navigation + Science instruments
init_data.num_hardware_exists.num_chemical_thruster = 1;  % Main propulsion
init_data.num_hardware_exists.num_reaction_wheel = 4;  % Attitude control
```

2.11.3 Common Attitude Control Implementations

The following examples show implementations for common attitude control laws:

2.11.3.1 PD Controller

A simple Proportional-Derivative controller for attitude:

```
function obj = func_software_SC_control_attitude_PD(obj, mission, i_SC)
    % Get current attitude error quaternion
    att_error_q = func_quaternion_error(mission.true_SC{i_SC}.software_SC_estimate_attitu
                                        obj.target_attitude);

    % Convert quaternion error to angle-axis representation
    [error_axis, error_angle] = func_quaternion_to_axis_angle(att_error_q);

    % Calculate error vectors
    att_error_vec = error_axis * error_angle;
    rate_error = mission.true_SC{i_SC}.software_SC_estimate_attitude.angular_velocity - o

    % PD controller with gains
    Kp = obj.control_gain(1);  % Proportional gain
    Kd = obj.control_gain(2);  % Derivative gain

    % Calculate desired control torque
    desired_torque = -Kp * att_error_vec - Kd * rate_error;
```

```
    % Apply control to reaction wheels
    for i_wheel = 1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_reaction_w
        % Get wheel axis
        wheel_axis = mission.true_SC{i_SC}.true_SC_reaction_wheel{i_wheel}.orientation;

        % Project desired torque onto wheel axis
        wheel_torque = dot(desired_torque, wheel_axis) * wheel_axis;

        % Set wheel torque (with limits)
        max_torque = mission.true_SC{i_SC}.true_SC_reaction_wheel{i_wheel}.max_torque;
        commanded_torque = min(max_torque, max(wheel_torque, -max_torque));

        mission.true_SC{i_SC}.true_SC_reaction_wheel{i_wheel}.input_torque = commanded_to
    end
end
```

2.11.4 Custom Hardware Example: Laser Rangefinder

Below is an example of implementing a custom laser rangefinder for proximity operations:

```
classdef Custom_Laser_Rangefinder < True_SC_Sensor
    properties
        max_range          % Maximum detection range [m]
        min_range          % Minimum detection range [m]
        range_accuracy     % Range measurement accuracy [m]
        field_of_view      % Field of view [deg]
        target_reflectivity % Target reflectivity factor [0-1]
        last_measurement   % Last valid range measurement [m]
        is_target_detected % Flag indicating target detection
    end

    methods
        % Constructor
        function obj = Custom_Laser_Rangefinder(init_data, mission, i_SC, i_HW)
            % Call parent constructor
            obj@True_SC_Sensor(init_data, mission, i_SC, i_HW);

            % Initialize properties
            obj.max_range = init_data.max_range;
            obj.min_range = init_data.min_range;
            obj.range_accuracy = init_data.range_accuracy;
            obj.field_of_view = init_data.field_of_view;
            obj.target_reflectivity = init_data.target_reflectivity;
            obj.last_measurement = -1;  % Invalid measurement
            obj.is_target_detected = 0;

            % Set standard properties
            obj.instantaneous_power_consumed = 2.5;  % [W]
```

```
            obj.instantaneous_data_rate_generated = 0.1 * 8;  % [kbps]
        end
    end
end

% Corresponding update function
function func_main_custom_laser_rangefinder(obj, mission, i_SC, i_HW)
    % Skip if not active
    if ~obj.flag_executive
        obj.is_target_detected = 0;
        obj.last_measurement = -1;
        return;
    end

    % Get target position in spacecraft body frame
    target_pos_inertial = mission.true_target{1}.position;
    sc_pos_inertial = mission.true_SC{i_SC}.true_SC_navigation.position;
    sc_att_q = mission.true_SC{i_SC}.true_SC_adc.attitude;

    % Calculate relative position vector in body frame
    rel_pos_inertial = target_pos_inertial - sc_pos_inertial;
    rel_pos_body = func_quaternion_rotate_vector(sc_att_q, rel_pos_inertial);

    % Calculate range and direction
    true_range = norm(rel_pos_body);
    direction = rel_pos_body / true_range;

    % Check if target is within detector range and FOV
    sensor_axis = obj.orientation;
    angle_to_target = acosd(dot(sensor_axis, direction));

    % Determine if target is detected
    if true_range >= obj.min_range && true_range <= obj.max_range && ...
       angle_to_target <= obj.field_of_view/2

        % Target is within FOV and range limits
        obj.is_target_detected = 1;

        % Add noise to measurement based on accuracy
        noise = randn(1) * obj.range_accuracy;
        obj.last_measurement = true_range + noise;
    else
        % No valid detection
        obj.is_target_detected = 0;
        obj.last_measurement = -1;
    end

    % Store data
```

```
    func_store_data(obj, mission);
end
```

These examples demonstrate typical implementation patterns for various MuSCAT components. You can use them as starting points for your own mission implementations, adapting them to your specific requirements.

Chapter 3

Environment Classes

3.1 `Storage`

Table of Contents

Class: Storage

Helps store all the data from the simulation

```
classdef Storage < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        time_step_storage % [sec] : Storage time step
        time_step_storage_attitude % [sec] : Storage time step for attitude
 dynamics loop (Optional)

        flag_visualize_SC_attitude_orbit_during_sim % [Boolean] : 1 = Shows
 the attitude and position during simulation (Optional)
        wait_time_visualize_SC_attitude_orbit_during_sim % [sec] (Optional)
        flag_visualize_past_SC_orbit_during_sim % [Boolean] : 1 = Shows the
 entire orbit from the start of sim (Optional)
```

[ ] Properties: Variables Computed Internally

```
        time_prev_storage % [sec] : Previous time when variables were stored #
        num_storage_steps % [integer] : Number of storage variables        #
        flag_store_this_time_step % [Boolean] : 1 = Store, else dont store #
        k_storage % [integer] : Storage counter variable                   #

        time_prev_storage_attitude % [sec] : Previous time when attitude
 variables were stored #
        num_storage_steps_attitude % [integer] : Number of storage variables
 for Attitude Dynamics Loop #
```

```
        flag_store_this_time_step_attitude % [Boolean] : 1 = Store, else dont
store, for Attitude Dynamics Loop #
        k_storage_attitude % [integer] : Storage counter variable, for
Attitude Dynamics Loop #


        prev_time_visualize_SC_attitude_orbit_during_sim % [sec]

        % Real-time plotting variables
        flag_realtime_plotting % [Boolean] : 1 = Enable real-time performance
plotting
        realtime_plot_handle % Handle to the real-time plot figure
        realtime_plot_last_update % [sec] : Time of last real-time plot update
        realtime_plot_update_interval % [sec] : Minimum time between real-time
plot updates
        realtime_plot_subhandles % Cell array of subplot handles for real-time
plotting


        % Initialize real-time visualization settings
        last_viz_update_time % Time of last visualization update
        viz_update_interval  % Update visualization every 50 simulation
seconds (reduced from 100)
```

[ ] Properties: Other Useful Variables

```
        numerical_accuracy_factor % [float <= 1, but limit -> 1] : Used to
take care of issues arising due to numerical accuracy of integer computations
#

        plot_parameters % Parameters used for plotting
        % - color_array
        % - marker_array
        % - standard_font_size
        % - standard_font_type
        % - title_font_size
        % - flag_save_plots % [Boolean] 1: Save them (takes little time), 0:
Doesnt save them
        % - flag_save_video % [Boolean] 1: Save them (takes a lot more time),
0: Doesnt save them
        % - quiver_auto_scale_factor % [float] : scale factor used for quiver3

        output_folder % [Boolean] Folder to store all outputs

        flag_stop_sim % flag to stop simulation

        last_mode % Cell array to store the last mode of each spacecraft

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = Storage(init_data, mission)

            if init_data.time_step_storage == 0
                % Use 0 to use the mission.true_time.time_step value
                obj.time_step_storage = mission.true_time.time_step; % [sec]

            else
                obj.time_step_storage = init_data.time_step_storage; % [sec]
            end

            obj.flag_store_this_time_step = 1;
            obj.time_prev_storage = mission.true_time.time; % [sec]
            obj.num_storage_steps = ceil( (mission.true_time.t_final -
mission.true_time.t_initial)/obj.time_step_storage ) + 1;
            obj.k_storage = 1;


            obj.last_viz_update_time = -inf; % Time of last visualization
update
            obj.viz_update_interval = 1000;  % Update visualization every 50
simulation seconds (reduced from 100)

            obj.flag_stop_sim = 0;


            if isfield(init_data, 'time_step_storage_attitude')
                % time_step_storage_attitude has been specified

                if init_data.time_step_storage_attitude == 0
                    % Use 0 to use the mission.true_time.time_step_attitude
value
                    obj.time_step_storage_attitude =
mission.true_time.time_step_attitude; % [sec]

                else
                    obj.time_step_storage_attitude =
init_data.time_step_storage_attitude; % [sec]
                end

            else
                obj.time_step_storage_attitude = obj.time_step_storage; %
[sec]
            end

            obj.flag_store_this_time_step_attitude = 1;
            obj.time_prev_storage_attitude = mission.true_time.time; % [sec]
            obj.num_storage_steps_attitude = ceil( (mission.true_time.t_final
- mission.true_time.t_initial)/obj.time_step_storage_attitude ) + 1;
            obj.k_storage_attitude = 1;
```

```
            obj.numerical_accuracy_factor = 0.99;

            % Set plot_parameters
            obj.plot_parameters = [];
            obj.plot_parameters.color_array = ['b' 'r' 'g' 'c' 'y' 'm' 'k'];
            % (Additional colors using rgb.m function from https://
www.mathworks.com/matlabcentral/fileexchange/24497-rgb-triple-of-color-name-
version-2)

            obj.plot_parameters.marker_array =
 ['o' 's' 'd' '^' 'v' '>' '<' 'p' 'h' '+'];
            obj.plot_parameters.standard_font_size = 20;
            obj.plot_parameters.standard_font_type = 'Times New Roman';
            obj.plot_parameters.title_font_size = 40;

            if isfield(init_data, 'flag_save_plots')
                obj.plot_parameters.flag_save_plots =
 init_data.flag_save_plots;
            else
                obj.plot_parameters.flag_save_plots = 1; % [Boolean] 1: Save
 them (takes little time), 0: Doesnt save them
            end

            if isfield(init_data, 'flag_save_video')
                obj.plot_parameters.flag_save_video =
 init_data.flag_save_video;
            else
                obj.plot_parameters.flag_save_video = 0; % [Boolean] 1: Save
 them (takes a lot more time), 0: Doesnt save them
            end

            if
 isfield(init_data, 'flag_visualize_SC_attitude_orbit_during_sim')
                obj.flag_visualize_SC_attitude_orbit_during_sim =
 init_data.flag_visualize_SC_attitude_orbit_during_sim;
            else
                obj.flag_visualize_SC_attitude_orbit_during_sim = 1;
            end

            if
 isfield(init_data, 'wait_time_visualize_SC_attitude_orbit_during_sim')
                obj.wait_time_visualize_SC_attitude_orbit_during_sim =
 init_data.wait_time_visualize_SC_attitude_orbit_during_sim; % [sec]
            else
                obj.wait_time_visualize_SC_attitude_orbit_during_sim = 0; %
 [sec]
            end
            obj.prev_time_visualize_SC_attitude_orbit_during_sim = -inf;

            if isfield(init_data, 'flag_visualize_past_SC_orbit_during_sim')
                obj.flag_visualize_past_SC_orbit_during_sim =
 init_data.flag_visualize_past_SC_orbit_during_sim;
            else
```

```
                obj.flag_visualize_past_SC_orbit_during_sim = 1;
            end

            % Initialize real-time plotting variables
            if isfield(init_data, 'flag_realtime_plotting')
                obj.flag_realtime_plotting = init_data.flag_realtime_plotting;
            else
                obj.flag_realtime_plotting = 1;
            end

            if isfield(init_data, 'quiver_auto_scale_factor')
                obj.plot_parameters.quiver_auto_scale_factor =
init_data.quiver_auto_scale_factor;
            else
                obj.plot_parameters.quiver_auto_scale_factor = 0.1;
            end

            % Output Folder
            obj.output_folder = ['../Output/', mission.name, '_',
char(datetime("now", "Format", "yyyy-MM-dd-HH'h'mm'm'ss's'")), ' (SimTime =
', char(string(mission.true_time.t_final/86400)), ' days)/'];
            %obj.output_folder = ['../Output/', mission.name, '_',
char(datetime("now", "Format", "yyyy-MM-dd-HH'h'mm'm'ss's'")), ' (SimTime =
',char(string(mission.true_time.t_final/86400)), ' days)/'];
            mkdir(obj.output_folder)

            % Store video of func_visualize_SC_attitude_orbit_during_sim
            if (obj.plot_parameters.flag_save_video == 1) &&
(obj.flag_visualize_SC_attitude_orbit_during_sim == 1)
                obj.plot_parameters.video_filename = [obj.output_folder,
mission.name,'_Attitude_Orbit.mp4'];
                obj.plot_parameters.myVideo =
VideoWriter(obj.plot_parameters.video_filename, 'MPEG-4');
                obj.plot_parameters.myVideo.FrameRate = 30;  % Default 30
                obj.plot_parameters.myVideo.Quality = 100;    % Default 75
                open(obj.plot_parameters.myVideo);
            end


        end
```

[ ] Methods: Update Storage Flag

Set the flag_store_this_time_step after sufficient time

```
        function obj = func_update_storage_flag(obj, mission)

            % Reset flags
            obj.flag_store_this_time_step = 0;

            if (mission.true_time.time - obj.time_prev_storage) >=
(obj.time_step_storage * obj.numerical_accuracy_factor)
                obj.flag_store_this_time_step = 1;
```

```
            end

            if mission.true_time.k == mission.true_time.num_time_steps
                obj.flag_store_this_time_step = 1;
            end

            if obj.flag_store_this_time_step == 1
                obj.time_prev_storage = mission.true_time.time; % [sec]
                obj.k_storage = obj.k_storage + 1;
            end

        end
```

[ ] Methods: Update Storage Flag Attitude

Set the flag_store_this_time_step_attitude after sufficient time

```
        function obj = func_update_storage_flag_attitude(obj, mission)

            % Reset flags
            obj.flag_store_this_time_step_attitude = 0;

            if (mission.true_time.time_attitude -
obj.time_prev_storage_attitude) >= (obj.time_step_storage_attitude *
obj.numerical_accuracy_factor)
                obj.flag_store_this_time_step_attitude = 1;
            end

            if (mission.true_time.k == mission.true_time.num_time_steps) &&
(mission.true_time.k_attitude == mission.true_time.num_time_steps_attitude)
                obj.flag_store_this_time_step_attitude = 1;
            end

            if obj.flag_store_this_time_step_attitude == 1
                obj.time_prev_storage_attitude =
mission.true_time.time_attitude; % [sec]
                obj.k_storage_attitude = obj.k_storage_attitude + 1;
            end

        end
```

[ ] Methods: Update Real-Time Plot

Update the real-time performance plot

```
        function obj = func_update_realtime_plot(obj, mission)
           if obj.flag_realtime_plotting
                % Initialize last_mode property if it doesn't exist
                if ~isfield(obj, 'last_mode')
                    obj.last_mode = {};
                    for i_SC = 1:mission.num_SC
                        obj.last_mode{i_SC} =
mission.true_SC{i_SC}.software_SC_executive.this_sc_mode;
```

```
                end
            end

            % Check for mode changes in any spacecraft
            mode_changed = false;
            for i_SC = 1:mission.num_SC
                current_mode =
mission.true_SC{i_SC}.software_SC_executive.this_sc_mode;
                if ~strcmp(current_mode, obj.last_mode{i_SC})
                    mode_changed = true;
                    obj.last_mode{i_SC} = current_mode;
                end
            end

            % Update visualization if time interval has elapsed OR mode
has changed
            if (mission.true_time.time - obj.last_viz_update_time >=
obj.viz_update_interval) || mode_changed
                % Update visualization with attitude rotation and store
the time
                func_visualize_SC(obj, mission, true);
                obj.last_viz_update_time = mission.true_time.time;

                % Force display update without blocking execution
                drawnow limitrate;
            end
        end
    end
```

[ ] Methods: Visualize Simulation Data

Visualize all simulation data

```
    function obj = func_visualize_simulation_data(obj, mission)
        % First, ensure we're not keeping any unnecessary figures open
        close all
        mission.flag_stop_sim = 1;

        % Close all video files
        if (obj.plot_parameters.flag_save_video == 1)
            if isfield(mission.storage.plot_parameters, 'myVideo')
                close(obj.plot_parameters.myVideo);
            end

            for i_SC = 1:1:mission.num_SC
                % Close Camera video files
                for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_camera
                    if
isfield(mission.true_SC{i_SC}.true_SC_camera{i_HW}.data, 'myVideo')

close(mission.true_SC{i_SC}.true_SC_camera{i_HW}.data.myVideo);
                    end
```

```
                    end

                    % Close Radar video files
                    for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_science_radar
                        if
isfield(mission.true_SC{i_SC}.true_SC_science_radar{i_HW}.data, 'myVideo')

close(mission.true_SC{i_SC}.true_SC_science_radar{i_HW}.data.myVideo);
                        end
                    end
                end
            end

            % Memory optimization: create a function to run between plots to
cleanup memory
            function cleanup_memory()
                drawnow limitrate;  % Flush graphics queue and allow MATLAB to
reclaim memory
                % More can be added here in case of need !
            end

            % Process one spacecraft at a time to limit memory usage
            for i_SC = 1:1:mission.num_SC
                % Basic plots for all spacecraft (minimal memory use)
                % Orbit Vizualization (shared plot)

                if i_SC == 1
                    % Shared for all spacecraft
                    fprintf('Plotting orbit visualization...\n');
                    func_plot_orbit_visualization(mission);
                    cleanup_memory();
                end

                % Spacecraft-specific plots
                fprintf('Plotting SC%d orbit estimator...\n', i_SC);
                func_plot_orbit_estimator(mission, i_SC);
                cleanup_memory();

                fprintf('Plotting SC%d orbital control performance...\n',
i_SC);
                func_plot_orbital_control_performance(mission, i_SC);
                cleanup_memory();

                fprintf('Plotting SC%d attitude visualization...\n', i_SC);
                func_plot_attitude_visualization(mission, i_SC);
                cleanup_memory();

                fprintf('Plotting SC%d attitude actuator performance...\n',
i_SC);
                func_plot_attitude_actuator_performance(mission, i_SC);
                cleanup_memory();

                fprintf('Plotting SC%d power visualization...\n', i_SC);
```

```
                func_plot_power_visualization(mission, i_SC);
                cleanup_memory();

                fprintf('Plotting SC%d individual power consumption...\n',
 i_SC);
                func_plot_individual_power_consumption(mission, i_SC);
                cleanup_memory();

                fprintf('Plotting SC%d data handling visualization...\n',
 i_SC);
                func_plot_data_handling_visualization(mission, i_SC);
                cleanup_memory();

                fprintf('Plotting SC%d individual data generation...\n',
 i_SC);
                func_plot_individual_data_usage(mission, i_SC);
                cleanup_memory();

                fprintf('Plotting software executive visualization...\n');
                func_plot_software_executive_visualization(mission, i_SC);
                cleanup_memory();

                % Telecom Viz
                if
 mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_communication_link
 > 0
                    fprintf('Plotting SC%d telecom...\n', i_SC);
                    func_plot_telecom(mission, i_SC);
                    cleanup_memory();
                end

                % Radar Viz
                for i_HW =
 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_science_radar
                    fprintf('Plotting SC%d radar %d coverage...\n', i_SC,
 i_HW);

 func_visualize_SC_radar_coverage_during_sim(mission.true_SC{i_SC}.true_SC_science_radar{i
 mission, i_SC, i_HW);
                    cleanup_memory();
                end
            end
        end

    end

end
```

Published with MATLAB® R2022a

3.2 True_Ground_Station

Table of Contents

Class: True_Ground_Station

Tracks the data sent and recieved by Ground Station

```
classdef True_Ground_Station < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        num_GS_radio_antenna % [integer] Number of GS Radio Antenna
```

[ ] Properties: Variables Computed Internally

```
        instantaneous_data_transmitted % [kb] Data transmitted by GS over
 mission.true_time.time_step sec

        total_data_transmitted % [kb] Data transmitted by GS over time

        instantaneous_data_received % [kb] Data received by GS over
 mission.true_time.time_step sec

        total_data_received % [kb] Data received by GS over time

        list_HW_data_transmitted % List of HW that transmitted data

        array_HW_data_transmitted % [kb] Total data transmitted by this HW

        list_HW_data_received % List of HW that received data

        array_HW_data_received % [kb] Total data received by this HW
```

```
        warning_counter % [integer] Counter stops the warning after 10
displays

        data % Other useful data
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_Ground_Station(init_data, mission)

            obj.num_GS_radio_antenna = init_data.num_GS_radio_antenna;

            obj.instantaneous_data_transmitted = 0; % [kb]
            obj.total_data_transmitted = 0; % [kb]
            obj.instantaneous_data_received = 0; % [kb]
            obj.total_data_received = 0; % [kb]

            obj.list_HW_data_transmitted = [];
            obj.array_HW_data_transmitted = [];
            obj.list_HW_data_received = [];
            obj.array_HW_data_received = [];

            obj.warning_counter = 0;

            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end

            % Initialize Variables to store
            obj.store = [];

            obj.store.instantaneous_data_transmitted =
zeros(mission.storage.num_storage_steps,
length(obj.instantaneous_data_transmitted));
            obj.store.instantaneous_data_received =
zeros(mission.storage.num_storage_steps,
length(obj.instantaneous_data_received));
```

```
            obj.store.total_data_transmitted =
zeros(mission.storage.num_storage_steps, length(obj.total_data_transmitted));
            obj.store.total_data_received =
zeros(mission.storage.num_storage_steps, length(obj.total_data_received));

        end
```

[ ] Methods: Initialize list_HW_data_transmitted

Initialize list_HW_data_transmitted for HW and Classes

```
        function obj = func_initialize_list_HW_data_transmitted(obj,
equipment, mission)

            this_name = equipment.name;
            flag_name_exisits = 0;

            for i = 1:1:length(obj.list_HW_data_transmitted)
                if strcmp( obj.list_HW_data_transmitted{i}, this_name )
                    flag_name_exisits = 1;
                end
            end

            if flag_name_exisits == 0
                i = length(obj.list_HW_data_transmitted);
                obj.list_HW_data_transmitted{i+1} = this_name;

                if isprop(equipment, 'instantaneous_data_rate_transmitted')
                    this_instantaneous_data_transmitted
= (equipment.instantaneous_data_rate_transmitted *
mission.true_time.time_step); % [kb]
                elseif
isprop(equipment, 'instantaneous_data_transmitted_per_sample')
                    this_instantaneous_data_transmitted =
equipment.instantaneous_data_transmitted_per_sample; % [kb]
                else
                    error('Data transmitted incorrect!')
                end

                obj.array_HW_data_transmitted(1,i+1) =
this_instantaneous_data_transmitted; % [kb]
            end

        end
```

[ ] Methods: Initialize list_HW_data_received

Initialize list_HW_data_received for HW and Classes

```
        function obj = func_initialize_list_HW_data_received(obj, equipment,
mission)

            this_name = equipment.name;
```

```
            flag_name_exisits = 0;

            for i = 1:1:length(obj.list_HW_data_received)
                if strcmp( obj.list_HW_data_received{i}, this_name )
                    flag_name_exisits = 1;
                end
            end

            if flag_name_exisits == 0
                i = length(obj.list_HW_data_received);
                obj.list_HW_data_received{i+1} = this_name;

                if isprop(equipment, 'instantaneous_data_rate_received')
                    this_instantaneous_data_received = 
(equipment.instantaneous_data_rate_received * mission.true_time.time_step); % 
[kb]
                elseif 
isprop(equipment, 'instantaneous_data_received_per_sample')
                    this_instantaneous_data_received = 
equipment.instantaneous_data_received_per_sample; % [kb]
                else
                    error('Data received incorrect!')
                end

                obj.array_HW_data_received(1,i+1) = 
this_instantaneous_data_received; % [kb]
            end

        end
```

[ ] Methods: Initialize Store

Initialize store of array_HW_data_transmitted and array_HW_data_received

```
        function obj = func_initialize_store_HW_data_transmitted_received(obj, 
mission)

            obj.store.list_HW_data_transmitted = obj.list_HW_data_transmitted;
            obj.store.list_HW_data_received = obj.list_HW_data_received;

            obj.store.array_HW_data_transmitted = 
zeros(mission.storage.num_storage_steps, 
length(obj.array_HW_data_transmitted));
            obj.store.array_HW_data_received = 
zeros(mission.storage.num_storage_steps, length(obj.array_HW_data_received));

            obj = func_update_true_ground_station_store(obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_ground_station_store(obj, mission)

            if mission.storage.flag_store_this_time_step == 1

obj.store.instantaneous_data_transmitted(mission.storage.k_storage,:) =
obj.instantaneous_data_transmitted; % [kb]

obj.store.instantaneous_data_received(mission.storage.k_storage,:) =
obj.instantaneous_data_received; % [kb]

                obj.store.total_data_transmitted(mission.storage.k_storage,:)
= obj.total_data_transmitted; % [kb]
                obj.store.total_data_received(mission.storage.k_storage,:) =
obj.total_data_received; % [kb]


obj.store.array_HW_data_transmitted(mission.storage.k_storage,:) =
obj.array_HW_data_transmitted; % [kb]
                obj.store.array_HW_data_received(mission.storage.k_storage,:)
= obj.array_HW_data_received; % [kb]
            end

        end
```

[ ] Methods: Main

Main Ground Station code

```
        function obj = func_main_true_ground_station(obj, mission, i_SC)

            obj.total_data_transmitted = obj.total_data_transmitted +
obj.instantaneous_data_transmitted; % [kb]
            obj.total_data_received = obj.total_data_received +
obj.instantaneous_data_received; % [kb]

            % Store
            obj = func_update_true_ground_station_store(obj, mission);

            % Reset All Variables
            obj.instantaneous_data_transmitted = 0; % [kb]
            obj.instantaneous_data_received = 0; % [kb]

        end
```

[ ] Methods: Update Instantaneous Data Transmitted

Updates instantaneous_data_transmitted by all HW and Classes

```
        function obj = func_update_instantaneous_data_transmitted(obj,
equipment, mission)
```

```
            if isprop(equipment, 'instantaneous_data_rate_transmitted')
                this_instantaneous_data_transmitted
= (equipment.instantaneous_data_rate_transmitted *
mission.true_time.time_step); % [kb]
            elseif
isprop(equipment, 'instantaneous_data_transmitted_per_sample')
                this_instantaneous_data_transmitted =
equipment.instantaneous_data_transmitted_per_sample; % [kb]
            else
                error('Data transmitted incorrect!')
            end

            obj.instantaneous_data_transmitted =
obj.instantaneous_data_transmitted + this_instantaneous_data_transmitted; %
[kb]

            this_name = equipment.name;
            flag_name_exisits = 0;
            this_idx = 0;

            for i = 1:1:length(obj.list_HW_data_transmitted)
                if strcmp( obj.list_HW_data_transmitted{i}, this_name )
                    flag_name_exisits = 1;
                    this_idx = i;
                end
            end

            if flag_name_exisits == 0
                error('HW not found!')
            else
                obj.array_HW_data_transmitted(1,this_idx)
= obj.array_HW_data_transmitted(1,this_idx) +
this_instantaneous_data_transmitted; % [kb]
            end

        end
```

[ ] Methods: Update Instantaneous Data Received

Updates instantaneous_data_received by all HW and Classes

```
        function obj = func_update_instantaneous_data_received(obj, equipment,
mission)

            if isprop(equipment, 'instantaneous_data_rate_received')
                this_instantaneous_data_received =
(equipment.instantaneous_data_rate_received * mission.true_time.time_step); %
[kb]
            elseif isprop(equipment, 'instantaneous_data_received_per_sample')
                this_instantaneous_data_received =
equipment.instantaneous_data_received_per_sample; % [kb]
```

```
            else
                error('Data received incorrect!')
            end

            obj.instantaneous_data_received = obj.instantaneous_data_received
 + this_instantaneous_data_received; % [kb]

            this_name = equipment.name;
            flag_name_exisits = 0;
            this_idx = 0;

            for i = 1:1:length(obj.list_HW_data_received)
                if strcmp( obj.list_HW_data_received{i}, this_name )
                    flag_name_exisits = 1;
                    this_idx = i;
                end
            end

            if flag_name_exisits == 0
                error('HW not found!')
            else
                obj.array_HW_data_received(1,this_idx) =
 obj.array_HW_data_received(1,this_idx) + this_instantaneous_data_received; %
 [kb]
            end

        end

    end

end
```

Published with MATLAB® R2022a

3.3 True_GS_Radio_Antenna

Table of Contents

Class: True_GS_Radio_Antenna

Tracks the GS's Radio Antennas

```
classdef True_GS_Radio_Antenna < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        antenna_type % [string]
        % - 'Dipole'
        % - 'High Gain'

        mode_true_GS_radio_antenna_selector % [string]
        % - TX
        % - RX

        % Optional (only for Link Margin Calculations)

        antenna_gain % [dB] gain of Earth receiver

        noise_temperature % [K] temperature noise

        beamwidth % [MHz] receiver beamwwidth

        energy_bit_required % [dB] Minimum energy bit required

        line_loss % [dB] Loss due to pointing or others

        coding_gain % [dB] Coding gain
```

[ ] Properties: Variables Computed Internally

```
        name % [string] 'GS Radio Antenna i'
```

```
        health % [integer] Health of sensor/actuator
        % - 0. Switched off
        % - 1. Switched on, works nominally

        flag_executive % [Boolean] Executive has told this sensor/actuator to
 do its job

        instantaneous_data_rate_transmitted % [kbps] : Data rate, in kilo bits
 per sec (kbps) due to RX

        instantaneous_data_rate_received % [kbps] : Data rate, in kilo bits
 per sec (kbps) due to TX

        data % Other useful data
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_GS_Radio_Antenna(init_data, mission, i_HW)

            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
                obj.name = ['GS Radio Antenna ',num2str(i_HW)];
            end

            obj.health = 1;
            obj.flag_executive = 0;

            obj.antenna_type = init_data.antenna_type;

            obj.mode_true_GS_radio_antenna_selector =
 init_data.mode_true_GS_radio_antenna_selector;

            if isfield(init_data, 'antenna_gain')

                obj.antenna_gain = init_data.antenna_gain; % [dB]
                obj.noise_temperature = init_data.noise_temperature; % [K]
                obj.beamwidth = init_data.beamwidth; % [MHz]
```

```
            obj.energy_bit_required = init_data.energy_bit_required; %
[dB]
            obj.line_loss = init_data.line_loss; % [dB]
            obj.coding_gain = init_data.coding_gain; % [dB]

        end

        obj.instantaneous_data_rate_transmitted = 0; % [kbps]
        obj.instantaneous_data_rate_received = 0; % [kbps]

        if isfield(init_data, 'data')
            obj.data = init_data.data;
        else
            obj.data = [];
        end

        % Initialize Variables to store: flag_executive mode_TX_RX
        obj.store = [];

        obj.store.flag_executive =
zeros(mission.storage.num_storage_steps, length(obj.flag_executive)); %
[integer]
        obj.store.mode_TX_RX = zeros(mission.storage.num_storage_steps,
1); % [integer]
        obj.store.instantaneous_data_rate_transmitted =
zeros(mission.storage.num_storage_steps,
length(obj.instantaneous_data_rate_transmitted)); % [kbps]
        obj.store.instantaneous_data_rate_received =
zeros(mission.storage.num_storage_steps,
length(obj.instantaneous_data_rate_received)); % [kbps]

        % Update Storage
        obj = func_update_true_GS_radio_antenna_store(obj, mission);

        % Update Ground Station Class (Generated and Removed)

func_initialize_list_HW_data_transmitted(mission.true_ground_station, obj,
mission);

        func_initialize_list_HW_data_received(mission.true_ground_station,
obj, mission);

    end
```

[ ] Methods: Store

Update the store variable

```
    function obj = func_update_true_GS_radio_antenna_store(obj, mission)

        if mission.storage.flag_store_this_time_step == 1
            obj.store.flag_executive(mission.storage.k_storage,:) =
obj.flag_executive; % [integer]
```

```
obj.store.instantaneous_data_rate_transmitted(mission.storage.k_storage,:) =
obj.instantaneous_data_rate_transmitted; % [kbps]

obj.store.instantaneous_data_rate_received(mission.storage.k_storage,:) =
obj.instantaneous_data_rate_received; % [kbps]

                switch obj.mode_true_GS_radio_antenna_selector
                    case 'TX'
                        obj.store.mode_TX_RX(mission.storage.k_storage,1) = 1;
                    case 'RX'
                        obj.store.mode_TX_RX(mission.storage.k_storage,1) = 2;
                    otherwise
                        error('Should not reach here!')
                end

            end

        end
```

[ ] Methods: Main

Update Camera

```
        function obj = func_main_true_GS_radio_antenna(obj, mission)

            if (obj.flag_executive == 1) && (obj.health == 1)
                % TX or RX Data

                % Update SC Data Handling Class (Generated and Removed)

func_update_instantaneous_data_transmitted(mission.true_ground_station, obj,
mission);


func_update_instantaneous_data_received(mission.true_ground_station, obj,
mission);

            else
                % Do nothing

            end

            % Update Storage
            obj = func_update_true_GS_radio_antenna_store(obj, mission);

            % Reset All Variables
            obj.flag_executive = 0;
            obj.instantaneous_data_rate_transmitted = 0; % [kbps]
            obj.instantaneous_data_rate_received = 0; % [kbps]

        end

    end
```

```
end
```

Published with MATLAB® R2022a

3.4 True_Solar_System

Table of Contents

Class: True_Solar_System

Tracks the position of Sun, Earth, Moon, etc. and other useful panetary bodies

```
classdef True_Solar_System < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        num_SS_body
```

[ ] Properties: Variables Computed Internally

```
        SS_body % Data about selected SS body
        % - name
        % - radius [km]
        % - mu [km^3 sec^-2]
        % - mass [kg]
        % - position [km] wrt Sun-centered J2000
        % - velocity [km/sec] wrt Sun-centered J2000
        % - position_array % [km] Position array wrt Sun-centered J2000,
 corresponding to time array in mission.true_time.time_position_array
        % - rgb_color [string] Used for plotting

        solar_constant_AU % [W/m^2]
        AU_distance % [km]
        light_speed % [m/sec]
        gravitational_constant % [km^3 kg^{#1} s^{#2}]

        index_Sun % [integer] : Index of Sun
        index_Earth % [integer] : Index of Earth
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_Solar_System(init_data, mission)

            obj.solar_constant_AU = 1361; % [W/m^2]
            obj.AU_distance = 1.49598e8; % [km]
            obj.light_speed = 299792458; % [m/sec]
            obj.gravitational_constant = 6.67430e-20; % [km^3 kg^{#1} s^{#2}]

            obj.num_SS_body = length(init_data.SS_body_names);
            obj.SS_body = [];

            all_SS_body_data = func_load_all_SS_body_data(obj);

            for i = 1:1:obj.num_SS_body

                this_SS_body_name =
 convertStringsToChars(init_data.SS_body_names(i));

                for j = 1:1:length(all_SS_body_data)

                    if strcmp(this_SS_body_name, all_SS_body_data{j}.name)
                        obj.SS_body{i} = all_SS_body_data{j};
                    end

                end

                obj.SS_body{i}.position = zeros(1,3); % [km]
                obj.SS_body{i}.velocity = zeros(1,3); % [km/sec]
                obj.SS_body{i}.position_array =
 zeros( mission.true_time.num_time_steps_position_array,3); % [km]


                if strcmp(obj.SS_body{i}.name, 'Sun')
                    obj.index_Sun = i;
                end

                if strcmp(obj.SS_body{i}.name, 'Earth')
                    obj.index_Earth = i;
```

```
            end

        end

        % Update Position and Velocity
        cspice_furnsh('../../MuSCAT_Supporting_Files/SPICE/de440s.bsp')

        obj = func_main_true_solar_system(obj, mission);


        % Initialize Variables to store position and velocity of each body
        obj.store = [];

        for i = 1:1:obj.num_SS_body

            obj.store.SS_body{i}.name = obj.SS_body{i}.name;
            obj.store.SS_body{i}.position =
zeros(mission.storage.num_storage_steps, length(obj.SS_body{i}.position));
            obj.store.SS_body{i}.velocity =
zeros(mission.storage.num_storage_steps, length(obj.SS_body{i}.velocity));

        end

        obj = func_update_solar_system_store(obj, mission);

    end
```

[ ] Methods: Store

Update the store variable

```
    function obj = func_update_solar_system_store(obj, mission)

        if mission.storage.flag_store_this_time_step == 1
            for i = 1:1:obj.num_SS_body
                obj.store.SS_body{i}.position(mission.storage.k_storage,:)
= obj.SS_body{i}.position; % [km]
                obj.store.SS_body{i}.velocity(mission.storage.k_storage,:)
= obj.SS_body{i}.velocity; % [km/sec]
            end
        end

    end
```

[ ] Methods: Main

% Function to update position of Sun, Earth, Moon, etc. ... given current time

```
    function obj = func_main_true_solar_system(obj, mission)

        for i = 1:1:obj.num_SS_body
```

```
                body_pos_vel_this_time =
cspice_spkezr(obj.SS_body{i}.spice_name,mission.true_time.date,'J2000','NONE','SUN');

                obj.SS_body{i}.position = body_pos_vel_this_time(1:3,1)'; %
[km]
                obj.SS_body{i}.velocity = body_pos_vel_this_time(4:6,1)'; %
[km]

                body_pos_vel_array = (cspice_spkezr(obj.SS_body{i}.name,
mission.true_time.prev_date +
mission.true_time.time_position_array' ,'J2000','NONE','SUN'))';
                obj.SS_body{i}.position_array = body_pos_vel_array(:,1:3);

            end

            % Store
            obj = func_update_solar_system_store(obj, mission);

        end
```

[ ] Methods: Load Data

Store all useful data about all SS bodies

```
        function all_SS_body_data = func_load_all_SS_body_data(obj)

            all_SS_body_data = [];
            k = 0;

            % Sun's Data
            this_data = [];
            this_data.name = 'Sun';
            this_data.spice_name = '10'; % [string] : Body's SPICE Name
            this_data.radius = 6.95700e5; % [km]
            this_data.mu = 1.32712440018e11; % [km^3 sec^-2]
            this_data.mass = 1.9885e30; % [kg]
            this_data.rgb_color = 'Gold'; % [string]
            k = k + 1;
            all_SS_body_data{k} = this_data;

            % Mercury's Data
            this_data = [];
            this_data.name = 'Mercury';
            this_data.spice_name = '199'; % [string] : Body's SPICE Name
            this_data.radius = 2.4397e3; % [km] https://en.wikipedia.org/wiki/
Mercury_(planet)
            this_data.mu = 2.2032e4; % [km^3 sec^-2] https://en.wikipedia.org/
wiki/Standard_gravitational_parameter
            this_data.mass = 3.3011e23; % [kg]
            this_data.rgb_color = 'Silver'; % [string]
            k = k + 1;
            all_SS_body_data{k} = this_data;
```

```
        % Venus's Data
        this_data = [];
        this_data.name = 'Venus';
        this_data.spice_name = '299'; % [string] : Body's SPICE Name
        this_data.radius = 6.0518e3; % [km] https://en.wikipedia.org/wiki/
Venus
        this_data.mu = 3.24859e5; % [km^3 sec^-2] https://
en.wikipedia.org/wiki/Standard_gravitational_parameter
        this_data.mass = 4.8675e24; % [kg]
        this_data.rgb_color = 'Yellow'; % [string]
        k = k + 1;
        all_SS_body_data{k} = this_data;

        % Earth's Data
        this_data = [];
        this_data.name = 'Earth';
        this_data.spice_name = '399'; % [string] : Body's SPICE Name
        this_data.radius = 6.371e3; % [km]
        this_data.mu = 3.986004418e5; % [km^3 sec^-2] https://
en.wikipedia.org/wiki/Standard_gravitational_parameter
        this_data.mass = 5.9722e24; % [kg]
        this_data.rgb_color = 'Navy'; % [string]
        k = k + 1;
        all_SS_body_data{k} = this_data;

        % Moon's Data
        this_data = [];
        this_data.name = 'Moon';
        this_data.spice_name = '301'; % [string] : Body's SPICE Name
        this_data.radius = 1.7374e3; % [km]
        this_data.mu = 4.9048695e3; % [km^3 sec^-2] https://
en.wikipedia.org/wiki/Standard_gravitational_parameter
        this_data.mass = 7.342e22; % [kg]
        this_data.rgb_color = 'Silver'; % [string]
        k = k + 1;
        all_SS_body_data{k} = this_data;

        % Mars's Data
        this_data = [];
        this_data.name = 'Mars';
        this_data.spice_name = '4'; % [string] : Body's SPICE Name
        this_data.radius = 3.3895e3; % [km] https://en.wikipedia.org/wiki/
Mars
        this_data.mu = 4.282837e4; % [km^3 sec^-2] https://
en.wikipedia.org/wiki/Standard_gravitational_parameter
        this_data.mass = 6.4171e23; % [kg]
        this_data.rgb_color = 'DarkRed'; % [string]
        k = k + 1;
        all_SS_body_data{k} = this_data;

        % Jupiter's Data
        this_data = [];
        this_data.name = 'Jupiter';
        this_data.spice_name = '5'; % [string] : Body's SPICE Name
```

```
            this_data.radius = 6.9911e4; % [km] https://en.wikipedia.org/wiki/
Jupiter
            this_data.mu = 1.26686534e8; % [km^3 sec^-2] https://
en.wikipedia.org/wiki/Standard_gravitational_parameter
            this_data.mass = 1.8982e27; % [kg]
            this_data.rgb_color = 'Orange'; % [string]
            k = k + 1;
            all_SS_body_data{k} = this_data;

            % Saturn's Data
            this_data = [];
            this_data.name = 'Saturn';
            this_data.spice_name = '699'; % [string] : Body's SPICE Name
            this_data.radius = 5.8232e4; % [km] https://en.wikipedia.org/wiki/
Saturn
            this_data.mu = 3.7931187e7; % [km^3 sec^-2] https://
en.wikipedia.org/wiki/Standard_gravitational_parameter
            this_data.mass = 5.6834e26; % [kg]
            this_data.rgb_color = 'Goldenrod'; % [string]
            k = k + 1;
            all_SS_body_data{k} = this_data;

            % Mimas's Data
            this_data = [];
            this_data.name = 'Mimas';
            this_data.spice_name = '601'; % [string] : Body's SPICE Name
            this_data.radius = 1.982e2; % [km] https://en.wikipedia.org/wiki/
Mimas
            this_data.mass = 3.75094e19; % [kg]
            this_data.mu = obj.gravitational_constant * this_data.mass; %
 [km^3 sec^-2]
            this_data.rgb_color = 'Gray'; % [string]
            k = k + 1;
            all_SS_body_data{k} = this_data;

            % Enceladus's Data
            this_data = [];
            this_data.name = 'Enceladus';
            this_data.spice_name = '602'; % [string] : Body's SPICE Name
            this_data.radius = 2.521e2; % [km] https://en.wikipedia.org/wiki/
Enceladus
            this_data.mass = 1.080318e20; % [kg]
            this_data.mu = obj.gravitational_constant * this_data.mass; %
 [km^3 sec^-2]
            this_data.rgb_color = 'Gray'; % [string]
            k = k + 1;
            all_SS_body_data{k} = this_data;

            % Tethys's Data
            this_data = [];
            this_data.name = 'Tethys';
            this_data.spice_name = '603'; % [string] : Body's SPICE Name
            this_data.radius = 5.614e2; % [km] https://en.wikipedia.org/wiki/
Tethys_(moon)
```

```
            this_data.mass = 6.1749e20; % [kg]
            this_data.mu = obj.gravitational_constant * this_data.mass; %
 [km^3 sec^-2]
            this_data.rgb_color = 'Gray'; % [string]
            k = k + 1;
            all_SS_body_data{k} = this_data;

            % Dione's Data
            this_data = [];
            this_data.name = 'Dione';
            this_data.spice_name = '604'; % [string] : Body's SPICE Name
            this_data.radius = 5.31e2; % [km] https://en.wikipedia.org/wiki/
Dione_(moon)
            this_data.mass = 1.0954868e21; % [kg]
            this_data.mu = obj.gravitational_constant * this_data.mass; %
 [km^3 sec^-2]
            this_data.rgb_color = 'Gray'; % [string]
            k = k + 1;
            all_SS_body_data{k} = this_data;

            % Rhea's Data
            this_data = [];
            this_data.name = 'Rhea';
            this_data.spice_name = '605'; % [string] : Body's SPICE Name
            this_data.radius = 7.635e2; % [km] https://en.wikipedia.org/wiki/
Rhea_(moon)
            this_data.mass = 2.3064854e21; % [kg]
            this_data.mu = obj.gravitational_constant * this_data.mass; %
 [km^3 sec^-2]
            this_data.rgb_color = 'Gray'; % [string]
            k = k + 1;
            all_SS_body_data{k} = this_data;

            % Titan's Data
            this_data = [];
            this_data.name = 'Titan';
            this_data.spice_name = '606'; % [string] : Body's SPICE Name
            this_data.radius = 2.57473e3; % [km] https://en.wikipedia.org/
wiki/Titan_(moon)
            this_data.mass = 1.3452e23; % [kg]
            this_data.mu = obj.gravitational_constant * this_data.mass; %
 [km^3 sec^-2]
            this_data.rgb_color = 'Gray'; % [string]
            k = k + 1;
            all_SS_body_data{k} = this_data;

            % Hyperion's Data
            this_data = [];
            this_data.name = 'Hyperion';
            this_data.spice_name = '607'; % [string] : Body's SPICE Name
            this_data.radius = 1.35e2; % [km] https://en.wikipedia.org/wiki/
Hyperion_(moon)
            this_data.mass = 5.5510e18; % [kg]
```

```
            this_data.mu = obj.gravitational_constant * this_data.mass; %
 [km^3 sec^-2]
            this_data.rgb_color = 'Gray'; % [string]
            k = k + 1;
            all_SS_body_data{k} = this_data;

            % Iapetus's Data
            this_data = [];
            this_data.name = 'Iapetus';
            this_data.spice_name = '608'; % [string] : Body's SPICE Name
            this_data.radius = 7.344e2; % [km] https://en.wikipedia.org/wiki/
Iapetus_(moon)
            this_data.mass = 1.80565e21; % [kg]
            this_data.mu = obj.gravitational_constant * this_data.mass; %
 [km^3 sec^-2]
            this_data.rgb_color = 'Gray'; % [string]
            k = k + 1;
            all_SS_body_data{k} = this_data;

            % Phoebe's Data
            this_data = [];
            this_data.name = 'Phoebe';
            this_data.spice_name = '609'; % [string] : Body's SPICE Name
            this_data.radius = 1.065e2; % [km] https://en.wikipedia.org/wiki/
Iapetus_(moon)
            this_data.mass = 8.3123e18; % [kg]
            this_data.mu = obj.gravitational_constant * this_data.mass; %
 [km^3 sec^-2]
            this_data.rgb_color = 'Gray'; % [string]
            k = k + 1;
            all_SS_body_data{k} = this_data;

            % Helene's Data
            this_data = [];
            this_data.name = 'Helene';
            this_data.spice_name = '612'; % [string] : Body's SPICE Name
            this_data.radius = 1.81e2; % [km] https://en.wikipedia.org/wiki/
Iapetus_(moon)
            this_data.mass = 7.1e15; % [kg]
            this_data.mu = obj.gravitational_constant * this_data.mass; %
 [km^3 sec^-2]
            this_data.rgb_color = 'Gray'; % [string]
            k = k + 1;
            all_SS_body_data{k} = this_data;


        end

    end

end
```

Published with MATLAB® R2022a

3.5 True_Stars

Table of Contents

Class: True_Stars

Stars in the sky

```
classdef True_Stars < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        maximum_magnitude % [float] Maximum magnitude of stars visible to
 camera (Optional)
```

[ ] Properties: Variables Computed Internally

```
        num_stars % [integer] Number of stars
        sao_name % [string] Smithsonian Astrophysical Observatory (SAO) Star
 Catalog%s name of star
        magnitude_visible % [float] Magnitude of star
        all_stars_unit_vector % [] Unit vector denoting position of all stars

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class, Initalize from SAO Catalog

```
        function obj = True_Stars(mission)

            YYYY = str2double(mission.true_time.t_initial_date_string(8:11));

            % SAO Star Catalog : http://tdc-www.harvard.edu/catalogs/sao.html
```

```
            fid=fopen('saoNAN.txt');
            M=textscan(fid, '%f %f %f %f %f %f %f %f', 'headerlines', 1);
            fclose(fid);

            obj.sao_name=M{1};
            obj.magnitude_visible=M{3};
            RA=(M{5}+(M{7}*(YYYY-2000)))/15;
            DEC=(M{6}+(M{8}*(YYYY-2000)));

            obj.num_stars = length(obj.sao_name);

            obj.all_stars_unit_vector = zeros(obj.num_stars,3);
            for i=1:1:obj.num_stars

                x_hat = [1 0 0]';

                RA_angle = deg2rad(RA(i)*15); % [rad]
                Dec_angle = deg2rad(DEC(i)); % [rad]

                Rot_Z_star_RA = [cos(RA_angle) -sin(RA_angle) 0;
                    sin(RA_angle)  cos(RA_angle) 0;
                    0                     0 1];

                Rot_Y_star_Dec = [cos(Dec_angle) 0 sin(Dec_angle);
                    0 1 0;
                    -sin(Dec_angle) 0 cos(Dec_angle)];

                Rot_RA_dec = Rot_Y_star_Dec * Rot_Z_star_RA;

                obj.all_stars_unit_vector(i,:) = (Rot_RA_dec*x_hat)';

            end

            obj.maximum_magnitude = max(obj.magnitude_visible);

        end

    end

end
```

Published with MATLAB® R2022a

3.6 True_Target_SPICE

Table of Contents

Class: True_Target_SPICE

Tracks the main target body (uses SPICE for updating position, velocity)

```
classdef True_Target_SPICE < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        name % [string] Name of Target
```

[ ] Properties: Variables Computed Internally

```
        rotation_period % [sec] Period of one rotation
        rotation_rate % [rad/sec]

        gravity_filename % [string] Filename of the Target gravity field in a
 particular format
        gravity_field % Target's gravity field, computed from gravity_filename
        gravity_degree_harmonics % [integer] Degree harmonics of the gravity
 field

        shape_model % Shape model of Target
        % - shape_model.Vertices [m] : Position of vertices
        % - shape_model.Faces : Triplet of vertex indices define a face
        shape_model_type % [string] Type of shape model
        radius % [km] Radius of Target

        pole_RA % [deg] Right Ascension (RA) of Target's pole
        pole_Dec % [deg] Declination (DEC) of Target's pole
        prime_meridian % [deg] : Initial Prime Meridian angle of Target
        rotation_matrix_pole_RA_Dec % Rotation matrix of Target's pole due to
 RA, Dec only (dosent' change with time)
```

```
        rotation_matrix % Rotation matrix of Target from Body Frame to J2000
 (changes with time)

        spice_filename % [string] Target's SPICE FileName
        spice_name % [string] Target's SPICE Name

        mu % [km^3 sec^-2] Target's standard gravitational parameter μ = GM
        mass % [kg] Mass of Target

        position % [km] Current position of Target wrt Sun-centered J2000
        velocity % [km/sec] Current velocity of Target wrt Sun-centered J2000
        position_array % [km] Position array of Target wrt Sun-centered J2000,
 corresponding to time array in mission.true_time.time_position_array
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_Target_SPICE(init_data, mission)

            path_body_data = '../../MuSCAT_Supporting_Files/SB_data/';

            obj.name = init_data.target_name;

            switch obj.name

                case 'Bennu'
                    % obj.name = 'Bennu';

                    obj.rotation_period = 4.296057*3600; % [sec] From https://
en.wikipedia.org/wiki/101955_Bennu

                    % Gravity Model
                    obj.gravity_filename = [path_body_data 'Bennu/
bennu_harmonics_jpl5.txt'];
                    obj.gravity_field = GravityField(obj.gravity_filename); %
 Load gravity field
                    obj.gravity_degree_harmonics = 8;

                    % Shape Model
                    % readObj.m from https://www.mathworks.com/matlabcentral/
fileexchange/18957-readobj
```

```
                    obj_shape = readObj([path_body_data 'Bennu/
bennu_g_06290mm_spc_obj_0000n00000_v008.obj']);
                    % other options are Bennu_OSIRIS-REx_2018.obj (2.6MB) and
 Bennu_OSIRIS-REx_2019.obj (7.2MB)

                    obj.shape_model_type = 'trisurf';
                    obj.shape_model = [];
                    obj.shape_model.Vertices = (1e3)*obj_shape.v; % [m]
                    obj.shape_model.Faces = obj_shape.f.v;

                    % SPICE
                    obj.spice_filename = [path_body_data 'Bennu/
sb-101955-118.bsp'];
                    obj.spice_name = '2101955';

                    % Pole Data
                    obj.pole_RA = 85.65; % [deg]
                    obj.pole_Dec = -60.17; % [deg]
                    obj.prime_meridian = 0; % [deg] (at t_init)


                case 'Apophis'
                    % obj.name = 'Apophis';

                    obj.rotation_period = (360/3.155588020452885e+02)*86400; %
 [sec] From SPICE

                    % Gravity Model
                    obj.gravity_filename = [path_body_data 'Apophis/
Apophis_CMoffset.txt'];
                    obj.gravity_field = GravityField(obj.gravity_filename); %
 Load gravity field
                    obj.gravity_degree_harmonics = 8;

                    % Shape Model
                    obj_shape = readObj([path_body_data 'Apophis/
ApophisModel1.obj']);
                    obj.shape_model = [];
                    obj.shape_model_type = 'trisurf';
                    obj.shape_model.Vertices = obj.gravity_field.R * 1e3 *
 obj_shape.v; % [m]
                    obj.shape_model.Faces = obj_shape.f.v;

                    % SPICE
                    obj.spice_filename = [path_body_data 'Apophis/
apophis.bsp'];
                    obj.spice_name = '2099942';

                    % Pole Data
                    obj.pole_RA = 250; % [deg]
                    obj.pole_Dec = -75; % [deg]
                    obj.prime_meridian = 0; % [deg] (at t_init)
```

```
            case 'Toutatis'
                % obj.name = 'Toutatis';

                % Rotation Rate
                obj.rotation_period = 176*3600; % [sec] https://
en.wikipedia.org/wiki/4179_Toutatis
                obj.rotation_rate = 2*pi/obj.rotation_period; % [rad /sec]
                warning('Toutatis is tumbling!') % http://
abyss.uoregon.edu/~js/ast121/lectures/toutatis.html

                % Gravity Model
                obj.gravity_filename = 'Toutatis_CMoffset.txt';
                obj.gravity_field = GravityField(obj.gravity_filename); %
 Load gravity field
                obj.gravity_degree_harmonics = 8;



                obj_shape =
 readObj([path_body_data 'Toutatis/4179toutatis.tab.obj']);
                obj.shape_model = [];
                obj.shape_model_type = 'trisurf';
                obj.shape_model.Vertices = obj.gravity_field.R * 1e3 *
 obj_shape.v; % [m]
                obj.shape_model.Faces = obj_shape.f.v;



                obj.spice_filename =
 [path_body_data 'Toutatis/2004179.bsp'];
                obj.spice_name = '2004179';

                % Pole Data
                obj.pole_RA = 0; % [deg]
                obj.pole_Dec = 90*pi/180; % [deg]
                obj.prime_meridian = 0; % [deg] (at t_init)

                obj.mass =  1.9e13;
                obj.ode_options =  odeset( 'RelTol',1e-14,'AbsTol',1e-14);


            case 'Itokawa'
                % obj.name = 'Itokawa';

                % Rotation Rate
                obj.rotation_period = 12.132*3600; % [sec] https://
en.wikipedia.org/wiki/25143_Itokawa
                obj.rotation_rate   = 2*pi/obj.rotation_period; % [rad /
sec]

                % Gravity Model
                obj.gravity_filename = 'Itokawa_CMoffset.txt';
                obj.gravity_field = GravityField(obj.gravity_filename); %
 Load gravity field
```

```
                    obj.gravity_degree_harmonics = 8;

                    % Shape Model
                    % Shape model from https://sbn.psi.edu/pds/shape-models/
                    % readObj.m from https://www.mathworks.com/matlabcentral/
fileexchange/18957-readobj
                    obj_shape = readObj([path_body_data 'Itokawa/
Itokawa_ver64q.tab.obj']);
                    obj.shape_model = [];
                    obj.shape_model_type = 'trisurf';
                    obj.shape_model.Vertices = obj.gravity_field.R * 1e3 *
 obj_shape.v; % [m]
                    obj.shape_model.Faces = obj_shape.f.v;

                    obj.spice_filename =
 [path_body_data 'Itokawa/2025143.bsp'];
                    obj.spice_name = '2025143';

                    % Pole Data
                    obj.pole_RA =90.53*pi/180; % [rad]
                    obj.pole_Dec =-66.30*pi/180; % [rad]
                    obj.prime_meridian = 0; % [deg] (at t_init)

                    obj.mass =  3.51e10;
                    obj.ode_options =  odeset( 'RelTol',1e-14,'AbsTol',1e-14);

                case '1996HW1'
                    % obj.name = '1996HW1';

                    % Rotation Rate
                    obj.rotation_period = 8.762*3600; % [sec] https://
echo.jpl.nasa.gov/asteroids/1996HW1/1996hw1.html
                    obj.rotation_rate = 2*pi/obj.rotation_period; % [rad /sec]

                    % Gravity Model
                    obj.gravity_filename = '1996HW1_CMoffset.txt';
                    obj.gravity_field = GravityField(obj.gravity_filename); %
 Load gravity field
                    obj.gravity_degree_harmonics = 8;



                    % Shape Model
                    % Shape model from https://sbn.psi.edu/pds/shape-models/
                    % readObj.m from https://www.mathworks.com/matlabcentral/
fileexchange/18957-readobj
                    obj_shape =
 readObj([path_body_data '1996HW1/1996HW1_a8567.tab.obj']);
                    obj.shape_model = [];
                    obj.shape_model_type = 'trisurf';
                    obj.shape_model.Vertices = obj.gravity_field.R * 1e3 *
 obj_shape.v; % [m]
                    obj.shape_model.Faces = obj_shape.f.v;
```

```
                    obj.spice_filename =
 [path_body_data 'Itokawa/2008567.bsp'];
                    obj.spice_name = '2008567';

                    % Pole Data
                    obj.pole_RA =281*pi/180; % [rad]
                    obj.pole_Dec =-30*pi/180; % [rad]
                    obj.prime_meridian = 0; % [deg] (at t_init)

                    obj.mass =  3.51e10; % I CANT FIND IT
                    obj.ode_options =  odeset( 'RelTol',1e-14,'AbsTol',1e-14);

                case 'Earth'
                    % obj.name = 'Earth';

                    obj.rotation_period = 23.9345 * 3600; % [sec] From
 https://nssdc.gsfc.nasa.gov/planetary/factsheet/earthfact.html

                    % Gravity Model (https://www2.csr.utexas.edu/grace/
gravity/ggm02/)
                    obj.gravity_filename = [path_body_data 'Earth/
ggm02c.txt'];
                    obj.gravity_field = GravityField(obj.gravity_filename); %
 Load gravity field
                    if isfield(mission_init_data,'gravity_degree_harmonics')
                        obj.gravity_degree_harmonics =
 mission_init_data.gravity_degree_harmonics;
                    else
                        obj.gravity_degree_harmonics = 8;
                    end

                    % Shape Model
                    obj.shape_model = [];
                    obj.shape_model_type = 'sphere';
                    obj.shape_model.img = [path_body_data 'Earth/
earth_surface.jpg'];

                    % SPICE
                    obj.spice_name = '399';
                    obj.spice_filename = [path_body_data 'Earth/
earth_200101_990825_predict.bpc'];

                    % Pole Data
                    % From https://nssdc.gsfc.nasa.gov/planetary/factsheet/
earthfact.html
                    ref_date_time = cal2sec('01-JAN-2000 00:12:00');
                    T = (mission_true_time.t_initial_date - ref_date_time) /
 (365.525*86400*100); % Julian centuries from reference date
                    obj.pole_RA = 0.00 - 0.641 * T; % [deg]
                    obj.pole_Dec = 90.00 - 0.557 * T; % [deg]

                    cspice_furnsh([path_body_data 'Earth/naif0012.tls']) %
 Leapseconds kernel file
```

```
                    JD_UTC =
cspice_et2utc(mission_true_time.t_initial_date, 'J', 6); % Format 'JD
2446533.18834276'
                    JD_UTC = strsplit(JD_UTC, ' ');
                    JD_UTC = str2double(JD_UTC{2});
                    JD_UT1 = JD_UTC; % Approximation, UTC is design to follow
UT1 within +/- 0.9s
                    % From NASA TP 20220014814, Sec 4.3.2 Sidereal Motion
                    obj.prime_meridian =
rad2deg(wrapTo2Pi(2*pi*(0.7790572732640 + 1.00273781191135448 * (JD_UT1 -
2451545.0)))); % [deg] (at t_init)

                case 'IBD_Asteroid'
                    % obj.name = 'IBD_Asteroid';

                    obj.rotation_period = (360/3.155588020452885e+02)*86400; %
[sec] From SPICE

                    % Gravity Model
                    obj.gravity_filename = [path_body_data 'IBDAst/
Apophis_CMoffset.txt'];
                    obj.gravity_field = GravityField(obj.gravity_filename); %
Load gravity field
                    obj.gravity_degree_harmonics = 8;

                    % Shape Model
                    obj_shape = readObj([path_body_data 'IBDAst/Bennu-
Radar.obj']);
                    obj.shape_model = [];
                    obj.shape_model_type = 'trisurf';
                    obj.shape_model.Vertices = obj.gravity_field.R * 1e3 *
obj_shape.v; % [m]
                    obj.shape_model.Faces = obj_shape.f.v;

                    % SPICE
                    obj.spice_filename = [path_body_data 'IBDAst/
apophis.bsp'];
                    obj.spice_name = '2099942';

                    % Pole Data
                    obj.pole_RA = 250; % [deg]
                    obj.pole_Dec = -75; % [deg]
                    obj.prime_meridian = 0; % [deg] (at t_init)


                    obj.mass =  6.1e10;
                    obj.ode_options =  odeset( 'RelTol',1e-14,'AbsTol',1e-14);

                case 'Enceladus'
                    % obj.name = 'Enceladus';

                    obj.rotation_period = 1.370218*86400; % [sec] https://
en.wikipedia.org/wiki/Enceladus
```

```
                    % Gravity Model
                    obj.gravity_filename = [path_body_data 'Bennu/
bennu_harmonics_jpl5.txt'];
                    obj.gravity_field = GravityField(obj.gravity_filename); %
 Load gravity field
                    obj.gravity_degree_harmonics = 8;

                    % Shape Model
                    obj.shape_model = [];
                    obj.shape_model_type = 'sphere';
                    obj.shape_model.img = [path_body_data 'Enceladus/
Enceladus_surface_color.jpg'];

                    % SPICE
                    obj.spice_filename = '../../MuSCAT_Supporting_Files/
SC_data/Nightingale/insar_6stride_26d_v7_scpse.bsp';
                    obj.spice_name = '602';

                    % Pole Data
                    obj.pole_RA = 40.7; % [deg]
                    obj.pole_Dec = 83.5; % [deg]
                    obj.prime_meridian = 0; % [deg] (at t_init)

                    % Use SPICE TPC file instead
                    cspice_furnsh('../../MuSCAT_Supporting_Files/SB_data/
Enceladus/enceladus_ssd_230702_v1.tpc')
                    % cspice_furnsh('../../MuSCAT_Supporting_Files/SB_data/
Enceladus/pck_sat441.tpc')
                    % cspice_furnsh('../../MuSCAT_Supporting_Files/SB_data/
Enceladus/pck_sat441_enceladus_frame_edit_only_for_recreation.tpc')

                    obj.mass =  1.080318e20; % [kg]
                    obj.radius = 252; % [km]


                otherwise
                    error('Invalid Target type')
            end

            cspice_furnsh('../../MuSCAT_Supporting_Files/SPICE/de440s.bsp');
            cspice_furnsh(obj.spice_filename);

            obj.rotation_rate = 360/obj.rotation_period; % [deg /sec]

            % Rotation Matrix to Target's Body-fixed Intertial Frame.
            % See details here: https://naif.jpl.nasa.gov/pub/naif/
toolkit_docs/MATLAB/req/pck.html#Orientation%20Models%20used%20by%20PCK
%20Software
            Rot_Z_pole_RA = [
                cosd(90 + obj.pole_RA) -sind(90 + obj.pole_RA) 0;
                sind(90 + obj.pole_RA)  cosd(90 + obj.pole_RA) 0;
                0 0 1];
            Rot_X_pole_Dec = [
                1 0 0;
```

```
                0 cosd(90 - obj.pole_Dec) -sind(90 - obj.pole_Dec);
                0 sind(90 - obj.pole_Dec)  cosd(90 - obj.pole_Dec)];

            obj.rotation_matrix_pole_RA_Dec = Rot_Z_pole_RA * Rot_X_pole_Dec;

            % Other Parameters
            obj.mu = obj.gravity_field.GM; % [km^3 sec^-2]
            obj.radius = obj.gravity_field.R ; % [km]


            % Initialize position, velocity, and rotation matrix

            obj.position = zeros(1,3); % [km]
            obj.velocity = zeros(1,3); % [km/sec]
            obj.position_array =
zeros( mission.true_time.num_time_steps_position_array,3); % [km]

            obj = func_main_true_target(obj, mission);

            % Initialize Variables to store position and velocity of target
            obj.store = [];

            obj.store.name = obj.name;
            obj.store.position = zeros(mission.storage.num_storage_steps,
length(obj.position));
            obj.store.velocity = zeros(mission.storage.num_storage_steps,
length(obj.velocity));

            obj = func_update_target_store(obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_target_store(obj, mission)

            if mission.storage.flag_store_this_time_step == 1
                obj.store.position(mission.storage.k_storage,:) =
obj.position; % [sec]
                obj.store.velocity(mission.storage.k_storage,:) =
obj.velocity; % [sec]
            end

        end
```

[ ] Methods: Main

Update target's position, velocity, rotation matrix for current time

```
        function obj = func_main_true_target(obj,mission)
```

```
            target_pos_vel_this_time =
cspice_spkezr(obj.spice_name,mission.true_time.date,'J2000','NONE','SUN');
            obj.position = target_pos_vel_this_time(1:3)'; % [km]
            obj.velocity = target_pos_vel_this_time(4:6)'; % [km/sec]

            target_pos_vel_array = (cspice_spkezr(obj.spice_name,
mission.true_time.prev_date +
mission.true_time.time_position_array' ,'J2000','NONE','SUN'))';
            obj.position_array = target_pos_vel_array(:,1:3);

            % Small bodies
            obj.rotation_matrix = func_compute_target_rotation_matrix(obj,
mission);

            % Planets
            % obj.rotation_matrix = cspice_pxform('J2000', ['IAU_',obj.name],
mission_true_time.date);

            % Store
            obj = func_update_target_store(obj, mission);
        end
```

[ ] Methods: Compute Rotation Matrix

Update target's rotation matrix for current time

```
        function rot = func_compute_target_rotation_matrix(obj, mission)

            switch obj.name

                case 'Enceladus'
                    fromFrame = 'IAU_ENCELADUS'; % Body-fixed frame of
Enceladus
                    toFrame = 'J2000';           % Inertial frame (e.g.,
J2000)

                    rot = cspice_pxform(fromFrame, toFrame,
mission.true_time.date);

                otherwise
                    theta_PM = obj.prime_meridian + obj.rotation_rate *
(mission.true_time.time - mission.true_time.t_initial);
                    Rot_Z_PM = [
                        cosd(theta_PM) sind(theta_PM) 0;
                        -sind(theta_PM) cosd(theta_PM) 0;
                        0 0 1];
                    rot = Rot_Z_PM*obj.rotation_matrix_pole_RA_Dec; % From
J2000 to Body frame

                    rot = rot'; % From Body frame to J2000
            end
        end

    end
```

```
end
```

Published with MATLAB® R2022a

3.7 True_Time

Table of Contents

Class: True_Time

Keeps track of the all time variables in the simulation

```
classdef True_Time < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        t_initial % [sec] : Start time
        t_final % [sec] : Final time
        time_step % [sec] : Simulation time step
        t_initial_date_string % [string] : Start date of simulation. Format =
 [DD-MMM(words)-YYYY HH-MM-SS].

        time_step_attitude % [sec] : Time step for attitude dynamics
 (Optional)

        print_progress_steps % [integer] : Number of steps to skip between
 printing progress (Optional)

        time_step_position_array % [sec] : Time step for position dynamics
 array (Optional)
```

[ ] Properties: Variables Computed Internally

```
        t_initial_date % [sec from J2000] : Start date of simulation.
```

```
        num_time_steps % [integer] : Number of simulation time steps       #
        time % [sec] : Current true time                                   #
        date % [sec from J2000] : Current true date                        #

        num_time_steps_attitude % [integer] : Number of attitude dynamics loop
 time steps within one simulation time step #
        time_attitude % [sec] : Current true time within attitude dynamics
 loop #

        k % [integer] : Time loop variable                                 #
        k_attitude % [integer] : Attitude Dynamics Time loop variable      #

        num_time_steps_position_array % [integer]
        time_position_array % [sec]

        prev_time % [sec] : Previous true time
    #
        prev_date % [sec from J2000] Previous true date

        data % to store other values
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_Time(init_data)

            obj.t_initial = init_data.t_initial;
            obj.time = obj.t_initial;

            obj.t_final = init_data.t_final;
            obj.time_step = init_data.time_step;

            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end

            obj.num_time_steps = ceil((obj.t_final - obj.t_initial)/
obj.time_step);
```

```
            obj.t_initial_date_string = init_data.t_initial_date_string;
            obj.t_initial_date = cal2sec(obj.t_initial_date_string);
            obj.date = obj.t_initial_date + obj.time; % Seconds from '01-
JAN-2000 00:00:00'

            if isfield(init_data, 'time_step_attitude')
                % time_step_attitude_dynamics has been specified
                obj.time_step_attitude = init_data.time_step_attitude;
            else
                obj.time_step_attitude = obj.time_step;
            end

            obj.num_time_steps_attitude = (obj.time_step/
obj.time_step_attitude);

            if ~isinteger(int32(obj.num_time_steps_attitude))
                error('time_step must be divisble by
 time_step_attitude_dynamics!');
            end

            obj.time_attitude = obj.time;

            obj.k = 0;
            obj.k_attitude = 0;


            if isfield(init_data, 'print_progress_steps')
                % print_progress_steps has been specified
                obj.print_progress_steps = init_data.print_progress_steps;
            else
                obj.print_progress_steps = ceil((obj.num_time_steps)/1000);
            end


            % Create Time Array for Position Dynamics

            if isfield(init_data, 'time_step_position_array')
                obj.time_step_position_array =
 init_data.time_step_position_array;
            else
                obj.time_step_position_array = min([10, obj.time_step,
 obj.time_step_attitude]); % [sec]
            end

            obj.num_time_steps_position_array = (obj.time_step/
obj.time_step_position_array) + 1;

            if ~isinteger(int32(obj.num_time_steps_position_array))
                error('time_step must be divisble by
 time_step_position_array!');
            end

            obj.time_position_array = [0: obj.time_step_position_array :
 obj.time_step]';
```

```
            obj.prev_time = obj.time; % [sec]
            obj.prev_date = obj.date; % [sec from J2000]

        end
```

[ ] Methods: Initialize Store

Initialize the store variable

```
        function obj = func_initialize_time_store(obj, mission)

            % Variables to store: time, date, time_attitude
            obj.store.time = zeros(mission.storage.num_storage_steps,
 length(obj.time));
            obj.store.date = zeros(mission.storage.num_storage_steps,
 length(obj.date));
            obj.store.time_attitude =
 zeros(mission.storage.num_storage_steps_attitude, length(obj.time_attitude));

            % Store first set of variables
            obj = func_update_time_store(obj, mission);
            obj = func_update_time_store_attitude(obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_time_store(obj, mission)

            if mission.storage.flag_store_this_time_step == 1
                obj.store.time(mission.storage.k_storage,:) = obj.time; %
 [sec]
                obj.store.date(mission.storage.k_storage,:) = obj.date; %
 [sec]
            end

        end
```

[ ] Methods: Store Attitude

Update the attitude store variable

```
        function obj = func_update_time_store_attitude(obj, mission)

            if mission.storage.flag_store_this_time_step_attitude == 1
                obj.store.time_attitude(mission.storage.k_storage_attitude,:)
 = obj.time_attitude; % [sec]
            end
```

```
        end
```

[ ] Methods: Main

Function to update current time and date within main loop

```
        function obj = func_update_true_time_date(obj, k)

            obj.k = k;

            obj.prev_time = obj.time; % [sec]
            obj.prev_date = obj.date; % [sec from J2000]

            obj.time = obj.time + obj.time_step;
            obj.date = obj.t_initial_date + obj.time;

            % Print progress
            if mod(obj.k, obj.print_progress_steps) == 0

                % Expected time left
                time_elap = seconds(toc);
                time_per_loop = time_elap / obj.k;
                time_left = time_per_loop * (obj.num_time_steps - obj.k);

                time_sim_elapsed = seconds(obj.time - obj.t_initial);
                time_sim_total = seconds(obj.t_final - obj.t_initial);

                perc = round(time_sim_elapsed / time_sim_total * 100, 1);

                format = 'dd:hh:mm:ss';
                time_elap.Format = format;
                time_left.Format = format;
                time_sim_elapsed.Format = format;
                time_sim_total.Format = format;

                % Base progress message
                progress_msg = ['- Simulation: ', char(time_sim_elapsed), ' /
 ', char(time_sim_total), ' (', num2str(perc),'%),' ...
                    ' Elapsed: ', char(time_elap), ', Left: ',
 char(time_left), ', Total: ', char(time_elap + time_left)];

                % Add memory info every 100 iterations
                if mod(obj.k, obj.print_progress_steps * 100) == 0
                    memoryInfo = evalc('dispmemory()');
                    progress_msg = [progress_msg, '  |  Current Memory Usage
 By Matlab: ', strtrim(memoryInfo)];
                end

                disp(progress_msg)
            end

        end
```

[ ] Methods: Main Attitude

Function to update current time within attitude dyanmics loop

```
        function obj = func_update_true_time_attitude(obj, k_attitude)

            obj.k_attitude = k_attitude;
            obj.time_attitude = obj.time_attitude + obj.time_step_attitude;

        end
```

[ ] Methods: Set Time

Set time to a specific value

```
        function obj = func_set_time(obj, time)

            obj.time = time;
            obj.date = obj.t_initial_date + obj.time;

        end

    end

end
```

Published with MATLAB® R2022a

Chapter 4

SC Physics Based Simulation Layer Classes

4.1 True_SC_ADC

Table of Contents

Class: True_SC_ADC

Tracks the attitude and angular velocity of the SC

```
classdef True_SC_ADC < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        attitude % [quanternion] : Orientation of inertial frame I with
 respect to the body frame B

        angular_velocity % [rad/sec] : Angular velocity of inertial frame I
 with respect to the body frame B

        mode_true_SC_attitude_dynamics_selector % [string] Different attitude
 dynamics modes
        % - 'Rigid' : Use Rigid Body Dynamics
```

[ ] Properties: Variables Computed Internally

```
        rotation_matrix % : Rotation matrix that converts vector in body frame
 B to vector in inertial frame I
        dot_angular_velocity % [rad/sec^2] : Time derivative of
 angular_velocity (needed by RWA)
               % RWA - Reaction Wheels | MT momentum Thrusters?
        control_torque % [Nm] : Control torque about Center of Mass of SC,
 usually generated by MT thrusters and RWA
        disturbance_torque % [Nm] : Disturbance torque about Center of Mass of
 SC
        total_torque % [Nm] - Sum of the two above
```

```
        total_wheel_momentum % [kg#m^2/s] : Total momentum of all reaction
wheels

        ode_options % : Options for Matlab%s ODE function
odeset( RelTol',1e-14,'AbsTol',1e-14)

        plot_handle % : plot handle for attitude visualization
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_ADC(init_data, mission)

            obj.attitude = func_quaternion_properize(init_data.attitude); %
[quaternion]
            obj.angular_velocity = init_data.angular_velocity; % [rad/sec]

            % Compute Rotation Matrix
            obj = func_update_true_SC_ADC_rotation_matrix(obj);

            obj.dot_angular_velocity = [0 0 0];
            obj.control_torque = [0 0 0];
            obj.disturbance_torque = [0 0 0];
            obj.total_wheel_momentum = [0 0 0]; % Initialize as 3x1 vector
            obj.total_torque = [0 0 0];

            obj.ode_options = odeset('RelTol',1e-14,'AbsTol',1e-14);

            obj.mode_true_SC_attitude_dynamics_selector =
init_data.mode_true_SC_attitude_dynamics_selector;

            % Initialize Variables to store: attitude and angular velocity of
SC
            obj.store = [];

            obj.store.attitude =
zeros(mission.storage.num_storage_steps_attitude, length(obj.attitude));
            obj.store.angular_velocity =
zeros(mission.storage.num_storage_steps_attitude,
length(obj.angular_velocity));
```

```
            obj.store.control_torque =
zeros(mission.storage.num_storage_steps_attitude,
length(obj.control_torque));
            obj.store.disturbance_torque =
zeros(mission.storage.num_storage_steps_attitude,
length(obj.disturbance_torque));
            obj.store.total_torque =
zeros(mission.storage.num_storage_steps_attitude, length(obj.total_torque));


            obj = func_update_true_SC_adc_store(obj, mission);
        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_adc_store(obj, mission)
            if mission.storage.flag_store_this_time_step_attitude == 1
                obj.store.attitude(mission.storage.k_storage_attitude,:) =
obj.attitude; % [sec]

obj.store.angular_velocity(mission.storage.k_storage_attitude,:) =
obj.angular_velocity; % [sec]

                obj.store.control_torque(mission.storage.k_storage_attitude,:)
= obj.control_torque; % [sec]

obj.store.disturbance_torque(mission.storage.k_storage_attitude,:) =
obj.disturbance_torque; % [sec]
                obj.store.total_torque(mission.storage.k_storage_attitude,:) =
obj.total_torque; % [sec]
            end
        end
```

[ ] Methods: Main

Update SC's Attitude and Angular Velocity

```
        function obj = func_main_true_SC_attitude(obj, mission, i_SC)

            switch obj.mode_true_SC_attitude_dynamics_selector

                case 'Rigid'

                    % Update disturbance torque is done
                    % in the SRP and GG classes

                    % Update total wheel momentum
                    obj = func_update_total_wheel_momentum(obj, mission,
i_SC);
```

```
                    % Update attitude and angular velocity
                    obj = func_true_SC_attitude_dynamics_rigid(obj, mission,
 i_SC);

                otherwise
                    error('Havent written yet!')

            end

            % Sum torques for storage
            obj.total_torque = obj.control_torque + obj.disturbance_torque;

            % Compute Rotation Matrix
            obj = func_update_true_SC_ADC_rotation_matrix(obj);

            % Store
            obj = func_update_true_SC_adc_store(obj, mission);

            % Reset variables
            obj.control_torque =  [0 0 0];     % [Nm]

            % Reset every main time step
            if (mission.true_time.k_attitude ==
 mission.true_time.num_time_steps_attitude)
                obj.disturbance_torque = [0 0 0]; % Reset torque
            end
        end
```

[ ] Methods: Update Rotation Matrix

Update SC's Rotation Matrix

```
        function obj = func_update_true_SC_ADC_rotation_matrix(obj)

            % Compute Rotation Matrix
            SC_True_e_current = obj.attitude(1:3)/norm(obj.attitude(1:3));
            SC_True_Phi_current = 2*acos(obj.attitude(4)); % [rad]
            obj.rotation_matrix =
 func_create_rotation_matrix(SC_True_e_current, SC_True_Phi_current);

        end
```

[ ] Methods: Rigid Attitude Dynamics

Update SC's Attitude and Angular Velocity

```
        function obj = func_true_SC_attitude_dynamics_rigid(obj, mission,
 i_SC)

            SC_Quaternion_Omega_current = [obj.attitude';
 obj.angular_velocity'];

            this_time_array = [0 mission.true_time.time_step_attitude];
```

```
            [T,X]=ode45(@(t,X) func_ode_attitude_dynamics(t, X, mission,
i_SC), this_time_array, SC_Quaternion_Omega_current, obj.ode_options);

            new_SC_Quaternion_Omega_current = X(end,:);

            obj.attitude =
func_quaternion_properize(new_SC_Quaternion_Omega_current(1:4)); %
[quaternion]
            obj.angular_velocity = new_SC_Quaternion_Omega_current(5:7); %
[rad/sec]

            %retrieve cache
            X_dot = func_ode_attitude_dynamics(this_time_array(end),
new_SC_Quaternion_Omega_current', mission, i_SC);
            obj.dot_angular_velocity = X_dot(5:7)';

        end
```

[ ] Methods: Update Reaction Wheel Momentum

```
        function obj = func_update_total_wheel_momentum(obj, mission, i_SC)
            % Initialize total wheel momentum as a 3x1 vector
            obj.total_wheel_momentum = zeros(3, 1);

            % Loop through all reaction wheels and add their individual
momentum vectors
            for i =
1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_reaction_wheel
                % Each wheel's total_momentum is already a vector in the body
frame
                if
isfield(mission.true_SC{i_SC}.true_SC_reaction_wheel{i}, 'total_momentum')
&& ...

~isempty(mission.true_SC{i_SC}.true_SC_reaction_wheel{i}.total_momentum)
                    obj.total_wheel_momentum = obj.total_wheel_momentum +
mission.true_SC{i_SC}.true_SC_reaction_wheel{i}.total_momentum;
                end
            end
        end

    end

end
```

Published with MATLAB® R2022a

4.2 True_SC_Body

Table of Contents

Class: True_SC_Body

Tracks the SC Body

```
classdef True_SC_Body < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        name % [string] = 'SC j' for jth SC

        mass % : Mass of the SC
        % - dry : Dry mass of the SC, that doesn't change position/attitude
        % - - mass [kg] : Actual mass
        % - - location [m] : Location of this mass in body frame B
        % - - MI_over_m [m^2] : Computed once during initialization, shouldn't
 change with time (NOTE: NOT MULTIPLED BY MASS)

        % - supplement : Positive/negative mass that is added/removed from the
 SC. (e.g. sample collection or projectile) (Optional)

        % - # propellant : Propellant mass of the SC that does change value
 (Optional)
        % Take propellant mass from True_SC_Fuel_Tank

        % - # solar_panel : Solar panel mass of the SC, that doesnot change
 value (Optional)
        % Take solar panel mass from True_SC_Solar_Panel

        total_mass % [kg] : Total mass of the SC
```

```
        mode_COM_selector % Select which COM to use
        % 'given' : Give apriori
        % 'update' : Computed by the code

        location_COM % [m] : Compute CM from above data

        shape_model % : Cell of SC shape models
        % – Vertices [m] : Position of vertices in body frame B
        % – Faces : Triplet of vertex indices define a face
        % – Face_reflectance_factor in [0, 1] : Used for ith face (used for
SRP)
        % - r_CM [m] : CM of this shape
        % - I_through_r_CM [kg m^2] : Intertia matrix of this shape, about its
CM
        % - volume [m^2] : Volume of this shape
        % - Face_center [m] : Center of each Face
        % – Face_normal [unit vector] : Normal out vector of each face (used
for SRP)
        % - Face_area [m^2] : Area of each face
        % - type [string] : Type of shape is used for MI and volume
calculations

        total_volume % [m^3] : Total volume of the SC

        mode_MI_selector % Select which MI to use
        % 'given' : Give apriori
        % 'update' : Computed by the code

        total_MI % [kg m^2] : Total MI of the SC

        num_hardware_exists % Data structure that denotes if a hardware exists
on a SC or not (1 >= HW exists, 0 = It doesn t exist)
        % Initialized to zero using init_num_hardware_exists.m file
        % - num_onboard_clock [integer]
        % - num_sun_sensor [integer]
        % - num_star_tracker [integer]
        % - num_imu [integer]
        % - num_micro_thruster [integer]
        % - num_reaction_wheel [integer]
        % - num_magnetorquer [integer]
        % - num_camera [integer]
        % - num_chemical_thruster [integer]
        % - num_ep_thruster [integer]
        % - num_solar_panel [integer]
        % - num_RTG [integer]
        % - num_battery [integer]
        % - num_PDC [integer]
        % - num_radio_antenna [integer]
        % - num_dte_communication [integer]
        % - num_intersat_communication [integer]
        % - num_onboard_memory [integer]
        % - num_science_radar [integer]
        % - num_science_altimeter [integer]
        % - num_science_telescope [integer]
```

```
        % - num_science_camera [integer]
```

[ ] Properties: Variables Computed Internally

```
        flag_update_SC_body_total_mass_COM_MI % [Boolean] Flag sets if these
 variables should be computed again
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Body(init_data, mission)

            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
                obj.name = ['SC ',num2str(init_data.i_SC)];
            end

            % mass
            obj.mass = [];
            obj.mass.dry{1}.mass = 0; % [kg]
            obj.mass.dry{1}.location = [0 0 0]; % [m]
            obj.mass.dry{1}.MI_over_m = zeros(3,3); % [m^2]

            if isfield(init_data.mass, 'supplement')
                obj.mass.supplement = init_data.mass.supplement;

            else
                obj.mass.supplement{1}.mass = 0;
                obj.mass.supplement{1}.location = [0 0 0]; % [m]
                obj.mass.supplement{1}.MI_over_m = zeros(3,3); % [m^2]
            end

            obj.mass.propellant{1}.mass = 0; % [kg]
            obj.mass.propellant{1}.location = [0 0 0]; % [m]
            obj.mass.propellant{1}.MI_over_m = zeros(3,3); % [m^2]

            obj.mass.solar_panel{1}.mass = 0; % [kg]
            obj.mass.solar_panel{1}.location = [0 0 0]; % [m]
            obj.mass.solar_panel{1}.MI_over_m = zeros(3,3); % [m^2]
```

```
            obj.mode_COM_selector = init_data.mode_COM_selector;

            if strcmp(obj.mode_COM_selector, 'given')
                obj.total_mass = init_data.total_mass; % [kg]
                obj.location_COM = init_data.location_COM; % [m]
                obj.total_volume = init_data.total_volume; % [m^3]
            else

                obj.total_mass = 0; % [kg]
                obj.location_COM = [0 0 0]; % [m]
                obj.total_volume = 0; % [m^3]
            end

            % shape model
            obj.shape_model = init_data.shape_model;


            for i_shape = 1:length(obj.shape_model)
                % warning('Shape model should be a cell of structs with fields
(r_CM, I_over_m, volume, etc)');
                shape = obj.shape_model{i_shape};

                % Center of mass
                r_CM = mean(shape.Vertices, 1); % [m]

                switch obj.shape_model{i_shape}.type

                    case 'cuboid'

                        % Inertia matrix (assume cuboid)
                        L = max(shape.Vertices(:,1)) -
min(shape.Vertices(:,1)); % [m]
                        W = max(shape.Vertices(:,2)) -
min(shape.Vertices(:,2)); % [m]
                        H = max(shape.Vertices(:,3)) -
min(shape.Vertices(:,3)); % [m]
                        I_through_r_CM = diag([1/12*(W^2+H^2), 1/12*(L^2+H^2),
1/12*(L^2+W^2)]); % [m^2]

                        % Volume
                        volume = L*W*H; % [m^3]

                    otherwise
                        error('Havent written yet!')

                end

                % Update
                obj.shape_model{i_shape}.r_CM = r_CM;
                obj.shape_model{i_shape}.I_through_r_CM = I_through_r_CM;
                obj.shape_model{i_shape}.volume = volume;

                % obj.total_volume = obj.total_volume +
obj.shape_model{i_shape}.volume; % [m^3]
```

```
            end

            % compute face orientation + normal vector + area
            for i_shape = 1:length(obj.shape_model)

                shape = obj.shape_model{i_shape};
                Face_center = zeros(size(shape.Faces));
                Face_normal = zeros(size(shape.Faces));
                Face_area = zeros(size(shape.Faces,1),1);

                SC_centroid = mean(shape.Vertices);

                for i=1:size(shape.Faces,1)
                    % face center : [(V1x+V2x+V3x)/3 ; (V1y+V2y+V3y)/3 : (V1z
+V2z+V3z)/3 ]
                    Face_center(i,:) = [

 (shape.Vertices(shape.Faces(i,1),1)+shape.Vertices(shape.Faces(i,2),1)+shape.Vertices(sha

 (shape.Vertices(shape.Faces(i,1),2)+shape.Vertices(shape.Faces(i,2),2)+shape.Vertices(sha

 (shape.Vertices(shape.Faces(i,1),3)+shape.Vertices(shape.Faces(i,2),3)+shape.Vertices(sha
                    % normal vector : cross(V1-V3,V2-V3)
                    normal_vector_unsigned = cross(...
                        shape.Vertices(shape.Faces(i,1),:)-
shape.Vertices(shape.Faces(i,3),:), ...
                        shape.Vertices(shape.Faces(i,2),:)-
shape.Vertices(shape.Faces(i,3),:));
                    normal_vector_unsigned = normal_vector_unsigned/
norm(normal_vector_unsigned);
                    % correct to get normal pointing outward
                    out_vector = (Face_center(i,:)-SC_centroid)/
norm(Face_center(i,:)-SC_centroid); % vector_pointing_out : form SC centroid
 to face centroid
                    if acos(dot(out_vector,normal_vector_unsigned)) > pi/2
                        Face_normal(i,:) = -normal_vector_unsigned;
                    else
                        Face_normal(i,:) = normal_vector_unsigned;
                    end
                    % Face area
                    vertex_index = shape.Faces(i,:); % index of vertices for
 this face
                    a = norm(shape.Vertices(vertex_index(1),:) -
 shape.Vertices(vertex_index(2),:));
                    b = norm(shape.Vertices(vertex_index(2),:) -
 shape.Vertices(vertex_index(3),:));
                    c = norm(shape.Vertices(vertex_index(3),:) -
 shape.Vertices(vertex_index(1),:));
                    s = (a+b+c)/2;                                          %
 semi perimeter
                    Face_area(i) = sqrt(s*(s-a)*(s-b)*(s-c));    % Heron
 formula
                end
```

```
                obj.shape_model{i_shape}.Face_center = Face_center;
                obj.shape_model{i_shape}.Face_normal = Face_normal;
                obj.shape_model{i_shape}.Face_area = Face_area;
            end

            % Add all HW on SC
            obj.num_hardware_exists = init_data.num_hardware_exists;

            % Moment of Intertia
            obj.mode_MI_selector = init_data.mode_MI_selector;

            if strcmp(obj.mode_MI_selector, 'given')
                obj.total_MI = init_data.total_MI; % [kg m^2]
            end

            % Compute dry mass
            if ~strcmp(obj.mode_MI_selector, 'given')

                for i_shape = 1:length(obj.shape_model)
                    obj.mass.dry{i_shape}.mass =
obj.shape_model{i_shape}.mass; % [kg]
                    obj.mass.dry{i_shape}.location =
obj.shape_model{i_shape}.r_CM; % [m]
                    obj.mass.dry{i_shape}.MI_over_m =
obj.shape_model{i_shape}.I_through_r_CM; % [m^2]
                end

                % Compute total mass and COM and MI
                obj = func_update_SC_body_total_mass_COM_MI(obj);
            end

            % Reset Flag
            obj.flag_update_SC_body_total_mass_COM_MI = 0;

            % Initialize Variables to store: total_mass location_COM total_MI
            obj.store = [];

            obj.store.total_mass = zeros(mission.storage.num_storage_steps,
length(obj.total_mass));
            obj.store.location_COM = zeros(mission.storage.num_storage_steps,
length(obj.location_COM));
            obj.store.total_MI = zeros(mission.storage.num_storage_steps, 9);

            obj = func_update_true_SC_body_store(obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_body_store(obj, mission)
```

```
            if mission.storage.flag_store_this_time_step == 1
                obj.store.total_mass(mission.storage.k_storage,:) =
obj.total_mass; % [kg]
                obj.store.location_COM(mission.storage.k_storage,:) =
obj.location_COM; % [m]
                obj.store.total_MI(mission.storage.k_storage,:) =
reshape(obj.total_MI,1,9); % [kg m^2]
            end
        end
```

[ ] Methods: Main

Main function

```
        function obj = func_main_true_SC_body(obj, mission, i_SC)

            % First update fuel and solar panel masses if needed
            if obj.flag_update_SC_body_total_mass_COM_MI == 1
                % Update mass values from fuel tanks and solar panels first
                obj = func_update_SC_body_mass(obj, mission, i_SC);

                % Then compute total mass and COM and MI
                obj = func_update_SC_body_total_mass_COM_MI(obj);
            end

            % Update Store
            obj = func_update_true_SC_body_store(obj, mission);

        end
```

[ ] Methods: Update Total Mass, COM, MI

Update total mass and COM

```
        function obj = func_update_SC_body_total_mass_COM_MI(obj)

            % Reset Flag
            obj.flag_update_SC_body_total_mass_COM_MI = 0;

            % Update Total Mass and COM
            if strcmp(obj.mode_COM_selector, 'update')

                obj.total_mass = 0; % [kg]
                obj.location_COM = [0 0 0]; % [m]

                for i_mass_class = 1:1:4

                    this_mass_class = [];

                    switch i_mass_class

                        case 1
```

```
                    this_mass_class = obj.mass.dry;
                case 2
                    this_mass_class = obj.mass.supplement;
                case 3
                    this_mass_class = obj.mass.propellant;
                case 4
                    this_mass_class = obj.mass.solar_panel;
                otherwise
                    error('this_mass_class does not exist!')
            end

            for i=1:1:length(this_mass_class)
                obj.location_COM = ((obj.total_mass
* obj.location_COM) + (this_mass_class{i}.mass *
this_mass_class{i}.location)); % [kg m]
                obj.total_mass = obj.total_mass +
this_mass_class{i}.mass; % [kg]
                obj.location_COM = (obj.location_COM /
obj.total_mass); % [m]
            end

        end

    end


    % Update MI
    if strcmp(obj.mode_MI_selector, 'update')

        obj.total_MI = zeros(3,3); % [kg m^2]

        for i_mass_class = 1:1:4

            this_mass_class = [];

            switch i_mass_class

                case 1
                    this_mass_class = obj.mass.dry;
                case 2
                    this_mass_class = obj.mass.supplement;
                case 3
                    this_mass_class = obj.mass.propellant;
                case 4
                    this_mass_class = obj.mass.solar_panel;
                otherwise
                    error('this_mass_class does not exist!')
            end

            for i=1:1:length(this_mass_class)

                % Displacement vector from the shape CM to the SC CM
                r_CM_i = obj.location_COM -
this_mass_class{i}.location;
```

```
                    % Parallel Axis Theorem: I_cm_sc = I_cm_shape + m *
(r' * r * I_3 - r * r')
                    I_i = (this_mass_class{i}.mass *
this_mass_class{i}.MI_over_m) + (this_mass_class{i}.mass * ( (r_CM_i *
r_CM_i' * eye(3)) - (r_CM_i' * r_CM_i)));

                    % Add inertia matrix to the total inertia matrix
                    obj.total_MI = obj.total_MI + I_i;

                end

            end

        end

    end
```

[ ] Methods: Update Mass

Update the mass class with solar panel and propellant mass

```
    function obj = func_update_SC_body_mass(obj, mission, i_SC)

        if isfield(mission.true_SC{i_SC}, 'true_SC_solar_panel')
            for i_SP = 1:1:obj.num_hardware_exists.num_solar_panel
                obj.mass.solar_panel{i_SP}.mass =
mission.true_SC{i_SC}.true_SC_solar_panel{i_SP}.mass; % [kg]
                obj.mass.solar_panel{i_SP}.location =
mission.true_SC{i_SC}.true_SC_solar_panel{i_SP}.shape_model.r_CM; % [m]
                obj.mass.solar_panel{i_SP}.MI_over_m =
mission.true_SC{i_SC}.true_SC_solar_panel{i_SP}.shape_model.I_through_r_CM; %
[kg m^2]
            end
        end

        if isfield(mission.true_SC{i_SC}, 'true_SC_fuel_tank')
            for i_FT = 1:1:obj.num_hardware_exists.num_fuel_tank
                % Update propellant mass from fuel tank
                obj.mass.propellant{i_FT}.mass =
mission.true_SC{i_SC}.true_SC_fuel_tank{i_FT}.instantaneous_fuel_mass; % [kg]
                obj.mass.propellant{i_FT}.location =
mission.true_SC{i_SC}.true_SC_fuel_tank{i_FT}.location; % [m]

                % Calculate approximate moment of inertia for a simple
cuboid fuel mass
                % This is a simplified approach - for greater accuracy, a
detailed shape model would be better
                if
~isempty(mission.true_SC{i_SC}.true_SC_fuel_tank{i_FT}.shape_model)
                    % If shape model exists, use it
                    if
isfield(mission.true_SC{i_SC}.true_SC_fuel_tank{i_FT}.shape_model, 'I_through_r_CM')
```

```
                            obj.mass.propellant{i_FT}.MI_over_m =
mission.true_SC{i_SC}.true_SC_fuel_tank{i_FT}.shape_model.I_through_r_CM;
                        else
                            % Approximate as cuboid if dimensions available
                            obj.mass.propellant{i_FT}.MI_over_m = zeros(3,3);
                        end
                    else
                        % Fallback to simple approximation - treat as point
mass with small inertia
                        obj.mass.propellant{i_FT}.MI_over_m = 1e-3 * eye(3); %
[m^2]
                    end

                    % Set flag to update total mass, COM, and MI
                    obj.flag_update_SC_body_total_mass_COM_MI = 1;
                end
            end

        end

    end

end
```

Published with MATLAB® R2022a

4.3 True_SC_Data_Handling

Table of Contents

Class: True_SC_Data_Handling

Tracks the Data Generated onboard the spacecraft

```
classdef True_SC_Data_Handling < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        mode_true_SC_data_handling_selector % [string] Select which Mode to
 run
```

[ ] Properties: Variables Computed Internally

```
        instantaneous_data_change % [kb] Data generated - Data removed over
 mission.true_time.time_step sec

        instantaneous_data_generated % [kb] Data generated by HW and Classes
 over mission.true_time.time_step sec

        instantaneous_data_removed % [kb] Data removed by Communication over
 mission.true_time.time_step sec

        list_HW_data_generated % List of HW and Classes that generates data
```

```
        array_HW_data_generated % [kb] Total data generated by this HW and
 Class

        list_HW_data_removed % List of HW and Classes that removes data

        array_HW_data_removed % [kb] Total data removed by this HW and Class

        warning_counter % [integer] Counter stops the warning after 10
 displays

        data % Other useful data
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Data_Handling(init_data, mission)

            obj.mode_true_SC_data_handling_selector =
 init_data.mode_true_SC_data_handling_selector;

            obj.instantaneous_data_change = 0; % [kb]
            obj.instantaneous_data_generated = 0; % [kb]
            obj.instantaneous_data_removed = 0; % [kb]

            obj.list_HW_data_generated = [];
            obj.array_HW_data_generated = [];
            obj.list_HW_data_removed = [];
            obj.array_HW_data_removed = [];

            obj.warning_counter = 0;

            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end
            obj.data.store_instantaneous_data_change =
 obj.instantaneous_data_change; % [kb]

            % Initialize Variables to store
            obj.store = [];
```

```
            obj.store.instantaneous_data_change =
zeros(mission.storage.num_storage_steps,
length(obj.instantaneous_data_change));
            obj.store.instantaneous_data_generated =
zeros(mission.storage.num_storage_steps,
length(obj.instantaneous_data_generated));
            obj.store.instantaneous_data_removed =
zeros(mission.storage.num_storage_steps,
length(obj.instantaneous_data_removed));

        end
```

[ ] Methods: Initialize list_HW_data_generated

Initialize list_HW_data_generated for HW and Classes

```
        function obj = func_initialize_list_HW_data_generated(obj, equipment,
mission)

            this_name = equipment.name;
            flag_name_exisits = 0;

            for i = 1:1:length(obj.list_HW_data_generated)
                if strcmp( obj.list_HW_data_generated{i}, this_name )
                    flag_name_exisits = 1;
                end
            end

            if flag_name_exisits == 0
                i = length(obj.list_HW_data_generated);
                obj.list_HW_data_generated{i+1} = this_name;

                if isprop(equipment, 'instantaneous_data_rate_generated')
                    this_instantaneous_data_generated
= (equipment.instantaneous_data_rate_generated *
mission.true_time.time_step); % [kb]
                elseif
isprop(equipment, 'instantaneous_data_generated_per_sample')
                    this_instantaneous_data_generated =
equipment.instantaneous_data_generated_per_sample; % [kb]
                else
                    error('Data generated incorrect!')
                end

                obj.array_HW_data_generated(1,i+1) =
this_instantaneous_data_generated; % [kb]
            end

        end
```

[ ] Methods: Initialize list_HW_data_removed

Initialize list_HW_data_removed for HW and Classes

```
        function obj = func_initialize_list_HW_data_removed(obj, equipment, mission)

            this_name = equipment.name;
            flag_name_exisits = 0;

            for i = 1:1:length(obj.list_HW_data_removed)
                if strcmp( obj.list_HW_data_removed{i}, this_name )
                    flag_name_exisits = 1;
                end
            end

            if flag_name_exisits == 0
                i = length(obj.list_HW_data_removed);
                obj.list_HW_data_removed{i+1} = this_name;

                if isprop(equipment, 'instantaneous_data_rate_removed')
                    this_instantaneous_data_removed = (equipment.instantaneous_data_rate_removed * mission.true_time.time_step); % [kb]
                elseif isprop(equipment, 'instantaneous_data_removed_per_sample')
                    this_instantaneous_data_removed = equipment.instantaneous_data_removed_per_sample; % [kb]
                else
                    error('Data removed incorrect!')
                end

                obj.array_HW_data_removed(1,i+1) = this_instantaneous_data_removed; % [kb]
            end

        end
```

[ ] Methods: Initialize Store

Initialize store of array_HW_data_generated and array_HW_data_removed

```
        function obj = func_initialize_store_HW_data_generated_removed(obj, mission)

            obj.store.list_HW_data_generated = obj.list_HW_data_generated;
            obj.store.list_HW_data_removed = obj.list_HW_data_removed;

            obj.store.array_HW_data_generated = zeros(mission.storage.num_storage_steps, length(obj.array_HW_data_generated));
            obj.store.array_HW_data_removed = zeros(mission.storage.num_storage_steps, length(obj.array_HW_data_removed));

            obj = func_update_true_SC_data_store(obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_data_store(obj, mission)

            if mission.storage.flag_store_this_time_step == 1

obj.store.instantaneous_data_change(mission.storage.k_storage,:) =
obj.data.store_instantaneous_data_change; % [kb]

obj.store.instantaneous_data_generated(mission.storage.k_storage,:) =
obj.instantaneous_data_generated; % [kb]

obj.store.instantaneous_data_removed(mission.storage.k_storage,:) =
obj.instantaneous_data_removed; % [kb]

                obj.store.array_HW_data_generated(mission.storage.k_storage,:)
= obj.array_HW_data_generated; % [kb]

                if isempty(obj.array_HW_data_removed)
                    % Do nothing!
                else

obj.store.array_HW_data_removed(mission.storage.k_storage,:) =
obj.array_HW_data_removed; % [kb]
                end
            end

        end
```

[ ] Methods: Main

Main data handling code

```
        function obj = func_main_true_SC_data_handling(obj, mission, i_SC)

            switch obj.mode_true_SC_data_handling_selector

                case 'Generic'
                    obj = func_true_SC_data_handling_Generic(obj, mission,
i_SC);

                case 'Nightingale'
                    obj = func_true_SC_data_handling_Nightingale(obj, mission,
i_SC);

                otherwise
                    error('Data Handling mode not defined!')
            end

            % Store
```

```
            obj = func_update_true_SC_data_store(obj, mission);

            % Reset All Variables
            obj.instantaneous_data_change = 0; % [kb]
            obj.instantaneous_data_generated = 0; % [kb]
            obj.instantaneous_data_removed = 0; % [kb]

        end
```

[ ] Methods: Main Function for Generic

Generic data handling code

```
        function obj = func_true_SC_data_handling_Generic(obj, mission, i_SC)

            obj.instantaneous_data_change = (obj.instantaneous_data_generated
 - obj.instantaneous_data_removed); % [kb]
            obj.data.store_instantaneous_data_change =
 obj.instantaneous_data_change; % [kb]

            if obj.instantaneous_data_change > 0
                % Add Data to Memory

                for i_memory =
 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_onboard_memory

                    if
 mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.instantaneous_capacity
 >= mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.maximum_capacity
                        % Skip this memory

                    elseif
 (mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.maximum_capacity -
 mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.instantaneous_capacity)
 <= obj.instantaneous_data_change
                        % Fill this memory as much as possible
                        obj.instantaneous_data_change =
 obj.instantaneous_data_change -
 (mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.maximum_capacity -
 mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.instantaneous_capacity); %
 [kb]

 mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.instantaneous_capacity
 = mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.maximum_capacity; %
 [kb]

                    else
                        % Put entirely in this memory

 mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.instantaneous_capacity
 =
 mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.instantaneous_capacity
 + obj.instantaneous_data_change; % [kb]
```

```
                        obj.instantaneous_data_change = 0; % [kb]

                    end

                end

                if obj.instantaneous_data_change > 0

                    if obj.warning_counter < 10
                        warning('All Memories are Full!')
                        obj.warning_counter = obj.warning_counter + 1;
                    end


mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.instantaneous_capacity
=
mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.instantaneous_capacity
+ obj.instantaneous_data_change; % [kb]
                    obj.instantaneous_data_change = 0; % [kb]
                else
                    obj.warning_counter = 0;
                end


            else
                % Remove Data from Memory and obj.instantaneous_data_change <
0

                for i_memory =
mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_onboard_memory:-1:1

                    if
mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.instantaneous_capacity
<= 0
                        % Skip this memory

                    elseif
mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.instantaneous_capacity
< abs(obj.instantaneous_data_change)
                        % Delete all this memory
                        obj.instantaneous_data_change =
obj.instantaneous_data_change +
mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.instantaneous_capacity;

mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.instantaneous_capacity
= 0; % [kb]

                    else
                        % Remove some of this memory

mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.instantaneous_capacity
=
mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.instantaneous_capacity
+ obj.instantaneous_data_change; % [kb]
```

```
                        obj.instantaneous_data_change = 0; % [kb]

                    end

                end

                if obj.instantaneous_data_change < 0

                    if obj.warning_counter < 10
                        warning('All Memories are Empty!')
                        obj.warning_counter = obj.warning_counter + 1;
                    end


 mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.instantaneous_capacity
 =
 mission.true_SC{i_SC}.true_SC_onboard_memory{i_memory}.instantaneous_capacity
 + obj.instantaneous_data_change; % [kb]
                    obj.instantaneous_data_change = 0; % [kb]
                else
                    obj.warning_counter = 0;
                end

            end



        end
```

[ ] Methods: Update Instantaneous Data Generated

Updates instantaneous_data_generated by all HW and Classes

```
        function obj = func_update_instantaneous_data_generated(obj,
 equipment, mission, varargin)

            if isprop(equipment, 'instantaneous_data_rate_generated')
                this_instantaneous_data_generated
 = (equipment.instantaneous_data_rate_generated *
 mission.true_time.time_step); % [kb]
            elseif
 isprop(equipment, 'instantaneous_data_generated_per_sample')
                this_instantaneous_data_generated =
 equipment.instantaneous_data_generated_per_sample; % [kb]
            else
                error('Data generated incorrect!')
            end

            if ~isempty(varargin)
                chosen_memory = varargin{1};
                i_SC = varargin{2};
```

```
mission.true_SC{i_SC}.true_SC_onboard_memory{chosen_memory}.instantaneous_capacity
=
mission.true_SC{i_SC}.true_SC_onboard_memory{chosen_memory}.instantaneous_capacity
+ this_instantaneous_data_generated; % [kb]
           else
               obj.instantaneous_data_generated =
obj.instantaneous_data_generated + this_instantaneous_data_generated; % [kb]
           end

           this_name = equipment.name;
           flag_name_exisits = 0;
           this_idx = 0;

           for i = 1:1:length(obj.list_HW_data_generated)
               if strcmp( obj.list_HW_data_generated{i}, this_name )
                   flag_name_exisits = 1;
                   this_idx = i;
               end
           end

           if flag_name_exisits == 0
               error('HW not found!')
           else
               obj.array_HW_data_generated(1,this_idx) =
obj.array_HW_data_generated(1,this_idx) +
this_instantaneous_data_generated; % [kb]
           end

       end
```

[ ] Methods: Update Instantaneous Data Generated during Attitude Loop

Updates instantaneous_data_generated by all HW and Classes, in ADL

```
       function obj = func_update_instantaneous_data_generated_attitude(obj,
equipment, mission, varargin)

           if isprop(equipment, 'instantaneous_data_rate_generated')
               this_instantaneous_data_generated
= (equipment.instantaneous_data_rate_generated *
mission.true_time.time_step_attitude); % [kb]
           elseif
isprop(equipment, 'instantaneous_data_generated_per_sample')
               this_instantaneous_data_generated =
equipment.instantaneous_data_generated_per_sample; % [kb]
           else
               error('Data generated incorrect!')
           end

           if ~isempty(varargin)
```

```
                chosen_memory = varargin{1};
                i_SC = varargin{2};

mission.true_SC{i_SC}.true_SC_onboard_memory{chosen_memory}.instantaneous_capacity
=
mission.true_SC{i_SC}.true_SC_onboard_memory{chosen_memory}.instantaneous_capacity
+ this_instantaneous_data_generated; % [kb]
            else
                obj.instantaneous_data_generated =
obj.instantaneous_data_generated + this_instantaneous_data_generated; % [kb]
            end

            this_name = equipment.name;
            flag_name_exisits = 0;
            this_idx = 0;

            for i = 1:1:length(obj.list_HW_data_generated)
                if strcmp( obj.list_HW_data_generated{i}, this_name )
                    flag_name_exisits = 1;
                    this_idx = i;
                end
            end

            if flag_name_exisits == 0
                error('HW not found!')
            else
                obj.array_HW_data_generated(1,this_idx) =
obj.array_HW_data_generated(1,this_idx) +
this_instantaneous_data_generated; % [kb]
            end

        end
```

[ ] Methods: Update Instantaneous Data Removed

Updates instantaneous_data_removed by all HW and Classes

```
        function obj = func_update_instantaneous_data_removed(obj, equipment,
mission, varargin)

            if isprop(equipment, 'instantaneous_data_rate_removed')
                this_instantaneous_data_removed =
(equipment.instantaneous_data_rate_removed * mission.true_time.time_step); %
[kb]
            elseif isprop(equipment, 'instantaneous_data_removed_per_sample')
                this_instantaneous_data_removed =
equipment.instantaneous_data_removed_per_sample; % [kb]
            else
                error('Data removed incorrect!')
            end
```

```
            if ~isempty(varargin)
                chosen_memory = varargin{1};
                i_SC = varargin{2};

 mission.true_SC{i_SC}.true_SC_onboard_memory{chosen_memory}.instantaneous_capacity
 =
 mission.true_SC{i_SC}.true_SC_onboard_memory{chosen_memory}.instantaneous_capacity
 - this_instantaneous_data_removed; % [kb]
            else
                obj.instantaneous_data_removed =
 obj.instantaneous_data_removed + this_instantaneous_data_removed; % [kb]
            end

            this_name = equipment.name;
            flag_name_exisits = 0;
            this_idx = 0;

            for i = 1:1:length(obj.list_HW_data_removed)
                if strcmp( obj.list_HW_data_removed{i}, this_name )
                    flag_name_exisits = 1;
                    this_idx = i;
                end
            end

            if flag_name_exisits == 0
                error('HW not found!')
            else
                obj.array_HW_data_removed(1,this_idx) =
 obj.array_HW_data_removed(1,this_idx) + this_instantaneous_data_removed; %
 [kb]
            end

        end

    end

end
```

Published with MATLAB® R2022a

4.4 True_SC_Gravity_Gradient

Table of Contents

Class: True_SC_Gravity_Gradient

Computes Gravity Gradient disturbance torque

```
classdef True_SC_Gravity_Gradient < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        enable_G2 % [boolean]
```

[ ] Properties: Variables Computed Internally

```
        disturbance_torque_G2 % [Nm]
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Gravity_Gradient(init_data, mission, i_SC)

            % Optional parameters
```

```
            obj.disturbance_torque_G2 = [0 0 0]; % [N]
            obj.enable_G2 = init_data.enable_G2;

            % Calculate GG before first iteration of ADL
            obj.func_main_true_SC_gravity_gradient(mission, i_SC);

            % Initialize storage
            obj.store.disturbance_torque_G2 =
 zeros(mission.storage.num_storage_steps, length(obj.disturbance_torque_G2));

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_gravity_gradient_store(obj, mission)
            if mission.storage.flag_store_this_time_step == 1
                obj.store.disturbance_torque_G2(mission.storage.k_storage,:) =
 obj.disturbance_torque_G2;
            end
        end
```

[ ] Methods: Main

Compute GG Disturbance torque

```
        function obj = func_main_true_SC_gravity_gradient(obj, mission, i_SC)

            % Reset disturbance torque and force
            obj.disturbance_torque_G2 = [0 0 0]; % [N]

            if obj.enable_G2 == 1
                % Gravity direction from SB
                Rc =
 1e3*(mission.true_SC{i_SC}.true_SC_navigation.position_relative_target);
  %[m]
                Rc_sc = (mission.true_SC{i_SC}.true_SC_adc.rotation_matrix') *
 Rc';          %[m]

                % Gravity gradient torque [Nm]
                obj.disturbance_torque_G2 =
 ( (3*(mission.true_target{mission.true_SC{i_SC}.true_SC_navigation.index_relative_target}
 * 1e9)/(norm(Rc_sc)^5)) * cross(Rc_sc,
 mission.true_SC{i_SC}.true_SC_body.total_MI *Rc_sc) )';

                % Accumulate disturbances
                mission.true_SC{i_SC}.true_SC_adc.disturbance_torque
 = mission.true_SC{i_SC}.true_SC_adc.disturbance_torque +
 obj.disturbance_torque_G2;

            else
                % Don't do anything!
```

```
            end

            % Update storage after calculation
            obj.func_update_true_gravity_gradient_store(mission);

        end

    end

end
```

Published with MATLAB® R2022a

4.5 True_SC_Navigation

Table of Contents

Class: True_SC_Navigation

Tracks the position and velocity of the SC

```
classdef True_SC_Navigation < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        position % [km] : Current position of SC in inertial frame I
        velocity % [km/sec] : Current velocity of SC in inertial frame I
        position_relative_target % [km] : Current position of SC relative to
 SB-center J2000 inertial frame
        velocity_relative_target % [km/sec] : Current velocity of SC relative
 to SB-center J2000 inertial frame
        name_relative_target % [string] : Name of the target, relative to
 which position and velocity are specified

        spice_filename % [string] : SC's SPICE FileName
        spice_name % [string] : SC's SPICE Name

        mode_true_SC_navigation_dynamics_selector % [string] Different
 navigation dynamics modes
        % - 'SPICE' : Use pre-computed SPICE trajectory
        % - 'Absolute Dynamics'
        % - 'Relative Dynamics'
```

[ ] Properties: Variables Computed Internally

```
        index_relative_target % [integer] : Index of the target, relative to
 which position and velocity are specified
```

```
        flag_visible_Sun % [Boolean] Check if Sun is visible
        flag_visible_Earth % [Boolean] Check if Earth is visible

        flag_SC_crashed % [Boolean] Check if SC has crashed into anything!
        position_array % [km] Position array wrt Sun-centered J2000,
corresponding to time array in mission.true_time.time_position_array

        control_force % [N] : Control force vector generated by thrusters
(e.g. MT, CT) that passes through Center of Mass of SC
        disturbance_force % [N] : Disturbance force vector generated by SRP
that passes through Center of Mass of SC

        ode_options % : Options for Matlab%s ODE function
odeset( RelTol',1e-14,'AbsTol',1e-14)
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Navigation(init_data, mission)

            if strcmp(mission.frame,'Absolute') ||
isfield(init_data, 'position')
                obj.position = init_data.position; % [km]
                obj.velocity = init_data.velocity; % [km/sec]

                if isfield(init_data, 'name_relative_target')
                    obj.name_relative_target = init_data.name_relative_target;
                else
                    obj.name_relative_target = mission.true_target{1}.name;
                end

                for i_target = 1:1:mission.num_target
                    if strcmp(mission.true_target{i_target}.name,
obj.name_relative_target)
                        obj.index_relative_target = i_target;
                        position_target =
mission.true_target{i_target}.position;
                        velocity_target =
mission.true_target{i_target}.velocity;
```

```
                    end
                end

                obj.position_relative_target = obj.position -
position_target; % [km]
                obj.velocity_relative_target = obj.velocity -
velocity_target; % [km/sec]


            elseif strcmp(mission.frame,'Relative') ||
isfield(init_data, 'position_relative_target')
                obj.position_relative_target =
sc_body_init_data.position_relative_target; % [km]
                obj.velocity_relative_target =
sc_body_init_data.velocity_relative_target; % [km/sec]
                obj.name_relative_target = init_data.name_relative_target; %
[string]

                for i_target = 1:1:mission.num_target
                    if strcmp(mission.true_target{i_target}.name,
obj.name_relative_target)
                        obj.index_relative_target = i_target;
                        position_target =
mission.true_target{i_target}.position;
                        velocity_target =
mission.true_target{i_target}.velocity;
                    end
                end

                obj.position = position_target +
obj.position_relative_target; % [km]
                obj.velocity = velocity_target +
obj.velocity_relative_target; % [km/sec]

            else
                error('Navigation initialization incorrect!')
            end

            obj.control_force = [0 0 0]; % [N]
            obj.disturbance_force = [0 0 0]; % [N]
            obj.flag_SC_crashed = 0;


            % Select Dynamics Mode
            obj.mode_true_SC_navigation_dynamics_selector =
init_data.mode_true_SC_navigation_dynamics_selector; % [string]

            if strcmp( obj.mode_true_SC_navigation_dynamics_selector, 'SPICE'
)
                % Use SPICE trajectory
                obj.spice_filename = init_data.spice_filename;
                obj.spice_name = init_data.spice_name;
                cspice_furnsh(obj.spice_filename)
            end
```

```
            obj.ode_options = odeset('RelTol',1e-14,'AbsTol',1e-14);

            % Update flag visible
            obj = func_update_visible_Sun_Earth(obj, mission);

            % Initialize Variables to store: position and velocity of SC
            obj.store = [];

            obj.store.position = zeros(mission.storage.num_storage_steps,
 length(obj.position));
            obj.store.velocity = zeros(mission.storage.num_storage_steps,
 length(obj.velocity));
            obj.store.position_relative_target =
 zeros(mission.storage.num_storage_steps,
 length(obj.position_relative_target));
            obj.store.velocity_relative_target =
 zeros(mission.storage.num_storage_steps,
 length(obj.velocity_relative_target));
            obj.store.flag_visible_Sun =
 zeros(mission.storage.num_storage_steps, length(obj.flag_visible_Sun));
            obj.store.flag_visible_Earth =
 zeros(mission.storage.num_storage_steps, length(obj.flag_visible_Earth));

            obj = func_update_true_SC_navigation_store(obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_navigation_store(obj, mission)

            if mission.storage.flag_store_this_time_step == 1
                obj.store.position(mission.storage.k_storage,:) =
 obj.position; % [km]
                obj.store.velocity(mission.storage.k_storage,:) =
 obj.velocity; % [km/sec]

 obj.store.position_relative_target(mission.storage.k_storage,:) =
 obj.position_relative_target; % [km]

 obj.store.velocity_relative_target(mission.storage.k_storage,:) =
 obj.velocity_relative_target; % [km/sec]
                obj.store.flag_visible_Sun(mission.storage.k_storage,:) =
 obj.flag_visible_Sun; % [Boolean]
                obj.store.flag_visible_Earth(mission.storage.k_storage,:) =
 obj.flag_visible_Earth; % [Boolean]
            end

        end
```

[ ] Methods: Main

Select method to update position and velocity

```
        function obj = func_main_true_SC_navigation(obj, mission, i_SC)

            switch obj.mode_true_SC_navigation_dynamics_selector

                case 'SPICE'
                    % Use SPICE trajectory
                    obj =
func_update_SC_navigation_position_velocity_SPICE(obj, mission);

                case 'Absolute Dynamics'
                    % Use Absolute Dynamics
                    obj =
func_update_SC_navigation_position_velocity_Absolute_Dynamics(obj, mission,
i_SC);

                otherwise
                    error('Navigation mode not defined!')
            end

            % Update flag visible
            obj = func_update_visible_Sun_Earth(obj, mission);

            % Update SC crash
            obj = func_update_flag_SC_crashed(obj, mission, i_SC);

            % Store
            obj = func_update_true_SC_navigation_store(obj, mission);

            obj.control_force = [0 0 0]; % [N]
            obj.disturbance_force = [0 0 0]; % [N]

        end
```

[ ] Methods: Update Position Velocity SPICE

Update position and velocity using SPICE

```
        function obj = func_update_SC_navigation_position_velocity_SPICE(obj,
mission)

            SC_pos_vel =
cspice_spkezr(obj.spice_name,mission.true_time.date,'J2000','NONE','SUN');

            obj.position = SC_pos_vel(1:3)'; % [km]
            obj.velocity = SC_pos_vel(4:6)'; % [km/sec]

            position_target =
mission.true_target{obj.index_relative_target}.position;
```

```
            velocity_target = 
mission.true_target{obj.index_relative_target}.velocity;

            obj.position_relative_target = obj.position - position_target; %
[km]
            obj.velocity_relative_target = obj.velocity - velocity_target; %
[km/sec]

            SC_pos_vel_array = (cspice_spkezr(obj.spice_name, 
mission.true_time.prev_date + 
mission.true_time.time_position_array' ,'J2000','NONE','SUN'))';
            obj.position_array = SC_pos_vel_array(:,1:3);

        end
```

[ ] Methods: Update Position Velocity Absolute Dynamics

Update position and velocity using Absolute dynamics

```
        function obj = 
func_update_SC_navigation_position_velocity_Absolute_Dynamics(obj, mission, 
i_SC)

            this_time_array = mission.true_time.time_position_array;

            %               obj = obj.func_update_disturbance_force(mission, 
i_SC);

            SC_pos_vel_current = [obj.position'; obj.velocity']; % [km, km/
sec] in (6,1) format
            [T,X]=ode113(@(t,X) func_ode_orbit_inertial_absolute_dynamics(t, 
X, mission, i_SC), this_time_array, SC_pos_vel_current, obj.ode_options);

            new_SC_pos_vel_current = X(end,:);

            obj.position = new_SC_pos_vel_current(1:3); % [km]
            obj.velocity = new_SC_pos_vel_current(4:6); % [km/sec]

            position_target = 
mission.true_target{obj.index_relative_target}.position;
            velocity_target = 
mission.true_target{obj.index_relative_target}.velocity;

            obj.position_relative_target = obj.position - position_target; %
[km]
            obj.velocity_relative_target = obj.velocity - velocity_target; %
[km/sec]

            obj.position_array = X(:,1:3); % [km]

        end
```

```
        %          function obj = func_update_disturbance_force(obj,mission,
 i_SC)
        %              % Sum up all disturbance forces
        %              obj.disturbance_force =
 mission.true_SC{i_SC}.true_SRP.disturbance_force_SRP';
        %          end
```

[ ] Methods: Update Visible Sun Earth

Update flag_visible_Sun and flag_visible_Earth

```
        function obj = func_update_visible_Sun_Earth(obj, mission)

            % Use lins math: https://mathworld.wolfram.com/Point-
LineDistance3-Dimensional.html

            for i_vis = 1:1:2

                flag_visible = 1;

                if i_vis == 1
                    % Sun
                    x1 =
 mission.true_solar_system.SS_body{mission.true_solar_system.index_Sun}.position; %
 [km]
                elseif i_vis == 2
                    % Earth
                    x1 =
 mission.true_solar_system.SS_body{mission.true_solar_system.index_Earth}.position; %
 [km]
                else
                    error('Shouldnt reach here')
                end

                % SC Position
                x2 = obj.position; % [km]

                % Check all Targets
                for i_target = 1:1:mission.num_target

                    x0 = mission.true_target{i_target}.position; % [km]

                    d = norm(cross(x0 - x1, x0 - x2))/norm(x2 - x1);
                    if d >= mission.true_target{i_target}.radius % [km]
                        % No chance of eclipse
                    else
                        % Check t
                        t = - dot(x1 - x0, x2 - x1 )/ (norm(x2  - x1))^2;
                        if (t >= 0) && (t <= 1)
                            flag_visible = 0;
                        else
```

```
                        % Body is outside the line of sight
                    end
                end
            end

            % Check all SS Bodies
            for i_SS_body = 1:1:mission.true_solar_system.num_SS_body

                if (i_vis == 1) && (i_SS_body ==
mission.true_solar_system.index_Sun)
                    % Skip this!

                elseif (i_vis == 2) && (i_SS_body ==
mission.true_solar_system.index_Earth)
                    % Skip this!

                else

                    x0 =
mission.true_solar_system.SS_body{i_SS_body}.position; % [km]

                    d = norm(cross(x0 - x1, x0 - x2))/norm(x2 - x1);
                    if d >=
mission.true_solar_system.SS_body{i_SS_body}.radius % [km]
                        % No chance of eclipse
                    else
                        % Check t
                        t = - dot(x1 - x0, x2 - x1 )/ (norm(x2  - x1))^2;
                        if (t >= 0) && (t <= 1)
                            flag_visible = 0;
                        else
                            % Body is outside the line of sight
                        end
                    end

                end
            end


            if i_vis == 1
                % Sun
                obj.flag_visible_Sun = flag_visible;
            elseif i_vis == 2
                % Earth
                obj.flag_visible_Earth = flag_visible;
            else
                error('Shouldnt reach here')
            end


        end

    end
```

[ ] Methods: Check SC Crashed

Update flag_SC_crashed

```
        function obj = func_update_flag_SC_crashed(obj, mission, i_SC)

            for t = 1:1:length(mission.true_time.time_position_array)

                % SC position
                x1 = obj.position_array(t,:);

                % Check all Targets
                for i_target = 1:1:mission.num_target

                    x0 = mission.true_target{i_target}.position_array(t,:); %
 [km]

                    if norm(x0 - x1) <= mission.true_target{i_target}.radius %
 [km]
                        obj.flag_SC_crashed = 1;

 disp('-----------------------------------------------')
                        disp(['SC ',num2str(i_SC),' crashed into
 ',mission.true_target{i_target}.name])

 disp('-----------------------------------------------')
                        mission.storage.flag_stop_sim = 1;
                        break;
                    end

                end

            end

        end

    end

end
```

Published with MATLAB® R2022a

4.6 True_SC_Power

Table of Contents

Class: True_SC_Power

Track the power status onboard the spacecraft

```
classdef True_SC_Power < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        power_loss_rate % [float] Fraction of the total power loss: Power loss
 [W] = (1 + power_loss_rate) * total_instantaneous_power_consumed
```

[ ] Properties: Variables Computed Internally

```
        name % [string] 'Power Subsystem'

        instantaneous_total_power_consumed % [W] Total power comsumed by all
 sensors and actuators over mission.true_time.time_step sec

        instantaneous_total_power_generated % [W] Total power generated by
 solar panels or RTG over mission.true_time.time_step sec

        instantaneous_energy % [W hr] Converted into Energy for storage in
 battery

        instantaneous_energy_unused % [W hr] Excess Energy, that is usually
 going to heat the SC

        list_HW_energy_consumed % List of HW that consumes power
```

```
        list_HW_energy_generated % List of HW that generates power

        array_HW_energy_consumed % [W hr] Total energy consumed by this HW

        array_HW_energy_generated % [W hr] Total energy generated by this HW

        warning_counter % [integer] Counter stops the warning after 10
 displays

        power_emergency % [boolean] Flag to indicate a critical power deficit
 when batteries are empty

        power_deficit % [W hr] Track power deficit when batteries are empty

        data % Other useful data
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Power(init_data, mission)

            obj.instantaneous_total_power_consumed = 0; % [W]
            obj.instantaneous_total_power_generated = 0; % [W]
            obj.instantaneous_energy = 0; % [W hr]
            obj.instantaneous_energy_unused = 0; % [W hr]

            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
                obj.name = 'Power Subsystem';
            end

            obj.power_loss_rate = init_data.power_loss_rate; % [float]

            obj.list_HW_energy_consumed = [];
            obj.list_HW_energy_generated = [];
            obj.array_HW_energy_consumed = [];
            obj.array_HW_energy_generated = [];
            obj.warning_counter = 0;
            obj.power_emergency = false;
            obj.power_deficit = 0;
```

```
            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end
            obj.data.store_instantaneous_energy = obj.instantaneous_energy; %
 [W hr]

            % Initialize Variables to store: power and energy
            obj.store = [];

            obj.store.instantaneous_power_consumed =
 zeros(mission.storage.num_storage_steps,
 length(obj.instantaneous_total_power_consumed));
            obj.store.instantaneous_power_generated =
 zeros(mission.storage.num_storage_steps,
 length(obj.instantaneous_total_power_generated));
            obj.store.instantaneous_energy =
 zeros(mission.storage.num_storage_steps, length(obj.instantaneous_energy));
            obj.store.instantaneous_energy_unused =
 zeros(mission.storage.num_storage_steps,
 length(obj.instantaneous_energy_unused));

        end
```

[ ] Methods: Initialize list_HW_energy_consumed

Initialize list_HW_energy_consumed for all HW

```
        function obj = func_initialize_list_HW_energy_consumed(obj, equipment,
 mission)

            this_name = equipment.name;
            flag_name_exists = 0;

            for i = 1:1:length(obj.list_HW_energy_consumed)
                if strcmp( obj.list_HW_energy_consumed{i}, this_name )
                    flag_name_exists = 1;
                end
            end

            if flag_name_exists == 0
                i = length(obj.list_HW_energy_consumed);
                obj.list_HW_energy_consumed{i+1} = this_name;
                obj.array_HW_energy_consumed(1,i
+1) = equipment.instantaneous_power_consumed *
 (mission.true_time.time_step/3600); % [W hr]
            end

        end
```

[ ] Methods: Initialize list_HW_energy_generated

Initialize list_HW_energy_generated for Solar Panels or RTG

```
        function obj = func_initialize_list_HW_energy_generated(obj,
 equipment, mission)

            this_name = equipment.name;
            flag_name_exists = 0;

            for i = 1:1:length(obj.list_HW_energy_generated)
                if strcmp( obj.list_HW_energy_generated{i}, this_name )
                    flag_name_exists = 1;
                end
            end

            if flag_name_exists == 0
                i = length(obj.list_HW_energy_generated);
                obj.list_HW_energy_generated{i+1} = this_name;
                obj.array_HW_energy_generated(1,i
+1) = equipment.instantaneous_power_generated *
 (mission.true_time.time_step/3600); % [W hr]
            end

        end
```

[ ] Methods: Initialize Store

Initialize store of array_HW_energy_consumed and array_HW_energy_generated

```
        function obj = func_initialize_store_HW_power_consumed_generated(obj,
 mission)

            obj.store.list_HW_energy_consumed = obj.list_HW_energy_consumed;
            obj.store.list_HW_energy_generated = obj.list_HW_energy_generated;

            obj.store.array_HW_energy_consumed =
 zeros(mission.storage.num_storage_steps,
 length(obj.array_HW_energy_consumed));
            obj.store.array_HW_energy_generated =
 zeros(mission.storage.num_storage_steps,
 length(obj.array_HW_energy_generated));

            obj = func_update_true_SC_power_store(obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_power_store(obj, mission)

            if mission.storage.flag_store_this_time_step == 1

obj.store.instantaneous_power_consumed(mission.storage.k_storage,:) =
obj.instantaneous_total_power_consumed; % [W]

obj.store.instantaneous_power_generated(mission.storage.k_storage,:) =
obj.instantaneous_total_power_generated; % [W]
                obj.store.instantaneous_energy(mission.storage.k_storage,:) =
obj.data.store_instantaneous_energy; % [W hr]

obj.store.instantaneous_energy_unused(mission.storage.k_storage,:) =
obj.instantaneous_energy_unused; % [W hr]


obj.store.array_HW_energy_consumed(mission.storage.k_storage,:) =
obj.array_HW_energy_consumed; % [W hr]

obj.store.array_HW_energy_generated(mission.storage.k_storage,:) =
obj.array_HW_energy_generated; % [W hr]
            end

        end
```

[ ] Methods: Main

Main power code

```
        function obj = func_main_true_SC_power(obj, mission, i_SC)

            obj.instantaneous_energy =
(obj.instantaneous_total_power_generated -
obj.instantaneous_total_power_consumed) *
(mission.true_time.time_step/3600); % [W hr]
            obj.data.store_instantaneous_energy = obj.instantaneous_energy; %
[W hr]


            if obj.instantaneous_energy > 0
                % Excess Energy use to Recharge Battery
                obj.power_emergency = false; % Clear emergency flag when we
have excess energy

                for i_batt =
mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_battery:-1:1

                    if (mission.true_SC{i_SC}.true_SC_battery{i_batt}.health
== 1) && (obj.instantaneous_energy > 0)

                        if
mission.true_SC{i_SC}.true_SC_battery{i_batt}.instantaneous_capacity >=
mission.true_SC{i_SC}.true_SC_battery{i_batt}.maximum_capacity
```

```
                           % Do nothing!

                       elseif
 (mission.true_SC{i_SC}.true_SC_battery{i_batt}.instantaneous_capacity
 + (mission.true_SC{i_SC}.true_SC_battery{i_batt}.charging_efficiency *
 obj.instantaneous_energy)) <=
 mission.true_SC{i_SC}.true_SC_battery{i_batt}.maximum_capacity
                           % Charge this Battery

 mission.true_SC{i_SC}.true_SC_battery{i_batt}.instantaneous_capacity
 = mission.true_SC{i_SC}.true_SC_battery{i_batt}.instantaneous_capacity
 + (mission.true_SC{i_SC}.true_SC_battery{i_batt}.charging_efficiency *
 obj.instantaneous_energy); % [W hr]
                           obj.instantaneous_energy = 0; % [W hr]

                       else
                           % Fill this Battery
                           obj.instantaneous_energy =
 obj.instantaneous_energy -
 (mission.true_SC{i_SC}.true_SC_battery{i_batt}.maximum_capacity -
 mission.true_SC{i_SC}.true_SC_battery{i_batt}.instantaneous_capacity)/
mission.true_SC{i_SC}.true_SC_battery{i_batt}.charging_efficiency; % [W hr]

 mission.true_SC{i_SC}.true_SC_battery{i_batt}.instantaneous_capacity =
 mission.true_SC{i_SC}.true_SC_battery{i_batt}.maximum_capacity; % [W hr]

                       end

                   end

               end

               if obj.instantaneous_energy > 0
                   obj.instantaneous_energy_unused =
 obj.instantaneous_energy; % [W hr]
               end

           else
               % Discharge Battery (obj.instantaneous_energy < 0)

               for i_batt =
 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_battery

                   if (mission.true_SC{i_SC}.true_SC_battery{i_batt}.health
 == 1) && (obj.instantaneous_energy < 0)

                       if
 mission.true_SC{i_SC}.true_SC_battery{i_batt}.instantaneous_capacity <= 0
                           % Do nothing!

                       elseif
 (mission.true_SC{i_SC}.true_SC_battery{i_batt}.instantaneous_capacity *
 mission.true_SC{i_SC}.true_SC_battery{i_batt}.discharging_efficiency) >=
 abs(obj.instantaneous_energy)
```

```
                            % Lots of extra Energy

mission.true_SC{i_SC}.true_SC_battery{i_batt}.instantaneous_capacity =
mission.true_SC{i_SC}.true_SC_battery{i_batt}.instantaneous_capacity -
(abs(obj.instantaneous_energy) /
mission.true_SC{i_SC}.true_SC_battery{i_batt}.discharging_efficiency); % [W
hr]
                            obj.instantaneous_energy = 0;

                        else
                            % Empty this Battery!
                            obj.instantaneous_energy =
obj.instantaneous_energy +
(mission.true_SC{i_SC}.true_SC_battery{i_batt}.instantaneous_capacity *
mission.true_SC{i_SC}.true_SC_battery{i_batt}.discharging_efficiency); % [W
hr]

mission.true_SC{i_SC}.true_SC_battery{i_batt}.instantaneous_capacity = 0; %
[W hr]
                        end

                    end

                end

                if obj.instantaneous_energy < 0
                    % All batteries are empty but we still need power
                    % Set power emergency flag and calculate the deficit
                    obj.power_emergency = true;
                    obj.power_deficit = abs(obj.instantaneous_energy); % Track
the deficit

                    % Limit the number of warnings displayed
                    if obj.warning_counter < 10
                        warning('All Batteries are Empty! Power deficit: %0.2f
W-hr', obj.power_deficit);
                        obj.warning_counter = obj.warning_counter + 1;
                    end

                    % Reset instantaneous_energy to 0 to prevent negative
values
                    obj.instantaneous_energy = 0;
                else
                    obj.power_emergency = false;
                    obj.warning_counter = 0;
                    obj.power_deficit = 0;
                end

            end

            % Store
            obj = func_update_true_SC_power_store(obj, mission);

            % Reset All Variables
```

```
            obj.instantaneous_total_power_consumed = 0; % [W]
            obj.instantaneous_total_power_generated = 0; % [W]
            obj.instantaneous_energy = 0; % [W hr]
            obj.instantaneous_energy_unused = 0; % [W hr]

        end
```

[ ] Methods: Update Instantaneous Power Consumed

Updates instantaneous_power_consumed by all HW

```
        function obj = func_update_instantaneous_power_consumed(obj,
 equipment, mission)

            obj.instantaneous_total_power_consumed =
 obj.instantaneous_total_power_consumed +
 equipment.instantaneous_power_consumed * (1 + obj.power_loss_rate); % [W]

            this_name = equipment.name;
            flag_name_exists = 0;
            this_idx = 0;

            for i = 1:1:length(obj.list_HW_energy_consumed)
                if strcmp( obj.list_HW_energy_consumed{i}, this_name )
                    flag_name_exists = 1;
                    this_idx = i;
                end
            end


            if flag_name_exists == 0
                error('HW not found!')
            else
                obj.array_HW_energy_consumed(1,this_idx)
 = obj.array_HW_energy_consumed(1,this_idx) +
 (equipment.instantaneous_power_consumed*(mission.true_time.time_step/3600)); %
 [W hr]
            end
        end
```

[ ] Methods: Update Instantaneous Power Consumed Attitude

Updates instantaneous_power_consumed by all HW, within ADL

```
        function obj = func_update_instantaneous_power_consumed_attitude(obj,
 equipment, mission)
            obj.instantaneous_total_power_consumed =
 obj.instantaneous_total_power_consumed +
```

```
 equipment.instantaneous_power_consumed*(mission.true_time.time_step_attitude/
mission.true_time.time_step); % [W]

            this_name = equipment.name;
            flag_name_exists = 0;
            this_idx = 0;

            for i = 1:1:length(obj.list_HW_energy_consumed)
                if strcmp( obj.list_HW_energy_consumed{i}, this_name )
                    flag_name_exists = 1;
                    this_idx = i;
                end
            end

            if flag_name_exists == 0
                error('HW not found!')
            else
                obj.array_HW_energy_consumed(1,this_idx)
 = obj.array_HW_energy_consumed(1,this_idx) +
 (equipment.instantaneous_power_consumed*(mission.true_time.time_step_attitude/3600)); %
 [W hr]
            end

        end
```

[ ] Methods: Update Instantaneous Power Generated

Updates instantaneous_power_generated by Solar Panels or RTG

```
        function obj = func_update_instantaneous_power_generated(obj,
 equipment, mission)
            obj.instantaneous_total_power_generated =
 obj.instantaneous_total_power_generated +
 equipment.instantaneous_power_generated; % [W]

            this_name = equipment.name;
            flag_name_exists = 0;
            this_idx = 0;

            for i = 1:1:length(obj.list_HW_energy_generated)
                if strcmp( obj.list_HW_energy_generated{i}, this_name )
                    flag_name_exists = 1;
                    this_idx = i;
                end
            end

            if flag_name_exists == 0
                error('HW not found!')
            else
                obj.array_HW_energy_generated(1,this_idx)
 = obj.array_HW_energy_generated(1,this_idx) +
```

```
 (equipment.instantaneous_power_generated*(mission.true_time.time_step/3600)); %
 [W hr]
            end

        end

    end

end
```

Published with MATLAB® R2022a

4.7 True_SC_SRP

Table of Contents

Class: True_SC_SRP

Tracks the Solar Radiation Pressure (SRP) effects on spacecraft

```
classdef True_SC_SRP < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        enable_SRP % [boolean] Enable/disable SRP calculations
```

[ ] Properties: Variables Computed Internally

```
        disturbance_torque_SRP % [Nm] Torque induced by solar radiation
 pressure
        disturbance_force_SRP % [N] Force induced by solar radiation pressure

        num_faces % Number of spacecraft body faces
        face_data % Data for spacecraft body faces
        % - reflectance_factor : # [0, 1] for ith face
        % - area [m^2] : Area of face
        % - orientation [unit vector] : Normal vector in body frame B
        % - location_center_of_pressure [m] : Center of pressure

        num_solar_panel_faces % Number of solar panel faces
        solar_panels_face_data % Data for solar panel faces
        % - reflectance_factor : # [0, 1] for ith face
        % - area [m^2] : Area of face
        % - orientation [unit vector] : Normal vector in body frame B
        % - location_center_of_pressure [m] : Center of pressure
```

[ ] Properties: Storage Variables

```
        store
```

```
    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_SRP(init_data, mission, i_SC)

            % Initialize SRP enable flag
            obj.enable_SRP = init_data.enable_SRP;

            % Initialize disturbance vectors
            obj.disturbance_torque_SRP = zeros(1,3);
            obj.disturbance_force_SRP = zeros(1,3);

            % Process spacecraft body faces
            obj.num_faces = 0;
            for i_shape =
 1:length(mission.true_SC{i_SC}.true_SC_body.shape_model)
                shape_i =
 mission.true_SC{i_SC}.true_SC_body.shape_model{i_shape};
                obj.num_faces = obj.num_faces + size(shape_i.Faces,1);

                for i_face = 1:size(shape_i.Faces,1)
                    i_face_cnt = i_face + (i_shape-1)*size(shape_i.Faces,1);
                    obj.face_data(i_face_cnt).reflectance_factor =
 shape_i.Face_reflectance_factor(i_face);
                    obj.face_data(i_face_cnt).area =
 shape_i.Face_area(i_face);
                    obj.face_data(i_face_cnt).orientation =
 shape_i.Face_normal(i_face,:);
                    obj.face_data(i_face_cnt).location_center_of_pressure =
 shape_i.Face_center(i_face,:);
                end
            end

            % Process solar panel faces
            obj.num_solar_panel_faces = 0;
            if isfield(mission.true_SC{i_SC}, 'true_SC_solar_panel')
                for i_SP = 1:length(mission.true_SC{i_SC}.true_SC_solar_panel)
                    SP = mission.true_SC{i_SC}.true_SC_solar_panel{i_SP};
                    n_face = size(SP.shape_model.Faces,1);
                    obj.num_solar_panel_faces = obj.num_solar_panel_faces +
 2*n_face; % Both sides

                    for j = 1:n_face
                        % Solar cell side
                        idx = (i_SP-1)*2*n_face + j;
```

```
                        obj.solar_panels_face_data(idx).reflectance_factor =
 SP.shape_model.Face_reflectance_factor_solar_cell_side(j);
                        obj.solar_panels_face_data(idx).area =
 SP.shape_model.Face_area;
                        obj.solar_panels_face_data(idx).orientation =
 SP.shape_model.Face_orientation_solar_cell_side;

 obj.solar_panels_face_data(idx).location_center_of_pressure =
 SP.shape_model.Face_center(j,:);

                        % Opposite side
                        idx = (i_SP-1)*2*n_face + j + n_face;
                        obj.solar_panels_face_data(idx).reflectance_factor =
 SP.shape_model.Face_reflectance_factor_opposite_side(j);
                        obj.solar_panels_face_data(idx).area =
 SP.shape_model.Face_area;
                        obj.solar_panels_face_data(idx).orientation = -
SP.shape_model.Face_orientation_solar_cell_side;

 obj.solar_panels_face_data(idx).location_center_of_pressure =
 SP.shape_model.Face_center(j,:);
                    end
                end
            end

            % Calculate SRP before first iteration of ADL
            obj.func_main_true_SC_SRP(mission, i_SC);

            % Initialize storage
            obj.store.disturbance_torque_SRP =
 zeros(mission.storage.num_storage_steps, length(obj.disturbance_torque_SRP));
            obj.store.disturbance_force_SRP =
 zeros(mission.storage.num_storage_steps, length(obj.disturbance_force_SRP));

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_SRP_store(obj, mission)
            if mission.storage.flag_store_this_time_step == 1
                obj.store.disturbance_torque_SRP(mission.storage.k_storage,:)
 = obj.disturbance_torque_SRP;
                obj.store.disturbance_force_SRP(mission.storage.k_storage,:) =
 obj.disturbance_force_SRP;
            end
        end
```

[ ] Methods: Main

Update SRP Disturbance Force and Torque

```
        function obj = func_main_true_SC_SRP(obj, mission, i_SC)

            % Reset disturbance terms
            obj.disturbance_torque_SRP = [0 0 0];
            obj.disturbance_force_SRP = [0 0 0];

            if obj.enable_SRP == 1

                % Process all faces (spacecraft body + solar panels)
                for i = 1:obj.num_faces + obj.num_solar_panel_faces

                    % Get face data
                    if i <= obj.num_faces
                        face_i = obj.face_data(i).orientation';
                        faceCP_sc =
 obj.face_data(i).location_center_of_pressure';
                        face_area = obj.face_data(i).area;
                        face_reflectance_factor =
 obj.face_data(i).reflectance_factor;
                    else
                        face_i = obj.solar_panels_face_data(i-
obj.num_faces).orientation';
                        faceCP_sc = obj.solar_panels_face_data(i-
obj.num_faces).location_center_of_pressure';
                        face_area = obj.solar_panels_face_data(i-
obj.num_faces).area;
                        face_reflectance_factor =
 obj.solar_panels_face_data(i-obj.num_faces).reflectance_factor;
                    end

                    % Calculate sun vector and incidence
                    faceCP_sun =
 (mission.true_SC{i_SC}.true_SC_navigation.position -
 mission.true_solar_system.SS_body{mission.true_solar_system.index_Sun}.position)'
 + ...
                        mission.true_SC{i_SC}.true_SC_adc.rotation_matrix *
 faceCP_sc;

                    faceCP_sun_normalized = faceCP_sun/norm(faceCP_sun);

                    SC_face_normal =
 mission.true_SC{i_SC}.true_SC_adc.rotation_matrix * face_i;
                    SC_face_normal_normalized = SC_face_normal/
norm(SC_face_normal);

                    % Calculate incidence angle
                    incidence = real(acosd(dot(SC_face_normal_normalized,
 faceCP_sun_normalized)));


                    % Calculate force and torque if face is illuminated
                    if abs(incidence) < 90
                        % Force calculation
```

```
                        F_SRP_magnitude =
mission.true_solar_system.solar_constant_AU /
mission.true_solar_system.light_speed * ...
                            (mission.true_solar_system.AU_distance /
norm(mission.true_SC{i_SC}.true_SC_navigation.position -
mission.true_solar_system.SS_body{mission.true_solar_system.index_Sun}.position))^2
* ...
                            face_area * (1 + face_reflectance_factor) *
cosd(incidence);

                        F_SRP_vector_J2000 = F_SRP_magnitude *
faceCP_sun_normalized;

                        % Torque calculation
                        force_on_surface_at_cp =
(mission.true_SC{i_SC}.true_SC_adc.rotation_matrix)' * F_SRP_vector_J2000;
                        this_face_lever_arm = faceCP_sc -
mission.true_SC{i_SC}.true_SC_body.location_COM';
                        this_face_torque = cross(this_face_lever_arm,
force_on_surface_at_cp);

                        % Accumulate disturbances
                        obj.disturbance_torque_SRP =
obj.disturbance_torque_SRP + this_face_torque';

                        obj.disturbance_force_SRP = obj.disturbance_force_SRP
+ F_SRP_vector_J2000';
                    end
                end

                % Update disturbance Force and Torque
                mission.true_SC{i_SC}.true_SC_navigation.disturbance_force
= mission.true_SC{i_SC}.true_SC_navigation.disturbance_force +
obj.disturbance_force_SRP;
                mission.true_SC{i_SC}.true_SC_adc.disturbance_torque
= mission.true_SC{i_SC}.true_SC_adc.disturbance_torque +
obj.disturbance_torque_SRP;

            else
                % Dont' do anything!
            end



            % Update storage
            obj = func_update_true_SC_SRP_store(obj, mission);
        end

    end

end
```

Published with MATLAB® R2022a

Chapter 5

SC Sensors and Actuators Classes

5.1 True_SC_Battery

Table of Contents

Class: True_SC_Battery

Tracks the Battery state of charge

```
classdef True_SC_Battery < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_power_consumed % [Watts] : Instantaneous power consumed

        instantaneous_data_rate_generated % [kbps] : Data rate generated
 during current time step, in kilo bits (kb) per sec

        maximum_capacity % [Watts * hr] : Maximum energy storage capacity of
 the battery
```

[ ] Properties: Variables Computed Internally

```
        name % [string] 'Batt i'

        health % [integer] Health of sensor/actuator
        % - 0. Switched off
        % - 1. Switched on, works nominally

        temperature % [deg C] : Temperature of sensor/actuator

        instantaneous_capacity % [Watts * hr] : Instantaneous capacity of
 battery

        state_of_charge % [percentage] : SoC is defined by = 100×
 instantaneous_capacity / maximum_capacity
```

```
        charging_efficiency % float # [0, 1]

        discharging_efficiency % float # [0, 1]
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Battery(init_data, mission, i_SC, i_HW)

            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
                obj.name = ['Battery ',num2str(i_HW)];
            end

            obj.health = 1;
            obj.temperature = 10; % [deg C]

            obj.instantaneous_power_consumed =
 init_data.instantaneous_power_consumed; % [W]
            obj.instantaneous_data_rate_generated =
 init_data.instantaneous_data_rate_generated; % [kbps]

            obj.maximum_capacity = init_data.maximum_capacity; % [W hr]
            obj.instantaneous_capacity = obj.maximum_capacity; % [W hr]
            obj.state_of_charge = 100*obj.instantaneous_capacity/
obj.maximum_capacity; % [percentage]

            obj.charging_efficiency = init_data.charging_efficiency;
            obj.discharging_efficiency = init_data.discharging_efficiency; %
 [float <= 1]

            % Initialize Variables to store: instantaneous_capacity
 state_of_charge
            obj.store = [];

            obj.store.instantaneous_capacity =
 zeros(mission.storage.num_storage_steps, length(obj.instantaneous_capacity));
            obj.store.state_of_charge =
 zeros(mission.storage.num_storage_steps, length(obj.state_of_charge));
```

```
            obj = func_update_true_SC_battery_store(obj, mission);

            % Update SC Power Class

 func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
 obj, mission);

            % Update SC Data Handling Class

 func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
 obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_battery_store(obj, mission)

            if mission.storage.flag_store_this_time_step == 1
                obj.store.instantaneous_capacity(mission.storage.k_storage,:)
 = obj.instantaneous_capacity; % [W hr]
                obj.store.state_of_charge(mission.storage.k_storage,:) =
 obj.state_of_charge; % [percentage]
            end

        end
```

[ ] Methods: Main

Update Battery SoC

```
        function obj = func_main_true_SC_battery(obj, mission, i_SC)

            obj.state_of_charge = 100*obj.instantaneous_capacity/
obj.maximum_capacity; % [percentage]

            obj = func_update_true_SC_battery_store(obj, mission);

            % Update Power Consumed

 func_update_instantaneous_power_consumed(mission.true_SC{i_SC}.true_SC_power,
 obj, mission);

            % Update Data Generated

 func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
 obj, mission);

        end

    end
```

```
end
```

Published with MATLAB® R2022a

5.2 True_SC_Camera

5.2 True_SC_Camera

Table of Contents

Class: True_SC_Camera

SC's Navigation Camera

```
classdef True_SC_Camera < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_power_consumed % [Watts] : Instantaneous power consumed

        instantaneous_data_generated_per_pixel % [kb] : Data generated per
 pixel in camera image

        instantaneous_data_compression % [float <= 1] : Camera data
 compression (Optional)

        mode_true_SC_camera_selector % [string]
        % - Simple

        measurement_wait_time % [sec] How often can measurements be taken?

        location % [m] : Location of sensor, in body frame B

        orientation % [unit vector] : Normal vector from location

        orientation_up % [unit vector] : Up Normal vector from location in
 camera frame

        resolution % [x y] : Resolution of the camera in pixels (e.g. [1024
 1024])

        field_of_view % [deg] : Field of view (FOV) of the camera in deg
```

```
        flag_show_camera_plot % [Boolean] : 1 = Shows the camera plot

        flag_show_stars % [Boolean] : 1 = Show stars upto
mission.true_stars.maximum_magnitude. This takes a lot of time for wide FOV
cameras. (Optional)
```

[ ] Properties: Variables Computed Internally

```
        name % [string] 'Camera i'

        health % [integer] Health of sensor/actuator
        % - 0. Switched off
        % - 1. Switched on, works nominally

        temperature % [deg C] : Temperature of sensor/actuator

        measurement_vector % [Image]

        measurement_time % [sec] SC time when this measurement was taken

        flag_executive % [Boolean] Executive has told this sensor/actuator to
do its job

        plot_handle % Matlab plot handle for the image

        flag_target_visible % [Boolean] : 1 = Target is visible to this camera

        instantaneous_data_generated_per_sample % [kb] : Data generated per
sample, in kilo bits (kb)

        data % Other useful data
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Camera(init_data, mission, i_SC, i_HW)

            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
```

```
            obj.name = ['Camera ',num2str(i_HW)];
        end

        obj.health = 1;
        obj.temperature = 10; % [deg C]

        obj.instantaneous_power_consumed =
init_data.instantaneous_power_consumed; % [W]
        obj.instantaneous_data_generated_per_pixel =
init_data.instantaneous_data_generated_per_pixel; % [kb]
        obj.instantaneous_data_generated_per_sample = 0; % [kb] Data is
only generated when an image is captured

        obj.mode_true_SC_camera_selector =
init_data.mode_true_SC_camera_selector; % [string]
        obj.measurement_wait_time = init_data.measurement_wait_time; %
[sec]

        obj.flag_executive = 0;

        obj.measurement_time = 0; % [sec]

        obj.location = init_data.location; % [m]
        obj.orientation = init_data.orientation; % [unit vector]
        obj.orientation_up = init_data.orientation_up; % [unit vector]

        obj.resolution = init_data.resolution;  % [x y] pixel
        obj.field_of_view = init_data.field_of_view; % [deg]

        obj.flag_show_camera_plot = init_data.flag_show_camera_plot;

        if isfield(init_data, 'flag_show_stars')
            obj.flag_show_stars = init_data.flag_show_stars;
        else
            obj.flag_show_stars = 0;
        end

        obj.flag_target_visible = 0;

        if isfield(init_data, 'instantaneous_data_compression')
            obj.instantaneous_data_compression =
init_data.instantaneous_data_compression;
        else
            obj.instantaneous_data_compression = 1;
        end

        if isfield(init_data, 'data')
            obj.data = init_data.data;
        else
            obj.data = [];
        end
        obj.data.flag_take_picture = 0;

        % Initialize Variables to store: flag_target_visible
```

```
            obj.store = [];
            obj.store.flag_target_visible = 
zeros(mission.storage.num_storage_steps, length(obj.flag_target_visible));
            obj.store.flag_take_picture = 
zeros(mission.storage.num_storage_steps, length(obj.data.flag_take_picture));
            obj.store.flag_executive = 
zeros(mission.storage.num_storage_steps, length(obj.flag_executive));
            obj.store.instantaneous_data_generated_per_sample = 
zeros(mission.storage.num_storage_steps, 
length(obj.instantaneous_data_generated_per_sample)); % [kbps]
            obj.store.instantaneous_power_consumed = 
zeros(mission.storage.num_storage_steps, 
length(obj.instantaneous_power_consumed)); % [W]

            % Update Storage
            obj = func_update_true_SC_camera_store(obj, mission);

            % Update SC Power Class

func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power, 
obj, mission);

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling, 
obj, mission);


            % Store video of func_visualize_SC_attitude_orbit_during_sim
            if (mission.storage.plot_parameters.flag_save_video == 1) && 
(obj.flag_show_camera_plot == 1)
                obj.data.video_filename = [mission.storage.output_folder, 
mission.name,'_SC',num2str(i_SC),'_Camera',num2str(i_HW),'.mp4'];
                obj.data.myVideo = 
VideoWriter(obj.data.video_filename, 'MPEG-4');
                obj.data.myVideo.FrameRate = 30;  % Default 30
                obj.data.myVideo.Quality = 100;    % Default 75
                open(obj.data.myVideo);
            end

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_camera_store(obj, mission)

            if mission.storage.flag_store_this_time_step == 1
                obj.store.flag_executive(mission.storage.k_storage_attitude,:) 
= obj.flag_executive; % [Boolean]

                if obj.flag_executive == 1
```

```
                    obj.store.flag_target_visible(mission.storage.k_storage,:)
= obj.flag_target_visible; % [Boolean]
                    obj.store.flag_take_picture(mission.storage.k_storage,:) =
obj.data.flag_take_picture; % [Boolean]


obj.store.instantaneous_data_generated_per_sample(mission.storage.k_storage,:)
= obj.instantaneous_data_generated_per_sample; % [kbps]

obj.store.instantaneous_power_consumed(mission.storage.k_storage,:) =
obj.instantaneous_power_consumed; % [W]
                end
            end

        end
```

[ ] Methods: Main

Update Camera

```
        function obj = func_main_true_SC_camera(obj, mission, i_SC, i_HW)

            if (obj.flag_executive == 1) && (obj.health == 1)
                % Take measurement

                if (mission.true_time.time - obj.measurement_time) >=
obj.measurement_wait_time

                    % Sufficient time has elasped for a new measurement
                    obj.measurement_time = mission.true_time.time; % [sec]
                    obj.data.flag_take_picture = 1;

                    switch obj.mode_true_SC_camera_selector

                        case 'Simple'
                            obj = func_true_SC_camera_Simple(obj, mission,
i_SC, i_HW);

                        otherwise
                            error('Camera mode not defined!')
                    end


                    % Update Data Generated

func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

                else
                    % Data not generated in this time step
                    obj.instantaneous_data_generated_per_sample = 0; % [kb]
Data is only generated when an image is captured
                    obj.data.flag_take_picture = 0;
```

```
                end

                % Update Power Consumed

func_update_instantaneous_power_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            else
                % Do nothing
                obj.data.flag_take_picture = 0;
            end

            % Update Storage
            obj = func_update_true_SC_camera_store(obj, mission);

            % Reset Variables
            obj.flag_executive = 0;

        end
```

[ ] Methods: Simple Camera

Simple Camera mode

```
        function obj = func_true_SC_camera_Simple(obj, mission, i_SC, i_HW)

            obj.instantaneous_data_generated_per_sample =
obj.instantaneous_data_compression *
obj.instantaneous_data_generated_per_pixel * obj.resolution(1) *
obj.resolution(2); % [kb]

            if obj.flag_show_camera_plot == 1
                % Show Camera Plot

                obj.plot_handle = figure( (5*i_SC) + i_HW);
                clf
                set(obj.plot_handle,'Color',rgb('Black'));
                set(obj.plot_handle, 'Units', 'pixels', 'Position', [1 1
obj.resolution])
                %
set(obj.plot_handle,'PaperPositionMode','auto');
                set(obj.plot_handle, 'Resize','off');
                hold on

                % Plot Target Body
                for i_target = 1:1:mission.num_target

                    func_plot_target_shape(i_target, mission);

                end

                axis vis3d off
                axis equal
```

```
                material([0 1 0])

                % field of view
                camva(obj.field_of_view);

                camproj('perspective');
                axis image
                axis off;


                % Light comming from sun
                %         camlight('headlight')
                h = light;
                h.Position =
(mission.true_solar_system.SS_body{mission.true_solar_system.index_Sun}.position
-
mission.true_target{mission.true_SC{i_SC}.true_SC_navigation.index_relative_target}.posit
                h.Style = 'local';

                % Move SC away from Target

campos(mission.true_SC{i_SC}.true_SC_navigation.position_relative_target);

                target_distance =
norm(mission.true_SC{i_SC}.true_SC_navigation.position_relative_target);


                % Manage view from current attitude
                x_true_hat =
(mission.true_SC{i_SC}.true_SC_adc.rotation_matrix * obj.orientation')';

                y_true_hat =
(mission.true_SC{i_SC}.true_SC_adc.rotation_matrix * obj.orientation_up')';

                camtarget(target_distance * x_true_hat)
                camup([y_true_hat(1), y_true_hat(2), y_true_hat(3)])

                % Plot Stars
                if obj.flag_show_stars == 1



                    dot_product_angle_array =
acosd(mission.true_stars.all_stars_unit_vector * x_true_hat');
                    flag_in_FOV = logical(dot_product_angle_array <=
(obj.field_of_view*2));

                    flag_magnitude_limit =
logical(mission.true_stars.magnitude_visible <=
mission.true_stars.maximum_magnitude);

                    flag_magnitude_limit_FOV = (flag_in_FOV &
flag_magnitude_limit);
```

```
                    idx_array = find(flag_magnitude_limit_FOV);
                    hold on

                    for s = 1:1:length(idx_array)
                        this_star = target_distance *
mission.true_stars.all_stars_unit_vector(idx_array(s),:);

plot3(this_star(1),this_star(2),this_star(3),'*w','MarkerSize',(1 +
mission.true_stars.maximum_magnitude -
mission.true_stars.magnitude_visible(idx_array(s))),'MarkerFaceColor','w','MarkerEdgeColo
                    end
                end

                drawnow limitrate

                if (mission.storage.plot_parameters.flag_save_video == 1)
                    open(obj.data.myVideo);
                    writeVideo(obj.data.myVideo, getframe(obj.plot_handle));
                end

            end

            obj = func_true_SC_camera_target_visible(obj, mission, i_SC);

            % Update Storage
            obj = func_update_true_SC_camera_store(obj, mission);

        end
```

[ ] Methods: Check Target Visible

Check if Target is visible in Camera image

```
        function obj = func_true_SC_camera_target_visible(obj, mission, i_SC)

            Target_relative_pos_hat =
func_normalize_vec(mission.true_target{mission.true_SC{i_SC}.true_SC_navigation.index_rel
- mission.true_SC{i_SC}.true_SC_navigation.position);

            x_true_hat = (mission.true_SC{i_SC}.true_SC_adc.rotation_matrix *
obj.orientation')';

            Camera_angle = acosd(dot(Target_relative_pos_hat, x_true_hat)); %
[deg]

            if Camera_angle <= (obj.field_of_view)
                obj.flag_target_visible = 1;
            else
                obj.flag_target_visible = 0;
            end

        end

    end
```

```
end
```

Published with MATLAB® R2022a

5.3 True_SC_Communication_Link

Table of Contents

Class: True_SC_Communication_Link

Tracks the Links between Radio Antennas

```
classdef True_SC_Communication_Link < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        TX_spacecraft % [integer] Use 0 for Ground Station
        TX_spacecraft_Radio_HW % [integer]

        RX_spacecraft % [integer] Use 0 for Ground Station
        RX_spacecraft_Radio_HW % [integer]

        % TODO - Decide if this is should stay here or go to software comm
        wait_time_comm_dte % [sec] : Wait time without transmiting to earth.
 This is a constant.
        last_communication_time % [sec] : Last time that data has been sent.
 This is updated in SC_Executive

        flag_compute_data_rate % [Boolean]

        given_data_rate % [kbps]

        instantaneous_power_consumed % [Watts] : Communication Link control
 overhead power consumption
```

[ ] Properties: Variables Computed Internally

```
        name % [string] 'Comm Link i'

        TX_name % [string]
```

```
        RX_name % [string]

        this_data_rate % [kbps] Actually used in simulation

        flag_executive % [Boolean] Executive has told this sensor/actuator to
 do its job

        flag_TX_RX_visible % [Boolean]
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Communication_Link(init_data, mission, i_SC,
 i_HW)

            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
                obj.name = ['Comm Link ',num2str(i_HW)];
            end

            obj.flag_executive = 0;
            obj.flag_TX_RX_visible = 0;

            obj.TX_spacecraft = init_data.TX_spacecraft;
            obj.TX_spacecraft_Radio_HW = init_data.TX_spacecraft_Radio_HW;

            obj.RX_spacecraft = init_data.RX_spacecraft;
            obj.RX_spacecraft_Radio_HW = init_data.RX_spacecraft_Radio_HW;

            obj.flag_compute_data_rate = init_data.flag_compute_data_rate;
            obj.given_data_rate = init_data.given_data_rate; % [kbps]

            % Initialize the power consumption property
            if isfield(init_data, 'instantaneous_power_consumed')
                obj.instantaneous_power_consumed =
 init_data.instantaneous_power_consumed;
            else
                obj.instantaneous_power_consumed = 0.5; % Default low power
 for link control overhead
```

```
            end

            if obj.flag_compute_data_rate == 1
                obj.this_data_rate = 0; % [kbps]
            else
                obj.this_data_rate = obj.given_data_rate; % [kbps]
            end

            % Handle TX name
            if obj.TX_spacecraft == 0
                obj.TX_name =
mission.true_GS_radio_antenna{obj.TX_spacecraft_Radio_HW}.name;
            else
                tx_sc = mission.true_SC{obj.TX_spacecraft};
                if iscell(tx_sc.true_SC_radio_antenna)
                    tx_antenna =
tx_sc.true_SC_radio_antenna{obj.TX_spacecraft_Radio_HW};
                else
                    if obj.TX_spacecraft_Radio_HW ~= 1
                        error('TX_spacecraft_Radio_HW index is %d, but
true_SC_radio_antenna is not a cell array.', obj.TX_spacecraft_Radio_HW);
                    end
                    tx_antenna = tx_sc.true_SC_radio_antenna;
                end
                obj.TX_name = ['SC ', num2str(obj.TX_spacecraft), ' ',
tx_antenna.name];
            end

            % Handle RX name
            if obj.RX_spacecraft == 0
                obj.RX_name =
mission.true_GS_radio_antenna{obj.RX_spacecraft_Radio_HW}.name;
            else
                rx_sc = mission.true_SC{obj.RX_spacecraft};
                if iscell(rx_sc.true_SC_radio_antenna)
                    rx_antenna =
rx_sc.true_SC_radio_antenna{obj.RX_spacecraft_Radio_HW};
                else
                    if obj.RX_spacecraft_Radio_HW ~= 1
                        error('RX_spacecraft_Radio_HW index is %d, but
true_SC_radio_antenna is not a cell array.', obj.RX_spacecraft_Radio_HW);
                    end
                    rx_antenna = rx_sc.true_SC_radio_antenna;
                end
                obj.RX_name = ['SC ', num2str(obj.RX_spacecraft), ' ',
rx_antenna.name];
            end

            % Initialize Variables to store
            obj.store = [];

            obj.store.flag_executive =
zeros(mission.storage.num_storage_steps, length(obj.flag_executive)); %
[integer]
```

```
            obj.store.flag_TX_RX_visible =
zeros(mission.storage.num_storage_steps, length(obj.flag_TX_RX_visible)); %
[integer]
            obj.store.this_data_rate =
zeros(mission.storage.num_storage_steps, length(obj.this_data_rate)); %
[kbps]

            % Update Storage
            obj = func_update_true_SC_communication_link_store(obj, mission);

            % Register with power system if this is a spacecraft component
(not a ground station)
            if i_SC > 0

func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);
            end
        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_communication_link_store(obj,
mission)

            if mission.storage.flag_store_this_time_step == 1

                obj.store.flag_executive(mission.storage.k_storage,:) =
obj.flag_executive; % [integer]
                obj.store.flag_TX_RX_visible(mission.storage.k_storage,:) =
obj.flag_TX_RX_visible; % [integer]
                obj.store.this_data_rate(mission.storage.k_storage,:) =
obj.this_data_rate; % [kbps]

            end

        end
```

[ ] Methods: Main

Update all variables

```
        function obj = func_main_true_SC_communication_link(obj, mission,
i_SC)

            % Check Link Visibility
            if obj.TX_spacecraft == 0
                obj.flag_TX_RX_visible =
mission.true_SC{obj.RX_spacecraft}.true_SC_navigation.flag_visible_Earth;

            elseif obj.RX_spacecraft == 0
```

```
                obj.flag_TX_RX_visible =
 mission.true_SC{obj.TX_spacecraft}.true_SC_navigation.flag_visible_Earth;

            else
                error('Need to write this code where both are SC!')

            end

            % Compute Data Rate (if visible)
            if obj.flag_TX_RX_visible == 1
                % LOS to Earth avaiable
                if obj.flag_compute_data_rate == 1
                    obj.this_data_rate = 0; % [kbps]
                    error('Write code to compute Link Margin!')
                else
                    obj.this_data_rate = obj.given_data_rate; % [kbps]
                end
            else
                % In eclipse
                obj.this_data_rate = 0; % [kbps]
            end

            % Perform Data Transfer
            if (obj.flag_executive == 1) % && (obj.flag_TX_RX_visible == 1)

                if (obj.TX_spacecraft > 0) && (obj.flag_TX_RX_visible
 == 1) && ((obj.this_data_rate * mission.true_time.time_step) >=
 mission.true_SC{obj.TX_spacecraft}.software_SC_data_handling.total_data_storage)
                    obj.this_data_rate =
 mission.true_SC{obj.TX_spacecraft}.software_SC_data_handling.total_data_storage/
mission.true_time.time_step; % [kbps]
                end

                % Start TX and transmit data
                if obj.TX_spacecraft == 0
                    % This is GS
                    if
 mission.true_GS_radio_antenna{obj.TX_spacecraft_Radio_HW}.flag_executive ~= 0
                        error('[GS] TX link is already on!')
                    else

 mission.true_GS_radio_antenna{obj.TX_spacecraft_Radio_HW}.flag_executive = 1;

 mission.true_GS_radio_antenna{obj.TX_spacecraft_Radio_HW}.mode_true_GS_radio_antenna_sele
 = 'TX';

 mission.true_GS_radio_antenna{obj.TX_spacecraft_Radio_HW}.instantaneous_data_rate_transmi
 = obj.this_data_rate; % [kbps]
                    end

                else
                    % This is SC
                    tx_sc = mission.true_SC{obj.TX_spacecraft};
                    if iscell(tx_sc.true_SC_radio_antenna)
```

```
                        tx_antenna =
tx_sc.true_SC_radio_antenna{obj.TX_spacecraft_Radio_HW};
                    else
                        if obj.TX_spacecraft_Radio_HW ~= 1
                            error('TX_spacecraft_Radio_HW index is %d, but
true_SC_radio_antenna is not a cell array.', obj.TX_spacecraft_Radio_HW);
                        end
                        tx_antenna = tx_sc.true_SC_radio_antenna;
                    end

                    if tx_antenna.flag_executive ~= 0
                        error('[SC] TX link is already on!')
                    else
                        tx_antenna.flag_executive = 1;
                        tx_antenna.mode_true_SC_radio_antenna_selector = 'TX';
                        tx_antenna.instantaneous_data_rate_removed =
obj.this_data_rate; % [kbps]
                    end

                end

                % Start RX and receive data
                if obj.RX_spacecraft == 0
                    % This is GS
                    if
mission.true_GS_radio_antenna{obj.RX_spacecraft_Radio_HW}.flag_executive ~= 0
                        error('[GS] RX link is already on!')
                    else

mission.true_GS_radio_antenna{obj.RX_spacecraft_Radio_HW}.flag_executive = 1;

mission.true_GS_radio_antenna{obj.RX_spacecraft_Radio_HW}.mode_true_GS_radio_antenna_sele
= 'RX';

mission.true_GS_radio_antenna{obj.RX_spacecraft_Radio_HW}.instantaneous_data_rate_receive
= obj.this_data_rate; % [kbps]
                    end

                else
                    % This is SC
                    rx_sc = mission.true_SC{obj.RX_spacecraft};
                    if iscell(rx_sc.true_SC_radio_antenna)
                        rx_antenna =
rx_sc.true_SC_radio_antenna{obj.RX_spacecraft_Radio_HW};
                    else
                        if obj.RX_spacecraft_Radio_HW ~= 1
                            error('RX_spacecraft_Radio_HW index is %d, but
true_SC_radio_antenna is not a cell array.', obj.RX_spacecraft_Radio_HW);
                        end
                        rx_antenna = rx_sc.true_SC_radio_antenna;
                    end

                    if rx_antenna.flag_executive ~= 0
                        error('[SC] RX link is already on!')
```

```
                    else
                        rx_antenna.flag_executive = 1;
                        rx_antenna.mode_true_SC_radio_antenna_selector = 'RX';
                        rx_antenna.instantaneous_data_rate_generated =
 obj.this_data_rate; % [kbps]
                    end
                end

                % Update power consumption for this link's control overhead
                if i_SC > 0

 func_update_instantaneous_power_consumed(mission.true_SC{i_SC}.true_SC_power,
 obj, mission);
                end
            end

            % Update Storage
            obj = func_update_true_SC_communication_link_store(obj, mission);

            % Reset All Variables
            obj.flag_executive = 0;

        end

    end

end
```

Published with MATLAB® R2022a

5.4 True_SC_Chemical_Thruster

Table of Contents

Class: True_SC_Chemical_Thruster

Individual SC's chemical thruster

```
classdef True_SC_Chemical_Thruster < handle

    % True_SC_Chemical_Thruster class represents a single chemical-thruster
    % with various properties and methods for simulation and analysis.
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_power_consumption  %[Watts] : Instantaneous power
 consumed by unit (if it is switched on)

        thruster_warm_up_power_consumed  %[Watts] : Power consumed during
 warm-up time

        command_actuation_power_consumed %[Watts] : Power consumed during
 actuation

        name                             % Name of the thruster

        thruster_noise                   %[N] : Added to every dimension of
 commanded_thrust

        isp                              %[s] : Specific impulse of the
 thruster

        command_wait_time                %[sec] : Seconds between commands
```

```
        orientation                     %[Unit vector] : Normal vector of
thrust in body frame B
        location                        %[m] : Location of actuator, in body
frame B

        maximum_thrust                  %[N]
        minimum_thrust                  %[N] : This need not be 0
```

[ ] Properties: Variables Computed Internally

```
        instantaneous_power_consumed    %[Watts] : Alias for power tracking
system

        health                          % Health of the thruster (0 : Not
working - 1 : Working)
        temperature                     %[Celsius] Temperature of the
thruster

        instantaneous_data_generated_per_sample     %[kb] : Data generated
during the current time step, in kilo bits

        control_force_CT                %[N] : Control force vector generated
by the unit that passes through Center of Mass of SC
        control_torque_CT               %[Nm] : Control torque about Center
of Mass of SC, generated by the unit

        mode_true_chemical_thruster_selector% Mode (Truth/Simple)
        flag_executive % [Bool] do we need to fire this time step (set by sw
orbit control)
        flag_warming_up % [Bool] is the thruster in warm-up mode

        thruster_warm_up_time           %[sec] : How much warm-up time is
needed?
        accumulated_warm_up_time        %[sec] : How long has the thruster
been warming up
        command_time                    %[sec] : Time when latest Command was
actuated

        warm_up_start_time              %[sec] : Time when warm-up started
        ready_state_start_time          %[sec] : Time when thruster entered
ready state
        pending_fire                    %[Boolean] : Flag to indicate a
pending fire command between cycles
        pending_thrust                  %[N] : Remembered thrust value for a
pending fire command

        command_actuation               %[Boolean] : 1 = Command actuation
during this time step (after actuator has warmed up)
        command_executed                %[Boolean] : 1 = Command executed
during this time step

        thruster_state                  %[String] : Current state of the
thruster: 'idle', 'warming_up', 'ready', 'firing'
```

```
        force_inertial                  %[N] : Vector force in inertial frame
applied by this thruster

        commanded_thrust                %[N] : Comes from the SC's orbit
control software

        true_commanded_thrust           %[N] : Actual thrust with noise
applied, unknown to SC software

        % New properties for fuel consumption
        fuel_consumed_per_firing        %[kg] : Amount of fuel consumed in
current firing
        total_fuel_consumed             %[kg] : Total fuel consumed by this
thruster
```

[ ] Properties: Storage Variables

```
        store                           % Structure to store historical data

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Chemical_Thruster(init_data, mission, i_SC,
i_MT)
            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
                obj.name = ['Chemical Thruster ', num2str(i_MT)];
            end
            obj.health = true;
            obj.temperature = 20;
            obj.instantaneous_power_consumption =
init_data.instantaneous_power_consumption; % Watts
            obj.instantaneous_power_consumed =
init_data.instantaneous_power_consumption; % Watts

            % Initialize specific power consumption settings
            if isfield(init_data, 'thruster_warm_up_power_consumed')
                obj.thruster_warm_up_power_consumed =
init_data.thruster_warm_up_power_consumed; % Watts
            else
                obj.thruster_warm_up_power_consumed =
obj.instantaneous_power_consumption; % Default to regular power
```

```
            end

            if isfield(init_data, 'command_actuation_power_consumed')
                obj.command_actuation_power_consumed =
init_data.command_actuation_power_consumed; % Watts
            else
                obj.command_actuation_power_consumed = 3 *
obj.instantaneous_power_consumption; % Default to 3x regular power
            end

            obj.instantaneous_data_generated_per_sample =
init_data.instantaneous_data_generated_per_sample; % Kb
            obj.thruster_noise = init_data.chemical_thruster_noise; % Noise
level
            obj.command_wait_time = init_data.command_wait_time; % Seconds
between commands
            obj.location = init_data.location; % Meters (body frame)
            obj.orientation = init_data.orientation; % Unit vector (body
frame)

            obj.isp = init_data.chemical_thruster_ISP; % sec
            obj.force_inertial = zeros(1,3);

            obj.minimum_thrust = init_data.minimum_thrust;
            obj.maximum_thrust = init_data.maximum_thrust;

            % Ensure thrust variables are properly initialized as scalars
            obj.commanded_thrust = 0; % Initialize as scalar 0, not empty
array
            obj.true_commanded_thrust = 0; % Initialize as scalar 0, not empty
array
            obj.control_force_CT = zeros(1,3); % Ensure it's a 1x3 array
            obj.control_torque_CT = zeros(1,3); % Ensure it's a 1x3 array

            % Initialize warm-up related properties
            obj.thruster_warm_up_time = 30; % Default warm-up time (30
seconds)
            obj.accumulated_warm_up_time = 0;
            obj.warm_up_start_time = 0;
            obj.ready_state_start_time = 0;
            obj.flag_warming_up = false;
            obj.thruster_state = 'idle';

            % Initialize command properties
            obj.command_actuation = false;
            obj.command_executed = false;
            obj.command_time = 0;
            obj.flag_executive = false;
            obj.pending_fire = false;
            obj.pending_thrust = 0;

            % Initialize fuel consumption properties
            obj.fuel_consumed_per_firing = 0;
            obj.total_fuel_consumed = 0;
```

```
            % Initialize Storage Variables
            obj.store = [];
            obj.store.commanded_thrust =
 zeros(mission.storage.num_storage_steps,1);
            obj.store.true_commanded_thrust =
 zeros(mission.storage.num_storage_steps,1);
            obj.store.force_inertial =
 zeros(mission.storage.num_storage_steps,3); % Changed from 1 to 3 columns
            obj.store.fuel_consumed_per_firing =
 zeros(mission.storage.num_storage_steps,1);
            obj.store.total_fuel_consumed =
 zeros(mission.storage.num_storage_steps,1);
            obj.store.thruster_state =
 cell(mission.storage.num_storage_steps,1);
            obj.store.warm_up_progress =
 zeros(mission.storage.num_storage_steps,1);
            obj.store.pending_fire =
 zeros(mission.storage.num_storage_steps,1);
            obj.store.pending_thrust =
 zeros(mission.storage.num_storage_steps,1);
            obj.store.control_torque_CT =
 zeros(mission.storage.num_storage_steps,3); % Add storage

            % Update storage
            func_update_true_chemical_thruster_store(obj, mission);

            % Update SC Power Class

 func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
 obj, mission);

            % Update SC Data Handling Class

 func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
 obj, mission);
        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_chemical_thruster_store(obj, mission)
            % Append new thrust data to the storage arrays

            % Ensure all values are valid before storing (defend against empty
 arrays)
            if isempty(obj.commanded_thrust)
                obj.commanded_thrust = 0;
            end

            if isempty(obj.true_commanded_thrust)
                obj.true_commanded_thrust = 0;
```

```
            end

            % Store values with safety checks
            obj.store.commanded_thrust(mission.storage.k_storage,:) =
obj.commanded_thrust;
            obj.store.true_commanded_thrust(mission.storage.k_storage,:) =
obj.true_commanded_thrust;
            obj.store.force_inertial(mission.storage.k_storage,:) =
obj.force_inertial;
            obj.store.fuel_consumed_per_firing(mission.storage.k_storage,:) =
obj.fuel_consumed_per_firing;
            obj.store.total_fuel_consumed(mission.storage.k_storage,:) =
obj.total_fuel_consumed;
            obj.store.thruster_state{mission.storage.k_storage} =
obj.thruster_state;

            % Store pending fire information
            obj.store.pending_fire(mission.storage.k_storage) =
obj.pending_fire;
            obj.store.pending_thrust(mission.storage.k_storage) =
obj.pending_thrust;

            % Store control torque
            obj.store.control_torque_CT(mission.storage.k_storage,:) =
obj.control_torque_CT;

            % Calculate warm-up progress as a percentage
            if obj.thruster_warm_up_time > 0
                obj.store.warm_up_progress(mission.storage.k_storage) =
min(100, (obj.accumulated_warm_up_time / obj.thruster_warm_up_time) * 100);
            else
                obj.store.warm_up_progress(mission.storage.k_storage) = 100; %
No warm-up needed
            end
        end
```

[ ] Methods: Start Warm-Up

```
        function obj = func_start_warm_up(obj, mission)
            % Start the thruster warm-up process
            if ~obj.flag_warming_up && strcmp(obj.thruster_state, 'idle') &&
obj.health
                obj.flag_warming_up = true;
                obj.thruster_state = 'warming_up';
                obj.warm_up_start_time = mission.true_time.time;
                obj.accumulated_warm_up_time = 0;
            end
        end
```

[ ] Methods: Check Warm-Up Status

```
        function is_ready = func_is_thruster_ready(obj)
            % Check if the thruster is ready to fire
```

```
            is_ready = strcmp(obj.thruster_state, 'ready') ||
strcmp(obj.thruster_state, 'firing');
        end
```

[ ] Methods: Validate Thruster Properties

```
        function obj = func_validate_thruster_properties(obj)
            % Safety function to ensure all properties are properly
initialized

            % Check and fix scalar properties
            if isempty(obj.commanded_thrust)
                obj.commanded_thrust = 0;
            end

            if isempty(obj.true_commanded_thrust)
                obj.true_commanded_thrust = 0;
            end

            if isempty(obj.instantaneous_power_consumption)
                obj.instantaneous_power_consumption = 0;
            end

            if isempty(obj.instantaneous_power_consumed)
                obj.instantaneous_power_consumed = 0;
            end

            % Check and fix vector properties
            if isempty(obj.force_inertial) ||
~isequal(size(obj.force_inertial), [1,3])
                obj.force_inertial = zeros(1,3);
            end

            if isempty(obj.control_torque_CT) ||
~isequal(size(obj.control_torque_CT), [1,3])
                obj.control_torque_CT = zeros(1,3);
            end

            if isempty(obj.control_force_CT) ||
~isequal(size(obj.control_force_CT), [1,3])
                obj.control_force_CT = zeros(1,3);
            end

            % Check other critical properties
            if isempty(obj.thruster_state)
                obj.thruster_state = 'idle';
            end

            if isempty(obj.ready_state_start_time)
                obj.ready_state_start_time = 0;
            end

            if isempty(obj.pending_fire)
```

```
            obj.pending_fire = false;
        end

        if isempty(obj.pending_thrust)
            obj.pending_thrust = 0;
        end

        if isempty(obj.instantaneous_data_generated_per_sample)
            obj.instantaneous_data_generated_per_sample = 0;
        end
    end
```

[ ] Methods: Main

```
    function func_main_true_chemical_thruster(obj, mission, i_SC, ~)
        % Main function for True_SC_Chemical_Thruster
        % Controls thrust application, power consumption, and data
generation.

        % Validate properties to ensure everything is properly initialized
        obj = func_validate_thruster_properties(obj);

        % Reset fuel consumed this firing (but NOT command_executed - that
needs
        % to persist for one cycle so orbit control can see it)
        obj.fuel_consumed_per_firing = 0;

        % Initialize power consumption to idle value
        obj.instantaneous_power_consumption = 0;
        obj.instantaneous_power_consumed = 0;

        % Save a local copy of command_executed for this cycle's
processing
        was_executed_last_cycle = obj.command_executed;

        % Check health status
        if obj.health == 0
            obj.thruster_state = 'idle';
            obj.flag_warming_up = false;
            obj.command_executed = false;
            return;
        end

        % State machine for thruster operation
        switch obj.thruster_state
            case 'idle'
                % Check if we need to start warming up
                if obj.flag_warming_up
                    disp(['Thruster transitioning from idle to warming_up
at time ', num2str(mission.true_time.time), ' sec']);
                    obj.thruster_state = 'warming_up';
                    obj.accumulated_warm_up_time = 0;
                end
```

```
                    % Minimal idle power consumption (fixed 0.1W in idle
state)
                    obj.instantaneous_power_consumption = 0.1;

                case 'warming_up'
                    % Update accumulated warm-up time
                    obj.accumulated_warm_up_time =
obj.accumulated_warm_up_time + mission.true_time.time_step;

                    % Check if warm-up is complete
                    if obj.accumulated_warm_up_time >=
obj.thruster_warm_up_time
                        disp(['Thruster completed warm-up and entering ready
state at time ', num2str(mission.true_time.time), ' sec']);
                        obj.thruster_state = 'ready';
                        obj.ready_state_start_time = mission.true_time.time; %
Set the start time of ready state
                    end

                    % Set warm-up power consumption
                    obj.instantaneous_power_consumption =
obj.thruster_warm_up_power_consumed;

                case 'ready'
                    % Thruster is ready to fire
                    % Maintain warm-up power until firing or timeout
                    obj.instantaneous_power_consumption =
obj.thruster_warm_up_power_consumed;

                    % Check for command actuation
                    if obj.flag_executive && obj.commanded_thrust > 0
                        % Save the command for the next cycle
                        obj.pending_fire = true;
                        obj.pending_thrust = obj.commanded_thrust;

                        disp(['Thruster transitioning from ready to firing at
time ', num2str(mission.true_time.time), ' sec']);
                        disp(['  Commanded thrust: ',
num2str(obj.commanded_thrust), ' N']);
                        obj.thruster_state = 'firing';
                    end

                    % Check for timeout (5 minutes idle in ready state)
                    % Use the ready_state_start_time as reference to measure
timeout period
                    if (mission.true_time.time - obj.ready_state_start_time) >
300
                        disp(['Thruster timing out from ready state after ',
num2str(mission.true_time.time - obj.ready_state_start_time), ' seconds']);
                        obj.thruster_state = 'idle';
                        obj.flag_warming_up = false;
                    end
```

```
            case 'firing'
                % Process thruster firing - use either current command or
pending command from previous cycle
                if (obj.flag_executive && obj.commanded_thrust > 0) ||
obj.pending_fire
                    try
                        % Use either active command or saved pending
command
                        if obj.flag_executive && obj.commanded_thrust > 0
                            thrust_to_use = obj.commanded_thrust;
                        else
                            thrust_to_use = obj.pending_thrust;
                            disp(['Using pending thrust from previous
cycle: ', num2str(thrust_to_use), ' N']);
                        end

                        % Update thrust with noise
                        obj.true_commanded_thrust = thrust_to_use +
obj.thruster_noise * (2*rand() - 1);

                        % Ensure thrust remains within bounds
                        obj.true_commanded_thrust =
max(min(obj.true_commanded_thrust, obj.maximum_thrust), obj.minimum_thrust);

                        % Get current attitude matrix to transform from
body to inertial frame
                        R =
quaternionToRotationMatrix(mission.true_SC{i_SC}.true_SC_adc.attitude);

                        % Calculate force vector in body frame first
                        force_body = obj.true_commanded_thrust *
obj.orientation;

                        % Transform to inertial frame
                        obj.force_inertial = R * force_body'; % Netwons

                        % Log the thruster firing
                        disp(['THRUSTER FIRING with thrust
of ', num2str(obj.true_commanded_thrust), ' N at time ',
num2str(mission.true_time.time), ' sec']);

                        % Make sure that the control orbit verifies if
                        % the deltaV has been performed correctly

mission.true_SC{i_SC}.software_SC_control_orbit.flag_executive = 1;

                        % Add thrust on the SC (in inertial frame)

mission.true_SC{i_SC}.true_SC_navigation.control_force =
mission.true_SC{i_SC}.true_SC_navigation.control_force + obj.force_inertial';

                        % Compute the disturbance torque
                        r = obj.location -
mission.true_SC{i_SC}.true_SC_body.location_COM;
```

```
                            obj.control_torque_CT = cross(r, force_body);

                            % Apply torque to attitude system

mission.true_SC{i_SC}.true_SC_adc.disturbance_torque =
mission.true_SC{i_SC}.true_SC_adc.disturbance_torque + obj.control_torque_CT;

                            % Update power consumption (warm-up + actuation)
                            obj.instantaneous_power_consumption =
obj.thruster_warm_up_power_consumed + obj.command_actuation_power_consumed;

                            % Set command execution flag - this will persist
until next cycle
                            obj.command_executed = true;

                            % Calculate DeltaV applied and directly update
orbit control
                            dt = mission.true_time.time_step;
                            sc_mass =
mission.true_SC{i_SC}.true_SC_body.total_mass;

                            % Calculate DeltaV applied (normalized direction *
magnitude)
                            DeltaV_applied = (norm(obj.force_inertial) * dt /
sc_mass) * (obj.force_inertial / norm(obj.force_inertial));

                            % Update orbit control's total executed DeltaV
directly

mission.true_SC{i_SC}.software_SC_control_orbit.total_DeltaV_executed =
mission.true_SC{i_SC}.software_SC_control_orbit.total_DeltaV_executed +
DeltaV_applied;

                            % Log the actuation
                            disp(['Applied DeltaV: [',
num2str(DeltaV_applied(1)), ', ', num2str(DeltaV_applied(2)), ', ',
num2str(DeltaV_applied(3)), '] m/s']);
                            disp(['Total DeltaV now: [',
num2str(mission.true_SC{i_SC}.software_SC_control_orbit.total_DeltaV_executed(1)), ',
', ...

num2str(mission.true_SC{i_SC}.software_SC_control_orbit.total_DeltaV_executed(2)), ',
', ...

num2str(mission.true_SC{i_SC}.software_SC_control_orbit.total_DeltaV_executed(3)), ']
m/s']);

                            % Calculate and display the remaining DeltaV to be
applied
                            remaining_DeltaV =
mission.true_SC{i_SC}.software_SC_control_orbit.desired_control_DeltaV -
mission.true_SC{i_SC}.software_SC_control_orbit.total_DeltaV_executed;
                            disp(['Remaining DeltaV: ',
num2str(norm(remaining_DeltaV)), ' m/s']);
```

```
                            % Data generatio
                            if isempty(obj.instantaneous_data_volume)
                                obj.instantaneous_data_volume =
obj.instantaneous_data_generated;
                            end

                            % Calculate fuel consumption
                            dt = mission.true_time.time_step;
                            g0 = 9.80665; % m/s^2
                            obj.fuel_consumed_per_firing =
(obj.true_commanded_thrust * dt) / (obj.isp * g0);
                            obj.total_fuel_consumed = obj.total_fuel_consumed
+ obj.fuel_consumed_per_firing;

                            % Consume fuel from the tank if fuel tank exists
                            if
isfield(mission.true_SC{i_SC}, 'true_SC_fuel_tank') && ...

mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_fuel_tank > 0

                                % Find the assigned fuel tank for this
thruster (assuming the first one for now)
                                i_tank = 1; % In a more complex
implementation, each thruster might have a specific tank assigned

                                % Consume fuel from the tank

mission.true_SC{i_SC}.true_SC_fuel_tank{i_tank}.func_consume_fuel(obj.fuel_consumed_per_f
                            end

                            % Clear pending fire flag after successful firing
                            obj.pending_fire = false;
                            obj.pending_thrust = 0;

                        catch exception
                            % Log error but continue execution
                            %                             warning('Error
during thruster firing: %s', exception.message);
                            warning('Error during thruster firing');
                            obj.thruster_state = 'ready';
                            obj.command_executed = false;
                            obj.pending_fire = false;
                            obj.pending_thrust = 0;
                        end
                    else
                        % No command to fire, go back to ready state
                        if strcmp(obj.thruster_state, 'firing')
                            disp(['Thruster returning to ready state from
firing at time ', num2str(mission.true_time.time), ' sec']);
                        end
                        obj.thruster_state = 'ready';
                        % We don't reset command_executed here as it needs to
persist for one cycle
```

```
                end
            end

            % Always update power consumed for power tracking
            obj.instantaneous_power_consumed =
obj.instantaneous_power_consumption;

            % Update Power Consumed

func_update_instantaneous_power_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            % Update Data Generated

func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

            % Update storage
            obj.func_update_true_chemical_thruster_store(mission);

            % Reset executive flag and thrust command after processing
            obj.flag_executive = false;
            obj.commanded_thrust = 0;
            obj.control_torque_CT = zeros(1,3);

            % Reset command_executed flag ONLY if it was set in the previous
cycle
            % (not the current one)
            if was_executed_last_cycle
                obj.command_executed = false;
            end

            obj.true_commanded_thrust = 0;
        end

    end

end
```

Published with MATLAB® R2022a

5.5 True_SC_Fuel_Tank

Table of Contents

Class: True_SC_Fuel_Tank

Tracks the fuel state of the spacecraft propellant tank

```
classdef True_SC_Fuel_Tank < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        name                       % [string] 'Fuel Tank i'

        instantaneous_power_consumed      % [Watts] Power consumed by the fuel
 tank (e.g., heaters)

        instantaneous_data_rate_generated % [kbps] Data rate generated during
 current time step

        maximum_capacity           % [kg] Maximum fuel mass capacity

        instantaneous_fuel_mass % [kg] Current fuel mass in the tank

        fuel_density               % [kg/m^3] Density of the propellant

        location                   % [m] Location of the tank in the body frame

        shape_model                % Structure containing shape model information
```

[ ] Properties: Variables Computed Internally

```
        health                     % [integer] Health of fuel tank (0: Off, 1:
 On)

        temperature                % [deg C] Temperature of fuel tank
```

```
        flag_update_SC_body     % [Boolean] Flag to signal when SC body mass
 needs to be updated
```

[ ] Properties: Storage Variables

```
        store                   % Structure to store historical data

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Fuel_Tank(init_data, mission, i_SC, i_HW)
            % Constructor for the fuel tank class

            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
                obj.name = ['Fuel Tank ', num2str(i_HW)];
            end

            obj.health = 1; % Default to healthy
            obj.temperature = 20; % Default temperature in Celsius

            % Power and data parameters
            obj.instantaneous_power_consumed =
 init_data.instantaneous_power_consumed;
            obj.instantaneous_data_rate_generated =
 init_data.instantaneous_data_rate_generated;

            % Fuel parameters
            obj.maximum_capacity = init_data.maximum_capacity;
            obj.instantaneous_fuel_mass = init_data.initial_fuel_mass;
            obj.fuel_density = init_data.fuel_density;

            % Physical parameters
            obj.location = init_data.location;

            % Shape model if provided
            if isfield(init_data, 'shape_model')
                obj.shape_model = init_data.shape_model;
            else
                obj.shape_model = [];
            end

            % Flag for body update
```

```
            obj.flag_update_SC_body = 0;

            % Initialize storage variables
            obj.store = [];
            obj.store.instantaneous_fuel_mass =
zeros(mission.storage.num_storage_steps, 1);
            obj.store.instantaneous_power_consumed =
zeros(mission.storage.num_storage_steps, 1);

            % Update storage
            obj = func_update_true_SC_fuel_tank_store(obj, mission);

            % Update SC Power Class

func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);
        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_fuel_tank_store(obj, mission)
            % Update storage variables for the fuel tank

            if mission.storage.flag_store_this_time_step == 1

obj.store.instantaneous_fuel_mass(mission.storage.k_storage, :) =
obj.instantaneous_fuel_mass;

obj.store.instantaneous_power_consumed(mission.storage.k_storage, :) =
obj.instantaneous_power_consumed;
            end
        end
```

[ ] Methods: Consume Fuel

```
        function obj = func_consume_fuel(obj, fuel_mass_consumed)
            % Consume fuel from the tank

            % Check if there's enough fuel
            if fuel_mass_consumed > obj.instantaneous_fuel_mass
                warning('Fuel tank %s: Attempted to consume more fuel than
available!', obj.name);
                fuel_mass_consumed = obj.instantaneous_fuel_mass;
            end

            % Update fuel mass
```

```
            obj.instantaneous_fuel_mass = obj.instantaneous_fuel_mass -
fuel_mass_consumed;

            % Set flag to update SC body
            obj.flag_update_SC_body = 1;
        end
```

[ ] Methods: Main

```
        function obj = func_main_true_SC_fuel_tank(obj, mission, i_SC)
            % Main function for the fuel tank

            % Update propellant mass in the spacecraft body
            if obj.flag_update_SC_body == 1
                % Instead of directly updating the mass, just set the flag for
the body to update
                % The body's func_update_SC_body_mass will grab the latest
fuel mass

mission.true_SC{i_SC}.true_SC_body.flag_update_SC_body_total_mass_COM_MI = 1;

                % Reset update flag
                obj.flag_update_SC_body = 0;
            end

            % Update power system with this tank's power consumption (heaters,
valves, etc.)

func_update_instantaneous_power_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            % Update storage
            obj = func_update_true_SC_fuel_tank_store(obj, mission);
        end

    end

end
```

Published with MATLAB® R2022a

5.6 True_SC_Generic_Sensor

Table of Contents

Class: True_SC_Generic_Sensor

Generic Sensor class

```
classdef True_SC_Generic_Sensor < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_power_consumed % [Watts] : Instantaneous power consumed

        instantaneous_data_rate_generated % [kbps] : Data rate, in kilo bits
 per sec (kbps)
```

[ ] Properties: Variables Computed Internally

```
        name % [string] 'Generic Sensor i'

        health % [integer] Health of sensor/actuator
        % - 0. Switched off
        % - 1. Switched on, works nominally

        temperature % [deg C] : Temperature of sensor/actuator

        flag_executive % [Boolean] Executive has told this sensor/actuator to
 do its job

        data % Other useful data
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Generic_Sensor(init_data, mission, i_SC, i_HW)

            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
                obj.name = ['Generic Sensor ',num2str(i_HW)];
            end

            obj.health = 1;
            obj.temperature = 10; % [deg C]

            obj.instantaneous_power_consumed =
 init_data.instantaneous_power_consumed; % [W]
            obj.instantaneous_data_rate_generated =
 init_data.instantaneous_data_rate_generated; % [kbps]

            obj.flag_executive = 0;

            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end

            % Initialize Variables to store: measurement_vector
            obj.store = [];
            obj.store.flag_executive =
 zeros(mission.storage.num_storage_steps, length(obj.flag_executive));
            obj.store.instantaneous_data_rate_generated =
 zeros(mission.storage.num_storage_steps,
 length(obj.instantaneous_data_rate_generated)); % [kbps]
            obj.store.instantaneous_power_consumed =
 zeros(mission.storage.num_storage_steps,
 length(obj.instantaneous_power_consumed)); % [W]

            % Update Storage
            obj = func_update_true_SC_generic_sensor_store(obj, mission);

            % Update SC Power Class

 func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
 obj, mission);

            % Update SC Data Handling Class
```

```
func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_generic_sensor_store(obj, mission)

            if mission.storage.flag_store_this_time_step == 1
                obj.store.flag_executive(mission.storage.k_storage_attitude,:)
= obj.flag_executive; % [Boolean]

                if obj.flag_executive == 1

obj.store.instantaneous_data_rate_generated(mission.storage.k_storage,:) =
obj.instantaneous_data_rate_generated; % [kbps]

obj.store.instantaneous_power_consumed(mission.storage.k_storage,:) =
obj.instantaneous_power_consumed; % [W]
                end
            end

        end
```

[ ] Methods: Main

Update Generic Sensor

```
        function obj = func_main_true_SC_generic_sensor(obj, mission, i_SC)

            if (obj.flag_executive == 1) && (obj.health == 1)
                % Take measurement

                if
isfield(obj.data, 'instantaneous_power_consumed_per_SC_mode')
                    obj.instantaneous_power_consumed =
obj.data.instantaneous_power_consumed_per_SC_mode(mission.true_SC{i_SC}.software_SC_execu
[W]
                end

                % Update Power Consumed

func_update_instantaneous_power_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

                % Update Data Generated

func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);
```

```
            else
                % Do nothing
            end

            % Update Storage
            obj = func_update_true_SC_generic_sensor_store(obj, mission);

            % Reset Variables
            obj.flag_executive = 0;

        end

    end

end
```

Published with MATLAB® R2022a

5.7 True_SC_IMU

Table of Contents

Class: True_SC_IMU

Tracks the IMU measurements

```
classdef True_SC_IMU < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_power_consumed % [Watts] : Instantaneous power consumed

        instantaneous_data_generated_per_sample % [kb] : Data generated per
 sample, in kilo bits (kb)

        mode_true_SC_imu_selector % [string]
        % - Truth
        % - Simple

        measurement_noise % [rad/sec] (1-sigma standard deviation)

        measurement_wait_time % [sec]

        location % [m] : Location of sensor, in body frame B

        orientation % [unit vector] : Normal vector from location
```

[ ] Properties: Variables Computed Internally

```
        name % [string] 'Sun Sensor i'

        health % [integer] Health of sensor/actuator
        % - 0. Switched off
```

```
        % - 1. Switched on, works nominally

        temperature % [deg C] : Temperature of sensor/actuator

        measurement_vector % [quaternion]

        measurement_time % [sec] SC time when this measurement was taken

        flag_executive % [Boolean] Executive has told this sensor/actuator to
 do its job

        data % Other useful data
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_IMU(init_data, mission, i_SC, i_HW)

            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
                obj.name = ['IMU ',num2str(i_HW)];
            end

            obj.health = 1;
            obj.temperature = 10; % [deg C]

            obj.instantaneous_power_consumed =
 init_data.instantaneous_power_consumed; % [W]
            obj.instantaneous_data_generated_per_sample =
 init_data.instantaneous_data_generated_per_sample; % [kb]

            obj.mode_true_SC_imu_selector =
 init_data.mode_true_SC_imu_selector; % [string]
            obj.measurement_wait_time = init_data.measurement_wait_time; %
 [sec]
            obj.measurement_noise = init_data.measurement_noise; % [rad]

            obj.measurement_vector = zeros(1,3);

            obj.flag_executive = 1;
```

```
            obj.measurement_time = -inf; % [sec]

            obj.location = init_data.location; % [m]
            obj.orientation = init_data.orientation; % [unit vector]

            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end

            % Initialize Variables to store: measurement_vector
            obj.store = [];
            obj.store.measurement_vector =
zeros(mission.storage.num_storage_steps, length(obj.measurement_vector));

            % Update Storage
            obj = func_update_true_SC_imu_store(obj, mission);

            % Update SC Power Class

func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_imu_store(obj, mission)

            if mission.storage.flag_store_this_time_step_attitude == 1

obj.store.measurement_vector(mission.storage.k_storage_attitude,:) =
obj.measurement_vector; % [quaternion]
            end

        end
```

[ ] Methods: Main

Update Camera

```
        function obj = func_main_true_SC_imu(obj, mission, i_SC)

            if (obj.flag_executive == 1) && (obj.health == 1)
```

```
               % Take measurement

               if (mission.true_time.time_attitude - obj.measurement_time) >=
obj.measurement_wait_time

                   % Sufficient time has elasped for a new measurement
                   obj.measurement_time = mission.true_time.time_attitude; %
[sec]

                   switch obj.mode_true_SC_imu_selector

                       case 'Truth'
                           obj = func_true_SC_imu_Truth(obj, mission, i_SC);

                       case 'Simple'
                           obj = func_true_SC_imu_Simple(obj, mission, i_SC);

                       otherwise
                           error('IMU mode not defined!')
                   end

                   % Update Data Generated

func_update_instantaneous_data_generated_attitude(mission.true_SC{i_SC}.true_SC_data_hand
obj, mission);

               else
                   % Data not generated in this time step

               end

               % Update Power Consumed

func_update_instantaneous_power_consumed_attitude(mission.true_SC{i_SC}.true_SC_power,
obj, mission);


           else
               % Do nothing

           end

           % Update Storage
           obj = func_update_true_SC_imu_store(obj, mission);

           % Reset Variables
           obj.flag_executive = 0;

       end
```

[ ] Methods: Truth

IMU mode

```
        function obj = func_true_SC_imu_Truth(obj, mission, i_SC)
            obj.measurement_vector =
 mission.true_SC{i_SC}.true_SC_adc.angular_velocity;
        end
```

[ ] Methods: Simple

IMU mode

```
        function obj = func_true_SC_imu_Simple(obj, mission, i_SC)
            obj.measurement_vector =
 mission.true_SC{i_SC}.true_SC_adc.angular_velocity +
 obj.measurement_noise*randn(1,3) ;
        end

    end

end
```

Published with MATLAB® R2022a

5.8 True_SC_Micro_Thruster

Table of Contents

Class: True_SC_Micro_Thruster

Individual SC's micro thruster

```
classdef True_SC_Micro_Thruster < handle

    % True_SC_Micro_Thruster class represents a single micro-thruster
    % with various properties and methods for simulation and analysis.
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_power_consumption  %[Watts] : Instantaneous power
 consumed by unit (if it is switched on)

        instantaneous_data_generated_per_sample     %[kb] : Data generated
 during the current time step, in kilo bits

        mode_true_SC_micro_thruster_selector % Mode (Truth/Simple)

        thruster_noise                   %[N] : Added to every dimension of
 commanded_thrust

        isp                              %[s] : Specific impulse of the
 thruster

        maximum_thrust                   %[N]

        minimum_thrust                   %[N]

        command_wait_time                %[sec] : Seconds betzeen commands
```

```
        orientation                     %[Unit vector] : Normal vector of
thrust in body frame B

        location                        %[m] : Location of actuator, in body
frame B
```

[ ] Properties: Variables Computed Internally

```
        instantaneous_data_volume       % [kb]

        instantaneous_power_consumed    %[Watts]
        thruster_warm_up_power_consumed %[Watts] : Power consumed during
warm-up time
        command_actuation_power_consumed %[Watts] : Power consumed during
actuation
        name                            % Name of the thruster
        health                          % Health of the thruster (0 : Not
working - 1 : Working)
        temperature                     %[Celcius] Temerature of the thruster

        control_force_MT                %[N] : Control force vector generated
by the unit that passes through Center of Mass of SC
        control_torque_MT               %[Nm] : Control torque about Center
of Mass of SC, generated by the unit

        thruster_warm_up_time           %[sec] : How much warm-up time is
needed?
        accumulated_warm_up_time        %[sec]
        command_time                    %[sec] : Time when latest Command was
actuated

        command_actuation               %[Boolean] :  Command actuation
during this time step (after actuator has warmed up)
        command_executed                %[Boolean] :  Command executed during
this time step

        commanded_thrust                %[N] : Comes from the SC's software

        true_commanded_thrust           %[N] : Add thruster noise to
commanded_thrust. This is the actual thrust of this thruster, which the SC
software doesn t know.

        % Fuel consumption properties

        fuel_consumed_per_firing        %[kg] : Amount of fuel consumed in
current firing
        total_fuel_consumed             %[kg] : Total fuel consumed by this
thruster
```

[ ] Properties: Storage Variables

```
        store
```

```
    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Micro_Thruster(init_data, mission, i_SC, i_MT)
            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
                obj.name = ['Micro Thruster ', num2str(i_MT)];
            end
            obj.health = true;
            obj.temperature = 20;
            obj.instantaneous_power_consumption =
 init_data.instantaneous_power_consumption; % Watts
            obj.instantaneous_power_consumed =
 init_data.instantaneous_power_consumption; % Watts
            obj.instantaneous_data_generated_per_sample =
 init_data.instantaneous_data_generated_per_sample; % Kb
            obj.mode_true_SC_micro_thruster_selector =
 init_data.mode_true_SC_micro_thruster_selector; % Mode (Truth/Simple)
            obj.command_wait_time = init_data.command_wait_time; % Seconds
 between commands
            obj.location = init_data.location; % Meters (body frame)

            obj.orientation = init_data.orientation; % Unit vector (body
 frame)
            obj.orientation = obj.orientation / norm(obj.orientation); %
 Normalize

            obj.thruster_noise = init_data.thruster_noise; % Noise level [N]
            obj.minimum_thrust = init_data.minimum_thrust;
            obj.maximum_thrust = init_data.maximum_thrust; % [N]

            % Set default values for warm-up parameters
            obj.thruster_warm_up_time = 0; % Default no warm-up
            obj.accumulated_warm_up_time = 0;
            obj.thruster_warm_up_power_consumed = 0;
            obj.command_actuation_power_consumed =
 obj.instantaneous_power_consumption; % Default to regular consumption
            obj.instantaneous_data_volume =
 obj.instantaneous_data_generated_per_sample; % [kb]

            % Initialize fuel consumption properties
            obj.isp = init_data.micro_thruster_ISP; % Get ISP from init data
            obj.fuel_consumed_per_firing = 0;
            obj.total_fuel_consumed = 0;
```

```
            % Reset all variables
            obj = func_reset_state(obj);

            % Initialize Storage Variables
            obj.store = [];
            obj.store.true_commanded_thrust =
zeros(mission.storage.num_storage_steps_attitude,1);
            obj.store.control_torque_MT =
zeros(mission.storage.num_storage_steps_attitude,
length(obj.control_torque_MT));
            obj.store.control_force_MT =
zeros(mission.storage.num_storage_steps_attitude,
length(obj.control_force_MT));
            obj.store.fuel_consumed_per_firing =
zeros(mission.storage.num_storage_steps_attitude,1);
            obj.store.total_fuel_consumed =
zeros(mission.storage.num_storage_steps_attitude,1);

            % Update storage
            func_update_true_SC_micro_thruster_store(obj, mission);

            % Update SC Power Class

func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_micro_thruster_store(obj, mission)
            % Append new thrust data to the storage arrays

obj.store.true_commanded_thrust(mission.storage.k_storage_attitude,:) =
obj.true_commanded_thrust;
            obj.store.control_torque_MT(mission.storage.k_storage_attitude,:)
= obj.control_torque_MT;
            obj.store.control_force_MT(mission.storage.k_storage_attitude,:) =
obj.control_force_MT;

obj.store.fuel_consumed_per_firing(mission.storage.k_storage_attitude,:) =
obj.fuel_consumed_per_firing;

obj.store.total_fuel_consumed(mission.storage.k_storage_attitude,:) =
obj.total_fuel_consumed;
        end
```

[ ] Methods: Reset

```
function obj = func_reset_state(obj)
    % Reset temporary state variables after each time step
    % This ensures clean state for the next time step

    % Reset actuation flags
    obj.command_actuation = false;
    obj.command_executed = false;

    % Reset thruster state for next time step
    obj.commanded_thrust = 0;
    obj.true_commanded_thrust = 0;
    obj.control_torque_MT = [0, 0, 0]; % [Nm]
    obj.control_force_MT = [0 0 0]; % [N]

    % Reset fuel consumption for this firing
    % Note: total_fuel_consumed is kept as it's cumulative
    obj.fuel_consumed_per_firing = 0;
end
```

[ ] Methods: Main

```
function func_main_true_SC_micro_thruster(obj, mission, i_SC, ~)
    % Main function for True_SC_Micro_Thruster
    % Controls thrust application, power consumption, and data
generation.

    % Reset fuel consumed this firing
    obj.fuel_consumed_per_firing = 0;

    % Check if the thruster is healthy
    if obj.health == 0
        obj.commanded_thrust = 0; % Thruster is offline, no thrust can
be applied
        obj.command_executed = false; % Mark as not executed
        obj.instantaneous_power_consumption = 0;
        obj.instantaneous_power_consumed = 0;
        return;
    end

    % Fire the thruster if the actuation flag is true
    % (should be set in the function optimize_thruster_dart in sw
attitude control)
    if obj.command_actuation
        % Check warm-up time
        if obj.accumulated_warm_up_time < obj.thruster_warm_up_time
            % Thruster warming up
            obj.instantaneous_power_consumption =
obj.thruster_warm_up_power_consumed;
            obj.instantaneous_power_consumed =
obj.thruster_warm_up_power_consumed;
```

```
                    obj.accumulated_warm_up_time =
obj.accumulated_warm_up_time + mission.time_step;
                    obj.command_executed = false; % Not yet ready to fire
                else
                    % Thruster ready to fire
                    obj.instantaneous_power_consumption =
obj.command_actuation_power_consumed;
                    obj.instantaneous_power_consumed =
obj.command_actuation_power_consumed;

                    % Randomize noise
                    current_thruster_noise = obj.thruster_noise * (2*rand() -
1); % Generates a number between 1.0e-04 and - 1.0e-04

                    % Compute the true thrust with noise
                    obj.true_commanded_thrust = obj.commanded_thrust +
current_thruster_noise;

                    % Compute force vector
                    obj.control_force_MT = obj.orientation *
obj.true_commanded_thrust;

                    % Compute the torque generated by the thruster
                    obj.control_torque_MT = cross(obj.location -
mission.true_SC{i_SC}.true_SC_body.location_COM, obj.control_force_MT);

                    % Apply the generated torque to the spacecraft ADC
                    mission.true_SC{i_SC}.true_SC_adc.control_torque = ...

mission.true_SC{i_SC}.true_SC_adc.control_torque + obj.control_torque_MT;

                    % Apply the generated force to the spacecraft navigation
                    mission.true_SC{i_SC}.true_SC_navigation.disturbance_force
= ...

mission.true_SC{i_SC}.true_SC_navigation.disturbance_force +
(obj.control_force_MT * mission.true_time.time_step_attitude /
mission.true_time.time_step ); % [N]

                    % Calculate fuel consumption
                    g0 = 9.80665; % m/s^2
                    obj.fuel_consumed_per_firing = (obj.true_commanded_thrust
* mission.true_time.time_step_attitude) / (obj.isp * g0);
                    obj.total_fuel_consumed = obj.total_fuel_consumed +
obj.fuel_consumed_per_firing;

                    % Consume fuel from the tank if fuel tank exists
                    if isfield(mission.true_SC{i_SC}, 'true_SC_fuel_tank')
&& ...

mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_fuel_tank > 0
                        % Find the assigned fuel tank (assuming the first one
for now)
                        i_tank = 1;
```

```
                        % Consume fuel from the tank

mission.true_SC{i_SC}.true_SC_fuel_tank{i_tank}.func_consume_fuel(obj.fuel_consumed_per_f
                    end

                    % Generate data for this actuation step
                    obj.instantaneous_data_generated_per_sample =
obj.instantaneous_data_volume;

                    % Mark as executed
                    obj.command_executed = true;
                end

            else
                % Thruster not actuating
                obj.commanded_thrust = 0;
                obj.true_commanded_thrust = 0;
                obj.control_torque_MT = [0, 0, 0]; % No torque applied
                obj.command_executed = false;
                obj.instantaneous_power_consumption = 0; % No power used
                obj.instantaneous_power_consumed = 0;
                obj.instantaneous_data_generated_per_sample = 0; % No data
generated
            end

            % Update Power Consumed

func_update_instantaneous_power_consumed_attitude(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            % Update Data Generated

func_update_instantaneous_data_generated_attitude(mission.true_SC{i_SC}.true_SC_data_hand
obj, mission);

            % Update storage
            func_update_true_SC_micro_thruster_store(obj, mission);

            % Add this line to properly reset state after the time step is
complete
            % and all data has been stored
            func_reset_state(obj);
        end

    end

end
```

Published with MATLAB® R2022a

5.9 True_SC_Onboard_Computer

Table of Contents

Class: True_SC_Onboard_Computer

Onboard Computer class for spacecraft

```
classdef True_SC_Onboard_Computer < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_power_consumed % [Watts] : Instantaneous power consumed

        instantaneous_data_rate_generated % [kbps] : Data rate, in kilo bits
 per sec (kbps)

        processor_utilization % [%] : CPU usage (0-100%)
```

[ ] Properties: Variables Computed Internally

```
        name % [string] 'Onboard Computer i'

        health % [integer] Health of computer
        % - 0. Switched off
        % - 1. Switched on, works nominally

        temperature % [deg C] : Temperature of computer

        flag_executive % [Boolean] Executive has told this computer to do its
 job

        data % Other useful data
```

[ ] Properties: Storage Variables

```
        store
```

```
    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Onboard_Computer(init_data, mission, i_SC,
 i_HW)

            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
                obj.name = ['Onboard Computer ',num2str(i_HW)];
            end

            obj.health = 1;
            obj.temperature = 15; % [deg C]

            obj.instantaneous_power_consumed =
 init_data.instantaneous_power_consumed; % [W]
            obj.instantaneous_data_rate_generated =
 init_data.instantaneous_data_rate_generated; % [kbps]

            if isfield(init_data, 'processor_utilization')
                obj.processor_utilization = init_data.processor_utilization; %
 [%]
            else
                obj.processor_utilization = 10; % [%] default utilization
            end

            obj.flag_executive = 0;

            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end

            % Initialize Variables to store
            obj.store = [];
            obj.store.flag_executive =
 zeros(mission.storage.num_storage_steps, length(obj.flag_executive));
            obj.store.instantaneous_data_rate_generated =
 zeros(mission.storage.num_storage_steps,
 length(obj.instantaneous_data_rate_generated)); % [kbps]
            obj.store.instantaneous_power_consumed =
 zeros(mission.storage.num_storage_steps,
 length(obj.instantaneous_power_consumed)); % [W]
```

```
            obj.store.processor_utilization =
zeros(mission.storage.num_storage_steps, 1); % [%]

            % Update Storage
            obj = func_update_true_SC_onboard_computer_store(obj, mission);

            % Update SC Power Class

func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_onboard_computer_store(obj,
mission)

            if mission.storage.flag_store_this_time_step == 1
                obj.store.flag_executive(mission.storage.k_storage_attitude,:)
= obj.flag_executive; % [Boolean]

                if obj.flag_executive == 1

obj.store.instantaneous_data_rate_generated(mission.storage.k_storage,:) =
obj.instantaneous_data_rate_generated; % [kbps]

obj.store.instantaneous_power_consumed(mission.storage.k_storage,:) =
obj.instantaneous_power_consumed; % [W]

obj.store.processor_utilization(mission.storage.k_storage,:) =
obj.processor_utilization; % [%]
                end
            end

        end
```

[ ] Methods: Main

Update Onboard Computer

```
        function obj = func_main_true_SC_onboard_computer(obj, mission, i_SC)

            if (obj.flag_executive == 1) && (obj.health == 1)
                % Operate computer - constant power and data rate regardless
of processor utilization
```

```
                % Update power consumed for spacecraft power budget

func_update_instantaneous_power_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

                % Update data generated for spacecraft data handling

func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

            else
                % Computer is off or malfunctioning
            end

            % Update Storage
            obj = func_update_true_SC_onboard_computer_store(obj, mission);

            % Do not reset flag_executive because computer is always on

        end

    end

end
```

Published with MATLAB® R2022a

5.10 True_SC_Onboard_Clock

Table of Contents

Class: True_SC_Onboard_Clock

Tracks the time onboard the SC

```
classdef True_SC_Onboard_Clock < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_power_consumed % [Watts] : Instantaneous power consumed

        instantaneous_data_rate_generated % [kbps] : Data rate generated
 during current time step, in kilo bits (kb) per sec

        mode_true_SC_onboard_clock_selector % [string]
        % - Simple

        measurement_noise % [sec] (1-sigma standard deviation) (Optional)

        measurement_wait_time % [sec]
```

[ ] Properties: Variables Computed Internally

```
        name % [string] 'Clock i'

        health % [integer] Health of sensor/actuator
        % - 0. Switched off
        % - 1. Switched on, works nominally

        temperature % [deg C] : Temperature of sensor/actuator

        measurement_vector % [sec] [Time, Date]

        measurement_time % [sec] SC time when this measurement was taken
```

```
        flag_executive % [Boolean] Executive has told this sensor/actuator to
 do its job
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Onboard_Clock(init_data, mission, i_SC, i_HW)

            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
                obj.name = ['Clock ',num2str(i_HW)];
            end

            obj.health = 1;
            obj.temperature = 10; % [deg C]

            obj.instantaneous_power_consumed =
 init_data.instantaneous_power_consumed; % [W]
            obj.instantaneous_data_rate_generated =
 init_data.instantaneous_data_rate_generated; % [kbps]

            if isfield(init_data, 'measurement_noise')
                obj.measurement_noise = init_data.measurement_noise; % [sec]
            else
                obj.measurement_noise = 0; % [sec]
            end

            obj.mode_true_SC_onboard_clock_selector =
 init_data.mode_true_SC_onboard_clock_selector; % [string]
            obj.measurement_wait_time = init_data.measurement_wait_time; %
 [sec]

            obj.flag_executive = 1;

            this_measurement_noise = obj.measurement_noise*2*(rand-0.5); %
 [sec]
            obj.measurement_vector = [(mission.true_time.time +
 this_measurement_noise) (mission.true_time.date + this_measurement_noise)]; %
 [sec] [Time, Date]
            obj.measurement_time = obj.measurement_vector(1); % [sec]
```

```
            % Initialize Variables to store: measurement_vector
measurement_time
            obj.store = [];

            obj.store.measurement_vector =
zeros(mission.storage.num_storage_steps, length(obj.measurement_vector));
            obj.store.measurement_time =
zeros(mission.storage.num_storage_steps, length(obj.measurement_time));
            obj.store.measurement_noise = obj.measurement_noise; % [sec]

            % Update Storage
            obj = func_update_true_SC_onboard_clock_store(obj, mission);

            % Update SC Power Class

func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_onboard_clock_store(obj, mission)

            if mission.storage.flag_store_this_time_step == 1
                obj.store.measurement_vector(mission.storage.k_storage,:) =
obj.measurement_vector; % [sec]
                obj.store.measurement_time(mission.storage.k_storage,:) =
obj.measurement_time; % [sec]
            end

        end
```

[ ] Methods: Main

Update Clock Time

```
        function obj = func_main_true_SC_onboard_clock(obj, mission, i_SC)

            if (obj.flag_executive == 1) && (obj.health == 1)
                % Take measurement

                if (mission.true_time.time - obj.measurement_time) >=
obj.measurement_wait_time
```

```
                    % Sufficient time has elasped for a new measurement

                    switch obj.mode_true_SC_onboard_clock_selector

                        case 'Simple'
                            this_measurement_noise =
obj.measurement_noise*2*(rand-0.5); % [sec]
                            obj.measurement_vector = [(mission.true_time.time
+ this_measurement_noise) (mission.true_time.date +
this_measurement_noise)]; % [sec]
                            obj.measurement_time = mission.true_time.time; %
[sec]

                        otherwise
                            error('Clock mode not defined!')
                    end

                end

                % Update Power Consumed

func_update_instantaneous_power_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);


                % Update Data Generated

func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

            else
                % Do nothing

            end

            % Update Storage
            obj = func_update_true_SC_onboard_clock_store(obj, mission);

            % Reset Variables
            obj.flag_executive = 0;

        end

    end

end
```

Published with MATLAB® R2022a

5.11 True_SC_Onboard_Memory

Table of Contents

Class: True_SC_Onboard_Memory

Tracks the onboard Memory state

```
classdef True_SC_Onboard_Memory < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_power_consumed % [Watts] : Instantaneous power consumed

        instantaneous_data_rate_generated % [kbps] : Data rate generated
 during current time step, in kilo bits (kb) per sec

        maximum_capacity % [kb] : Maximum data storage capacity of the Memeory
```

[ ] Properties: Variables Computed Internally

```
        name % [string] 'Memory i'

        health % [integer] Health of sensor/actuator
        % - 0. Switched off
        % - 1. Switched on, works nominally

        temperature % [deg C] : Temperature of sensor/actuator

        instantaneous_capacity % [kb] : Instantaneous capacity of Memeory

        state_of_data_storage % [percentage] : SoDS is defined by = 100×
 instantaneous_capacity / maximum_capacity
```

[ ] Properties: Storage Variables

```
        store
```

```
    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Onboard_Memory(init_data, mission, i_SC, i_HW)

            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
                obj.name = ['Memory ',num2str(i_HW)];
            end

            obj.health = 1;
            obj.temperature = 10; % [deg C]

            obj.instantaneous_power_consumed =
 init_data.instantaneous_power_consumed; % [W]
            obj.instantaneous_data_rate_generated =
 init_data.instantaneous_data_rate_generated; % [kbps]

            obj.maximum_capacity = init_data.maximum_capacity; % [kb]
            obj.instantaneous_capacity = 0; % [kb]
            obj.state_of_data_storage = 100*obj.instantaneous_capacity/
obj.maximum_capacity; % [percentage]

            % Initialize Variables to store: instantaneous_capacity
 state_of_charge
            obj.store = [];

            obj.store.instantaneous_capacity =
 zeros(mission.storage.num_storage_steps, length(obj.instantaneous_capacity));
            obj.store.state_of_data_storage =
 zeros(mission.storage.num_storage_steps, length(obj.state_of_data_storage));
            obj.store.maximum_capacity = obj.maximum_capacity; % [kb]

            obj = func_update_true_SC_onboard_memory_store(obj, mission);

            % Update SC Power Class

 func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
 obj, mission);

            % Update SC Data Handling Class

 func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
 obj, mission);
```

```
        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_onboard_memory_store(obj, mission)

            if mission.storage.flag_store_this_time_step == 1
                obj.store.instantaneous_capacity(mission.storage.k_storage,:)
 = obj.instantaneous_capacity; % [kb]
                obj.store.state_of_data_storage(mission.storage.k_storage,:) =
 obj.state_of_data_storage; % [percentage]
            end

        end
```

[ ] Methods: Main

Update Memory SoDS

```
        function obj = func_main_true_SC_onboard_memory(obj, mission, i_SC)

            %              if obj.instantaneous_capacity <= 0
            %                  obj.instantaneous_capacity = 1e-3; % [kb]
            %              end

            obj.state_of_data_storage = 100*obj.instantaneous_capacity/
obj.maximum_capacity; % [percentage]

            obj = func_update_true_SC_onboard_memory_store(obj, mission);

            % Update Power Consumed

 func_update_instantaneous_power_consumed(mission.true_SC{i_SC}.true_SC_power,
 obj, mission);

            % Update Data Generated

 func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
 obj, mission);

        end

    end

end
```

Published with MATLAB® R2022a

5.12 True_SC_Radio_Antenna

Table of Contents

Class: True_SC_Radio_Antenna

Tracks the Radio Antennas

```
classdef True_SC_Radio_Antenna < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        antenna_type % [string]
        % - 'Dipole'
        % - 'High Gain'

        location % [m] : Location of sensor, in body frame B

        orientation % [unit vector] : Normal vector from location

        mode_true_SC_radio_antenna_selector % [string]
        % - TX
        % - RX

        TX_power_consumed % [Watts] : Power consumed during TX

        RX_power_consumed % [Watts] : Power consumed during RX

        base_data_rate_generated % [kbps] : Data rate, in kilo bits per sec
 (kbps) due to Health Keeping

        % Optional (only for Link Margin Calculations)

        antenna_gain % [dB] gain of Earth receiver

        noise_temperature % [K] temperature noise
```

```
        beamwidth % [MHz] receiver beamwwidth

        energy_bit_required % [dB] Minimum energy bit required

        line_loss % [dB] Loss due to pointing or others

        coding_gain % [dB] Coding gain
```

[ ] Properties: Variables Computed Internally

```
        name % [string] 'Radio Antenna i'

        health % [integer] Health of sensor/actuator
        % - 0. Switched off
        % - 1. Switched on, works nominally

        temperature % [deg C] : Temperature of sensor/actuator

        flag_executive % [Boolean] Executive has told this sensor/actuator to
 do its job

        instantaneous_power_consumed % [Watts] : Instantaneous power consumed

        instantaneous_data_rate_generated % [kbps] : Data rate, in kilo bits
 per sec (kbps) due to RX

        instantaneous_data_rate_removed % [kbps] : Data rate, in kilo bits per
 sec (kbps) due to TX

        data % Other useful data

        maximum_data_rate
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Radio_Antenna(init_data, mission, i_SC, i_HW)

            if isfield(init_data, 'name')
```

```
            obj.name = init_data.name;
        else
            obj.name = ['Radio Antenna ',num2str(i_HW)];
        end

        obj.health = 1;
        obj.temperature = 10; % [deg C]
        obj.flag_executive = 0;
        %
        obj.antenna_type = init_data.antenna_type;
        %
        % obj.mode_true_SC_radio_antenna_selector =
init_data.mode_true_SC_radio_antenna_selector;
        %
        obj.TX_power_consumed = init_data.TX_power_consumed; % [Watts]
        obj.RX_power_consumed = init_data.RX_power_consumed; % [Watts]
        obj.instantaneous_power_consumed = obj.TX_power_consumed; %
[Watts] Will be modified dynamically but a value is needed to register

        obj.location = init_data.location; % [m]
        obj.orientation = init_data.orientation; % [unit vector]

        % switch obj.mode_true_SC_radio_antenna_selector
        %     case 'TX'
        %         obj.instantaneous_power_consumed =
obj.TX_power_consumed; % [Watts]
        %     case 'RX'
        %         obj.instantaneous_power_consumed =
obj.RX_power_consumed; % [Watts]
        %     otherwise
        %         error('Should not reach here!')
        % end

        if isfield(init_data, 'antenna_gain')

            obj.antenna_gain = init_data.antenna_gain; % [dB]
            obj.noise_temperature = init_data.noise_temperature; % [K]
            obj.beamwidth = init_data.beamwidth; % [MHz]
            obj.energy_bit_required = init_data.energy_bit_required; %
[dB]
            obj.coding_gain = init_data.coding_gain; % [dB]

        end
        %
        obj.base_data_rate_generated =
init_data.base_data_rate_generated; % [kbps]
        obj.instantaneous_data_rate_generated =
obj.base_data_rate_generated; % [kbps]
        obj.instantaneous_data_rate_removed = 0; % [kbps]
        obj.maximum_data_rate = obj.maximum_data_rate; % [kbps]

        % if isfield(init_data, 'data')
        %     obj.data = init_data.data;
        % else
```

```
            %     obj.data = [];
            % end
            %
            % Initialize Variables to store
            obj.store = [];

            obj.store.flag_executive =
zeros(mission.storage.num_storage_steps, length(obj.flag_executive)); %
[integer]
            obj.store.mode_TX_RX = zeros(mission.storage.num_storage_steps,
1); % [integer]
            obj.store.instantaneous_data_rate_generated =
zeros(mission.storage.num_storage_steps,
length(obj.instantaneous_data_rate_generated)); % [kbps]
            obj.store.instantaneous_data_rate_removed =
zeros(mission.storage.num_storage_steps,
length(obj.instantaneous_data_rate_removed)); % [kbps]
            obj.store.instantaneous_power_consumed =
zeros(mission.storage.num_storage_steps,
length(obj.instantaneous_power_consumed)); % [W]

            % Update Storage
            obj = func_update_true_SC_radio_antenna_store(obj, mission);
            %
            % % Update SC Power Class

func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);
            %
            % % Update SC Data Handling Class (Generated and Removed)

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

func_initialize_list_HW_data_removed(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_radio_antenna_store(obj, mission)

            if mission.storage.flag_store_this_time_step == 1
                obj.store.flag_executive(mission.storage.k_storage,:) =
obj.flag_executive; % [integer]

                if obj.flag_executive == 1

obj.store.instantaneous_data_rate_generated(mission.storage.k_storage,:) =
obj.instantaneous_data_rate_generated; % [kbps]
```

```
obj.store.instantaneous_data_rate_removed(mission.storage.k_storage,:) =
obj.instantaneous_data_rate_removed; % [kbps]

obj.store.instantaneous_power_consumed(mission.storage.k_storage,:) =
obj.instantaneous_power_consumed; % [W]

                   switch obj.mode_true_SC_radio_antenna_selector
                       case 'TX'
                           obj.store.mode_TX_RX(mission.storage.k_storage,1)
= 1;
                       case 'RX'
                           obj.store.mode_TX_RX(mission.storage.k_storage,1)
= 2;
                       otherwise
                           error('[True_SC_Radio_Antenna] Should not reach
here!')
                   end

               end

           end

       end
```

[ ] Methods: Main

Update all variables

```
       function obj = func_main_true_SC_radio_antenna(obj, mission, i_SC)

           if (obj.flag_executive == 1) && (obj.health == 1)

               switch obj.mode_true_SC_radio_antenna_selector
                   case 'TX'
                       obj.instantaneous_power_consumed =
obj.TX_power_consumed; % [Watts]
                   case 'RX'
                       obj.instantaneous_power_consumed =
obj.RX_power_consumed; % [Watts]
                   otherwise
                       error('[True_SC_Radio_Antenna] Should not reach
here!')
               end

               % Update SC Power Class

func_update_instantaneous_power_consumed(mission.true_SC{i_SC}.true_SC_power,obj,
mission);


func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);
```

```
                % Update SC Data Handling Class (Generated and Removed)

 func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
 obj, mission);


 func_update_instantaneous_data_removed(mission.true_SC{i_SC}.true_SC_data_handling,
 obj, mission);

            end

            % Update Storage
            obj = func_update_true_SC_radio_antenna_store(obj, mission);

            % Reset All Variables
            obj.flag_executive = 0;
            obj.instantaneous_data_rate_generated =
 obj.base_data_rate_generated; % [kbps]
            obj.instantaneous_data_rate_removed = 0; % [kbps]

        end

    end

end
```

Published with MATLAB® R2022a

5.13 True_SC_Reaction_Wheel

Table of Contents

Class: True_SC_Reaction_Wheel

Represents a single reaction wheel for spacecraft attitude control

```
classdef True_SC_Reaction_Wheel < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        location                      %[m] : Location of the reaction wheel in
 the body frame
        orientation                   %[Unit vector] : Axis of rotation in the
 body frame
        max_torque                    %[Nm] : Maximum torque the wheel can
 apply
        max_angular_velocity          %[rad/s] : Maximum angular velocity

        radius                        %[m] radius of 1 RW
        mass                          %[kg] : Mass of the reaction wheel
        power_consumed_angular_velocity_array % [power_array ; velocity_array]
        angular_velocity_noise        %[rad/s] : Random noise added to
 commanded torque

        instantaneous_data_generated_per_sample %[Kb] : Data generated during
 the current time step
```

[ ] Properties: Variables Computed Internally

```
        name                          % Name of the reaction wheel
        health                        % Health status (0: Not working, 1:
 Working)
```

```
        temperature                  %[deg C]
        moment_of_inertia            %[kg·m^2] : Moment of inertia of the 
wheel

        total_momentum               %[kg·m^2/s] : Total momentum of the wheel

        commanded_angular_acceleration % [rad/s] : Desired angular velocity of 
the wheel
        actual_angular_acceleration  % [rad/s] : Actual realised angular 
velocity of the wheel
        min_acceleration             % [rad/s^-2]
        angular_velocity             % [rad/s] : Current angular velocity of 
the wheel

        actual_torque                % [Nm] : Actual torque considering 
saturation and noise
        saturated                    % [Boolean] Is the wheel currently 
saturated ?
        instantaneous_power_consumption %[Watts] : Power consumed during 
operation
        instantaneous_power_consumed    %[Watts] : Alias for power tracking 
system

        flag_executive               %[Bool] : Is the wheel currently 
executing a command ?
        envelope_ratio               %[Ratio] : Ratio of the minimum distance 
between wheels to the radius of the wheel
        maximum_torque               %[Nm] : Maximum torque the wheel can 
apply
        momentum_capacity            %[kg·m^2/s] : Momentum capacity of the 
wheel
        maximum_acceleration         %[rad/s^2] : Maximum acceleration the 
wheel can apply

        instantaneous_data_volume        % [kb]
```

[ ] Properties: Storage Variables

```
        store                        %[Struct] : Store of the reaction wheel

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Reaction_Wheel(init_data, mission, i_SC, i_RW)
```

```
            obj.name = ['Reaction Wheel ', num2str(i_RW)];

            obj.health = true;
            obj.location = init_data.location;
            obj.orientation = init_data.orientation;
            obj.max_angular_velocity = init_data.max_angular_velocity;
            obj.radius = init_data.radius;
            obj.mass = init_data.mass;

            obj.instantaneous_data_generated_per_sample =
 init_data.instantaneous_data_generated_per_sample; % [kb]
            obj.instantaneous_data_volume =
 obj.instantaneous_data_generated_per_sample; % [kb]

            % Calculate moment of inertia
            % For a disk rotating around its center axis : 1/2*m*r^2
            obj.moment_of_inertia = 0.5 * obj.mass * obj.radius^2;

            obj.power_consumed_angular_velocity_array =
 init_data.power_consumed_angular_velocity_array;

            % Torque envelope
            if isfield(init_data, 'max_torque')
                % Maximum Torque and Momentum Envelopes for Reaction Wheel
 Arrays
                % https://ntrs.nasa.gov/api/citations/20110015369/
downloads/20110015369.pdf

 assert(ismember(mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_reaction_wheel
 [3 4 5 6]), 'Number of reaction wheel must be 3, 4, 5 or 6')
                switch
 mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_reaction_wheel
                    case 3
                        d_min = 1; % d_12
                    case 4
                        d_min = 1.633; % d_12 = d_13
                    case 5
                        d_min = 5/8 * 2.667; % d_24 = d_42
                    case 6
                        d_min = 2.667; % d_23
                end
                obj.envelope_ratio = d_min;
                obj.maximum_torque = init_data.max_torque;

                % Get maximum acceleration from init_data if provided,
 otherwise calculate it
                if isfield(init_data, 'maximum_acceleration')
                    obj.maximum_acceleration = init_data.maximum_acceleration;
                else
                    obj.maximum_acceleration = obj.maximum_torque /
 obj.moment_of_inertia;  % rad/s^2
                end
            else
```

```
                obj.envelope_ratio = 1;
                obj.maximum_torque = Inf;
                obj.momentum_capacity = Inf;
                obj.maximum_acceleration = Inf;
            end

            obj.min_acceleration = 1; % rad/s^2

            obj.angular_velocity_noise = init_data.angular_velocity_noise;

            % Initialize dynamic state
            obj.angular_velocity = 0;
            obj.commanded_angular_acceleration = 0;
            obj.saturated = false;
            obj.flag_executive = false;
            obj.instantaneous_power_consumption = 0;
            obj.instantaneous_power_consumed = 0;

            obj.actual_torque = [0,0,0];

            % Initialize storage
            obj.total_momentum = 0;

            obj.store = [];
            obj.store.angular_velocity =
zeros(mission.storage.num_storage_steps_attitude, 1);
            obj.store.torque =
zeros(mission.storage.num_storage_steps_attitude, 1);
            obj.store.saturated =
zeros(mission.storage.num_storage_steps_attitude, 1);

            obj.store.commanded_angular_acceleration =
zeros(mission.storage.num_storage_steps_attitude, 1);
            obj.store.actual_angular_acceleration =
zeros(mission.storage.num_storage_steps_attitude, 1);
            obj.store.actual_torque =
zeros(mission.storage.num_storage_steps_attitude, 3);

            obj.store.max_angular_velocity = obj.max_angular_velocity;

            % Update storage
            func_update_reaction_wheel_store(obj, mission);

            % Update SC Power Class

func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_reaction_wheel_store(obj, mission)
            obj.store.angular_velocity(mission.storage.k_storage_attitude, :)
= obj.angular_velocity;
            obj.store.actual_torque(mission.storage.k_storage_attitude, :) =
obj.actual_torque;

obj.store.commanded_angular_acceleration(mission.storage.k_storage_attitude, :)
= obj.commanded_angular_acceleration;
            obj.store.saturated(mission.storage.k_storage_attitude, :) =
obj.saturated;
        end
```

[ ] Methods: Main

Update Reaction Wheel

```
        function func_main_true_reaction_wheel(obj, mission, i_SC, ~)
            % Main function that runs the reaction wheel simulation
            if ~obj.health
                obj.commanded_angular_acceleration = 0;
                obj.angular_velocity = 0;
                obj.instantaneous_power_consumption = 0;
                obj.instantaneous_power_consumed = 0;
                obj.instantaneous_data_generated_per_sample = 0;
                obj.actual_torque = [0,0,0];
                obj.actual_angular_acceleration = 0;
                return;
            end

            if(obj.flag_executive && abs(obj.commanded_angular_acceleration) >
0)

                % Limit commanded acceleration
                if abs(obj.commanded_angular_acceleration) >
obj.maximum_acceleration
                    obj.commanded_angular_acceleration =
sign(obj.commanded_angular_acceleration) * obj.maximum_acceleration;
                end

                % Calculate torque directly from acceleration (# = I*#)
                torque_magnitude = obj.moment_of_inertia *
obj.commanded_angular_acceleration;
                obj.actual_torque = torque_magnitude * obj.orientation;

                % Update velocity with noise and limits
                if obj.commanded_angular_acceleration ~= 0
                    % Add noise only during active commands
                    current_vel_noise = obj.angular_velocity_noise * (2*rand()
- 1);
```

```
            else
                current_vel_noise = 0; % No noise when idle
            end

            % Calculate the new velocity without limits
            unconstrained_velocity = obj.angular_velocity +
obj.commanded_angular_acceleration * mission.true_time.time_step_attitude +
current_vel_noise;

            % Apply rate limiting to prevent dramatic velocity changes in
a single step
            % Maximum allowed change in velocity per time step (10% of max
velocity is a reasonable value)
            max_velocity_change = 0.1 * obj.max_angular_velocity;

            % ENHANCED SAFETY: Add more conservative limits for direction
reversals
            % Detect potential reversal (wheel going one way, command
pushing it the complete other way)
            if sign(unconstrained_velocity) ~= sign(obj.angular_velocity)
&& abs(obj.angular_velocity) > 0.3 * obj.max_angular_velocity
                % This is a potential direction reversal and the wheel is
at significant speed
                % Reduce maximum allowed change dramatically for safer
deceleration
                max_velocity_change = 0.02 * obj.max_angular_velocity;

                % Log this event to help debugging
                disp(['REACTION WHEEL SAFETY: Detected potential rapid
direction reversal for ', obj.name]);
                disp(['Current velocity: ',
num2str(obj.angular_velocity), ' rad/s']);
                disp(['Commanded acceleration: ',
num2str(obj.commanded_angular_acceleration), ' rad/s^2']);
                disp(['Limiting velocity change to ',
num2str(max_velocity_change), ' rad/s per time step']);
            end

            % Limit the velocity change
            if abs(unconstrained_velocity - obj.angular_velocity) >
max_velocity_change
                limited_velocity = obj.angular_velocity +
sign(unconstrained_velocity - obj.angular_velocity) * max_velocity_change;
            else
                limited_velocity = unconstrained_velocity;
            end

            % Apply absolute velocity limits (don't exceed max angular
velocity)
            new_velocity = max(min(limited_velocity,
obj.max_angular_velocity), -obj.max_angular_velocity);

            % If the velocity didn't change much, leave it as is to avoid
numerical issues
```

```
               velocity_tolerance = 1e-4;
               if abs(new_velocity - obj.angular_velocity) <
velocity_tolerance
                   new_velocity = obj.angular_velocity; % Clamp near-zero
velocities
               end

               % Calculate the actual acceleration that occurred (for
telemetry)
               obj.actual_angular_acceleration = (new_velocity -
obj.angular_velocity) / mission.true_time.time_step_attitude;

               % Update the angular velocity
               obj.angular_velocity = new_velocity;

               % Check for saturation
               % > If reaches 80% of max angular velocity
               obj.saturated = (abs(obj.angular_velocity) >=
obj.max_angular_velocity * 0.80);

               % Update spacecraft torque directly
               mission.true_SC{i_SC}.true_SC_adc.control_torque = ...
                   mission.true_SC{i_SC}.true_SC_adc.control_torque +
obj.actual_torque;

               % Update power and data
               obj.instantaneous_power_consumption = abs(obj.actual_torque *
obj.angular_velocity);


               % Calculate individual wheel momentum: h = I * # * direction
               % The wheel momentum is a vector along the wheel's spin axis
(orientation)
               momentum_magnitude = obj.moment_of_inertia *
obj.angular_velocity;
               obj.total_momentum = momentum_magnitude * obj.orientation;


               % Update power and data
               power_consumptions =
obj.power_consumed_angular_velocity_array(1, :);
               angular_velocities =
obj.power_consumed_angular_velocity_array(2, :);

               % Ensure the array is sorted by angular velocity
               [angular_velocities, sortIdx] = sort(angular_velocities);
               power_consumptions = power_consumptions(sortIdx);

               % Interpolate to find the power consumption for the current
angular velocity
               if obj.angular_velocity < min(angular_velocities)
                   obj.instantaneous_power_consumption =
power_consumptions(1);
               elseif obj.angular_velocity > max(angular_velocities)
```

```
                    obj.instantaneous_power_consumption =
power_consumptions(end);
                else
                    obj.instantaneous_power_consumption
= interp1(angular_velocities, power_consumptions,
obj.angular_velocity, 'linear');
                end
                % Set property for power tracking system
                obj.instantaneous_power_consumed =
obj.instantaneous_power_consumption;

                % Update the data generated
                obj.instantaneous_data_generated_per_sample =
obj.instantaneous_data_volume; % [kb]


            else
                obj.commanded_angular_acceleration = 0;
                obj.instantaneous_power_consumption = 0;
                obj.instantaneous_power_consumed = 0;
                obj.instantaneous_data_generated_per_sample = 0;
            end

            % Update Power Consumed

func_update_instantaneous_power_consumed_attitude(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            % Update Data Generated

func_update_instantaneous_data_generated_attitude(mission.true_SC{i_SC}.true_SC_data_hand
obj, mission);

            % Update storage
            func_update_reaction_wheel_store(obj, mission);

            % CRITICAL FIX: Reset command flags at the end of each cycle
            % This prevents commands from persisting indefinitely between
cycles
            obj.flag_executive = false;
            obj.commanded_angular_acceleration = 0;
        end

    end

end
```

Published with MATLAB® R2022a

5.14 True_SC_Science_Processor

Table of Contents

Class: True_SC_Science_Processor

Tracks the Science Processor

```
classdef True_SC_Science_Processor < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_power_consumed % [Watts] : Instantaneous power consumed

        instantaneous_data_rate_generated % [kbps] : Data rate, in kilo bits
 per sec (kbps)

        instantaneous_data_removed_per_sample % [kb] : Data in kilo bits (kb)

        flag_show_science_processor_plot % [Boolean] : 1 = Shows the Science
 Processor plot

        mode_true_SC_science_processor_selector % [string] Select which Mode
 to run
```

[ ] Properties: Variables Computed Internally

```
        name % [string] 'Generic Sensor i'

        health % [integer] Health of sensor/actuator
        % - 0. Switched off
        % - 1. Switched on, works nominally

        temperature % [deg C] : Temperature of sensor/actuator
```

```
        flag_executive % [Boolean] Executive has told this sensor/actuator to
 do its job

        data % Other useful data
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Science_Processor(init_data, mission, i_SC,
 i_HW)

            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
                obj.name = ['Science Processor ',num2str(i_HW)];
            end

            obj.health = 1;
            obj.temperature = 10; % [deg C]

            obj.instantaneous_power_consumed =
 init_data.instantaneous_power_consumed; % [W]
            obj.instantaneous_data_rate_generated =
 init_data.instantaneous_data_rate_generated; % [kbps]
            obj.instantaneous_data_removed_per_sample =
 init_data.instantaneous_data_removed_per_sample; % [kb]
            obj.flag_show_science_processor_plot =
 init_data.flag_show_science_processor_plot; % [Boolean]
            obj.mode_true_SC_science_processor_selector =
 init_data.mode_true_SC_science_processor_selector; % [string]

            obj.flag_executive = 0;

            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end

            % Initialize Variables to store: measurement_vector
            obj.store = [];
```

```
            obj.store.flag_executive =
zeros(mission.storage.num_storage_steps, length(obj.flag_executive));
            obj.store.instantaneous_data_rate_generated =
zeros(mission.storage.num_storage_steps,
length(obj.instantaneous_data_rate_generated)); % [kbps]
            obj.store.instantaneous_data_removed_per_sample =
zeros(mission.storage.num_storage_steps,
length(obj.instantaneous_data_removed_per_sample)); % [kb]
            obj.store.instantaneous_power_consumed =
zeros(mission.storage.num_storage_steps,
length(obj.instantaneous_power_consumed)); % [W]

            % Additional Science Processor Variables
            switch obj.mode_true_SC_science_processor_selector

                case 'Nightingale'
                    obj =
func_true_SC_science_processor_Nightingale_constructor(obj, mission, i_SC);

                otherwise
                    % Do nothing!
            end

            % Update Storage
            obj = func_update_true_SC_science_processor_store(obj, mission);

            % Update SC Power Class

func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

func_initialize_list_HW_data_removed(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_science_processor_store(obj,
mission)

            if mission.storage.flag_store_this_time_step == 1
                obj.store.flag_executive(mission.storage.k_storage_attitude,:)
= obj.flag_executive; % [Boolean]

                if obj.flag_executive == 1
```

```
obj.store.instantaneous_data_rate_generated(mission.storage.k_storage,:) =
obj.instantaneous_data_rate_generated; % [kbps]

obj.store.instantaneous_data_removed_per_sample(mission.storage.k_storage,:)
= obj.instantaneous_data_removed_per_sample; % [kb]

obj.store.instantaneous_power_consumed(mission.storage.k_storage,:) =
obj.instantaneous_power_consumed; % [W]
                end
            end

        end
```

[ ] Methods: Main

Update Science Processor

```
        function obj = func_main_true_SC_science_processor(obj, mission, i_SC)

            if (obj.flag_executive == 1) && (obj.health == 1)
                % Take measurement

                if
isfield(obj.data, 'instantaneous_power_consumed_per_SC_mode')
                    obj.instantaneous_power_consumed =
obj.data.instantaneous_power_consumed_per_SC_mode(mission.true_SC{i_SC}.software_SC_execu
[W]
                end

                switch obj.mode_true_SC_science_processor_selector

                    case 'Nightingale'
                        obj = func_true_SC_science_processor_Nightingale(obj,
mission, i_SC);

                    otherwise
                        error('Should not reach here!')
                end

                % Update Power Consumed

func_update_instantaneous_power_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

                % Update Data Handling

func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

func_update_instantaneous_data_removed(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);
```

```
            else
                % If not active, set power to a low standby value
                obj.instantaneous_power_consumed =
 obj.instantaneous_power_consumed * 0.1; % 10% of normal power when in standby

                % Still update power system even when in standby

 func_update_instantaneous_power_consumed(mission.true_SC{i_SC}.true_SC_power,
 obj, mission);
            end

            % Update Storage
            obj = func_update_true_SC_science_processor_store(obj, mission);

            % Reset Variables
            obj.flag_executive = 0;

        end

    end

end
```

Published with MATLAB® R2022a

5.15 True_SC_Science_Radar

Table of Contents

Class: True_SC_Science_Radar

Tracks the onboard Radar measurements

```
classdef True_SC_Science_Radar < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_power_consumed % [Watts] : Instantaneous power consumed

        instantaneous_data_rate_generated % [kbps] : Data rate, in kilo bits
 per sec (kbps)

        mode_true_SC_science_radar_selector % [string]
        % - DROID

        measurement_wait_time % [sec]

        location % [m] : Location of sensor, in body frame B

        orientation % [unit vector] : Normal vector from location

        field_of_view % [deg] : Field of view (FOV) of the radar in deg
        % Set to 0 to select the cloest point

        flag_show_radar_plot % [Boolean] : 1 = Shows the radar plot
        wait_time_visualize_SC_radar_coverage_during_sim % [sec] (Optional)

        num_points % [integer] Number of points in mesh
```

[ ] Properties: Variables Computed Internally

```
        name % [string] 'Radar i'
```

```
        health % [integer] Health of sensor/actuator
        % - 0. Switched off
        % - 1. Switched on, works nominally

        temperature % [deg C] : Temperature of sensor/actuator

        measurement_vector % [Image]

        measurement_time % [sec] SC time when this measurement was taken

        flag_executive % [Boolean] Executive has told this sensor/actuator to
 do its job

        pos_points % [unit vector] Location of points in mesh

        spherical_points % [unit vector] Location of points in Sphere

        monostatic_observed_point % [array] Monostatic: which point is
 observed how many times

        monostatic_num_point_observed % [integer] Monostatic: total number of
 points observed

        prev_time_visualize_SC_radar_coverage_during_sim % [sec]

        data % Other useful data
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Science_Radar(init_data, mission, i_SC, i_HW)

            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
                obj.name = ['Radar ',num2str(i_HW)];
            end

            obj.health = 1;
            obj.temperature = 10; % [deg C]
```

```
            obj.instantaneous_power_consumed =
init_data.instantaneous_power_consumed; % [W]
            obj.mode_true_SC_science_radar_selector =
init_data.mode_true_SC_science_radar_selector; % [string]
            obj.instantaneous_data_rate_generated =
init_data.instantaneous_data_rate_generated; % [kbps]

            obj.measurement_wait_time = init_data.measurement_wait_time; %
[sec]
            obj.measurement_time = -inf; % [sec]

            obj.flag_executive = 0;

            obj.location = init_data.location; % [m]
            obj.orientation = init_data.orientation; % [unit vector]

            obj.field_of_view = init_data.field_of_view; % [deg]

            obj.flag_show_radar_plot = init_data.flag_show_radar_plot; %
[Boolean]

            if
isfield(init_data, 'wait_time_visualize_SC_radar_coverage_during_sim')
                obj.wait_time_visualize_SC_radar_coverage_during_sim =
init_data.wait_time_visualize_SC_radar_coverage_during_sim;
            else
                obj.wait_time_visualize_SC_radar_coverage_during_sim = 0; %
[sec]
            end
            obj.prev_time_visualize_SC_radar_coverage_during_sim = -inf;

            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end

            % load the science points
            obj.num_points = init_data.num_points; % [integer]
            obj.pos_points = func_load_science_points_v2(obj.num_points);

            obj.spherical_points = zeros(obj.num_points, 2);
            for i = 1:1:obj.num_points

                %                   sph =
Cartesian2Spherical(obj.pos_points(i,:)); % [r, theta, phi] in radians
                %                   longitude = rad2deg(sph(3)); % [deg]
                %                   latitude = rad2deg(sph(2)); % [deg]
                %                   latitude = latitude - 90; % [deg]

                [radius, lon, lat] = cspice_reclat(obj.pos_points(i,:)'); %
[radius, longitude [rad], latitude [rad] ]

                obj.spherical_points(i,:) = [rad2deg(lon), rad2deg(lat)];
```

```
            end

            % monostatic data
            obj.monostatic_observed_point = zeros(1,obj.num_points);
            obj.monostatic_num_point_observed = 0;


            % Initialize Variables to store: monostatic_num_point_observed
            obj.store = [];

            obj.store.monostatic_num_point_observed =
zeros(mission.storage.num_storage_steps,
length(obj.monostatic_num_point_observed));
            obj.store.flag_executive =
zeros(mission.storage.num_storage_steps, length(obj.flag_executive));
            obj.store.instantaneous_data_rate_generated =
zeros(mission.storage.num_storage_steps,
length(obj.instantaneous_data_rate_generated)); % [kbps]
            obj.store.instantaneous_power_consumed =
zeros(mission.storage.num_storage_steps,
length(obj.instantaneous_power_consumed)); % [W]

            % Update Storage
            obj = func_update_true_SC_science_radar_store(obj, mission);

            % Update SC Power Class

func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

            % Store video of func_visualize_SC_orbit_during_sim
            if (mission.storage.plot_parameters.flag_save_video == 1) &&
(obj.flag_show_radar_plot == 1)
                obj.data.video_filename = [mission.storage.output_folder,
mission.name,'_SC',num2str(i_SC),'_Radar',num2str(i_HW),'.mp4'];
                obj.data.myVideo =
VideoWriter(obj.data.video_filename, 'MPEG-4');
                obj.data.myVideo.FrameRate = 30;  % Default 30
                obj.data.myVideo.Quality = 100;    % Default 75
                open(obj.data.myVideo);
            end
        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_science_radar_store(obj, mission)
```

```
            if mission.storage.flag_store_this_time_step == 1

obj.store.monostatic_num_point_observed(mission.storage.k_storage,:) =
obj.monostatic_num_point_observed; % [integer]
                obj.store.flag_executive(mission.storage.k_storage,:) =
obj.flag_executive; % [integer]

                if obj.flag_executive == 1

obj.store.instantaneous_data_rate_generated(mission.storage.k_storage,:) =
obj.instantaneous_data_rate_generated; % [kbps]

obj.store.instantaneous_power_consumed(mission.storage.k_storage,:) =
obj.instantaneous_power_consumed; % [W]
                end

            end

        end
```

[ ] Methods: Main

Update Radar

```
        function obj = func_main_true_SC_science_radar(obj, mission, i_SC,
 i_HW)

            if (obj.flag_executive == 1) && (obj.health == 1)
                % Take measurement

                if (mission.true_time.time - obj.measurement_time) >=
obj.measurement_wait_time

                    % Sufficient time has elasped for a new measurement
                    obj.measurement_time = mission.true_time.time; % [sec]

                    switch obj.mode_true_SC_science_radar_selector

                        case 'DROID'
                            obj = func_true_SC_science_radar_DROID(obj,
mission, i_SC);

                        case 'Nightingale'
                            obj = func_true_SC_science_radar_Nightingale(obj,
mission, i_SC);

                        otherwise
                            error('Radar mode not defined!')
                    end

                    obj.prev_time_visualize_SC_radar_coverage_during_sim = -
inf;
```

```
                else
                    % Data not generated in this time step
                    % Data is only generated when a radar measurement is
performed

                end

                if
isfield(obj.data, 'instantaneous_power_consumed_per_SC_mode')
                    obj.instantaneous_power_consumed =
obj.data.instantaneous_power_consumed_per_SC_mode(mission.true_SC{i_SC}.software_SC_execu
[W]
                end

                % Update Power Consumed

func_update_instantaneous_power_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            else
                % Do nothing

            end

            % Plot Radar Coverage
            if (obj.flag_show_radar_plot == 1) &&
(mission.true_SC{i_SC}.software_SC_executive.time -
obj.prev_time_visualize_SC_radar_coverage_during_sim >=
obj.wait_time_visualize_SC_radar_coverage_during_sim )
                obj = func_visualize_SC_radar_coverage_during_sim(obj,
mission, i_SC, i_HW);
            end

            % Update Storage
            obj = func_update_true_SC_science_radar_store(obj, mission);

            % Reset Variables
            obj.flag_executive = 0;

        end
```

[ ] Methods: Visualize Radar Coverage

Visualize all SC attitude orbit during simulation

```
        function obj = func_visualize_SC_radar_coverage_during_sim(obj,
mission, i_SC, i_HW)

            obj.prev_time_visualize_SC_radar_coverage_during_sim =
mission.true_SC{i_SC}.software_SC_executive.time; % [sec]

            %  (20*i_SC) + i_HW
```

```
            plot_handle = figure('Name',['SC ',num2str(i_SC),' Radar
 ',num2str(i_HW),' Coverage']);
            clf
            set(plot_handle,'Color',[1 1 1]);
            set(plot_handle,'units','normalized','outerposition',[0 0 1 1])
            set(plot_handle,'PaperPositionMode','auto');

            time_sim_elapsed = seconds(mission.true_time.time -
 mission.true_time.t_initial);
            time_sim_elapsed.Format = 'dd:hh:mm:ss';

            sgtitle(['SC ',num2str(i_SC),', Radar ',num2str(i_HW),'
 Coverage = ',num2str(round(100 * obj.monostatic_num_point_observed /
 obj.num_points,1)),' %, Simulation Time =
 ',char(time_sim_elapsed)],'FontSize',mission.storage.plot_parameters.title_font_size,'Fon

            %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%%%%%%%%%
            % % 3D Radar Vizualization % %
            %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%%%%%%%%%


            subplot(1,2,1)
            hold on

            for i_SC = 1:1:mission.num_SC

 plot3(mission.true_SC{i_SC}.true_SC_navigation.position_relative_target(1),
 mission.true_SC{i_SC}.true_SC_navigation.position_relative_target(2),
 mission.true_SC{i_SC}.true_SC_navigation.position_relative_target(3), 's','MarkerSize',15

                if (obj.flag_executive == 1)
                    % Plot Radar Orientation
                    this_location =
 mission.true_SC{i_SC}.true_SC_navigation.position_relative_target;
                    this_orientation =
 (mission.true_SC{i_SC}.true_SC_adc.rotation_matrix * obj.orientation')';

                    quiver3(this_location(1), this_location(2),
 this_location(3), this_orientation(1), this_orientation(2),
 this_orientation(3), ...

  'LineWidth',3,'DisplayName',obj.name,'Color',rgb('Orange'), 'AutoScaleFactor',200*missio
                end

            end

            i_target =
 mission.true_SC{i_SC}.true_SC_navigation.index_relative_target;
            func_plot_target_shape(i_target, mission);
```

```
            this_pos_points = mission.true_target{i_target}.radius *
(mission.true_target{i_target}.rotation_matrix * obj.pos_points')'; % [km]

            % Define a colormap
            cmap = jet(max(obj.monostatic_observed_point)+1); % Use a colormap
with max(obj.monostatic_observed_point)+1 colors

            % Map the values to colors
            colors = cmap(1+obj.monostatic_observed_point', :);

            scatter3(this_pos_points(:,1), this_pos_points(:,2),
this_pos_points(:,3), 10, colors, 'filled','DisplayName','Radar Points'); %
50 is the size of the markers

            grid on

            axis equal
            legend('Location','southwest')
            xlabel('X axis [km]')
            ylabel('Y axis [km]')
            zlabel('Z axis [km]')

set(gca, 'FontSize',mission.storage.plot_parameters.standard_font_size,'FontName',mission
            title('3D Radar Coverage in Target-centered Rotating
Frame','FontSize',mission.storage.plot_parameters.standard_font_size)

            %              view(3)
            view(-40,-30)
            axis equal

            hold off

            %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%%%%%%%%%
            % % 2D Radar Vizualization % %
            %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%%%%%%%%%


            subplot(1,2,2)
            hold on

            scatter(obj.spherical_points(:,2), obj.spherical_points(:,1), 10,
colors, 'filled');

            for i_SC = 1:1:mission.num_SC

                %                  sph =
Cartesian2Spherical(mission.true_target{i_target}.rotation_matrix' *
mission.true_SC{i_SC}.true_SC_navigation.position_relative_target'); % [r,
theta, phi] in radians
                %                  longitude = rad2deg(sph(3)); % [deg]
                %                  latitude = rad2deg(sph(2)); % [deg]
                %                  latitude = latitude - 90; % [deg]
```

```
                [radius, lon, lat] =
cspice_reclat(mission.true_target{i_target}.rotation_matrix' *
mission.true_SC{i_SC}.true_SC_navigation.position_relative_target'); %
[radius, longitude [rad], latitude [rad] ]
                plot(rad2deg(lat),
rad2deg(lon), 's','MarkerSize',15, 'MarkerFaceColor',rgb('Gray'), 'DisplayName',mission.t
            end

            % Add colorbar to show mapping
            colorbar;
            caxis([0 max(obj.monostatic_observed_point)+1]);

            axis equal
            ylabel('Longitude [deg]')
            xlabel('Latitude [deg]')

set(gca, 'FontSize',mission.storage.plot_parameters.standard_font_size,'FontName',mission
            title('2D Radar Coverage in Target-centered Static
Frame','FontSize',mission.storage.plot_parameters.standard_font_size)



            drawnow limitrate

            if (mission.storage.plot_parameters.flag_save_video == 1) &&
(mission.flag_stop_sim == 0)
                open(obj.data.myVideo);
                writeVideo(obj.data.myVideo, getframe(plot_handle));
            end

            if (mission.storage.plot_parameters.flag_save_plots == 1) &&
(mission.flag_stop_sim == 1)
                saveas(plot_handle,[mission.storage.output_folder,
mission.name,'_SC',num2str(i_SC),'_Radar',num2str(i_HW),'.png'])
            end

        end

    end

end
```

Published with MATLAB® R2022a

5.16 True_SC_Solar_Panel

Table of Contents

Class: True_SC_Solar_Panel

SC's Solar Panels

```
classdef True_SC_Solar_Panel < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_power_consumed % [Watts] : Instantaneous power consumed
 (irrespective of whether it is generating power or not)

        instantaneous_data_rate_generated % [kbps] : Data rate generated
 during current time step, in kilo bits (kb) per sec

        mass % [kg] : Mass of ith solar panel

        shape_model % : Shape model of Solar Panel
        % - Vertices [m] : Position of vertices in body frame B
        % - Faces : Triplet of vertex indices define a face
        % - Face_reflectance_factor_solar_cell_side : # [0, 1] for ith face
 (used for SRP)
        % - Face_reflectance_factor_opposite_side : # [0, 1] for ith face
 (used for SRP)
        % - Face_orientation_solar_cell_side [unit vector] : Normal vector in
 body frame B
        % - # Face_center [m] : Center of this Face
        % - # Face_area [m^2]
        % - type [string] : Type of shape is used for MI and volume
 calculations

        type % [string] : Solar panel type
```

```
        % 'body_mounted' : Stuck to SC side (only solar cell side is used for
SRP)
        % 'passive_deployed' : Passively deployed (orientation in body frame B
does not change, i.e. it is static)
        % 'active_deployed_gimballed' : Actively gimballed (orientation in
body frame B changes)

        packing_fraction % [float] # [0, 1] Packing fraction of solar cells in
solar panel

        solar_cell_efficiency % [float] # [0, 1] Efficiency of each solar cell
```

[ ] Properties: Variables Computed Internally

```
        name % [string] 'SP i_SP'

        health % [integer] Health of sensor/actuator
        % - 0. Switched off
        % - 1. Switched on, works nominally

        temperature % [deg C] : Temperature of sensor/actuator

        instantaneous_power_generated % [Watts] : Instantaneous power produced
by ith solar panel

        maximum_power % [Watts] : Maximum power that could have been produced
by ith solar panel is the Sun was exactly along SP’s orientation

        Sun_incidence_angle % [deg] : Angle between Sun vector and
Face_orientation_solar_cell_side
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Solar_Panel(init_data, mission, i_SC, i_HW)

            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
```

```
                obj.name = ['Solar Panel ',num2str(i_HW)];
            end

            obj.health = 1;
            obj.temperature = 10; % [deg C]

            obj.instantaneous_power_consumed =
 init_data.instantaneous_power_consumed; % [W]
            obj.instantaneous_data_rate_generated =
 init_data.instantaneous_data_rate_generated; % [kbps]

            % Initialize Shape
            obj.shape_model = init_data.shape_model;

            Face_center = zeros(size(obj.shape_model.Faces));
            for i=1:size(obj.shape_model.Faces,1)
                % face center : [(V1x+V2x+V3x)/3 ; (V1y+V2y+V3y)/3 : (V1z+V2z
+V3z)/3 ]
                Face_center(i,:) = [
                    (obj.shape_model.Vertices(obj.shape_model.Faces(i,1),1)
 + obj.shape_model.Vertices(obj.shape_model.Faces(i,2),1) +
 obj.shape_model.Vertices(obj.shape_model.Faces(i,3),1))/3;
                    (obj.shape_model.Vertices(obj.shape_model.Faces(i,1),2)
 + obj.shape_model.Vertices(obj.shape_model.Faces(i,2),2) +
 obj.shape_model.Vertices(obj.shape_model.Faces(i,3),2))/3;
                    (obj.shape_model.Vertices(obj.shape_model.Faces(i,1),3)
 + obj.shape_model.Vertices(obj.shape_model.Faces(i,2),3) +
 obj.shape_model.Vertices(obj.shape_model.Faces(i,3),3))/3];
            end
            obj.shape_model.Face_center = Face_center;

            % SP area from vertices
            area = 0; % [m^2]
            for f=1:size(obj.shape_model.Faces,1)
                vertex_index = obj.shape_model.Faces(f,:);  % index of
 vertices for this face
                a = norm(obj.shape_model.Vertices(vertex_index(1),:) -
 obj.shape_model.Vertices(vertex_index(2),:));
                b = norm(obj.shape_model.Vertices(vertex_index(2),:) -
 obj.shape_model.Vertices(vertex_index(3),:));
                c = norm(obj.shape_model.Vertices(vertex_index(3),:) -
 obj.shape_model.Vertices(vertex_index(1),:));
                s = (a+b+c)/2;  % semi perimeter
                area = area + sqrt(s*(s-a)*(s-b)*(s-c)); % Heron formula
            end

            obj.shape_model.Face_area = area;

            % Center of mass
            obj.shape_model.r_CM = mean(obj.shape_model.Vertices, 1); % [m]

            switch obj.shape_model.type

                case 'cuboid'
```

```
                    % Inertia matrix (assume cuboid)
                    L = max(obj.shape_model.Vertices(:,1)) -
min(obj.shape_model.Vertices(:,1)); % [m]
                    W = max(obj.shape_model.Vertices(:,2)) -
min(obj.shape_model.Vertices(:,2)); % [m]
                    H = max(obj.shape_model.Vertices(:,3)) -
min(obj.shape_model.Vertices(:,3)); % [m]
                    obj.shape_model.I_through_r_CM = diag([1/12*(W^2+H^2),
1/12*(L^2+H^2), 1/12*(L^2+W^2)]); % [m^2]

                    % Volume
                    obj.shape_model.volume = L*W*H; % [m^3]

                otherwise
                    error('Havent written yet!')

            end

            obj.mass = init_data.mass; % [kg]

            obj.packing_fraction = init_data.packing_fraction;

            obj.type = init_data.type;

            obj.solar_cell_efficiency = init_data.solar_cell_efficiency;

            obj.instantaneous_power_generated = 0; % [W]

            obj.maximum_power = 0; % [W]

            obj.Sun_incidence_angle = 180; % [deg]

            obj = func_update_SP_instantaneous_power_generated(obj, mission,
i_SC);

            % Initialize Variables to store: instantaneous_power_generated
maximum_power Sun_incidence_angle
            obj.store = [];

            obj.store.instantaneous_power_generated =
zeros(mission.storage.num_storage_steps,
length(obj.instantaneous_power_generated));
            obj.store.maximum_power = zeros(mission.storage.num_storage_steps,
length(obj.maximum_power));
            obj.store.Sun_incidence_angle =
zeros(mission.storage.num_storage_steps, length(obj.Sun_incidence_angle));

            obj = func_update_true_SC_SP_store(obj, mission);

            % Update SC Power Class

func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);
```

```
func_initialize_list_HW_energy_generated(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_SP_store(obj, mission)

            if mission.storage.flag_store_this_time_step == 1

obj.store.instantaneous_power_generated(mission.storage.k_storage,:) =
obj.instantaneous_power_generated; % [W]
                obj.store.maximum_power(mission.storage.k_storage,:) =
obj.maximum_power; % [W]
                obj.store.Sun_incidence_angle(mission.storage.k_storage,:) =
obj.Sun_incidence_angle; % [deg]
            end

        end
```

[ ] Methods: Main

Update SP's instantaneous_power_generated

```
        function obj = func_main_true_SC_solar_panel(obj, mission, i_SC)

            obj = func_update_SP_instantaneous_power_generated(obj, mission,
i_SC);

            obj = func_update_true_SC_SP_store(obj, mission);

            % Update Power Generated Consumed

func_update_instantaneous_power_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

func_update_instantaneous_power_generated(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            % Update Data Generated

func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);
```

```
        end
```

[ ] Methods: Instantaneous Power Generated

Update SP's instantaneous_power_generated

```
        function obj = func_update_SP_instantaneous_power_generated(obj,
 mission, i_SC)

            if (obj.health == 1) &&
 (mission.true_SC{i_SC}.true_SC_navigation.flag_visible_Sun == 1)

                Sun_vector =
 mission.true_solar_system.SS_body{mission.true_solar_system.index_Sun}.position
 - mission.true_SC{i_SC}.true_SC_navigation.position; % [km]

                Sun_vector_normalized = func_normalize_vec(Sun_vector); %
 [unit vector]

                obj.Sun_incidence_angle =
 real(acosd(dot(Sun_vector_normalized',
 mission.true_SC{i_SC}.true_SC_adc.rotation_matrix *
 obj.shape_model.Face_orientation_solar_cell_side'))); % [deg]

                obj.maximum_power =
 mission.true_solar_system.solar_constant_AU *
 (mission.true_solar_system.AU_distance/norm(Sun_vector))^2
 * obj.shape_model.Face_area * obj.packing_fraction *
 obj.solar_cell_efficiency; % [W]

                if obj.Sun_incidence_angle <= 90 % [deg]

                    obj.instantaneous_power_generated = obj.maximum_power *
 cosd(obj.Sun_incidence_angle); % [W]

                else
                    % No power generated
                    obj.instantaneous_power_generated = 0; % [W]

                end

            else
                % Unhealthy Solar Panel

                obj.maximum_power = 0; % [W]

                obj.instantaneous_power_generated = 0; % [W]

                obj.Sun_incidence_angle = inf; % [deg]

            end

        end
```

```
    end
end
```

Published with MATLAB® R2022a

5.17 True_SC_Star_Tracker

Table of Contents

Class: True_SC_Star_Tracker

Tracks the Star Tracker measurements

```
classdef True_SC_Star_Tracker < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_power_consumed % [Watts] : Instantaneous power consumed

        instantaneous_data_generated_per_sample % [kb] : Data generated per
 sample, in kilo bits (kb)

        mode_true_SC_star_tracker_selector % [string]
        % - Truth
        % - Simple
        % - Simple with Sun outside FOV

        measurement_noise % [rad] (1-sigma standard deviation) (Optional)

        measurement_wait_time % [sec]

        location % [m] : Location of sensor, in body frame B

        orientation % [unit vector] : Normal vector from location

        field_of_view % [deg] : Field of view (FOV) of the camera in deg (No
 measurement if Sun is within this FOV)
```

[ ] Properties: Variables Computed Internally

```
        name % [string] 'Sun Sensor i'
```

```
        health % [integer] Health of sensor/actuator
        % - 0. Switched off
        % - 1. Switched on, works nominally

        temperature % [deg C] : Temperature of sensor/actuator

        measurement_vector % [quaternion]

        measurement_time % [sec] SC time when this measurement was taken

        flag_executive % [Boolean] Executive has told this sensor/actuator to
 do its job

        data % Other useful data
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Star_Tracker(init_data, mission, i_SC, i_HW)

            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
                obj.name = ['Star Tracker ',num2str(i_HW)];
            end

            obj.health = 1;
            obj.temperature = 10; % [deg C]

            obj.instantaneous_power_consumed =
 init_data.instantaneous_power_consumed; % [W]
            obj.instantaneous_data_generated_per_sample =
 init_data.instantaneous_data_generated_per_sample; % [kb]

            obj.mode_true_SC_star_tracker_selector =
 init_data.mode_true_SC_star_tracker_selector; % [string]
            obj.measurement_wait_time = init_data.measurement_wait_time; %
 [sec]
            obj.measurement_noise = init_data.measurement_noise; % [rad]
```

```
            obj.measurement_vector = zeros(1,4);

            obj.flag_executive = 1;

            obj.measurement_time = -inf; % [sec]

            obj.location = init_data.location; % [m]
            obj.orientation = init_data.orientation; % [unit vector]
            obj.field_of_view = init_data.field_of_view; % [deg]

            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end

            % Initialize Variables to store: measurement_vector
            obj.store = [];
            obj.store.measurement_vector =
zeros(mission.storage.num_storage_steps, length(obj.measurement_vector));

            % Update Storage
            obj = func_update_true_SC_star_tracker_store(obj, mission);

            % Update SC Power Class

func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_star_tracker_store(obj, mission)

            if mission.storage.flag_store_this_time_step_attitude == 1

obj.store.measurement_vector(mission.storage.k_storage_attitude,:) =
obj.measurement_vector; % [quaternion]
            end

        end
```

[ ] Methods: Main

Update Camera

```
        function obj = func_main_true_SC_star_tracker(obj, mission, i_SC)

            if (obj.flag_executive == 1) && (obj.health == 1)
                % Take measurement

                if (mission.true_time.time_attitude - obj.measurement_time) >=
obj.measurement_wait_time

                    % Sufficient time has elasped for a new measurement
                    obj.measurement_time = mission.true_time.time_attitude; %
[sec]

                    switch obj.mode_true_SC_star_tracker_selector

                        case 'Truth'
                            obj = func_true_SC_star_tracker_Truth(obj,
mission, i_SC);

                        case 'Simple'
                            obj = func_true_SC_star_tracker_Simple(obj,
mission, i_SC);

                        case 'Simple with Sun outside FOV'

                            this_orientation =
(mission.true_SC{i_SC}.true_SC_adc.rotation_matrix * obj.orientation')'; %
[unit vector]

                            Sun_vector =
mission.true_solar_system.SS_body{mission.true_solar_system.index_Sun}.position
- mission.true_SC{i_SC}.true_SC_navigation.position; % [km]
                            Sun_vector_normalized =
func_normalize_vec(Sun_vector); % [unit vector]

                            if func_angle_between_vectors(this_orientation,
Sun_vector_normalized) >= deg2rad(obj.field_of_view)
                                obj = func_true_SC_star_tracker_Simple(obj,
mission, i_SC);
                            else
                                % Measurement doesn't exist
                                obj.measurement_vector = nan(1,4);
                            end

                        otherwise
                            error('Star Tracker mode not defined!')
                    end

                    % Update Data Generated

func_update_instantaneous_data_generated_attitude(mission.true_SC{i_SC}.true_SC_data_hand
obj, mission);

                else
                    % Data not generated in this time step
```

```
                end

                % Update Power Consumed

func_update_instantaneous_power_consumed_attitude(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            else
                % Do nothing

            end

            % Update Storage
            obj = func_update_true_SC_star_tracker_store(obj, mission);

            % Reset Variables
            obj.flag_executive = 0;

        end
```

[ ] Methods: Truth

Star Tracker mode

```
        function obj = func_true_SC_star_tracker_Truth(obj, mission, i_SC)
            obj.measurement_vector =
func_quaternion_properize( mission.true_SC{i_SC}.true_SC_adc.attitude);
        end
```

[ ] Methods: Simple

Star Tracker mode

```
        function obj = func_true_SC_star_tracker_Simple(obj, mission, i_SC)
            % OLD Incorrect Method
            % obj.measurement_vector =
func_quaternion_properize( mission.true_SC{i_SC}.true_SC_adc.attitude +
obj.measurement_noise*randn(1,4) );

            % New Correct Method

            % Define the error quaternion (small rotation) in axis-angle
format
            error_angle = obj.measurement_noise; % [rad]
            error_axis = randn(1,3);
            error_axis = error_axis/norm(error_axis); % [unit vector]

            % Convert axis-angle to quaternion
            error_quaternion = [sin(error_angle/2) * error_axis,
cos(error_angle/2)];
            error_quaternion = func_quaternion_properize(error_quaternion);
```

```
            % Apply the error by quaternion multiplication (Hamilton product)
            obj.measurement_vector =
 func_quaternion_multiply(mission.true_SC{i_SC}.true_SC_adc.attitude,
 error_quaternion);
            obj.measurement_vector =
 func_quaternion_properize(obj.measurement_vector);

        end

    end

end
```

Published with MATLAB® R2022a

5.18 True_SC_Sun_Sensor

Table of Contents

Class: True_SC_Sun_Sensor

Tracks the Sun Sensor measurements

```
classdef True_SC_Sun_Sensor < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_power_consumed % [Watts] : Instantaneous power consumed

        instantaneous_data_generated_per_sample % [kb] : Data generated per
 sample, in kilo bits (kb)

        mode_true_SC_sun_sensor_selector % [string]
        % - Truth
        % - Simple
        % - Simple with Sun in FOV

        measurement_noise % [rad] (1-sigma standard deviation)

        measurement_wait_time % [sec]

        location % [m] : Location of sensor, in body frame B

        orientation % [unit vector] : Normal vector from location

        field_of_view % [deg] : Field of view (FOV) of the camera in deg (No
 measurement if Sun is outside this FOV)
```

[ ] Properties: Variables Computed Internally

```
        name % [string] 'Sun Sensor i'
```

```
        health % [integer] Health of sensor/actuator
        % - 0. Switched off
        % - 1. Switched on, works nominally

        temperature % [deg C] : Temperature of sensor/actuator

        measurement_vector % [quaternion]

        measurement_time % [sec] SC time when this measurement was taken

        flag_executive % [Boolean] Executive has told this sensor/actuator to
 do its job

        data % Other useful data
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = True_SC_Sun_Sensor(init_data, mission, i_SC, i_HW)

            if isfield(init_data, 'name')
                obj.name = init_data.name;
            else
                obj.name = ['Sun Sensor ',num2str(i_HW)];
            end

            obj.health = 1;
            obj.temperature = 10; % [deg C]

            obj.instantaneous_power_consumed =
 init_data.instantaneous_power_consumed; % [W]
            obj.instantaneous_data_generated_per_sample =
 init_data.instantaneous_data_generated_per_sample; % [kb]

            obj.mode_true_SC_sun_sensor_selector =
 init_data.mode_true_SC_sun_sensor_selector; % [string]
            obj.measurement_wait_time = init_data.measurement_wait_time; %
 [sec]
            obj.measurement_noise = init_data.measurement_noise; % [rad]
```

```
            obj.measurement_vector = zeros(1,4);

            obj.flag_executive = 1;

            obj.measurement_time = -inf; % [sec]

            obj.location = init_data.location; % [m]
            obj.orientation = init_data.orientation; % [unit vector]
            obj.field_of_view = init_data.field_of_view; % [deg]

            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end

            % Initialize Variables to store: measurement_vector
            obj.store = [];
            obj.store.measurement_vector =
zeros(mission.storage.num_storage_steps, length(obj.measurement_vector));

            % Update Storage
            obj = func_update_true_SC_sun_sensor_store(obj, mission);

            % Update SC Power Class

func_initialize_list_HW_energy_consumed(mission.true_SC{i_SC}.true_SC_power,
obj, mission);

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_true_SC_sun_sensor_store(obj, mission)

            if mission.storage.flag_store_this_time_step_attitude == 1

obj.store.measurement_vector(mission.storage.k_storage_attitude,:) =
obj.measurement_vector; % [quaternion]
            end

        end
```

[ ] Methods: Main

Update Camera

```
        function obj = func_main_true_SC_sun_sensor(obj, mission, i_SC)

            if (obj.flag_executive == 1) && (obj.health == 1)
                % Take measurement

                if (mission.true_time.time_attitude - obj.measurement_time) >=
obj.measurement_wait_time

                    % Sufficient time has elasped for a new measurement
                    obj.measurement_time = mission.true_time.time_attitude; %
[sec]

                    switch obj.mode_true_SC_sun_sensor_selector

                        case 'Truth'
                            obj = func_true_SC_sun_sensor_Truth(obj, mission,
i_SC);

                        case 'Simple'
                            obj = func_true_SC_sun_sensor_Simple(obj, mission,
i_SC);

                        case 'Simple with Sun in FOV'

                            this_orientation =
(mission.true_SC{i_SC}.true_SC_adc.rotation_matrix * obj.orientation')'; %
[unit vector]

                            Sun_vector =
mission.true_solar_system.SS_body{mission.true_solar_system.index_Sun}.position
- mission.true_SC{i_SC}.true_SC_navigation.position; % [km]
                            Sun_vector_normalized =
func_normalize_vec(Sun_vector); % [unit vector]

                            if func_angle_between_vectors(this_orientation,
Sun_vector_normalized) <= deg2rad(obj.field_of_view)
                                obj = func_true_SC_sun_sensor_Simple(obj,
mission, i_SC);
                            else
                                % Measurement doesn't exist
                                obj.measurement_vector = nan(1,4);
                            end

                        otherwise
                            error('Sun Sensor mode not defined!')
                    end

                    % Update Data Generated

func_update_instantaneous_data_generated_attitude(mission.true_SC{i_SC}.true_SC_data_hand
obj, mission);

                else
                    % Data not generated in this time step
```

```
                end

                % Update Power Consumed

func_update_instantaneous_power_consumed_attitude(mission.true_SC{i_SC}.true_SC_power,
obj, mission);


            else
                % Do nothing

            end

            % Update Storage
            obj = func_update_true_SC_sun_sensor_store(obj, mission);

            % Reset Variables
            obj.flag_executive = 0;

        end
```

[ ] Methods: Truth

Sun Sensor mode

```
        function obj = func_true_SC_sun_sensor_Truth(obj, mission, i_SC)
            obj.measurement_vector =
func_quaternion_properize( mission.true_SC{i_SC}.true_SC_adc.attitude);
        end
```

[ ] Methods: Simple

Sun Sensor mode

```
        function obj = func_true_SC_sun_sensor_Simple(obj, mission, i_SC)
            % OLD Incorrect Method
            % obj.measurement_vector =
func_quaternion_properize( mission.true_SC{i_SC}.true_SC_adc.attitude +
obj.measurement_noise*randn(1,4) );

            % New Correct Method

            % Define the error quaternion (small rotation) in axis-angle
format
            error_angle = obj.measurement_noise; % [rad]
            error_axis = rand(1,3) - 0.5;
            error_axis = error_axis/norm(error_axis); % [unit vector]

            % Convert axis-angle to quaternion
            error_quaternion = [sin(error_angle/2) * error_axis,
cos(error_angle/2)];
            error_quaternion = func_quaternion_properize(error_quaternion);
```

```
            % Apply the error by quaternion multiplication (Hamilton product)
            obj.measurement_vector =
 func_quaternion_multiply(mission.true_SC{i_SC}.true_SC_adc.attitude,
 error_quaternion);
            obj.measurement_vector =
 func_quaternion_properize(obj.measurement_vector);

        end

    end

end
```

Published with MATLAB® R2022a

Chapter 6

SC System-Level and Functional-Level Autonomy Software Layer Classes

6.1 `Software_SC_Communication`

Table of Contents

Class: Software_SC_Communication

Tracks the Communication Links of the Spacecraft

```
classdef Software_SC_Communication  < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_data_generated_per_sample % [kb] : Data generated per
 sample, in kilo bits (kb)

        mode_software_SC_communication_selector % [string] Different
 communication modes
        % - 'DART'
        % - 'Nightingale'

        attitude_error_threshold % [rad]
```

[ ] Properties: Variables Computed Internally

```
        name % [string] =  SC j for jth SC + SW Communication

        flag_executive % [Boolean] Executive has told this sensor/actuator to
 do its job

        this_attitude_error % [rad] current attitude error

        data % Other useful data

        last_communication_time % [sec]
        wait_time_comm_dte  % [sec] time to wait for communicating info to
 earth
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = Software_SC_Communication(init_data, mission, i_SC)

            obj.name = [mission.true_SC{i_SC}.true_SC_body.name, ' SW
Communication']; % [string]
            obj.flag_executive = 0;

            obj.instantaneous_data_generated_per_sample =
init_data.instantaneous_data_generated_per_sample; % [kb]
            obj.mode_software_SC_communication_selector =
init_data.mode_software_SC_communication_selector; % [string]

            obj.attitude_error_threshold =
deg2rad(init_data.attitude_error_threshold_deg); % [rad]

            obj.this_attitude_error = inf;

            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end

            % Initialize communication time tracker
            if isfield(init_data, 'last_communication_time')
                obj.last_communication_time =
init_data.last_communication_time;
            else
                obj.last_communication_time = 0; % Start at 0 so first check
will attempt communication
            end

            % Initialize wait time for DTE communications if provided
            if isfield(init_data, 'wait_time_comm_dte')
                obj.wait_time_comm_dte = init_data.wait_time_comm_dte;
            else
                obj.wait_time_comm_dte = 3600; % Default to 1 hour (3600
seconds)
            end
```

```
            % Initialize Variables to store
            obj.store = [];

            obj.data.transmission_complete = false;


            obj.store.flag_executive =
zeros(mission.storage.num_storage_steps, length(obj.flag_executive));
            obj.store.this_attitude_error =
zeros(mission.storage.num_storage_steps, length(obj.this_attitude_error));

            % Update Storage
            obj = func_update_software_SC_communication_store(obj, mission);

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

        end
```

[ ] Methods: Store

Update the store variables

```
        function obj = func_update_software_SC_communication_store(obj,
mission)

            if mission.storage.flag_store_this_time_step == 1
                obj.store.flag_executive(mission.storage.k_storage,:) =
obj.flag_executive; % [Boolean]
                obj.store.this_attitude_error(mission.storage.k_storage,:) =
obj.this_attitude_error; % [rad]
            end

        end
```

[ ] Methods: Main

Main Function

```
        function obj = func_main_software_SC_communication(obj, mission, i_SC)

            if (obj.flag_executive == 1)

                switch obj.mode_software_SC_communication_selector

                    case 'DART'
                        obj = func_update_software_SC_communication_Dart(obj,
mission, i_SC);

                    case 'Nightingale'
```

```
                        obj = 
func_update_software_SC_communication_Nightingale(obj, mission, i_SC);

                    otherwise
                        disp('Communication mode not defined!')
                end

                % Update Data Generated

func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling, 
obj, mission);

            end

            % Update Storage
            obj = func_update_software_SC_communication_store(obj, mission);

            % Reset Variables
            obj.flag_executive = 0;
            obj.this_attitude_error = inf;

        end

    end

end
```

Published with MATLAB® R2022a

6.2 Software_SC_Control_Attitude

Table of Contents

Class: Software_SC_Control_Attitude

Control the Attitude of the Spacecraft

```
classdef Software_SC_Control_Attitude < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_data_generated_per_sample % [kb] : Data generated per
 sample, in kilo bits (kb)

        mode_software_SC_control_attitude_selector % [string] Different
 attitude control modes
        % - 'DART Oracle' : Directly change True_SC_ADC.attitude values for
 DART mission
        % - 'Nightingale Oracle' : Directly change True_SC_ADC.attitude values
 for Nightingale mission
        % - 'Oracle with Control' : Use True_SC_ADC values + Noise
```

[ ] Properties: Variables Computed Internally

```
        name % [string] =  SC j for jth SC + SW Control Attitude

        flag_executive % [Boolean] Executive has told this sensor/actuator to
 do its job

        desired_attitude % [quanternion] : Orientation of inertial frame I
 with respect to the body frame B

        error_angle_desired_attitude % [radians] : Angle error between
 desired_attitude and true attitude
```

```
        desired_angular_velocity % [rad/sec] : Angular velocity of inertial
 frame I with respect to the body frame B

        desired_control_torque % [Nm] : Desired control torque

        data % Other useful data

        desaturation_procedure % [Bool] - Is the procedure started ?
        thruster_contribution_matix        % thruster contribution
        pinv_reaction_wheel_contribution_matrix % reaction wheel contribution
 matrix
        reaction_wheel_attitude_control_threshold % [rad] Angle from which
 wheels can take over the correction
        optim_data

        max_thrust   % [N] : Maximum thrust of the thruster
        min_thrust   % [N] : Minimum thrust of the thruster

        % Cached torque capabilities
        max_rw_torque % [Nm] : Maximum torque capability of reaction wheels
        max_mt_torque % [Nm] : Maximum torque capability of micro thrusters
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = Software_SC_Control_Attitude(init_data, mission, i_SC)

            obj.name = [mission.true_SC{i_SC}.true_SC_body.name, ' SW Control
 Attitude']; % [string]
            obj.flag_executive = 1;

            obj.instantaneous_data_generated_per_sample = 0; % [kb]
            obj.mode_software_SC_control_attitude_selector =
 init_data.mode_software_SC_control_attitude_selector; % [string]


            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end
```

```
            % Update SC Data Handling Class
 func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
 obj, mission);

            % Initialization of thruster and RW optimization data
            func_initialize_optimization_data(obj, mission, i_SC);

            % Initialize matrices and hardware data
            if
 mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_micro_thruster > 0
                obj = func_initialize_micro_thruster_contribution(obj,
 mission, i_SC);
            end

            if
 mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_reaction_wheel > 0
                obj = func_initialize_reaction_wheel_contribution(obj,
 mission, i_SC);
            end

            % Calculate and cache max torque capabilities
            obj.max_rw_torque = func_calculate_max_reaction_wheel_torque(obj,
 mission, i_SC);
            obj.max_mt_torque = func_calculate_max_thruster_torque(obj,
 mission, i_SC);

            % All the zeros
            obj.desaturation_procedure = 0;
            obj.desired_attitude = zeros(1,4); % [quaternion]
            obj.error_angle_desired_attitude = 0; % [rad]
            obj.desired_control_torque = zeros(1,3); % [Toraue Vector Nm]
            obj.desired_angular_velocity = zeros(1,3); % [rad/sec]
            obj.data.integral_error = zeros(3,1); % Initialize as 3x1 vector
 for X/Y/Z axes

            % Initialize control gains
            if isfield(init_data, 'control_gain')
                obj.data.control_gain = init_data.control_gain;
            else
                obj.data.control_gain = [0.1 1];   % [Kr ; Lambda_r] for RWA/
MT control
            end
            obj.data.prev_desired_attitude = zeros(1,4); % [quaternion]
            obj.data.num_prev_desired_attitude = 60;

            % Initialize Variables to store
            obj.store = [];

            obj.store.flag_executive =
 zeros(mission.storage.num_storage_steps_attitude,
 length(obj.flag_executive));
```

```
            obj.store.desaturation_procedure =
zeros(mission.storage.num_storage_steps_attitude,
length(obj.desaturation_procedure));
            obj.store.desired_attitude =
zeros(mission.storage.num_storage_steps_attitude,
length(obj.desired_attitude));
            obj.store.desired_angular_velocity =
zeros(mission.storage.num_storage_steps_attitude,
length(obj.desired_angular_velocity));
            obj.store.desired_control_torque =
zeros(mission.storage.num_storage_steps_attitude,
length(obj.desired_control_torque));
            obj.store.error_angle_desired_attitude
= zeros(mission.storage.num_storage_steps_attitude,
length(obj.error_angle_desired_attitude));

            % Update Storage
            obj = func_update_software_SC_control_attitude_store(obj,
mission);


            if isfield(init_data, 'reaction_wheel_attitude_control_threshold')
                obj.reaction_wheel_attitude_control_threshold =
init_data.reaction_wheel_attitude_control_threshold;
            else
                obj.reaction_wheel_attitude_control_threshold = 0.1; % [Rad]-
Nominal is 0.05
            end

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_software_SC_control_attitude_store(obj,
mission)
            if mission.storage.flag_store_this_time_step_attitude == 1
                obj.store.flag_executive(mission.storage.k_storage_attitude,:)
= obj.flag_executive;

obj.store.desaturation_procedure(mission.storage.k_storage_attitude,:) =
obj.desaturation_procedure; % [quaternion]


obj.store.desired_attitude(mission.storage.k_storage_attitude,:) =
obj.desired_attitude; % [quaternion]
```

```
obj.store.desired_angular_velocity(mission.storage.k_storage_attitude,:) =
obj.desired_angular_velocity; % [rad/sec]

obj.store.desired_control_torque(mission.storage.k_storage_attitude,:) =
obj.desired_control_torque; % [Nm]


obj.store.error_angle_desired_attitude(mission.storage.k_storage_attitude,:)
= obj.error_angle_desired_attitude; % [rad]
           end
       end
```

[ ] Methods: Main

Main Function

```
       function obj = func_main_software_SC_control_attitude(obj, mission,
i_SC)

           if (obj.flag_executive == 1)


               switch obj.mode_software_SC_control_attitude_selector

                   case {'DART Oracle', 'DART Control Asymptotically Stable
send to ADC directly', 'DART Control PD', 'DART Control Asymptotically Stable
send to actuators', 'DART Control Asymptotically Stable send to thrusters'}
                       obj =
func_update_software_SC_control_attitude_DART(obj, mission, i_SC);

                   case {'Nightingale Oracle', 'Nightingale Control
Asymptotically Stable send to ADC directly', 'Nightingale Control PD send
to ADC directly', 'Nightingale Control PD send to thrusters', 'Nightingale
Control PD send to actuators', 'Nightingale Control Asymptotically Stable
send to actuators', 'Nightingale Control Asymptotically Stable send to
rwa', 'Nightingale Control Asymptotically Stable send to thrusters'}
                       obj =
func_update_software_SC_control_attitude_Nightingale_v2(obj, mission, i_SC);

                   otherwise
                       error('Attitude Control mode not defined!')
               end

               % Update Data Generated

func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);
           end

           % Update Storage
           obj = func_update_software_SC_control_attitude_store(obj,
mission);
```

```
            % DO NOT SWITCH OFF FUNCTIONS USING flag_executive INSIDE Attitude
 Dynamics Loop (ADL)
        end

    end

end
```

Published with MATLAB® R2022a

6.3 Software_SC_Control_Orbit

Table of Contents

Class: Software_SC_Control_Orbit

Control the Orbit of the Spacecraft

```
classdef Software_SC_Control_Orbit < handle

    % Software_SC_Control_Orbit: Manages spacecraft control parameters for
 orbiting small bodies.
    % Includes functionalities for trajectory calculations, intercept
 predictions,
    % and delta-V computations tailored for spacecraft mission scenarios.
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        mode_software_SC_control_orbit_selector % [string] Different orbit
 control modes
        % - 'DART'

        max_time_before_control % [s]
```

[ ] Properties: Variables Computed Internally

```
        name % [string] =  SC j for jth SC + SW Control Orbit

        instantaneous_data_generated_per_sample % [kb] : Data generated per
 sample, in kilo bits (kb)

        data % Other useful data

        last_time_control % [s]
        flag_executive    % [bool]
```

```
        % Maneuver tracking
        maneuver_start_time % [s] Time when current maneuver began execution
        thruster_fired_successfully % [bool] Flag to track if thruster
actually fired

        % Delta-V control parameters
        desired_control_DeltaV % [m/s]: Desired Delta-V vector
        desired_control_DeltaV_units % [string]: Units for Delta-V
        total_DeltaV_executed % [m/s]: Accumulated executed Delta-V

        burn_duration % [s]

        % Thrust control parameters
        desired_control_thrust % [N]: Desired thrust for trajectory control
        desired_control_thrust_units % [string]: Units for thrust (e.g., N,
kN)

        % Time horizons and intercept data
        time_horizon % [sec]: Time horizon for trajectory planning
        time_intercept % [sec]: Time of intercept with target
        time_horizon_DeltaV % [sec]: Time horizon for Delta-V execution
        time_DeltaV % [sec]: Time of Delta-V execution
        time_horizon_data_cutoff % [sec]: Time cutoff for data integration
        time_data_cutoff % [sec]: Data cutoff time

        % Intercept and trajectory details
        intercept_SB_position % [km]: Intercept position relative to small
body
        intercept_SB_velocity % [km/s]: Intercept velocity relative to small
body
        intercept_distance % [km]: Distance at intercept
        desired_intercept_distance % [km]: Desired distance at intercept

        % Options for numerical integrations
        options % [struct]: Options for ODE solvers

        % Flags and execution controls
        desired_DeltaV_needs_to_be_executed % [boolean]: Whether Delta-V needs
execution
        desired_DeltaV_computed % [boolean]: Whether Delta-V is computed
        desired_attitude_for_DeltaV_achieved % [boolean]: Attitude flag for
Delta-V execution
        desired_DeltaV_achieved % [boolean]: Whether Delta-V has been achieved

        % Desired trajectory details
        desired_time_array % [sec]: Array of planned trajectory times
        desired_SC_pos_vel_current_SBcentered % [km, km/s]: Desired spacecraft
state in small body frame
        flag_position_velocity_burn % [int]: Indicator for position or
velocity-based burns
        desired_control_DeltaV_position_burn % [m/s]: Position-based Delta-V
        time_DeltaV_position_burn % [sec]: Time for position-based burn
        desired_control_DeltaV_velocity_burn % [m/s]: Velocity-based Delta-V
        time_DeltaV_velocity_burn % [sec]: Time for velocity-based burn
```

```
        threshold_minimum_deltaV % [m/s] - the minimum deltaV that is worth
executing, usually 0.001 m/s

        % Fuel management properties
        min_fuel_threshold % [kg]: Minimum fuel threshold to allow maneuvers
        estimated_fuel_required % [kg]: Estimated fuel required for maneuver
        flag_insufficient_fuel % [boolean]: Flag indicating insufficient fuel
```

[ ] Properties: Storage Variables

```
        store % Structure to store historical data

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = Software_SC_Control_Orbit(init_data, mission, i_SC)
            % Initialize the spacecraft control orbit class

            obj.name = [mission.true_SC{i_SC}.true_SC_body.name, ' SW Control
Orbit']; % [string]

            obj.mode_software_SC_control_orbit_selector =
init_data.mode_software_SC_control_orbit_selector;
            obj.max_time_before_control = init_data.max_time_before_control;

            obj.flag_executive = 0;
            obj.last_time_control = 0;

            obj.instantaneous_data_generated_per_sample = 0; % [kb]

            obj.desired_control_thrust = 0; % Initialize thrust to zero
            obj.options = odeset('RelTol', 1e-14, 'AbsTol', 1e-14);

            obj.time_DeltaV = 0; % Initialize Delta-V time
            obj.time_horizon = 10 * 24 * 60 * 60; % Default planning horizon
(10 days)

            obj.desired_DeltaV_needs_to_be_executed = false;
            obj.desired_DeltaV_computed = false;
            obj.desired_attitude_for_DeltaV_achieved = 0;


            obj.intercept_distance = 0; % Initialize intercept distance
            obj.desired_intercept_distance = 0; % Initialize desired intercept
distance
```

```
            obj.desired_control_DeltaV = zeros(3, 1); % Initialize Delta-V
vector
            obj.desired_DeltaV_achieved = false;

            obj.total_DeltaV_executed =  zeros(3, 1); % Initialize Delta-V
vector

            obj.time_horizon_DeltaV = 30 * 60; % Default Delta-V planning
horizon (30 minutes)
            obj.time_horizon_data_cutoff = 0; % No data cutoff initially

            obj.threshold_minimum_deltaV = 0.01;

            % Initialize fuel management properties
            obj.min_fuel_threshold = 0.1; % Minimum fuel threshold in kg
            obj.estimated_fuel_required = 0; % Estimated fuel required for
maneuver
            obj.flag_insufficient_fuel = false; % Flag indicating insufficient
fuel

            % Initialize Storage Variables
            obj.store = [];
            obj.store.intercept_distance =
zeros(mission.storage.num_storage_steps_attitude,1); % Initialize as empty
numeric array
            obj.store.desired_DeltaV_computed =
zeros(mission.storage.num_storage_steps_attitude,1);
            obj.store.desired_attitude_for_DeltaV_achieved =
zeros(mission.storage.num_storage_steps_attitude,1);

            obj.store.desired_control_DeltaV =
zeros(mission.storage.num_storage_steps_attitude, 3);
            obj.store.total_DeltaV_executed =
zeros(mission.storage.num_storage_steps_attitude, 3);
            obj.store.attitude_error =
zeros(mission.storage.num_storage_steps_attitude, 3); % Euler angles error
            obj.store.deltaV_magnitude_desired =
zeros(mission.storage.num_storage_steps_attitude, 1);
            obj.store.deltaV_magnitude_executed =
zeros(mission.storage.num_storage_steps_attitude, 1);
            obj.store.flag_insufficient_fuel =
zeros(mission.storage.num_storage_steps_attitude, 1);
            obj.store.estimated_fuel_required =
zeros(mission.storage.num_storage_steps_attitude, 1);

            obj.desired_DeltaV_achieved = 0;
            obj.total_DeltaV_executed = [0 0 0]'; % [m/sec]
            obj.desired_attitude_for_DeltaV_achieved = 0;

            % Initialize maneuver tracking properties
            obj.maneuver_start_time = 0;
            obj.thruster_fired_successfully = false;
```

```
            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);
        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_software_SC_Control_Orbit_store(obj,
mission)
            obj.store.intercept_distance(mission.storage.k_storage,:) =
obj.intercept_distance;
            obj.store.desired_DeltaV_computed(mission.storage.k_storage,:) =
obj.desired_DeltaV_computed;

obj.store.desired_attitude_for_DeltaV_achieved(mission.storage.k_storage,:) =
obj.desired_attitude_for_DeltaV_achieved;

            % New variables
            obj.store.desired_control_DeltaV(mission.storage.k_storage, :) =
obj.desired_control_DeltaV;
            obj.store.total_DeltaV_executed(mission.storage.k_storage, :) =
obj.total_DeltaV_executed;

            % % Compute attitude error
            % actual_quat =
mission.true_SC{i_SC}.software_SC_estimate_attitude.attitude;
            % desired_quat =
mission.true_SC{i_SC}.software_SC_control_attitude.desired_attitude;
            % error_quat = quatmultiply(quatconj(actual_quat), desired_quat);
            % euler_error = quat2eul(error_quat, 'ZYX'); % Convert to Euler
angles (rad)
            % obj.store.attitude_error(mission.storage.k_storage, :) =
euler_error;

            % DeltaV magnitudes
            obj.store.deltaV_magnitude_desired(mission.storage.k_storage) =
norm(obj.desired_control_DeltaV);
            obj.store.deltaV_magnitude_executed(mission.storage.k_storage) =
norm(obj.total_DeltaV_executed);

            % Fuel management data
            obj.store.flag_insufficient_fuel(mission.storage.k_storage) =
obj.flag_insufficient_fuel;
            obj.store.estimated_fuel_required(mission.storage.k_storage) =
obj.estimated_fuel_required;
        end
```

[ ] Methods: Main

Main Function

```
        function func_main_software_SC_control_orbit(obj, mission, i_SC)

            if (obj.flag_executive == 1)

                switch obj.mode_software_SC_control_orbit_selector

                    case 'DART'
                        obj = func_update_software_SC_control_orbit_DART(obj,
 mission, i_SC);

                    case 'Inactive'
                        % Do nothing!

                    otherwise
                        error('Orbit Control mode not defined!')
                end

                % Update Data Generated

 func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
 obj, mission);

            end

            % Update Storage
            obj.func_update_software_SC_Control_Orbit_store(mission);

            % Reset Variables
            obj.flag_executive = 0;


        end

    end

end
```

Published with MATLAB® R2022a

6.4 Software_SC_Data_Handling

Table of Contents

Class: Software_SC_Data_Handling

Track the data_handling status onboard the spacecraft

```
classdef Software_SC_Data_Handling < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_data_generated_per_sample % [kb] : Data generated per
 sample, in kilo bits (kb)

        mode_software_SC_data_handling_selector % [string] Different Data
 Handling modes
        % - 'Generic'
```

[ ] Properties: Variables Computed Internally

```
        name % [string] =  SC j for jth SC + SW Data Handling

        flag_executive % [Boolean] Executive has told this sensor/actuator to
 do its job

        total_data_storage % [kb] : Total data in all memories

        mean_state_of_data_storage % [percentage] : SoDS is defined by = 100×
 Sum (instantaneous_capacity) / Sum (maximum_capacity)

        data % Other useful data
```

[ ] Properties: Storage Variables

```
        store
```

```
    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = Software_SC_Data_Handling(init_data, mission, i_SC)

            obj.name = [mission.true_SC{i_SC}.true_SC_body.name, ' SW Data
 Handling']; % [string]
            obj.flag_executive = 0;

            obj.instantaneous_data_generated_per_sample =
 init_data.instantaneous_data_generated_per_sample; % [kb]

            obj.mode_software_SC_data_handling_selector =
 init_data.mode_software_SC_data_handling_selector;

            obj.mode_software_SC_data_handling_selector = 'Generic';

            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end

            % Update Mean SoC
            obj = func_update_mean_state_of_data_storage(obj, mission, i_SC);

            obj.mean_state_of_data_storage = 0;

            % Initialize Variables to store
            obj.store = [];

            obj.store.flag_executive =
 zeros(mission.storage.num_storage_steps, length(obj.flag_executive));
            obj.store.mean_state_of_data_storage =
 zeros(mission.storage.num_storage_steps,
 length(obj.mean_state_of_data_storage));
            obj.store.total_data_storage =
 zeros(mission.storage.num_storage_steps, length(obj.total_data_storage));

            % Update Storage
            obj = func_update_software_SC_data_handling_store(obj, mission);

            % Update SC Data Handling Class

 func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
 obj, mission);
```

```
        end
```

[ ] Methods: Store

Update the store variables

```
        function obj = func_update_software_SC_data_handling_store(obj,
mission)

            if mission.storage.flag_store_this_time_step == 1
                obj.store.flag_executive(mission.storage.k_storage,:) =
obj.flag_executive; % [Boolean]

obj.store.mean_state_of_data_storage(mission.storage.k_storage,:) =
obj.mean_state_of_data_storage; % [percentage]
                obj.store.total_data_storage(mission.storage.k_storage,:) =
obj.total_data_storage; % [kb]
            end

        end
```

[ ] Methods: Main

Main Function

```
        function obj = func_main_software_SC_data_handling(obj, mission, i_SC)


            switch obj.mode_software_SC_data_handling_selector

                case 'Generic'
                    % Update Mean SoC
                    obj = func_update_mean_state_of_data_storage(obj, mission,
i_SC);

                case 'Nightingale'
                    % Update Mean SoC for (num_onboard_memory-1) only
                    obj =
func_update_mean_state_of_data_storage_Nightingale(obj, mission, i_SC);

                otherwise
                    error('Data Handling mode not defined!')
            end

            % Update Data Generated

func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);


            % Update Storage
            obj = func_update_software_SC_data_handling_store(obj, mission);
```

```
            % Reset Variables
            obj.flag_executive = 0;

        end

    end

end
```

Published with MATLAB® R2022a

6.5 Software_SC_Estimate_Attitude

Table of Contents

Class: Software_SC_Estimate_Attitude

Estimates the Attitude of the Spacecraft

```
classdef Software_SC_Estimate_Attitude < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_data_generated_per_sample % [kb] : Data generated per
 sample, in kilo bits (kb)

        mode_software_SC_estimate_attitude_selector % [string] Different
 attitude estimation modes
        % - 'Truth' : Use True_SC_ADC values
        % - 'Truth with Noise' : Use True_SC_ADC values + Noise
        % - 'KF' : Use Kalman Filter
```

[ ] Properties: Variables Computed Internally

```
        name % [string] =  SC j for jth SC + SW Estimate Attitude

        flag_executive % [Boolean] Executive has told this sensor/actuator to
 do its job

        attitude % [quaternion] : Orientation of inertial frame I with respect
 to the body frame B

        angular_velocity % [rad/sec] : Angular velocity of inertial frame I
 with respect to the body frame B

        dot_angular_velocity % [rad/sec^2] : Time derivative of
 angular_velocity (needed by RWA)
```

```
        attitude_uncertainty % [error in quaternion]

        angular_velocity_uncertainty % [rad/sec]

        dot_angular_velocity_uncertainty % [rad/sec^2]

        data % Other useful data
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = Software_SC_Estimate_Attitude(init_data, mission, i_SC)

            obj.name = [mission.true_SC{i_SC}.true_SC_body.name, ' SW Estimate
 Attitude']; % [string]
            obj.flag_executive = 1;

            obj.instantaneous_data_generated_per_sample = 0; % [kb]
            obj.mode_software_SC_estimate_attitude_selector =
 init_data.mode_software_SC_estimate_attitude_selector; % [string]

            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end

            obj = func_update_software_SC_estimate_attitude_Truth(obj,
 mission, i_SC);

            % Initialize Variables to store: attitude angular_velocity
 dot_angular_velocity and uncertainties
            obj.store = [];

            obj.store.flag_executive =
 zeros(mission.storage.num_storage_steps_attitude,
 length(obj.flag_executive));

            obj.store.attitude =
 zeros(mission.storage.num_storage_steps_attitude, length(obj.attitude));
```

```
            obj.store.attitude_uncertainty =
zeros(mission.storage.num_storage_steps_attitude,
length(obj.attitude_uncertainty));

            obj.store.angular_velocity =
zeros(mission.storage.num_storage_steps_attitude,
length(obj.angular_velocity));
            obj.store.angular_velocity_uncertainty
= zeros(mission.storage.num_storage_steps_attitude,
length(obj.angular_velocity_uncertainty));

            obj.store.dot_angular_velocity =
zeros(mission.storage.num_storage_steps_attitude,
length(obj.dot_angular_velocity));
            obj.store.dot_angular_velocity_uncertainty
= zeros(mission.storage.num_storage_steps_attitude,
length(obj.dot_angular_velocity_uncertainty));

            % Update Storage
            obj = func_update_software_SC_estimate_attitude_store(obj,
mission);

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_software_SC_estimate_attitude_store(obj,
mission)

            if mission.storage.flag_store_this_time_step_attitude == 1
                obj.store.flag_executive(mission.storage.k_storage_attitude,:)
= obj.flag_executive;

                obj.store.attitude(mission.storage.k_storage_attitude,:) =
obj.attitude; % [quaternion]

obj.store.attitude_uncertainty(mission.storage.k_storage_attitude,:) =
obj.attitude_uncertainty;


obj.store.angular_velocity(mission.storage.k_storage_attitude,:) =
obj.angular_velocity; % [rad/sec]

obj.store.angular_velocity_uncertainty(mission.storage.k_storage_attitude,:)
= obj.angular_velocity_uncertainty;
```

```
obj.store.dot_angular_velocity(mission.storage.k_storage_attitude,:) =
obj.dot_angular_velocity; % [rad/sec^2]

obj.store.dot_angular_velocity_uncertainty(mission.storage.k_storage_attitude,:)
= obj.dot_angular_velocity_uncertainty;
            end

        end
```

[ ] Methods: Main

Main Function

```
        function obj = func_main_software_SC_estimate_attitude(obj, mission,
i_SC)

            if (obj.flag_executive == 1)

                switch obj.mode_software_SC_estimate_attitude_selector

                    case 'Truth'
                        obj =
func_update_software_SC_estimate_attitude_Truth(obj, mission, i_SC);

                    case 'KF'
                        obj =
func_update_software_SC_estimate_attitude_KF(obj, mission, i_SC);

                    otherwise
                        error('Attitude Estimation mode not defined!')
                end

                % Update Data Generated

func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

            end

            % Update Storage
            obj = func_update_software_SC_estimate_attitude_store(obj,
mission);

            % Reset Variables
            if abs(mission.true_time.time - mission.true_time.time_attitude)
<= 1e-6
                obj.flag_executive = 0;
            else
                % DONOT SWITCH OFF FUNCTIONS USING flag_executive INSIDE
Attitude Dynamics Loop (ADL)
            end
```

```
        end
    end
end
```

Published with MATLAB® R2022a

6.6 Software_SC_Estimate_Orbit

Table of Contents

Class: Software_SC_Estimate_Orbit

Estimates the Orbits of the Spacecraft and Target

```
classdef Software_SC_Estimate_Orbit < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_data_generated_per_sample % [kb] : Data generated per
 sample, in kilo bits (kb)

        mode_software_SC_estimate_orbit_selector % [string] Different attitude
 dynamics modes
        % - 'Truth' : Use True values
        % - 'Truth with Noise' : Use True values + Noise
        % - 'TruthWithErrorGrowth' : Use True values with error growth when
 target is not visible

        compute_wait_time % [sec]
```

[ ] Properties: Variables Computed Internally

```
        name % [string] =  SC j for jth SC + SW Estimate Orbit

        flag_executive % [Boolean] Executive has told this sensor/actuator to
 do its job

        position % [km] : Current position of SC in inertial frame I
        position_uncertainty % [km]

        velocity % [km/sec] : Current velocity of SC in inertial frame I
        velocity_uncertainty % [km/sec]
```

```
        position_relative_target % [km] : Current position of SC relative to
 SB-center J2000 inertial frame
        position_relative_target_uncertainty % [km]

        velocity_relative_target % [km/sec] : Current velocity of SC relative
 to SB-center J2000 inertial frame
        velocity_relative_target_uncertainty % [km/sec]

        name_relative_target % [string] : Name of the target, relative to
 which position and velocity are specified
        index_relative_target % [integer] : Index of the target, relative to
 which position and velocity are specified

        position_target % [km] Current position of Target wrt Sun-centered
 J2000
        position_target_uncertainty % [km]

        velocity_target % [km/sec] Current velocity of Target wrt Sun-centered
 J2000
        velocity_target_uncertainty % [km/sec]

        compute_time % [sec] SC time when this measurement was taken

        data % Other useful data
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = Software_SC_Estimate_Orbit(init_data, mission, i_SC)

            obj.name = [mission.true_SC{i_SC}.true_SC_body.name, ' SW Estimate
 Orbit']; % [string]
            obj.flag_executive = 1;

            obj.instantaneous_data_generated_per_sample = 0; % [kb]
            obj.mode_software_SC_estimate_orbit_selector =
 init_data.mode_software_SC_estimate_orbit_selector; % [string]

            obj.name_relative_target =
 mission.true_SC{i_SC}.true_SC_navigation.name_relative_target; % [string]
            obj.index_relative_target =
 mission.true_SC{i_SC}.true_SC_navigation.index_relative_target; % [integer]
```

```
            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end

            % Initialize data fields for error growth mode
            if
strcmp(obj.mode_software_SC_estimate_orbit_selector, 'TruthWithErrorGrowth')
                obj.data.last_target_visible_time = -inf; % [sec] Initialize
to a value that ensures we start with uncertainty
                obj.data.position_error_growth_rate = 0.01; % [km/sec] Rate at
which position uncertainty grows
                obj.data.velocity_error_growth_rate = 0.001; % [km/sec²] Rate
at which velocity uncertainty grows
            end

            if isfield(init_data, 'compute_wait_time')
                obj.compute_wait_time = init_data.compute_wait_time; % [sec]
            else
                obj.compute_wait_time = 0; % [sec]
            end

            obj.compute_time = -inf; % [sec]

            obj = func_update_software_SC_estimate_orbit_Truth(obj, mission,
i_SC);

            % Initialize Variables to store: position velocity of SC and
Target
            obj.store = [];

            obj.store.position = zeros(mission.storage.num_storage_steps,
length(obj.position));
            obj.store.position_uncertainty =
zeros(mission.storage.num_storage_steps, length(obj.position_uncertainty));

            obj.store.velocity = zeros(mission.storage.num_storage_steps,
length(obj.velocity));
            obj.store.velocity_uncertainty =
zeros(mission.storage.num_storage_steps, length(obj.velocity_uncertainty));

            obj.store.position_relative_target =
zeros(mission.storage.num_storage_steps, length(obj.position));
            obj.store.position_relative_target_uncertainty =
zeros(mission.storage.num_storage_steps,
length(obj.position_relative_target_uncertainty));

            obj.store.velocity_relative_target =
zeros(mission.storage.num_storage_steps, length(obj.velocity));
            obj.store.velocity_relative_target_uncertainty =
zeros(mission.storage.num_storage_steps,
length(obj.velocity_relative_target_uncertainty));
```

```
            obj.store.position_target =
zeros(mission.storage.num_storage_steps, length(obj.position_target));
            obj.store.position_target_uncertainty =
zeros(mission.storage.num_storage_steps,
length(obj.position_target_uncertainty));

            obj.store.velocity_target =
zeros(mission.storage.num_storage_steps, length(obj.velocity_target));
            obj.store.velocity_target_uncertainty =
zeros(mission.storage.num_storage_steps,
length(obj.velocity_target_uncertainty));

            % Update Storage
            obj = func_update_software_SC_estimate_orbit_store(obj, mission);

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_software_SC_estimate_orbit_store(obj,
mission)

            if mission.storage.flag_store_this_time_step == 1
                obj.store.position(mission.storage.k_storage,:) =
obj.position; % [km]
                obj.store.position_uncertainty(mission.storage.k_storage,:) =
obj.position_uncertainty;

                obj.store.velocity(mission.storage.k_storage,:) =
obj.velocity; % [km/sec]
                obj.store.velocity_uncertainty(mission.storage.k_storage,:) =
obj.velocity_uncertainty;


obj.store.position_relative_target(mission.storage.k_storage,:) =
obj.position_relative_target; % [km]

obj.store.position_relative_target_uncertainty(mission.storage.k_storage,:) =
obj.position_relative_target_uncertainty;


obj.store.velocity_relative_target(mission.storage.k_storage,:) =
obj.velocity_relative_target; % [km/sec]
```

```
obj.store.velocity_relative_target_uncertainty(mission.storage.k_storage,:) =
obj.velocity_relative_target_uncertainty;

                obj.store.position_target(mission.storage.k_storage,:) =
obj.position_target; % [km]

obj.store.position_target_uncertainty(mission.storage.k_storage,:) =
obj.position_target_uncertainty;

                obj.store.velocity_target(mission.storage.k_storage,:) =
obj.velocity_target; % [km/sec]

obj.store.velocity_target_uncertainty(mission.storage.k_storage,:) =
obj.velocity_target_uncertainty;

            end

        end
```

[ ] Methods: Main

Main Function

```
        function obj = func_main_software_SC_estimate_orbit(obj, mission,
i_SC)

            if (obj.flag_executive == 1)

                switch obj.mode_software_SC_estimate_orbit_selector

                    case 'Truth'
                        obj =
func_update_software_SC_estimate_orbit_Truth(obj, mission, i_SC);

                    case 'TruthWithErrorGrowth'
                        obj =
func_update_software_SC_estimate_orbit_TruthWithErrorGrowth(obj, mission,
i_SC);

                    otherwise
                        error('Orbit Estimation mode not defined!')
                end

                % Update Data Generated

func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

            end

            % Update Storage
            obj = func_update_software_SC_estimate_orbit_store(obj, mission);
```

```
            % Reset Variables
            obj.flag_executive = 0;

        end

    end

end
```

Published with MATLAB® R2022a

6.7 Software_SC_Executive

Table of Contents

Class: Software_SC_Executive

Tracks the tasks performed by Executive

```
classdef Software_SC_Executive < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        sc_modes % [Cells of strings] All Spacecraft Modes

        mode_software_SC_executive_selector % [string] Select which Executive
 to run

        instantaneous_data_generated_per_sample % [kb] : Data generated per
 sample, in kilo bits (kb)

        compute_wait_time % [sec]
```

[ ] Properties: Variables Computed Internally

```
        name % [string] =  SC j for jth SC + SW Executive

        time % [sec] : Current SC time
        date % [sec from J2000] : Current SC date

        this_sc_mode % [string] : Current SC mode
        this_sc_mode_value % [integer] : Current SC mode

        compute_time % [sec] SC time when this measurement was taken
        time_SB_visible % [sec]
```

```
        data % Other useful data
```

[ ] Properties: Storage Variables

```
        store
    end
```

Methods

```
    methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = Software_SC_Executive(init_data, mission, i_SC)

            obj.name = [mission.true_SC{i_SC}.true_SC_body.name, ' SW
 Executive']; % [string]
            obj.time = mission.true_time.time; % [sec]
            obj.date = mission.true_time.date; % [sec from J2000]

            obj.sc_modes = init_data.sc_modes;
            obj.mode_software_SC_executive_selector =
 init_data.mode_software_SC_executive_selector;
            obj.instantaneous_data_generated_per_sample = 0; % [kb]

            obj.this_sc_mode = obj.sc_modes{1};
            obj.this_sc_mode_value = func_find_this_sc_mode_value(obj,
 obj.this_sc_mode);

            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end

            if isfield(init_data, 'compute_wait_time')
                obj.compute_wait_time = init_data.compute_wait_time; % [sec]
            else
                obj.compute_wait_time = 0; % [sec]
            end

            obj.compute_time = -inf; % [sec]

            % Initialize Variables to store: this_sc_mode_value time date data
            obj.store = [];

            obj.store.this_sc_mode_value =
 zeros(mission.storage.num_storage_steps, length(obj.this_sc_mode_value));
            obj.store.time = zeros(mission.storage.num_storage_steps,
 length(obj.time));
```

```
            obj.store.date = zeros(mission.storage.num_storage_steps,
length(obj.date));
            obj.store.sc_modes = obj.sc_modes; % [sec]

            % Additional Executive Variables
            switch obj.mode_software_SC_executive_selector

                case 'DART'
                    obj = func_software_SC_executive_Dart_constructor(obj,
mission, i_SC);

                case 'Nightingale'
                    obj =
func_software_SC_executive_Nightingale_constructor(obj, mission, i_SC);

                otherwise
                    % Do nothing!
                    disp('Using only DART Executive variables!')
            end

            % Update Storage
            obj = func_update_software_SC_executive_store(obj, mission);

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

        end
```

[ ] Methods: Store

Update the store variable

```
        function obj = func_update_software_SC_executive_store(obj, mission)
            if mission.storage.flag_store_this_time_step == 1
                obj.store.this_sc_mode_value(mission.storage.k_storage,:) =
obj.this_sc_mode_value; % [integer]
                obj.store.time(mission.storage.k_storage,:) = obj.time; %
[sec]
                obj.store.date(mission.storage.k_storage,:) = obj.date; %
[sec]

                % Additional Storage Variables
                switch obj.mode_software_SC_executive_selector
                    case 'Nightingale'
                        obj =
func_update_software_SC_executive_store_Nightingale(obj, mission);

                    otherwise
                        % Do nothing!
                end
            end
```

```
        end
```

[ ] Methods: Main

Main Function

```
        function obj = func_main_software_SC_executive(obj, mission, i_SC)

            % Update Time
            for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_onboard_clock

mission.true_SC{i_SC}.true_SC_onboard_clock{i_HW}.flag_executive = 1; % Make
sure time is measured
                obj.time =
mission.true_SC{i_SC}.true_SC_onboard_clock{i_HW}.measurement_vector(1); %
[sec]
                obj.date =
mission.true_SC{i_SC}.true_SC_onboard_clock{i_HW}.measurement_vector(2); %
[sec from J2000]
            end

            switch obj.mode_software_SC_executive_selector

                case 'DART'
                    obj = func_software_SC_executive_DART(obj, mission, i_SC);
                    obj.this_sc_mode_value = func_find_this_sc_mode_value(obj,
obj.this_sc_mode);


                case 'Nightingale'
                    obj = func_software_SC_executive_Nightingale(obj, mission,
i_SC);

                otherwise
                    error('Executive mode not defined!')
            end


            % Update Data Generated

func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

            % Update Storage
            obj = func_update_software_SC_executive_store(obj, mission);

        end

    end

end
```

Published with MATLAB® R2022a

6.8 Software_SC_Power

Table of Contents

Class: Software_SC_Power

Track the power status onboard the spacecraft

```
classdef Software_SC_Power < handle
```

Properties

```
    properties
```

[ ] Properties: Initialized Variables

```
        instantaneous_data_generated_per_sample % [kb] : Data generated per
 sample, in kilo bits (kb)

        mode_software_SC_power_selector % [string] Different power modes
        % - 'Generic'
```

[ ] Properties: Variables Computed Internally

```
        name % [string] =  SC j for jth SC + SW Power

        flag_executive % [Boolean] Executive has told this sensor/actuator to
 do its job

        mean_state_of_charge % [percentage] : Mean SoC is defined by = 100×
 Sum (instantaneous_capacity) / Sum(maximum_capacity)

        data % Other useful data
```

[ ] Properties: Storage Variables

```
        store

    end
```

Methods

```
methods
```

[ ] Methods: Constructor

Construct an instance of this class

```
        function obj = Software_SC_Power(init_data, mission, i_SC)

            obj.name = [mission.true_SC{i_SC}.true_SC_body.name, ' SW
Power']; % [string]
            obj.flag_executive = 0;

            obj.instantaneous_data_generated_per_sample =
init_data.instantaneous_data_generated_per_sample; % [kb]

            obj.mode_software_SC_power_selector =
init_data.mode_software_SC_power_selector;

            if isfield(init_data, 'data')
                obj.data = init_data.data;
            else
                obj.data = [];
            end

            % Update Mean SoC
            obj = func_update_mean_state_of_charge(obj, mission, i_SC);

            % Initialize Variables to store
            obj.store = [];

            obj.store.flag_executive =
zeros(mission.storage.num_storage_steps, length(obj.flag_executive));
            obj.store.mean_state_of_charge =
zeros(mission.storage.num_storage_steps, length(obj.mean_state_of_charge));

            % Update Storage
            obj = func_update_software_SC_power_store(obj, mission);

            % Update SC Data Handling Class

func_initialize_list_HW_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

        end
```

[ ] Methods: Store

Update the store variables

```
        function obj = func_update_software_SC_power_store(obj, mission)
```

```
            if mission.storage.flag_store_this_time_step == 1
                obj.store.flag_executive(mission.storage.k_storage,:) =
obj.flag_executive; % [Boolean]
                obj.store.mean_state_of_charge(mission.storage.k_storage,:) =
obj.mean_state_of_charge; % [percentage]
            end

        end
```

[ ] Methods: Main

Main Function

```
        function obj = func_main_software_SC_power(obj, mission, i_SC)

            if (obj.flag_executive == 1)

                switch obj.mode_software_SC_power_selector

                    case 'Generic'

                        % Update Mean SoC
                        obj = func_update_mean_state_of_charge(obj, mission,
i_SC);

                    case 'Nightingale'
                        % obj =
func_update_software_SC_power_Nightingale(obj,mission,i_SC);

                        % Update Mean SoC
                        obj = func_update_mean_state_of_charge(obj, mission,
i_SC);

                    otherwise
                        error('Power mode not defined!')
                end

                % Update Data Generated

func_update_instantaneous_data_generated(mission.true_SC{i_SC}.true_SC_data_handling,
obj, mission);

            end

            % Update Storage
            obj = func_update_software_SC_power_store(obj, mission);

            % Reset Variables
            obj.flag_executive = 0;

        end

    end
```

```
end
```

Published with MATLAB® R2022a

Chapter 7

Main File

7.1 `main_v3`

Table of Contents

main_v3

This is the main time loop that runs everything!

```
tic
```

Time Loop

```
disp('Starting Main Time Loop')
for k = 1:1:mission.true_time.num_time_steps
```

Update Time, Date

```
    func_update_true_time_date(mission.true_time, k);
```

Update Storage

```
    func_update_storage_flag(mission.storage, mission);
    func_update_time_store(mission.true_time, mission);
```

Update Solar System

```
    func_main_true_solar_system(mission.true_solar_system, mission);
```

Update Target Position Velocity

```
    for i_target = 1:1:mission.num_target
        func_main_true_target(mission.true_target{i_target}, mission);
    end
```

For Each Spacecraft

```
    for i_SC = 1:1:mission.num_SC
```

[ ] Update Solar Radiation Pressure

```
        func_main_true_SC_SRP(mission.true_SC{i_SC}.true_SC_SRP, mission,
 i_SC);
```

[ ] Update Gravity Gradient

```
 func_main_true_SC_gravity_gradient(mission.true_SC{i_SC}.true_SC_gravity_gradient,
 mission, i_SC);
```

[ ] Update SC Body

```
        func_main_true_SC_body(mission.true_SC{i_SC}.true_SC_body, mission,
i_SC);
```

[ ] Update SC Position Velocity

```
        func_main_true_SC_navigation(mission.true_SC{i_SC}.true_SC_navigation,
mission, i_SC);
```

[ ] Update SC Onbaord Clock

```
        for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_onboard_clock

func_main_true_SC_onboard_clock(mission.true_SC{i_SC}.true_SC_onboard_clock{i_HW},
mission, i_SC);
        end
```

[ ] Update SC Onboard Computer

```
        for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_onboard_computer

func_main_true_SC_onboard_computer(mission.true_SC{i_SC}.true_SC_onboard_computer{i_HW},
mission, i_SC);
        end
```

[ ] Update Software SC Executive

```
func_main_software_SC_executive(mission.true_SC{i_SC}.software_SC_executive,
mission, i_SC);
```

[ ] Update SC Camera

```
        for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_camera

func_main_true_SC_camera(mission.true_SC{i_SC}.true_SC_camera{i_HW}, mission,
i_SC, i_HW);
        end

    end
```

Attitude Dynamics Loop (ADL)

```
    for k_attitude = 1:1:mission.true_time.num_time_steps_attitude
```

[ ] Update Time in ADL

```
func_update_true_time_attitude(mission.true_time, k_attitude);
```

[ ] Update Storage in ADL

```
func_update_storage_flag_attitude(mission.storage, mission);
func_update_time_store_attitude(mission.true_time, mission);
```

[ ] For Each Spacecraft

```
for i_SC = 1:1:mission.num_SC
```

[ ] [ ] Update SC Attitude in ADL

```
    func_main_true_SC_attitude(mission.true_SC{i_SC}.true_SC_adc,
mission, i_SC);
```

[ ] [ ] Update SC Sun Sensor in ADL

```
    for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_sun_sensor

func_main_true_SC_sun_sensor(mission.true_SC{i_SC}.true_SC_sun_sensor{i_HW},
mission, i_SC);
    end
```

[ ] [ ] Update SC Star Tracker in ADL

```
    for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_star_tracker

func_main_true_SC_star_tracker(mission.true_SC{i_SC}.true_SC_star_tracker{i_HW},
mission, i_SC);
    end
```

[ ] [ ] Update SC IMU in ADL

```
    for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_imu
        func_main_true_SC_imu(mission.true_SC{i_SC}.true_SC_imu{i_HW},
mission, i_SC);
    end
```

[ ] [ ] Update Software SC Attitude Estimation in ADL

```
func_main_software_SC_estimate_attitude(mission.true_SC{i_SC}.software_SC_estimate_attitu
mission, i_SC);
```

[ ] [ ] Update Software SC Attitude Control

```
func_main_software_SC_control_attitude(mission.true_SC{i_SC}.software_SC_control_attitude
mission, i_SC);
```

[ ] Update Micro Thrusters

```
           for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_micro_thruster

func_main_true_SC_micro_thruster(mission.true_SC{i_SC}.true_SC_micro_thruster{i_HW},
mission, i_SC, i_HW);
           end
```

[ ] Update Reaction wheels

```
           for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_reaction_wheel

func_main_true_reaction_wheel(mission.true_SC{i_SC}.true_SC_reaction_wheel{i_HW},
mission, i_SC, i_HW);
           end

       end

   end
```

For Each Spacecraft

```
   for i_SC = 1:1:mission.num_SC
```

[ ] Update SC Science Radar

```
       for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_science_radar

func_main_true_SC_science_radar(mission.true_SC{i_SC}.true_SC_science_radar{i_HW},
mission, i_SC, i_HW);
       end
```

[ ] Update SC Science Processor

```
        for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_science_processor

func_main_true_SC_science_processor(mission.true_SC{i_SC}.true_SC_science_processor{i_HW}
mission, i_SC);
        end
```

[ ] Update Software SC Communication

```
func_main_software_SC_communication(mission.true_SC{i_SC}.software_SC_communication,
mission, i_SC);
```

[ ] Update SC Communication Link

```
        for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_communication_link

func_main_true_SC_communication_link(mission.true_SC{i_SC}.true_SC_communication_link{i_H
mission, i_SC);
        end
```

[ ] Update SC Radio Antenna

```
        for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_radio_antenna

func_main_true_SC_radio_antenna(mission.true_SC{i_SC}.true_SC_radio_antenna{i_HW},
mission, i_SC);
        end
```

[ ] Update SC Generic Sensor

```
        for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_generic_sensor

func_main_true_SC_generic_sensor(mission.true_SC{i_SC}.true_SC_generic_sensor{i_HW},
mission, i_SC);
        end
```

[ ] Update SC Solar Panels

```
        for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_solar_panel

func_main_true_SC_solar_panel(mission.true_SC{i_SC}.true_SC_solar_panel{i_HW},
mission, i_SC);
        end
```

[ ] Update Software SC Orbit Estimation in ADL

```
func_main_software_SC_estimate_orbit(mission.true_SC{i_SC}.software_SC_estimate_orbit,
mission, i_SC);
```

[ ] Update Software SC Orbit Control in ADL

```
func_main_software_SC_control_orbit(mission.true_SC{i_SC}.software_SC_control_orbit,
mission, i_SC);
```

[ ] Update Chemical Thruster

```
       for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_chemical_thruster

func_main_true_chemical_thruster(mission.true_SC{i_SC}.true_SC_chemical_thruster,
mission, i_SC, i_HW);
       end
```

[ ] Update Fuel Tanks

```
       for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_fuel_tank

func_main_true_SC_fuel_tank(mission.true_SC{i_SC}.true_SC_fuel_tank{i_HW},
mission, i_SC);
       end
```

[ ] Update SC Battery

```
       for i_HW =
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_battery

func_main_true_SC_battery(mission.true_SC{i_SC}.true_SC_battery{i_HW},
mission, i_SC);
       end
```

[ ] Update Software SC Power

```
       func_main_software_SC_power(mission.true_SC{i_SC}.software_SC_power,
mission, i_SC);
```

[ ] Update SC Data Handling

```
func_main_true_SC_data_handling(mission.true_SC{i_SC}.true_SC_data_handling,
mission, i_SC);
```

[ ] Update SC Onboard Memory

```
        for i_HW = 
1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_onboard_memory

func_main_true_SC_onboard_memory(mission.true_SC{i_SC}.true_SC_onboard_memory{i_HW},
mission, i_SC);
        end
```

[ ] Update Software SC Data Handling

```
func_main_software_SC_data_handling(mission.true_SC{i_SC}.software_SC_data_handling,
mission, i_SC);
```

[ ] Update SC Power

```
        func_main_true_SC_power(mission.true_SC{i_SC}.true_SC_power, mission,
i_SC);

    end
```

Update Ground Stations's Radio Antenna

```
    for i_HW = 1:1:mission.true_ground_station.num_GS_radio_antenna
        func_main_true_GS_radio_antenna(mission.true_GS_radio_antenna{i_HW},
mission);
    end
```

Update Ground Station

```
    func_main_true_ground_station(mission.true_ground_station, mission, i_SC);
```

Fix Warnings

```
    w = warning('query','last');
    if  ~isempty(w)
        warning('off',w.identifier);
    end
```

Update real-time visualization

```
    func_update_realtime_plot(mission.storage, mission);
```

Stop Sim

```
    if mission.storage.flag_stop_sim == 1
        disp('Stopping Sim!')
```

```
        break
    end
end
```

Close all SPICE files

```
cspice_kclear
```

Published with MATLAB® R2022a

Chapter 8

Mission Classes

8.1 Mission_DART

Table of Contents

DART Mission

Initialization File for DART (Double Asteroid Redirection Test) mission simulation

```
% Clear workspace
clear
close all
clc

% Change workspace folder to this file location
mfile_name          = mfilename('fullpath');
[pathstr,name,ext]  = fileparts(mfile_name);
cd(pathstr);
clear mfile_name pathstr name ext

% Add required paths
addpath(genpath('../../MuSCAT_Supporting_Files'))
addpath(genpath('../.'))
```

Mission Definition

```
mission = [];
mission.name = 'DART';          % Name of the Mission
mission.num_SC = 1;             % Number of Spacecraft
mission.num_target = 1;         % Number of Target bodies
mission.frame = 'Absolute';     % Frame type: 'Absolute', 'Relative', or
 'Combined'
mission.flag_stop_sim = 0;      % Boolean flag to stop simulation if needed
```

Time Configuration

```
init_data = [];
init_data.t_initial = 0;                                    % [sec] Initial
 time
init_data.t_final = 200000;                                 % [sec] Final time
init_data.time_step = 5;                                    % [sec] Simulation
 time step
init_data.t_initial_date_string = '02-NOV-2018 00:00:00';   % Format = [DD-
MMM-YYYY HH:MM:SS]
init_data.time_step_attitude = 0.1;                         % [sec] Time step
 for attitude dynamics
mission.true_time = True_Time(init_data);
```

Storage Configuration

```
init_data = [];
init_data.time_step_storage = 1;
init_data.time_step_storage_attitude = 0.5;
init_data.flag_visualize_SC_attitude_orbit_during_sim = 0;  % [Boolean] Show
 attitude during sim
init_data.flag_realtime_plotting = 0;       % [Boolean] Show mission data and
 attitude during sim
init_data.flag_save_plots = 1;              % [Boolean] 1: Save them (takes
 little time), 0: Doesnt save them
init_data.flag_save_video = 0;              % [Boolean] 1: Save them (takes
 more time), 0: Doesnt save them
```

```
mission.storage = Storage(init_data, mission);

% Set font size for plots
mission.storage.plot_parameters.standard_font_size = 15;

% Initialize time storage
func_initialize_time_store(mission.true_time, mission);
```

Star Catalog Configuration

```
mission.true_stars = True_Stars(mission);
mission.true_stars.maximum_magnitude = 10;  % Maximum star magnitude to
 include
```

Solar System Configuration

```
init_data = [];
init_data.SS_body_names = ["Sun", "Earth"];  % Solar system bodies to include
mission.true_solar_system = True_Solar_System(init_data, mission);
```

Target Body Configuration

```
for i_target = 1:1:mission.num_target
    init_data = [];
    init_data.target_name = 'Bennu';        % Target asteroid name
    mission.true_target{i_target} = True_Target_SPICE(init_data, mission);
end
```

Ground Station Configuration

```
init_data = [];
init_data.num_GS_radio_antenna = 1;         % Number of ground station
 antennas
mission.true_ground_station = True_Ground_Station(init_data, mission);
```

Ground Station Radio Antenna Configuration

```
for i_HW = 1:1:mission.true_ground_station.num_GS_radio_antenna
    init_data = [];
    init_data.antenna_type = 'High Gain';
    init_data.mode_true_GS_radio_antenna_selector = 'RX';

    % Link Margin Calculation Parameters
    init_data.antenna_gain = 90;            % [dB]
    init_data.noise_temperature = 100;      % [K]
    init_data.beamwidth = 0.1;              % [MHz]
    init_data.energy_bit_required = 4.2;    % [dB]
    init_data.line_loss = 0;                % [dB]
    init_data.coding_gain = 7.3;            % [dB]
```

```
    mission.true_GS_radio_antenna{i_HW} = True_GS_Radio_Antenna(init_data,
 mission, i_HW);
end
```

Spacecraft Initialization

```
for i_SC = 1:1:mission.num_SC
    mission.true_SC{i_SC} = [];
end
```

Spacecraft Body Configuration

```
i_SC = 1;  % First spacecraft

init_data = [];
init_data.i_SC = i_SC;

% Body shape model
init_data.shape_model{1} = [];
init_data.shape_model{1}.Vertices = [0 0 0;
    0.3 0 0;
    0.3 0 0.1;
    0 0 0.1;
    0 0.2 0;
    0.3 0.2 0;
    0.3 0.2 0.1;
    0 0.2 0.1]; % [m]
init_data.shape_model{1}.Faces = [1 2 3;
    1 4 3;
    2 3 7;
    2 6 7;
    3 4 8;
    3 7 8;
    1 4 8;
    1 5 8;
    1 2 6;
    1 5 6;
    5 6 7;
    5 8 7];

init_data.shape_model{1}.Face_reflectance_factor =
 0.6*ones(size(init_data.shape_model{1}.Faces,1),1);
init_data.shape_model{1}.type = 'cuboid';
init_data.shape_model{1}.mass = 11; % [kg] Dry mass

% Additional mass components
init_data.mass.supplement{1}.mass = 0.5; % [kg]
init_data.mass.supplement{1}.location = [0.1 0 0]; % [m]
init_data.mass.supplement{1}.MI_over_m = zeros(3,3); % [m^2]

init_data.mass.supplement{2}.mass = 0.5; % [kg]
init_data.mass.supplement{2}.location = [0 0 0.1]; % [m]
init_data.mass.supplement{2}.MI_over_m = zeros(3,3); % [m^2]
```

```
init_data.mode_COM_selector = 'update';  % Compute Center of Mass dynamically
init_data.mode_MI_selector = 'update';   % Compute Moment of Inertia
 dynamically

% Initialize hardware configuration
run init_num_hardware_exists
init_data.num_hardware_exists = num_hardware_exists;
clear num_hardware_exists

% Define hardware complement
init_data.num_hardware_exists.num_onboard_clock = 1;
init_data.num_hardware_exists.num_camera = 1;
init_data.num_hardware_exists.num_solar_panel = 3;
init_data.num_hardware_exists.num_battery = 2;
init_data.num_hardware_exists.num_onboard_memory = 2;
init_data.num_hardware_exists.num_sun_sensor = 6;
init_data.num_hardware_exists.num_star_tracker = 3;
init_data.num_hardware_exists.num_imu = 1;
init_data.num_hardware_exists.num_micro_thruster = 12;
init_data.num_hardware_exists.num_chemical_thruster = 1;
init_data.num_hardware_exists.num_reaction_wheel = 3;
init_data.num_hardware_exists.num_communication_link = 2;
init_data.num_hardware_exists.num_radio_antenna = 1;
init_data.num_hardware_exists.num_fuel_tank = 1;
init_data.num_hardware_exists.num_onboard_computer = 2;

mission.true_SC{i_SC}.true_SC_body = True_SC_Body(init_data, mission);
```

Initialize First Spacecraft's Position and Velocity

```
init_data = [];
init_data.spice_filename = '../../MuSCAT_Supporting_Files/SC_data/DART/
traj_daresim_simple.bsp'; % [string] : SC s SPICE FileName
cspice_furnsh(init_data.spice_filename)

% bandyopa@MT-319257 exe % ./brief ../../../SC_data/traj_daresim_simple.bsp
%
% BRIEF -- Version 4.0.0, September 8, 2010 -- Toolkit Version N0066
%
%
% Summary for: ../../../SC_data/traj_daresim_simple.bsp
%
% Body: -110
%       Start of Interval (ET)              End of Interval (ET)
%       -----------------------------       -----------------------------
%       2018 OCT 27 21:36:30.000            2018 NOV 03 21:36:00.000

init_data.spice_name = '-110'; % [string] : SC's SPICE Name

% Sun centered - J2000 frame (inertial)
```

```
init_data.SC_pos_vel =
 cspice_spkezr(init_data.spice_name,mission.true_time.date,'J2000','NONE','SUN');
init_data.position = init_data.SC_pos_vel(1:3)'; % [km]
init_data.velocity = init_data.SC_pos_vel(4:6)'; % [km/sec]

init_data.mode_true_SC_navigation_dynamics_selector = 'Absolute Dynamics';

mission.true_SC{i_SC}.true_SC_navigation = True_SC_Navigation(init_data,
 mission);
```

Initialize First Spacecraft's Attitude

```
init_data = [];
init_data.SC_MRP_init = [0.1 0.2 0.3]; % MRP
init_data.SC_omega_init = [0 0 0.001]; % [rad/sec]

init_data.SC_e_init = init_data.SC_MRP_init/norm(init_data.SC_MRP_init);
init_data.SC_Phi_init = 4*atand(init_data.SC_MRP_init(1)/
init_data.SC_e_init(1)); % [deg]
init_data.SC_beta_v_init = init_data.SC_e_init *
 sind(init_data.SC_Phi_init/2);
init_data.SC_beta_4_init = cosd(init_data.SC_Phi_init/2);

init_data.attitude = [init_data.SC_beta_v_init, init_data.SC_beta_4_init]; %
 [quaternion]
init_data.attitude = func_quaternion_properize(init_data.attitude); %
 [quaternion] properized
init_data.angular_velocity = init_data.SC_omega_init;

init_data.mode_true_SC_attitude_dynamics_selector = 'Rigid';

mission.true_SC{i_SC}.true_SC_adc = True_SC_ADC(init_data, mission);
```

Initialize First Spacecraft's Power

```
init_data = [];
init_data.power_loss_rate = 0.05; % [float] 5% power loss in distribution and
 conversion
mission.true_SC{i_SC}.true_SC_power = True_SC_Power(init_data, mission);
```

Initialize First Spacecraft's Data

```
init_data = [];
init_data.mode_true_SC_data_handling_selector = 'Generic';
mission.true_SC{i_SC}.true_SC_data_handling = True_SC_Data_Handling(init_data,
 mission);
```

Initialize First Spacecraft's Radio Antenna

```
for i_HW =
 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_radio_antenna
```

```
    init_data = [];
    init_data.location = [0 1 0];   % [unit vector] antenna physical axis in Body frame
    init_data.orientation = [0 0 1];   % [unit vector] antenna pointing direction for nominal gain in Body frame

    %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
    % Antennas
    init_data.antenna_type = "dipole";      % antenna type
    init_data.antenna_gain = 28.1;          % [dB] Gain of DTE antenna SC
    init_data.antenna_axis = [0 1 0];       % [unit vector] antenna physical axis in Body frame
    init_data.antenna_pointing = [0 0 1];   % [unit vector] antenna pointing direction for nominal gain in Body frame
    init_data.antenna_frequency = 8450;     % [MHz]
    init_data.tx_line_loss = 1;             % [dB]
    init_data.noise_temperature = 100;   % [K]
    init_data.energy_bit_required = 4.2; % [dB]
    init_data.coding_gain = 7.3;         % [dB]
    init_data.beamwidth = 0.1;           % [MHz]

    init_data.maximum_data_rate = 1000;  % [kbps]
    init_data.base_data_rate_generated = 10; % [kbps]

    init_data.TX_power_consumed = 50;  % [W] Based on 50 W RF output and 50% efficiency
    init_data.RX_power_consumed = 25;   % [W] Typical for spacecraft receivers

    mission.true_SC{i_SC}.true_SC_radio_antenna{i_HW} = True_SC_Radio_Antenna(init_data, mission, i_SC, i_HW);
end
```

Spacecraft Fuel Tank Configuration

```
for i_HW = 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_fuel_tank
    init_data = [];

    % Basic properties
    init_data.name = ['Fuel Tank ', num2str(i_HW)];
    init_data.instantaneous_power_consumed = 2.0;    % [W] for heaters, valves, etc.
    init_data.instantaneous_data_rate_generated = 0.1;  % [kbps] for telemetry

    % Fuel properties
    init_data.maximum_capacity = 5.0;    % [kg] total fuel capacity
    init_data.initial_fuel_mass = 5.0;   % [kg] initial fuel mass (full tank)
    init_data.fuel_density = 1000;       % [kg/m^3] typical hydrazine density

    % Physical properties
    init_data.location = [0.15, 0.1, 0.05];  % [m] tank location in body frame
```

```
    % Shape model - simplified cuboid
    init_data.shape_model = [];
    init_data.shape_model.Vertices = [
        0.1, 0.05, 0.0;
        0.2, 0.05, 0.0;
        0.2, 0.15, 0.0;
        0.1, 0.15, 0.0;
        0.1, 0.05, 0.1;
        0.2, 0.05, 0.1;
        0.2, 0.15, 0.1;
        0.1, 0.15, 0.1
    ];
    init_data.shape_model.Faces = [
        1, 2, 3;
        1, 3, 4;
        5, 6, 7;
        5, 7, 8;
        1, 2, 6;
        1, 6, 5;
        2, 3, 7;
        2, 7, 6;
        3, 4, 8;
        3, 8, 7;
        4, 1, 5;
        4, 5, 8
    ];
    init_data.shape_model.type = 'cuboid';

    % Create fuel tank object
    mission.true_SC{i_SC}.true_SC_fuel_tank{i_HW} =
 True_SC_Fuel_Tank(init_data, mission, i_SC, i_HW);

    % Update spacecraft body with fuel mass properties
    mission.true_SC{i_SC}.true_SC_body.mass.propellant{i_HW}.mass =
 init_data.initial_fuel_mass;
    mission.true_SC{i_SC}.true_SC_body.mass.propellant{i_HW}.location =
 init_data.location;
    mission.true_SC{i_SC}.true_SC_body.mass.propellant{i_HW}.MI_over_m =
 zeros(3,3);  % Simple approximation

    % Trigger mass properties update
    mission.true_SC{i_SC}.true_SC_body.flag_update_SC_body_total_mass_COM_MI =
 1;
end
```

Initialize First Spacecraft's Solar Panels

```
for i_HW =
 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_solar_panel

    init_data = [];
    init_data.instantaneous_power_consumed = 0.01; % [W] (irrespective of
 whether it is generating power or not)
```

```
    init_data.instantaneous_data_rate_generated = (1e-3)*8; % [kbps] i.e. 1
 Byte per sec

    init_data.shape_model = [];
    init_data.shape_model.Vertices = [0 0 0; 0.2 0 0; 0.2 0 -0.6; 0 0 -0.6];
           % [m] vertices
    init_data.shape_model.Faces = [1 2 3; 1 4 3];
           % faces
    init_data.shape_model.Face_reflectance_factor_solar_cell_side = [0.01;
 0.01];         % reflectance factor of solar cell side
    init_data.shape_model.Face_reflectance_factor_opposite_side = [0.5; 0.5];
           % reflectance factor of solar cell side
    init_data.shape_model.Face_orientation_solar_cell_side = [0 -1 0];
           % orientation normal vector of solar cell side
    init_data.shape_model.type = 'cuboid';


    init_data.mass = 0.24; % [kg] ~ 2 kg/m^2

    init_data.type = 'passive_deployed';
    % 'body_mounted' : Stuck to SC side (only solar cell side is used for SRP)
    % 'passive_deployed' : Passively deployed (orientation in body frame B
 does not change, i.e. it is static)
    % 'active_deployed_gimballed' : Actively gimballed (orientation in body
 frame B changes)

    init_data.packing_fraction = 0.74; % Packing fraction of solar cells in
 solar panel
    init_data.solar_cell_efficiency = 0.28; % Efficiency of each solar cell

    if i_HW == 2
        init_data.shape_model.Vertices = [0 0 0.1; 0.2 0 0.1; 0.2 0 0.7; 0 0
 0.7];        % [m] vertices
    end

    if i_HW == 3
        init_data.shape_model.Vertices =
 mission.true_SC{i_SC}.true_SC_body.shape_model{1}.Vertices;
        init_data.shape_model.Faces =
 mission.true_SC{i_SC}.true_SC_body.shape_model{1}.Faces(1:2,:);
        init_data.type = 'body_mounted';
    end

    mission.true_SC{i_SC}.true_SC_solar_panel{i_HW} =
 True_SC_Solar_Panel(init_data, mission, i_SC, i_HW);

end
```

Initialize First Spacecraft's Battery

```
for i_HW =
 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_battery
```

```
    init_data = [];
    init_data.maximum_capacity = 40; % [W hr]
    init_data.charging_efficiency = 0.96; % [float <= 1]
    init_data.discharging_efficiency = 0.96; % [float <= 1]
    init_data.instantaneous_power_consumed = 1e-4; % [W]
    init_data.instantaneous_data_rate_generated = (1e-3)*8; % [kbps] i.e. 1
 Byte per sec

    mission.true_SC{i_SC}.true_SC_battery{i_HW} = True_SC_Battery(init_data,
 mission, i_SC, i_HW);

end
```

Initialize First Spacecraft's Onboard Memory

```
for i_HW =
 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_onboard_memory

    init_data = [];
    init_data.maximum_capacity = 1e6; % [kb]
    init_data.instantaneous_power_consumed = 1; % [W]
    init_data.instantaneous_data_rate_generated = (1e-3)*8; % [kbps] i.e. 1
 Byte per sec

    mission.true_SC{i_SC}.true_SC_onboard_memory{i_HW} =
 True_SC_Onboard_Memory(init_data, mission, i_SC, i_HW);

end
```

Initialize First Spacecraft's Onboard Clock

```
for i_HW =
 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_onboard_clock

    init_data = [];
    init_data.instantaneous_power_consumed = 0.1; % [W]
    init_data.instantaneous_data_rate_generated = (1e-3)*16; % [kbps] i.e. 2
 Bytes per sec
    init_data.mode_true_SC_onboard_clock_selector = 'Simple';
    init_data.measurement_wait_time = 0; % [sec]

    mission.true_SC{i_SC}.true_SC_onboard_clock{i_HW} =
 True_SC_Onboard_Clock(init_data, mission, i_SC, i_HW);

end
```

Initialize First Spacecraft's Cameras

```
for i_HW =
 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_camera
```

```
    init_data = [];
    init_data.instantaneous_power_consumed = 10; % [W] https://
dragonflyaerospace.com/products/caiman/
    init_data.mode_true_SC_camera_selector = 'Simple';
    init_data.measurement_wait_time = 60; % [sec] -> This was 10x60 but in the
 v1 is 60 only and that is how switch mode is implemented

    init_data.location = [0.3 0.1 0.05]; % [m]
    init_data.orientation = [1 0 0]; % [unit vector]
    init_data.orientation_up = [0 0 1]; % [unit vector]

    init_data.resolution = [512 512];  % [x y] pixel
    init_data.field_of_view = 10; % [deg]
    init_data.flag_show_camera_plot = 0;
    init_data.flag_show_stars = 1;

    init_data.instantaneous_data_generated_per_pixel = (1e-3)* 8; % [kb]

    mission.true_SC{i_SC}.true_SC_camera{i_HW} = True_SC_Camera(init_data,
 mission, i_SC, i_HW);

end
```

Initialize First Spacecraft's Sun Sensors

```
for i_HW =
 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_sun_sensor

    init_data = [];
    init_data.instantaneous_power_consumed = 36e-3; % [W] https://
www.cubesatshop.com/wp-content/uploads/2016/06/SSOCA60-Technical-
Specifications.pdf
    init_data.instantaneous_data_generated_per_sample = (4 + 1)*16e-3; %
 [kb] : 4 quaternion + 1 time vector, each of 16-bit depth
    init_data.mode_true_SC_sun_sensor_selector = 'Simple with Sun in FOV';
    init_data.measurement_wait_time = 0.1; % [sec]
    init_data.measurement_noise = deg2rad(0.5); % [rad] 0.5 degrees
    init_data.field_of_view = 60; % [deg]

    switch i_HW

        case 1
            init_data.location = [0.3 0.05 0.05]; % [m]
            init_data.orientation = [1 0 0]; % [unit vector]

        case 2
            init_data.location = [0 0.05 0.05]; % [m]
            init_data.orientation = [-1 0 0]; % [unit vector]

        case 3
            init_data.location = [0.15 0.2 0.05]; % [m]
            init_data.orientation = [0 1 0]; % [unit vector]
```

```
        case 4
            init_data.location = [0.15 0 0.05]; % [m]
            init_data.orientation = [0 -1 0]; % [unit vector]

        case 5
            init_data.location = [0.15 0.1 0.1]; % [m]
            init_data.orientation = [0 0 1]; % [unit vector]

        case 6
            init_data.location = [0.15 0.1 0]; % [m]
            init_data.orientation = [0 0 -1]; % [unit vector]

        otherwise
            error('Should not reach here!')
    end

    mission.true_SC{i_SC}.true_SC_sun_sensor{i_HW} =
 True_SC_Sun_Sensor(init_data, mission, i_SC, i_HW);

end
```

Initialize First Spacecraft's Star Tracker

```
for i_HW =
 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_star_tracker

    init_data = [];

    init_data.instantaneous_power_consumed = 1.5; %
 [W] https://www.bluecanyontech.com/static/datasheet/
BCT_DataSheet_Components_StarTrackers.pdf
    init_data.instantaneous_data_generated_per_sample = (4 + 1)*16e-3; %
 [kb] : 4 quaternion + 1 time vector, each of 16-bit depth
    init_data.mode_true_SC_star_tracker_selector = 'Simple with Sun outside
 FOV';
    init_data.measurement_wait_time = 0.1; % [sec]
    init_data.measurement_noise = 2e-4; % [rad]
    init_data.field_of_view = 90; % [deg]

    switch i_HW

        case 1
            init_data.location = [0.3 0.15 0.05]; % [m]
            init_data.orientation = [1 0 0]; % [unit vector]

        case 2
            init_data.location = [0 0.15 0.05]; % [m]
            init_data.orientation = [-1 0 0]; % [unit vector]

        case 3
            init_data.location = [0.10 0.2 0.05]; % [m]
            init_data.orientation = [0 1 0]; % [unit vector]
```

```
        otherwise
            error('Should not reach here!')
    end

    mission.true_SC{i_SC}.true_SC_star_tracker{i_HW} =
 True_SC_Star_Tracker(init_data, mission, i_SC, i_HW);

end
```

Initialize First Spacecraft's IMU

```
for i_HW = 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_imu

    init_data = [];

    init_data.instantaneous_power_consumed = 0.6; % [W] https://www.micro-
a.net/imu-tmpl.html
    init_data.instantaneous_data_generated_per_sample = (3 + 1)*16e-3; %
 [kb] : 3 angular velocity + 1 time vector, each of 16-bit depth
    init_data.mode_true_SC_imu_selector = 'Simple';
    init_data.measurement_wait_time = 0.1; % [sec]
    init_data.measurement_noise = 9.7e-5; % [rad/sec]

    init_data.location = [0 0 0]; % [m]
    init_data.orientation = [1 0 0]; % [unit vector]

    mission.true_SC{i_SC}.true_SC_imu{i_HW} = True_SC_IMU(init_data, mission,
 i_SC, i_HW);

end
```

Initialize First Spacecraft's Micro Thrusters

```
for i_HW =
 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_micro_thruster

    init_data = [];

    init_data.instantaneous_power_consumption = 10; % Watts
    init_data.instantaneous_data_generated_per_sample = (3)*16e-3; % [kb] :
 thrust + health + temperature, each of 16-bit depth
    init_data.mode_true_SC_micro_thruster_selector = 'Simple'; % Mode (Truth/
Simple)
    init_data.thruster_noise = 100*(1e-6); % Noise level [N](unit depends on
 implementation)

    init_data.micro_thruster_ISP = 700; % [sec]

    init_data.minimum_thrust = 0.001; % [N]
    init_data.maximum_thrust = 10*(1e-2); % [N]

    init_data.command_wait_time = 0.5; % Seconds between commands
```

```matlab
switch i_HW
    case 1
        init_data.location = [0.3 0.1 0.05]; % [m]
        init_data.orientation = [0 1 0]; % [unit vector]

    case 2
        init_data.location = [0.3 0.1 0.05]; % [m]
        init_data.orientation = [0 -1 0]; % [unit vector]

    case 3
        init_data.location = [0.3 0.1 0.05]; % [m]
        init_data.orientation = [0 0 1]; % [unit vector]

    case 4
        init_data.location = [0.3 0.1 0.05]; % [m]
        init_data.orientation = [0 0 -1]; % [unit vector]

    case 5
        init_data.location = [0 0.1 0.05]; % [m]
        init_data.orientation = [0 1 0]; % [unit vector]

    case 6
        init_data.location = [0 0.1 0.05]; % [m]
        init_data.orientation = [0 -1 0]; % [unit vector]

    case 7
        init_data.location = [0 0.1 0.05]; % [m]
        init_data.orientation = [0 0 1]; % [unit vector]

    case 8
        init_data.location = [0 0.1 0.05]; % [m]
        init_data.orientation = [0 0 -1]; % [unit vector]

    case 9
        init_data.location = [0.15 0.2 0.05]; % [m]
        init_data.orientation = [0 0 1]; % [unit vector]

    case 10
        init_data.location = [0.15 0.2 0.05]; % [m]
        init_data.orientation = [0 0 -1]; % [unit vector]

    case 11
        init_data.location = [0.15 0 0.05]; % [m]
        init_data.orientation = [0 0 1]; % [unit vector]

    case 12
        init_data.location = [0.15 0 0.05]; % [m]
        init_data.orientation = [0 0 -1]; % [unit vector]

    otherwise
        error('Should not reach here!')
end
```

```
    mission.true_SC{i_SC}.true_SC_micro_thruster{i_HW} =
 True_SC_Micro_Thruster(init_data, mission, i_SC, i_HW);

end
```

Initialize the Reaction Wheels

Dart can be simulated using 3 or 4 wheels as an example !

```
for i_HW =
 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_reaction_wheel

    init_data = [];
    init_data.location = [0,0,0];
    init_data.radius = (43e-3)/2; % [m] radius of 1 RW
    init_data.mass = 0.137; % [kg] mass of 1 RW
    init_data.max_angular_velocity = 6500*2*pi/60; % [rad/s] 6500 RPM
    init_data.angular_velocity_noise = 0.001*2*pi/60;      % [rad/s] velocity
 noise (reduced from 0.01)
    init_data.instantaneous_data_generated_per_sample = (3)*16e-3; % [kb] :
 thrust + health + temperature, each of 16-bit depth
    init_data.max_torque = 3.2*1e-3; % Nm

    % Calculate and set maximum acceleration
    % This is redundant with the calculation in the True_SC_Reaction_Wheel
 constructor,
    % but makes it explicit and easier to adjust
    moment_of_inertia = 0.5 * init_data.mass * init_data.radius^2;
    init_data.maximum_acceleration = init_data.max_torque /
 moment_of_inertia; % rad/s^2

    init_data.power_consumed_angular_velocity_array = [1e-3*[180 600
 6000]; [0 1000*2*pi/60 init_data.max_angular_velocity]]; % [power_array ;
 velocity_array]

    % 3 wheel configuration

  if(mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_reaction_wheel
 == 3)
        switch i_HW
            case 1
                init_data.orientation = [1, 0, 0];  % X-axis
            case 2
                init_data.orientation = [0, 1, 0];  % Y-axis
            case 3
                init_data.orientation = [0, 0, 1];  % Z-axis
        end
    end

    % 4 wheel configuration

  if(mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_reaction_wheel
 == 4)
```

```
        switch i_HW
            case 1
                init_data.orientation = [1, 1, 0]/sqrt(2);  % Diagonal in XY-
plane
            case 2
                init_data.orientation = [1, -1, 0]/sqrt(2); % Diagonal in XY-
plane
            case 3
                init_data.orientation = [0, 1, 1]/sqrt(2);  % Diagonal in YZ-
plane
            case 4
                init_data.orientation = [0, 1, -1]/sqrt(2); % Diagonal in YZ-
plane
        end
    end

    mission.true_SC{i_SC}.true_SC_reaction_wheel{i_HW} =
 True_SC_Reaction_Wheel(init_data, mission, i_SC, i_HW);

end
```

Chemical Thruster Configuration

```
init_data = [];
i_HW =
 mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_chemical_thruster;

% Power and data parameters
init_data.instantaneous_power_consumption = 2.0;        % [W] Base power draw
 (standby)
init_data.thruster_warm_up_power_consumed = 5.0;        % [W] Power during
 warm-up phase
init_data.command_actuation_power_consumed = 15.0;      % [W] Power during
 active thrust
init_data.instantaneous_data_generated_per_sample = 10; % [kb] per sample
init_data.chemical_thruster_noise = 10e-4;              % [N] Thrust noise
 level

% Thruster properties
init_data.chemical_thruster_ISP = 200;                 % [s] Specific impulse
init_data.command_wait_time = 1;                       % [s] Minimum time
 between commands
init_data.location = [0.3, 0.2/2, 0.1/2];                % [m] Thruster
 location in body frame
init_data.orientation = [-1, 0, 0];                     % Thrust direction
 (unit vector)

init_data.maximum_thrust = 1;                          % [N] Maximum thrust
 level
init_data.minimum_thrust = 0.01;                       % [N] Minimum thrust
 level

% Create chemical thruster object
```

```
mission.true_SC{i_SC}.true_SC_chemical_thruster =
 True_SC_Chemical_Thruster(init_data, mission, i_SC, i_HW);
```

Onboard Computer Configuration

```
for i_HW =
 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_onboard_computer
    init_data = [];

    % Basic properties
    init_data.name = ['Onboard Computer ', num2str(i_HW)];

    % Set different properties for primary and backup computers
    if i_HW == 1
        % Primary computer
        init_data.instantaneous_power_consumed = 8.0;     % [W] Main flight
 computer
        init_data.instantaneous_data_rate_generated = 2.0;  % [kbps] for
 telemetry and logs
        init_data.processor_utilization = 25;             % [%] Fixed CPU
 usage
    else
        % Backup computer
        init_data.instantaneous_power_consumed = 4.0;     % [W] Backup in
 standby mode
        init_data.instantaneous_data_rate_generated = 0.5;  % [kbps] minimal
 telemetry
        init_data.processor_utilization = 5;              % [%] Fixed low
 utilization in standby
    end

    % Create onboard computer object
    mission.true_SC{i_SC}.true_SC_onboard_computer{i_HW} =
 True_SC_Onboard_Computer(init_data, mission, i_SC, i_HW);
end
```

Spacecraft Communication Links Configuration

```
for i_HW =
 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_communication_link
    init_data = [];

    % Configure appropriate link based on index
    if i_HW == 1
        % Downlink: Spacecraft to Earth
        init_data.TX_spacecraft = i_SC;             % Transmitter is this
 spacecraft
        init_data.TX_spacecraft_Radio_HW = 1;       % Using antenna 1

        init_data.RX_spacecraft = 0;                % Receiver is Ground
 Station (0)
```

```
        init_data.RX_spacecraft_Radio_HW = 1;      % Using GS antenna 1

        init_data.flag_compute_data_rate = 0;      % Use given data rate
 instead of computing
        init_data.given_data_rate = 360;            % [kbps] Downlink data
 rate
    else
        % Uplink: Earth to Spacecraft
        init_data.TX_spacecraft = 0;               % Transmitter is Ground
 Station (0)
        init_data.TX_spacecraft_Radio_HW = 1;      % Using GS antenna 1

        init_data.RX_spacecraft = i_SC;            % Receiver is this
 spacecraft
        init_data.RX_spacecraft_Radio_HW = 1;      % Using antenna 1

        init_data.flag_compute_data_rate = 0;      % Use given data rate
 instead of computing
        init_data.given_data_rate = 0;             % [kbps] Set low to avoid
 overfilling memory
    end

    % Create communication link object
    mission.true_SC{i_SC}.true_SC_communication_link{i_HW} =
 True_SC_Communication_Link(init_data, mission, i_SC, i_HW);
end
```

Initialize Solar Radiation Pressure

```
init_data = [];
init_data.enable_SRP = 1; % Enable SRP calculations

mission.true_SC{i_SC}.true_SC_SRP = True_SC_SRP(init_data, mission, i_SC);
```

Initialize Gravity Gradient for Earth

```
init_data = [];
init_data.enable_G2 = 0; % Disable gravity gradient because Dart is an
 interceptor

mission.true_SC{i_SC}.true_SC_gravity_gradient =
 True_SC_Gravity_Gradient(init_data, mission, i_SC);
```

Spacecraft Software: Executive Configuration

```
init_data = [];
init_data.sc_modes = {'Point camera to Target', 'Maximize SP Power', 'Point
 Thruster along DeltaV direction', 'DTE Comm'};
init_data.mode_software_SC_executive_selector = 'DART';

mission.true_SC{i_SC}.software_SC_executive = Software_SC_Executive(init_data,
 mission, i_SC);
```

Spacecraft Software: Attitude Estimation Configuration

```
init_data = [];
init_data.mode_software_SC_estimate_attitude_selector = 'Truth';  % Use true
 attitude values

mission.true_SC{i_SC}.software_SC_estimate_attitude =
 Software_SC_Estimate_Attitude(init_data, mission, i_SC);
```

Spacecraft Software: Orbit Estimation Configuration

```
init_data = [];
init_data.mode_software_SC_estimate_orbit_selector = 'TruthWithErrorGrowth';
  % Use true orbit values with error growth when target not visible

mission.true_SC{i_SC}.software_SC_estimate_orbit =
 Software_SC_Estimate_Orbit(init_data, mission, i_SC);
```

Spacecraft Software: Orbit Control Configuration

```
init_data = [];
init_data.max_time_before_control = 0.5*60*60 + 900;  % 45 minutes
init_data.mode_software_SC_control_orbit_selector = 'DART';

mission.true_SC{i_SC}.software_SC_control_orbit =
 Software_SC_Control_Orbit(init_data, mission, i_SC);
```

Spacecraft Software: Attitude Control Configuration

```
init_data = [];
init_data.mode_software_SC_control_attitude_selector = 'DART Control
 Asymptotically Stable send to actuators';
init_data.control_gain = [1 0.2];    % Controller gain parameters

mission.true_SC{i_SC}.software_SC_control_attitude =
 Software_SC_Control_Attitude(init_data, mission, i_SC);
```

Spacecraft Software: Communication Configuration

```
init_data = [];
```

```
init_data.mode_software_SC_communication_selector = 'DART';
init_data.instantaneous_data_generated_per_sample = (1e-3)*8*2;  % [kb] 2
 Bytes per sample
init_data.attitude_error_threshold_deg = 1;  % [deg] Max attitude error for
 communication

init_data.data = [];
init_data.data.last_communication_time = 0;
init_data.data.wait_time_comm_dte = 0.7*60*60;  % [sec] 42 minutes between DTE
 comms

mission.true_SC{i_SC}.software_SC_communication =
 Software_SC_Communication(init_data, mission, i_SC);
```

Spacecraft Software: Power Management Configuration

```
init_data = [];
init_data.mode_software_SC_power_selector = 'Generic';
init_data.instantaneous_data_generated_per_sample = (1e-3)*8*2;  % [kb] 2
 Bytes per sample

mission.true_SC{i_SC}.software_SC_power = Software_SC_Power(init_data,
 mission, i_SC);
```

Spacecraft Software: Data Handling Configuration

```
init_data = [];
init_data.mode_software_SC_data_handling_selector = 'Generic';
init_data.instantaneous_data_generated_per_sample = (1e-3)*8*2;  % [kb] 2
 Bytes per sample

mission.true_SC{i_SC}.software_SC_data_handling =
 Software_SC_Data_Handling(init_data, mission, i_SC);
```

Final Things to Do Before Running the Simulation

```
% Initialize mass, COM, MI
func_update_SC_body_total_mass_COM_MI(mission.true_SC{i_SC}.true_SC_body);

% Initialize store of Power
func_initialize_store_HW_power_consumed_generated(mission.true_SC{i_SC}.true_SC_power,
 mission);

% Initialize store of Data Handling
func_initialize_store_HW_data_generated_removed(mission.true_SC{i_SC}.true_SC_data_handlin
 mission);
```

```
% Initialize onboard computers
for i_HW =
 1:1:mission.true_SC{i_SC}.true_SC_body.num_hardware_exists.num_onboard_computer
    mission.true_SC{i_SC}.true_SC_onboard_computer{i_HW}.flag_executive = 1; %
 Start active
end
```

Save All Data

```
clear init_data i_SC i_HW i_target

% Vizualise the SC in 3D + Dashboard
func_visualize_SC(mission.storage, mission, true);
save([mission.storage.output_folder, 'all_data.mat'], '-v7.3')
```

Execute Main File

```
run main_v3.m
```

Save All Data

```
close all
disp ('-----------------------------------------')
disp('Simulation Over. Starting saving data to disk...');

save([mission.storage.output_folder, 'all_data.mat'], '-v7.3')

disp(['Finished writing to file "all_data.mat" in folder : ',
 mission.storage.output_folder])
disp ('-----------------------------------------')
```

Plots

Use our memory-optimized visualization

```
fprintf('Starting memory-optimized visualization...');
memoryInfo = evalc('dispmemory()');
disp(['Current memory before visualisation - ', memoryInfo(1:end-1), ])

func_visualize_simulation_data(mission.storage, mission);

memoryInfo = evalc('dispmemory()');
fprintf('Visualization complete.');
disp(['Current memory after visualisation - ', memoryInfo(1:end-1), ])
disp ('-----------------------------------------')
```

Published with MATLAB® R2022a

Bibliography

[1] S. Bandyopadhyay, Y. K. Nakka, L. Fesq, and S. Ardito, "Design and development of MuSCAT: Multi-spacecraft concept and autonomy tool," in *AIAA ASCEND Autonomous Operations in Space*, Las Vegas, NV, 2024.