Formats of apriori files for VTD.

L. Petrov

Abstract:

This document provides description of formats for a priori data used for computing VLBI time delay and Doppler frequency shift for observations of objects in the Solar system.

Table of contents:

1 Preliminaries remarks

- 1.1 Date format:
- 1.2 Solve date format
- 1.3 VEX date format
- 1.4 Angle formats

2 Data formats

- 2.1 LEAP SECOND
- 2.2 <u>DE_EPHEMERIDES</u>
- 2.3 STATION DESCRIPTION
- 2.4 SOURCE_COORDINATES
- 2.5 SOURCE_COORDINATES: SOU-MODFILES
- 2.6 SOURCE_COORDINATES: CAT-FORMAT
- 2.7 SOURCE COORDINATES: GETPAR SOU-FORMAT
- 2.8 STATION COORDINATES
- 2.9 STATION_VELOCITIES
- 2.10 STATION ECCENTRICITIES
- 2.11 AEM_FILE
- 2.12 ERM FILE
- 2.13 HARMONIC_EOP_FILE:
- 2.14 EOP SERIES
- 2.15 POSVAR MOD: (HARMONIC MODEL)
- 2.16 POSVAR MOD: (TIME SERIES)
- 2.17 POSVAR MOD: (B SPLINE)
- 2.18 ANTENNA_DEFORMATIONS_FILE
- 2.19 SLANTED PATH DELAY BIAS FILE
- 2.20 EXTERNAL DELAY DIR
- 2.21 <u>IONOSPHERE DATA FILE</u>
- 2.22 HYDROSTATIC_MAPPING_FUNCTION/WET_MAPPING_FUNCTION: (MMF)

1 Preliminaries remarks

1.1 Date format:

Internally dates are kept in VTD in a pair of variables: MJD of INTEGER*4 type and TAI of REAL*8 type. TAI keeps time elapsed from the midnight. External dates can be presented in two formats: Solve format compatible with ISO 8601 and VEX format.

1.2 Solve date format

```
where YYYY stands for year
          \ensuremath{\mathsf{MM}} stands for the month number
          DD stands for the day of month
          hh stands for the hour
          mm stands for the minute
          ss stands for the second. Decimal point
             and the fractional part are optional
  Example: 2010.06.20T10:45:51.120391
  This format is compatible with ISO 8601.
  VTD also accepts date with character "_" instead of "T" \,
  in the 11-th position for better readability.
  Example: 2010.06.20_10:46:36
  This format is incompatible with ISO 8601.
                                                      1.3 VEX date format
  {\tt YYYYyDDDdHHhNNmSS.SSSSSs}
  where YYYY stands for year
         DDD stands for the day of year
          HH stands for the hour
          NN stands for the minute
          SS stands for the second. Decimal point
             and the fractional part are optional
  Examples:
  2010y171d10h49m19.129803s
  2010y171d10h50m49s
                                                       1.4 Angle formats
Angles are presented in the form
DDD_MM_SS.SSSSS or HH_MM_SS.SSSSS
where DDD is degree
       MM is arc-minute
       SS is arcsecond. Decimal point
          and the fractional part are optional
      HH is hour
      MM is minute
      SS is second of time. Decimal point
          and the fractional part are optional
Delimiters "_" or ":" are acceptable
Examples:
-64_21_58.19083
+64:21:58
10:52:02.282921
 10_54_57
                                                        2 Data formats
                                                       2.1 LEAP_SECOND
```

Label: # LEAP_SECOND file Version of 2004.01.29

Purpose: Data file in LEAP_SECOND format contains the dates of of the difference TAI-UTC as a function of UTC time tag.

 $\ensuremath{\mathsf{TAI}}$ stands for international atomic time

(Temps Atomique International), and UTC is a non-differential $% \left(1\right) =\left(1\right) \left(1\right$

step-wise function of time.

Type: Ascii

Example: \$(VTD_ROOT)/share/leapsec.dat

Comment character: #

```
Data record format:
```

Field 1:6 A6 Delimiter: Date:

Field 7:27 A21 Date as UTC time tag in Solve format.

Field 28:38 All Delimiter: TAI-UTC:

Field 39:43 F5.1 The difference TAI minus UTC

2.2 DE EPHEMERIDES

Label: ?

Purpose: Table of Chebyshev coefficients for expansion of positions

of the Sun, Moon and 9 major planets.

Type: Ascii

Example: \$(VTD_ROOT)/share/DE403_JPL.dat

Comment character: n/a

Data record format: I completely forgot, sorry. It is rather complicated

2.3 STATION_DESCRIPTION

Label: # STATION DESCRIPTION Format version of 2004.01.26 Purpose: Defines name of the tectonic plate, type of the mounting, and the value of axis offset for stations.

Ascii

Example: \$(VTD_ROOT)/share/station.desc

Comment character: # Data record format:

Field 1:8 A8 IVS Site name Field 12:15 A4 Antenna mounting code: AZEL, EQUA, X-YN, X-YE, RICH

Field 18:25 F8.5 Antenna offset (m)

Field 28:31 A4 Tectonic plate according to NUVEL

Field 35:80 A46 Comments

2.4 SOURCE COORDINATES

Three formats are supported

2.5 SOURCE_COORDINATES: SOU-MODFILES

Label: \$\$ SOU-MODFILE Format pre-2000

Purpose: Defines IVS source name, source right ascension, source declination, and the semi-major axis of the

error ellipse.

Type: Ascii

Example: \$(VTD_ROOT)/share/glo.src

Comment character: \$ Data record format:

2357-326 00 00 20.399945 -32 21 01.23327 0.60 ! J0000-3221

Field 1:4 A4 Delimiter. Must be blank

Field 5:12 A8 IVS name of the source. For 98% sources IVS name coincides with B1950 name. For remaining sources

a common name is used.

Field 15:16 I2 Hours of right ascension Field 18:19 I2 Minutes of right ascension Field 21:28 F9.6 Seconds of right ascension Field 35:37 I3 Degrees of declination

Field 39:40 I3 Minutes of declination

Field 42:49 F8.5 Arcseconds of declination Field 53:58 F6.2 Semi-major axis of the error ellipse.

Units: milli-arcseconds.

Value 999.99 indicates that no estimate of the error ellipse is available. NB: in that case there may be no Field 61:128 A58 Comments

2.6 SOURCE_COORDINATES: CAT-FORMAT

```
Label: $$ SOU-MODFILE Format pre-2000
Purpose: Defines IVS source name, IAU J2000 name, source right ascension,
         source declination, information about errors, and correlated
         flux densities.
         Ascii
Example: http://astrogeo.org/rfc
Comment character: #
Data record format:
Field
         1:1
                Α1
                       Category: C (calibrator), N (non-calibrator), U (unreliable coordinates)
         4:11 A8
Field
                       IVS name (B1950)
Field 13:22 A10 IAU name (J2000.0)
Field 25:26
                12
                       Right ascension: hours
Field 28:29 I2
                       Right ascension: minutes
       31:39 F9.6 Right ascension: seconds
Field
Field 41:43 I3
                       Declination: degrees
Field 45:46 I3 Declination: minutes
Field 48:57 F8.5 Declination: seconds
Field
        58:63 F6.2 Inflated error in right ascension in mas
        65:70 F6.2 Inflated error in declination in mas
Field
Field 73:78 F6.3 Correlation between right ascension and declination Field 80:85 I6 Number of observations used Field 88:88 A1 Blank or < or - for X-band total flux density integrations.
                       Blank or < or - for X-band total flux density integrated over entire map
Field
       89:92 F4.2 X-band total flux density integrated over entire map, Jy
Field 94:94 A1 Blank or < or - for X-band unresolved flux density at VLBA baselines, Jy
        95:98 F4.2 X-band unresolved flux density at long VLBA baselines, Jy
Field
Field 101:101 A1 Blank or < or - for S-band total flux density integrated over entire map
Field 102:105 F4.2 S-band total flux density integrated over entire map, Jy
Field 107:107 A1 Blank or < or - for S-band unresolved flux density at VLBA baselines
Field 108:111 F4.2 S-band unresolved flux density at long VLBA baselines, Jy
Field 114:116 A3 Used Band: X, S or X/S
Field 119:130 A12 Catalogue name
       Missing value: -1.0
       minus in columns 88, 94, 101 or 107 means that no data in the following column present
           in columns 88, 94, 101 or 107 means that the upper limit of the flux density is presented in the following c
                                            2.7 SOURCE COORDINATES: GETPAR SOU-FORMAT
Label: # GETPAR_SOU format version 1.0 of 2001.05.25
Purpose: Contains estimates of right ascension and declination of
```

```
of the same source.
Type:
        Ascii
Example: http://astrogeo.org/rfc
Comment character: #
Data record format:
       Field Format Units Meaning
             A8 --
Field 1:8
                           record type identifier: SOU_GCO:
Field 11:18 A8
                           IVS source name.
                   hours right ascension. hours part
Field 25:26 I2
                           separator "_"
Field 27:27 A1
                    --
Field 28:29 I2
                    min.
                           right ascension. minutes part
Field 30:30
             Α1
                           separator "_"
Field 31:41 F11.8 sec.
                           right ascension. seconds part
Field 46:55
             F10.4 mas
                           formal error of right ascension
Field 62:64 I3
                           declination. degrees part.
                    deg.
Field 65:65
             Α1
                           separator "_"
Field 66:67 I2
                    arcmin declination. arcminutes part.
Field 68:68 A1
                           separator "
             F10.7 arcsec declination. arcseconds part.
Field 69:78
Field 83:92 F10.4 mas
                           formal uncertainty of declination
Field 99:104 F6.4 d/l
                           correlation between the estimates of
                           right ascension and declination.
Field 116:122 I7
                           the number of observations of this source
```

sources, as well as their formal uncertainties and correlations between right ascension and declination

used in solution.

Field 133:139 I7 total number of observations of this source. Field 151:155 I5 -the number of sessions of this source used in

solution.

Field 166:170 I5 total number of sessions with this source. Field 182:191 A10 the date of the first session with this source

used in solution. format: yyyy.mm.dd

(as integer numbers).

the date of the last session with this source Field 203:212 A10 --

used in solution. format: yyyy.mm.dd (as integer numbers).

2.8 STATION_COORDINATES

Label: \$\$ SIT-MODFILE Format 2001.09.26

Purpose: Defines position of stations at the specified epoch.

Type: Ascii

Example: \$(VTD_ROOT)/share/glo.sit

Comment character: #

Epoch of the station catalogue in date Solve formats defined

in the 3rd row at fields 11:21.

Data record format:

Field 1:4 A4 Delimiter. Must be blank Field 5:12 A8 Field 13:15 A3 IVS station name Delimiter. Must be blank Field 16:27 F12.3 Station X-coordinate in meters Field 28:31 A4 Delimiter. Must be blank

Field 32:43 F12.3 Station Y-coordinate in meters Field 45:47 A4 Delimiter. Must be blank Field 48:59 F12.3 Station Z-coordinate in meters

Field 60:128 A49 Comments

2.9 STATION_VELOCITIES

Label: \$\$ VEL-MODFILE Format 2001.09.26 Purpose: Defines secular velocities of stations

Type: Ascii

Example: \$(VTD_ROOT)/share/glo.vel

Comment character: # Data record format:

Field 1:4 A4 Field 5:12 A8 Delimiter. Must be blank IVS station name Field 13:20 A8 Delimiter. Must be blank

Field 21:28 F8.2 Station velocity along X-axis in mm/year

Field 29:36 A8 Delimiter. Must be blank

Field 37:44 F8.2 Station velocity along Y-axis in mm/year

Delimiter. Must be blank

Field 45:52 A8 Field 53:60 F8.2 Station velocity along Z-axis in mm/year

Field 62:128 A47 Comments

2.10 STATION ECCENTRICITIES

Label: # ECC-FORMAT V 1.0 ECCENTRICITY FILE

Purpose: Defines a monument number for each VLBI station and an eccentricity vector from the monument to the antenna's

reference point (axis intersection)

Ascii Type:

Example: \$(VTD_ROOT)/share/ECCDAT.ecc

Comment character: # Data record format:

Field 3:10 IVS station name Field 12:15 Monument number

Field 18:33 Starting date of validity of the eccentricity vector

```
Field 18:21 Year of starting date of validity
Field 23:24 Month of starting date of validity
Field 26:27 Day of month of starting date of validity
Field 29:30 Hour (UTC) of starting date of validity
Field 32:33 Minute (UTC) of starting date of validity
Field 36:51 Ending date of validity of validity of the eccentricity vector
Field 36:39 Year of ending date of validity
Field 41:42 Month of ending date of validity
Field 44:45 Day of month of ending date of validity
Field 47:48 Hour (UTC) of ending date of validity
Field 50:51 Minute (UTC) of ending date of validity
Field 54:63 First coordinate of eccentricity (in meters)
Field 65:74 Second coordinate of eccentricity (in meters)
Field 76:85 Third coordinate of eccentricity (in meters)
Field 88:90 Type of eccentricity data. Set meaning of eccentricity
             coordinates.
             Two types are supported:
             NEU -- 1-st coordinate is a north projection;
                     2-nd coordinate is an east projection;
                     3-rd coordinate is a vertical projection directed up
                    (more precisely speaking it is directed along
                     a normal to the ellipsoid)
             XYZ -- 1-st coordinate is a X-coordinate in crust
                          fixed system;
                     2-nd coordinate is a Y-coordinate in crust
                          fixed system;
                     3-rd coordinate is a Z-coordinate in crust
                          fixed system.
```

2.11 AEM_FILE

TBD

2.12 ERM_FILE

TBD

2.13 HARMONIC EOP FILE:

Label: HEO Format version of 2007.08.23

Purpose: Describes small harmonic variations in the Earth orientation. "Small" means that the squares of the $\ensuremath{\mathsf{T}}$

rotation angles can be neglected.

Type: Ascii

Example: \$(VTD_ROOT)/share/heo_20091201.heo

A file in HEO format consists of records of variable length in ASCII coding. The records are separated by a character with decimal code 13. The records of the following types are supported:

- Header record;
- N-record: Model name record;
- E-record: Time epoch record;
- 4) H-record: Harmonic definition records;5) A-record: Amplitude definition records;
- 6) V-record: Velocities definition records;
- 7) S-record: Amplitude errors definition records;
- 8) R-record: Velocities errors definition records;
- 9) Trailer record.

Records which start from # character are considered as comments.

The first record of a valid file in HEO format is the header record. It is followed by the model name record, time epoch record and then by one or more harmonic definition records and one or more harmonic definition records. The last record is a trailer record. All harmonic definition records should precede amplitude and velocity definition records. Names of a harmonic in the amplitude or velocity records should be defined in the harmonic definition record. The number of velocity records can be less than the number of amplitude records, and the number of amplitude records can be less than the number of harmonic records. If a harmonic is not defined in an amplitude records, its amplitude is considered to be zero. If a harmonic is not defined

in a velocity records, the rate of change of the amplitude of that harmonic is considered to be zero.

Records format:

1) A header record contains the string "HEO Format version of 2007.08.23"

The header record allows to distinguish the valid file in the HEO format from files in other formats and tells to a parsing software that is the version of the format.

A name record defines the name of the model of the harmonic Earth orientation variations.

Format of an N-record:

```
Field 1:1 A1 -- Records ID: letter N (decimal code 78).
field 2:3 a2 -- delimiters: blanks.
Field 4:80 A77 -- 77-letter long model name. May contain any characters in the decimal range [32, 255].
```

3) An epoch record defines the epoch of the expansion. An expansion may have mixed terms (t-t0)*sin(at+p), (t-t0)*cos(at+p), where t is time. The E-record defines the epoch t0 in mixed terms. If an expansion does not have mixed terms, then the epoch defined in this record is not used. Time scale TDT is used for defining the reference epoch.

Format of a E-record:

```
Field 1:1 A1
                  -- Records ID: letter E (decimal code 69).
field 2:2 a2 -- delimiters: blanks.
Field 4:7 I4
                  -- Year
field 8:8 a1
                 -- delimiter: letter . (decimal code 46).
Field 9:10 I2
                  -- The index of the month in the year in the range [1,12]
field 11:11 a1
                  -- delimiter: letter . (decimal code 46).
Field 12:13 I2
                  -- The index of the day in the month in the range [1,31]
                  -- delimiter: letter - (decimal code 45).
field 14:14 a1
Field 15:16 I2
                  -- Hour in the range [0,23]
field 17:17 a1
                  -- delimiter: letter : (decimal code 58).
Field 18:19 I2
                  -- Minute in the range [0,23]
field 20:20 a1
                  -- delimiter: letter : (decimal code 58).
Field 21:24 F4.1 -- Seconds in the range [0.0, 59.9]
```

4) A harmonic definition record defines the argument of the harmonic in the form {phase + freq*(t-tr) + 1/2*accel*(t-tr)**2} where t is time in TDT time scale and tr is the reference epoch J2000.0, 01 January 2000, 12 hours TDT. The file cannot contain more than one definition of the same harmonic.

Format of an H-record:

```
-----
```

```
-- Records ID: letter H (decimal code 72).
Field 1:1 A1
field 2:3 a2
                  -- delimiters: blanks.
Field 4:11 A8
                  -- 8-letter long harmonic name. May contain any
                      characters with decimal codes 32-255, but blanks
                      are allowed only at the end of the harmonic name.
                      This field should not necessarily have a special
                     meaning. Parsing software should not try to
                     interpret this name.
                  -- delimiters: blanks.
field 12:13 a2
Field 14:25 F11.9 -- Phase of the harmonic in float format.
                    Units: rad.
field 26:27 a2
                  -- delimiters: blanks.
Field 28:46 D19.12 -- Frequency of the harmonic in float format.
                     Units: rad/sec.
field 47:48 a2
                  -- delimiters: blanks.
Field 49:59 D11.4 -- Acceleration of the harmonic in float format.
                    Units: rad/sec**2.
field 60:60 a1
                   -- delimiters: blanks.
field 61:80 A20 -- Comment. Parser ignores contents of this field.
```

5) An amplitude record specifies the harmonic and 4 amplitudes of the variation of the Earth orientation: the in_phase polar motion (PM_amp_cos), the out_of_phase polar motion (PM_amp_sin), the in_phase rotation around E3 axis (E3_amp_cos), and the out_of_phase rotation around E3 axis (E3_amp_sin). A file cannot contain more than one amplitude record for the same harmonic. The harmonic referred in an amplitude record must be defined in the preceding harmonic definition record.

These amplitudes allows to define instantaneous small Euler angles of the perturbations in the Earth rotation with respect to an apriori model in this way:

```
E1 = [ PM_amp_cos + PM_vel_cos*(t-t0) ] *
    cos { (ut1-tdt)*2*pi/86400 + phase + freq*(t-tr) + 1/2*accel*(t-tr)**2 }
+ [ PM_amp_sin + PM_vel_sin*(t-t0) ] *
    sin { (ut1-tdt)*2*pi/86400 + phase + freq*(t-tr) + 1/2*accel*(t-tr)**2 }

E2 = [ PM_amp_cos + PM_vel_cos*(t-t0) ] *
    sin { (ut1-tdt)*2*pi/86400 + phase + freq*(t-tr) + 1/2*accel*(t-tr)**2 }
- [ PM_amp_sin + PM_vel_sin*(t-t0) ] *
    cos { (ut1-tdt)*2*pi/86400 + phase + freq*(t-tr) + 1/2*accel*(t-tr)**2 }

E3 = [ E3_amp_cos + E3_vel_cos*(t-t0) ] *
    cos { (ut1-tdt)*2*pi/86400 + phase + freq*(t-tr) + 1/2*accel*(t-tr)**2 }
+ [ E3_amp_sin + E3_vel_sin*(t-t0) ] *
    sin { (ut1-tdt)*2*pi/86400 + phase + freq*(t-tr) + 1/2*accel*(t-tr)**2 }

Sin { (ut1-tdt)*2*pi/86400 + phase + freq*(t-tr) + 1/2*accel*(t-tr)**2 }
```

Where

- ${\sf E1}$ -- rotation around axis 1 (+Y angle of the polar motion)
- E2 -- rotation around axis 2 (+X angle of the polar motion)
- E3 -- rotation around axis 3 (-1.0027*Ut1 angle of the Earth's rotation)
- t-tr -- The interval of time in scale TAU elapsed since 01 January 2000, 12 hours TAI, in seconds
- t-t0 -- The interval of time in scale TAI elapsed since the reference epoch for the expansion defined in the E-record, in seconds.

Format of a A-record

```
Field 1:1 A1
                -- Record ID: letter A (decimal code 65).
field 2:3 a2
                 -- Delimiters: blanks.
Field 4:11 A8
                  -- 8-letter long harmonic name. The harmonic name
                  must be defined in a preceding H-record.
field 12:13 a2
                  -- Delimiters: blanks.
Field 14:25 F12.0 -- PM_amp_cos -- cosine amplitude of the small angle
                    of polar motion. Units: prad.
                 -- delimiter: blank.
field 26:26 a1
Field 27:38 F12.0 -- PM_amp_sin -- sine amplitude of the small angle
                    of polar motion. Units: prad.
field 39:39 a2 -- Delimiters: blanks.
Field 41:52 F12.0 -- E3_amp_cos -- cosine amplitude of the small angle
                   of the Earth rotation around axis 3. Units: prad.
field 53:53 a1
                  -- Delimiter: blank.
Field 54:65 F12.0 -- E3_amp_sin -- sine amplitude of the small angle
                     of the Earth rotation around axis 3. Units: prad.
```

6) A velocity record specifies rates of changes of the amplitudes of the harmonic of the variation of the Earth orientation: in phase polar motion (PM_vel_cos), out_of_phase polar motion (PM_vel_sin), in_phase rotation around E3 axis (E3_vel_cos), out_of_phase rotation around E3 axis (E3_vel_sin). A file cannot contain more than one velocity record for the same harmonic. The harmonic referred in an velocity record must be defined in the preceding harmonic definition record.

Format of a V-record

```
Field 1:1 A1 -- Record ID: letter A (decimal code 65).

field 2:3 a2 -- Delimiters: blanks.

Field 4:11 A8 -- 8-letter long harmonic name. The harmonic name must be defined in a preceding H-record.

field 12:13 a2 -- Delimiters: blanks.

Field 14:25 F12.0 -- PM_vel_cos -- rate of change of the cosine amplitude
```

of the small angle of polar motion.

Units: 10^{-21} rad/sec. field 26:26 a1 -- delimiter: blank.

Field 27:38 F12.0 -- PM_amp_sin -- rate of change of the sine amplitude of the small angle of polar motion.

Units: 10^{-21} rad/sec.

field 39:40 a2 -- Delimiters: blanks.

Field 41:52 F12.0 -- E3_amp_cos -- rate of change of the cosine amplitude of the small angle of the Earth rotation around axis 3. Units: 10^{-21} rad/sec.

field 53:53 a1 -- Delimiter: blank.

Field 54:65 F12.0 -- E3_amp_sin -- rate of change of the sine amplitude of the small angle of the Earth rotation around axis 3. Units: 10^{-21} rad/sec.

7) An amplitude error record specifies the harmonic and 4 formal uncertainties of amplitudes of the variation of the Earth orientation: the error of the in_phase polar motion (PM_amp_cos_err), the error of the out_of_phase polar motion (PM_amp_sin_err), the error of the in_phase rotation around E3 axis (E3_amp_cos_err), and the error of the out_of_phase rotation around E3 axis (E3 amp sin). A file cannot contain more than one amplitude error record for the same harmonic. If information about errors of the amplitude of the harmonic is unavailable, the record can be omitted. The harmonic referred in an amplitude error record must be defined in the preceding harmonic definition record.

Format of a S-record

-- Record ID: letter A (decimal code 83). Field 1:1 A1

field 2:3 a2 -- Delimiters: blanks.

Field 4:11 A8 -- 8-letter long harmonic name. The harmonic name must be defined in a preceding H-record.

field 12:13 a2 -- Delimiters: blanks.

Field 15:26 F12.1 -- PM_amp_cos_err -- cosine amplitude of the small

angle of polar motion. Units: prad. -- delimiter: blank.

field 27:27 a1 Field 28:39 F12.1 -- PM_amp_sin_err -- sine amplitude of the small

polar motion. Units: prad.

-- Delimiters: blanks. field 40:41 a2

Field 42:53 F12.1 -- E3_amp_cos_err -- cosine amplitude of the small angle of the Earth rotation around axis 3. Units: prad.

field 54:54 a1 -- Delimiter: blank.

Field 55:66 F12.1 -- E3_amp_sin_err -- sine amplitude of the small angle of the Earth rotation around axis 3. Units: prad.

8) A velocity error record specifies errors of rates of changes of the amplitudes of the harmonic of the variation of the Earth orientation: the in_phase polar motion (PM_vel_cos_err), the out_of_phase polar motion (PM_vel_sin_err), the in_phase rotation around E3 axis (E3_vel_cos_err), and the out_of_phase rotation around E3 axis (E3_vel_sin_err). A file cannot contain more than one velocity record for the same harmonic. If information about errors of the rate of change of amplitude of the harmonic is unavailable, the record can be omitted. The harmonic referred in an velocity record must be defined in the preceding harmonic definition record.

Format of a R-record

```
Field 1:1 A1
                  -- Record ID: letter R (decimal code 82).
```

field 2:3 a2 -- Delimiters: blanks.

Field 4:11 A8 -- 8-letter long harmonic name. The harmonic name must be defined in a preceding H-record.

field 12:13 a2 -- Delimiters: blanks.

Field 14:25 F12.0 -- PM_vel_cos_err -- error of the rate of change of the cosine amplitude of the small angle of polar motion. Units: 10^{-21} rad/sec.

-- delimiter: blank. field 26:26 a1

Field 27:38 F12.0 -- PM_amp_sin_err -- error of the rate of change of the sine amplitude of the small angle of polar motion. Units: 10^{-21} rad/sec.

field 39:40 a2 -- Delimiters: blanks.

Field 41:52 F12.0 -- E3_amp_cos_err -- error of rate of change of the cosine amplitude of the small angle of the Earth rotation around axis 3.

```
\label{limits: 10^{-21} rad/sec.}  field 53:53 a1 -- Delimiter: blank.
```

Field 54:65 F12.0 -- E3_amp_sin_err -- error of rate of change of the sine amplitude of the small angle of the Earth rotation around axis 3. Units: 10^{-21} rad/sec.

9) Trailer record is the same as the header record.

2.14 EOP_SERIES

Label: EOP-MOD Ver 2.0

Purpose: Define the time series of the Earth orientation parameters,

such as pole coordinates and UT1-TAI angle.

Type: Ascii, records of fixed length
Example: \$(VTD_ROOT)/share/vlbi_apr.erp

NB: 1) All records of this file must have length 76 bytes

2) non-standard units are used

Comment character: #
Header record format:

Filed 1:15 Label: EOP-MOD Ver 2.0

Field 18:26 F9.1 Julian date (TAI) of the first data record

Field 28:33 F6.2 Time step in days

Field 34:39 I6 The number of records Field 42:48 A7 Meaning of the 4th column

Field 42:48 A7 Meaning of the 4th column Field 52:56 A5 Meaning is lost

Field 52:56 A5 Meaning is lost Field 57:76 A18 Delimiter: blank

Data record format:

Filed 1:9 F9.1 Julian date (TAI)

Filed 11:17 F7.4 X pole coordinate. Units: 0.1 arcsec

Filed 19:25 F7.4 Y pole coordinate. Units: 0.1 arcsec

Filed 27:35 I9 $\,$ UT1-TAI. Units: microsecond of time Filed 36:76 A41 $\,$ some information not used by VTD.

Its meaning is forgotten

2.15 POSVAR_MOD: (HARMONIC_MODEL)

Label: HARPOS Format version of 2002.12.12 Purpose: Describes site displacements which can

be represented by a finite set of harmonic components.

Type: Ascii

Example: \$(VTD_ROOT)/share/2007b_oclo.hps

A file in HARPOS format consists of records of variable length in ASCII coding. The records are separated by a character with decimal code 13. The records of the following types are supported:

- 1) Header record;
- 2) Harmonic definition records;
- Site definition records;
- 4) Displacement definition records;
- 5) Trailer record.

Records which start from # character are considered as comments.

Each valid file in HARPOS format has the first header record, one or more harmonic definition records, one or more site definition records and one or more displacement definition records. The last record is a trailer record. All harmonic definition records should precede site definition records. All site definition records should precede displacement definition records.

Records format:

1) A header record contains the string "HARPOS Format version of 2002.12.12"

The header record allows to distinguish the valid file in the HARPOS format from files in other formats.

2) A harmonic definition record defines the argument of the harmonic in the form $\{phase + freq*(t-t0) + 1/2*accel*(t-t0)**2\}$ where t is time in TDT time scale and t0 is the reference epoch J2000.0, 01 January 2000, 12 hours TDT. The file cannot contain more than one definition of the same harmonic.

Format of an H-record:

```
-- Records ID: letter H (decimal code 72).
```

Field 1:1 A1 field 2:3 a2 -- delimiters: blanks.

Field 4:11 A8 -- 8-letter long harmonic name. May contain any characters with decimal codes 32-255, but blanks are allowed only at the end of the harmonic name. This field should not necessarily have a special meaning. Parsing software should not try to interpret this name.

field 12:13 a2 -- delimiters: blanks.

Field 14:26 D13.6 -- Phase of the harmonic in float format.

Units: rad.

field 27:28 a2 -- delimiters: blanks.

Field 29:47 D19.12 -- Frequency of the harmonic in float format.

Units: rad/sec.

field 48:49 a2 -- delimiters: blanks.

Field 50:59 D10.3 -- Acceleration of the harmonic in float format.

Units: rad/sec**2.

field 60:80 a21 -- delimiters: blanks.

3) A site definition record defines the site identifier and site coordinates in a crust-fixed reference frame. The file cannot contain more than one definition of the same site.

Format of an S-record:

```
-- Record ID. Should be letter S (decimal code 83)
```

-- Delimiters: blanks.

Field 1:1 A1 Field 2:3 A2 Field 4:11 A8 -- 8-letter long site identifier. May contain any characters with decimal codes 32-255, but blanks are allowed only at the end of the site identifier. This site identifier should be unique among S-records. This field should not necessarily have a special meaning. Parsing

software should not try to interpret it.

field 12:13 a2 -- delimiters: blanks.

Field 14:26 F13.4 -- Site X coordinate in a crust fixed reference

frame. Units: meters.

field 27:27 a1 -- delimiters: blanks.

Field 28:40 F13.4 -- Site Y coordinate in a crust fixed reference

frame. Units: meters.

field 41:41 a1 -- delimiters: blanks.

Field 42:54 F13.4 -- Site Z coordinate in a crust fixed reference

frame. Units: meters. field 55:56 a2 -- delimiters: blanks.

Field 57:64 F8.4 -- Site geocentric latitude, positive to north,

in degrees. This field is for information only.

Parsing software MUST ignore it.

field 65:65 a1 -- delimiters: blanks.

Field 66:73 F8.4 -- Site longitude, positive towards east,

in degrees. This field is for information only.

Parsing software MUST ignore it.

field 74:74 a1 -- delimiters: blanks.

Field 75:80 F6.1 -- Site height above the reference ellipsoid in meters. This field is for information only.

Parsing software MUST ignore it.

4) A data record specifies the site, the harmonic and 6 amplitudes of displacements: Up cosine, East cosine, North cosine, Up sine, East sine. North sine. A file cannot contain more than one data record for the same harmonic, the same site. The site and the harmonic referred in a data record must be defined in the preceding site and harmonic definition records.

Notation "Up cosine" and "Up sine" amplitudes of the displacement means that the radial component of the topocentric vector of the displacement, which is parallel to the vector from the geocenter to the site, depends on time in the following way:

 $D_up = Ampl_cos_up * cos {phase + freq*(t-t0) + 1/2*accel*(t-t0)**2} +$

```
Ampl\_sin\_up * sin \{phase + freq*(t-t0) + 1/2*accel*(t-t0)**2\}
```

Analogously, "East cosine", "East sine" amplitudes define time dependence of the east component of the displacement vector, and "North cosine", "North sine" define time dependence of the north

Format of a D-record:

```
Field 1:1 A1
                   -- Record ID: letter D (decimal code 68).
                -- delimiters: blanks.
-- 8-letter long harmonic name. The harmonic name
field 2:3 a2
Field 4:11 A8
                    must be defined in a preceding H-record.
field 12:13 a2
                   -- delimiters: blanks.
Field 14:21 A8
                  -- 8-letter long site identifier. The site
                      identifier must be defined in a preceding
                      S-record.
field 22:24 a3
                   -- delimiters: blanks.
Field 25:32 F8.5 -- Cosine amplitude of the Up component of the
                      displacement vector. Up direction is along the
                      vector from the geocenter to the site.
                    Units: meters.
field 33:33 A1
                   -- delimiter: blank.
Field 34:41 F8.5 -- Cosine amplitude of the East component of the
                      displacement vector. Units: meters.
field 42:42 a1
                   -- delimiter: blank.
Field 43:50 F8.5 -- Cosine amplitude of the North component of the
                     displacement vector. Units: meters.
field 51:53 a3
                   -- delimiter: blanks.
Field 54:61 F8.5 -- Sine amplitude of the Up component of the
                      displacement vector. Up direction is along the
                      vector from the geocenter to the site.
                      Units: meters.
field 62:62 a1
                   -- delimiter: blank.
Field 63:70 F8.5 -- Sine amplitude of the East component of the
                    displacement vector. Units: meters.
field 71:71 a1
                   -- delimiter: blank.
Field 72:79 F8.5 -- Sine amplitude of the North component of the
                     displacement vector Units: meters
                   -- delimiter: blank.
field 80:80 a1
```

5) Trailer record is the same as the header record.

2.16 POSVAR_MOD: (TIME_SERIES)

Label: BINDISP

Purpose: describing time series of site position

variations. A file in this format contains three

components of the

displacement vector of a specific site equally sampled

within a certain time range.

Binary, little endian Type:

A file consists of records of fixed length. Record length is 8 bytes. A file has 44 header records and at least one data record which follows header records.

Header record 1:

Field 1:8 A8 -- Unix magic record. Should be "BINDISP" for a valid file

Header record 2:

Field 1:4 I*4 -- Integer modified Julian of the format

revision date.

Field 5:5 A1 -- Identifier for used binary integer format.

Supported identifiers: B -- big endian format

L -- little endian format

```
Supported identifiers:
                   I -- IEEE 754/854 format.
                   D -- Dec format.
Field 7:8 I*2 -- Reserved. filled with binary value 0.
Header record 3:
Field 1:8 A8 -- 8-letter long site identifier. May contain
                   any characters with decimal codes 32-255, but
                   blanks are allowed only at the end of the site
                   identifier. This field should not necessarily
                   have a special meaning. Parsing software should
                   not try to interpret it.
Header record 4:
Field 1:4 \quad I*4 \quad \mbox{--} The total number of data records.
Field 5:8 R*4 -- Sampling interval in seconds: the interval
                   between two consecutive epochs.
Header record 5:
Field 1:8 R*8 -- X site coordinate in a crust fixed reference
                   frame. Units: meter.
Header record 6:
Field 1:8 R*8 -- Y site coordinate in a crust fixed reference
                   frame. Units: meter.
Header record 7:
Field 1:8 R*8 -- Z site coordinate in a crust fixed reference
                   frame. Units: meter.
Header record 8:
Field 1:4 I*4 -- Integer modified Julian data at the midnight
                  of the time epoch of the first data record.
Field 5:8 R*4 -- Time in TDT elapsed from the midnight of
                   the time epoch of the first data record,
                   in seconds.
Header record 9:
Field 1:8 C*8 -- Model type
Header record 10:
Field 1:8 C*8 -- Model name
Header record 10:
Field 1:8 C*8 -- Model version
Header records 11 to 44:
Field 1:8 C*8 -- Comment
Data record:
Displacement is endcoded as a sum of the base displacement and
extension. Total extension is computed as
```

total = 1.0D-5 * base + 0.32D0 * sign(base)*extension

Field 6:6 A1 -- Identifier for used binary float format.

The total displacement can be in a range [-5.44, 5.44] meters.

- Field 1:2 I*2 -- 1.0D-5 singed base X coordinate of site displacement for a given epoch in a crust-fixed reference system.

 Units: 1.D-5 meter.
- Field 3:4 I*2 -- base Y coordinate of site displacement without extension for a given epoch in a crust-fixed reference system.

 Units: 1.D-5 meter.
- Field 5:6 I*2 -- base Z coordinate of site displacement without extension for a given epoch in a crust-fixed reference system.

 Units: 1.D-5 meter.
- Field 7:8 I*2 -- Bit fields of extension. The word is split into four bit fields of 4 bits each.
 bits 0:3 -- reserved
 bits 4:7 -- unsigned extension for X coordinate
 bits 8:11 -- unsigned extension for Y coordinate
 bits 12:15 -- unsigned extension for Z coordinate

Comments:

- Data records follow in chronological order. No records can be missed. The epoch of the J+1 th record is the epoch of the J -th record plus the sampling interval. The epoch of the K-th physical record of the file is (MJD,TDT) + (K-9)*Sample_interval. Physical records are counted from 1.
- Maximal displacements in site positions which can be described in this file cannot exceed by modulo 5.4 meters.

2.17 POSVAR_MOD: (B_SPLINE)

Label: BSPPOS Format version of 2007.10.30"

Purpose: To describe site displacements which can be represented as the sum of the polynomial of the first degree and an expansion with the B-spline basis. The expansion is defined on a expanded non-descending sequence of knots. The first and the last knot has multiplicity 1-degree, other knots are represented as simple. The sequence may have several consecutive knots with equal epochs, except the first and the last. The number of knots with the same epochs should not exceed the degree of the B-spline basis. The expanded sequence of knots has indexes

1-degree, 1-degree+1, ... 0, 1, 2, ... N, N+1, N+2, ... N+degree, i.e. in the expanded sequence the first and the last knot are split into the set of knots with the number of elements equal to the degree.

BSPPOS file provides the number of knots, the degree of the B-spline basis, apriori site position, time epochs of knots, estimates of B-spline coefficients, global site position, and global site velocity.

A file in BSPPOS format consists of records of variable length in ASCII coding. The records are separated by a character with decimal code 13. The records of the following types are supported:

- 1) Header record
- 2) Solution identifier
- Solution date
- 4) Record that specifies the total number of sites
- 5) Site definition record
- 6) Record that specifies the B-spline degree $\,$
- 7) Record that specifies the number of knots for spline for this site
- 8) Record that specifies the reference epoch for site positions $\ \ \,$
- 9) Record that specifies position at reference epoch
- 10) Record that specifies site velocity
- 11) Record that specifies epoch of the spline
- 12) Record that specifies B-spline coefficients
- 13) Record that specifies elements of the covariance matrix of B-spline coefficients (optional)
- 14) Trailer record

The records should be placed in this order. Records 5-10 are repeated for each site, records 11-12 are repeated for each spline knot and each site

Records which start from # character are considered as comments.

1. Header record

A header record contains the string "BSPPOS Format version of 2007.10.30"

The header record allows to distinguish the valid file in the BSPPOS format from files in other formats.

2. Solution identifier

```
Field 1:7 A7 Field ID: SOL_ID:
Field 8:10 a3 Delimiter (blank)
Field 11:43 A32 Text identifying the solution
```

3. Solution date

```
Field 1:9 A9 Field ID: SOL_DATE:
Field 10:10 a1 Delimiter (blank)
Field 11:29 A19 Date of the solution in ISO format
```

4. Record that specifies the total number of sites

```
Field 1:6 A6 Field ID: N_STA:
Field 7:7 a1 Delimiter (blank)
Field 8:11 I4 The total number of sites
```

5. Site definition record

```
Field 1:2 A2 Field ID: S:
Field 3:3 a3 Site ID: an arbitrary sequence of letters.
                  NB: parsing software SHOULD NOT ATTEMPT to interpret
Field 8:11 I4
                  The total number of sites
Field 12:13 a2 Delimiter (blanks)
Field 14:26 F13.5 X-coordinate of the site in the crust fixed coordinate system
Field 27:27 a1 Delimiter (blank)
Field 28:40 F13.5 Y-coordinate of the site in the crust fixed coordinate system
Field 41:41 a1 Delimiter (blank)
Field 42:54 F13.5 Z-coordinate of the site in the crust fixed coordinate system
Field 12:13 a2
                  Delimiter (blanks)
Field 57:64 F8.4 Site geocentric latitude.
Field 65:65 a1 Delimiter (blank)
Field 66:73 F8.4 Site geocentric longitude positive to East in [0,360]
Field 74:74 al Delimiter (blank)
Field 75:80 F5.1 Site height above the reference ellipsoid
```

6. Record that specifies the B-spline degree

```
Field 1:6
                 Field ID: L_DEG:
Field 7:7
                  Delimiter (blank)
            a1
Field 8:11 I4
                 Spline degree
Field 12:18 a7
Field 19:22 I4
                   Delimiter STA:
                 Site index. The index of the site definition
                   record for this site, counted from 1
Field 23:24 a2
                   Delimiter (blanks)
Field 25:32 A8
                   Site name specified in the preceding site definition
                   record
```

7. Record that specifies the number of knots for spline for this site

```
Field ID: N NOD:
Field 1:6
            A6
Field 7:7
                 Delimiter (blank)
           a1
Field 8:11 I4
                  The number of knots for this site
Field 12:18 a7 Delimiter STA:
Field 19:22 I4
                  Site index. The index of the site definition
                  record for this site, counted from 1
Field 23:24 a2
                  Delimiter (blanks)
Field 25:32 A8
                 Site name specified in the preceding site definition
```

8. Record that specifies the reference epoch for site positions

```
Field 1:6 A6 Field ID: R_EPC: Field 7:18 a12 Delimiter Field 19:22 I4 Site index. The i
                                       STA:
                       Site index. The index of the site definition
                       record for this site, counted from 1
   Field 23:24 a2
                       Delimiter (blanks)
    Field 25:32 A8
                       Site name specified in the preceding site definition
                       record
   Field 33:34 a2
                       Delimiter (blanks)
   Field 35:57 A23 Reference epoch for site positions in TAI in ISO format.
9. Record that specifies position at reference epoch
   Field 1:6 A6 Field ID:
Field 7:18 a12 Delimiter
                       Field ID: P_EST:
                                        STA ·
   Field 19:22 I4
                       Site index. The index of the site definition
                       record for this site, counted from 1
   Field 23:24 a2
                       Delimiter (blanks)
   Field 25:32 A8 Site name specified in the preceding site definition
                       record
   Field 33:34 a2
                      Delimiter (blanks)
   Field 35:48 F14.6 X component of site position at the reference epoch in meters
   Field 49:49 a1 Delimiter (blanks)
   Field 50:63 F14.6 Y component of site position at the reference epoch in meters
   Field 64:64
                      Delimiter (blanks)
                 a1
   Field 65:78 F14.6 Z component of site position at the reference epoch in meters
10. Record that specifies site velocity
   Field 1:6
                A6 Field ID: P EST:
   Field 7:18 a12 Delimiter
Field 19:22 I4 Site index.
                                        STA:
                      Site index. The index of the site definition
                       record for this site, counted from \ensuremath{\text{1}}
   Field 23:24 a2
                       Delimiter (blanks)
   Field 25:32 A8 Site name specified in the preceding site definition
                       record
   Field 33:34 a2
                       Delimiter (blanks)
   Field 35:48 F14.6 X component of site velocity in m/s
   Field 49:49 a1 Delimiter (blanks)
   Field 50:63 F14.6 Y component of site velocity in m/s
   Field 64:64 al Delimiter (blanks)
   Field 65:78 F14.6 Z component of site velocity in m/s
11. Record that specifies epoch of the spline
   Field 1:6
                 A6
                      Field ID: EPOCH:
   Field 7:7
                 a1
                       Delimiter (blank)
   Field 8:11 I4
                       The knot index starting from 1-L_DEG
   Field 12:18 a7
                       Delimiter STA:
   Field 19:22 I4
                     Site index. The index of the site definition
                       record for this site, counted from 1
   Field 23:24 a2
                       Delimiter (blanks)
   Field 25:32 A8
                      Site name specified in the preceding site definition
                       record
   Field 35:57 A23 Epoch of the knot in TAI in ISO fort mat.
12. Record that specifies B-spline coefficients
   Field 1:6
                A6
                      Field ID: EPOCH:
   Field 7:7
                       Delimiter (blank)
                 a1
   Field 8:11 I4
                       The knot index starting from 1-L_DEG
   Field 12:18 a7
                      Delimiter STA:
                     Site index. The index of the site definition
   Field 19:22 I4
                       record for this site, counted from \ensuremath{\text{1}}
   Field 23:24 a2
                       Delimiter (blanks)
   Field 25:32 A8
                       Site name specified in the preceding site definition
                       record
   Field 33:35 a3
                       Delimiter (blanks)
   Field 36:48 F13.6 B-spline coefficient for X component of position of this site, this knot
   Field 49:49
                al Delimiter (blanks)
   Field 50:62 F13.6 B-spline coefficient for Y component of position of this site, this knot
   Field 63:63 a1 Delimiter (blanks)
   Field 64:76 F13.6 B-spline coefficient for Z component of position of this site, this knot
13. Record that specifies elements of the covariance matrix of B-spline
    coefficients (optional). Covariance matrix is a 4-dimensional array
    in the crust-fixed terrestrial coordinate system. The first two
    dimensions run through the knot indexes + global position + global
   velocity. The second two dimensions, the 3rd and the 4th, run through
```

components of the coordinate vectors: X, Y, Z.

Field 1:6	A6	Field ID: EPOCH:
Field 7:18	a12	Delimiter (blank)
Field 12:18	a7	Delimiter STA:
Field 19:22	14	Site index. The index of the site definition
		record for this site, counted from 1
Field 23:24	a2	Delimiter (blanks)
Field 25:32	A8	Site name specified in the preceding site definition
		record
Field 33:41	a9	Delimiters
Field 43:43	I1	The first component of the displacement vector in the
		terrestrial coordinate system. Components runs as
		X, Y, and Z.
Field 49:49	a1	Delimiter (blanks)
Field 50:52	a3	Delimiters
Field 53:56	14	The first covariance element index. Index starts from
		1-L_DEG and runs through N_NOD+L_DEG-1. The element
		with index N_NOD+L_DEG+1 corresponds to the global
		position, the element with index N_NOD+L_DEG corresponds
		to the global velocity, other indexes correspond to knot
		index.
Field 57:65	a9	Delimiters
Field 66:66	I1	The second component of the displacement vector in the
		terrestrial coordinate system. Components runs as
		X, Y, and Z.
Field 67:75	a9	Delimiters
Field 76:79	14	The second covariance element index. Index starts from
		1-L_DEG and runs through N_NOD+L_DEG-1. The element
		with index N_NOD+L_DEG+1 corresponds to the global
		position, the element with index N_NOD+L_DEG corresponds
		to the global velocity, other indexes correspond to knot
		index.
Field 80:86		Delimiters
Field 87:99	D13.6	The element of the covariance matrix

14. Trailer record

The same as the header record, string: "BSPPOS Format version of 2007.10.30"

2.18 ANTENNA_DEFORMATIONS_FILE

Label: \$ Antenna Gravity Deformation File Format Version of 2008.04.25 Purpose: Contains the table of the antenna focus line as a function

of elevation angle.

Type: ascii

Example: \$(VTD_ROOT)/share/agd.dat

Comment character: # Data record format:

1:5 A3 Delimiter: "AGD 6:13 A8 IVS station name Delimiter: "AGD " 14:15 A2 Delimiter: blank 16:22 A7 Focus type 23:24 A2 Delimiter: blank

25:28 F4.1 Elevation (in deg) 29:30 A2 Delimiter: blank

31:37 F7.3 Focus length change (in mm)

2.19 SLANTED PATH DELAY BIAS FILE

Label: SPD_3D_BIAS Format version of 2010.05.18 Purpose: Determine empirical bias and scale factor for the slanted path delay model. The non-hydrostatic component of the Slanted path delay is to be multiplied by the scale and added the bias.

Example: n/a

Comment character: # Data record format:

A file in the SPD_ASCII format consists of records of variable length in ASCII coding. The records are separated by a character with decimal code 13. The records are grouped into sections. Sections follow in this order:

- 1) N-record -- defines the number of records in further other sections.
- 2) S-record -- defines name and coordinates of stations for which path delay have been computed.
- 3) B-record -- defines bias and scaling factor

Format of an N-record:

```
Field 1:1 A1 -- Record ID: letter "N".
field 2:3 a2 delimiter: blank.
Field 4:7 I4 -- Number of M-records in the file. i.e. brief algorithm
                    description and options used during computations.
field 8:9 a2
                     delimiter: blank.
field 10:13 I4 -- Number of I-records in the file, i.e. the number of
                     lines with a brief description of the numeric
                     model of the atmosphere used during computation.
field 14:15 a2
                     delimiter: blank.
field 16:21 I6 -- Number of S-records in the file, i.e. the number
                     of stations.
field 22:23 a2
                     delimiter: blank.
field 24:27 I4 -- Number of E-records in the file, i.e. the number
                     elevations in the grid.
field 28:29 a2
                     delimiter: blank.
                 -- Number of A-records in the file, i.e. the number
field 30:33 I4
                     azimuths in the grid.
```

Format of an S-record:

```
Field 1:1 A1 -- Record ID: letter "S".
field 2:3 a2
                   delimiter: blanks.
                -- station index
field 4:9 I6
field 10:11 a2
                   delimiter: blanks.
Field 12:19 A8
                 -- 8-letter long site identifier. May contain
                     any characters with decimal codes 32-255, but
                     blanks are allowed only at the end of the site
                     identifier. This site identifier should be unique
                     among S-records. This field should not
                     necessarily have a special meaning. Parsing
                     software SHOULD NOT TRY TO INTERPRET it.
field 20:21 a2
                     delimiter: blanks.
Field 22:33 F12.3 -- X site coordinate in a crust fixed reference
                     frame. Units: meters.
field 34:34 a1
                     delimiter: blank.
Field 35:46 F13.4 -- Y site coordinate in a crust fixed reference
                     frame. Units: meters.
field 47:47 a1
                     delimiter: blank.
Field 48:59 F13.4 -- Z site coordinate in a crust fixed reference
                     frame. Units: meters.
field 60:61 a2
                     delimiter: blanks.
Field 62:69 F8.4 -- Site geocentric latitude, positive to north,
                     in degrees. This field is for information only.
                     Parsing software MUST ignore it.
field 70:70 a1
                     delimiter: blank.
Field 71:78 F8.4 -- Site longitude, positive towards east,
                     in degrees. This field is for information only.
                     Parsing software MUST ignore it.
field 79:80 a2
                     delimiter: blank.
Field 81:86 F6.1 -- Site height above the reference ellipsoid in
                     meters. This field is for information only.
                     Parsing software MUST ignore it.
field 87:87 a1
                     delimiter: blank.
Field 88:93 F6.1 -- Site height above the geoid in meters. This field
                     is for information only.
                     Parsing software MUST ignore it.
```

Format of an B-record:

```
Field 1:1 A1 -- Record ID: letter "B". field 2:11 a10 -- delimiter: blank
Field 12:19 A8 -- 8-letter long site identifier.
field 20:24 a5
                  -- delimiter: blank
Field 25:34 D10.3 -- Slanted path delay offset. Units: seconds
field 35:37 a3 -- delimiter: blank
Field 38:44 F7.4 -- Slanted path delay scale factor
                                                     2.20 EXTERNAL DELAY DIR
Label: spd_3d_bin 1.0 version of 2009.01.07 LE
Purpose: Contains results of computing slanted path delay of
         radio wave propagation through the 3D, continuous,
         heterogeneous atmosphere. The path delay is defined as
         a difference in the propagation time between the emitter
         and the receiver through the atmosphere and the propagation
         between these two points along the geodetic line in
         vacuum. The path delay is computed for a set of stations for
         a certain epoch at a regular grid of azimuths and elevations.
         The grid is equidistant at azimuths and non-equidistant at
         elevation angles. The values of path delays computed on
         a grid can be used for computing coefficients of the
         interpolating functions that enable us to compute
         the path delay in an arbitrary direction.
Example: http://astrogeo.org/spd_data/spd_6h_bin
Type:
         Binary, little endian.
File in spd_3d_bin format consists of records of 7 types.
The type of each record is determined by the first
8-characters long field prefix. The records follow in this order:
LAB_REC -- Defines offsets, sizes and the number of other records
TIM_REC -- Defines the start time, stop time of DEL records
           and the time step
STA REC -- Defines station coordinates
\ensuremath{\mathtt{MOD\_REC}} -- Defines the slanted path model type and the model description
{\tt MET\_REC} \ {\tt --} \ {\tt Defines} \ {\tt description} \ {\tt of} \ {\tt the} \ {\tt numerical} \ {\tt weather} \ {\tt model} \ {\tt used}
           for computation
\ensuremath{\mathsf{ELV\_REC}} -- Defines the elevation axis for the 2D grid of
           path delays through the neutral atmosphere
AZM_REC -- Defines the azimuth axis for the 2D grid of
           path delays through the neutral atmosphere
DEL_REC -- Defines the surface pressure surface temperature
           and the 2D grid of path delay through the neutral atmosphere.
The file contains only one record of the first seven types and usually
more than one record of DEL_REC. Each DEL_REC corresponds to one time
epoch. The time epochs follow each other in chronological order with
the same time step, without gaps. The time epoch of a specific DEL_REC
is determined by its index in the file, time of the first epoch, and
the time step.
Description of individual records:
LAB REC
       CHARACTER PREF*8
                              ! prefix: LAB REC
       INTEGER*8 LEN
                              ! length of the LAB_REC record
       CHARACTER FMT_LAB*40 ! Format label
       INTEGER*8 OFF_TIM
                            ! Offset of the TIM record in bytes wrt the file beginning
       INTEGER*8 OFF_STA
                              ! Offset of the STA record in bytes wrt the file beginning
       INTEGER*8 OFF_MOD
                             ! Offset of the MOD record in bytes wrt the file beginning
       INTEGER*8 OFF_MET
                            ! Offset of the MET record in bytes wrt the file beginning
       INTEGER*8 OFF_ELV
                             ! Offset of the ELV record in bytes wrt the file beginning
       INTEGER*8 OFF_AZM
                             ! Offset of the AZM record in bytes wrt the file beginning
       INTEGER*8 OFF DEL
                             ! Offset of the first TIM record in bytes wrt the file beginning
       INTEGER*8 LEN_TIM
                             ! Length of the TIM record in bytes
       INTEGER*8 LEN_STA
                             ! Length of the STA record in bytes
       INTEGER*8 LEN_MOD
```

! Length of the MOD record in bytes

! Length of the MET record in bytes

! Length of the ELV record in bytes ! Length of the AZM record in bytes

! Length of the DEL record in bytes

TIM REC

CHARACTER PREF*8 ! prefix: TIM_REC

INTEGER*4 TOT_NUM_DEL ! The number of DEL records

INTEGER*8 LEN_MET

INTEGER*8 LEN_ELV

INTEGER*8 LEN_AZM INTEGER*8 LEN_DEL

```
TNTEGER*8 NREC
                           ! The number of time epochs the file contains
                           INTEGER*4 MJD_BEG
       INTEGER*4 MJD END
      REAL*8
                 TAI BEG
                            ! TAI for the first epoch. Units: seconds
      REAL*8
                 TAI_END
                           ! TAI for the last epoch. Units: seconds
                 TIM_STEP
                           ! Time step. Units: seconds
      REAL*8
STA_REC
      CHARACTER PREF*8
                            ! prefix: STA REC
      CHARACTER NAME*8
                            ! Station name. NB: the station name does NOT necessarily
                            ! conforms any convention. It may be an arbitrary combination
                            ! of characters. Parser software should NOT assign any meaning
                            ! to this field
      REAL*8
                 COO_CFS(3) ! Station coordinates in the crust-fixed coordinate system.
                            ! Units: meters
      REAL*8
                 PHI_GCN
                           ! Station geocentric latitude. Units: radians
      REAL*8
                 PHI GDT
                           ! Station geodetic latitude. Units: radians
      REAL*8
                 HEI_ELL
                            ! Station height above the reference ellipsoid. Units: meters
      REAL*8
                 HEI GEOID ! Station height above the geoid. Units: meters
MOD REC
      CHARACTER PREF*8
                            ! prefix: MOD_REC
      INTEGER*4 N RFR
                            ! Number of components of the model
      CHARACTER SPD_TYPE(3)*8 ! Array of names of the slanted path delay model components.
                                Supported values:
                                          -- Total path delay through the neutral atmosphere
                                           -- Path delay through the hydrostatic component of the atmosphere
                                  non-hydr -- Path delay through the non-hydrostatic component of the atmosphere
                                  undef -- Undefined, not used
                              ! Number of lines with model description
      INTEGER*8 N LINES
                              ! Length of the text with model description in bytes
      INTEGER*8 LEN TEXT
      CHARACTER*1, POINTER :: TEXT(:) ! Text with the model description as a string that contains \n characters
                                     ! of length LEN_TEXT + 1 (the last character is \0)
MET_REC
       CHARACTER PREF*8
                            ! Prefix: STA_REC
       INTEGER*8 N_LINES
                          ! Number of lines with numerical weather model description
      INTEGER*8 LEN_TEXT ! Length of the text with the numerical model description in bytes
      CHARACTER*1, POINTER :: TEXT(:) ! Text with the numerical weather model description as
                                     ! a string that contains \n characters of length
                                     ! LEN_TEXT + 1 (the last character is \0)
ELV REC
      CHARACTER PREF*8
                           ! Prefix: ELV REC
      INTEGER*8 N EL
                           ! The number of elements along the elevation angle axis
      REAL*4.
                 POINTER :: ELEV(:) ! Array of elevation angles. Dimension: N_EL,
                                     ! Units: radians. Array is sorted in decreasing order.
AZM_REC
      CHARACTER PREF*8
      TNTEGER*8 N A7
                           ! The number of elements along the azimuth axis
      REAL*4, POINTER :: AZIM(:) ! Array of azimuth angles. Dimension: N_AZ,
                                     ! Units: radians. Array is sorted in increasing order.
DEL REC
      CHARACTER PREF*8
                 SURF_PRES ! Surface pressure. Units: Pascal
      RFAI *4
      REAL*4
                 SURF_TEMP ! Surface air temperature. Units: Kelvin
      REAL*4,
                 POINTER :: DEL(:,:,:) ! 3D array of slanted path delay components.
                                        ! The first axis runs over elevation angles.
                                        ! Dimension: N_EL defined in ELV_REC
                                        ! The second axis runs over azimuth angles
                                        ! Dimension: N_AZ defined in AZM_REC
                                        ! The third runs over components.
                                        ! Dimension: N_RFR defined in MOD_REC
                                        ! Units: seconds
```

2.21 IONOSPHERE_DATA_FILE

Label: VIONO Little-Endian Format of 2010.05.08

Purpose: Contains the total electron contents of the ionosphere presented at the regular 3D grid with axes: longitude,

latitude, and time.

Type: Binary, little endian

Example: http://astrogeo.org/viono/codg_01.vio

 ${\bf Format\ description:}$

The file in VIONO format consists of the header record and one or more data records.

HEADER:

```
CHARACTER LABEL*48 ! File label
CHARACTER MODEL*16
                    ! Model name
CHARACTER AUTHOR*16 ! Name of the model author
                  ! The number of grid steps along longitude axis
INTEGER*4 NLON
INTEGER*4 NLAT
                    ! The number of grid steps along latitude axis
INTEGER*4 NEPC
                    ! The number of grid steps along time axis
INTEGER*4 MJD_BEG ! MJD at TAI of the first epoch
INTEGER*2 MISSING ! Missing value
INTEGER*2 FILLER(3) ! fillers
REAL*8
          UTC_BEG
                     ! UTC Time tag of the first epoch. Units: seconds
REAL*8
          TIM_STEP
                    ! Time step along the time axis. Units: seconds
REAL*8
          SCALE
                     ! The scaling factor which should be applied to raw TEC values. Units: TECU
          LON_MIN
                     ! Longitude at the beginning of the longitude axis. Units: radians
REAL*8
REAL*8
          LAT_MIN
                    ! Latitude at the beginning of the latitude axis. Units: radians
                    ! Longitude step along the longitude axis. Units: radians
REAL*8
          LON STEP
          LAT STEP
                   ! Latitude step along the latitude axis. Units: radians
REAL*8
REAL*8
          HEIGHT
                    ! Height of the ionosphere. Units: meters
```

DATA RECORD:

```
INTEGER*2, POINTER :: TEC_VAL(:,:) ! TEC values on a 2D longitude/latitude grid.
                                   ! Dimensions: NLON, NLAT. Units: dimensionless
```

TEC_VAL array must by multiplied by SCALE. Units of the results: TECU.

2.22 HYDROSTATIC_MAPPING_FUNCTION/WET_MAPPING_FUNCTION: (MMF)

Label: # MMF_MOD Format of 2008.09.21

Purpose: contains coefficients of polynomials that expand the mean

mapping function in the neutral atmosphere for the set

observing stations. Example: \$(VTD_ROOT)/share/mmf.mod

A file in MMF_EPO format consists of records of variable length in ASCII coding. The records are separated by a character with decimal code 13. The records are grouped into sections. Sections follow in this order:

1) Header record -- the first record should have a signature: TROPO PATH DELAY Format version of 2007.10.04

> The header record allows to distinguish a valid file in the TROPO_PATH_DELAY $% \left(1\right) =\left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left$ in other formats.

2) M-record section

M-record has letter M in the first field. The M record keeps the model identifier.

- 3) N-record section
- 4) S-record section
- 5) D-record section
- 6) Trailer record -- the last record is the same as the header record.

Format of an S-record:

```
Field 1:1 A1 -- Record ID. Should be letter S (decimal code 83). field 2:2 a1 delimiter: blanks.
                   delimiter: blanks.
-- 8-letter long site identifier. May contain
Field 4:11 A8
                        any characters with decimal codes 32-255, but
                       blanks are allowed only at the end of the site
                       identifier. This site identifier should be unique
                        among S-records. This field should not
                       necessarily have a special meaning. Parsing
                       software should not try to interpret it.
field 12:13 a2
                       delimiter: blanks.
Field 14:26 F13.4 -- X site coordinate in a crust fixed reference
```

frame. Units: meters. field 27:27 a1 delimiter: blank. Field 28:40 F13.4 -- Y site coordinate in a crust fixed reference ${\it frame.\ Units:\ meters.}$ field 27:27 a1 delimiter: blank. Field 42:54 F13.4 -- Z site coordinate in a crust fixed reference frame. Units: meters. field 55:56 a2 delimiter: blanks.
Field 57:64 F8.4 -- Site geocentric latitude, positive to north, in degrees. This field is for information only. Parsing software MUST ignore it. field 65:65 a1 delimiter: blank. Field 66:73 F8.4 -- Site longitude, positive towards east, in degrees. This field is for information only. Parsing software MUST ignore it. field 74:74 a1 delimiter: blank. Field 75:80 F6.1 -- Site height above the reference ellipsoid in meters. This field is for information only. Parsing software MUST ignore it.

Questions and comments about this guide should be directed to:

Leonid Petrov (http://astrogeo.org/petrov)

Last update: 2020.03.08