

Carbon-Aware Kubernetes Scheduling with Embodied Emissions: Heuristic vs. MILP Oracle

Nasir Asadov, Vlad C. Coroamă, Martin Roch-Neirey, Marco Zambianco, Silvio Cretti,
and Matthias Finkbeiner

Abstract—Data centers account for over 1% of global electricity use, yet today’s container orchestrators optimize for performance and availability while ignoring carbon emissions that vary across time and location. At the same time, manufacturing (“embodied”) emissions are a first-order contributor that existing schedulers do not model. We ask whether container scheduling can reduce total emissions—operational and embodied—without sacrificing feasibility or incurring prohibitive runtime, and how closely a practical scheduler can approach an optimal oracle. To this end, we formulate a carbon-aware placement problem that integrates operational and embodied emissions under resource and timing constraints; design a fast heuristic that minimizes a comprehensive emissions objective; and implement a global mixed-integer linear program (MILP) as an oracle, alongside a carbon-agnostic Kubernetes-like baseline. All methods are evaluated on identical workloads, horizons, carbon forecasts, and power/embodied models. Across scales, the heuristic substantially reduces emissions while preserving high placement success and practical runtime. In a representative 80-pod evaluation, average per-pod emissions fall from 10.1 to 3.3 g CO₂e (67.5%) relative to the baseline, while tracking the MILP oracle closely (2.6 g). Runtime grows smoothly with pods and nodes and remains in single-digit seconds at our largest settings. These results establish carbon-aware container orchestration as a practical path to lower total emissions and provide a reproducible evaluation protocol for comparing heuristic and optimal approaches in sustainable cloud computing.

Index Terms—Carbon-aware computing, container orchestration, Kubernetes, sustainable computing, green cloud computing, optimization algorithms, mixed integer linear programming, global optimization.



1 INTRODUCTION

Cloud and edge data centers consume vast amounts of electricity [1], [2], and their carbon footprint continues to grow with the proliferation of containerized services and AI workloads. Today’s container orchestration stacks, exemplified by Kubernetes, optimize primarily for resource utilization and service-level objectives while ignoring carbon-intensity signals that vary across regions and time [3]. At the same time, hardware manufacturing (“embodied” carbon) and operational emissions both contribute materially to the environmental impact of running distributed systems [4]. This gap between what orchestrators optimize and what matters environmentally motivates a principled, system-level approach to carbon-aware scheduling, as increasingly demonstrated in industry practice [5] and recent research [6].

However, making container orchestration carbon-aware is nontrivial. Practical schedulers must respect placement feasibility (CPU/RAM), temporal constraints (earliest start and deadlines), and dynamic demand patterns, all while coping with carbon signals that change over time and across regions. Incorporating both operational and embod-

ied carbon into placement decisions further complicates the objective, and any approach must remain computationally tractable at cluster scale. This raises the central research question: can we reduce total carbon emissions through orchestration decisions without sacrificing feasibility or incurring prohibitive precomputation costs?

To this end, we present a carbon-aware orchestration framework that explores a fast heuristic scheduler that greedily minimizes a combined operational+embodied carbon objective under resource and timing constraints. Complementarily, we also explore a global-optimal formulation that solves a mixed-integer program (MILP) with a lexicographic objective (first maximize successful placements, then minimize emissions); and a carbon-agnostic vanilla baseline that mirrors Kubernetes’ resource-only scoring in order to provide upper and lower bounds for our heuristic scheduler [7]. We integrate carbon-intensity forecasts with a co-location-aware power and embodied-carbon model, enforce earliest-start and deadline constraints, and evaluate all approaches in an offline precomputation mode that simulates multi-timeslot scheduling. Our experimental design systematically varies pods and nodes to assess both effectiveness and time complexity, producing apples-to-apples comparisons across algorithms.

We implemented a prototype scheduler and evaluated it offline on controlled workloads across 12–24 hour horizons while varying pod and node scales; in a representative 80-pod run, average per-pod emissions dropped from 10.1 to 3.3 g CO₂e (−67.5%) relative to a vanilla baseline, while end-to-end precompute remained in single-digit seconds.

Our results show that carbon-aware scheduling can substantially reduce emissions while preserving high place-

N. Asadov, V. C. Coroamă, and M. Finkbeiner are with the Department of Environmental Technology, Technische Universität Berlin, Strasse des 17. Juni 135, 10623 Berlin, Germany (e-mail: nasir.asadov@tu-berlin.de; coroama@tu-berlin.de; matthias.finkbeiner@tu-berlin.de).

M. Roch-Neirey is with the Department of Computer Systems Networking and Telecommunications, Polytechnique Montréal, Montreal, Canada (e-mail: martin.roch-neirey@hefr.ch).

M. Zambianco and S. Cretti are with Fondazione Bruno Kessler, 38123 Trento, Italy (e-mail: zambianco@fbk.eu; cretti@fbk.eu).

Corresponding author: Nasir Asadov (e-mail: nasir.asadov@tu-berlin.de).

Manuscript received Month Day, Year; revised Month Day, Year.

ment success and practical runtime. The heuristic approach achieves favorable carbon–performance trade-offs and scales efficiently across realistic pod and node counts, while the MILP establishes an upper bound on achievable carbon reductions at a higher computational cost. Beyond demonstrating feasibility, we provide a reusable evaluation methodology—covering emissions modeling, constraint handling, and time-complexity sweeps—that enables rigorous, reproducible comparisons of carbon-aware orchestration strategies.

The remainder of this paper is organized as follows: Section 2 reviews related work. Section 3 introduces our carbon-aware scheduler, including accounting models (Section 3.1), problem formulation (Section 3.2), a MILP oracle (Section 3.3), and the heuristic algorithm (Section 3.4). Section 4 details the experimental setup. Section 5 presents results. Section 6 discusses implications and limitations. Section 7 concludes with sustainability implications and future work.

2 RELATED WORK

Carbon-aware workload scheduling leverages variations in the carbon intensity of electricity across *time* and *location*. Early research typically focused on *either* shifting workloads in time (temporal shifting) or across geographic locations (spatial shifting), but not both. A recent survey [8] found that most studies prior to 2023 pursued disjunct strategies—either temporal or spatial—rather than integrated approaches. Roughly 65% of works examined only one axis (time or space), though by 2024–2025 a growing share began to consider both. Beyond *when* and *where* workloads run, a complementary line of work examines how to allocate embodied (manufacturing) emissions in evaluating and optimizing schedulers. Standards such as SCI [9] and recent studies propose time- and utilization-aware attribution; we review these approaches and their implications in Subsection 2.3. The subsequent analysis does not aim to be an exhaustive presentation of the related work. Instead, it shows how the research landscape evolved from the early, disjunct spatial or temporal scheduling towards algorithms considering the two and those considering embodied emissions as well. For the early works in particular only a few archetypical examples are shown; a thorough analysis is provided in [8].

2.1 Disjunct Temporal or Spatial Scheduling

Temporal scheduling aims to defer workloads to periods when electricity is cleaner. For example, a carbon-aware Kubernetes scheduler that postpones non-critical batch jobs to predicted low-carbon hours was implemented in [10]. Using historical data to forecast carbon intensity, about 1.3% emissions reduction was achieved compared to default scheduling. Similar findings are reported in [11], indicating that selectively delaying tasks can meaningfully shrink emissions, especially under high renewable penetration and workload slack.

Spatial scheduling, by contrast, exploits geographic diversity in grid carbon intensity. Kubernetes was extended to prioritize data centers with lower carbon costs during job

placement in [12]. More recently, a geo-distributed service manager that routes requests to greener regions while minimizing user-perceived latency was developed in [13]. An approach that schedules serverless functions across cloud regions based on real-time carbon efficiency was proposed in [14]. A model for VM placement across geo-distributed data centers, optimizing for carbon, cost, and energy efficiency jointly, was introduced in [15]. While spatial shifting can yield large gains when regions differ significantly in grid mix, these strategies typically do not consider delaying jobs to greener times, potentially leaving savings untapped.

2.2 Combined Spatio-Temporal Scheduling

Modern spatio-temporal schedulers seek to jointly optimize both *when* and *where* to execute workloads. A Kubernetes-based system that schedules jobs at the right cluster and time using carbon forecasts and QoS constraints was proposed in [16], achieving a 33% carbon footprint reduction compared to QoS-only baselines. A dynamic multi-cloud scheduler that integrates live carbon intensity data to dispatch workloads across cloud regions and time windows was introduced in [17]. A framework that provisions and times workloads for carbon savings, though with less emphasis on real-time orchestration, was presented in [18].

A cautionary note is offered in [19]: many workloads show limited additional benefit from spatio-temporal scheduling beyond what single-axis strategies can achieve. Modeling across 123 regions found that simple heuristics often captured most gains, and joint shifting showed diminishing returns in carbon-stable grids or inflexible workloads.

Despite these caveats, the direction of research clearly favors holistic strategies. Kubernetes has emerged as a key enabling platform, supporting carbon-aware extensions that allow integration of forecasting, regional carbon signals, and multi-cluster placement logic [8], [16]. The fusion of container orchestration and carbon intelligence is enabling practical deployments of spatio-temporal scheduling at scale.

2.3 Embodied Emissions Allocation in Carbon-aware Scheduling

Embodied emissions (manufacturing, logistics, and end-of-life) are increasingly recognized as a first-order term in carbon-aware scheduling, yet are often omitted or uniformly amortized over calendar time. Two broad allocation strategies appear in the literature: (i) lifetime amortization (time-based), and (ii) utilization-aware attribution that splits embodied carbon by actual time-in-use and resource share.

Standards and frameworks: The Software Carbon Intensity (SCI) specification formalizes embodied allocation with

$$M = TE \times TS \times RS,$$

where TE is total device embodied emissions from LCA, TS is the time share (e.g., reserved or in-use fraction of expected lifetime), and RS is the resource share (e.g., vCPU, memory) attributed to the software component [9]. This structure subsumes both simple time-based amortization ($RS = 1$) and finer-grained attribution when detailed utilization or reservations are available.

Recent research: Beyond uniform amortization, several works incorporate embodied carbon into scheduling and

hardware-management decisions: (i) carbon depreciation models that allocate a larger share of embodied carbon to newly provisioned servers and recover idle-time impacts during active use are proposed in [20], showing that traditional accounting can inadvertently favor premature refresh; (ii) aging-aware CPU core management that extends lifetime and reduces embodied-attributed emissions in inference clusters with minimal QoS impact is demonstrated in [21]; (iii) joint embodied+operational objectives with heterogeneity and age in dispatch are formulated in [22], yielding lower total emissions under utilization-aware lifetime models; and (iv) for edge contexts, co-optimizing embodied and operational carbon under intermittent utilization and tight resource constraints is advocated in [23].

Implications for scheduling: (1) Pure calendar-based amortization is appropriate when only coarse information is available, but it obscures idle periods and can inflate per-workload embodied intensity. (2) With utilization traces (e.g., hourly CPU), allocating embodied emissions in proportion to time-in-use and resource share yields more faithful attribution and can shift policies toward reusing capacity, consolidating strategically, or delaying refresh. (3) Accounting for device age and heterogeneity reveals that newer hardware, despite higher performance-per-watt, carries substantial embodied carbon that must be amortized through sustained use before outperforming older devices on total emissions. (4) These effects are amplified at the edge, where intermittency and under-utilization are common.

In this paper, we adopt a refined, SCI-consistent allocation: we attribute embodied emissions using time-in-use and resource share derived from hourly CPU utilization, and we report results alongside a lifetime-amortization baseline to quantify how allocation choice affects scheduler decisions and total carbon efficiency. **[NA: leave the baseline comparison out? would it be relevant to the reader?]**

3 OUR CARBON-AWARE SCHEDULER

As stated from the outset, the aim of our carbon-aware scheduler is to minimize the carbon FP (footprint) for a random collection of nodes and pods. The carbon FP consists of operation and embodied carbon and therefore first and foremost we describe our model that accounts for both in Section 3.1. We continue with problem formulation in Section 3.2 that states the exact scheduling problem under those rules, so every solution faces the same constraints. Section 3.3 adds a MILP oracle—not for deployment, but to show what “best possible” looks like and to validate the model. Finally, after setting the stage with formalities we continue with our heuristic scheduler that captures most of the benefit at practical scale in Section 3.4 to tackle the NP-hard problem just described.

3.1 Carbon Accounting Models

As we need to define the operational carbon footprint before allocating it, we first establish the accounting foundations: the actionable carbon-intensity signal (Section 3.1.1) is multiplied by the energy consumption of the workload. For this purpose we use a node power model that maps pod requests to energy (Section 3.1.2). We elaborate on the actual

TABLE 1
Category-wise average embodied emissions and lifetimes

Hardware Category	Embodied Emissions (kg CO ₂ e)	Lifetime (years)
IoT	27.47	5.20
Smartphone	52.73	3.03
Laptop	231.86	4.13
Server	1230.66	3.87

amortization and allocation of embodied emissions in (Section 3.1.3). These components compose the per-candidate emissions objective used in the problem formulation (Section 3.2).

3.1.1 Operational: Carbon Signals

We use average carbon intensity (ACI) as the actionable signal that varies by region and hour. Forecasts are essential because our scheduler chooses not just where to run a pod, but when, within its earliest-start and deadline window. With a forward view of the grid, it can push flexible jobs toward cleaner hours, steer away from expected spikes, and, when options exist, favor greener regions.

We therefore treat a time- and location-indexed forecast as a shared input to all algorithms. Both the Oracle and our Heuristic use it to score candidate placements; the Heuristic also uses it to quickly rank hours and to break ties consistently across nodes. We align the forecast horizon with the scheduling horizon (12–24 h in our experiments). Forecasts are imperfect, but using the same input for all algorithms keeps comparisons fair. Section 4 details sources, coverage, and preprocessing.

3.1.2 Operational: Power Consumption of Workloads

Power model and per-workload attribution: Each node exposes a two-point power profile with an idle baseline P_{idle} and a maximum P_{max} . We model node power as a linear function of aggregate CPU utilization $U \in [0, 1]$: $P(U) = P_{idle} + (P_{max} - P_{idle})U$ for $U > 0$, and zero when no work is scheduled. The idle baseline is charged once per active slot.

For a workload requesting $\text{CPU}_{request}$ on a node with CPU_{total} , we attribute per-pod power per slot t using the same linear interpolation for the incremental component and allocate the idle baseline across concurrent workloads in proportion to CPU share:

$$p_{ij,t} = (P_{max} - P_{idle}) \cdot \frac{\text{CPU}_{request}}{\text{CPU}_{total}} + \theta_{ij,t} P_{idle},$$

where $\sum_i \theta_{ij,t} = 1$ for active slots and $\theta_{ij,t}$ is proportional to $\text{CPU}_{request}$ among concurrent workloads.

3.1.3 Embodied: Emissions and Amortization

Our embodied carbon calculations are based on lifecycle assessment (LCA) data from the Boavizta database [24], which aggregates manufacturer-reported environmental product declarations following ISO 14040/14044 standards.

The dataset encompasses over 200 hardware configurations from major manufacturers including Dell, Lenovo, and others, providing representative embodied carbon values

and expected lifetimes across different hardware categories. We computed category-wise averages for the device types used in our experimental evaluation, as summarized in Table 1.

The core challenge in embodied carbon accounting is properly amortizing the upfront manufacturing emissions over the hardware's operational lifetime and allocating them to individual workloads. Consistent with SCI's time-and-resource attribution, we amortize per *active* device-hour and allocate by time-in-use and resource share:

$$E_{emb,hourly} = \frac{E_{emb,total}}{L_{lifetime} \times 365 \times 24 \times u_j} \quad (1)$$

where $E_{emb,total}$ represents the total embodied emissions for a hardware unit (in grams CO_{2e}), $L_{lifetime}$ is the expected operational lifetime in years, $u_j \in (0, 1]$ is the expected active-time utilization of node j , and $E_{emb,hourly}$ is the amortized embodied carbon per *active* hour of device use.

For workload allocation, embodied emissions are attributed proportionally to both the time scheduled and the resource share within each active slot:

$$E_{emb,workload} = \sum_{k=0}^{d_i-1} E_{emb,hourly} \cdot \theta_{ij,t+k} \quad (2)$$

where $\theta_{ij,t}$ is the allocation share for pod i on node j at slot t (proportional to its resource share, with $\sum_i \theta_{ij,t} = 1$ for active slots). This allocation model reduces to uniform time-based amortization when detailed shares are unavailable (i.e., $\theta_{ij,t} = 1$ for a single active workload), and ensures that longer-running and higher-share workloads bear proportionally larger embodied carbon.

The embodied carbon calculation is integrated directly into the scheduling objective function, where it combines with operational emissions to provide a comprehensive carbon footprint assessment for each placement decision. This integrated approach ensures that both emission components influence scheduling decisions simultaneously, rather than treating them as separate optimization phases. We quantify the effect on placement patterns in Section 5.1.

3.2 Problem Formulation

We formulate the carbon-aware scheduling problem as a Mixed Integer Linear Programming (MILP) optimization that finds optimal assignments of pods (computational tasks) to nodes (computing resources) and timeslots while minimizing total carbon emissions incorporating both operational and embodied components. The following subsections detail the problem formulation.

3.2.1 Sets, Parameters and Decision Variables

Sets: Let $i \in \mathcal{P}$ denote the set of pods, $j \in \mathcal{F}$ the set of nodes, and $t \in \mathcal{T}$ the set of timeslots.

Parameters: Table 2 lists the notation and description of the inputs used in the formulation.

Decision Variables: The binary decision variable is defined as:

$$x_{ijt} = \begin{cases} 1 & \text{if pod } i \text{ placed on node } j \text{ at time } t \\ 0 & \text{otherwise} \end{cases} \quad (3)$$

TABLE 2
Glossary of parameters

Parameter	Description
$D_i \in \mathbb{N}^+$	Deadline timeslot for pod i
$s_i \in \mathbb{N}^+$	Earliest timeslot for pod i
$d_i \in \mathbb{N}^+$	Duration of pod i (in timeslots)
$w_i \in \mathbb{N}^+$	Temporal slack for pod i
$c_i \in \mathbb{R}^+$	CPU request of pod i
$r_i \in \mathbb{R}^+$	RAM request of pod i
$C_{jt} \in \mathbb{R}^+$	Available CPU of node j in timeslot t
$R_{jt} \in \mathbb{R}^+$	Available RAM of node j in timeslot t
$p_{ij} \in \mathbb{R}^+$	Power consumption of pod i on node j
$CI_{j,t} \in \mathbb{R}^+$	Carbon intensity of node j in timeslot t
$EC_j \in \mathbb{R}^+$	Embodied carbon of node j
$L_j \in \mathbb{R}^+$	Expected lifetime of node j
$u_j \in \mathbb{R}^+$	Utilization factor of node j

Feasible Placements: Let $\mathcal{V}_i \subset \mathcal{F} \times \mathcal{T}$ be the set of valid node-timeslot pairs for pod i :

$$\mathcal{V}_i = \{(j, t) \in \mathcal{F} \times \mathcal{T} \mid t \geq s_i, t + d_i \leq D_i, \\ C_{j(t+k)} \geq c_i \forall k \in \{0, \dots, d_i - 1\}, \\ R_{j(t+k)} \geq r_i \forall k \in \{0, \dots, d_i - 1\}\} \quad (4)$$

where the deadline timeslot $D_i = s_i + d_i + w_i$ includes the pod's execution duration and temporal slack for scheduling flexibility.

3.2.2 Objective Function

The optimization objective minimizes total carbon emissions across all scheduled pods:

$$\text{minimize } \sum_{i \in \mathcal{P}} \sum_{(j,t) \in \mathcal{V}_i} e_{ijt} \cdot x_{ijt} \quad (5)$$

where e_{ijt} represents the total carbon emissions for executing pod i on node j starting at timeslot t .

3.2.3 Carbon Emissions Model

The carbon emissions e_{ijt} incorporate both operational and embodied components over the pod's execution duration d_i :

$$e_{ijt} = \sum_{k=0}^{d_i-1} (op_{ij,t+k} + emb_{ij,t+k}) \quad (6)$$

where operational emissions $op_{ij,t+k} = p_{ij,t+k} \cdot CI_{j,t+k}$ depend on per-slot power $p_{ij,t+k}$ and carbon intensity $CI_{j,t+k}$, and embodied emissions per timeslot are $emb_{ij,t+k} = \frac{EC_j}{L_j \cdot u_j} \cdot \theta_{ij,t+k}$ based on total embodied carbon EC_j , lifetime L_j , node-level utilization factor u_j , and allocation share $\theta_{ij,t+k}$ (proportional to CPU share; $\sum_i \theta_{ij,t} = 1$ for active slots).

3.2.4 Constraints

Resource capacity:

$$\sum_{i \in \mathcal{P}} \sum_{k=0}^{d_i-1} c_i x_{ij,t+k} \leq C_{j\tau}, \quad (7)$$

$$\sum_{i \in \mathcal{P}} \sum_{k=0}^{d_i-1} r_i x_{ij,t+k} \leq R_{j\tau}, \quad (8)$$

for all $j \in \mathcal{F}$ and $\tau \in \mathcal{T}$. We take $x_{ijt} = 0$ when $t \notin \mathcal{T}$ or $(j, t) \notin \mathcal{V}_i$.

Assignment (per pod i):

$$\sum_{(j,t) \in \mathcal{V}_i} x_{ijt} = 1, \quad (9)$$

with the relaxed variant given in Section 3.3.1.

Temporal feasibility is encoded by the feasible set $\mathcal{V}_i$ defined earlier (earliest start and deadline windows, plus per-slot capacity checks along the pod's duration).

3.3 Theoretical Solution: MILP Oracle

Before Section 3.4 presents our proposed algorithm, the current section first discusses the theoretically ideal solution: global oracle, with knowledge of all current and future scheduling needs, and which thus globally – and with future knowledge – optimizes the scheduling for minimum carbon. The role of this oracle is twofold: First, to introduce upper-bound achievable emissions under identical data and constraints. Secondly, as theoretical but ideal solution, it will also be used in Sections 5 and 6 as one of the two benchmarks for our algorithm.

3.3.1 Feasibility and Relaxations

When the full MILP becomes infeasible (e.g., oversubscribed capacities or incompatible windows), we solve a relaxed variant that guarantees feasibility while preserving lexicographic priorities: (1) maximize pod placement; then (2) minimize total carbon given equal placement counts. We introduce binary slack variables y_i indicating unplaced pods and set a penalty $\lambda \gg \max e_{ijt}$ to enforce the priority ordering:

$$\text{Minimize } Z(\mathbf{x}, \mathbf{y}) = \lambda \sum_{i \in \mathcal{P}} y_i \quad (10)$$

$$+ \sum_{i \in \mathcal{P}} \sum_{(j,t) \in \mathcal{V}_i} e_{ijt} \cdot x_{ijt} \quad (11)$$

subject to the softened assignment constraint

$$\sum_{(j,t) \in \mathcal{V}_i} x_{ijt} + y_i = 1 \quad \forall i \in \mathcal{P}. \quad (12)$$

This hierarchy ensures responsiveness in intractable instances and yields upper bounds for heuristic comparisons.

3.3.2 Computational Complexity

The MILP contains $O(|\mathcal{P}| |\mathcal{F}| |\mathcal{T}|)$ binary variables over feasible pairs and is NP-hard with worst-case exponential time. Practical solvers (e.g., CBC) employ branch-and-bound with cutting planes; performance is reasonable at moderate scales but degrades with increasing horizon and candidate sets. We therefore use solver time limits and the above relaxation to bound latency and provide references at tractable sizes.

3.4 Proposed Heuristic Carbon-Aware Scheduler

The current paper introduces a further-developed version of the algorithm (Section 3.4.1) and its implementation (Section 3.4.2). Section 4 details the experimental protocol, while Section 5 compares the heuristic against both the carbon-agnostic baseline and the global MILP oracle.

While the MILP formulation provides optimal solutions, it becomes computationally intractable for large-scale deployments with hundreds of pods and nodes. To address these challenges, we developed a spatio-temporal scheduling algorithm. The principles of this algorithm were first presented in [8]; an improved—now implemented and benchmarked—version is presented in Algorithm 1 below.

3.4.1 Algorithmic Framework

The core algorithm maintains a priority queue of pending pods ordered by deadline urgency and evaluates all feasible (node, timeslot) combinations, scoring each candidate by e_{ijt} as defined in Section 3.2.3.

Constraint handling.: A candidate (j, t) is feasible only if per-slot CPU and RAM capacities hold across the pod's duration and t respects earliest/deadline windows, as defined in Section 3.2.4.

Candidate ordering.: Pods are processed by smallest scheduling window (deadline minus duration), then by larger CPU, RAM, and duration (stable sort). For each pod, we pre-order timeslots by lower forecasted carbon (best-effort, taking the minimum across nodes), then enumerate nodes.

Tie-breaking and determinism.: Primary score is total emissions e_{ijt} . On ties (within a tiny ϵ), we prefer tighter packing using a normalized slack metric over CPU and RAM across the pod's duration (smaller is better). We set $\epsilon = 10^{-9}$ to avoid floating-point artifacts without affecting ranking. Determinism follows from the fixed ordering of pods, timeslots, and nodes.

Search strategy.: We enumerate all feasible (node, timeslot) pairs for the pod (no node sampling or early-stop); the timeslot pre-ordering biases search toward lower-carbon hours.

Implementation notes.: We track per-slot residual capacity in dictionaries indexed by node and timeslot, and use stable sorts for deterministic processing. Per-iteration work remains $O(|\mathcal{F}| |\mathcal{T}|)$ per pod (see Section 3.3.2).

Unschedulable case.: If no feasible (j, t) exists for a pod (e.g., due to capacity or window constraints), the pod remains pending and is retried in the next scheduling round; deadlines/windows are re-evaluated each pass. No implicit relaxation or forced placement occurs in the heuristic.

3.4.2 Computational Complexity

The heuristic algorithm has time complexity $O(|\mathcal{P}| \times |\mathcal{F}| \times |\mathcal{T}|)$ for each scheduling iteration, where $|\mathcal{P}|$ is the number of pending pods, $|\mathcal{F}|$ is the number of nodes, and $|\mathcal{T}|$ is the number of timeslots. This represents a significant improvement over the MILP formulation while maintaining solution quality for practical deployment scenarios.

4 EXPERIMENTAL SETUP

To ensure clarity and reproducibility, we document the evaluation setup in the same order used to present results. Section 4.1 summarizes the system architecture (Fig. 1) to show where each scheduler runs. Section 4.2 defines the testbed—nodes, regions, carbon forecasts, and the scheduling horizon. Section 4.3 specifies the workloads:

Algorithm 1 Heuristic Carbon-Aware Scheduler

```

1: Input: Pods  $\mathcal{P}$ , nodes  $\mathcal{F}$ , timeslots  $\mathcal{T}$ ;
   pod parameters  $\{(c_i, r_i, d_i, s_i, D_i)\}_{i \in \mathcal{P}}$ ;
   capacities  $\{(C_{jt}, R_{jt})\}_{j \in \mathcal{F}, t \in \mathcal{T}}$ ;
   carbon intensity  $\{CI_{j,t}\}_{j,t}$ ; power  $p_{ij}$ ; embodied
   ( $EC_j, L_j$ )
2: Output: Schedule  $S \subseteq \mathcal{P} \times \mathcal{F} \times \mathcal{T}$ 
3:
4: Initialize residuals  $\tilde{C}_{jt} \leftarrow C_{jt}, \tilde{R}_{jt} \leftarrow R_{jt}$  for all  $j, t$ ;
    $S \leftarrow \emptyset$ 
5: Compute  $w_i \leftarrow D_i - d_i$ ; sort  $\mathcal{P}$  by  $(w_i \uparrow, c_i \downarrow, r_i \downarrow, d_i \downarrow)$ 
6: for each  $i \in \mathcal{P}$  do
7:    $e^* \leftarrow \infty, (j^*, t^*) \leftarrow (\emptyset, \emptyset), \pi^* \leftarrow \infty$ 
8:   for each  $t \in \mathcal{T}$  with  $t \geq s_i$  and  $t + d_i \leq D_i$  do
9:     for each  $j \in \mathcal{F}$  do
10:      if  $\tilde{C}_{j,t+\tau} \geq c_i$  and  $\tilde{R}_{j,t+\tau} \geq r_i$  for all  $\tau \in \{0, \dots, d_i - 1\}$  then
11:         $\hat{e}_{ijt} \leftarrow \sum_{\tau=0}^{d_i-1} (p_{ij} \cdot CI_{j,t+\tau} + EC_j/L_j)$ 
12:         $\pi_{ijt} \leftarrow \sum_{\tau=0}^{d_i-1} \left( \frac{\tilde{C}_{j,t+\tau} - c_i}{C_{j,t+\tau}} + \frac{\tilde{R}_{j,t+\tau} - r_i}{R_{j,t+\tau}} \right)$ 
13:        if  $\hat{e}_{ijt} < e^* - \epsilon$  or  $(|\hat{e}_{ijt} - e^*| \leq \epsilon$  and
            $\pi_{ijt} < \pi^*)$  then
14:           $e^* \leftarrow \hat{e}_{ijt}, (j^*, t^*) \leftarrow (j, t), \pi^* \leftarrow \pi_{ijt}$ 
15:        end if
16:      end if
17:    end for
18:  end for
19:  if  $(j^*, t^*) \neq (\emptyset, \emptyset)$  then
20:     $S \leftarrow S \cup \{(i, j^*, t^*)\}$ 
21:    for  $\tau = 0$  to  $d_i - 1$  do
22:       $\tilde{C}_{j^*, t^*+\tau} \leftarrow \tilde{C}_{j^*, t^*+\tau} - c_i; \tilde{R}_{j^*, t^*+\tau} \leftarrow \tilde{R}_{j^*, t^*+\tau} - r_i$ 
23:    end for
24:  end if
25: end for
26: return  $S$ 

```

pod mixes with CPU/RAM requests, durations, and earliest/deadline windows. Section 4.4 introduces the benchmarking baselines—a global MILP oracle (upper bound) and a carbon-agnostic scheduler (vanilla reference). Section 4.5 states the metrics we report, Section 4.6 details the protocol for fair, like-for-like comparisons, and Section 4.7 describes the runtime measurement setup.

4.1 System Architecture Overview

Our carbon-aware orchestration system is implemented as a distributed architecture that integrates with Kubernetes through a custom gRPC-based interface. The system decouples carbon-aware scheduling logic from the underlying orchestration platform, enabling algorithmic experimentation while maintaining production-grade performance and reliability.

The architecture in Figure 1 comprises four layers: (i) a client-facing ingress, (ii) a pluggable algorithm engine with three schedulers, (iii) internal data services, and (iv) external data sources. This separation (blue = core components/algorithms; green = internal data; orange = external

sources) decouples scheduling logic from data acquisition and persistence.

Ingress and dispatch. A Go client running in Kubernetes calls a gRPC Placement service that implements a stable IDL. The service forwards scheduling requests (cluster snapshot and workloads) to the Algorithm Engine, which dispatches to one of three schedulers: a carbon-agnostic Baseline (vanilla, capacity-only), a real-time carbon-aware Heuristic, or a global MILP Oracle used for offline benchmarking.

Algorithms and data dependencies. The Heuristic and MILP Oracle consume Carbon Data (time- and location-varying forecasts) and Hardware Metadata (power curves, embodied carbon, lifetimes). The Baseline interacts only with State Storage and ignores carbon inputs. All algorithms read/write State Storage to persist placements and metrics for reproducibility and experiment continuity.

Internal data services. Carbon Data maintains rolling 24–48 hour forecasts aligned to regions/nodes. Hardware Metadata stores per-node power/embodied parameters sourced from Kubernetes node labels and Boavizta LCA values. State Storage persists scheduling state and experiment logs.

External sources. Electricity Maps [25] provides carbon-intensity forecasts that feed Carbon Data; Kubernetes node information supplies hardware attributes to Hardware Metadata; Boavizta DB supplies embodied-carbon and lifetime parameters.

Availability. We release the full implementation as open-source software [26] and provide a ‘kubect!’ plugin for cluster operators [27].




Fig. 1. Carbon-aware orchestration system architecture with component interactions and data flow. Color Key: ■ Core components and algorithms ■ Internal data services ■ External data sources

4.2 Testbed Configuration

We evaluate all algorithms on a shared synthetic testbed with consistent infrastructure, workloads, and carbon forecasts:

Infrastructure and Nodes. Nodes are described by hardware metadata including region, embodied carbon and lifetime, and power profiles. Regions cover European grids with heterogeneous carbon intensity.

Carbon Forecasts. Hourly average carbon-intensity (ACI) forecasts are loaded from a consolidated JSON (aligned across algorithms). Forecast horizons span 12–24 hours, enabling temporal shifting while respecting earliest/deadline constraints.

Scheduling Horizon. All methods operate over identical timeslot horizons. For fairness, feasibility checks require capacity across the entire execution duration of a pod for any candidate start slot.

Validation. A batch validator checks earliest-timeslot, deadline, and capacity constraints on produced placements for all algorithms; current experiments pass with zero violations.

4.3 Workload Characteristics

Workloads consist of pods with CPU and RAM requests, integer-hour durations, and earliest start slots derived from their originating timeslot files. Deadlines are set as earliest + duration + slack to create bounded scheduling windows. We generate realistic mixes to induce nontrivial packing, with per-scale pod counts ranging from tens to hundreds.

4.4 Benchmarking Baselines

This subsection lays out the two reference points we use in all comparisons and how we configure them. We keep it simple on purpose: a global MILP oracle to show what “best possible under our model” looks like, and a plain carbon-agnostic scheduler to represent a reasonable vanilla choice. Together they bracket the space our heuristic aims to operate in.

MILP oracle. We instantiate the two-phase oracle with the following solver setup: OR-Tools CP-SAT by default (per-phase time limit 60 s, 8 threads, relative gap 0.05), with PuLP fallbacks for HiGHS/Gurobi/CPLEX/CBC using equivalent limits. Phase 2 uses binary activation variables to charge idle+embodied once per active (node, timeslot) with standard linking; we warm-start from Phase 1 where supported and, on timeout, run a dynamic-only fallback to return a usable bound. We log solver status, iteration counts (when available), and wall time.

Carbon-agnostic baseline. For a straightforward reference, we mirror Kubernetes’ *filter* $\rightarrow$ *score* $\rightarrow$ *select* path: (i) filter nodes that satisfy CPU/RAM across the pod’s duration at a candidate start, (ii) score feasible nodes with a LeastAllocated-like metric (equal CPU/RAM weights), and (iii) pick the best score at the earliest feasible start. It enforces earliest/deadline windows and ignores carbon in scoring. To keep behavior close to upstream, we enable node sampling and early feasible-stop so runtime and choices look like vanilla. Configuration: `percentage_of_nodes_to_score=50%`, `min_nodes_to_score=50`, `max_nodes_to_score=1000`, early stop after $k = 16$ feasible candidates. Feasibility uses a sliding-window check across the pod’s duration on each node. The baseline logs placements with zero on-the-fly emissions; totals are recomputed offline with the shared accounting.

4.5 Evaluation Metrics

We report:

- **Total emissions:** operational + amortized embodied (kg CO₂e), per run and per algorithm
- **Emissions per pod:** total divided by placed pods
- **Success rate:** fraction of pods placed (feasibility under constraints)
- **Runtime:** median/mean per-placement execution time and end-to-end precompute time

4.6 Evaluation Protocol and Fairness

To quantify carbon reductions, we evaluate three schedulers—*vanilla* (baseline), *heuristic* (carbon-aware), and *global-optimal* (MILP oracle)—over controlled workload scales (20–200 pods) and time horizons. All algorithms operate under the same constraints (earliest timeslot, CPU/Memory, node capacity/affinity) and the same emissions model (operational + amortized embodied carbon; identical regional carbon-intensity forecasts and node power profiles). We fix seeds where stochasticity is used and report confidence intervals when averaging over multiple runs.

Apples-to-apples comparison is non-trivial because algorithms can schedule different subsets of pods under the same load, confounding emissions with feasibility. We therefore present the **coverage-inclusive** view: emissions computed over all pods each algorithm successfully schedules, reflecting end-to-end impact (quality and coverage).

4.7 Runtime Measurement Protocol

We report median precompute runtime in offline mode with a 12-slot horizon. For node-scaling overlays, we fix pods at 200 and vary node count; for pod-scaling overlays, we fix nodes at 16 and vary pod count. Curves overlay multiple schedulers; error bars (when present) denote $\pm 1\sigma$ over three replicates.

5 RESULTS

We report how embodied emissions change placement behavior (Section 5.1), quantify emissions reductions and success rates (Section 5.2 and Fig. 6), and analyze runtime scaling (Section 5.4).

5.1 Impact of Embodied Emissions on Scheduling

Including embodied emissions fundamentally changes placement behavior: it shifts from clustering on low-CI nodes to more distributed utilization that amortizes fixed manufacturing emissions while still respecting operational carbon signals.

Taken together, Figures 2 and 3 show that accounting for embodied emissions alters the optimization landscape. The operational-only strategy prefers a small set of low-CI nodes, whereas the comprehensive objective prefers spreading load to amortize fixed embodied costs. This trade-off can increase operational emissions slightly in some slots but reduces total (operational+embodied) emissions across the horizon.

The result aligns with our allocation model: embodied emissions are a fixed, time-amortized cost that incentivizes




Fig. 2. Operational-only scheduling. Optimizing solely for electricity carbon intensity concentrates work on a subset of nodes, which can under-utilize other hardware and inflate per-workload embodied attribution.




Fig. 3. Operational+embodied scheduling. Incorporating amortized embodied costs yields more balanced placements, improving lifetime utilization and total carbon efficiency.

sustained, efficient hardware use. Ignoring them underestimates true impact and can create seemingly efficient but globally suboptimal utilization patterns.

5.2 Carbon Reduction

Figure 4 shows total emissions versus pod count (coverage-inclusive). As load increases, the carbon-aware schedulers reduce emissions relative to the vanilla baseline; the MILP oracle consistently provides a lower bound, and the heuristic tracks it closely in most scales. Because inclusive totals aggregate whatever each algorithm could schedule, we jointly report success rate in Figure 6 (protocol in Section 4).

Across both views we use the same emissions accounting (operational + embodied). For completeness, per-pod or per-CPU-hour normalizations and operational-only sensitivity analyses can be included in the supplement; the qualitative ordering remains stable under these variants in our experiments.

Concrete findings. In a representative 80-pod evaluation, per-pod emissions were: vanilla 10.1 g CO₂e, heuristic 3.3 g ($\approx 67.5\%$), and global-optimal 2.6 g ($\approx 74.0\%$). This gap illustrates that the heuristic captures most of the oracle's benefit while remaining deployable.

5.3 Placement Success Rate

Figure 6 shows scheduling success rate versus pod count. At low load, all three methods are near 100%; as load increases,




Fig. 4. Total carbon emissions vs. pod count (**coverage-inclusive**). Emissions are computed using a shared model (operational + amortized embodied). Inclusive results reflect each algorithm's *actual* coverage at a given scale.




Fig. 5. Average emissions per placed pod (kg CO₂e/pod) vs. pod count (coverage-inclusive). Carbon-aware methods remain nearly flat; vanilla starts high.

the heuristic remains above the vanilla baseline and close to the MILP oracle.

5.4 Runtime Cost: Time Complexity

Figures 7 and 8 summarise runtime. It grows roughly with the number of pods and remains compatible with online use at our largest scales. The MILP approach is far slower and sensitive to solver limits, so we treat it as a benchmarking oracle rather than a production scheduler. Following the vanilla baseline optimizations described above, the vanilla series shifts down substantially in both overlays.

Setup. We report median precompute runtime in offline mode with a 12-slot horizon. Figure 7 fixes pods to 200 and varies node count; Figure 8 fixes nodes to 32 and varies pod count. Curves overlay multiple schedulers; error bars (when present) denote $\pm 1\sigma$ over three replicates.

Results. Runtime grows smoothly with both nodes and pods. The heuristic remains compatible with online use across tested scales (single-digit seconds at the largest points), while the MILP oracle grows much faster and is sensitive to solver limits. The vanilla baseline is generally the fastest (simplest scoring), with the heuristic modestly above it but




Fig. 6. Scheduling success rate vs. pod count. Higher is better. Used jointly with inclusive emissions to disambiguate feasibility from carbon efficiency.




Fig. 7. Median precompute runtime versus node count at fixed 200 pods (overlay across algorithms; error bars where available denote $\pm 1\sigma$).

far below MILP; this ordering holds in both fixed-pods and fixed-nodes views.

Fixed pods (varying nodes): With 200 pods held constant, both vanilla and heuristic exhibit near-linear growth in precompute time as node count increases. The optimized vanilla curve lies consistently below its earlier baseline, indicating lower constant factors; its slope remains modest due to node sampling and early termination once a small set of feasible candidates is found. By contrast, the MILP oracle grows much more steeply with the number of nodes. Error bars are small across replicates, indicating stable timings and low run-to-run variance.

Fixed nodes (varying pods): With 32 nodes held constant, runtime grows approximately linearly with total pods for both vanilla and heuristic, as expected from per-pod evaluation over a bounded timeslot window. The optimized vanilla reduces both the intercept and the slope relative to the prior implementation, reflecting cheaper feasibility checks and less I/O in the hot path. The heuristic maintains a roughly constant factor overhead versus vanilla across scales—primarily from additional feasibility and scoring work—while remaining far below the MILP oracle, which grows faster-than-linearly and exhibits higher variance.

Takeaways. (i) Empirical scaling matches the intended de-




Fig. 8. Median precompute runtime versus pod count at fixed 32 nodes (overlay across algorithms; error bars where available denote $\pm 1\sigma$).

sign: linear in pods at fixed nodes, and close to linear in nodes at fixed pods; (ii) kube-inspired pruning (node sampling and early feasible stop) keeps growth in check; (iii) simulator-specific accelerations (tight timeslot windowing, sliding-window feasibility, array-backed capacity) reduce constant factors, shifting the vanilla curve downward without changing its qualitative scaling; (iv) MILP remains orders of magnitude slower and is best treated as an oracle for bounds rather than a production scheduler.

[NA: add a subsection on sensitivity to forecast error]

6 DISCUSSION

We interpret the emissions patterns (why per-pod curves are flat and why the vanilla baseline starts high), discuss implications and limitations, and outline threats to validity, tying back to the methods in Section 4 and results in Section 5.

Revisiting our questions.: Our results indicate that (i) feasibility remains high under carbon-aware placement with realistic slack, (ii) the heuristic approaches the MILP’s carbon outcome across scales while running orders of magnitude faster, and (iii) precompute latency remains compatible with nearline or periodic admission control, suggesting practical deployability.

6.1 Interpreting Emissions Patterns

Why per-pod curves are flat: With co-location-aware accounting, dynamic power for a node-hour is linear in aggregate utilization U , and per-pod attribution scales with CPU share. The pod-normalized dynamic term simplifies to $CI \times k \times u_i$, independent of the number of co-located pods. Idle and embodied are paid *once* per active node-hour and allocated proportionally to CPU share, so a pod’s share $\propto u_i/U$ shrinks as utilization grows. As a result, average emissions per pod stay approximately constant (or slightly decrease) even as the system fills and placement flexibility declines.

Why vanilla starts high: The vanilla scheduler’s LeastAllocated-like scoring spreads pods to underutilized nodes, activating many node-hours early. This incurs idle and amortized embodied costs across more nodes and often places work in high-CI nodes/timeslots from the outset, leading to substantially higher per-pod emissions relative

to carbon-aware schedulers that consolidate selectively and align with low-CI windows.

6.2 Implications and Limitations

How it scales.: In practice, runtime grows with the number of pods and nodes that must be evaluated. Two things keep it fast: (i) realistic deadlines shrink the number of eligible start times per pod, and (ii) early feasibility checks discard many node–time candidates before detailed scoring. Memory use grows with tracked capacity per node and the number of pods under consideration.

Empirical behavior.: Across our sweep (12-slot horizon; 8–64 nodes; 50–400 pods; three replicates), runtime increased smoothly with load and remained under eight seconds at the largest point, suitable for online or nearline admission control.

Implications for deployability.: When response-time targets are tight, we can further cap per-pod evaluations to a small set of promising nodes (e.g., by carbon intensity), reducing constant factors while preserving outcomes.

When it slows down.: Very loose deadlines, many nodes, or long durations increase candidates to check and can slow evaluation. Rich policy constraints also add per-candidate checks. The MILP oracle, by contrast, can be much slower and is retained as a benchmarking tool rather than for production.

Further speedups.: We can reduce overheads further by caching per-node energy/carbon curves, reusing capacity snapshots across similar pods, and evaluating batches of candidates together.

6.3 Threats to Validity

Internal validity. We control randomness via fixed seeds and validate constraints post hoc. Remaining risks include generator-induced artifacts; we mitigate by sweeping multiple pod counts and infrastructures.

Construct validity. We use ACI-based operational emissions and amortized embodied accounting. Alternative signals (e.g., marginal intensity, excess renewable) could change relative benefits.

External validity. Results derive from synthetic workloads and consolidated forecasts; real clusters may have additional constraints (affinity/anti-affinity, topology spread, storage). Our simulator architecture allows incrementally adding these.

Conclusion validity. We report multiple scales and pair emissions with success rate and runtime to avoid over-attributing gains to any single metric.

7 CONCLUSION AND FUTURE WORK

This paper shows that container orchestration can reduce *total* emissions—operational and embodied—without sacrificing feasibility or incurring prohibitive runtime. Across controlled scales, our carbon-aware heuristic consistently lowers emissions relative to a carbon-agnostic baseline while closely tracking a global MILP oracle. In a representative 80-pod evaluation, average per-pod emissions dropped from 10.1 to 3.3 g CO₂e (−67.5%) versus baseline, approaching the oracle at 2.6 g. Runtime grows smoothly with pods and

nodes and remains within single-digit seconds at our largest settings, indicating practicality for precompute or nearline use.

For practitioners, these results suggest an actionable path: integrate forecasted carbon signals and amortized embodied costs into placement, and deploy a fast heuristic to capture most of the achievable benefit. Our evaluation protocol—shared signals, models, constraints, and coverage-inclusive reporting—provides a reproducible basis for comparing algorithms and for tuning trade-offs between feasibility, carbon efficiency, and latency.

Our study has limitations. We evaluate on synthetic workloads and consolidated forecasts; real clusters introduce additional constraints (e.g., affinity, topology spread, storage) and dynamic interference. We use ACI as the operational signal and amortized embodied accounting; alternative signals (e.g., marginal intensity, excess-renewable availability) and allocation choices may shift outcomes. Network and migration energy are not modeled, and our experiments run in an offline precomputation mode.

Future work will: (i) integrate additional environmental indicators (e.g., water footprint, land use etc.); and (ii) evaluate on production traces and in live clusters with online admission. Together, these steps move carbon-aware orchestration from controlled studies toward robust production deployments.

REFERENCES

- [1] International Energy Agency, “Data centres and data transmission networks,” <https://www.iea.org/reports/data-centres-and-data-transmission-networks>, 2024, iEA Analysis; electricity use, growth, and forecasts.
- [2] E. Masanet, A. Shehabi, N. Lei, S. Smith, and J. Koomey, “Recalibrating global data center energy-use estimates,” *Science*, vol. 367, no. 6481, pp. 984–986, 2020.
- [3] Ember, “Global electricity review 2024,” <https://ember-climate.org/insights/research/global-electricity-review-2024/>, 2024.
- [4] Z. Cao, X. Zhou, X. Wu, Z. Zhu, T. Liu, J. Neng, and Y. Wen, “Data Center Sustainability: Revisits and Outlooks,” *IEEE Transactions on Sustainable Computing*, vol. 9, no. 3, pp. 236–248, May 2024. [Online]. Available: <https://ieeexplore.ieee.org/document/10139829/>
- [5] A. Radovanovic, J. Dean *et al.*, “Carbon-intelligent computing at google,” Google AI Blog, 2020. [Online]. Available: <https://ai.googleblog.com/2020/05/carbon-intelligent-computing-at-google.html>
- [6] L. Gu, W. Zhang, Z. Wang, D. Zeng, and H. Jin, “Service Management and Energy Scheduling Toward Low-Carbon Edge Computing,” *IEEE Transactions on Sustainable Computing*, vol. 8, no. 1, pp. 109–119, Jan. 2023. [Online]. Available: <https://ieeexplore.ieee.org/document/9905948/>
- [7] Kubernetes Authors, “Scheduling framework,” <https://kubernetes.io/docs/concepts/scheduling-eviction/scheduling-framework/>, 2025.
- [8] N. Asadov, V. C. Coroamă, M. Franzil, S. Galantino, and M. Finkbeiner, “Carbon-aware spatio-temporal workload shifting in edge-cloud environments: A review and novel algorithm,” *Sustainability*, vol. 17, no. 14, 2025. [Online]. Available: <https://www.mdpi.com/2071-1050/17/14/6433>
- [9] Green Software Foundation, “Software Carbon Intensity (SCI) Specification,” 2024. [Online]. Available: <https://sci.greensoftware.foundation/>
- [10] T. Piontek, K. Haghshenas, and M. Aiello, “Carbon emission-aware job scheduling for Kubernetes deployments,” *The Journal of Supercomputing*, Jun. 2023. [Online]. Available: <https://link.springer.com/10.1007/s11227-023-05506-7>

- [11] P. Wiesner, I. Behnke, D. Scheinert, K. Gontarska, and L. Thamsen, "Let's Wait Awhile: How Temporal Workload Shifting Can Reduce Carbon Emissions in the Cloud," in *Proceedings of the 22nd International Middleware Conference*, Dec. 2021, pp. 260–272, arXiv:2110.13234 [cs]. [Online]. Available: <http://arxiv.org/abs/2110.13234>
- [12] A. James and D. Schien, "A Low Carbon Kubernetes Scheduler," 2019.
- [13] A. Souza, S. Jasoria, B. Chakrabarty, A. Bridgwater, A. Lundberg, F. Skogh, A. Ali-Eldin, D. Irwin, and P. Shenoy, "CASPER: Carbon-Aware Scheduling and Provisioning for Distributed Web Services," in *Proceedings of the 14th International Green and Sustainable Computing Conference*, ser. IGSC '23. New York, NY, USA: Association for Computing Machinery, May 2024, pp. 67–73. [Online]. Available: <https://dl.acm.org/doi/10.1145/3634769.3634812>
- [14] M. Chadha, T. Subramanian, E. Arima, M. Gerndt, M. Schulz, and O. Abboud, "GreenCourier: Carbon-Aware Scheduling for Serverless Functions," in *Proceedings of the 9th International Workshop on Serverless Computing*, ser. WoSC '23. New York, NY, USA: Association for Computing Machinery, Dec. 2023, pp. 18–23. [Online]. Available: <https://doi.org/10.1145/3631295.3631396>
- [15] S. Rawas, A. Zekri, and A. El-Zaart, "LECC: Location, energy, carbon and cost-aware VM placement model in geo-distributed DCs," *Sustainable Computing: Informatics and Systems*, vol. 33, p. 100649, Jan. 2022. [Online]. Available: <https://linkinghub.elsevier.com/retrieve/pii/S2210537921001323>
- [16] T. Bahreini, A. N. Tantawi, and O. Tardieu, "Caspian: A Carbon-aware Workload Scheduler in Multi-Cluster Kubernetes Environments," in *2024 32nd International Conference on Modeling, Analysis and Simulation of Computer and Telecommunication Systems (MASCOTS)*, Oct. 2024, pp. 1–8, iSSN: 2375-0227. [Online]. Available: <https://ieeexplore.ieee.org/document/10786568/?arnumber=10786568>
- [17] B. M. Beena, P. C. Ranga, T. S. S. Manideep, S. Saragadam, and G. Karthik, "A Green Cloud-Based Framework for Energy-Efficient Task Scheduling Using Carbon Intensity Data for Heterogeneous Cloud Servers," *IEEE Access*, vol. 13, pp. 73 916–73 938, 2025. [Online]. Available: <https://ieeexplore.ieee.org/abstract/document/10971939>
- [18] W. A. Hanafy, L. Wu, D. Irwin, and P. Shenoy, "CarbonFlex: Enabling Carbon-aware Provisioning and Scheduling for Cloud Clusters," May 2025, arXiv:2505.18357 [cs]. [Online]. Available: <http://arxiv.org/abs/2505.18357>
- [19] T. Sukprasert, A. Souza, N. Bashir, D. Irwin, and P. Shenoy, "On the Limitations of Carbon-Aware Temporal and Spatial Workload Shifting in the Cloud," in *Proceedings of the Nineteenth European Conference on Computer Systems*. Athens Greece: ACM, Apr. 2024, pp. 924–941. [Online]. Available: <https://dl.acm.org/doi/10.1145/3627703.3650079>
- [20] S. Ji, Z. Yang, A. K. Jones, and P. Zhou, "Towards Datacenter Environmental Sustainability Using Carbon Depreciation Models," Mar. 2025, arXiv:2403.04976 [cs]. [Online]. Available: <http://arxiv.org/abs/2403.04976>
- [21] T. B. Hewage, S. Ilager, M. R. Read, and R. Buyya, "Aging-aware CPU Core Management for Embodied Carbon Amortization in Cloud LLM Inference," Jan. 2025, arXiv:2501.15829 [cs]. [Online]. Available: <http://arxiv.org/abs/2501.15829>
- [22] Y. Zhang, Y. Song, and S. Sahoo, "Carbon and Reliability-Aware Computing for Heterogeneous Data Centers," Apr. 2025, arXiv:2504.00518 [eess]. [Online]. Available: <http://arxiv.org/abs/2504.00518>
- [23] A. M. Panteleaki, V. Paramanayakam, V. Pentsos, A. Karatzas, S. Tragoudas, and I. Anagnostopoulos, "A Vertical Approach to Designing and Managing Sustainable Heterogeneous Edge Data Centers," Jun. 2025, arXiv:2506.01712 [eess]. [Online]. Available: <http://arxiv.org/abs/2506.01712>
- [24] "Boavizta/environmental-footprint-data," Jun. 2023, original-date: 2020-12-30T15:01:59Z. [Online]. Available: <https://github.com/Boavizta/environmental-footprint-data>
- [25] Electricity Maps, "Live 24/7 co₂ emissions of electricity consumption," 2024. [Online]. Available: <http://electricitymap.tmrow.co>
- [26] N. Asadov, "nasadov/carbon-aware-orchestrator," Oct. 2025, original-date: 2025-02-28T17:05:28Z. [Online]. Available: <https://github.com/nasadov/carbon-aware-orchestrator>
- [27] S. Cretti and N. Asadov, "nasadov/kubectl-carbon," Sep. 2025, original-date: 2025-04-14T10:02:09Z. [Online]. Available: <https://github.com/nasadov/kubectl-carbon>