



Cables Plus Enterprises, Inc. 931 Village Blvd. Ste. 905-346 West Palm Beach, FL 33409 tel: 908-797-4111 e: cablesplus@gmail.com

PRODUCT DATA SHEET


PRODUCT OVERVIEW:

APLSF-1265

CONSTRUCTION: 12 Bare Copper Parallel PVC
APPROVALS: NEC/UL Standards for Low Energy Cable
APPLICATION: Low Voltage Lighting Cable 60C/150V

CONSTRUCTION PARAMETERS:

CONDUCTOR: 12 Stranded Bare Copper
STRANDING: 65/30 Annealed Bare Copper
NUMBER OF CONDUCTORS: 2
INSULATION MATERIAL: PVC
INSULATION THICKNESS: 0.045" Nominal Each Conductor
FINISHED NOMINAL O.D.: 0.195" x 0.390"



ELECTRICAL & PHYSICAL PROPERTIES:

APPROX. EACH CENTER CONDUCTOR LBS. /1000': 20.1
BREAK LOAD of EACH CENTER CONDUCTOR: 223 lbs.
RESISTANCE OHMS/1000' PER CONDUCTOR: 1.70
LOAD CURRENT: 25 AMPS
INSULATION COLOR: BLACK/BLACK- ANY COLOR AVAILABLE UPON REQUEST

On special orders, the customer will accept all mil lengths and +/- 10% of total order requested. The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Cables Plus, Inc. Any information contained herein shall not be disclosed to any party without written consent of Cables Plus, Inc.

Manufactured in the U.S.A.