



Cables Plus Enterprises, Inc. 931 Village Blvd. Ste. 905-346 West Palm Beach, FL 33409 tel: 908-797-4111 e: cablesplus@gmail.com

PRODUCT DATA SHEET

PRODUCT OVERVIEW:

CCA-1241

CONSTRUCTION: 12 10% Copper Clad Aluminum Parallel PVC

APPROVALS: NEC/UL Standards for Low Energy Cable

APPLICATION: Low Voltage Lighting Cable 60C/150V

CONSTRUCTION PARAMETERS:

CONDUCTOR: 12 Stranded 10% Copper Clad Aluminum

STRANDING: 41/28" Annealed 10% CCA

NUMBER OF CONDUCTORS: 2

INSULATION MATERIAL: PVC

INSULATION THICKNESS: 0.045" Nominal Each Conductor

FINISHED NOMINAL O.D.: 0.195" x 0.390"

ELECTRICAL & PHYSICAL PROPERTIES:

APPROX. EACH CENTER CONDUCTOR LBS. /1000': 7.50

BREAK LOAD of EACH CENTER CONDUCTOR: 114.91 lbs.

RESISTANCE OHMS/1000' PER CONDUCTOR: 2.59

LOAD CURRENT: 20 AMPS

INSULATION COLOR: BLACK/BLACK- ANY COLOR AVAILABLE UPON REQUEST

On special orders, the customer will accept all mil lengths and +/- 10% of total order requested. The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Cables Plus, Inc. Any information contained herein shall not be disclosed to any party without written consent of Cables Plus, Inc.

Manufactured in the U.S.A.