

MST

Falcon Acoustics & Passive Fire Solutions Pvt. Ltd. Plot No 60/A, Kandivali Industrial Area, Charkop, Kandivali (W), Mumbai -400067. Tel: +91 22 28699520 +91 22 28672800, Web Site: www.falcontechno.in PROJECT NAME: ETERNIA LOCATION: Tower A,B,C,D Document Title: Method Statement for Fire Sealant Application Date of Issue: 08-12-2021 Document No./Submittal:ET-FAL-MEP-MST-0001 Revision Number: 0 Consultants: **Contractor: Pravin Electrical Limited** Method Pre-Qlfctn Work Program PQP Test Results Surveys Statemnt Calcultns O & M HSE Certificate Warranty Others Manuals Submittal Originator: Falcon Acoustics & Passive Fire Protection Pvt. Ltd. Date: 08-12-2021 Co-ordination Sign off: Prashant Ravindran Date: 08-12-2021 Actual Submission: 08-12-2021 Approval Reqd By: Planned Submission : Submittal Received: <Consultant /Employer> Date: The Contractor hereby certifies that the documents/data submitted are in accordance with the contract conditions, scope of works and local regulations and building standards **Engineers Review and Comments** Approvals Code A - NO OBJECTION Code B - NO OBJECTION WITH COMMENTS Code C - OBJECTION Code D - FOR INFO & RECORDS ONLY **Consultant Review Comments** Employer's (ORL HO) Comments NOTE: The concerned contractor's action is required within 3 days. Approval of the Documents/Data does not relieve the Contractor of his obligation in completing the works in accordance with contract documents, drawings and any applicable local regulations and standards < Date & Signature > < Name >Falcon Acoustics & Passive Fire Solutions Pvt Lt. Prashant Ravindran 07-12-2021 Released by: < *Name* > < Date & Signature > Oberoi Construction Limited Kaustubh Burange

ORL-HO-DCM-FM-0007 R03: Sep-16

Method Statement

Product: Protecta FR Acrylic **Packing:** 310 ml Cartridge

Application: For Cable, cable bunch, metallic and non metallic

Pipe penetrations Through wall or Floor

Image

Description

Surface Preperation:

Ensure the faces of the aperture opening are free of dust and any other contaminants. The faces may be moistened for better adhesion.

Pipe Wrap:

For penetrants like non metallic pipes, protecta pipe wrap needs to be installed. The number of turns required depends on the diameter of the pipe.

Rockwool:

Insert the rockwool tightly into the gap between the penetrant and the cutout.



Sealant Depth:

Measure and adjust the rockwool as per the depth required for sealant installation as per certifications

Image

Description



Sealant Application:

Apply Protecta FR Acrylic sealant into the gap with an applicator gun. Put in sufficient quantity for tooling it into place.

Tooling:

Tool the sealant with the help of a spatula or any suitable tool by applying sufficient pressure that will push the sealant into the gap leaving no blank space. Clean up any excess sealant.

Repeat all the steps on other side of the wall.

Final Product