

[← Go Back](#)

Hardware

[Gesture Recognition with the Nano 33 BLE Sense](#)[Get Started With Machine Learning on Arduino](#)[Getting Started with OpenMV](#)[Reading Temperature & Humidity on Nano 33 BLE Sense Rev2](#)[Connecting Two Nano 33 BLE Sense Boards Through I2C](#)[Accessing Accelerometer Data on Nano 33 BLE Sense Rev2](#)[Accessing Gyroscope Data on Nano 33 BLE Sense Rev2](#)[Accessing Magnetometer Data on Nano 33 BLE Sense Rev2](#)[Debugging with Lauterbach TRACE32 GDB Front-End Debugger](#)[Controlling the On-Board RGB LED with Microphone](#)[Proximity Detection with the Nano 33 BLE Sense](#)[Detecting Colors with the Nano 33 BLE Sense Board](#)[Voice Commands With The Arduino Speech Recognition Engine](#)[Connecting Two Nano 33 BLE Sense Boards Through UART](#)

[Home](#) / [Hardware](#) / [Nano 33 BLE Sense Rev2](#) / [Accessing Magnetometer Data on Nano 33 BLE Sense Rev2](#)

Accessing Magnetometer Data on Nano 33 BLE Sense Rev2

Learn how to detect disturbances in the magnetic field around an electronic device using the Nano 33 BLE Sense Rev2 board.

Author · Nefeli Last Alushi revision · 10/31/2025

ON THIS PAGE

IMU Module

[Goals](#)[Hardware & Software Needed](#)[The BMI270 & BMM150 Inertial Modules](#)[Creating the Program](#)[Testing It Out](#)[Conclusion](#)

IMU Module

This tutorial will focus on the 3-axis magnetometer sensor of the IMU system on the Arduino Nano 33 BLE Sense Rev2. The tutorial will utilize the IMU sensor in order to create an application that will detect changes and disturbances in the magnetic field around an appliance or electric device. This will be achieved by reading the values of the magnetometer's axes and blink the board's in-built LED according to the magnetic disturbances.

Goals

The goals of this project are to:

[Help](#)

Nano 33 BLE Sense Rev2 works.

Use the [BMI270_BMM150 library](#).

Measure the value of a magnetometer sensor.

Create visual feedback according to magnetic disturbance in the environment.

Convert the sensor's values in LED light intensity.


Hardware & Software Needed

This project uses no external sensors or components.

In this tutorial we will use the Arduino Create Cloud Editor to program the board.

The BMI270 & BMM150 Inertial Modules

IMU stands for: inertial measurement unit. It is an electronic device that measures and reports a body's specific force, angular rate and the orientation of the body, using a combination of accelerometers, gyroscopes, and oftentimes magnetometers. In this tutorial we will learn a bit more about the built in IMU system of the Arduino Nano 33 BLE Sense



The IMU system on the Arduino Nano 33 BLE Sense Rev2.

The IMU system on the Arduino Nano 33 BLE Sense Rev2 is a combination of two modules, the 6-axis BMI270, and the 3-axis BMM150, that together add up to a combined 9-axis IMU system that can measure acceleration, as well as rotation and magnetic fields all in 3D space.

The Library

The [Arduino BMI270_BMM150 library](#) allows us to use the Arduino Nano 33 BLE Sense Rev2 IMU module without having to go into complicated programming. The library takes care of the sensor initialization and sets its values as follows:

Accelerometer range is set at $[-4, +4]g$ ± 0.122 mg.

Gyroscope range is set at $[-2000, +2000]$ dps ± 70 mdps.

Magnetometer range is set at $[-400, +400]$ uT ± 0.014 uT.

Accelerometer output data rate is fixed at 104 Hz.

Gyroscope output data rate is fixed at 104 Hz.

If you want to read more about the sensor modules that make up the IMU system, find the datasheet for the [BMI270](#) and the [BMM150](#) here.

Magnetometer

A magnetometer is a device that measures magnetism, that is the direction, strength, or relative change of a magnetic field at a particular location.




How a magnetometer works.

In this tutorial we will read the values X, Y and Z and provide visual feedback through the in-built LED according to the intensity of magnetism around an electric object's cord.

Creating the Program

1. Setting up


Let's start by opening the [Arduino Cloud Editor](#) and creating a new sketch, this can be named "magnetometer". Then, navigate to the **Libraries** tab, search for the **BMI270_BMM150** library and click on the **Include** button.



Finding the library in the Cloud Editor.

2. Connecting the board

Next, connect the Arduino Nano 33 BLE Sense Rev2 to the computer and make sure that the Cloud Editor recognizes it. If so, the board and port should appear as shown in the image below. If they don't appear, follow the [instructions](#) to install the plugin that will allow the Editor to recognize your board.



Selecting the board.

3. Identifying changes in the magnetic field

After including the library, we can begin by building the rest of the code.

Let's start by defining the float variables

```
float x,y,z, ledvalue;
```

which will be needed for our code to work.

In the `setup()` we only need to initialize the IMU sensor with the following code:

```
1  if (!IMU.begin()) {  
2      Serial.println("Fa  
3      while (1);  
4  }
```

In the `loop()` we add the function

```
IMU.readMagneticField(x, y,  
z);
```

in order to read the values of the three axes on the IMU. Next we will add an `if` statement that checks if the magnetic field detected by the board is positive or negative (it will depend on the orientation of the board). If the magnetic field is negative, we convert the ledvalue in a positive range with `ledvalue = -(x);`, meaning that it is a valid value for the built in LED.

Lastly, we use the command

```
analogWrite(LED_BUILTIN,  
ledvalue);
```

to set the intensity of the LED according to the disturbance in the magnetic field, and add a small delay.

4. Complete code

The complete code can be found below:

```
1  /*
2   Arduino BMI270_BMM
3
4   This example reads
5   and `analogWrite`
6   the magnetic field
7
8   The circuit:
9   - Arduino Nano 33
10
11   Created by Benjamin
12   4 Dec 2020
13
14   This example code
15  */
16
17
18  #include "Arduino_BMI270.h"
19  float x,y,z, ledvalue;
20
21  void setup() {
22    if (!IMU.begin())
23      Serial.println("IMU not found");
24    while (1);
25  }
26  }
27
28  void loop() {
```


Testing It Out

After you have successfully verified and uploaded the sketch to the board, it's time to put it to the test. You can choose an electric appliance at home or any object that runs with electrical current. For example, in this tutorial we will use a laptop charger to test it out.

Place your board on top of the laptop's charging cord for 5-10 seconds and then move it away from it for some seconds again.

(orange) built-in LED blinking.
The intensity of the LED will vary according to the magnetic field detected.

Here is a screenshot illustrating the board's position:



Checking for
magnetic
disturbance.

However, there are other ways you can play around with this application. If you feel that the LED's brightness intensity is not visible enough you could experiment with other devices such as: electric kettle, toaster, TV or coffee machine. To do so, simply follow the same process and place the board close to the cable when the said device is active.

Troubleshoot

Sometimes errors occur, if the code is not working there are some common issues we can troubleshoot:

- Missing a bracket or a semicolon.

- Arduino board connected to the wrong port.

- Accidental interruption of cable connection.

In this simple tutorial we learned what an IMU sensor module is, how to use the **BMI270_BMM150** library, and how to use an Arduino Nano 33 BLE Sense Rev2 microcontroller, to detect magnetic field disturbances with a magnetometer sensor. Furthermore, we created an application that controls the intensity of an LED according to the values read from an IMU sensor module.

Suggest changes	Need support?	License
The content on docs.arduino.cc is facilitated through a public GitHub repository. If you see anything wrong, you can edit this page here .	Help Center Ask the Arduino Forum Discover Arduino Discord	The Arduino documentation is licensed under the Creative Commons Attribution-Share Alike 4.0 license.

Was this article helpful?

