

← Go Back

Hardware

Nano 33 BLE Sense Rev2

Tutorials

Access Barometric Pressure
Sensor Data on Nano 33
BLE Sense

Connecting Nano 33 BLE
Devices over Bluetooth®

Controlling RGB LED
Through Bluetooth®

Nano 33 BLE Sense Rev2
User Manual

Nano 33 BLE Sense
Community Projects

Edge Impulse with the
Nano 33 BLE Sense

Gesture Recognition with
the Nano 33 BLE Sense

Get Started With Machine
Learning on Arduino

Getting Started with
OpenMV

Reading Temperature &
Humidity on Nano 33 BLE
Sense Rev2

Connecting Two Nano 33
BLE Sense Boards Through
I2C

Accessing Accelerometer
Data on Nano 33 BLE Sense
Rev2

Accessing Gyroscope Data
on Nano 33 BLE Sense Rev2

Accessing Magnetometer
Data on Nano 33 BLE Sense
Rev2

Home / Hardware / Nano 33 BLE
Sense Rev2 / Controlling RGB LED
Through Bluetooth®

Controlling RGB LED Through Bluetooth®

Learn how to control the built in RGB
LED on the Nano 33 BLE Sense board
over Bluetooth®, using an app on your
phone.

Author · Fabricio Troya · Last revision · 07/17/2024

In this tutorial we will use an
Arduino Nano 33 BLE Sense, to
turn on an RGB LED over
Bluetooth®, made possible by the
communications chipset
embedded on the board.

Goals

The goals of this project are:

- Learn what Bluetooth® Low
Energy and Bluetooth® are.
- Use the Arduino BLE library.
- Learn how to create a new
service.
- Learn how to turn on a RGB
LED from an external device
(smartphone).

Hardware & Software Needed

This project uses no
external sensors or

ON THIS PAGE


Goals

- Hardware & Software Needed
- Bluetooth® Low Energy and
Bluetooth®
- Service & Characteristics
- Unique Universal Identifier
(UUID)
- Creating the Program
- Testing It Out
- Conclusion

+

In this tutorial we will use the [Arduino Cloud Editor](#) to program the board.

Bluetooth® Low Energy and Bluetooth®



The nRF52840 module.

Bluetooth® Low Energy separates itself from what is now known as “Bluetooth® Classic” by being optimized to use low power with low data rates. There are two different types of Bluetooth® devices: central or peripheral. A central Bluetooth® device is designed to read data from peripheral devices, while the peripheral devices are designed to do the opposite. Peripheral devices continuously post data for other devices to read, and it is precisely what we will be focusing on this tutorial.

Service & Characteristics

A service can be made up of different data measurements. For example, if we have a device that measures wind speed, temperature and humidity, we

device also records battery levels and energy consumption, we can set up a service that is called "Energy information". These services can then be subscribed to central Bluetooth® devices.

Characteristics are components of the service we mentioned above. For example, the temperature or battery level are both characteristics, which record data and update continuously.

Unique Universal Identifier (UUID)

When we read data from a service, it is important to know what type of data we are reading. For this, we use UUIDs, who basically give a name to the characteristics. For example, if we are recording temperature, we want to label that characteristic as temperature, and to do that, we have to find the UUID, which in this case is "2A6E". When we are connecting to the device, this service will then appear as "temperature". This is very useful when tracking multiple values.

If you want to read more about UUIDs, services, and characteristics, check the links below:


[GATT services.](#)

[GATT characteristics.](#)

Creating the

1. Setting up


Let's start by opening the [Arduino Cloud Editor](#), click on the **Libraries** tab and search for the **ArduinoBLE** library. Then in **> Examples > Peripheral**, open the **LED** sketch and once it opens, you could rename it as desired.



Finding the library in the Cloud Editor.

2. Connecting the board

Now, connect the Arduino Nano 33 BLE Sense to the computer and make sure that the Cloud Editor recognizes it, if so, the board and port should appear as shown in the image below. If they don't appear, follow the [instructions](#) to install the plugin that will allow the Editor to recognize your board.



Selecting board and port.

3. Turning ON the LED

Now we will need to modify the code on the example, in order to turn the RGB LED on in different colors, based on the information we sent through the smartphone

After including the

`ArduinoBLE.h` library, in the `ledService()` function change the argument to `"180A"` which is translated to **"Device Information"**. Then in the `switchCharacteristic()` function change the argument to `"2A57"` which is translated to **"Digital Output"**.

```
1  BLEService ledService("
2
3  // BLE LED Switch Chara
4  BLEByteCharacteristic s
```

In the `setup()` after initializing the serial communication we set the LED's pins as `OUTPUT`, and then turn them OFF, including the `LED_BUILTIN` that we will use to show if we are connected to the board.

```
1  // set LED pin to outp
2  pinMode(LED_R, OUTPUT);
3  pinMode(LED_G, OUTPUT);
4  pinMode(LED_B, OUTPUT);
5  pinMode(LED_BUILTIN, 0
6
7  digitalWrite(LED_BUILT
8  digitalWrite(LED_R, HIG
9  digitalWrite(LED_G, HIG
10 digitalWrite(LED_B, HIG
```

In the `BLE.setLocalName()` we need to change the name to `"Nano 33 BLE Sense"` in order to identify the board we are using.

```
1 // set advertised local
2 BLE.setLocalName("Nan
3 BLE.setAdvertisedServ
```

Now, in the `loop()` after the `Serial.println(central.address());` we need to set the `LED_BUILTIN` to `HIGH` to turn on the LED when the phone is connected to the board.

```
1 // print the central's
2 Serial.println(central.
3 digitalWrite(LED_BUILTI
```

Then we replace the second `if()` function inside the `while` loop with a `switch case` function, where each case will turn each color of the LED.

```

1 // while the central
2 while (central.connec
3
4 // if the remote devi
5 // use the value to c
6
7 if (switchCharacteris
8 switch (switchCharact
9     case 01:
10     Serial.println("F
11     digitalWrite(LED
12     digitalWrite(LED
13     digitalWrite(LED
14     break;
15     case 02:
16     Serial.println("C
17     digitalWrite(LED
18     digitalWrite(LED
19     digitalWrite(LED
20     break;
21     case 03:
22     Serial.println("E
23     digitalWrite(LED
24     digitalWrite(LED
25     digitalWrite(LED
26     break;
27     default:
28     Serial.println(F(

```

Lastly, after the last

`Serial.println()` function we use the `digitalWrite()` to turn off the LED once the phone is disconnected from the board.

```

1 // when the central dis
2 Serial.print(F("Disconn
3 Serial.println(central.
4 digitalWrite(LED_BUILT
5 digitalWrite(LED, HIGH
6 digitalWrite(LED, HIGH
7 digitalWrite(LED, HIGH
8 }
9 }

```


4. Complete code

If you choose to skip the code building section, the complete code can be found below:

```
1  #include <ArduinoBLE>
2
3  BLEService ledService
4
5  // BLE LED Switch Characteristic
6  BLEByteCharacteristic ledCharacteristic
7
8  void setup() {
9    Serial.begin(9600)
10   while (!Serial);
11
12   // set LED's pin to output
13   pinMode(LED_R, OUTPUT);
14   pinMode(LED_G, OUTPUT);
15   pinMode(LED_B, OUTPUT);
16   pinMode(LED_BUILTIN, INPUT);
17
18   digitalWrite(LED_R, LOW);
19   digitalWrite(LED_R, HIGH);
20   digitalWrite(LED_G, LOW);
21   digitalWrite(LED_B, LOW);
22
23   // begin initialization
24   if (!BLE.begin())
25     Serial.println("BLE not found");
26
27   while (1);
28 }
```

Testing It Out

Once we are finished with the coding, we can upload the sketch to the board. When it has successfully uploaded, open the Serial Monitor. In the Serial Monitor, the text "**BLE LED Peripheral**" will appear as seen in the image below.



Serial Monitor output.

We can now discover our Nano 33 BLE Sense board in the list of available Bluetooth® devices. To access the service and characteristic we recommend using the **LightBlue** application. Follow [this link for iPhones](#) or [this link for Android phones](#).

Once we have the application open, follow the image below for instructions:



Accessing through a Bluetooth® phone app.

To control the RGB LED, we simply need to write 1,2 or 3 in the "WRITTEN VALUES" field to turn on the red, blue or the green LED and any other value to turn them off. This is within the "**Digital Output**" characteristic, which is located under "**Device Information**".

Troubleshoot

Sometimes errors occur, if the code is not working there are some common issues we can troubleshoot:

Arduino board connected to the wrong port.

We haven't opened the Serial Monitor to initialize the program.

The device you are using to connect has its Bluetooth® turned off.

Conclusion

In this tutorial we have created a basic Bluetooth® peripheral device. We learned how to create services and characteristics, and how to use UUIDs from the official Bluetooth® documentation. Lastly, we turn on different colors of the RGB LED based on the values sent from the smartphone.

Now that you have learned a little bit how to use the ArduinoBLE library, you can try out some of our other tutorials for the Nano 33 BLE Sense board. You can also check out the [ArduinoBLE](#) library for more examples and inspiration for creating Bluetooth® projects!

Suggest changes	Need support?	License
The content on docs.arduino.cc is facilitated through a public GitHub repository . If you see anything	Help Center Ask the Arduino Forum Discover Arduino Discord	The Arduino documentation is licensed under the Creative Commons Attribution-Share Alike 4.0 license.

this page
[here](#).

Was this article helpful?

