```
public class Frodo extends Bilbo
{
  public void method1()
  {
    System.out.println("Frodo 1");
    super.method1();
  }

  public void method3()
  {
    System.out.println("Frodo 3");
  }
}
public class Gandalf
{
  public void method1()
  {
    System.out.println("Gandalf 1");
  }

  public void method2()
  {
    System.out.println("Gandalf 2");
    method1();
  }
}
public class Bilbo extends Gandalf
{
  public void method1()
  {
    System.out.println("Bilbo 1");
  }
}
public class Gollum extends Gandalf
{
  public void method3()
  {
    System.out.println("Gollum 3");
  }
}
```

And assuming the following variables have been defined:

```
Gandalf var1 = new Frodo();
Gandalf var2 = new Bilbo();
Gandalf var3 = new Gandalf();
Object var4 = new Bilbo();
```

```
Bilbo var5 = new Frodo();
Object var6 = new Gollum();
```

In the table below, indicate in the right-hand column the output produced by the statement in the left-hand column. If the statement produces more than one line of output, indicate the line breaks with slashes as in "a/b/c" to indicate three lines of output with "a" followed by "b" followed by "c". If the statement causes an error, fill in the right-hand column with either the phrase "compiler error" or "runtime error" to indicate when the error would be detected.

Statement	Output
`var1.method1();`	
`var2.method1();`	
`var4.method1();`	
`var6.method1();`	
`var1.method2();`	
`var3.method2();`	
`var4.method2();`	
`var5.method2();`	
`var6.method2();`	
`((Frodo)var4).method3();`	
`((Frodo)var6).method2();`	
`((Gollum)var1).method3();`	
`((Gollum)var4).method1();`	
`((Gandalf)var1).method2();`	
`((Frodo)var4).method1();`	
`((Gollum)var6).method2();`	
`((Gandalf)var2).method1();`	
`((Bilbo)var6).method2();`	
`((Frodo)var1).method3();`	
`((Gandalf)var5).method3();`	