Dataset

April 14, 2019

1 Pattern Project

1.1 Import Necessary Library

In [371]:
```
import pandas as pd
import numpy as np
import glob
import os
from os import listdir
from os.path import isfile, join
import csv
from sklearn.preprocessing import LabelEncoder
import matplotlib.pyplot as plt

#DecisionTreeClassifier
from sklearn.tree import DecisionTreeClassifier

#Gaussian Naive bayes
from sklearn.naive_bayes import GaussianNB

#svm with rbf karnel
import sklearn
from sklearn import svm, preprocessing
#SVM
from sklearn import datasets,svm
from sklearn.cross_validation import train_test_split
from sklearn import metrics
#CN Matrix
from sklearn.metrics import accuracy_score, confusion_matrix

#Algo
from sklearn.linear_model import LogisticRegression
from sklearn.neighbors import KNeighborsClassifier
from sklearn.naive_bayes import GaussianNB
from sklearn.naive_bayes import BernoulliNB
from sklearn.svm import SVC
from sklearn.svm import LinearSVC
from sklearn.ensemble import RandomForestClassifier
```

```
from sklearn.tree import DecisionTreeRegressor
from sklearn import model_selection
```

1.2 Import DataSet

In [162]:
```
dataFrame0 = pd.read_csv("F:/python/4.2/project/main/dataset/DATASET_01.csv")
dataFrame1 = pd.read_csv("F:/python/4.2/project/main/dataset/DATASET_02.csv")
dataFrame2 = pd.read_csv("F:/python/4.2/project/main/dataset/DATASET_03.csv")
dataFrame3 = pd.read_csv("F:/python/4.2/project/main/dataset/DATASET_04.csv")
dataFrame4 = pd.read_csv("F:/python/4.2/project/main/dataset/DATASET_05.csv")
dataFrame5 = pd.read_csv("F:/python/4.2/project/main/dataset/DATASET_06.csv")

dataFrame0.head()
#dataFrame1.head()
#dataFrame2.head()
#dataFrame3.head()
#dataFrame4.head()
#dataFrame5.head()
```

Out[162]:

	Unnamed: 0	Current Place	Unnamed: 2	Unnamed: 3	Place of interest
0	NaN	Place Name	Latitude	Longitude	Place Name
1	151340976.0	Goran	23.75027	90.43413	Cox's Bazar
2	151340977.0	Banasree	22.513531	88.301537	Sea Beach
3	151340978.0	Azimpur	23.7270399	90.3846895	Kaptai Lake
4	151340980.0	Niketon	23.70731	90.41548	home

	Unnamed: 5	Unnamed: 6	Food you like most	Leisure time activity
0	Latitude	Longitude	NaN	NaN
1	21.41127	91.995891	Biriyani	Movies
2	NaN	NaN	Kachchi	Sports
3	22.755208	92.277031	kacchi biryani	Series
4	23.70731	90.41548	any	movies,music

	Future plan	Typically your days are started at:
0	NaN	NaN
1	Software Engineer	LR
2	BCS/Business	LR
3	Higher Study in North America	ER
4	software Engineer	LR

1.3 Dataset Concatenate

In [165]:
```
#path = "F:/python/4.2/project/main/dataset/"
#filenames = [path+'DATASET_01.csv', 'dataset/DATASET_02.csv', 'dataset/DATASET_03.c
 #           'dataset/DATASET_05.csv', 'dataset/DATASET_06.csv']

#dataFrames = []
#for f in filenames:
```

```
#    dataFrames.append(pd.read_csv(f))
#outputFile = "dataset/finalData/finalData.csv"
#data_dir= glob.glob(os.path.join(path, '*.csv'))
#print(os.listdir(data_dir))
```

In [62]:
```
#filenames = glob('dataset/DATASET*.csv')
#dataFrames = [pd.read_csv(f) for f in filenames]
```

In [201]:
```
def concatenate (indir = "F:/python/4.2/project/main/dataset/", outfile = "F:/python/
    #os.chdir(indir)
    #fileList = glob.glob(indir+"*.csv")
    fileList = [f for f in listdir(indir) if isfile(join(indir, f))]
    dfList = []
    #colnames=["ID"]
    for filename in fileList:
        print(filename)
        df = pd.read_csv(filename, header= None)
        dfList.append(df)
    concateDf= pd.concat(dfList, axis=0)
    concateDf.to_csv(outfile, index = None)
concatenate()
```

```
DATASET_01.csv
DATASET_02.csv
DATASET_03.csv
DATASET_04.csv
DATASET_05.csv
DATASET_06.csv
```

1.3.1 Column Add from other Dataset

In [212]:
```
# Loading data and preprocessing
filePath1 = "F:/python/4.2/project/main/dataset/Total/TotalfinalData_1.csv"
filePath2 = "F:/python/4.2/project/main/extra/EXTENDED_1.csv"
mergedFile = "F:/python/4.2/project/main/dataset/Total/TotalfinalData_3.csv"

df1 = pd.read_csv(filePath1)
df2 = pd.read_csv(filePath2)
columnsNeed = ["ID", "AcademicResult", "Co_curri", "Skill","Achi","Physical","Higher"
for column in df2.columns:
    dropChecker = True
    for colName in columnsNeed:
        if column == colName:
            dropChecker = False
            break

    if dropChecker == True:
        df2.drop(column, axis=1, inplace=True)
```

```
merged = df1.merge(df2, on="ID")
# for column in df1
merged.to_csv(mergedFile, index=False)

data_frame = pd.read_csv("F:/python/4.2/project/main/dataset/Total/TotalfinalData_fi
```

1.4 Dataset Processed

```
In [206]: cols = ["ID", "Name", "OLat", "OLong","PI", "PILat", "PIlong", "Food", "Leisure", "F
          df = pd.read_csv("F:/python/4.2/project/main/dataset/Total/TotalfinalData_final.csv"
          df.columns = [''] * len(df.columns)
          df = df[1:]
          df.reset_index(drop=True)
          df.columns = cols

          df.drop(['Name'], axis = 1, inplace = True)
          df.drop(['ID'], axis = 1, inplace = True)
          df.head()
```

Out[206]:

	OLat	OLong	PI	PILat	PIlong	Food	\
1	23.75027	90.43413	Cox's Bazar	21.41127	91.995891	Biriyani	
2	22.513531	88.301537	Cox's Bazar	20.9232	92.2676	Biriyani	
3	23.7270399	90.3846895	Kaptai Lake	22.755208	92.277031	Biriyani	
4	23.70731	90.41548	home	23.70731	90.41548	any	
5	22.301411	70.822357	home	22.301411	70.822357	Sea food	

	Leisure	FP	LR	AcademicResult	\
1	Movies	Software Engineer	LR	3.13	
2	Sports	BCS/Business	LR	2.71	
3	Series	Higher Study in North America	ER	3.59	
4	Movies, Music	Software Engineer	LR	2.92	
5	Music	Businessman	LR	2.53	

	Co_curri	Skill	Achi	Physical	Higher
1	None	None	1.0	Yes	No
2	None	Web Development	5.0	Yes	Yes
3	Club committee	None	2.0	Yes	No
4	None	None	1.0	Yes	No
5	None	Java	3.0	No	Yes

1.5 Label the Dataset

```
In [238]: df.dropna(axis = 0, inplace = True)
          lb_make = LabelEncoder()
          df["PI"] = lb_make.fit_transform(df["PI"])
          df["Food"] = lb_make.fit_transform(df["Food"])
          df["Leisure"] = lb_make.fit_transform(df["Leisure"])
```

```
df["FP"] = lb_make.fit_transform(df["FP"])
df["LR"] = lb_make.fit_transform(df["LR"])
df["Co_curri"] = lb_make.fit_transform(df["Co_curri"])
df["Skill"] = lb_make.fit_transform(df["Skill"])
df["Physical"] = lb_make.fit_transform(df["Physical"])
df["Higher"] = lb_make.fit_transform(df["Higher"])
df.head()
```

Out[238]:

	OLat	OLong	PI	PILat	PIlong	Food	Leisure	FP	\
29	23.828959	90.375672	33	48.856613	2.352222	44	4	35	
105	23.7325976	90.4025838	45	40.463669	-3.74922	38	42	31	
108	23.738078	90.372485	9	21.43392	91.98703	47	39	14	
43	20.53829	86.30937	1	21.8311	92.368629	20	20	27	
57	20.53829	86.30937	36	20.6237016	92.3233948	9	45	33	

	LR	AcademicResult	Co_curri	Skill	Achi	Physical	Higher
29	1	3.41	1	2	3.0	1	1
105	1	3.36	1	0	3.0	1	1
108	1	3.07	1	0	1.0	0	0
43	1	2.89	1	1	2.0	0	0
57	1	3.07	1	4	2.0	0	0

1.6 Classifier - Problem 1

In [239]:
```
df = sklearn.utils.shuffle(df)
x = df.drop("Higher",axis = 1).values
y = df["Higher"].values
```

1.6.1 Decision Tree - Accuracy Test

In [253]:
```
test_size = int(0.2*len(x))
train_x = x[:-test_size]
train_y = y[:-test_size]
test_x = x[-test_size:]
test_y = y[-test_size:]

clf = DecisionTreeClassifier()
clf.fit(train_x, train_y)
clf.score(test_x, test_y)

#print(clf.predict([train_x[7]]))
```

Out[253]: 0.46153846153846156

1.6.2 Test single Data - Decision Tree

In [225]:
```
print(clf.predict([train_x[6]]))
#1-Yes, 0 -No
```

[1]

1.6.3 Gaussian Naive Bayes - Accuracy Test

In [231]:
```
#Gaussian Naive bayes
clf = GaussianNB()
clf.fit(train_x, train_y)
clf.score(test_x, test_y)
```

Out[231]: 0.65384615384615385

1.6.4 Bernouli Naive Bayes

In [332]:
```
from sklearn.naive_bayes import BernoulliNB
model1=BernoulliNB()
model1.fit(X_train,y_train)
predict1=model1.predict(X_test)
x=y_test.iloc[:].values

length1=len(predict1)
correct1=0
for i in range(length1):
    if(x[i]==predict1[i]):
        correct1=correct1+1
print(correct1)

accuracy1=correct1*100/len(x)
print(accuracy1)
```

```
9
56.25
```

In [333]:
```
print(metrics.confusion_matrix(y_test,predict1,labels=[0,1,2]))
cm=metrics.confusion_matrix(y_test,predict1,labels=[0,1,2])
fig = plt.figure()
ax = fig.add_subplot(111)
cax = ax.matshow(cm)
plt.title('Confussion Matrix for Bernoulli Naive Bayes')
plt.xlabel('Prediction')
plt.ylabel('True')
plt.show()
```

```
[[0 7 0]
 [0 9 0]
 [0 0 0]]
```



1.6.5 svm with rbf kernel

```
In [261]: #svm with rbf karnel
          df = sklearn.utils.shuffle(df)
          x = df.drop("Higher",axis = 1).values
          y = df["Higher"].values

          x = preprocessing.scale(x)
          test_size = int(0.2*len(x))
          train_x = x[:-test_size]
          train_y = y[:-test_size]
          test_x = x[-test_size:]
          test_y = y[-test_size:]

          clf = svm.SVR(kernel = "rbf")
          clf.fit(train_x, train_y)
          abs(clf.score(test_x, test_y))
```

```
C:\Users\nasim\Anaconda3\envs\workshop\lib\site-packages\sklearn\utils\validation.py:475: DataC
  warnings.warn(msg, DataConversionWarning)
```

```
Out[261]: 0.40339571140762054
```

1.6.6 SVM

In [325]:
```
X=df.drop('Higher',axis=1)
y=df['Higher']
X_train,X_test,y_train,y_test=train_test_split(X,y,test_size=0.12)

model=svm.SVC(kernel='linear')
model.fit(X_train,y_train)
```

Out[325]:
```
SVC(C=1.0, cache_size=200, class_weight=None, coef0=0.0,
  decision_function_shape='ovr', degree=3, gamma='auto', kernel='linear',
  max_iter=-1, probability=False, random_state=None, shrinking=True,
  tol=0.001, verbose=False)
```

In [330]:
```
predict=model.predict(X_test)
x=y_test.iloc[:].values
length=len(predict)

correct=0
for i in range(length):
    if(predict[i]==x[i]):
        correct+=1
print(correct)

accuracy=correct*100/len(x)
print(accuracy)
```

```
9
56.25
```

In [331]:
```
#print("{0}".format(metrics.confusion_matrix(y_test,predict,labels=[0,1,2])))
print(metrics.confusion_matrix(y_test,predict,labels=[0,1,2]))
cm=metrics.confusion_matrix(y_test,predict,labels=[0,1,2])
fig = plt.figure()
ax = fig.add_subplot(111)
cax = ax.matshow(cm)
plt.title('Confussion Matrix for SVM')
plt.xlabel('Prediction')
plt.ylabel('True')
plt.show()
```

```
[[2 5 0]
 [2 7 0]
 [0 0 0]]
```



1.6.7 Random Forest Classifier

```
In [356]: model=RandomForestClassifier()
          mode2=DecisionTreeRegressor()

          model.fit(X_train,y_train)
          mode2.fit(X_train,y_train)

          predict3=model3.predict(X_test)
          predict4=model4.predict(X_test)

          length3=len(predict3)
          correct3=0
          for i in range(length3):
              if(x[i]==predict3[i]):
                  correct3=correct3+1
          print(correct3)
          accuracy3=correct3*100/len(x)
          print(accuracy3)
```

```
9
56.25
```

```
In [335]: print(metrics.confusion_matrix(y_test,predict3,labels=[0,1,2]))
          cm=metrics.confusion_matrix(y_test,predict3,labels=[0,1,2])
          fig = plt.figure()
          ax = fig.add_subplot(111)
          cax = ax.matshow(cm)
          plt.title('Confussion Matrix for Random Forest')
          plt.xlabel('Prediction')
          plt.ylabel('True')
          plt.show()
```

```
[[0 7 0]
 [2 7 0]
 [0 0 0]]
```



1.6.8 Box Plot for Algorithm Comparison

```
In [345]: models = []
          models.append(('DT', LogisticRegression()))
          models.append(('KNN', KNeighborsClassifier()))
          models.append(('GB', GaussianNB()))
          models.append(('NB', BernoulliNB()))
          models.append(('SVC', SVC()))
          models.append(('LSVC', LinearSVC()))
```

```
models.append(('RFC', RandomForestClassifier()))

seed = 7
results = []
names = []
X = X_train
Y = y_train

for name, model in models:
    kfold = model_selection.KFold(
        n_splits=10, random_state=seed)
    cv_results = model_selection.cross_val_score(
        model, X, Y, cv=kfold, scoring='accuracy')
    results.append(cv_results)
    names.append(name)
    msg = "%s: %f " % (name, cv_results.mean()*100)
    print(msg)
```

```
DT: 56.363636
KNN: 51.969697
GB: 51.363636
NB: 59.772727
SVC: 62.348485
LSVC: 54.469697
RFC: 58.636364
```

In [346]:
```
fig = plt.figure()
fig.suptitle('Algorithm Comparison')
ax = fig.add_subplot(111)
plt.boxplot(results)
ax.set_xticklabels(names)
plt.show()
```



1.7 Classifier - Problem 2

```
In [263]: df = sklearn.utils.shuffle(df)
          x = df.drop("Physical",axis = 1).values
          y = df["Physical"].values

In [283]: #Decision Tree
          test_size = int(0.2*len(x))
          train_x = x[:-test_size]
          train_y = y[:-test_size]
          test_x = x[-test_size:]
          test_y = y[-test_size:]

          clf = DecisionTreeClassifier()
          clf.fit(train_x, train_y)
          #clf.score(test_x, test_y)
          print('Accuracy:', clf.score(test_x, test_y))

          #print(clf.predict([train_x[7]]))

Accuracy: 0.384615384615


In [295]: #Gaussian Naive bayes
          clf = GaussianNB()
```

```
clf.fit(train_x, train_y)
#clf.score(test_x, test_y)
print('Accuracy:', clf.score(test_x, test_y))
```

```
Accuracy: 0.461538461538
```

```
In [297]: #svm with rbf karnel
          df = sklearn.utils.shuffle(df)
          x = df.drop("Higher",axis = 1).values
          y = df["Higher"].values

          x = preprocessing.scale(x)
          test_size = int(0.2*len(x))
          train_x = x[:-test_size]
          train_y = y[:-test_size]
          test_x = x[-test_size:]
          test_y = y[-test_size:]

          clf = svm.SVR(kernel = "rbf")
          clf.fit(train_x, train_y)
          #abs(clf.score(test_x, test_y))
          print('Accuracy:', abs(clf.score(test_x, test_y)))
```

```
Accuracy: 0.588040596803
```

```
C:\Users\nasim\Anaconda3\envs\workshop\lib\site-packages\sklearn\utils\validation.py:475: DataC
  warnings.warn(msg, DataConversionWarning)
```

1.7.1 SVM

```
In [363]: X=df.drop('LR',axis=1)
          y=df['LR']
          X_train,X_test,y_train,y_test=train_test_split(X,y,test_size=0.12)

          model=svm.SVC(kernel='linear')
          model.fit(X_train,y_train)
```

```
Out[363]: SVC(C=1.0, cache_size=200, class_weight=None, coef0=0.0,
            decision_function_shape='ovr', degree=3, gamma='auto', kernel='linear',
            max_iter=-1, probability=False, random_state=None, shrinking=True,
            tol=0.001, verbose=False)
```

```
In [364]: predict=model.predict(X_test)
          x=y_test.iloc[:].values
          length=len(predict)
```

```
correct=0
for i in range(length):
    if(predict[i]==x[i]):
        correct+=1
print(correct)

accuracy=correct*100/len(x)
print(accuracy)
```

```
13
81.25
```

In [366]:
```
#print("{0}".format(metrics.confusion_matrix(y_test,predict,labels=[0,1,2])))
print(metrics.confusion_matrix(y_test,predict,labels=[0,1,2]))
cm=metrics.confusion_matrix(y_test,predict,labels=[0,1,2])
fig = plt.figure()
ax = fig.add_subplot(111)
cax = ax.matshow(cm)
plt.title('Confussion Matrix for SVM')
plt.xlabel('Prediction')
plt.ylabel('True')
plt.show()
```

```
[[ 0  3  0]
 [ 0 13  0]
 [ 0  0  0]]
```



1.7.2 Random Forest Classifier

In [367]:
```
model=RandomForestClassifier()
mode2=DecisionTreeRegressor()

model.fit(X_train,y_train)
mode2.fit(X_train,y_train)

predict3=model3.predict(X_test)
predict4=model4.predict(X_test)

length3=len(predict3)
correct3=0
for i in range(length3):
    if(x[i]==predict3[i]):
        correct3=correct3+1
print(correct3)
accuracy3=correct3*100/len(x)
print(accuracy3)
```

```
8
50.0
```

In [368]:
```
print(metrics.confusion_matrix(y_test,predict3,labels=[0,1,2]))
cm=metrics.confusion_matrix(y_test,predict3,labels=[0,1,2])
fig = plt.figure()
ax = fig.add_subplot(111)
cax = ax.matshow(cm)
plt.title('Confussion Matrix for Random Forest')
plt.xlabel('Prediction')
plt.ylabel('True')
plt.show()
```

```
[[0 3 0]
 [5 8 0]
 [0 0 0]]
```



1.7.3 Boxplot for algorithm comparison

```
In [369]: models = []
          models.append(('DT', LogisticRegression()))
          models.append(('KNN', KNeighborsClassifier()))
          models.append(('GB', GaussianNB()))
          models.append(('NB', BernoulliNB()))
          models.append(('SVC', SVC()))
          models.append(('LSVC', LinearSVC()))
          models.append(('RFC', RandomForestClassifier()))

          seed = 7
          results = []
          names = []
          X = X_train
          Y = y_train

          for name, model in models:
              kfold = model_selection.KFold(
                  n_splits=10, random_state=seed)
              cv_results = model_selection.cross_val_score(
                  model, X, Y, cv=kfold, scoring='accuracy')
              results.append(cv_results)
              names.append(name)
```

```
        msg = "%s: %f " % (name, cv_results.mean()*100)
        print(msg)
```

```
DT: 73.712121
KNN: 70.227273
GB: 62.727273
NB: 75.227273
SVC: 77.727273
LSVC: 68.636364
RFC: 69.242424
```

```
In [370]: fig = plt.figure()
          fig.suptitle('Algorithm Comparison')
          ax = fig.add_subplot(111)
          plt.boxplot(results)
          ax.set_xticklabels(names)
          plt.show()
```



1.7.4 Error Rate Calculation

```
In [351]: #error rate = (1 - (test_y / train_y)) * 100
```

```
In [ ]:
```