

# **CSE4214: Assignment**

Monday, March 19, 2019

*Zabir Haque*

**MD Abdullah Al Nasim**  
**150104085**

---

## LAB 01

---

### Question 1

#### **append() and extend() function in python**

(a) *Append Function*

```
append(): Appends object at the end.  
x = [1, 2, 3]  
x.append([4, 5])  
print (x)
```

(b) *What is the output?*

```
[1, 2, 3, [4, 5]]
```

(c) *Extend Function*

```
extend(): Extends list by appending elements from the iterable.
```

(d) *Write the extend Code*

```
x = [1, 2, 3]  
x.extend([4, 5])  
print (x)
```

(e) *What is the output?*

```
[1, 2, 3, 4, 5]
```

### Question 2

#### **Zip and Enumerate in python**

(a) What does `zip()` do in python?

**Python `zip()`:** The `zip()` function take iterables (can be zero or more), makes iterator that aggregates elements based on the iterables passed, and returns an iterator of tuples.

(b) Why do we use `zip` in Python?

**Python `zip()`:** `zip()` in Python. The purpose of `zip()` is to map the similar index of multiple containers so that they can be used just using as single entity. Unzipping means converting the zipped values back to the individual self as they were.

(c) What is the use of `zip` in Python?

Basically, `.zip` is a container itself. It holds the real file inside. Similarly, Python `zip` is a container that holds real data inside. Python `zip` function takes iterable elements as input, and returns iterator.

### Question 3

**How do you create a dictionary in Python?**

- i Create a new dictionary-In order to construct a dictionary you can start with an empty one.
- ii Add a value to the dictionary.
- iii Remove a key and it's value.
- iv Check the length.
- v Test the dictionary.
- vi Get a value of a specified key.
- vii Print all keys with a for loop.
- viii Print all key and values.

### Question 4

**How to index in python?**

There are 2types of indexing.

**1.Pure integer indexing**

**2.Boolean indexing**

(a) *Pure integer indexing:*

Integer array indexing allows selection of arbitrary items in the array based on their N-dimensional index. Each integer array represents a number of indexes into that dimension. When the index consists of as many integer arrays as the array being indexed has dimensions, the indexing is straight forward, but different from slicing.

**Example:**

```
»> x = np.array([[1, 2], [3, 4], [5, 6]])
»> x[[0, 1, 2], [0, 1, 0]]
array([1, 4, 5])
```

(b) *Boolean indexing:*

This advanced indexing occurs when obj is an array object of Boolean type, such as may be returned from comparison operators. A single boolean index array is practically identical to `x[obj.nonzero()]` where, as described above, `obj.nonzero()` returns a tuple (of length `obj.ndim`) of integer index arrays showing the True elements of obj. However, it is faster when `obj.shape == x.shape`.

If `obj.ndim == x.ndim`, `x[obj]` returns a 1-dimensional array filled with the elements of x corresponding to the True values of obj. The search order will be row-major, C-style. If obj has True values at entries that are outside of the bounds of x, then an index error will be raised. If obj is smaller than x it is identical to filling it with False

---

## LAB 02

---

### Question 5

#### What is the Lambda expression?

A lambda function is a small anonymous function. A lambda function can take any number of arguments, but can only have one expression. **The power of lambda is better shown when you use them as an anonymous function inside another function.** **Syntax:-** `lambda arguments: expression` The expression is evaluated and returned.

### Question 6

#### What is Slicing in python?

We can also call out a range of characters from the string. Say we would like to just print the word Shark. We can do so by creating a slice, which is a sequence of characters within an original string. With slices, we can call multiple character values by creating a range of index numbers separated by a colon string[x:y]. Slicing can not only be used for lists, tuples or arrays, but custom data structures as well, with the slice object. **Slicing arguments:** [start:end:step], [row:column], [start:end,start:end]

## Question 7

Listing 1: Lab 1 and 2 sample Code

```
1
2 # coding: utf-8
3
4 # # Lab 01
5
6 # ## List
7
8 # In[5]:
9
10
11 for i in range (1, 10, 1):
12     print(i);
13
14 list1 = [0,0,10]
15
16 print(min(list1))
17
18 L = ['A', 'B', 'C']
19
20 for x in L:
21     print(x)
22
23 for i in range (len(L)):
24     L[i] = L[i] + ' is zombie '
25
26 for x in L:
27     print(x)
28
29
30 # ### append
31
32 # In[6]:
33
34
35 x = [1,2,3]
36 x.append([4,5])
37 print(x)
```

```
38
39
40 # ### extend
41
42 # In [7]:
43
44
45 x.extend([8,9])
46 print(x)
47
48
49 # ### enumerate, zip
50
51 # In [8]:
52
53
54 days = [ "Sun", "Mon", "Tue" ]
55 daysFr = [ "Dim", "Lun", "Mar" ]
56
57 for m in range (len (days)):
58     print(m+1,days[m])
59
60 for i,m in enumerate (days, start=1):
61     print(i,m)
62
63 for m in zip (days,daysFr):
64     print(m)
65
66 for i,m in enumerate (zip(days,daysFr), start=1):
67     print(i,m[0], "=",m[1], "in French")
```

## Question 8

### What is SVM?

SVM is a supervised machine learning algorithm which can be used for classification or regression problems. It uses a technique called the kernel trick to transform your data and then based on these transformations it finds an optimal boundary between the possible outputs. Simply put, it does some extremely complex data transformations, then figures out how to separate your data based on the labels or outputs you've defined.

---

## LAB 03

---

## Question 9

Listing 2: Lab 3 sample code

```
1
2 # coding: utf-8
3
4 # In [1]:
5
6
7 import pandas as pd
8 import numpy as np
9
10
11 # In [5]:
12
13
14 s = pd.Series([0, 1, 4, 9, 16, 25], name='squares')
15 print(s.index)
16 print(s.values, s.index)
17 print(s[2:4])
18
19
20 # In [6]:
21
22
23 pop2014 = pd.Series([100, 99.3, 95.5], index=['java', 'c', 'c++'])
24 print(pop2014)
25
26
27 # In [11]:
28
29
30 pop2015 = pd.Series({'java':100, 'c':99.3, 'c++':95.5})
31 print(pop2015)
32
33
34 # In [12]:
35
36
37 print(pop2014.index)
38
39
40 # In [14]:
41
42
43 print(pop2014.iloc[0:2])
44 print(pop2014.loc['c'])
45
46
```

```
47 # In [15]:
48
49
50 twoYears = pd.DataFrame({'2014': pop2014, '2015': pop2015 })
51 print(twoYears)
52
53
54 # In [16]:
55
56
57 twoYears['Average'] = 0.5* (twoYears['2014']+twoYears['2015'])
58 print(twoYears)
59
60
61 # In [18]:
62
63
64 test_data = pd.DataFrame
65 (np.random.choice(['a','b','c','d'], (3,3)),
66 index=[1,2,3], columns=['AA','BB','CC'])
67 print(test_data)
68
69
70 # In [19]:
71
72
73 open('tips.csv','r').readlines()[10]
74
75
76 # In [20]:
77
78
79 tips=pd.read_csv('tips.csv')
80 tips.head()
81
82
83 # In [21]:
84
85
86 print(tips[:10])
87
88
89 # In [22]:
90
91
92 tips.mean()
93
94
95 # In [23]:
```



```
96
97
98 tips['tip'].mean()
99
100
101 # In[24]:
102
103
104 tips.dtypes
105
106
107 # In[25]:
108
109
110 tips.describe()
111
112
113 # In[26]:
114
115
116 tips.groupby('gender').mean()
117
118
119 # In[29]:
120
121
122 t=tips.groupby(['gender','smoker']).mean()
123 print(t['tip'])
124
125
126 # In[30]:
127
128
129 pd.pivot_table(tips, 'total_bill', 'gender', 'smoker')
130
131
132 # In[31]:
133
134
135 pd.pivot_table(tips, 'total_bill',
136 ['gender', 'smoker'], ['day', 'time'])
137
138
139 # In[34]:
140
141
142 from matplotlib import pyplot as plt
143 url='http://archive.ics.uci.edu/ml/
144 machine-learning-databases/iris/iris.data'
```

```
145 df = pd.read_csv(url)
146 df.head()
147
148
149 # In [35]:
150
151
152 df.columns = ['sepal_length', 'sepal_width',
153 'petal_length', 'petal_width', 'flower_type']
154 df.head()
155
156
157 # In [36]:
158
159
160 df['flower_type'] = df['flower_type'].astype('category')
161
162
163 # In [39]:
164
165
166 df.flower_type = df.flower_type.cat.rename_categories([0,1,2])
167 df.head()
168 print(df[40:50])
169
170
171 # In [40]:
172
173
174 print(len(df))
175
176
177 # In [41]:
178
179
180 df['flower_type'].describe()
181
182
183 # In [42]:
184
185
186 df.hist()
187 plt.show()
188
189
190 # In [43]:
191
192
193 pd.scatter_matrix(df, diagonal='kde')
```

```
194 plt.show()  
195  
196  
197 # In [44]:  
198  
199  
200 df.to_csv('iris_normalized.csv')
```

## Question 10

### What is KNN?

A powerful classification algorithm used in pattern recognition. K nearest neighbors stores all available cases and classifies new cases based on a similarity measure (e.g. distance function). A non-parametric lazy learning algorithm (An Instancebased Learning method

## Question 11

### Write algorithm of KNN

- i All the instances correspond to points in an n-dimensional feature space.
- ii Each instance is represented with a set of numerical attributes.
- iii Each of the training data consists of a set of vectors and a class label associated with each vector.
- iv Classification is done by comparing feature vectors of different K nearest points.
- v Select the K-nearest examples to E in the training set.
- vi Assign E to the most common class among its K-nearest neighbors.

## Question 12

### How to choose K?

- i If K is too small it is sensitive to noise points.
- ii Larger K works well. But too large K may include majority points from other classes.
- iii Rule of thumb is  $K < \sqrt{n}$ , n is number of examples.

## Question 13

### Strength of KNN

- i If Very simple and intuitive.
- ii Can be applied to the data from any distribution.
- iii Good classification if the number of samples is large enough.

## Question 14

### Weakness of KNN

- i Takes more time to classify a new example.
- ii need to calculate and compare distance from new example to all other examples.
- iii Choosing k may be tricky.
- iv Need large number of samples for accuracy.