An IoT-Enabled Hybrid Soft Sensor for Real-Time Residual-Moisture Monitoring and Resource Accounting in Compact Wool Scouring Machines

Robiya Tuguzbaeva, Sherkul Khakimov, Firuza Dustova, and Ruzimurod Rosulov

***Abstract*—Wool scouring is among the most water- and energy-intensive steps in primary wool processing, yet small regional plants operate their machines without any instrumentation, and the key quality variable—residual moisture of the wool after each squeeze stage—is measured only occasionally by oven drying. This paper presents a low-cost Internet of Things (IoT) framework for a compact five-bowl wool scouring machine with an improved ribbed-drum/mesh squeezing device. An ESP32-based edge node acquires bowl temperature, liquor level and turbidity, squeeze-drum angular speed, make-up water flow and electrical power, and streams them over Wi-Fi (HTTP/MQTT) to a server that provides storage, alarms, per-kilogram resource indicators and a bilingual web/mobile application. We propose a hybrid soft sensor in which a design-of-experiments (DoE) regression model of the squeezing device, obtained from a 2^3 full-factorial experiment, serves as a physics-informed prior, and an online ridge-regression correction learned from sparse laboratory samples accounts for operating conditions. In a [TODO: N]-shift field deployment at [TODO: plant], the soft sensor achieved an RMSE of [TODO: x] % against oven-dry reference measurements, compared with [TODO: y] % for the DoE model alone and [TODO: z] % for a purely data-driven model, while the system delivered [TODO: packet-delivery ratio] % of messages with a median latency of [TODO: ms]. The measured specific energy and water consumption were [TODO: kWh/kg] and [TODO: L/kg].**

***Index Terms*—Industrial Internet of Things, soft sensor, wool scouring, edge computing, resource efficiency, textile manufacturing, digital twin.**

I. Introduction

PRIMARY wool processing—opening, scouring, squeezing and drying—determines the quality and cost of all downstream textile products. Scouring removes grease, suint and mineral dirt in a sequence of bowls filled with hot alkaline liquor; between bowls, squeezing devices remove the dirty liquor from the wool. Insufficient squeezing carries dirt into the next bowl, shortens liquor life and increases water and detergent consumption, and every percentage point of residual moisture must later be evaporated in the dryer. Scouring is a major contributor to the water footprint and life-cycle burden of wool products [3], [4], and its highly polluted effluent requires costly treatment [5], [6].

In regions such as Uzbekistan, where wool comes largely from Karakul sheep and is processed in small, decentralised plants, large centralised scouring lines are uneconomic. A compact, resource-saving machine with an improved squeezing device (ribbed squeeze drum, guide slat drum and wrapped mesh surface) was developed and patented in previous work [1], [2]; factory tests reported a reduction of residual moisture from 65–70 % to 55–60 % and of installed power from 13 to 4.2 kW. However, such machines are operated without sensors: operators cannot see liquor temperature or dirtiness, moisture is measured only by occasional oven-dry samples, and resource consumption is not accounted per kilogram of wool.

Related work. Industrial IoT increasingly moves analytics to the edge of the network [7], [8], and IoT/big-data frameworks have been demonstrated for health-state monitoring, fault detection and cloud–edge–device collaborative monitoring of manufacturing systems [9]–[11]. Low-cost nodes make such monitoring affordable [12], [13], and digital retrofitting is the practical route for legacy machines that cannot be replaced [14]. Digital twins built from sensor data extend this to model-based operation [15]–[17]. In the textile sector, Industry 4.0 and AI work concentrates on spinning, inspection and garment production [18]–[21]; energy benchmarking of wet processing in SMEs has been proposed but relies on manual audits [22].

Soft sensors estimate hard-to-measure quality variables from routine measurements [23]. Purely data-driven models need many labelled samples, which are expensive when the reference is a laboratory analysis [24]; gray-box and physics-informed models reduce this need and improve explainability [25], [26], while adaptive schemes keep the model calibrated online [27]. In IoT settings, self-improving soft sensors have been used to reduce costly measurements [28]. To our knowledge, however, no work instruments the wool scouring/squeezing stage, and none uses a design-of-experiments model of the machine as the prior of an IoT soft sensor.

Contributions.

1) A low-cost (≈ US$ 200) IoT architecture for wool scouring machines with an ESP32 edge node, HTTP/MQTT transport, server-side analytics and an installable bilingual (EN/RU) web/mobile application.
2) A hybrid soft sensor for residual moisture that combines a 2^3 factorial regression model of the squeezing device (geometry prior) with an online, regularised correction

The authors are with the Tashkent Institute of Textile and Light Industry, 5 Shohjahon Street, Tashkent 100100, Uzbekistan (e-mail: trobiya89@mail.ru; lionandlion9@mail.ru; firuzadustovahamraevna@mail.ru; rasulov.ruzimurad@mail.ru).

ORCID iDs: R. Tuguzbaeva 0009-0001-8480-9696; S. Khakimov 0000-0002-1933-1948; F. Dustova 0009-0007-5928-3198; R. Rosulov 0000-0003-0590-3121.

Corresponding author: Robiya Tuguzbaeva (e-mail: trobiya89@mail.ru).

[TODO: Funding: state grant 7/275, etc.]




Fig. 1. Architecture of the proposed IoT framework.

for operating conditions, calibrated from sparse laboratory samples.

3) Real-time per-kilogram resource indicators (kWh/kg, L/kg) and rule-based fault alarms (heater failure, low level, dirty liquor, drum speed deviation).
4) A field deployment on an industrial machine with [TODO: N] shifts of data, with open code at https://github.com/nasin0764-bit/woolwash-iot and [TODO: open dataset].

II. Machine and Squeezing Model

The machine comprises five bowls (2.5 m^3 each); moving rakes (length 250 mm, linear speed [TODO: 0.15] m/s) transport the wool, and each bowl is followed by a squeezing device with a ribbed drum of diameter D, a mesh of hole diameter d and a drum–mesh gap h [1].

A. DoE prior

A 2^3 full-factorial experiment with three replicates ($N = 8$, $m = 3$) with coded factors $X_1 = (d - 2)/1$, $X_2 = (D - 250)/50$, $X_3 = (h - 3)/1$ (mm) gave, after Student's test ($t_{0.05;16} = 2.12$), the adequate model ($F = 0.71 < F_{0.05;4;16} = 3.01$)

$$W_0 = 57.31 + 0.81X_1 - 0.95X_2 + 0.30X_3 \quad [\%]. \tag{1}$$

B. Hybrid soft sensor

Equation (1) captures geometry only. During operation, moisture also depends on the drum angular speed ω, the feed rate q, the liquor temperature T and the liquor turbidity τ. With normalised deviations $\boldsymbol{\phi} = [(\omega - \omega_0)/s_\omega, (q - q_0)/s_q, (T - T_0)/s_T, (\tau - \tau_0)/s_\tau]^\top$ we model

$$\hat{W} = W_0(d, D, h) + \mathbf{w}^\top \boldsymbol{\phi} + c, \tag{2}$$

where $(\mathbf{w}, c)$ minimise $\sum_i (W_i - W_{0,i} - \mathbf{w}^\top \boldsymbol{\phi}_i - c)^2 + \lambda \|\mathbf{w}\|^2$ over laboratory samples W_i taken after the squeezer and dried at 105 °C. The model is refitted on the server each time a sample is added; with no samples it reduces to the DoE prior. [TODO: Compare with: DoE only; ridge/GPR/random forest without prior; report learning curve vs number of samples.]

III. IoT System Architecture

Fig. 1 shows the architecture. The node supports both HTTP and MQTT; the choice trades broker infrastructure against energy and overhead, as quantified in recent protocol comparisons [29], [30]. [TODO: Describe sensor placement (photo), sampling period (2 s), payload size, power supply, enclosure, calibration of each sensor (method and uncertainty).]

TABLE I
Residual-moisture prediction on held-out field samples

Model	RMSE (%)	MAE (%)	R^2
DoE prior only (1)	[TODO:]	[TODO:]	[TODO:]
Data-driven ridge (no prior)	[TODO:]	[TODO:]	[TODO:]
Random forest (no prior)	[TODO:]	[TODO:]	[TODO:]
Hybrid (proposed)	[TODO:]	[TODO:]	[TODO:]

IV. Experimental Setup

[TODO: Plant, dates, wool type (spring/autumn Karakul), number of shifts, lab sampling protocol (every 30 min, 3 replicates), train/test split by day, network environment (AP distance, RSSI).]

V. Results

A. Soft-sensor accuracy

B. Resource indicators

[TODO: kWh/kg and L/kg per shift, baseline vs improved machine, mean ± SD, n.]

C. Communication performance

[TODO: Packet delivery ratio, latency distribution, outages, energy of node.]

D. Fault detection

[TODO: Detection delay and false-alarm rate for heater-off, low-level, drum-speed scenarios.]

VI. Discussion and Limitations

[TODO: Generalisation across wool types, sensor fouling (turbidity probes in alkaline liquor), Wi-Fi in wet halls, scaling to multiple plants, security (device token, TLS).]

VII. Conclusion

[TODO:]

References

[1] R. B. Tuguzbayeva, "Improvement of the working parts of a wool washing machine," Ph.D. dissertation, Tashkent Inst. Textile Light Ind., Tashkent, Uzbekistan, 2024.
[2] R. B. Tuguzbayeva *et al.*, "Device for squeezing wool in a wool washing bowl," Uzbekistan Utility Model Patent FAP 02351, 2023. [TODO: check inventors]
[3] X. Li *et al.*, "Water footprint assessment of wool products with a low-water footprint baseline," *Sustain. Prod. Consum.*, vol. 34, pp. 310–317, Nov. 2022, doi: 10.1016/j.spc.2022.09.023.
[4] I. Bianco, G. Picerno, and G. A. Blengini, "Life cycle assessment (LCA) of worsted and woollen processing in wool production: ReviWool® noils and other wool co-products," *J. Clean. Prod.*, vol. 415, Art. no. 137877, Aug. 2023, doi: 10.1016/j.jclepro.2023.137877.
[5] C. Shi *et al.*, "Inorganic composite coagulant for wool scouring wastewater treatment: Performance, kinetics and coagulation mechanism," *Sep. Purif. Technol.*, vol. 313, Art. no. 123482, May 2023, doi: 10.1016/j.seppur.2023.123482.
[6] T. Sinisaari, J. Nieminen, A. Ora, M. Mänttäri, and T. Rissanen, "Performance comparison of four polymeric ultrafiltration membranes for wool scouring effluent treatment," *Water Resour. Ind.*, vol. 34, Art. no. 100333, Dec. 2025, doi: 10.1016/j.wri.2025.100333.

[7] T. Qiu, J. Chi, X. Zhou, Z. Ning, M. Atiquzzaman, and D. O. Wu, "Edge computing in industrial Internet of Things: Architecture, advances and challenges," *IEEE Commun. Surveys Tuts.*, vol. 22, no. 4, pp. 2462–2488, 4th Quart. 2020, doi: 10.1109/COMST.2020.3009103.
[8] S. Deng, H. Zhao, W. Fang, J. Yin, S. Dustdar, and A. Y. Zomaya, "Edge intelligence: The confluence of edge computing and artificial intelligence," *IEEE Internet Things J.*, vol. 7, no. 8, pp. 7457–7469, Aug. 2020, doi: 10.1109/JIOT.2020.2984887.
[9] W. Yu, Y. Liu, T. Dillon, W. Rahayu, and F. Mostafa, "An integrated framework for health state monitoring in a smart factory employing IoT and big data techniques," *IEEE Internet Things J.*, vol. 9, no. 3, pp. 2443–2454, Feb. 2022, doi: 10.1109/JIOT.2021.3096637.
[10] W. Yu, Y. Liu, T. Dillon, and W. Rahayu, "Edge computing-assisted IoT framework with an autoencoder for fault detection in manufacturing predictive maintenance," *IEEE Trans. Ind. Informat.*, vol. 19, no. 4, pp. 5701–5710, Apr. 2023, doi: 10.1109/TII.2022.3178732.
[11] C. Zhang, X. Zhang, J. Dong, L. Ma, C. Zhang, and K. Peng, "Trinity of safety–quality–efficiency: Cloud–edge–device collaborative monitoring for manufacturing systems with industrial validation," *IEEE Internet Things J.*, vol. 13, no. 7, pp. 12702–12715, Apr. 2026, doi: 10.1109/JIOT.2026.3652179.
[12] A. Gonzalez-Perez and S. Casteleyn, "Hypnos: A hardware and software toolkit for energy-aware sensing in low-cost IoT nodes," *IEEE Internet Things J.*, vol. 9, no. 15, pp. 13524–13541, Aug. 2022, doi: 10.1109/JIOT.2022.3145338.
[13] S. D. Kalamaras, M.-A. Tsitsimpikou, C. A. Tzenos, A. A. Lithourgidis, D. S. Pitsikoglou, and T. A. Kotsopoulos, "A low-cost IoT system based on the ESP32 microcontroller for efficient monitoring of a pilot anaerobic biogas reactor," *Appl. Sci.*, vol. 15, no. 1, Art. no. 34, Jan. 2025, doi: 10.3390/app15010034.
[14] A. Alqoud, D. Schaefer, and J. Milisavljevic-Syed, "Industry 4.0: A systematic review of legacy manufacturing system digital retrofitting," *Manuf. Rev.*, vol. 9, Art. no. 32, 2022, doi: 10.1051/mfreview/2022031.
[15] J. Leng, D. Wang, W. Shen, X. Li, Q. Liu, and X. Chen, "Digital twins-based smart manufacturing system design in Industry 4.0: A review," *J. Manuf. Syst.*, vol. 60, pp. 119–137, Jul. 2021, doi: 10.1016/j.jmsy.2021.05.011.
[16] J. Friederich, D. P. Francis, S. Lazarova-Molnar, and N. Mohamed, "A framework for data-driven digital twins of smart manufacturing systems," *Comput. Ind.*, vol. 136, Art. no. 103586, Apr. 2022, doi: 10.1016/j.compind.2021.103586.
[17] M. Perno, L. Hvam, and A. Haug, "Implementation of digital twins in the process industry: A systematic literature review of enablers and barriers," *Comput. Ind.*, vol. 134, Art. no. 103558, Jan. 2022, doi: 10.1016/j.compind.2021.103558.
[18] P. H. Han, X. Li, R. Liu, S. Zhang, and C. Yuan, "Prediction method of carding process production quality based on digital twin technology," *Textile Res. J.*, vol. 94, no. 5–6, pp. 713–724, Mar. 2024, doi: 10.1177/00405175231217120.
[19] Y. Xu *et al.*, "Zero-defect manufacturing in the textile industry: A review of current advances and challenges," *Textile Res. J.*, vol. 95, no. 1–2, pp. 194–219, Jan. 2025, doi: 10.1177/00405175241260892.
[20] G. Safavi Jahromi and S. Ghazinoory, "Clothing industry in transition from Industry 4.0 to Industry 5.0," *J. Textile Inst.*, vol. 116, no. 3, pp. 365–379, 2025, doi: 10.1080/00405000.2024.2336438.
[21] N. Ingle and W. J. Jasper, "A review of the evolution and concepts of deep learning and AI in the textile industry," *Textile Res. J.*, vol. 95, no. 13–14, pp. 1709–1737, Jul. 2025, doi: 10.1177/00405175241310632.
[22] S. Kasturi and B. A. Kannappan, "A methodological framework to benchmark and monitor energy performance in textile wet processing small and medium enterprises: Proposal and evaluation," *Energy Sustain. Dev.*, vol. 71, pp. 585–599, Dec. 2022, doi: 10.1016/j.esd.2022.11.001.
[23] Q. Sun and Z. Ge, "A survey on deep learning for data-driven soft sensors," *IEEE Trans. Ind. Informat.*, vol. 17, no. 9, pp. 5853–5866, Sep. 2021, doi: 10.1109/TII.2021.3053128.
[24] X.-H. Zhang, Y. Xu, Y.-L. He, and Q.-X. Zhu, "Novel manifold learning based virtual sample generation for optimizing soft sensor with small data," *ISA Trans.*, vol. 109, pp. 229–241, Mar. 2021, doi: 10.1016/j.isatra.2020.10.006.
[25] I. Ahmad, A. Ayub, M. Kano, and I. I. Cheema, "Gray-box soft sensors in process industry: Current practice, and future prospects in era of big data," *Processes*, vol. 8, no. 2, Art. no. 243, Feb. 2020, doi: 10.3390/pr8020243.
[26] T. Bikmukhametov and J. Jäschke, "Combining machine learning and process engineering physics towards enhanced accuracy and explainability of data-driven models," *Comput. Chem. Eng.*, vol. 138, Art. no. 106834, Jul. 2020, doi: 10.1016/j.compchemeng.2020.106834.
[27] S. H. Hasnen, M. Shahid, H. Zabiri, and S. A. A. Taqvi, "Semi-supervised adaptive PLS soft-sensor with PCA-based drift correction method for online valuation of NOx emission in industrial water-tube boiler," *Process Saf. Environ. Prot.*, vol. 172, pp. 787–801, Apr. 2023, doi: 10.1016/j.psep.2023.02.080.
[28] H.-S. Lee, S.-H. Park, and S.-Y. Kim, "Cost-efficient sensing with self-improving soft sensor based on predictive uncertainty estimation in IoT environments," *IEEE Internet Things J.*, vol. 13, no. 2, pp. 3055–3068, Jan. 2026, doi: 10.1109/JIOT.2025.3631946.
[29] V. Seoane, C. Garcia-Rubio, F. Almenares, and C. Campo, "Performance evaluation of CoAP and MQTT with security support for IoT environments," *Comput. Netw.*, vol. 197, Art. no. 108338, Oct. 2021, doi: 10.1016/j.comnet.2021.108338.
[30] S. H. Dalmas, A. N. Bonatto, A. dos Santos Roque, D. H. Pohren, and E. P. de Freitas, "Comparative analysis on energy consumption of the CoAP, HTTP, and MQTT protocols for resource-constrained IoT applications," *IEEE Internet Things J.*, vol. 13, no. 15, pp. 32739–32749, Aug. 2026, doi: 10.1109/JIOT.2026.3690887.

Robiya Tuguzbaeva received the Ph.D. degree in technical sciences from the Tashkent Institute of Textile and Light Industry, Tashkent, Uzbekistan, in [TODO: year], and is currently an Assistant Professor with the Department of Natural Fiber Technology and Engineering, Tashkent Institute of Textile and Light Industry. Research interests include wool processing machinery, resource-efficient textile technology, and industrial IoT.

Sherkul Khakimov is a Professor with the Tashkent Institute of Textile and Light Industry, Tashkent, Uzbekistan. [TODO: 2–3 lines.]

Firuza Dustova is with the Tashkent Institute of Textile and Light Industry, Tashkent, Uzbekistan. [TODO: 2–3 lines.]

Ruzimurod Rosulov is with the Tashkent Institute of Textile and Light Industry, Tashkent, Uzbekistan. [TODO: 2–3 lines.]