GENERAL DESCRIPTION	UoM	125kVA
New Name after Emission Certification	Engine Model	**AL6DTIDG2**
No of Cylinders	Qty	6
Gross Rated Power	kW/hp	116 / 157.8
Overload Power (110 %)	kW/hp	127.6 / 173.6
RPM		1800
Typical Alternator Efficiency	% age	91.8
Working Principle	2/4 Stroke	4
BORE / STROKE	mm / mm	104 x 113
Displacement	cc	5760
Compression Ratio	mm	16.5 ± 0.5:1
Unit Dry Wt of Bare Engine Kg	kg	380
Flywheel Housing	SAE	SAE 3
Direction of Rotation from Flywheel End		Counter Clockwise
Firing Order	Seq	1-4-2-6-3-5
Mechanical efficiency	% age	94.0%
Thermal efficiency	% age	39%
Reference Standard	REF	ISO 8178
Governing system		Elecronic
Type of Governor		
Class Of Governor		A0
Engine Speed Droop (Governing)	% age	0%
Heat Rejection to atmosphere	% age	4-7%
Battery Volts	Volts	12V
Battery Capacity	A.H.	90 AH
No. of Starter Motors provided	Qty.	1
Rating Of starter motor	kW	2.8
Battery Charging alternator Capacity amps	amp	35
Intake Manifold Temperature (Max)	deg.C	48 ± 2
Intake Manifold Pressure	kPa	100-180
Intake Air Flow	m3/min	8.43
Max. Allowable restriction in Air Element	inch	14
Air Cleaner efficiency for dirt removal	% age	99.95%
Engine Cooling System Coolant Capacity	Lit.	22.5
Cooling Heat Rejection, kW	kW	103
Max Cooling System Pressure	PSI	12.8
Coolant Outlet Temp (Max)	deg. C	95
Coolant Inlet Temperature	deg. C	75
Start to Open temp for Thermostat	deg. C	82
Fully Open temp for Thermostat	deg. C	95
Coolant topping-up / draining frequency		Every 2 Years or 1000 hrs.
Fan Diameter	inch	26"

Fan Power	kW	4.5
Manifold Type		Dry Type
Max. Wt of Exhaust System on Engine	kg	18
Dia of Exhaust Outlet (inside)	mm	72
No of Exhaust outlet	Nos.	1
Max allowable System back pressure kPa	kPa	7
Heat rejection to exhaust	kW	77.2
Heat rejection to coolant	kW	103
Heat rejection to atmosphere	%	~4to7%
Stack Temp	deg. C	500
SFC at 100%	gms/bhp/Hr	155.26
SFC at 75%	gms/bhp/Hr	161.09
SFC at 50%	gms/bhp/Hr	169.53
No of Holes	no	4
Dia of Hole	mm	11
PCD	mm	125
Fuel Pump		Rotary
Fuel Transfer pump type		Plunger
Filter Type		Spin On
No of filters		1
Refill volume with Lube Filter change	lit	18
Lub Oil system capacity (with filters)	lit	18
Lub Oil temperature (max)	deg. C	120
Fuel Shut-Off solenoid type & Travel		Electrical
Low Lub Oil Pressure Shut-Off	psi	7.5
High Water Tempo Shut-Off	deg.C	105 ± 3
Crank termination signal	r.p.m / Oil. Press	Oil Pressure
Lub Oil Pressure Guage		Digital
Water Temp Guage		Digital
Hourmeter cum r.p.m meter		Digital
Ammeter		Digital
Flywheel Housing Coupling Size	SAE	SAE 3
Flywheel Coupling Size	SAE	SAE 10
Flywheel Diameter	mm	390
Flywheel Width	mm	88
Flywheel No of teeth	no.	126
Flywheel Weight	kg	30
Noise on Full Load at 1 m	dba	98
Engine Warm-Up time before putting load	Sec	60

Engine Cooling time before Engine Shut-Down	Sec	120
Sudden 100% decrease in Load. =<10%	%	NA
Sudden 100% increase in Load. =<10%	%	NA
Recovery for 100% decrease inload =<8 sec	Sec	NA
Recovery for 100% increase inload =<8 sec	Sec	NA

125 KVA Ashok Leyland - Generator Specifications.

Bore x Stroke (mm)	104 x 113 mm
Rating	125 kVA
Engine Make	Ashok Leyland
Model Number	SG125AL
Noise Level	85 dB
Cooling System	Liquid Cooling
Frequency	50/60 Hz
Battery Capacity	12V 90 Ah
Dimension	3500 x 1250 x 1850 mm
Fuel Tank Capacity	650 Liter
Weight	2375 kg
Electric Power	100 kWe
Rated Current @ 380V	190 A
Engine Model	AL6DTIDG2
Aspiration	TA
Engine Rated kW	116
No. of Cylinders	6
Displacement	5.76 Liter
Coolant Capacity Approx.	20 Liter
Lube Oil Capacity Approx.	17.5 Liter
Lube Oil Specification	SAE15W 40 CI4
Oil Change Period	300 Hours
IP Rating	IP33

Key Features:

- Reliable, Robust & Rugged engines designed to deliver continuously in arduous environment
- Better Block Loading Capability
- Compact engine: Engineered for Optimized Power Solutions
- Governor: Mechanical
- Low Oil & Fuel consumption
- Continuous duty Power rating
- Minimal vibrations and lower noise levels
- Easy Serviceability & Repairability
- Alternator: STAMFORD Brushless, Single Bearing, Class H Insulated, Voltage Regulation: ± 0.5%, 0.8PF Lag